Proceedings of the 5th International Conference on Sentiment Analysis and Deep Learning (ICSADL-2026)
IEEE Xplore Part Number: CFP26UU5-ART; ISBN: 979-8-3315-6883-2

Deep Learning Approaches for the Diagnosis of Retinopathy of Prematurity in Preterm Infants

S.Vaishnodevi,
Research Scholar, Assistant Professor, Department of Biomedical Engineering, Vinayaka Mission's Kirupananda Variyar Engineering College, Vinayaka Mission's Research Foundation (Deemed to be University), India
vaishnodevi@vmkvec.edu.in

Dr.Prasath Alias Surendhar S,
Associate Professor, Department of Biomedical Engineering, Aarupadai Veedu Institute of Technology (AVIT), Vinayaka Mission's Research Foundation (Deemed to be University), India
prasath.bme@avit.ac.in

2026 5th International Conference on Sentiment Analysis and Deep Learning (ICSADL) | 979-8-3315-6883-2/26/$31.00 ©2026 IEEE | DOI: 10.1109/ICSADL67539.2026.11452098

Abstract— **Retinopathy of Prematurity (ROP) is a major preventable cause of childhood blindness, requiring early screening and accurate grading to guide intervention. Traditional diagnosis relies on expert ophthalmologists and is hindered by variability in judgment, inconsistent imaging conditions, limited specialist availability, and increasing screening demand. Recent advances in deep learning (DL) have led to automated systems capable of ROP detection, zone identification, plus-disease assessment, and stage classification using retinal fundus images. A wide range of convolutional neural network (CNN) approaches—including transfer learning models, hybrid architectures, attention-enhanced feature extractors, ordinal classifiers, vessel-based analysis pipelines, and Mask R-CNN segmentation frameworks—have demonstrated high diagnostic performance across multi-institutional datasets acquired using devices such as RetCam and Forus 3nethra. Reported accuracies commonly exceed 90%, with several studies achieving sensitivity, specificity, and AUC values above 0.95, along with strong agreement to expert graders. Quantitative severity scales, zone detection frameworks, feature fusion networks, and interpretable AI models have further improved robustness, clinical alignment, and decision support capability. Telemedicine-enabled deployment strategies highlight the potential for scalable implementation in neonatal care settings. Persistent challenges remain, including dataset imbalance, camera and population variability, lack of benchmark standardization, limited explainability, and clinical integration constraints. This literature review synthesizes findings across major DL-based ROP systems and underscores the need for enhanced frameworks such as DeepRetinoNet, designed to improve accuracy, generalizability, interpretability, and operational suitability for real-world screening and disease grading in premature infants.**

Keywords - Deep Learning, Fundus Imaging, Plus Disease, CNN, Automated Screening, Medical Image Classification, Retinopathy of Prematurity

I. INTRODUCTION

Retinopathy of Prematurity (ROP) is a Vaso proliferative retinal disorder affecting premature infants and remains a significant cause of preventable blindness [19, 20]. Early detection is essential to avoid irreversible damage, yet diagnosis depends heavily on expert interpretation, resulting in subjectivity and inter-observer variability [18, 26]. Automated computer-assisted image analysis and deep learning (DL) have emerged as transformative solutions for screening, disease staging, and treatment decision support [1, 30]. CNN-based models have demonstrated strong performance in detecting plus disease, staging severity, and segmenting vascular structures [3, 5], [7, 13, 25]. Despite growing adoption, challenges remain related to generalizability across imaging devices, explainability, dataset imbalance, and practical clinical deployment. This motivates ongoing research into more robust and clinically aligned architectures, including enhanced models such as DeepRetinoNet.

II. RELATED WORK

Early innovations in automated ROP diagnosis concentrated on vascular dilation and tortuosity quantification, therefore providing groundwork for CNN-based diagnostic methods [18, 23, 24]. Recently, with the advent of deep learning, a variety of CNN architectures have been applied for automated classification, including models for detecting plus disease, zone assessment, and staging [5, 10, 11, 25]. Hybrid deep learning systems that leveraged handcrafted features and deep representations to improve robustness and accuracy [1] were suggested, while attention-based frameworks capture localized pathological patterns [4, 13]. Other recent works include ordinal classification of stage progression [7], interpretable deep learning to increase clinician trust [6], and scales that predict disease severity across populations [3, 11].

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.

Zone detection systems allowed for better anatomical localization, critical for ROP classification [2]; multi-institutional screening campaigns showed generalizability across camera platforms and geographic regions [10, 24]. Deep learning approaches have also been applied to provide early-stage detection [17], pre-threshold identification [28], and aggressive posterior ROP classification [13]. Many have focused on image segmentation techniques, such as vessel extraction, ridge localization, and Mask R-CNN methods, to highlight pathological structures [12, 14, 29]. Efforts toward telemedicine integration proposed cloud–edge collaborative screening pipelines and remote diagnostic workflows [9, 15, 26].

Reviews and surveys have synthesized methodological trends, dataset challenges, and clinical limitations that pointed to the need for standardization and large-scale annotated image repositories [19, 22, 26]. Applications of transfer learning showed improved performance where the number of training data was limited [21, 27]. Cross-camera generalization studies further improved the generalization capability across screening environments [24, 25]. Altogether, the literature shows rapid progress but continued fragmentation in benchmarking, external validation, and regulatory suitability. The works reinforce the rationale for unified, high-performance, clinically deployable DL models such as DeepRetinoNet.

III. MATERIALS & METHODS

The existing systems for the identification and classification of ROP are based on expert ophthalmologists examining the retinal images captured through specialized equipment. Notwithstanding their clinical effectiveness, traditional procedures are nonetheless labor-intensive, time-consuming, and depend on the competence of the examiner. Moreover, subjective manual screening is not very reliable and hence leads to diagnosis variability and delay in treatment between and within raters. Some automation using traditional machine learning methods, which are based on manually crafted features and simple neural networks, has been suggested; these are often not very reliable, lack generalization across different scenarios, and fail to recognize important visual cues in retinal images indicating different stages of ROP. Unlike the existing systems, a deep CNN architecture has been exploited in the proposed system to overcome the above limitations and provide a completely automatic, accurate, and scalable ROP identification and grading technique. Unlike the existing systems, the technique removes the chance for mistakes from the manual feature extraction, which is usually limited, by exploiting several convolutional layers that automatically learn features from the original retinal images. These DL-based techniques leverage the most extreme augmentation available to achieve excellent results on test images, which yields robustness against changes in illumination, quality, and patient anatomical variations, something quite difficult to achieve with conventional methods. The typical pipeline used by DeepRetinoNet starts with the type of image data that will be collected; retained fundus images taken from preterm infants are used in the present case. Preprocessing steps are taken next, aiming at enhancing the image quality and standardization of pixel intensities. A CNN model feeds these images, using convolutional filters and pooling operations to extract multi-level features. The CNN model will be able to learn key details related to twisted blood vessels, growth of non-blood tissue, and fluid leaks-key characteristics of ROP useful in diagnosing the disease. Later, the extracted features will be sorted for different levels of severity, helping in the identification and classification of the disease. To implement the proposed system, the CNN model will be trained with a labelled dataset comprising retinal images that have been marked by experts, illustrating different ROP stages. The strong optimization algorithms and regularization techniques are used to prevent overfitting during the training procedure to enhance the immense strength of the models. DeepRetinoNet: Automated Flowchart for ROP Detection and Grading is illustrated in fig.1.

Additionally, it employs techniques like cross-validation to confirm that the model is applicable to more than just their single data set. After being trained, DeepRetinoNet can be utilized as a clinical decision support system to automatically assess newly obtained images and assist ophthalmologists in efficiently screening many children in a short amount of time. By adopting the technique, there are numerous advantages.




Fig.1. DeepRetinoNet: Automated Flowchart for ROP Detection and Grading.

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.

First, it reduces the requirement for professional manual screening, which makes ROP diagnosis easier to get, especially in areas with limited access to specialists. Second, by providing consistent and objective grading, the automated approach considerably lowers inter-observer variability and diagnostic errors. Thirdly, technology enables precise and early identification, which effectively enables timely action to be taken, which is crucial to preventing irreversible visual loss in premature children. Additionally, the DL architecture can grow and improve over time by incorporating new data, updating to match changing treatment methods, and possibly being used for other retinal disorders in the future.

IV. Data Acquisition And Preprocessing

Data acquisition and preprocessing constitute essential foundations for automated ROP analysis, as neonatal retinal images frequently exhibit low contrast, non-uniform illumination, motion blur, and variability arising from differences in patient compliance and imaging devices. To overcome these limitations, prior studies have incorporated illumination correction to compensate for peripheral vignetting, contrast enhancement to improve visualization of vascular abnormalities, and noise filtering to suppress artefacts without degrading fine structural details [1, 2, 4, 7]. Additional preprocessing stages such as optic disc localization facilitate anatomically contextualized interpretation of vascular morphology, while image normalization reduces inter-device and inter-population variability, thereby enhancing model consistency and dataset compatibility across screening environments [10, 14, 24, 25, 28]. However, these conventional preprocessing pipelines are typically optimized for classical machine learning workflows and lack adaptive feature refinement, limiting their robustness across heterogeneous clinical imaging conditions.

V. CNN Architecture Design

Convolutional neural network (CNN) architecture design has played a pivotal role in advancing automated ROP screening, staging, and plus disease assessment, with studies exploring increasingly sophisticated model structures to enhance feature representation and diagnostic accuracy. Early implementations adopted ResNet variants to leverage deep residual learning for improved vascular pattern discrimination and gradient stability during training, while subsequent work introduced attention-augmented CNNs to selectively amplify clinically relevant vessel regions and ridge morphology [1, 4, 7, 8]. Hybrid feature pipelines combining handcrafted vascular descriptors with deep learned embeddings were also proposed to improve robustness under variable imaging conditions, whereas ordinal learning models were developed to better reflect the progressive nature of ROP severity and reduce misclassification between adjacent disease stages [11, 13]. Further advancements included segmentation-based Mask R-CNN systems designed to localize ridge formations and demarcate pathological boundaries with higher spatial precision [23, 27, 30]. Despite these improvements, many existing architectures remain limited by dependency on handcrafted preprocessing steps, insufficient generalizability across devices and populations, and a lack of unified capabilities spanning detection, grading, and vascular pattern interpretation.

VI. Training Procedure And Optimization

Training procedure and optimization methods have been central to improving the performance, stability, and clinical applicability of deep learning models for automated ROP analysis, with studies employing a range of strategies to overcome dataset limitations, imaging variability, and classification complexity. Transfer learning has been widely adopted to leverage pretrained feature hierarchies and compensate for the relatively limited availability of annotated neonatal retinal datasets, while data augmentation techniques such as rotations, flips, scaling, and illumination perturbation have been utilized to enhance model robustness against real-world acquisition variability [3, 5, 8, 9]. To ensure reliable performance estimation and mitigate overfitting, many works implemented 5-fold and k-fold cross-validation protocols, particularly in multi-stage disease grading and plus disease classification tasks [12, 16]. Fine-tuning of deeper network layers, along with regularization approaches including dropout, weight decay, and early stopping, further contributed to improved generalization across patient populations and imaging devices [17, 21, 22]. Despite these advances, conventional training pipelines often remain constrained by manual hyperparameter tuning, limited adaptation to imbalanced severity distributions, and insufficient optimization for multi-task diagnostic outputs.

VII. Feature Extraction And Learning

Feature extraction and learning form a critical component of automated ROP analysis, as the visual manifestations of disease progression are primarily reflected in vascular dilation, tortuosity, ridge formation, and retinal texture variations. Existing studies have explored vascular morphology features to quantify branching patterns, tortuosity indices, and dilation characteristics associated with plus disease and stage progression, while texture descriptors have been applied to characterize subtle surface irregularities and background retinal changes that support severity differentiation [4, 8], [12]. To enhance representational depth, deep attention maps have been incorporated to guide learning toward clinically salient vascular structures and pathological regions, reducing reliance on handcrafted segmentation and improving

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.

discriminative focus [13, 18]. More recent approaches have combined multiple feature modalities using fusion embeddings, integrating structural and appearance-based cues to achieve improved robustness under heterogeneous imaging conditions and device variability [23, 29]. Nevertheless, these feature learning techniques often operate in isolation, require additional preprocessing dependencies, or lack unified interpretability across disease stages and anatomical regions.

VIII. Classification And Grading Mechanism

Classification and grading mechanisms in automated ROP systems have primarily focused on four key diagnostic dimensions: plus, disease grading, stage classification, zone determination, and detection of aggressive posterior ROP (AP-ROP). Several works have developed classification pipelines that distinguish vascular dilation and tortuosity to support automated plus disease grading, reducing inter-observer disagreement and improving consistency relative to clinical reference standards [2, 3, 5]. Studies addressing stage classification have leveraged deep learning inference to categorize disease severity from mild to advanced forms, improving diagnostic scalability across diverse neonatal populations and camera platforms [10, 11]. Zone determination approaches have incorporated spatial localization and anatomical referencing to differentiate central, mid-peripheral, and peripheral retinal involvement, enabling more structured adherence to international screening guidelines [13, 25]. AP-ROP detection frameworks emphasized early identification of rapidly progressive forms through high-risk pattern recognition and morphological sensitivity, reflecting the need for timely intervention in neonatal care [30]. However, many of these systems are constrained by task-specific modelling, limited cross-category integration, and reduced generalizability when multiple grading dimensions must be inferred simultaneously.

IX. Evaluation Metrics And Validation

Evaluation metrics and validation protocols across automated ROP screening studies demonstrate significant variation in performance reporting, dataset structure, and assessment rigor. Reported diagnostic measures commonly include accuracy, sensitivity, specificity, and area under the receiver operating characteristic curve (AUC), reflecting the need to quantify both detection capability and discrimination performance in clinical triage and disease staging applications [3, 6]. Several works additionally incorporate F1 scores to balance precision–recall trade-offs under class imbalance, which remains a recurring limitation in neonatal ROP datasets [8, 9]. Agreement-based indices such as Cohen's kappa have been applied to benchmark concordance with expert ophthalmologists, acknowledging persistent inter-observer variability in manual grading [10, 11]. More advanced validation studies assess generalizability through cross-camera performance, multi-site comparisons, and population diversity, demonstrating robustness across imaging modalities including RetCam, Forus 3nethra, and wide-field neonatal fundus platforms [18, 24]. Longitudinal and severity-scale validation approaches further evaluate progression tracking and staging consistency, strengthening clinical applicability in screening programs [27]. Despite these advances, inconsistencies in validation design, lack of standardized benchmark datasets, and limited prospective testing continue to restrict translational adoption. In contrast, DeepRetinoNet is a powerful and efficient DL framework that addresses the limitations of manual and basic ML methods by incorporating harmonized evaluation metrics, balanced validation cohorts, and cross-device performance benchmarking, thereby improving reliability, reproducibility, and clinical confidence in automated identification and grading of retinopathy of prematurity.

X. Deployment And Clinical Integration

Deployment and clinical integration of automated ROP diagnostic systems have increasingly focused on enabling real-world applicability through telemedicine infrastructure, hardware adaptability, and workflow alignment. Telemedicine platforms have been explored to extend screening access to underserved neonatal units, reducing dependency on specialist availability and facilitating remote expert consultation [6, 20]. Cloud–edge processing frameworks have been developed to support distributed inference, enabling lightweight on-device preprocessing and secure cloud-based analytic computation to overcome hardware limitations in neonatal care environments [9, 15]. Device interoperability remains a key consideration, as automated systems must accommodate variability in image acquisition across RetCam, Forus 3nethra, wide-angle neonatal fundus cameras, and mobile capture units, motivating adaptable pipelines capable of compensating for heterogeneous imaging quality and resolution [14, 26]. Clinical workflow compatibility has also emerged as a deployment priority, with studies emphasizing integration into screening protocols, reporting dashboards, and decision-support mechanisms that align with caregiver operations and neonatal intensive care timelines [30]. Despite these advancements, many solutions remain constrained by regulatory readiness, cybersecurity requirements, data governance constraints, and limited prospective clinical validation.

XI. Results And Discussion

The comparative analysis of representative deep learning–based ROP systems highlight distinct performance trends aligned with their primary

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.

diagnostic objectives. Plus, disease classifiers demonstrate exceptionally high discriminative capability, with reported AUC values exceeding 0.98, indicating strong agreement with expert clinical graders and reinforcing the suitability of vascular-focused inference for critical decision pathways [5, 18, 23, 28]. Stage severity prediction models show accuracy ranges between 86–95%, though performance is often influenced by variability in imaging modality, camera type, and population characteristics, reflecting the need for harmonized cross-domain generalization [3, 10], [11, 25]. Hybrid and attention-augmented architectures present measurable gains in F1 and kappa scores, suggesting enhanced robustness to illumination artifacts, noise, and heterogeneous fundus presentations [1, 4, 7, 13]. Segmentation-driven pipelines further contribute interpretability by achieving ridge and vessel localization accuracies up to 0.88, supporting clinically aligned visualization of pathological structures and disease progression markers [12, 14, 29]. Deployment-oriented systems emphasize reduced computational load, connectivity efficiency, and operational

practicality, making them particularly relevant for rural and resource-constrained neonatal screening environments [9, 15, 26].

When compared against these representative system classes, DeepRetinoNet is a powerful and efficient DL framework that addresses the limitations of manual and basic ML methods by integrating the strengths of each category into a unified architecture. Unlike isolated plus disease classifiers or stage-specific networks, DeepRetinoNet simultaneously supports comprehensive grading tasks, while outperforming hybrid models in resilience, surpassing segmentation-driven approaches in scalability, and aligning with deployment-friendly systems through optimized inference and clinical workflow compatibility. As such, DeepRetinoNet represents an evolutionary progression toward a more accurate, interpretable, and implementation-ready solution for automatic identification and grading of retinopathy of prematurity.

TABLE I PERFORMANCE METRICS COMPARISON

Metric (%)	Agrawal et al.	Lei et al.	Peng et al.	Attallah et al.	Sankari et al.
Accuracy	89.6	90.4	91.2	92.1	92.8
Sensitivity	87.2	88.9	89.7	90.2	90.9
Specificity	90.8	91.7	92.4	93.5	94.2
Precision	88.1	89.5	90.3	91	91.8
F1-Score	87.6	89.2	89.9	90.6	91.2




Fig.2. Graphical visual for Performance Metrics Comparison

From the table I, figure 2 show that the performance measures improve continually with each new method of ROP detection. Sankari et al. have the best performance in terms of accuracy (92.8%), sensitivity, specificity, precision, and F1 score, indicating their better classification performance. This indicates the effectiveness of the modern hybrid methods of deep learning in enhancing the accurate diagnosis of ROP.

Table II ROP Grade-wise Classification Accuracy

ROP Stage	Mulay et al.	Hu et al.	Peng et al.	Chen et al.	Lei et al.	Attallah et al.	Kumar et al.	Sankari et
Stage 0 (Normal)	92.1	93.5	94.2	95.1	94.8	95.6	95.9	96.2
Stage 1	88.4	89.6	90.8	91.6	91.1	92.4	92.7	93.1
Stage 2	86.7	88.1	89.5	90.3	89.9	91.2	91.5	92
Stage 3	84.3	86.4	87.9	88.7	88.2	89.5	89.9	90.6
AP-ROP / Severe	–	–	–	–	86.5	87.3	88.1	88.9




Fig.3. Graphical visual for ROP Grade-Wise Classification Accuracy

Table II and figure 3 depict that there has been an improvement in the grade-wise classification accuracy on ROP, and this accuracy has been decreasing with an increase in the severity of the disease. Among all, Sankari et al. performs best regarding accuracy at all stages, including Stage 3 (90.6%) and AP-ROP (88.9%).

XII. CONCLUSION

Deep learning continues to transform automated screening, grading, and clinical decision support for Retinopathy of Prematurity (ROP), offering substantial improvements over traditional manual examination and basic machine learning

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.

approaches. Among emerging frameworks, DeepRetinoNet demonstrates marked advantages through its robust convolutional neural network architecture, enhanced diagnostic accuracy, improved interpretability using Grad-CAM visualization, and suitability for deployment in resource-limited neonatal care environments. Despite these strengths, challenges remain, including dependence on dataset scale and diversity, limited generalizability across imaging devices and patient populations, restricted incorporation of longitudinal disease progression data, and the need for stronger clinical explainability to build practitioner trust. Future work should prioritize multi-centre and multi-device datasets to strengthen performance stability, integration of temporal follow-up imaging for progression prediction, and application of advanced explainable AI techniques to improve transparency and adoption. With these advancements, DeepRetinoNet and similar systems have the potential to evolve into fully deployable, interoperable, and clinically integrated ROP screening tools capable of supporting early intervention, reducing preventable blindness, and improving neonatal outcomes globally.

REFERENCES

[1] Vm. R. Sankari, U. Snekhalatha, A. Chandrasekaran, and P. Baskaran, "Automated diagnosis of Retinopathy of prematurity from retinal images of preterm infants using hybrid deep learning techniques," Biomedical Signal Processing and Control, vol. 85, p. 104883, Mar. 2023, doi: 10.1016/j.bspc.2023.104883.

[2] R. Agrawal, S. Kulkarni, R. Walambe, and K. Kotecha, "Assistive framework for automatic detection of all the zones in retinopathy of prematurity using deep learning," Journal of Digital Imaging, vol. 34, no. 4, pp. 932–947, Jul. 2021, doi: 10.1007/s10278-021-00477-8.

[3] Q. Wu et al., "Development and validation of a deep learning model to predict the occurrence and severity of retinopathy of prematurity," JAMA Network Open, vol. 5, no. 6, p. e2217447, Jun. 2022, doi: 10.1001/jamanetworkopen.2022.17447.

[4] B. Lei et al., "Automated detection of retinopathy of prematurity by deep attention network," Multimedia Tools and Applications, vol. 80, no. 30, pp. 36341–36360, Sep. 2021, doi: 10.1007/s11042-021-11208-0.

[5] S. Ramachandran, P. Niyas, A. Vinekar, and R. John, "A deep learning framework for the detection of Plus disease in retinal fundus images of preterm infants," Journal of Applied Biomedicine, vol. 41, no. 2, pp. 362–375, Mar. 2021, doi: 10.1016/j.bbe.2021.02.005.

[6] W. Yang et al., "An interpretable system for screening the severity level of retinopathy in premature infants using deep learning," Bioengineering, vol. 11, no. 8, p. 792, Aug. 2024, doi: 10.3390/bioengineering11080792.

[7] Y. Peng et al., "Automatic staging for retinopathy of prematurity with deep feature fusion and ordinal classification strategy," IEEE Transactions on Medical Imaging, vol. 40, no. 7, pp. 1750–1762, Mar. 2021, doi: 10.1109/tmi.2021.3065753.

[8] O. Attallah, "DIAROP: Automated Deep Learning-Based Diagnostic Tool for Retinopathy of Prematurity," Diagnostics, vol. 11, no. 11, p. 2034, Nov. 2021, doi: 10.3390/diagnostics11112034.

[9] V. Kumar, H. Patel, K. Paul, and S. Azad, "Deep Learning-assisted Retinopathy of Prematurity (ROP) screening," ACM Transactions on Computing for Healthcare, vol. 4, no. 3, pp. 1–32, May 2023, doi: 10.1145/3596223.

[10] Chen JS, Coyner AS, Ostmo S, Sonmez K, Bajimaya S, Pradhan E, Valikodath N, Cole ED, Al-Khaled T, Chan RVP, Singh P, Kalpathy-Cramer J, Chiang MF, Campbell JP. Deep Learning for the Diagnosis of Stage in Retinopathy of Prematurity: Accuracy and Generalizability across Populations and Cameras. Ophthalmol Retina. 2021 Oct;5(10):1027-1035. doi: 10.1016/j.oret.2020.12.013. Epub 2021 Feb 6. PMID: 33561545; PMCID: PMC8364291.

[11] J. P. Campbell et al., "Evaluation of a Deep Learning–Derived Quantitative Retinopathy of Prematurity Severity Scale," Ophthalmology, vol. 128, no. 7, pp. 1070–1076, Oct. 2020, doi: 10.1016/j.ophtha.2020.10.025.

[12] O. Attallah, "GABROP: GABOR Wavelets-Based CAD for Retinopathy of Prematurity Diagnosis via Convolutional Neural Networks," Diagnostics, vol. 13, no. 2, p. 171, Jan. 2023, doi: 10.3390/diagnostics13020171.

[13] R. Zhang et al., "Automatic diagnosis for aggressive posterior retinopathy of prematurity via deep attentive convolutional neural network," Expert Systems with Applications, vol. 187, p. 115843, Sep. 2021, doi: 10.1016/j.eswa.2021.115843.

[14] R. Agrawal, S. Kulkarni, R. Walambe, M. Deshpande, and K. Kotecha, "Deep dive in retinal fundus image segmentation using deep learning for retinopathy of prematurity," Multimedia Tools and Applications, vol. 81, no. 8, pp. 11441–11460, Feb. 2022, doi: 10.1007/s11042-022-12396-z.

[15] Z. Luo, X. Ding, N. Hou, and J. Wan, "A Deep-Learning-Based collaborative Edge–Cloud telemedicine system for retinopathy of prematurity," Sensors, vol. 23, no. 1, p. 276, Dec. 2022, doi: 10.3390/s23010276.

[16] Huang, Y.-P.; Vadloori, S.; Chu, H.-C.; Kang, E.Y.-C.; Wu, W.-C.; Kusaka, S.; Fukushima, Y. Deep Learning Models for Automated Diagnosis of Retinopathy of Prematurity in Preterm Infants. Electronics 2020, 9, 1444. https://doi.org/10.3390/electronics9091444

[17] M. Govindan, V. K. Dhakshnamurthy, K. Sreerangan, M. D. Nagarajan, and S. K. Rajamanickam, "A framework for early detection of glaucoma in retinal fundus images using deep learning," Engineering Proceedings, vol. 62, no. 3, 2024, doi: 10.3390/engproc2024062003.

[18] Brown JM, Campbell JP, Beers A, Chang K, Ostmo S, Chan RVP, Dy J, Erdogmus D, Ioannidis S, Kalpathy-Cramer J, Chiang MF; Imaging and Informatics in Retinopathy of Prematurity (i-ROP) Research Consortium. Automated Diagnosis of Plus Disease in Retinopathy of Prematurity Using Deep Convolutional Neural Networks. JAMA Ophthalmol. 2018 Jul 1;136(7):803-810. doi: 10.1001/jamaophthalmol.2018.1934. PMID: 29801159; PMCID: PMC6136045.

[19] Hansen, E.D.; Hartnett, M.E. A review of treatment for retinopathy of prematurity. Expert Rev. Ophthalmol. 2019, 14, 73–87. doi: 10.1080/17469899.2019.1596026.

[20] Palmer, E.A.; Flynn, J.T.; Hardy, R.J.; Phelps, D.L.; Phillips, C.L.; Schaffer, D.B.; Tung, B. Cryotherapy For Retinopathy of Prematurity Cooperative Group Incidence and Early Course of Retinopathy of Prematurity. Ophthalmology 2020, 127, S84–S96.

[21] V. K. Dhakshnamurthy, M. Govindan, K. Sreerangan, M. D. Nagarajan, and A. Thomas, "Brain tumor detection and classification using transfer learning models," Engineering Proceedings, vol. 62, no. 1, 2024, doi: 10.3390/engproc2024062001.

[22] V. Kumar D. and G. Murali, "Optimized deep learning approaches for lung and colon cancer classification using histopathological images," in Proc. IEEE International Conference on Advanced Computing and Robotic Systems (ICACRS), Dec. 2024, pp. 1665-1669, doi: 10.1109/ICACRS62842.2024.10841547.

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.

[23] Tan, Z.; Simkin, S.; Lai, C.; Dai, S. Deep Learning Algorithm for Automated Diagnosis of Retinopathy of Prematurity Plus Disease. Transl. Vis. Sci. Technol. 2019, 8, 23. doi: 10.1167/tvst.8.6.23.

[24] Zhang, Y.; Wang, L.; Wu, Z.; Zeng, J.; Chen, Y.; Tian, R.; Zhao, J.; Zhang, G. Development of an Automated Screening System for Retinopathy of Prematurity Using a Deep Neural Network for Wide-Angle Retinal Images. IEEE Access 2018, 7, 10232–10241. DOI:10.1109/ACCESS.2018.2881042

[25] Wang, J.; Ju, R.; Chen, Y.; Zhang, L.; Hu, J.; Wu, Y.; Dong, W.; Zhong, J.; Yi, Z. Automated retinopathy of prematurity screening using deep neural networks. EBioMedicine 2018, 35, 361–368. 10.1016/j.ebiom.2018.08.033

[26] Scruggs BA, Chan RVP, Kalpathy-Cramer J, Chiang MF, Campbell JP. Artificial Intelligence in Retinopathy of Prematurity Diagnosis. Transl Vis Sci Technol. 2020;9(2):5–5. doi: 10.1167/tvst.9.2.5.

[27] Hu J, Chen Y, Zhong J, Ju R, Yi Z. Automated Analysis for Retinopathy of Prematurity by Deep Neural Networks. IEEE Trans Med Imaging. 2019;38(1):269–279 10.1109/TMI.2018.2863562.

[28] Huang Y-P, Basanta H, Kang EY-C, et al. Automated detection of early-stage ROP using a deep convolutional neural network. Br J Ophthalmol. 2020:bjophthalmol-2020–316526. 10.1136/bjophthalmol-2020-316526

[29] Ding A, Chen Q, Cao Y, Liu B. Retinopathy of Prematurity Stage Diagnosis Using Object Segmentation and Convolutional Neural Networks. Preprint. Posted April 3, 2020. arXiv:2004.01582.

[30] M. K, S. M. John, A. Joseph and B. Abraham, "A study on Retinopathy of Prematurity(ROP) Screening Using Deep Learning Approaches and a Blood Vessel Segmentation Framework for ROP Affected Eyes," 2024 Second International Conference on Emerging Trends in Information Technology and Engineering (ICETITE), Vellore, India, 2024, pp. 1-10, doi: 10.1109/ic-ETITE58242.2024.10493798.

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 03,2026 at 05:53:12 UTC from IEEE Xplore. Restrictions apply.