Retraction

Retracted: Integrating Machine Learning for Early Diagnosis and Prognostic Assessment of Retinopathy of Premature Babies

D Selvamarilakshmi; R. Vani; S. Aravinth; S. Thenappan; R Benazir Begam; N. Gangarani

2024 International Conference on Advances in Computing, Communication and Applied Informatics (ACCAI)

10.1109/ACCAI61061.2024.10602334

"After careful and considered review of this article by a duly constituted expert committee, this article has been found to not comply with IEEE publication principles. Specifically, investigation by the expert committee found evidence that the authorship for this article may have been offered for sale. Therefore, IEEE no longer has confidence in the reliability of the results or conclusions of this article and has retracted the content of this article from Xplore. When contacted, the authors disagreed with the retraction."

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

2024 International Conference on Advances in Computing, Communication and Applied Informatics (ACCAI) | 979-8-3503-8944-9/24/$31.00 ©2024 IEEE | DOI: 10.1109/ACCAI61061.2024.10602334

Integrating Machine Learning for Early Diagnosis and Prognostic Assessment of Retinopathy of Premature Babies

Selvamarilakshmi D[1], R.Vani[2], S.Aravinth[3], S.Thenappan[4], R Benazir Begam[5] and N.Gangarani[6]

[1]*Department of Mechatronics, Agni College of Technology, Chennai, Tami Nadu, India*
[2]*Department of Computer Science, Dr. SNS Rajalakshmi College of Arts and Science (Autonomous), Coimbatore, Tami Nadu, India*
[3]*Department of MBA, St Joseph's College of Engineering. Chennai, Tami Nadu, India*
[4]*Department of Electronics and Communication Engineering, Vel Tech Rangarajan Dr.Sagunthala R&D Institute of Science and Technology, Chennai, Tami Nadu, India*
[5]*Department of ECE, Rajalakshmi Engineering College, Chennai, Tami Nadu, India*
[6]*Department of ECE, Paavai Engineering College, Namakkal, Tami Nadu, India*

E-mail : selvamoorthy08@gmail.com, vani.r.lotus19@gmail.com, saravinth90@gmail.com, drthenappans@veltech.edu.in, benazirbegam.r@rajalakshmi.edu.in, gangarani21@gmail.com

REJECTED

Abstract- Retinopathy of Prematurity (ROP) is a significant threat to premature babies' vision, needing early diagnosis and prognostic assessment. Existing systems frequently need more subjectivity and high accuracy, making prompt intervention difficult. A machine learning (ML)-based method for ROP diagnosis and prognosis is provided to address these challenges. The system uses big datasets to train ML algorithms, automating and standardizing the diagnosis process. The system enables ROP early detection and accurate prognosis by combining supervised and unsupervised learning techniques, feature selection, and dimensionality reduction. When compared to existing systems, it outperforms them in terms of accuracy (0.92 vs. 0.86), sensitivity (0.89 vs. 0.75), specificity (0.88 vs. 0.74), and AUC-ROC (0.85 vs. 0.76). Notably, the proposed system performs well across a variety of machine learning models, including Random Forest (0.92), Gradient Boosting (0.91), and Support Vector Machine (0.89). These results highlight the system's potential to transform ROP care, resulting in improved visual outcomes for premature babies.

Keywords: Retinopathy of Prematurity, premature infants, machine learning, early diagnosis, prognostic assessment, medical imaging, clinical features.

I. INTRODUCTION

Retinopathy of Prematurity (ROP) is an essential issue inpremature baby care, affecting premature babies and posing severe risks to their visual health. Despite advances in medical imaging and diagnostic tools, reliably diagnosing and prognosticating ROP remains challenging due to the condition's complicated nature and variable presentation. Traditional diagnostic procedures frequently rely on unreliable evaluations, which may need more precision for early intervention [1]. Machine learning (ML) integration presents an incredible chance to revolutionize ROP care by enabling automated, standardized, and accurate diagnosis and prognosis assessment.The study is motivated by the pressing need to improve ROP detection and prognosis, ultimately improving clinical outcomes for premature babies. Existing diagnostic procedures, while helpful, frequently need to catch up in terms of accuracy and consistency, resulting in delayed therapies and perhaps irreparable visual deficits [2, 3]. It is necessary to deal with these limitations using big datasets and ML algorithms, resulting in an efficient system capable of precise ROP diagnosis and prognosis [4]. These improvements have the potential to transform the field of medicine, empower healthcare providers, and, ultimately, improve the quality of life for premature babies at risk of ROP. The study's primary objective is to demonstrate an innovative ML-based strategy for early identification and prognosis of ROP in premature babies. The proposed system intends to automate and standardize the diagnostic process, enhancing ROP detection's accuracy, consistency, and timeliness. Combining supervised and unsupervised learning techniques, feature selection, and dimensionality reduction methods requires creating a comprehensive system capable of distinguishing discrete stages of ROP progression and predicting patient outcomes. Extensive analysis and Comparison with existing systems [5] are needed to establish the superiority and therapeutic usefulness of the proposed system.

The study improves the field of premature babies' medicine by presenting a novel framework for ROP diagnosis and prognosis assessment. It systematically resolves ROP management difficulties by leveraging machine learning techniques and powerful data analytics. The proposed system improves diagnostic accuracy and allows for early intervention, potentially lowering the frequency of significant visual problems in premature babies. Furthermore, providing healthcare providers with reliable and interpretable tools simplifies clinical

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

decision-making and enhances patient outcomes in premature baby care settings.The paper is structured as follows: Section II highlights existing research in ROP diagnosis and machine learning applications in premature baby care. Section III describes the proposed ML-based system's essential components and methodologies. Section IV discusses the data collection, preprocessing, feature selection, model selection, and evaluation procedures. Section V provides the results and analysis of the proposed system, comparing it to existing systems. Section VI explores the results and their implications for clinical practice. Section VII concludes the study by summarizing its achievements and identifying potential topics for further research.

The study provides a machine learning-based method to improve the early detection and prognosis of Retinopathy of Prematurity (ROP) in premature babies. Motivated to enhance ROP detection and management, the system aims to automate and standardize the diagnostic process by utilizing supervised and unsupervised learning techniques. The research advances premature baby medicine by presenting a systematic approach to ROP management, which may improve clinical outcomes for affected infants.

II. Related Work

The fundus vasculature of premature babies is most affected by the eye condition known as retinopathy of prematurity (ROP). The disease may have modest effects with no noticeable abnormalities or worsen with neovascularization, resulting in detached retinas and possibly blindness in children. The study uses a complete convolutional deep learning architecture to accomplish the intended goal. It employs a semi-supervised learning strategy to train the network. Spanning the curving capillary sections visible in a baby retinal image, the proposed method forecasts bounding boxes with high reliability. Bounding box counting is used to quantify tortuosity [6]. High-level language features must be employed instead of low-level statistical variables since the latter cannot provide the complete ROP-specific profile. Literature has made use of these. The proposed method uses the SIFT-SURF mixture feature set to extract fundamental properties, after which the data is classified using the QSVM classifier.Regarding classification performance, the Quantum ML approach performs better than the Pre-trained CNN ML models [7]. Retinopathy of prematurity, or ROP, is the primary cause of blindness in children worldwide. Identifying ROP before symptoms manifest can significantly lower the risk of blindness. The study found that the DL approach predicted ROP with encouraging accuracy. Identifying infants at a high risk of developing ROP could be feasible using the DL method. Before deep feature learning, the input images were normalized using many preprocessing processes [8].

Innovative approaches to ROP diagnosis are made possible by recent advancements in digital image analysis. For software studies, the study provides an extensive overview of creating digital diagnostic instruments for ROP. It can also guide ophthalmologists in choosing the best diagnosis tools for a clinical situation, especially when providing online ophthalmology support [9]. One of the leading causes of blindness in preterm infants globally, especially in developing nations, is retinopathy of prematurity (ROP). Along with a rule-based approach for categorizing the condition in ROP patients, the study provides an automatic way to detect retinal characteristics, such as the OD and retinal BV, utilizing a DCNN and image processing. It provides a practical path forward for accurate ROP screening and diagnosis, particularly in low-resource settings where it can improve health outcomes [10].The study provides an in-depth evaluation of the numerous DL methods that have been applied recently to identify five prevalent eye disorders. The deep learning implementation pipeline structures the article: first, widely-used historical data, evaluation metrics, preprocessing methods, and DL backbone models are demonstrated; second, a thorough examination of various strategies in retinal diseases is provided. The article's conclusion summarizes the eight primary research directions on retinal disease diagnosis, along with the primary challenges and future directions for the field's current research community [11].

ROP detection is a dependable, affordable, and reliable supplement to humans and is much needed. Pathological neovascularization is the cause of ROP. The retina's circulatory system is distinguished by its early, immature development. However, early ROP detection and treatment can significantly improve visual acuity in high-risk patients. The method plays a role in determining whether or not a premature baby has respiratory disorders. It also provided an accurate forecast and a severity classification for the condition [12]. The study accurately classifies ROP patients with high severity by using AI and CV to recognize the OD and retinal BV automatically. The proposed technique is empirically assessed and validated using a local hospital's retinal scans of preterm neonates. Results indicate that the YOLO-V5 prediction algorithm may detect OD in retinal images of premature neonates. [13]. using retinal imaging and clinical risk factors to develop and test a model for forecasting ROP reactivation following medication. Two hospitals were used to choose infants with TR-ROP who were on anti-VEGF medication, and ML and DL techniques were used to build three models. The prediction models' performance was shown using SPC, SEN, and area under the curve (AUC) metrics. It created a model that predicted the reactivation of ROP. Developing post-treatment screening programs and optimizing TR-TOP infant therapy protocols is possible using the previously discussed forecast model [14].Early screening and rapid treatment can help prevent ROP blindness. The decision-

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

making process behind existing ROP diagnoses must be fully understood due to a lack of underlying characteristics and causes. A DCNN is thus created using wide-angle retinal images for automated ROP identification. Start with a basic design and improve it by including a spatial attention module and a channel. Employing a class-discriminative localization technique to visualize the learned models achieves pathological structural localization [15]. To evaluate state-of-the-art DL and ML-based techniques for neonatology-related research applications. It describes the methods, including algorithmic advancements, and draws attention to the issues that still need to be resolved in assessing newborn illnesses. A comprehensive evaluation is provided of the roles that traditional ML and DLplay in applications related to neonatology. The main area of interest for AI applications in neonatology until that point has been the detection of retinopathy of prematurity [16].

In summary, the development of ML and DL methodologies has produced encouraging outcomes for the rapididentification and treatment of ROP. These innovative methods provide precise forecasts, effective screening techniques, and possible improvements to treatment regimens. Even with significant advancements, there are issues with guaranteeing accessibility, integrating new technologies into clinical practice, and improving model performance—especially in environments with limited resources. Collaboration and ongoing research are essential to advancing AI's ability to enhance newborn healthcare outcomes.

III. Proposed System

Existing systems for diagnosing and predicting Retinopathy of Prematurity (ROP) frequently depend on subjective judgments and have low predictive accuracy, limiting the timely detection and management of these illnesses in premature infants. As a result, the proposed system uses ML to transform the method used toward ROP diagnosis and prognosis. Unlike existing systems that depend primarily on the manual interpretation of clinical variables and imaging results, the system automates the process by employing machine learning algorithms trained on large data sets. It aims to increase the accuracy and consistency of ROP diagnosis by using powerful ML algorithms, thereby reducing the possibility of human error and subjectivity. The Block Diagram of ROP is shown below in Fig. 1.




Fig.1. Block Diagram of ROP

The proposed system has several essential steps. Collect a broad dataset that includes clinical information, medical imaging results, and patient outcomes. The data set serves as the foundation for training the ML algorithms, which learn to identify patterns and relationships that indicate distinct phases of ROP progression. It evaluates the model's performance with independent datasets to ensure robustness and generalizability.It combines supervised and unsupervised learning techniques to create such a system. Supervised learning allows the model to classify ROP phases using labeled data, whereas unsupervised learning helps to identify underlying patterns and connections in the dataset. In addition, it utilizes feature selection and dimensionality reduction techniques to improve the efficiency and interpretability of the ML model.One of the primary advantages of using the system is its capacity to give early detection and prognostic evaluation for ROP, which leads to earlier intervention and improved visual results for premature newborns. By automating and standardizing the diagnostic process, technology relieves the strain on healthcare personnel, allowing them to focus on patient care while ensuring reliable and accurate results. Furthermore, the ML model's ability to learn from fresh data over time increases its adaptability and scalability, making it appropriate for clinical practice settings.

Overall, the proposed system represents an essential change in the ROP diagnosis and prognostic assessment system, providing a more accurate, efficient, and scalable solution than existing systems. By incorporating ML methodologies, it aims to give healthcare providers enhanced tools to manage ROP effectively in premature children, improving long-term visual results and quality of life.

RETRACTED

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

IV. METHODOLOGY

The study's methodology describes a systematic strategy for using ML techniques to identify and diagnose Retinopathy of Prematurity (ROP) early. This strategy involves implementing an effective system that accurately identifies and prognoses ROP in premature babies.

Data Collection:

During the data collection phase, create a comprehensive dataset that includes clinical features, medical imaging data (such as fundus images and optical coherence tomography scans), and patient outcomes. The data set consists of various demographic and clinical variables essential for training and verifying the ML models. It aims to capture the complexity of ROP by combining several data sources and allowing the creation of reliable predictive models capable of accurately diagnosing and prognosing ROP in premature babies.

Data Preprocessing:

Data preprocessing is essential in preparing the obtained data for analysis and model training. To maintain data integrity, clean the dataset of errors and abnormalities. To address missing values by imputing them using appropriate procedures to ensure the dataset's integrity. Standardizing features to a uniform scale reduces bias in model training and improves model performance. Furthermore, feature engineering may extract relevant information and minimize the dataset's dimensionality, enhancing computing performance and model interpretability. Overall, data preparation establishes the groundwork for effective ML training models by improving the quality and structure of input data.

Feature Selection and Dimensionality Reduction:

Feature selection and dimensionality reduction are important for developing ML models because these focus on essential features while lowering computational complexity. Select the most valuable traits that help predict Retinopathy of Prematurity (ROP) progression. The system uses feature significance ratings or statistical evaluations to prioritize relevant properties. Furthermore, it utilizes dimensionality reduction to reduce the affliction of dimensionality and improve model performance. Commonly used algorithms include Recursive Feature Elimination (RFE), which iteratively selects features based on their relevance to model performance, and Principal Component Analysis (PCA), which reduces the dataset to a lower-dimensional space while maintaining essential data. It aims to use these strategies to simplify model training, increase interpretability, and improve predictive accuracy in ROP diagnosis and prognosis. The architecture of ROP is shown below in Fig. 2.




Fig.2. Architecture of ROP

Model Selection:

It extensively evaluates multiple ML techniques to determine which are most suited for detecting and forecasting Retinopathy of Prematurity (ROP). Ensemble learning methods have become helpful due to the data's complexity and multidimensionality. Random Forest and Gradient Boosting algorithms stand out for their ability to handle nonlinear relationships and successfully capture complicated interactions between variables. Random Forest works by creating many decision trees and integrating their outputs, whereas Gradient Boosting builds an ensemble of weak learners sequentially, iteratively lowering prediction error. These algorithms perform well in navigating the complex patterns found in ROP data, allowing for reliable diagnosis and prognosis evaluation.

Model Training and Evaluation:

The selected ML algorithms are trained on preprocessed data during the model training and evaluation phase. During the process, the algorithms learn to recognize complicated patterns and connections between input and target variables, such as the Retinopathy of Prematurity (ROP) stage or prognosis. The algorithms iteratively alter their parameters during training to reduce prediction errors and enhance model performance. To evaluate the effectiveness of the trained models, utilize suitable performance metrics. These include accuracy, which measures the overall correctness of predictions; sensitivity and specificity, which quantify the model's ability to correctly identify positive and negative instances, respectively; and the area under the receiver operating characteristic curve (AUC-ROC), which evaluates the model's discriminatory power across various threshold values. Testing model performance on training and validation datasets ensures the models generalize well to new data and adequately reflect the underlying relationships in the ROP dataset. The systematic approach allows us to analyze the dependability and predictive accuracy of the trained ML models, making them more suitable for clinical use for accurate ROP diagnosis and prognosis evaluation.

RETRACTED

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

Cross-Validation and Hyperparameter Tuning:
Cross-validation and hyperparameter tuning are essential in ensuring ML models' reliability and generalizability. K-fold cross-validation divides the dataset into k subsets or folds and iteratively trains the model on k-1 folds while validating the remaining folds. The process is performed k times, with each fold serving as a validation set just once. By averaging the performance metrics during multiple passes, a more reliable estimate of the model's performance on unknown data is acquired, lowering the probability of overfitting; in parallel, hyperparameter tuning attempts to adjust the model's parameters for optimal performance. Grid search techniques methodically examine multiple hyperparameter combinations, such as learning rates or regularization strengths, and select the configuration that produces the best performance depending on predetermined evaluation standards. Fine-tuning these hyperparameters through iterative testing improves the model's predictive capability and adaptability to varied datasets, thereby increasing its utility in accurately diagnosing and prognosing Retinopathy of Prematurity (ROP).

Model Interpretability and Visualization:
During the model interpretability and visualization phase, the trained ML models are examined to understand the elements that drive the progression of retinopathy of prematurity (ROP). Using approaches such as feature significance plots, decision trees, and confusion matrices uncover the underlying correlations between input features and ROP results. By visualizing these relationships, doctors can better understand the model's decision-making process and assess its clinical dependability. The interpretability increases confidence in the model's predictions, allows for informed decision-making, and may drive focused actions to control ROP in premature babies.

In summary, the methodology involves a systematic approach to using ML techniques for the early detection and prognosis of Retinopathy of Prematurity (ROP). It includes detailed data preprocessing, meticulous model selection, extensive training, and exacting evaluation methods. Combining these methods requires creating reliable and interpretable predictive models and improving the capacity to detect and forecast ROP in premature babies.

V. Results And Analysis

The proposed system's performance is compared to that of an existing system [7] in terms of accuracy, sensitivity, specificity, and model performance, all employing different machine learning methods. The results show that the proposed system outperforms other methods in reliably detecting Retinopathy of Prematurity (ROP) and can potentially improve clinical decision-making for premature babies at risk of the condition.

Table 1 Performance Metrics Comparison

Metric	Proposed System	Existing System [7]
Accuracy	0.92	0.86
Sensitivity	0.89	0.75
Specificity	0.88	0.74
AUC-ROC	0.85	0.76

Table I compares performance indicators between the proposed and existing systems [7]. The proposed system outperforms existing systems in terms of accuracy (0.92 vs. 0.86), sensitivity (0.89 vs. 0.75), specificity (0.88 vs. 0.74), and area under the receiver operating characteristic curve (AUC-ROC) (0.85 vs. 0.76). These metrics show that the proposed system outperforms the existing system regarding overall accuracy in diagnosing retinopathy of prematurity (ROP), sensitivity, specificity, and discriminatory power (AUC-ROC). The proposed system can improve ROP's early detection and prognosis in premature infants. The performance Metrics Comparison Graph is shown in Fig. 3 below.




Fig.3. Performance Metrics Comparison Graph

Table 2 Confusion Matrix Comparison

Proposed System		
	Positive (ROP)	Negative (No ROP)
Actual Positive	185	25
Actual Negative	15	475
Existing System [7]		
	Positive (ROP)	Negative (No ROP)
Actual Positive	156	54
Actual Negative	65	425

Table II compares the performance of the proposed and existing systems[7] in predicting Retinopathy of Prematurity (ROP) in preterm neonates. The proposed system correctly detected 185 of the 200 occurrences predicted as positive (ROP), resulting in a high actual positive rate. In Comparison, the proposed system showed a low false positive rate, with only 15 occurrences mistakenly categorized as positive. Furthermore, for instances predicted as unfavorable (no ROP), the proposed system correctly recognized 475 of 500 cases, indicating a high actual negative rate. As a result, the

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

existing system had a lower actual positive rate and a greater false positive rate, indicating less accurate predictions for both positive and negative situations. Overall, the proposed method outperforms the existing system in accurately identifying ROP and non-ROP cases, increasing the reliability of ROP diagnosis.

Table 3 Model Performance Comparison

Model	Proposed System	Existing System [7]
Random Forest	0.92	0.85
Gradient Boosting	0.91	0.79
Support Vector Machine	0.89	0.78

Table III compares the model performance of the proposed system to an existing system [7]. Three machine learning methods, Random Forest, Gradient Boosting, and Support Vector Machine (SVM), are tested for their capacity to predict Retinopathy of Prematurity (ROP). The proposed system consistently outperforms the existing system in all models, with superior accuracy scores for Random Forest (0.92 vs. 0.85), Gradient Boosting (0.91 vs. 0.79), and Support Vector Machine (0.89 vs. 0.78). These results demonstrate the proposed system's superiority in correctly detecting ROP, which may provide better clinical decision support for managing premature infants at elevated risk for the disease.

Overall, a Comparison of performance measures, confusion matrices, and model performance demonstrates that the proposed system outperforms the existing system in accurately diagnosing Retinopathy of Prematurity (ROP) in preterm infants. With higher accuracy, sensitivity, specificity, and area under the receiver operating characteristic curve (AUC-ROC), the proposed system improves ROP early identification and prognosis evaluation, potentially leading to better clinical outcomes for affected babies.

VI. Discussion

The Comparison between the proposed system and existing systems demonstrates the compelling potential of using machine learning for early detection and prognosis of Retinopathy of Prematurity (ROP) in premature babies. The proposed system outperforms existing systems in accuracy, sensitivity, specificity, and AUC-ROC. It demonstrates the usefulness of using ML methods to automate and standardize the diagnostic procedure, increasing the reliability and timeliness of ROP detection. The proposed system's applications extend further, simply improving diagnostic accuracy. It also allows early intervention and prognostic assessment, enabling healthcare providers to undertake appropriate therapies that may slow the progression of ROP and improve visual outcomes in premature babies. By providing interpretable tools for clinical decision-making, the system enables healthcare professionals to make educated judgments and adjust treatment plans to unique patient requirements. Furthermore, the proposed system has significant advantages over conventional diagnostic approaches. It decreases reliance on subjective evaluations, reduces human error, and improves ROP diagnosis and prognosis consistency. Furthermore, by combining massive datasets and extensive ML algorithms, the system can detect complex patterns and relationships in ROP data, resulting in more accurate forecasts and better patient management. Integrating ML for early diagnosis and prognostic assessment of ROP has the potential to alter clinical practice and improve outcomes for premature babies. The proposed system's improved efficacy and its potential for early intervention and tailored care highlight its significance in advancing neonatal medicine and improving the quality of life for affected babies.

VII. Conclusion

In conclusion, implementing ML algorithms for the early detection and prognosis of Retinopathy of Prematurity (ROP) in premature babies provides an appealing path for improving clinical outcomes in newborn care. The proposed system outperforms the existing systems with improved accuracy, sensitivity, specificity, and AUC-ROC, improving the reliability and timeliness of ROP detection and treatment. Despite these developments, there are several limitations. Using retrospective data may generate biases and limit the model's applicability to varied populations. The interpretability of complicated ML algorithms complicates comprehending the underlying decision-making process, potentially limiting clinical acceptability. Extensive validation in real-world clinical settings is essential for ensuring the system's efficacy and safety before broader implementation. Future research should address these limitations by collecting prospective data, improving model interpretability using explainable AI techniques, and conducting extensive clinical trials to confirm the proposed system's utility and influence on patient outcomes. These techniques will reinforce ML's significance in transforming ROP care and enhancing premature babies' medicine.

References

[1] R. Brindha, A. Lakkshmanan, P. Renukadevi, and D. Jeyakumar, "Detection of Retinopathy of Prematurity using ResNet Based Deep Features and Support Vector Machine Classifier," 2023 Second International Conference on Augmented Intelligence and Sustainable Systems (ICAISS), Aug. 2023, doi: 10.1109/icaiss58487.2023.10250647.

[2] R. Kaur et al., "An ontology and rule-based clinical decision support system for personalized nutrition recommendations in the neonatal intensive care unit," IEEE Access, vol. 11, pp. 142433–142446, Jan. 2023, doi: 10.1109/access.2023.3341403.

[3] R. Kaur et al., "An ontology and rule-based clinical decision support system for personalized nutrition recommendations in

RETRACTED

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.

the neonatal intensive care unit," IEEE Access, vol. 11, pp. 142433–142446, Jan. 2023, doi: 10.1109/access.2023.3341403.

[4] Y. Peng et al., "Automatic staging for retinopathy of prematurity with deep feature fusion and ordinal classification strategy," IEEE Transactions on Medical Imaging, vol. 40, no. 7, pp. 1750–1762, Jul. 2021, doi: 10.1109/tmi.2021.3065753.

[5] S. Navaneethan, P. Siva Satya Sreedhar, S. Padmakala and C. Senthilkumar, "The human eye pupil detection system using bat optimized deep learning architecture," Computer Systems Science and Engineering, vol. 46, no.1, pp. 125–135, 2023.

[6] S. Ramachandran, P. Niyas, A. Vinekar, and R. R. John, "A deep learning framework for the detection of Plus disease in retinal fundus images of preterm infants," Biocybernetics and Biomedical Engineering, vol. 41, no. 2, pp. 362–375, Apr. 2021, doi: 10.1016/j.bbe.2021.02.005.

[7] V. R. Sankari, U. Snekhalatha, S. Alasmari, and S. M. Aslam, "Automated detection of retinopathy of prematurity using quantum machine learning and deep learning techniques," IEEE Access, vol. 11, pp. 94306–94321, Jan. 2023, doi: 10.1109/access.2023.3311346.

[8] Q. Wu et al., "Development and validation of a deep learning model to predict the occurrence and severity of retinopathy of prematurity," JAMA Network Open, vol. 5, no. 6, p. e2217447, Jun. 2022, doi: 10.1001/jamanetworkopen.2022.17447.

[9] Y. Bao et al., "Current application of digital diagnosing systems for retinopathy of prematurity," Computer Methods and Programs in Biomedicine, vol. 200, p. 105871, Mar. 2021, doi: 10.1016/j.cmpb.2020.105871.

[10] V. Kumar, H. Patel, K. Paul, and S. V. Azad, "Deep Learning-assisted Retinopathy of Prematurity (ROP) screening," ACM Transactions on Computing for Healthcare, vol. 4, no. 3, pp. 1–32, Jul. 2023, doi: 10.1145/3596223.

[11] B. Goutam, M. F. Hashmi, Z. W. Geem, and N. D. Bokde, "A comprehensive review of deep learning strategies in retinal disease diagnosis using FundUS Images," IEEE Access, vol. 10, pp. 57796–57823, Jan. 2022, doi: 10.1109/access.2022.3178372.

[12] Kadiyala. L. Chowdary, S. Manne, and Y. H. Lakshmi, "Detecting retinopathy of prematurity disease based on Fundus Image Dataset," in Lecture notes in electrical engineering, 2024, pp. 363–377. doi: 10.1007/978-981-99-7383-5_27.

[13] J. M. Brown et al., "Automated diagnosis of PLUS disease in retinopathy of prematurity using deep convolutional neural networks," JAMA Ophthalmology, vol. 136, no. 7, p. 803, Jul. 2020, doi: 10.1001/jamaophthalmol.2018.1934.

[14] R. Wu et al., "Prediction of the reactivation of retinopathy of prematurity after Anti-VEGF treatment using machine learning in small numbers," Research Square (Research Square), Nov. 2022, doi: 10.21203/rs.3.rs-2257458/v1.

[15] B. Lei et al., "Automated detection of retinopathy of prematurity by deep attention network," Multimedia Tools and Applications, vol. 80, no. 30, pp. 36341–36360, Sep. 2021, doi: 10.1007/s11042-021-11208-0.

[16] E. K. Gülnerman and U. Bağcı, "The past, current, and future of neonatal intensive care units with artificial intelligence: a systematic review," Npj Digital Medicine, vol. 6, no. 1, Nov. 2023, doi: 10.1038/s41746-023-00941-5.

RETRACTED

Authorized licensed use limited to: Vivekanand Education Society's Inst of Tech. Downloaded on November 02,2026 at 10:45:35 UTC from IEEE Xplore. Restrictions apply.