

NEWS for VAST 3.7.0

Purpose of document:

This document lists substantial changes in R package VAST for each numbered release starting at 3.5.0. VAST depends upon utility functions within package FishStatsUtils, and this document therefore lists new features, bug fixes, deprecated features, and other changes occurring via edits to both VAST and FishStatsUtils.

CHANGES IN VAST 3.7.0

CHANGING DEPENDENCIES

- Requires FishStatsUtils version $\geq 2.9.0$

NEW FEATURES

- Integrate package `effects` to plot covariate-response curves based on user-specified formulae for density and catchability covariates (including basis-spline, polynomial, interaction or other basis-expansion methods) along with confidence intervals.
- Improve `predict` feature added in release 3.6.0 including: (1) adding an integrated-test to confirm that it behaves identically to `predict.glm` in some simple cases; (2) improving documentation; and (3) confirming that it can be integrated with package `pdp` to make partial dependence plots.

BUG FIXES

- Update `plot_quantile_residuals` to ensure that a residual >0.5 corresponds to data above the median from the predictive distribution, and a residual <0.5 corresponds to data below the median from the predictive distribution (the previous version had that swapped due to the sign-change caused by using a uniform-to-chi-squared function for aggregating quantile residuals).

26

27 **CHANGES IN VAST 3.6.1**

28 **BUG FIXES**

- 29 • Update `map` object which was generated incorrectly for several topics related to
30 backwards compatibility, as well as for some types of spatially varying coefficient
31 model.

32

33 **CHANGES IN VAST 3.6.0**

34 **CHANGING DEPENDENCIES**

- 35 • Requires FishStatsUtils version $\geq 2.8.0$

36 **NEW FEATURES**

- 37 • Expanding use of formula interface to specify covariates. A separate formula is now
38 specified for each linear predictor for density (X1_formula/X2_formula) or
39 catchability (Q1_formula/Q2_formula). Catchability formulas are parsed by user-
40 supplied data frame `catchability_data`. However, the user can still use previous
41 interface, either by passing X_itp / X_gtp directly, or by passing a single formula.
- 42 • Allowing user to specify spatially varying coefficients for each density linear
43 predictor separately (X1config_cp / X2config_cp), and adding new feature to allow
44 users to specify a spatially varying catchability covariate (Q1config_k / Q2config_k).
45 This allows users to, for example, estimate a differences in gear performance between
46 two surveys where gear performance varies spatially as a random field.
- 47 • Adding generic predict function for S3 class `fit_model`; the function is very slow
48 but could be expanded in the future to be similar to predict functions for other
49 common regression packages.

50 **ISSUES RESOLVED**

- Identify issue whereby VAST was giving different results when run using R version $\geq 4.0.0$, compared with earlier R versions. This occurred due to changes in base-R with how integers are sampled, as documented in [issue #244](#). A new option ``calculate_kmeans(..., backwards_compatible_kmeans=FALSE)`` has been added for users wanting to generate an identical k-means object to previous R versions; this is used e.g., in integrated-tests to ensure that results from prior versions can be replicated exactly.

BUG FIXES

- Update ``projargs`` strings passed to package `sp / RGDAL`, to keep up with changes to using PROJ6. The previous use of `projargs` strings was throwing annoying warning messages, but the change did not appear to impact functionality.

CODE AND STABILITY IMPROVEMENTS

- Omega (spatial random effects), Epsilon (spatio-temporal random effects), and Delta (overdispersion random effects) are now built to have zero-length when these features are not needed (by making one dimension have length-0). This is intended to (1) decrease memory required in the former approach of mapping these off, and (2) eliminating the chance that users might inadvertently set starting values to non-zero values, which would previously have resulted in incorrect results.
- ``make_covariates(.)`` has been re-structured to change the order of operations, resulting in a more stable implementation for use with factors and interactions

CHANGES IN VAST 3.5.1

BUG FIXES

- Fix error in compiling CPP version 9.3.0 and 9.4.0, which occurred using rtools40 as required by R version $\geq 4.0.0$. This involved change function ``abs(.)`` to ``fabs(.)`` in these CPP files.

CHANGES in VAST 3.5.0

CHANGING DEPENDENCIES

- Requires FishStatsUtils version $\geq 2.7.0$
- Requires R package DHARMa

NEW FEATURES

- Added a feature for barrier-SPDE, where vertices of the SPDE mesh that occur over land have a correlation of zero with nearby vertices.
- Changed density covariates to index by `X_gctp` (rather than `X_gtp`), so that manual editing can be used to implement cohort effects.
- Allows probability-integral-transform (PIT) residuals for delta-models, using DHARMa for plotting tools.

DEPRECATED AND DEFUNCT

- Eliminated deprecated and generally unused feature for seasonal modelling, whereby input `t_iz` is now replaced by `t_i`. This change simplifies code in CPP files in multiple places. Seasonal modelling is still feasible using the spatially-varying-coefficient features involving covariates.