

Apply filters to SQL queries

Project description

In this project I was asked to investigate potential security issues and to update computers. Using SQL I was asked to filter the information required to get more information about the security issue.

Retrieve after hours failed login attempts

First I was asked to retrieve all failed login attempts that occurred after business hours. I needed to filter all attempts that occurred after 18:00.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_time > '18:00' AND success = FALSE;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0

This query filters for failed login attempts that occurred after 18:00. First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with an `AND` operator to filter my results to output only login attempts that occurred after 18:00 and were unsuccessful. The first condition is `login_time > '18:00'`, which filters for the login attempts that occurred after 18:00. The second condition is `success = FALSE`, which filters for the failed login attempts.

Retrieve login attempts on specific dates

Second I need to retrieve login attempts that occurred on specific dates. There was a suspicious event noted on 2022-05-09 so I needed to retrieve all login attempts that occurred on this date.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	0
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0

First, I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE`

clause with an `OR` operator to filter my results to output only login attempts that occurred on either 2022-05-09 or 2022-05-08. The first condition is `login_date = '2022-05-09'`, which filters for logins on 2022-05-09. The second condition is `login_date = '2022-05-08'`, which filters for logins on 2022-05-08.

Retrieve login attempts outside of Mexico

I then needed to get information on logins that didn't originate in Mexico.

```
MariaDB [organization]> SELECT *  
-> FROM log_in_attempts  
-> WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	0
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	0

I started by selecting all data from the `log_in_attempts` table. Then, I used a `WHERE` clause with `NOT` to filter for countries other than Mexico. I used `LIKE` with `MEX%` as the pattern to match because the dataset represents Mexico as `MEX` and `MEXICO`. The percentage sign (%) represents any number of unspecified characters when used with `LIKE`.

Retrieve employees in Marketing

I then needed to get information on employees in the marketing department.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department = 'Marketing' AND office LIKE 'East%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267

I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `AND` to filter for employees who work in the Marketing department and in the East building. I used `LIKE` with `East%` as the pattern to match because the data in the `office` column represents the East building with the specific office number. The first condition is the `department = 'Marketing'` portion, which filters for employees in the Marketing department. The second condition is the `office LIKE 'East%'` portion, which filters for employees in the East building.

Retrieve employees in Finance or Sales

Updates then needed to be implemented in the finance and sales department so I had to retrieve information from these two departments.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE department = 'Finance' OR department = 'Sales';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170

I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `OR` to filter for employees who are in the Finance and Sales departments. I used the `OR` operator instead of `AND` because I want all employees who are in either department. The first condition is `department = 'Finance'`, which filters for employees from the Finance department. The second condition is `department = 'Sales'`, which filters for employees from the Sales department.

Retrieve all employees not in IT

The last security update needed to be made on employees who were not in the information technology department.

```
MariaDB [organization]> SELECT *  
-> FROM employees  
-> WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434

I started by selecting all data from the `employees` table. Then, I used a `WHERE` clause with `NOT` to filter for employees not in this department.

Summary

Using filters in SQL I was able to retrieve specific information on login attempts and employee machines. I accessed information from two tables, `log_in_attempts` and `employees`. I used AND, OR, and NOT to help me find and filter for the specific information needed to help solve the security issue. The use of LIKE and the % signs were also use to filter for wildcard patterns.