

Load necessary packages

```
source('GraphBuilder.R')
library(reshape2)
library(ggplot2)
library(NetworkDistance)
library(sna)
library(gridExtra)
library(docstring)
theme_set(theme_classic(base_size = 10))
```

Define function for later analyses

```
density.calc <- function(g, method = 1){

  d <- edge_density(g) # calculate unweighted density of graph
  # calculate weighted density using edge weights (either time or count depending on
  # method used in video coding)
  dw <- ifelse(method == 1, edge_density(g) * sum(E(g)$time) / length(E(g)),
               edge_density(g) * sum(E(g)$count) / length(E(g)))

  return(c(d, dw))
}

vars.calc <- function(g){
  n.members <- table(V(g)$group)
  groups <- names(n.members[n.members > 2])
  g.sub <- induced_subgraph(g, which(V(g)$group %in% groups))
  g.sub <- subgraph.edges(g.sub, eids = which(E(g.sub)$group == 'within'))

  within.var <- as_long_data_frame(g.sub) %>%
    group_by(from_group) %>%
    summarize(mean = mean(count),
              sum.squares = sum((count - mean)^2)) %>%
    ungroup() %>%
    summarize(within.var = sum(sum.squares)/(length(V(g.sub)) - length(groups))) %>%
    pull()

  return(within.var)
}

df.create <- function(list.of.graphs, session = NA, lab = NA, week = NA, method = 1,
                      func = 'density'){
  if(func == 'density'){
    df <- as.data.frame(t(matrix(unlist(lapply(list.of.graphs, density.calc,
                                              method = method))),
                        ncol = length(list.of.graphs))))
    colnames(df) <- c('density', 'density.weighted')
  } else {
    df <- as.data.frame(t(matrix(unlist(lapply(list.of.graphs, vars.calc)),
```

```

                                ncol = length(list.of.graphs)))
  colnames(df) <- c('within.variance')
}

args = c('session', 'lab', 'week', 'method')
i = 1
for(var in list(session, lab, week, method)){
  if(!is.na(var)){
    df[, args[i]] <- var
  }
  i = i + 1
}

return(df)
}

reliability <- function(g1, g2, method = 1, normalize = FALSE){
  hd <- nd.hamming(list(as_adjacency_matrix(g1), as_adjacency_matrix(g2)))$`D`[1]
  if(method == 1){
    weight = 'time'
  } else {
    weight = 'count'
  }
  hd.w <- nd.hamming(list(as_adjacency_matrix(g1, attr = weight),
                        as_adjacency_matrix(g2, attr = weight)))$D[1]

  if(normalize){
    max.matrix <- pmax(as_adjacency_matrix(g1, attr = weight),
                      as_adjacency_matrix(g2, attr = weight))

    d <- density.calc(graph_from_adjacency_matrix(max.matrix, mode = 'undirected',
                                                  weighted = weight), method = method)

    hd <- 1 - hd/d[1]
    hd.w <- 1 - hd.w/d[2]
  }
  return(c(hd, hd.w))
}

```


Load scan method graphs

Wednesday section

```

g.scan.9.11 <- create.graph(file1 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall20
                        file2 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall20
                        nvid2 = 6, name = '9-11 Scan')
plot.graph(g.scan.9.11)

```




9-11 Scan




```
g.scan.9.18 = create.graph(file1 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall201
                        file2 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall201
                        nvid2 = 7, name = '9-18 Scan')
plot.graph(g.scan.9.18)
```

9-18 Scan




```
g.scan.9.25 = create.graph(file1 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall201  
                        name = '9-25 Scan')  
plot.graph(g.scan.9.25)
```





Monday section

```
g.scan.9.16 <- graph.from.adjacency('C:/Users/Cole/Box Sync/Network analysis/Adjacency_Matrices/P1112_F  
                                     name = '9-16 Scan')  
plot.graph(g.scan.9.16)
```



```
g.scan.9.30 <- graph.from.adjacency('C:/Users/Cole/Box Sync/Network analysis/Adjacency_Matrices/P1112_F  
name = '9-30 Scan')  
plot.graph(g.scan.9.30)
```





Load skip method graphs


Wednesday section

```
g.skip.9.11 <- graph.from.adjacency('C:/Users/Cole/Box Sync/Network analysis/Adjacency_Matrices/P1112_F  
                                     name = '9-11 Skip')  
plot.graph(g.skip.9.11)
```

9-11 Skip




```
g.skip.9.18 <- graph.from.adjacency('C:/Users/Cole/Box Sync/Network analysis/Adjacency_Matrices/P1112_F  
name = '9-28 Skip')  
  
V(g.skip.9.18)$name <- c('1A', '1B', '2C', '2B', '2A', '3A', '3C', '3B', '4A', '4B', '4C',  
'5A', '5B', '5C', '6A', '6B', '6C', '7A', '7B')  
  
plot.graph(g.skip.9.18)
```

```
g.skip.9.25 = create_graph(file1 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall2019/Networks/9-25 Skip',
                           file2 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall2019/Networks/9-25 Skip',
                           nvid1 = 1, nvid2 = 1, method = 2, name = '9-25 Skip')
```

```
## Warning: Grouping rowwise data frame strips rowwise nature
```


```
plot.graph(g.skip.9.25)
```



9-25 Skip



```
g.skip.10.9 <- graph.from.adjacency('C:/Users/Cole/Box Sync/Network analysis/Adjacency_Matrices/P1112_F  
                                     name = '10-9 Skip')  
plot.graph(g.skip.10.9)
```



10-9 Skip



Check interrater reliability for 9-18

```
g.scan.9.18.DK = create.graph(file1 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall1
                        file2 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall1
                        nvid1 = 5, nvid2 = 7, offset1 = 142, method = 1)
# apply manual offset of 142 to first video file data
print('Reliability of scan method between CW and DK for 9-18...')
```

```
## [1] "Reliability of scan method between CW and DK for 9-18..."
```

```
reliability(g.scan.9.18, g.scan.9.18.DK)
```

```
## [1] 0.05847953 0.09805068
```

```
reliability(g.scan.9.18, g.scan.9.18.DK, normalize = TRUE)
```

```
## [1] 0.8850575 0.7931318
```

```
g.skip.9.18.CW = create.graph(file1 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall1
                        file2 = 'C:/Users/Cole/Box Sync/Network analysis/Exported_Data/P1112_Fall1
                        nvid1 = 5, nvid2 = 7, method = 2)
```

```

print('Reliability of skip method between CW and DK for 9-18...')

## [1] "Reliability of skip method between CW and DK for 9-18..."

reliability(g.skip.9.18, igraph::permute(g.skip.9.18.CW,
                                         match(V(g.skip.9.18.CW)$name,
                                                V(g.skip.9.18)$name)), method = 2)

## [1] 0.01754386 0.20467836

reliability(g.skip.9.18, igraph::permute(g.skip.9.18.CW,
                                         match(V(g.skip.9.18.CW)$name,
                                                V(g.skip.9.18)$name)), method = 2,
                                         normalize = TRUE)

## [1] 0.8571429 0.8292683

```

Analyze evolution of density over time

```

get_legend<-function(myggplot){
  tmp <- ggplot_gtable(ggplot_build(myggplot))
  leg <- which(sapply(tmp$grobs, function(x) x$name) == "guide-box")
  legend <- tmp$grobs[[leg]]
  return(legend)
}

scan.graphs.wednesday <- list(g.scan.9.11, g.scan.9.18, g.scan.9.25)
skip.graphs.wednesday <- list(g.skip.9.11, g.skip.9.18, g.skip.9.25, g.skip.10.9)
scan.graphs.monday <- list(g.scan.9.16, g.scan.9.30)

df.density <- rbind(df.create(scan.graphs.wednesday, session = 'Wednesday',
                             lab = c(1, 1, 2), week = c(1, 2, 1), method = 1),
                   df.create(skip.graphs.wednesday, session = 'Wednesday',
                             lab = c(1, 1, 2, 2), week = c(1, 2, 1, 2), method = 2),
                   df.create(scan.graphs.monday, session = 'Monday',
                             lab = c(1, 2), week = c(1, 1), method = 1)) %>%
  mutate(lab.week = paste('L', lab, 'W', week, sep = ''),
         method.session = paste('M', method, 'L', session)) %>%
  melt(., measure.vars = c('density', 'density.weighted'))

plot.unweight <- ggplot(df.density %>%
  filter(variable == 'density'),
  aes(x = as.factor(lab.week), y = value, group = method.session,
      color = as.factor(method))) +
  geom_point(size = 4, aes(shape = session)) +
  geom_line(stat = 'identity', size = 1) +
  labs(x = 'Lab week', y = 'Unweighted Density') +
  scale_color_manual(name = 'Method', values = c('#0072B2', '#E69F00')) +

```

```

scale_shape_manual(name = 'Lab Number', values = c(16, 15)) +
theme(legend.position = "none")


plot.weight <- ggplot(df.density %>%
  filter(variable == 'density.weighted') %>%
  mutate(method = ifelse(method == 1, 'one', 'two')),
  aes(x = as.factor(lab.week), y = value, group = method.session,
      color = as.factor(method)), shape = as.factor(session)) +
geom_point(size = 4, aes(shape = session)) +
geom_line(stat = 'identity', size = 1) +
facet_wrap(~method, scales = 'free', nrow = 2, strip.position = "left",
  labeller = as_labeller(c(one = "Weighted density (minutes)",
                           two = "Weighted density (count)")))) +

labs(x = 'Lab week') +
scale_color_manual(name = 'Method', values = c('#0072B2', '#E69F00'),
  labels = c('Scan', 'Skip')) +
scale_shape_manual(name = 'Lab session', values = c(16, 15)) +
theme(
  strip.background = element_blank(),
  strip.placement = "outside"
) +
ylab(NULL) +
theme(legend.position = "bottom")

legend <- get_legend(plot.weight)
plot.weight <- plot.weight + theme(legend.position = "none")

grid.arrange(plot.unweight, plot.weight, legend, layout_matrix = rbind(c(1, 2), c(3, 3)),
  widths = c(2.7, 2.7), heights = c(2.5, 0.2))

```



Analyze evolution of skip-group variance in scanactions over time

```
df.vars <- df.create(skip.graphs.wednesday, session = 'Wednesday', lab = c(1, 1),
                     week = c(1, 2),
                     method = 2, func = 'variance') %>%
  mutate(lab.week = paste('L', lab, 'W', week, sep = ''))

ggplot(df.vars, aes(x = lab.week, y = within.variance, group = method)) +
  geom_point(size = 4) +
  geom_line(stat = 'identity', size = 1) +
  labs(x = 'Lab session', y = 'Mean within-group variance')
```