

# Program memory: malloc

---

COSC 208, Introduction to Computer Systems, 2021-09-27

## Announcements

- Project 1 Part B (and revisions to Part A) due Thursday at 11pm

## Warm-up

Q1: Draw a memory diagram that displays the program's variables and their values just before the *printf* statements are executed.

```
char *split(char *str, char delim) {
    for (int i = 0; i < strlen(str); i++) {
        if (str[i] == delim) {
            str[i] = '\0';
            return &str[i+1];
        }
    }
    return NULL;
}

void parse(char *url) {
    char separator = '/';
    char *path = split(url, separator);
    int domainlen = strlen(url);
    int pathlen = strlen(path);
    printf("Domain (%d chars): %s\n", domainlen, url);
    printf("Path (%d chars): %s\n", pathlen, path);
}

int main() {
    //                01234567890123456
    char input[] = "colgate.edu/lgbtq";
    parse(input);
}
```

## Pointers as return values

```
int *one() {
    int x = 1;
    int *p = &x;
    return p;
}

int main() {
    int *q = one();
    printf("%d\n", *q);
}
```

There is a problem above... why?

## malloc

Q2: Write a function called *duplicate* that takes a string (i.e., an array of *char*) as a parameter and returns a copy of that string stored on the heap.

Q3: Write a function called *range* that behaves similar to the *range* function in Python. Your function should take an unsigned integer (*length*) as a parameter, and return a dynamically allocated array with *length* unsigned integers. The array should be populated with the values 0 through *length-1*.

Q4: Write a function called *substring* that takes a string, a starting index, and a length, and returns a substring. If the starting index is too large, the function should return *NULL*. If the length is too large, the function should return a shorter substring.

## From stack to heap

```
int* copy(int a[], int size) {
    int i, *a2;
    a2 = malloc(size*sizeof(int));
    if (a2 == NULL)
        return NULL;
    for (i = 0; i < size; i++)
        a2[i] = a[i];
    return a2;
}

int main(int argc, char** argv) {
    int nums[4] = {1, 2, 3, 4};
    int* ncopy = copy(nums, 4);
    // .. do stuff with the array ..
    free(ncopy);
    return EXIT_SUCCESS;
}
```

## Extra practice

Q5: Write a function called *lengths* that takes an array of strings and the number of elements in the array and returns an array of integers containing the length of each string.

Q6: Write a function called *generate\_password* that takes an unsigned integer (*length*) as a parameter, and returns a dynamically allocated array of with *length* randomly selected characters (e.g., uppercase letters, lowercase letters, digits, symbols). Your function should use the *rand()* function from the C standard library, which returns a pseudo-random integer in the range 0 to *RAND\_MAX*.