2021-09-15.md 9/15/2021

Exam 1 Review

COSC 208, Introduction to Computer Systems, 2021-09-15

Announcements

• Exam 1 on Friday

Outline

Exam 1 review

No warm-up — happy Wednesday!

Binary arithmetic

Perform the following calculations. Operands are be encoded using two's complement encoding with 6 bits. For each calculation, express the result in binary and decimal, and indicate whether the result overflows, underflows, or neither.

```
• 0b110000 + 0b111111 = 0b101111 = -17; neither
• 0b001111 + 0b000001 = 0b010000 = 16; neither
• 0b101010 + 0b100100 = 0b001110 = 14; underflow
• 0b001000 + 0b011000 = 0b100000 = -32; overflow
• 0b110000 + 0b010000 = 0b000000 = 0; neither
```

Strings

• The following program should ask the user to enter a word, then print the word's length and whether it is a palindrome (i.e., reads the same backward as forward). For example, if the user enters "kayak" the program should print "The word is 5 characters long and is a palindrome." However, the program contains several errors. Modify the program to correct the errors.

```
#include <stdio.h>

void palindrome(char word[]) {
    int i = 0;
    int j = strlen(word);
    while (i < j) {
        if (word[i] != word[j]) {
            return -1;
        }
        i++;
        j--;
    }
    return 1;
}</pre>
```

2021-09-15.md 9/15/2021

```
int main() {
    printf("Enter a word: ");
    char word[50];
    fgets(word, 50, stdin);
    word[strlen(word)-1] = '\0'; // Remove newline
    int len = strlen(word);
    printf("The word is %c characters long and is ", len);
    if (palindrome(word)) {
        printf("a palindrome.\n");
    } else {
        printf("not a palindrome.\n");
}
```

- o #include <string.h>
- Change return type of palindrome to int
- ∘ Initialize j to strlen(word) 1
- ∘ Change return -1 to return 0
- Change %c in 2nd printf in main to %d
- Write a function called molecular_formula that takes a string containing the constituent atoms of a molecule and updates the string to contain the molecular formula. For example, the string "HH0" should be changed to "H20", and the string "HHS0000" should be changed to "H2504". You can assume:
 - Molecules will only contain elements that are represented by a single letter e.g., a molecule may contain 'H' but not "Na"
 - All atoms of the same element are listed consecutively e.g., the constituent atoms may be provided as "HHO" but not "HOH"
 - The elements are listed in the order they should appear in the molecular formula e.g., the constituent atoms "HH0" are changed to the molecular formula "H20", whereas the constituent atoms "OHH" are changed to the molecular formula "OH2"
 - There will be at most 9 atoms of each element e.g., "H9C9" may occur, but "H10C11" will not occur

```
void molecular_formula(char elements[]) {
    int count = 1;
    int j = 0;
    for (int i = 1; i <= strlen(elements); i++) {</pre>
        if (elements[i] != elements[i-1]) {
             elements[j] = elements[i-1];
             j++;
             if (count > 1) {
                 elements[j] = count + '0';
                 j++;
             }
             count = 0;
        }
        count++;
    elements[j] = ' \setminus 0';
}
```

2021-09-15.md 9/15/2021

Number base conversions

Perform the following conversions

```
• 97 to 8-bit unsigned binary = 0b01100001
```

- -42 to 8-bit two's complement = 0b11010110
- 0b11001100 to unsigned decimal = 128 + 64 + 8 + 4 = 204
- 0b11001100 to signed decimal = -52
- 0x27 to unsigned decimal = 39
- 0xDEAD to 16-bit binary = 0b1101111010101101

Structs

- Define a struct for representing a chemical element, which includes the element's:
 - Name
 - Chemical symbol
 - o Atomic number
 - o State (solid, liquid, or gas) at room temperature

```
struct element {
   char name[20];
   char symbol[3];
   int number;
   char state;
};
```

• Write a function called *lookup* that takes a chemical symbol and an array containing a struct for each of the 118 elements in the periodic table. The function should return the specified element's atomic number. If the provided symbol does not correspond to a known element, the function should return -1.

```
int lookup(char symbol[], struct element table[]) {
   for (int i = 0; i < 118; i++) {
      if (strcmp(symbol, table[i].symbol) == 0) {
        return table[i].number;
      }
   }
  return -1;
}</pre>
```