

Incident report analysis

Instructions

As you continue through this course, you may use this template to record your findings after completing an activity or to take notes on what you've learned about a specific tool or concept. You can also use this chart as a way to practice applying the NIST framework to different situations you encounter.

Summary	The company had experienced a Denial of Service (DoS) attack due to an incoming flood of ICMP packets, which led to the internal network not being able to access any network resources. The security team responded by blocking the packets and stopping all non-critical network services online, and restoring critical network services.
Identify	The threat actor/s was able to attack the company with a DoS attack which involved flooding the company's network with ICMP packets. The internal network was affected and critical network resources needed to be restored.
Protect	The security team configured the previously unconfigured firewall to limit the rate of incoming ICMP packets and verify the source IP address on incoming packets. The team also implemented an IDS/IPS system to detect suspicious traffic attempting to enter the network.
Detect	The security team added source IP address verification on the firewall to check for spoofed IP addresses on incoming ICMP packets and also implemented network monitoring software to detect abnormal traffic patterns.
Respond	The team will isolate affected networks or systems to contain the attack and prevent further disruption to the entire network. The team will also restore

	critical systems and services that were affected by the attack. The analysis of network logs to further check for suspicious activity will also be conducted. After these, the team will report the details of the incident to management and legal authorities.
Recover	In order to recover from a DoS attack involving ICMP flooding, network systems and services need to be restored to a normal state. To prevent similar attacks in the future, configuring the firewall to block ICMP flood attacks is necessary. To further reduce unnecessary network activity, non-critical network services should be stopped. Then, critical network services should be prioritized for restoration. After making sure that the ICMP flooding has been controlled, all network systems and services can then be restored as well.

Reflections/Notes: