PASSCHIP®

Smart card chip reader with Wiegand protocol for lobby entrance

PRODUCT: Banking Smart card chip reader with Wiegand protocol for advanced access control systems

PASSCHIP enables Banks to facilitate the access of customers to the 24Hours Self Service area, in a secured, automatic way. The system is very flexible allowing multiple possible configurations and combined with its simplicity and intuitive GUI makes PASSCHIP an advanced and easy to use Access Control System.

**PRODUCT IMAGE of Applied model- Stainless Steel material:**

Dimension(WxHxD): 138x312x124 mm

The access selection is made following one or more criteria, according with the specific application:

*Name/Surname written on the credit cards(it is possible to define BLACK LISTS)
*Credit card number
*Type of credit card(Visa, Visa Electron, Visa Business, Visa Gold, Maestro....)
*Bank(the system may be programmed as only the bank's clients to have access or full different scenarios)
*Date of expiry

Note: The system is a security product, it does not log on sensitive and personal data, nor financial data of readed cards.

It is designed only for access and management purposes.

1 = chip reader; 2 = electric lock; 3 = exit button; 4 = magnetic contact; 5 = communication bus; 6 = access control module; 7 = control unit; 8 = computer with administration software

This application runs on the Control Unit and has to authenticate a customer before allowing him to enter the 24Hours Self Service area.

Functionality:

• Authentication / Authorization

authentication is initiated by the customer by presenting a smartcard to a PASSCHIP reader

• PASSCHIP reads the card details (Card Number and Expiration date) and then takes the appropriate action (allow or block access to the 24Hours Self Service area)

Error! No sequence specified.

Features:

- Fire - used in case of emergency – generated from an access control system

- External Timetable – used to control when to allow customers access to the 24Hours Self Service area - generated from an access control system

- Timetable – used to define the working schedule for the application

- Magnetic contact – used for confidentiality purposes after entrance

- PIR also for confidentiality purposes after entrance

--- PASSCHIP®
1 Piata Presei Libere, 1st District, 013888, Bucharest, Romania
Tel: 0040745342887, Fax: 0040378104216, office@passchip.com   www.passchip.com

Printed in Romania   Data subject to change without notice

- ID List – this is the list of bank's accepted ID for customer's smartcards; this feature is useful for blocking a specific type of smartcards (eg. Visa Electron

- BLK (blocked) List – this is a list of Card Numbers or Card Number prefixes that are not allowed to enter the 24Hours Self Service area; used for blocking a range of smartcards belonging to a bank or for blocking specific customers (eg. vandals).

- Door Timer – time period (seconds) that the Relay must be kept open; used to adjust the time period within which the customers are allowed to enter the 24Hours Self Service area

- Relay – PASSCHIP can control a relay which in turn locks / unlocks a door; this feature is useful for integrating PASSCHIP with a electromagnetic door lock

- Wiegand – PASSCHIP can act as a wiegand enabled reader which sends messages to an access control system; this feature is useful for integrating PASSCHIP with an existing access control system

- Different Display types (with different aspect ratios and resolutions) – during operation the display can be replaced with a different one

- Background Image customization – the background image can be replaced "on-the-fly" with a different one

- Text Messages customization – the text messages can be replaced "on-the-fly" with different ones

Sample images visible on the Display:

PENTRU ACCES ATM
INTRODUCETI CARDUL
FOR ATM ACCESS
PLEASE INSERT CARD

BANK PASSCHIP®

CITIRE CARD

READING CARD

BANK PASSCHIP®

RETRAGETI CARDUL

REMOVE CARD

BANK PASSCHIP®

ACCES PERMIS

ACCESS GRANTED

BANK PASSCHIP®

CARD EXPIRAT

CARD HAS EXPIRED

PASSCHIP

BANK PASSCHIP®

BANK PASSCHIP®

Server application

This application runs on a server and is responsible for controlling all PASSCHIPs and serving all requests from Client Application.

--- PASSCHIP®   Printed in Romania   Data subject to change without notice
1 Piata Presei Libere, 1st District, 013888, Bucharest, Romania
Tel: 0040745342887, Fax: 0040378104216, office@passchip.com www.passchip.com

HW Layout

Logical Layout

Functionality:

- Logging

- Monitoring

- Statistics (Reports)

- User configuration

- PASSCHIP management

All persistent data is stored using an SQL database.

--- PASSCHIP®   Printed in Romania   Data subject to change without notice
1 Piata Presei Libere, 1st District, 013888, Bucharest, Romania
Tel: 0040745342887, Fax: 0040378104216, office@passchip.com   www.passchip.com

Client application

This application runs on user workstations and is used for managing the entire system (both admin console and operator application).

--- PASSCHIP®   Printed in Romania   Data subject to change without notice
1 Piata Presei Libere, 1st District, 013888, Bucharest, Romania
Tel: 0040745342887, Fax: 0040378104216, office@passchip.com   www.passchip.com

File   Settings   Help

Authentication Required | Password Change | Operator | Location Mangement | PASSCHIP Profiles | PASSCHIP Configuration | **User Management** | License | Server

Groups

All
USER Admin
PASSCHIP Admin
Operator

Users

Admin
Ion Popescu

User

Username   Jane1
First Name   Jane
Last Name   Doe
Password
Groups   ☑ Operator ☐ PASSCHIP Admin ☐ USER Admin
              ☐ Change password on next login
              ☐ Account locked
              ☐ Password never expires
Password age 21 days

[Add] [Delete] [Save] [Reset Password]

Password Policy

Minumum Length	8
Minumum uppercase chars	1
Minumum digits	1
Minumum special chars	1
Maximum password age [days]	90
Failed attempts before lockout	3
Password history	3

[Save]

👤 Ion Popescu   **Specific Message**   Server Connection 🟢

File | Settings Help

Authentication Required | Password Change | Operator | Location Mangement | PASSCHIP Profiles | **PASSCHIP Configuration** | User Management | License | Server

Location	Status
⊟ All	
⊟ Brasov	GREY
— Brasov	OK
— Rasnov	ALARM
⊟ Prahova	
— Ploiesti	
— Brazi	
⊟ Timis	
— Timisoara	
⊟ Bucuresti	OK
⊟ Sector1	OK
— Grivita	OK
— Sector2	OK
⊟ Sector3	OK
— Iancului	OK

IP

IP Address 192.168.2.14
Netmask   255.255.255.0
Gateway   192.168.2.254
DNS   192.168.2.254
Display IP

802.1X

Username User
Password ************

Display resolution

480x272 ▼

[Save]

👤 Ion Popescu   **Specific Message**   Server Connection 🟢

Shield pinout:

PIN	Description
1	Wiegand Data0
2	Wiegand Data1
3	Wiegand GND
4	INT BAT GND
5	INT BAT +5V
6	Not Connected
7	Door Relay NO
8	Door Relay NC
9	Door Relay COM
10	Fault Relay NO
11	Fault Relay NC
12	Fault Relay COM
13	Not Connected
14	GND
15	Inactive (Fire) (NO)
16	GND
17	PIR (NC)
18	GND
19	Exit Button (NO)
20	GND
21	CM (NC)
22	- 12V
23	+12V

Cable

Position	Description	Color
R1	Wiegand Data0	
R2	Wiegand Data1	
R3	Wiegand GND	
R4	- 12V	
R5	+12V	
R6	Not Connected	
R7	Door Relay NO	
R8	Door Relay NC	
R9	Door Relay COM	
R10	Fault Relay NO	
R11	Fault Relay NC	
R12	Fault Relay COM	
R13	Not Connected	
R14	GND1	verde
R15	Inactive / Fire (NO)	a-verde
R16	GND2	albastru
R17	PIR (NC)	a-albastru
R18	GND3	maro
R19	Exit Button (NO)	a-maro
R20	GND4	portocaliu
R21	Magnetic Contact (NC)	a-porto
R22	TAMPER	
R23	TAMPER	
R24	GROUND	

POWER SOURCE
12 V DC, 3A

RELAY 1A 30V DC

Communication	Ethernet 100 Base-TX/10Base-T RS232 up to 115200 Bit/sec
	Clock and Data
	Wiegand up to 64 bit
Memory	Internal DRAM 1 GB, record of min 50 configurable ID banking cards profiles according EMV or non EMV standard, SD slot available 1xMMC
	Real time clock with back-up Li-Ion maintenance free battery
Reference Standards	ISO 7816 with T=0 and T=1, EMVCo Level 1, ISO 7810, ISO 7811, JIS X6301, JIS X6302I, contactless NFC
Processor	ARM 64-bit, 1.2 GHz, Quad
Operating System	Linux OS
Software Upgrade	On line, during functioning
Power Supply	85-264 VAC, 45-65 Hz, Cold Start,
Power Consumption	Max. 30 W
History Log capacity	5MB, aprox. 10 000 events with time stamp
Lifecycle	Min 125 000 functioning hours
	Min 500 000 insertion cycles
Insertion Speed	8-127 cm/sec
Construction	Applied mount in Stainless Steel case or Flush mount in Aluminium painted case, Antiskimming, metal bezel, antivandal, UV filter for LCD screen
Display	LCD: 4.3" 480x272 pixels
	Contrast ratio 300:1, Brightness min 300cd/sqm Color min QVGA 65 000 colors
Agency Approvals and Standards	CE Conformity
Ambient conditions	Operating Temp:-30 C +50 C
	Storage Temp:-35 C +60 C
	Humidity: 10-95%
Sound and interface	Multi-color LED and multi-tone buzzer
Size o f c ontr oller (W x H x D)	138 x 312 x 124 mm-Applied mount
	170 x 195 x 80 mm-Flush mount
Weight	3.90 Kg
Protection Class	IP65 for Stainless Steel Applied model
	IP50 for Flush mount
Interaction with the user	Virtually any available known written language, pictograms and multitone internal buzzer
Black list	YES, online programable for maximum 1 000 card profiles
NFC	OPTIONAL

 --- PASSCHIP®   Printed in Romania   Data subject to change without notice
1 Piata Presei Libere, 1st District, 013888, Bucharest, Romania
Tel: 0040745342887, Fax: 0040378104216, office@passchip.com   www.passchip.com