

# Teaching Machines to See Patterns

A Neural Networks Primer: Why We Needed Each Piece of the Puzzle

NLP Course 2025

From the 1950s mail sorting crisis to ChatGPT: How humanity taught machines to think

## Where We're Going Today

### Act I: The Problem (1943-1969)

- The mail sorting crisis
- First mathematical neurons
- The perceptron revolution
- The XOR catastrophe

### Intermission: Understanding the Basics

- How neurons calculate
- Why we need layers
- Following the forward pass

### Act II: The Struggles (1980s-1990s)

- Hidden layers save the day
- Backpropagation breakthrough
- Universal approximation proof

### Act III: The Revolution (2000s-Present)

- Deep learning explosion
- Modern architectures
- Real-world impact

### Epilogue: Your Turn

- Build your first network
- Next steps

Each act builds on the previous - no jumping ahead!

## 1950s: The Mail Sorting Crisis

### The Challenge:


- 150 million letters per day
- Hand-written addresses
- Human sorters: slow, expensive, error-prone
- Traditional programming: useless

### Why Traditional Code Failed:

- Can't write rules for every handwriting style
- Too many variations of each letter
- Context matters: "l" vs "I" vs "1"
- This wasn't computation—it was **pattern recognition**

This problem would take 40 years to solve properly

# 80 Years of Neural Networks: The Complete Journey



# Why Can't We Just Write Rules?

## Problem: Recognize the Letter "A"

### Traditional Approach (Failed):

```
if (has_triangle_top AND  
    has_horizontal_bar AND  
    two_diagonal_lines) {  
    return "A"  
}
```

But what about...

- Handwritten A's?
- Different fonts?
- Rotated A's?
- Partial A's?

The Challenge: Infinite Variations of "A"

A A A A

A a A A

Just for the letter "A", we'd need thousands of rules!

The breakthrough: What if machines could learn patterns like children do?

## The Birth of Computational Neuroscience

### The Revolutionary Paper:

- "A Logical Calculus of Ideas Immanent in Nervous Activity"
- First mathematical model of neurons
- Proved: Networks can compute ANY logical function
- Inspired von Neumann's computer architecture

### Key Insight:

- Neurons = Logic gates
- Brain = Computing machine
- Thinking = Computation

### The Model:

- Binary neurons (0 or 1)
- Threshold activation
- Fixed connections
- No learning yet!

### Historical Impact:

- Founded field of neural networks
- Influenced cybernetics movement
- Set stage for AI research
- "The brain is a computer" metaphor

14 years later, Rosenblatt would add the missing piece: learning

# 1957: The First Learning Machine - The Perceptron

## Frank Rosenblatt's Radical Idea: Neurons That Learn

### Beyond McCulloch-Pitts:

- Adjustable weights (not fixed!)
- Learning from mistakes
- Physical machine built (Mark I)
- Could recognize simple patterns

### The Hardware:

- 400 photocells (20×20 “retina”)
- 512 motor-driven potentiometers
- Weights adjusted by electric motors
- Took 5 minutes to learn patterns

### Mathematical Model:

- Inputs:  $x_1, x_2, \dots, x_n$
- Weights:  $w_1, w_2, \dots, w_n$
- Sum:  $z = \sum_{i=1}^n w_i x_i + b$
- Output:  $y = \begin{cases} 1 & \text{if } z > 0 \\ 0 & \text{if } z \leq 0 \end{cases}$

*In plain words: Each input gets a vote (weight). We add up all votes plus a bias. If total is positive, output 1; otherwise 0.*


**Learning Rule:** If wrong:  $w_i = w_i + \eta \cdot \text{error} \cdot x_i$

The New York Times, 1958: "The Navy revealed the embryo of an electronic computer that will be able to walk, talk, see, write, reproduce itself and be conscious of its existence."


# The Mark I Perceptron: A Physical Learning Machine

## The Mark I Perceptron (1957): A Physical Learning Machine

Mark I Perceptron Architecture



Physical Learning Process



The first neural network wasn't software—it was a room-sized machine with motors physically adjusting weights



## Let's Understand How This Actually Works

### We've Seen the History...

- McCulloch-Pitts invented the neuron
- Rosenblatt made it learn
- The perceptron was born

### Now Let's See the Science:

- How does a neuron calculate?
- What does learning mean?
- Why was XOR so hard?

**Next 5 slides: Hands-on calculations and exercises**  
Get your pencil ready - we're going to work through real examples!

Don't worry - we'll return to the story once you understand the basics

# Understanding Check: Can You Answer These?

## Let's Make Sure We're Together

### Quick Questions:

- ❶ Why couldn't traditional programming solve mail sorting?
- ❷ What does a weight represent in simple terms?
- ❸ Why do we need the bias term?
- ❹ What was revolutionary about Rosenblatt's perceptron?

### Think About It:

- A weight is like the importance/trust we give to each input
- Bias shifts our decision threshold
- Learning = adjusting these weights
- The perceptron was the first machine that could learn!

**Try It Yourself:** Draw a simple perceptron with 2 inputs. Label the weights, bias, and output. What would the weights be to compute AND logic?

If any of these are unclear, revisit the previous slides before continuing

**Problem: Learn OR function (output 1 if ANY input is 1)**

**Training Data:**

$x_1$	$x_2$	Output
0	0	0
0	1	1
1	0	1
1	1	1

**The Perceptron:**

$$z = w_1 \cdot x_1 + w_2 \cdot x_2 + b$$

$$\text{output} = \begin{cases} 1 & \text{if } z > 0 \\ 0 & \text{if } z \leq 0 \end{cases}$$

*In plain words: Multiply first input by first weight, second input by second weight, add bias, check if positive*

Success! But this was just the beginning...

**Learning Process:**

- ① Start with random weights
- ② For each example:
  - Calculate output
  - If wrong: adjust weights
  - If correct: keep weights
- ③ Repeat until all correct

**Final Solution:**  $w_1 = 1$ ,  $w_2 = 1$ ,  $b = -0.5$

# Let's Calculate Together: Is This Email Spam?

## A Real Perceptron Calculation You Can Follow

### The Email:

"FREE money! Click here NOW for amazing offer!!!"

### Our Features (Inputs):

- $x_1 = \text{Has "FREE"}? = 1$
- $x_2 = \text{Has "money"}? = 1$
- $x_3 = \text{Many "!"?} = 1$
- $x_4 = \text{From friend?} = 0$

### Learned Weights:

- $w_1 = +3$  (FREE is very spammy)
- $w_2 = +2$  (money is suspicious)
- $w_3 = +2$  (!!! is aggressive)
- $w_4 = -5$  (friends are trusted)
- $b = -2$  (threshold)

### Let's Calculate:

$$\begin{aligned} z &= w_1 \cdot x_1 + w_2 \cdot x_2 + w_3 \cdot x_3 + w_4 \cdot x_4 + b \\ &= 3 \cdot 1 + 2 \cdot 1 + 2 \cdot 1 + (-5) \cdot 0 + (-2) \\ &= 3 + 2 + 2 + 0 - 2 \\ &= 5 \end{aligned}$$

### Decision:

- $z = 5 > 0$
- Output = 1 = SPAM!

**Try It Yourself:** What if this email WAS from a friend ( $x_4 = 1$ )? Recalculate! Would it still be spam?

**Answer:**  $z = 5 - 5 = 0$ , borderline!

This is exactly how early spam filters worked - and why they failed on clever spam

## Breaking Down the Math Symbols

### Inputs and Weights:

- $x_i$  = input value (what we see)
- $w_i$  = weight (importance/strength)
- $b$  = bias (threshold adjuster)

### The Computation:

$$z = \sum_{i=1}^n w_i x_i + b$$

This means:

- Multiply each input by its weight
- Add them all up
- Add the bias

This simple math would evolve into deep learning

### Real Example:

Should I go outside?

Factor	Value	Weight
Sunny?	1	+2
Raining?	0	-3
Weekend?	1	+1

$$z = (1 \times 2) + (0 \times -3) + (1 \times 1) = 3$$

Decision:  $z > 0$ , so YES!

# 1969: The Crisis - XOR Problem

## Minsky & Papert's Devastating Discovery

### XOR (Exclusive OR):


$x_1$	$x_2$	Output
0	0	0
0	1	1
1	0	1
1	1	0

### The Problem:

- Can't draw a single line to separate
- Perceptron only learns linear boundaries
- Real-world problems are non-linear!

The field would be dormant for over a decade...

The XOR Crisis (1969)



### Impact:

- Funding dried up
- "AI Winter" begins
- Neural networks abandoned

# When One Line Isn't Enough: Real Problems Need More


## Let's See Why We Need Hidden Layers

### Problem 1: Spam Detection (Easy)

- Has many spam words? → SPAM
- Has few spam words? → NOT SPAM
- One line (threshold) works!

### Problem 2: Cat or Dog Photo (Hard)

- Small + fluffy? Could be either!
- Large + smooth? Could be either!
- Pointy ears + whiskers? → Cat
- Floppy ears + wet nose? → Dog
- Need multiple feature detectors!




### The Solution:

- 1 First layer: Multiple detectors
  - Detector 1: "Has cat features?"
  - Detector 2: "Has dog features?"
- 2 Second layer: Combine detections
  - If cat features  $\wedge$  dog features → Cat

This is why deep learning works: each layer builds more complex detectors from simpler ones

# Visual Bridge: Why XOR Needs Hidden Layers

## From Simple Lines to Complex Boundaries



### Single Perceptron = One Line:

- Can only draw straight boundaries
- Works for OR, AND
- Fails for XOR, real problems

### Hidden Layers = Multiple Lines:

- Each hidden neuron draws a line
- Output combines these lines
- Can create any shape!

**Common Confusion:** Hidden layers don't "hide" anything - they're called hidden because we don't directly set their values. They learn what features to detect!

This insight took 13 years to discover and implement properly



### 1980s: The Hidden Layer Revolution


#### The Insight:

- Stack multiple layers!
- First layer: detect simple features
- Hidden layer: combine features
- Output layer: final decision

#### Solving XOR:

- Hidden neuron 1: Is it (0,1)?
- Hidden neuron 2: Is it (1,0)?
- Output: OR of hidden neurons

#### Multi-Layer Network: Solving Complex Problems




#### New Architecture:

- Input layer: raw data
- Hidden layer(s): feature extraction

# Forward Pass Playground: Let's Calculate Through a Network!

## Follow the Numbers Step by Step

### Simple 2-Layer Network:



### Your Task: Calculate the output!

Try It Yourself: Fill in the blanks as we go:

- $h_1 = ?$
- $h_2 = ?$
- $y = ?$

This is exactly what happens millions of times per second in deep learning

### Step 1: Calculate Hidden Neurons

$$\begin{aligned}h_1 &= \text{ReLU}(1 \cdot 0.5 + 0 \cdot 2.0 - 0.5) \\&= \text{ReLU}(0.5 + 0 - 0.5) \\&= \text{ReLU}(0) = 0\end{aligned}$$



$$\begin{aligned}h_2 &= \text{ReLU}(1 \cdot 1.0 + 0 \cdot (-1) + 0.5) \\&= \text{ReLU}(1.0 + 0 + 0.5) \\&= \text{ReLU}(1.5) = 1.5\end{aligned}$$

### Step 2: Calculate Output

$$\begin{aligned}y &= 0 \cdot 1.5 + 1.5 \cdot 1.0 + 0 \\&= 0 + 1.5 + 0 = 1.5\end{aligned}$$







The network output is 1.5!

# Solving XOR: Step-by-Step with Hidden Layers



# Learning in Action: Weight Evolution

## Weight Evolution During Training



## The Credit Assignment Problem: Who's to Blame?

### The Challenge:

- Network makes error at output
- Many neurons contributed
- Which weights should change?
- By how much?

### The Solution: Chain Rule

- Calculate error at output
- Propagate error backwards
- Each layer gets its "share of blame"
- Adjust weights proportionally

### Mathematical Insight:

$$\frac{\partial E}{\partial w_{ij}} = \frac{\partial E}{\partial out_j} \cdot \frac{\partial out_j}{\partial net_j} \cdot \frac{\partial net_j}{\partial w_{ij}}$$

*In plain words: How much should we change this weight?  
= How wrong were we? times How sensitive is the output?  
times How much did this weight contribute?*

### In Simple Terms:

- ① How wrong were we? (Error)
- ② How sensitive is error to this weight?
- ③ Adjust weight in opposite direction
- ④ Repeat for all weights, back to front

This algorithm is still the foundation of all deep learning today

## Sejnowski & Rosenberg's Speaking Network

### The Challenge:

- English pronunciation is irregular
- "though" vs "through" vs "tough"
- Rule-based systems failed
- Can a network learn from examples?

### The Architecture:

- Input: 7 letters (context window)
- Hidden: 80 neurons
- Output: 26 phonemes
- 18,000 total weights

### The Results:

- Started: Random babbling
- After 10 epochs: Consonants/vowels
- After 30 epochs: Simple words
- After 50 epochs: 95% correct!

### Why It Mattered:

- Proved backprop works on real problems
- Learned complex, irregular mappings
- No rules programmed!
- Sounded like a child learning to read

The network literally learned English pronunciation overnight

## Cybenko's Theorem: Networks Can Learn ANY Function

**The Theorem:** "A feedforward network with:

- One hidden layer
- Finite neurons
- Sigmoid activation

can approximate ANY continuous function to arbitrary accuracy"

**What This Means:**

- Neural networks are universal
- Can solve any pattern recognition
- Just need enough neurons
- Mathematics guarantees it!

**The Catch:**



- Doesn't say HOW MANY neurons
- Doesn't say HOW to find weights
- Might need exponentially many
- Training might take forever

**Historical Impact:**

- Ended theoretical doubts
- Justified deep learning research
- Shifted focus to practical training
- "We know it's possible, now make it work"

This theorem convinced skeptics that neural networks were worth pursuing

# The Vanishing Gradient Problem: Why Deep Was Hard



Gradients shrink exponentially through layers—this blocked deep learning until ReLU (2011)



# Try It Yourself: Understanding Backpropagation

## Let's Work Through a Tiny Example

### Simple 2-Layer Network:

- Input: 1
- Weight 1: 2 (makes it 2)
- Weight 2: 3 (makes it 6)
- Target output: 10
- Actual output: 6
- Error: 4

**Try It Yourself:** If we're off by 4, and weight 2 multiplies by 3, how much should we adjust weight 2? What about weight 1?

### The Intuition:

- ❶ Error at output: -4 (too small)
- ❷ Weight 2's fault: It multiplied by 3
- ❸ Adjust weight 2: Add 1.3
- ❹ Weight 1's fault: Fed into weight 2
- ❺ Adjust weight 1: Smaller change

### Key Insight:

- Closer to output = bigger updates
- Further back = smaller updates
- This is the "chain rule" in action!

This simple idea scales to billions of parameters

## The Need for Non-Linearity

### Problem with Linear:

- Stack of linear layers = still linear!
- $f(g(x)) = (wx + b_1)w' + b_2 = w'wx + \dots$
- Can't learn complex patterns

### Solution: Activation Functions

- Add non-linearity after each layer
- Allows learning complex boundaries
- Different functions for different needs

### Common Activation Functions:

- **Sigmoid:**  $\sigma(x) = \frac{1}{1+e^{-x}}$ 
  - Smooth, outputs 0-1
  - Good for probabilities

*In plain words: Squashes any input to range 0-1. Large positive becomes 1, large negative becomes 0*

- **ReLU:**  $f(x) = \max(0, x)$ 
  - Simple, fast
  - Solves vanishing gradient
- **Tanh:**  $\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}}$ 
  - Outputs -1 to 1
  - Zero-centered

ReLU's simplicity revolutionized deep learning in 2011


## Teaching a Network to Separate Red from Blue Points

### The Setup:

- Input: (x, y) coordinates
- Output: Red or Blue class
- Network:  $2 \rightarrow 4 \rightarrow 2$  neurons

### Training Process:

- 1 Epoch 1: Random boundary
- 2 Epoch 10: Rough separation
- 3 Epoch 50: Good boundary
- 4 Epoch 100: Perfect fit



### What Each Layer Learns:

- Layer 1: Simple boundaries
- Hidden: Combine boundaries
- Output: Final decision

This same principle scales to millions of parameters

## 1998-2012: From Digits to ImageNet

### 1998 - LeNet: First Success

- Yann LeCun's CNN for digits
- $32 \times 32$  pixels  $\rightarrow$  10 classes
- 60,000 parameters
- Banks adopt for check reading

### Key Innovation: Convolutions

- Share weights across image
- Detect features anywhere
- Build complexity layer by layer

### 2012 - AlexNet: The Revolution

- 1000 ImageNet classes
- 60 million parameters
- GPUs enable training
- Error rate: 26%  $\rightarrow$  16%

### What Changed:

- Big Data (millions of images)
- GPU computing (100x faster)
- ReLU activation
- Dropout regularization

This victory ended the second AI winter permanently

# The Convolution Innovation: See Like Humans Do

## How We Actually Recognize Objects

### Human Vision Process:

- 1 Detect edges
- 2 Find shapes
- 3 Identify parts
- 4 Recognize object

### CNN Mimics This:

- Layer 1: Edge detectors
- Layer 2: Corner/curve detectors
- Layer 3: Part detectors
- Layer 4: Object detectors

### CNN: Building Complex Recognition from Simple Features

Layer 1: Edges



Layer 2: Corners



Layer 3: Parts



Layer 4: Objects



### Key Insight:


- A "wheel detector" works anywhere in image
- Share the same detector across positions
- Reduces parameters dramatically
- Makes network translation-invariant

This is why CNNs dominate computer vision

# The Mathematics of Learning: Gradient Descent

## Finding the Best Weights: Like Hiking Down a Mountain

Gradient Descent: Finding the Lowest Point



### The Optimization Problem:

- Millions of weights to adjust
- Each affects the error
- Need to find best combination

### Gradient Descent:

- 1 Calculate error (loss)
- 2 Find slope (gradient) for each weight
- 3 Step downhill:  $w = w - \alpha \cdot \nabla L$

*In plain words: New weight = old weight - (step size times slope)*

# Types of Learning: Different Problems, Different Approaches

## **Supervised Learning:**

- Have input-output pairs
- Learn mapping function
- Examples: Classification, Regression

## **Unsupervised Learning:**

- Only have inputs
- Find patterns/structure
- Examples: Clustering, Compression

## **Reinforcement Learning:**

- Learn through trial/error
- Maximize reward signal
- Examples: Games, Robotics

## **Self-Supervised (Modern):**

- Create labels from data itself
- Predict next word, masked words
- Examples: GPT, BERT

Self-supervised learning powers all modern language models

## Can You Match These Examples?

**Try It Yourself:** Match each scenario to a learning type: Supervised, Unsupervised, Reinforcement, Self-Supervised

### Scenarios:

- ① Teaching a robot to walk by giving rewards for standing
- ② Showing 1000 cat photos labeled "cat"
- ③ Giving GPT text with words masked out
- ④ Finding groups in customer data

### Answers:

- ① Reinforcement (trial and error)
- ② Supervised (labeled examples)
- ③ Self-supervised (creates own labels)
- ④ Unsupervised (finds patterns)

**Common Confusion:** Self-supervised IS supervised learning - we just create the labels automatically from the data itself!

Understanding these differences helps you choose the right approach



# The Overfitting Problem: When Learning Goes Too Far

## Memorization vs. Understanding

### The Problem:

- Network memorizes training data
- Fails on new, unseen data
- Like student memorizing answers

### Signs of Overfitting:

- Training accuracy: 99%
- Test accuracy: 60%
- Complex decision boundaries
- High variance




### Solutions:

- **More data:** Can't memorize everything
- **Dropout:** Randomly disable neurons
- **Regularization:** Penalize complexity
- **Early stopping:** Stop before overfitting

"With four parameters I can fit an elephant, with five I can make him wiggle his trunk" - von Neumann

# How Deep Networks See: Building Features Layer by Layer

## From Pixels to Concepts: The Hierarchy of Understanding



### What Each Layer Learns:

- **Layer 1:** Edges, colors, gradients
- **Layer 2:** Corners, textures, curves
- **Layer 3:** Parts (eyes, wheels, patterns)
- **Layer 4:** Objects (faces, cars, scenes)
- **Layer 5:** Concepts (identity, style, context)

Each layer combines features from the previous layer into more abstract concepts

### Why Hierarchy Matters:


- Reusable features
- Efficient representation
- Transfer learning works
- Mimics visual cortex

### Discovered Automatically:

- No manual feature engineering
- Emerges from data
- Different tasks, same hierarchy
- Universal pattern

# Training Dynamics: Watching Networks Learn

## Real-Time Monitoring: The Training Dashboard



### Key Metrics to Track:

- **Loss Curves:** Training vs validation
- **Accuracy:** How often we're right
- **Learning Rate:** Speed of updates
- **Gradient Norm:** Update magnitude

### Warning Signs:

- Gap = Overfitting
- Flat = Learning stopped
- Spikes = Instability
- NaN = Numerical issues

### Healthy Training:

- Smooth decrease
- Val follows train
- Gradients stable
- LR decays properly

### When to Stop:

- Validation plateaus
- Gap increasing
- Diminishing returns

## 2014-Present: Networks That Changed the World

### The Depth Revolution:

- 2014 - VGGNet: 19 layers
- 2015 - ResNet: 152 layers
- 2017 - Transformers: Attention
- 2020 - GPT-3: 175B parameters

### Why Depth Matters:

- Each layer = abstraction level
- Deep = complex reasoning
- Hierarchical feature learning

### Real-World Impact:

- **Vision:** Self-driving cars
- **Language:** Google Translate
- **Speech:** Siri, Alexa
- **Medicine:** Disease diagnosis
- **Science:** Protein folding

### The Scale:

- Billions of parameters
- Trained on internet-scale data
- Months of GPU time
- Emergent abilities appear

We went from recognizing digits to passing the bar exam in 25 years

## Problem: Networks Couldn't Get Deeper

### The Vanishing Gradient:


- Gradients multiply through layers
- Become exponentially small
- Deep layers stop learning
- 20 layers was the limit

### The Breakthrough: Skip Connections

- Add input directly to output
- $F(x) + x$  instead of just  $F(x)$
- Gradients flow directly backward
- Can train 1000+ layers!

This simple trick enabled the deep learning revolution

ResNet Innovation: Solving the Vanishing Gradient



### Why It Works:

- Learn residual (difference) only
- Identity mapping is easy default
- Gradients have direct path
- Each layer refines previous result

## The Internal Covariate Shift Problem

### BatchNorm Algorithm:

$$\mu_B = \frac{1}{m} \sum_{i=1}^m x_i$$

$$\sigma_B^2 = \frac{1}{m} \sum_{i=1}^m (x_i - \mu_B)^2$$

$$\hat{x}_i = \frac{x_i - \mu_B}{\sqrt{\sigma_B^2 + \epsilon}}$$

$$y_i = \gamma \hat{x}_i + \beta$$

### The Issue:

- Each layer's input distribution changes
- As previous layers update
- Makes learning unstable
- Requires tiny learning rates

### The Solution:

- Normalize inputs to each layer
- Mean = 0, Variance = 1
- Learn scale and shift parameters
- Apply during training and testing

*In plain words: 1) Find average, 2) Find spread, 3) Normalize to standard range, 4) Scale and shift as needed*

### Benefits:

- 10x faster training
- Higher learning rates OK
- Less sensitive to initialization

## Most Network Weights Don't Matter!

### The Discovery:

- Networks contain "winning tickets"
- Subnetworks that train well alone
- 90-95% of weights can be removed
- Performance stays the same!

**The Hypothesis:** "Dense networks succeed because they contain sparse subnetworks that are capable of training effectively"

### Implications:

- We massively overparameterize
- Training finds the needle in haystack
- Future: Train small from start?
- Mobile deployment possible

### Why It Matters:

- Explains why big networks train better
- Pruning after training works
- Efficiency revolution starting
- Changes how we think about learning

A 1 billion parameter model might only need 50 million

## The Right Architecture for the Right Problem

### What Are Inductive Biases?

- Assumptions built into architecture
- Guide learning toward solutions
- Trade flexibility for efficiency
- "Priors" about the problem

### Examples:

- **CNN:** Spatial locality matters
- **RNN:** Order/time matters
- **GNN:** Graph structure matters
- **Transformer:** All positions can interact

### Why They Matter:

- Reduce search space
- Faster convergence
- Better generalization
- Less data needed

### The Tradeoff:

- Right bias = 10x better
- Wrong bias = 10x worse
- General architectures = safe but slow
- Specialized = fast but limited

Choosing the right inductive bias is still an art



## Capabilities That Appear Suddenly with Scale

### The Phenomenon:

- Small models: Can't do task at all
- Medium models: Still can't
- Large models: Suddenly can!
- No gradual improvement

### Examples:

- 3-digit arithmetic ( $\sim 10$ B params)
- Chain-of-thought reasoning ( $\sim 50$ B)
- Code generation ( $\sim 20$ B)
- Multilingual translation ( $\sim 100$ B)

### Why It Happens:

- Complex patterns need capacity
- Phase transitions in learning
- Composition of simpler abilities
- "Grokking" - sudden understanding

### Implications:


- We can't predict what's next
- Scaling might unlock AGI
- Or hit fundamental limits
- Active area of research

GPT-3 showed abilities nobody expected or programmed


# Architecture Choices: Deep vs Wide Networks

## The Fundamental Tradeoff in Neural Architecture

Depth vs Width: Why Deep Networks Win



Architecture Comparison



### Deep Networks (Many Layers):

- Complex hierarchical features
- Exponential expressiveness growth
- Harder to train (vanishing gradients)
- Better for vision, NLP

### Wide Networks (Many Neurons):

### The Sweet Spot:

- Vision: Deep (100+ layers)
- Language: Very deep (24-96 layers)
- Tabular: Wide and shallow (2-4 layers)
- Time series: Moderate (5-10 layers)

### Modern Insights:

- Depth beats width for same parameters
- Skip connections enable extreme depth
- Width helps with memorization
- Depth helps with generalization



### Scaling Laws:

- Performance  $\propto$  depth<sup>0.8</sup>

# Scaling Laws: How Performance Grows with Data

## The Predictable Relationship Between Data, Model Size, and Performance

Data Scaling Laws (Chinchilla, 2022)



### The Chinchilla Law (2022):

- Optimal ratio: 20 tokens per parameter
- 10B model needs 200B tokens
- Most models are undertrained
- Data quality matters more than quantity

### Power Law Scaling:

NLP Course 2025

### Practical Implications:

- 10x data  $\rightarrow$  2x performance
- 10x parameters  $\rightarrow$  1.7x performance
- 10x compute  $\rightarrow$  3x performance
- Diminishing returns always

### Data Efficiency Tricks:

- Data augmentation
- Synthetic data generation
- Active learning
- Curriculum learning
- Multi-task training


**Why it matters:** These laws predict costs before training

Teaching Machines to See Patterns

# Optimization Algorithms: How Networks Learn

## The Evolution of Gradient Descent

Modern Optimizers: From SGD to Adam



### SGD (1951):

- Basic gradient descent
- Learning rate: Fixed

### Adam (2014):

- Adaptive learning rates per parameter
- Combines momentum + RMSprop
- De facto standard
- Works out-of-the-box

### Modern Variants:

- **AdamW:** Decoupled weight decay
- **RAdam:** Rectified Adam
- **LAMB:** Large batch training
- **Sophia:** 2nd-order approximation


### Choosing an Optimizer:

- Start with Adam ( $\alpha=3e-4$ )

# Quick Guide: Choosing Your Architecture

## Which Network Should You Use?

### Architecture Selection Guide



\* Transformer is now often best for all sequential data

### Decision Questions:

- 1 Is your data sequential?
- 2 Does position matter?
- 3 Is it images/spatial?
- 4 Fixed or variable size?

### Quick Rules:

- Images → CNN
- Text → Transformer/RNN
- Tabular → Feedforward
- Audio → CNN or RNN
- Video → CNN + RNN

**Common Confusion:** Transformers now dominate most tasks, but specialized architectures still win for specific problems!

# Neural Network Architectures: Right Tool for Right Job

## Feedforward Networks:

- Information flows forward only
- Fixed-size input and output
- Good for: Classification, regression

## Convolutional (CNN):

- Spatial feature detection
- Translation invariance
- Good for: Images, video

## Recurrent (RNN):

- Process sequences
- Maintain memory/state
- Good for: Text, time-series

## Transformer:

- Attention mechanism
- Parallel processing
- Good for: Language, everything else

Each architecture encodes different assumptions about the data

# Modern Training: Standing on Shoulders of Giants

## Transfer Learning:

- Start with pre-trained network
- Fine-tune on your task
- 100x less data needed
- Days → Hours training

## Data Augmentation:

- Create variations of training data
- Rotations, crops, color shifts
- Prevents overfitting
- Free performance boost

## Advanced Optimizers:

- **SGD:** Basic gradient descent
- **Momentum:** Remember past gradients
- **Adam:** Adaptive learning rates
- **AdamW:** With weight decay

## Mixed Precision:

- Use 16-bit floats where possible
- Keep 32-bit for critical ops
- 2-3x speedup
- Same accuracy

These techniques make deep learning practical for everyone

# Common Mental Models That Are WRONG

## Misconceptions That Will Confuse You

### WRONG: "Neurons are like brain neurons"

- **Brain neurons:** Complex, chemical, adaptive
- **Artificial neurons:** Simple math functions
- Just multiply and add!
- No biology involved

### WRONG: "Networks understand concepts"

- **What you think:** "It knows what a cat is"
- **Reality:** It found statistical patterns
- No understanding, just correlation
- Can be fooled by tiny changes

### WRONG: "More layers = always better"

- **Too deep:** Vanishing gradients
- **Too deep:** Overfitting
- **Right depth:** Depends on problem complexity
- Simple problems need shallow networks

### WRONG: "It learns like humans"

- **Humans:** Learn from few examples
- **Humans:** Transfer knowledge easily
- **Networks:** Need thousands of examples
- **Networks:** Struggle with new situations

**Remember:** Neural networks are just fancy pattern matchers.  
They don't think, understand, or reason - they find correlations in data.



# Why Deep Learning Exploded Now: The Perfect Storm

## 1. Data Explosion:

- Internet = infinite training data
- ImageNet: 14M labeled images
- Common Crawl: 300TB of text
- YouTube: 500 hours/minute

## 2. Hardware Revolution:

- GPUs: 100x faster than CPUs
- TPUs: Built for neural nets
- Cloud computing: Rent supercomputers
- Mobile chips with NPUs

## 3. Algorithm Breakthroughs:

- ReLU activation (2011)
- Batch normalization (2015)
- Skip connections (2015)
- Attention mechanism (2017)

## 4. Open Source Culture:


- TensorFlow, PyTorch free
- Pre-trained models shared
- Papers with code
- Collaborative research

The same ideas from 1980s finally had the resources to work

## The Exponential Growth of Neural Networks

### Parameter Growth:

- 1957 Perceptron: 20 weights
- 1987 NetTalk: 18,000
- 1998 LeNet: 60,000
- 2012 AlexNet: 60 million
- 2018 BERT: 340 million
- 2020 GPT-3: 175 billion
- 2023 GPT-4: 1.8 trillion



### What Scale Brings:

- Emergent abilities
- Zero-shot learning
- Multi-task capability

## Building a Digit Classifier in 10 Lines

### PyTorch Implementation:

```
import torch
import torch.nn as nn

class SimpleNet(nn.Module):
    def __init__(self):
        super().__init__()
        self.fc1 = nn.Linear(784, 128)
        self.fc2 = nn.Linear(128, 10)

    def forward(self, x):
        x = torch.relu(self.fc1(x))
        return self.fc2(x)

# Train
model = SimpleNet()
optimizer = torch.optim.Adam(model.parameters())
criterion = nn.CrossEntropyLoss()
```

This simple network achieves 97% accuracy on MNIST

### What This Does:

- Input: 28×28 pixel image
- Hidden: 128 neurons
- Output: 10 digit classes
- Activation: ReLU
- Training: Adam optimizer

### Training Loop:

- Forward pass
- Calculate loss
- Backward pass
- Update weights
- Repeat

## When Things Go Wrong (They Always Do)

### Gradient Issues:

- **Exploding:** Gradients  $\rightarrow$  infinity
  - Solution: Gradient clipping
- **Vanishing:** Gradients  $\rightarrow$  0
  - Solution: Better initialization, ReLU
- **Dead ReLU:** Neurons never activate
  - Solution: LeakyReLU, smaller learning rate

### Debugging Tools:

- TensorBoard: Visualize training
- Gradient histograms
- Activation distributions
- Weight evolution plots

### Common Failure Modes:

- Loss not decreasing: Learning rate
- Loss NaN: Numerical instability
- Oscillating loss: LR too high
- Plateau: Local minimum or LR too small

### Sanity Checks:

- 1 Overfit single batch first
- 2 Check gradient flow
- 3 Visualize first layer filters
- 4 Plot loss curves
- 5 Test on toy problem

"If it's not working, it's always the learning rate" - Andrej Karpathy

# Your Debugging Checklist: When Things Go Wrong

## Systematic Debugging Saves Hours

**Try It Yourself:** Save this checklist - you'll need it for every project!

### Step 1: Sanity Checks

- ☐ Can you overfit a single batch?
- ☐ Are inputs normalized?
- ☐ Is output layer correct?
- ☐ Loss function matches task?

### Step 2: Data Checks

- ☐ Plot sample inputs
- ☐ Check label distribution
- ☐ Verify train/val split
- ☐ Look for data leakage

### Step 3: Training Checks

- ☐ Plot loss curves
- ☐ Check gradient norms
- ☐ Monitor weight updates
- ☐ Try different learning rates

### Step 4: Architecture

- ☐ Start with known working model
- ☐ Add complexity gradually
- ☐ Check activation distributions
- ☐ Verify dimensions match

**Common Confusion:** 90% of bugs are in data preprocessing, not the model!

Print this slide and keep it handy

# Common Pitfalls: Learn from Others' Mistakes

## Data Problems:

- Not enough data
- Unbalanced classes
- Data leakage
- No validation set

## Architecture Issues:

- Too deep without skip connections
- Wrong activation functions
- Incorrect output layer
- Bad initialization

## Training Mistakes:

- Learning rate too high/low
- No normalization
- Overfitting ignored
- Wrong loss function

## Debugging Tips:

- Start simple, add complexity
- Overfit single batch first
- Monitor gradients
- Visualize predictions

"It's not working" usually means one of these issues

# The Future: What's Next?

## Current Frontiers:

- Multimodal models (text+image+audio)
- Efficient models for phones
- Neuromorphic hardware
- Quantum neural networks

## Unsolved Problems:

- True reasoning ability
- Learning from few examples
- Explaining decisions
- Energy efficiency

## Next Breakthroughs?

- Models that update continuously
- Networks that program themselves
- Biological-digital hybrids
- AGI (Artificial General Intelligence)?

## Your Role:

- This field is 70 years young
- Major breakthroughs every 2-3 years
- Anyone can contribute
- The best is yet to come

"We're still in the steam engine era of AI" - Geoffrey Hinton

# Final Check: Can You Explain These to a Friend?

## Test Your Understanding

### Core Concepts:

- ❶ Why do we need activation functions?
- ❷ What's backpropagation in one sentence?
- ❸ Why did deep learning explode after 2012?
- ❹ What's the vanishing gradient problem?
- ❺ Why do CNNs work for images?

**Try It Yourself:** Write one-sentence answers for each. Compare with a classmate!

### Key Answers:

- Without them, stacked layers = still linear
- Distributing error backwards through network
- GPUs + Big Data + ReLU converged
- Gradients shrink through many layers
- They detect features regardless of position

### If You're Stuck:

- Review activation functions slide
- Re-read backprop section
- Check AlexNet breakthrough
- Look at gradient flow diagram
- Study convolution hierarchy

Understanding these concepts prepares you for everything that follows



## The Journey So Far

### Core Concepts:

- ① **Neurons:**  $y = f(\sum w_i x_i + b)$
- ② **Learning:** Adjust weights to minimize error
- ③ **Depth:** Each layer adds abstraction
- ④ **Backpropagation:** Distribute error backwards
- ⑤ **Non-linearity:** Enables complex functions

### Historical Lessons:

- ① Every limitation spawned innovation
- ② Simple ideas + scale = revolution
- ③ Biology inspires but doesn't limit
- ④ Persistence pays (40-year problem!)
- ⑤ We're just getting started

**Remember: Neural networks are just functions that learn from examples**

Next: RNNs - Teaching networks to remember

## Stop Watching, Start Building!

### Step 1: Open Google Colab (Free!)

- Go to: [colab.research.google.com](https://colab.research.google.com)
- Click "New Notebook"
- Copy this code:

```
# Your first neural network!
import tensorflow as tf
from tensorflow import keras

# 1. Create network (like building LEGO)
model = keras.Sequential([
    keras.layers.Dense(4, activation='relu',
                        input_shape=[2]),
    keras.layers.Dense(1)
])

# 2. Prepare for learning
model.compile(optimizer='adam',
              loss='mse')

# 3. Training data (XOR problem!)
X = [[0,0], [0,1], [1,0], [1,1]]
y = [0, 1, 1, 0]

# 4. Train it!
model.fit(X, y, epochs=500, verbose=0)

# 5. Test it!
```

### Step 2: Run and Watch!

- Press Shift+Enter to run
- Watch it learn XOR
- It works! You did it!

### Step 3: Experiment

**Try It Yourself:** Change these and see what happens:

- Change 4 neurons to 8
- Change 'relu' to 'sigmoid'
- Change epochs to 1000
- Add another Dense layer!

### Three More Experiments:

- 1 Try OR instead of XOR

## Continue Your Journey

### Immediate Next Steps (This Week):

- ❶ **Fast.ai Practical Deep Learning**
  - Free course, no math required
  - Build real projects immediately
  - `course.fast.ai`
- ❷ **Google's ML Crash Course**
  - Interactive, with exercises
  - `developers.google.com/ml`
- ❸ **3Blue1Brown Neural Network Series**
  - Beautiful visualizations
  - YouTube: "But what is a neural network?"

### Books to Read (In Order):

- ❶ "Grokking Deep Learning" - Trask
  - Build everything from scratch
  - No libraries, just NumPy
- ❷ "Deep Learning" - Goodfellow et al.
  - The definitive textbook
  - Free online: `deeplearningbook.org`

### Projects to Try:

- MNIST digit recognition (classic!)
- Classify your own photos
- Build a simple chatbot
- Predict stock prices (it won't work!)

**Remember:** Everyone started knowing nothing.  
The difference between you and an expert? They started earlier.  
Your journey begins NOW!