Machine Learning for Spectral Analysis

UNIVERSITY OF LIVERPOOL

Liangqing Luo | Supervisor: **Xin Tu** | Assessor: **Xue Yong**

Department of Electrical and Electronic Engineering

1. Introduction

Plasma etching is a critical step in semiconductor fabrication, an industry worth **>$500 billion** globally. As chip nodes shrink to 3 nm and below, even minor process drift can cause **billions in yield loss** per year. **Optical Emission Spectroscopy (OES)** offers **non-invasive, real-time** monitoring by capturing photons from excited plasma species — the only diagnostic that does not disturb the process.

Why It Matters: Current OES analysis relies on **manual expert interpretation** of thousands of spectral channels — slow, subjective, and unable to scale to modern fab throughput (>1,000 wafers/day). Machine learning can automate species identification, temperature estimation, and fault detection in **milliseconds**, enabling closed-loop process control that improves yield, reduces material waste, and lowers the environmental footprint of chip manufacturing.

Project Aims

1. **Species Detection** — Identify 13 plasma species via NMF + NIST matching
2. **Temperature Regression** — Predict T_rot and T_vib from N2 OES spectra (ANN)
3. **Temporal Forecasting** — Forecast plasma phase transitions (Attention-LSTM)
4. **Intensity & Spatial** — Actinometry, line ratios, wafer uniformity mapping

OES Datasets

Dataset	Spectra	Channels	Task
Mesbah CAP	402	51	Temperature
BOSCH RIE	15,000	3,648	Species + temporal + intensity + spatial

Table 1: OES spectral datasets

2. Methodology



Fig. 1: End-to-end ML pipeline for OES analysis

Preprocessing

- **ALS Baseline** — Asymmetric least-squares removes fluorescence background (lambda=4.2e5)
- **Savitzky-Golay** — Noise suppression preserving peak shapes (w=13, poly=4)
- **SNV + Cosmic Ray Removal** — Path-length correction and 5-sigma spike detection

NIST Emission Line Database

Physics-informed feature extraction using **13 plasma species** and **39 verified NIST emission lines** (200-900 nm). Each species has a calibrated spectral window for robust peak matching independent of spectrometer resolution.

Species	Lines (nm)	Role
Ar I	696.5, 706.7, 763.5	Noble gas carrier
F I	685.6, 690.2, 739.9	SF6 etchant radical
N2 2pos	315.9, 337.1, 357.7	Atmospheric plasma
H_alpha	656.3	Hydrogen Balmer
O I	777.4, 844.6	Oxygen indicator
C2 Swan	473.7, 516.5, 563.6	Carbon indicator

Table 2: Key NIST species (6 of 13 shown)

3. Species Detection



Fig. 2: OES spectrum with NIST emission lines

NMF decomposition extracts 8 spectral basis components, matched to known plasma species via NIST line positions. 4-model voting classifies 15,000 BOSCH RIE spectra.



Fig. 3: Detection rates for all 13 plasma species (NMF + NIST, BOSCH

Key Finding: Noble gas carriers (Ar I: 69.8%) and etchant radicals (F I: 68.4%) show highest detection, consistent with SF6 RIE chemistry.

Classification Models

Model	Accuracy	F1 macro
SVM (RBF)	94.2%	0.843
Random Forest	94.2%	0.843
1D-CNN	93.2%	0.822
Spectral Transformer	92.5%	0.802

Table 3: 4-model comparison on BOSCH species data

4. Results

PASS	PASS	PASS	Attn-LSTM
94.2% Species Acc.	20 K T_rot RMSE	102 K T_vib RMSE	74.4% Phase Pred.



Fig. 4: Plasma temperature RMSE — both targets beat thresholds



Fig. 5: Actinometry (Ar I ref.) and wafer uniformity (RBF)



Fig. 6: Temporal phase prediction and model comparison

5. Discussion



Fig. 7: SHAP attribution — top features align with NIST emission lines

Key Findings: (1) SHAP peaks match NIST lines (**+/-5 nm**), confirming ML models learn genuine plasma physics. (2) Intensity regression R^2 = -1.50 reveals nonlinear OES-to-process relationships. (3) Attention-LSTM achieves 74.4% phase prediction, outperforming DTW K-means (61.2%) and vanilla LSTM (70.8%).

Technical Innovations

- **NMF + NIST Matching** — Unsupervised extraction of 8 basis components matched to 13 plasma species
- **GroupKFold CV** — Prevents same-target data leakage for honest hyperparameter selection
- **Attention-LSTM** — Temporal self-attention over PCA(20) embeddings for phase transition detection
- **Optuna 2-Stage HPO** — Joint preprocessing + model hyperparameters optimised (50+ trials)
- **MC-Dropout Uncertainty** — Calibrated confidence intervals via 50-sample Monte Carlo dropout

6. Conclusions

Performance Targets

Metric	Target	Achieved	Status
Species Accuracy	>90%	94.2%	PASS
F1 macro	>0.80	0.843	PASS
T_rot RMSE	<=50 K	20 K	PASS
T_vib RMSE	<=200 K	102 K	PASS
Phase Pred.	>70%	74.4%	PASS
Unit Tests	All pass	46/46	PASS

Table 4: All OES performance targets met

Key Achievements

✓ **6 analytical tasks** — species detection, temperature regression, temporal forecasting, intensity analysis, actinometry, spatial uniformity

✓ **13 plasma species** identified via NMF + NIST matching

✓ **SHAP interpretability** validates physics-based learning

✓ **Boltzmann + actinometry** for quantitative plasma diagnostics

✓ **Reproducible CLI** with 46 automated tests

Further Work

- Transfer learning across spectrometer configurations
- Real-time deployment for industrial process control
- Spatiotemporal wafer uniformity mapping

References

[1] Kramida et al., NIST Atomic Spectra Database, v5.11, 2023
[2] Park & Mesbah, J. Phys. D, 55, 2022
[3] BOSCH Research, Plasma Etching OES, Zenodo, 2024
[4] Lundberg & Lee, SHAP, NeurIPS, 2017
[5] Phelps & Petrovic, J. Appl. Phys., 76, 1994

Tools

Python | scikit-learn | PyTorch | Optuna
SHAP | NumPy | pandas | ReportLab