

Neovim Complete Field Guide

A practical, searchable map of the Vim language and the mappings declared in this checkout. Every custom row below is rebuilt from the current Lua configuration—new or changed keys replace the old documentation.

1 Find

Space f f opens files; Space f g searches project text.

2 Move

w / b move by word; / then n searches; gg / G jump in a file.

3 Change

Use operator + object: ciw changes a word, daw deletes a word.

4 Check

Space l f formats an LSP buffer; :w saves; Space l g opens LazyGit.

How to read this: Space f f means press Space, then f, then f. Context labels identify keys that only appear in Markdown, NvimTree, dashboard, or LSP-attached buffers.

Runtime cross-check: global 160, Markdown buffer 37, NvimTree buffer 74; LSP clients attached 0: 271 described runtime mappings observed. The source inventory is the published command truth; runtime data is used as a cross-check.

Move precisely, then act

Character, line & screen

h j k l	Left, down, up, right.
0 ^ \$	Line start / first nonblank / line end.
H M L	Top / middle / bottom visible screen line.
Ctrl-u Ctrl-d	Half-page up / down.
zt zz zb	Place cursor line at top / center / bottom.

Words, paragraphs & file

w b e	Next word start / previous word start / word end.
W B E	Same by whitespace-separated WORD.
{ }	Previous / next paragraph.
gg G	First / last line of the file.
:42 42G	Go to line 42.
%	Jump between matching delimiters.
Ctrl-o Ctrl-i	Older / newer jump location.

Find on one line

f x F x	Find character x forward / backward; land on it.
t x T x	Move until just before x, forward / backward.
; ,	Repeat the latest find in the same / opposite direction.
* #	Search word under cursor forward / backward.

Counts repeat the next command: 3w moves three words; 5dd deletes five lines; d2j deletes the current plus next two lines; 2ci(changes inside the next two parenthesized areas.

Your current configuration

Key	Action	Context
<F2>	Toggle line numbers	Global
<F3>	Toggle relative line numbers	Global
Space ?	Buffer Local Keymaps (which-key)	Global
Space nh	Clear search highlights	Global

Edit with operators, text objects & registers

Operators: the verbs

d	Delete (also copies to a register).
c	Change: delete, then enter Insert mode.
y	Yank: copy to a register.
> <	Indent right / left; add = to auto-indent.
a~ gu	Toggle case / lower / upper.
=	Auto-format indentation using filetype rules.

Text objects: the nouns

iw aw	Inner word / word including surrounding space.
i" a"	Inside quotes / quotes plus contents.
i(i[i{	Inside parentheses / brackets / braces.
a(a[a{	Object including delimiters.
ip ap	Inner paragraph / paragraph plus blank space.

Insert, paste & repeat

i I a A	Insert at cursor / first text; append / line end.
o O	Open a line below / above and insert.
p P	Paste after / before cursor or line.
u Ctrl-r	Undo / redo.
.	Repeat the last change.

Read keys as a sentence: dw deletes to the next word; ci" changes inside quotes; ya(copies parentheses and contents. Fast line forms: dd, cc, yy, >>.

Your current configuration

Key	Action	Context
Space ua	Toggle autopairs	Global
Space ui	Toggle indent guides	Global
Space us	Toggle indent scope	Global

Search, replace, save & get unstuck

Search within this file

<code>/text</code> <code>Enter</code> <code>?text</code> <code>Enter</code>	Search forward / backward.
<code>n</code> <code>N</code>	Next / previous match.
<code>:noh</code>	Clear highlighting, not the search pattern.
<code>/\cword</code> <code>/\Cword</code>	Force case-insensitive / case-sensitive search.
<code>/\Vliteral</code>	Search punctuation literally.
<code>q/</code>	Open editable search history.

Substitute

<code>:s/old/new/</code>	Replace first match on this line.
<code>:s/old/new/g</code>	Replace every match on this line.
<code>:%s/old/new/gc</code>	Whole file: replace all and confirm each.
<code>:'<,'>s/old/new/g</code>	Replace only the current visual selection.
<code>&</code> <code>:%&</code>	Repeat the latest substitute on this line / whole file.

Help & recovery

<code>:help {topic}</code>	Open built-in documentation.
<code>:map</code> <code>:nmap</code> <code>:imap</code>	Inspect mappings by mode.
<code>:checkhealth</code>	Diagnose Neovim, providers, and plugins.
<code>:messages</code>	Show recent notifications and errors.
<code>:w</code> <code>:q</code> <code>:wq</code> <code>:q!</code>	Save / quit / save+quit / force quit.

Your setup uses ignorecase + smartcase: lowercase searches ignore case; adding any capital makes the search case-sensitive.

Your current configuration

Key	Action	Context
<code>[t</code>	Previous todo comment	Global
<code>]t</code>	Next todo comment	Global
<code>Space f/</code>	Find in buffer	Global
<code>Space fb</code>	Find buffers	Global
<code>Space fd</code>	Find diagnostics	Global
<code>Space ff</code>	Find files	Global

Buffers, windows, tabs & lists

Buffers

:ls	:buffers	List open buffers.
:b name		Switch by partial buffer name.
:bnext	:bprev	Next / previous buffer.
:bdelete		Close buffer without necessarily closing its window.

Windows

:split	:vsplit	Horizontal / vertical split.
Ctrl-w h/j/k/l		Move focus between splits.
Ctrl-w c		Close current / keep only current window.
Ctrl-w o		
Ctrl-w =		Equalize split sizes.

Tabs, folds & lists

:tabnew	gt	New tab page / next / previous tab.	
gT			
za	zR	zM	Toggle fold / open all / close all.
:copen	:cnext	Open quickfix / next project-wide result.	
:lopen		Open location list for this window.	

Use Space f f for file names, Space f g for project text, / for the current file, and Space f / for fuzzy filtering inside the current buffer.

Your current configuration

Key	Action	Context
Shift-h	Previous buffer	Global
Shift-l	Next buffer	Global
Space bd	Close buffer	Global
Space bp	Pick buffer	Global
Space wr	Find session	Global
Space ws	Save session	Global

Git, diagnostics, LSP & completion

Choose the right Git tool

Space h ...	Act on one changed hunk: stage, reset, preview, blame, diff.
Space g ...	Find Git information through Telescope.
Space l g	Open the full LazyGit workflow.

Diagnostics & language features

[d]]d	Previous / next diagnostic; read its message.
Space l d	Show the full diagnostic at the cursor.
Space l f	Format the current LSP buffer; Markdown can use Prettier.
Space l i	Toggle inlay hints when the server supports them.

Completion & snippets

Tab Shift-Tab	Jump forward / backward through an active snippet; otherwise type a tab.
Ctrl-n Ctrl-p	Next / previous built-in completion candidate.
Ctrl-v Ctrl-e	Accept / cancel a built-in completion candidate.
Ctrl-x Ctrl-o	Request omnifunc completion where supported.

Diagnostic means an editor-reported error, warning, or hint. LSP is the language-aware engine that supplies diagnostics, formatting, completion, navigation, and more.

Your current configuration

Key	Action	Context
[h]	Previous hunk	Global
]h	Next hunk	Global
ih	Select hunk	Global
ih	Select hunk	Global
Space hB	Toggle line blame	Global
Space hb	Blame line	Global

Markdown, TODOs & writing tools

Markdown workflow

Preview	Rendered, hybrid, or split preview helps read while editing.
Links	Follow the current link or move through nearby links.
Tables & tasks	Format a table or toggle a task checkbox.
Writing hygiene	Project spell words, format-on-save, table mode, and linting are configured per project.

TODO discovery

TODO FIXME HACK	Use clear comment markers so they are searchable.
Quickfix location list	Send discovered TODOs to a navigable list.
Autopairs	Matching delimiters are configurable and intentionally disabled in picker/commit contexts.

Markdown buffers automatically enable US English spell checking, soft wrapping, line breaks, and break indentation in this setup.

Your current configuration

Key	Action	Context
Space ma	Toggle format on save	Global
Space mc	Toggle task	Global
Space mc	Toggle task	Global
Space md	Lint Markdown	Global
Space mF	Unfold section	Global
Space mf	Fold section	Global

Registers, visual mode & block edits

Registers: where copied text lives

"0	Latest yank; "0p pastes the last copied text.
"+	System clipboard in this setup.
"a	Named register: "ayy stores a line; "ap pastes it.
"_	Black-hole register: delete without replacing the clipboard.
:reg	Inspect copied text and registers.

Visual mode

v V	Select characters / whole lines, then use an operator.
Ctrl-v	Select a rectangle; I inserts on every selected line after Esc.
gv	Reselect the previous visual selection.
~	Swap selected text's case.
J gJ	Join lines with / without adding a space.

Your configuration uses unnamedplus, so ordinary yank, delete, and paste already share the system clipboard.

Your current configuration

Key	Action	Context
Space ua	Toggle autopairs	Global
Space ui	Toggle indent guides	Global
Space us	Toggle indent scope	Global

Sessions

Find session	Restore a saved workspace.
Save session	Persist the current layout and buffers.
What is saved	Buffers, layout, current directory, terminals, folds, tab pages, and local options.

Dashboard

New file	Start an empty editing buffer.
File recent text projects	Start common Telescope workflows from the dashboard.
Explorer LazyGit sessions	Open a workspace tool before entering an editing buffer.
Plugin manager quit	Maintain plugins or exit Neovim.

Personal display

F2 F3	Toggle absolute / relative line numbers.
Clear highlighting	Remove the visual highlight of the last search.
Indent guides	Toggle indentation and its scope highlight.
Autopairs	Toggle automatic bracket and quote pairing.

Dashboard shortcuts are intentionally context-labeled in the generated appendix: use them from the Alpha start screen, not from an editing buffer.

Your current configuration

Key	Action	Context
e	Start a new empty file	Dashboard buffer
ff	Find files	Dashboard buffer
fk	Find keymaps	Dashboard buffer
fp	Switch projects	Dashboard buffer
fr	Open recent files	Dashboard buffer
fs	Search project text	Dashboard buffer

Testing, debugging & code navigation

Testing loop

Run nearest test	Start with the test closest to the cursor.
Run file suite	Widen scope after the nearest test is useful.
Test output	Open output when a result needs diagnosis.
Toggle summary	Keep test state visible while editing.

Debugging loop

Toggle breakpoint	Mark the next place execution should pause.
Continue	Run to the next breakpoint.
Step over into	Move through execution without losing the current state.
Inspect UI	Open debugger panels for variables, stack, and console.

Code navigation

Definition references	Jump to where a symbol is defined or used.
Rename	Apply a language-aware rename through the LSP.
Code action	See available fixes and refactors.
Diagnostics	Move through editor-reported problems before changing code.

The complete appendix has the exact current keys. This page teaches the workflow first so it remains useful even when those keys evolve.

Your current configuration

Key	Action	Context
Space tA	Fallback: run test suite	Global
Space ta	Run test suite	Global
Space td	Debug nearest test	Global
Space tf	Run current file	Global
Space tn	Run nearest test	Global
Space to	Show test output	Global

Ctrl+F index

Search this PDF for an exact key string or an ordinary word. The guide repeats literal keys in the teaching sections and keeps a complete generated appendix after them.

Files & project navigation

find files, project text, recent files, buffers, help, keymaps, explorer

Editing

change, delete, copy, paste, repeat, register, text object, visual block

Code help

diagnostic, format, completion, inlay hint, LSP, snippet

Git

hunk, stage, reset, blame, diff, branch, commit, LazyGit

Writing

Markdown, link, preview, table, spell, TODO, lint

Discover anything else: Space f k opens searchable active keymaps. `:help` keyword explains built-ins; `:map`, `:nmap`, and `:imap` inspect mappings directly; `:checkhealth` diagnoses the setup.

Configured Tooling

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	Status	Configuration source
DAP adapter: codelldb	Configured integration	dap.lua
DAP adapter: debugpy	Configured integration	dap.lua
DAP adapter: delve	Configured integration	dap.lua
DAP adapter: netcoredbg	Configured integration	dap.lua
Executable: codelldb	Configured integration	dap.lua
Executable: dlv	Configured integration	dap.lua
Executable: nvr	Configured integration	set.lua
Executable: python	Configured integration	dap.lua
Executable: python3	Configured integration	dap.lua
Executable: uv	Configured integration	neotest.lua
Formatter: prettier	Configured integration	markdown.lua
Linter: markdownlint-cli2	Configured integration	markdown.lua
LSP server: basedpyright	Configured integration	lsp.lua
LSP server: jsonls	Configured integration	lsp.lua
LSP server: lua_ls	Configured integration	lsp.lua

Configured Tooling - part 2 of 5

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	Status	Configuration source
LSP server: roslyn_ls	Configured integration	lsp.lua
LSP server: yamlls	Configured integration	lsp.lua
Plugin: 3rd/image.nvim	Configured integration	image.lua
Plugin: akinsho/bufferline.nvim	Configured integration	bufferlines.lua
Plugin: akinsho/neotest-go	Configured integration	neotest.lua
Plugin: antoinemadec/FixCursorHold.nvim	Configured integration	neotest.lua
Plugin: b0o/SchemaStore.nvim	Configured integration	lsp.lua
Plugin: CollinRobison/neotest-dotnet	Configured integration	neotest.lua
Plugin: folke/todo-comments.nvim	Configured integration	todo-comments.lua
Plugin: folke/tokyonight.nvim	Configured integration	tokyonight.lua
Plugin: folke/which-key.nvim	Configured integration	which-key.lua
Plugin: goolord/alpha-nvim	Configured integration	alpha.lua
Plugin: haydenmeade/neotest-jest	Configured integration	neotest.lua
Plugin: jakewvincent/mkdnflow.nvim	Configured integration	markdown.lua
Plugin: jay-babu/mason-nvim-dap.nvim	Configured integration	mason-tools.lua

Configured Tooling - part 3 of 5

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	Status	Configuration source
Plugin: kdheepak/lazygit.nvim	Configured integration	lazygit.lua
Plugin: lewis6991/gitsigns.nvim	Configured integration	gitsigns.lua
Plugin: lukas-reineke/indent-blankline.nvim	Configured integration	indent-blankline.lua
Plugin: marilari88/neotest-vitest	Configured integration	neotest.lua
Plugin: mason-org/mason-lspconfig.nvim	Configured integration	lsp.lua
Plugin: mason-org/mason-lspconfig.nvim	Configured integration	mason-tools.lua
Plugin: mason-org/mason.nvim	Configured integration	mason-tools.lua
Plugin: mfussenegger/nvim-dap	Configured integration	dap.lua
Plugin: mfussenegger/nvim-lint	Configured integration	markdown.lua
Plugin: neovim/nvim-lspconfig	Configured integration	lsp.lua
Plugin: nvim-lua/plenary.nvim	Configured integration	todo-comments.lua
Plugin: nvim-lua/plenary.nvim	Configured integration	telescope.lua
Plugin: nvim-lua/plenary.nvim	Configured integration	lazygit.lua
Plugin: nvim-lualine/lualine.nvim	Configured integration	lualine.lua
Plugin: nvim-mini/mini.icons	Configured integration	mini-icon.lua

Configured Tooling - part 4 of 5

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	Status	Configuration source
Plugin: nvim-neotest/neotest	Configured integration	neotest.lua
Plugin: nvim-neotest/neotest-python	Configured integration	neotest.lua
Plugin: nvim-neotest/neotest-vim-test	Configured integration	neotest.lua
Plugin: nvim-neotest/nvim-nio	Configured integration	neotest.lua
Plugin: nvim-neotest/nvim-nio	Configured integration	dap.lua
Plugin: nvim-telescope/telescope-fzf-native.nvim	Configured integration	telescope.lua
Plugin: nvim-telescope/telescope-project.nvim	Configured integration	telescope.lua
Plugin: nvim-telescope/telescope.nvim	Configured integration	telescope.lua
Plugin: nvim-tree/nvim-tree.lua	Configured integration	nvimtree.lua
Plugin: nvim-tree/nvim-web-devicons	Configured integration	nvim-web-devicons.lua
Plugin: nvim-tree/nvim-web-devicons	Configured integration	bufferlines.lua
Plugin: nvim-tree/nvim-web-devicons	Configured integration	nvimtree.lua
Plugin: nvim-tree/nvim-web-devicons	Configured integration	lualine.lua
Plugin: nvim-treesitter/nvim-treesitter	Configured integration	nvim-treesitter.lua
Plugin: nvim-treesitter/nvim-treesitter	Configured integration	image.lua

Configured Tooling - part 5 of 5

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	Status	Configuration source
Plugin: orjangj/neotest-ctest	Configured integration	neotest.lua
Plugin: OXY2DEV/markview.nvim	Configured integration	markdown.lua
Plugin: rcarriga/nvim-dap-ui	Configured integration	dap.lua
Plugin: rmagatti/auto-session	Configured integration	auto-session.lua
Plugin: rouge8/neotest-rust	Configured integration	neotest.lua
Plugin: stevearc/conform.nvim	Configured integration	markdown.lua
Plugin: textDocument/codeLens	Configured integration	lsp.lua
Plugin: textDocument/completion	Configured integration	lsp.lua
Plugin: textDocument/inlayHint	Configured integration	lsp.lua
Plugin: theHamsta/nvim-dap-virtual-text	Configured integration	dap.lua
Plugin: vague-theme/vague.nvim	Configured integration	vague.lua
Plugin: vim-test/vim-test	Configured integration	neotest.lua
Plugin: windwp/nvim-autopairs	Configured integration	autopairs.lua
Plugin: windwp/nvim-ts-autotag	Configured integration	nvim-treesitter.lua

Buffers & Windows

Extracted from `bufferlines.lua`.

Mode	Key	Action	Context
Normal	Shift-h	Previous buffer	Global
Normal	Shift-l	Next buffer	Global
Normal	Space bd	Close buffer	Global
Normal	Space bp	Pick buffer	Global

Dashboard

Extracted from `alpha.lua`.

Mode	Key	Action	Context
Normal	<code>e</code>	Start a new empty file	Dashboard buffer
Normal	<code>ff</code>	Find files	Dashboard buffer
Normal	<code>fk</code>	Find keymaps	Dashboard buffer
Normal	<code>fp</code>	Switch projects	Dashboard buffer
Normal	<code>fr</code>	Open recent files	Dashboard buffer
Normal	<code>fs</code>	Search project text	Dashboard buffer
Normal	<code>lg</code>	Open LazyGit	Dashboard buffer
Normal	<code>nt</code>	Toggle file explorer	Dashboard buffer
Normal	<code>p</code>	Open plugin manager	Dashboard buffer
Normal	<code>q</code>	Quit Neovim	Dashboard buffer
Normal	<code>ss</code>	Find and restore a session	Dashboard buffer

Debugging

Extracted from dap.lua.

Mode	Key	Action	Context
Normal	Space dB	Conditional breakpoint	Global
Normal	Space db	Toggle breakpoint	Global
Normal	Space dc	Continue	Global
Normal	Space de	Evaluate expression	Global
Normal	Space di	Step into	Global
Normal	Space d0	Step out	Global
Normal	Space do	Step over	Global
Normal	Space dp	Pause debug session	Global
Normal	Space dq	Terminate debug session	Global
Normal	Space dr	Restart debug session	Global
Normal	Space du	Toggle DAP UI	Global
Normal	Space dv	Toggle DAP virtual text	Global

Find & Navigate

Extracted from telescope.lua, todo-comments.lua.

Mode	Key	Action	Context
Normal	[t]	Previous todo comment	Global
Normal	]t	Next todo comment	Global
Normal	Space f/	Find in buffer	Global
Normal	Space fb	Find buffers	Global
Normal	Space fd	Find diagnostics	Global
Normal	Space ff	Find files	Global
Normal	Space fg	Find text	Global
Normal	Space fh	Find help	Global
Normal	Space fk	Find keymaps	Global
Normal	Space fL	Todo comments to location list	Global

Find & Navigate · part 2 of 2

Extracted from telescope.lua, todo-comments.lua.

Mode	Key	Action	Context
Normal	Space fp	Find project	Global
Normal	Space fR	Resume last picker	Global
Normal	Space fr	Find recent files	Global
Normal	Space fT	Todo comments to quickfix	Global
Normal	Space ft	Find todo comments	Global
Normal	Space fw	Find word under cursor	Global
Normal	Space gb	Git branches	Global
Normal	Space gc	Git commits	Global
Normal	Space gs	Git status	Global

Extracted from gitsigns.lua, lazygit.lua.

Mode	Key	Action	Context
Normal	[h	Previous hunk	Global
Normal	]h	Next hunk	Global
Operator-pending	ih	Select hunk	Global
Visual	ih	Select hunk	Global
Normal	Space hB	Toggle line blame	Global
Normal	Space hb	Blame line	Global
Normal	Space hD	Diff against HEAD	Global
Normal	Space hd	Diff against index	Global
Normal	Space hi	Preview hunk inline	Global
Normal	Space hL	Hunks to location list	Global
Normal	Space hp	Preview hunk	Global
Normal	Space hQ	Repository hunks to quickfix	Global
Normal	Space hq	Hunks to quickfix	Global

Git · part 2 of 2

Extracted from gitsigns.lua, lazygit.lua.

Mode	Key	Action	Context
Normal	Space hR	Reset buffer	Global
Normal	Space hr	Reset hunk	Global
Visual	Space hr	Reset selection	Global
Normal	Space hS	Stage buffer	Global
Normal	Space hs	Stage hunk	Global
Visual	Space hs	Stage selection	Global
Normal	Space hU	Unstage buffer	Global
Normal	Space lG	LazyGit current file	Global
Normal	Space lg	LazyGit dashboard	Global
Normal	Space lL	LazyGit repository log	Global
Normal	Space ll	LazyGit file log	Global
Normal	Space uw	Toggle Git word diff	Global

LSP, Completion & Diagnostics

Extracted from lsp.lua.

Mode	Key	Action	Context
Normal	[d]	Previous diagnostic	Global
Normal	]d	Next diagnostic	Global
Normal	Space ld	Show diagnostic	Global
Insert	Ctrl-Space	Trigger LSP completion	LSP buffer (when attached)
Normal	Space lc	Toggle LSP completion	LSP buffer (when attached)
Normal	Space lf	Format buffer	LSP buffer (when attached)
Normal	Space li	Toggle inlay hints	LSP buffer (when attached)
Normal	Space lr	Refresh C# code lenses	LSP buffer (when attached)
Normal	Space lt	Run C# code lens	LSP buffer (when attached)

Markdown

Extracted from markdown.lua.

Mode	Key	Action	Context
Normal	Space ma	Toggle format on save	Global
Normal	Space mc	Toggle task	Global
Visual	Space mc	Toggle task	Global
Normal	Space md	Lint Markdown	Global
Normal	Space mF	Unfold section	Global
Normal	Space mf	Fold section	Global
Normal	Space mh	Toggle hybrid preview	Global
Normal	Space mL	Follow link	Global
Normal	Space mN	Previous link	Global
Normal	Space mn	Next link	Global

Markdown · part 2 of 2

Extracted from markdown.lua.

Mode	Key	Action	Context
Normal	Space mp	Toggle preview	Global
Normal	Space ms	Toggle preview split	Global
Normal	Space mT	Toggle table mode	Global
Normal	Space mt	Format table	Global
Normal	Space mW	Add all project spelling words	Global
Normal	Space mw	Add project spelling word	Global
Normal	Enter	Mkdnflow smart Enter	Markdown buffer
Insert	Enter	Mkdnflow smart Enter	Markdown buffer
Visual	Enter	Mkdnflow smart Enter	Markdown buffer

NvimTree

Extracted from nvimtree.lua.

Mode	Key	Action	Context
Normal	Space nc	Collapse nvim-tree	Global
Normal	Space ne	Expand nvim-tree	Global
Normal	Space nf	Reveal current file	Global
Normal	Space nn	Focus nvim-tree	Global
Normal	Space nr	Refresh nvim-tree	Global
Normal	Space nt	Toggle nvim-tree	Global

Personal Controls

Extracted from remap.lua, which-key.lua.

Mode	Key	Action	Context
Normal	<F2>	Toggle line numbers	Global
Normal	<F3>	Toggle relative line numbers	Global
Normal	Space ?	Buffer Local Keymaps (which-key)	Global
Normal	Space nh	Clear search highlights	Global

Testing

Extracted from `neotest.lua`.

Mode	Key	Action	Context
Normal	Space tA	Fallback: run test suite	Global
Normal	Space ta	Run test suite	Global
Normal	Space td	Debug nearest test	Global
Normal	Space tf	Run current file	Global
Normal	Space tn	Run nearest test	Global
Normal	Space to	Show test output	Global
Normal	Space ts	Toggle test summary	Global
Normal	Space tV	Fallback: run current file	Global
Normal	Space tv	Fallback: run nearest test	Global
Normal	Space tx	Stop test	Global

UI & Editing

Extracted from autopairs.lua, indent-blankline.lua.

Mode	Key	Action	Context
Normal	Space ua	Toggle autopairs	Global
Normal	Space ui	Toggle indent guides	Global
Normal	Space us	Toggle indent scope	Global

Workspaces & Sessions

Extracted from `auto-session.lua`.

Mode	Key	Action	Context
Normal	<code>Space wr</code>	Find session	Global
Normal	<code>Space ws</code>	Save session	Global