

Neovim Complete Field Guide

A practical, searchable map of the Vim language and the mappings declared in this checkout. Every custom row below is rebuilt from the current Lua configuration—new or changed keys replace the old documentation.

1 Find

Space f f opens files; Space f g searches project text.

2 Move

w / b move by word; / then n searches; gg / G jump in a file.

3 Change

Use operator + object: ciw changes a word, daw deletes a word.

4 Check

Space l f formats an LSP buffer; :w saves; Space l g opens LazyGit.

How to read this: Space f f means press Space, then f, then f. Context labels identify keys that only appear in Markdown, NvimTree, dashboard, or LSP-attached buffers.

Runtime cross-check: global 160, Markdown buffer 37, NvimTree buffer 74; LSP clients attached 0: 271 described runtime mappings observed. The source inventory is the published command truth; runtime data is used as a cross-check.

Move precisely, then act

Character, line & screen

h j k l	Left, down, up, right.
0 ^ \$	Line start / first nonblank / line end.
H M L	Top / middle / bottom visible screen line.
Ctrl-u Ctrl-d	Half-page up / down.
zt zz zb	Place cursor line at top / center / bottom.

Words, paragraphs & file

w b e	Next word start / previous word start / word end.
W B E	Same by whitespace-separated WORD.
{ }	Previous / next paragraph.
gg G	First / last line of the file.
:42 42G	Go to line 42.
%	Jump between matching delimiters.
Ctrl-o Ctrl-i	Older / newer jump location.

Find on one line

f x F x	Find character x forward / backward; land on it.
t x T x	Move until just before x, forward / backward.
; ,	Repeat the latest find in the same / opposite direction.
* #	Search word under cursor forward / backward.

Counts repeat the next command: 3w moves three words; 5dd deletes five lines; d2j deletes the current plus next two lines; 2ci(changes inside the next two parenthesized areas.

Your current configuration

Key	Action	Context
<F2>	Toggle line numbers	Global
<F3>	Toggle relative line numbers	Global
Space ?	Buffer Local Keymaps (which-key)	Global
Space nh	Clear search highlights	Global

Edit with operators, text objects & registers

Operators: the verbs

d	Delete (also copies to a register).
c	Change: delete, then enter Insert mode.
y	Yank: copy to a register.
> <	Indent right / left; add = to auto-indent.
g~ gu gU	Toggle case / lower / upper.
=	Auto-format indentation using filetype rules.

Text objects: the nouns

iw aw	Inner word / word including surrounding space.
i" a"	Inside quotes / quotes plus contents.
i(i[i{	Inside parentheses / brackets / braces.
a(a[a{	Object including delimiters.
ip ap	Inner paragraph / paragraph plus blank space.

Insert, paste & repeat

i I a A	Insert at cursor / first text; append / line end.
o O	Open a line below / above and insert.
p P	Paste after / before cursor or line.
u Ctrl-r	Undo / redo.
.	Repeat the last change.

Read keys as a sentence: dw deletes to the next word; ci" changes inside quotes; ya(copies parentheses and contents. Fast line forms: dd, cc, yy, >>.

Your current configuration

Key	Action	Context
Space ua	Toggle autopairs	Global
Space ui	Toggle indent guides	Global
Space us	Toggle indent scope	Global

Search, replace, save & get unstuck

Search within this file

<code>/text</code> <code>Enter</code>	Search forward /
<code>?text</code> <code>Enter</code>	backward.
<code>n</code> <code>N</code>	Next / previous match.
<code>:noh</code>	Clear highlighting, not the search pattern.
<code>/\cword</code> <code>/\Cword</code>	Force case-insensitive / case-sensitive search.
<code>/\Vliteral</code>	Search punctuation literally.
<code>q/</code>	Open editable search history.

Substitute

<code>:s/old/new/</code>	Replace first match on this line.
<code>:s/old/new/g</code>	Replace every match on this line.
<code>:%s/old/new/gc</code>	Whole file: replace all and confirm each.
<code>:'<,'>s/old/new/g</code>	Replace only the current visual selection.
<code>&</code> <code>:%&</code>	Repeat the latest substitute on this line / whole file.

Help & recovery

<code>:help {topic}</code>	Open built-in documentation.
<code>:map</code> <code>:nmap</code> <code>:imap</code>	Inspect mappings by mode.
<code>:checkhealth</code>	Diagnose Neovim, providers, and plugins.
<code>:messages</code>	Show recent notifications and errors.
<code>:w</code> <code>:q</code> <code>:wq</code> <code>:q!</code>	Save / quit / save+quit / force quit.

Your setup uses ignorecase + smartcase: lowercase searches ignore case; adding any capital makes the search case-sensitive.

Your current configuration

Key	Action	Context
<code>[t</code>	Previous todo comment	Global
<code>]t</code>	Next todo comment	Global
<code>Space f/</code>	Find in buffer	Global
<code>Space fb</code>	Find buffers	Global
<code>Space fd</code>	Find diagnostics	Global
<code>Space ff</code>	Find files	Global

Buffers

<code>:ls</code> <code>:buffers</code>	List open buffers.
<code>:b name</code>	Switch by partial buffer name.
<code>:bnext</code> <code>:bprev</code>	Next / previous buffer.
<code>:bdelete</code>	Close buffer without necessarily closing its window.

Windows

<code>:split</code> <code>:vsplit</code>	Horizontal / vertical split.
<code>Ctrl-w h/j/k/l</code>	Move focus between splits.
<code>Ctrl-w c</code> <code>Ctrl-w o</code>	Close current / keep only current window.
<code>Ctrl-w =</code>	Equalize split sizes.

Tabs, folds & lists

<code>:tabnew</code> <code>gt</code> <code>gT</code>	New tab page / next / previous tab.
<code>za</code> <code>zR</code> <code>zM</code>	Toggle fold / open all / close all.
<code>:copen</code> <code>:cnext</code>	Open quickfix / next project-wide result.
<code>:lopen</code>	Open location list for this window.

Use Space f f for file names, Space f g for project text, / for the current file, and Space f / for fuzzy filtering inside the current buffer.

Your current configuration

Key	Action	Context
<code>Shift-h</code>	Previous buffer	Global
<code>Shift-l</code>	Next buffer	Global
<code>Space bd</code>	Close buffer	Global
<code>Space bp</code>	Pick buffer	Global
<code>Space wr</code>	Find session	Global
<code>Space ws</code>	Save session	Global

Git, diagnostics, LSP & completion

Choose the right Git tool

Space h ...	Act on one changed hunk: stage, reset, preview, blame, diff.
Space g ...	Find Git information through Telescope.
Space l g	Open the full LazyGit workflow.

Diagnostics & language features

[d]d	Previous / next diagnostic; read its message.
Space l d	Show the full diagnostic at the cursor.
Space l f	Format the current LSP buffer; Markdown can use Prettier.
Space l i	Toggle inlay hints when the server supports them.

Completion & snippets

Tab Shift-Tab	Jump forward / backward through an active snippet; otherwise type a tab.
Ctrl-n Ctrl-p	Next / previous built-in completion candidate.
Ctrl-y Ctrl-e	Accept / cancel a built-in completion candidate.
Ctrl-x Ctrl-o	Request omnifunc completion where supported.

Diagnostic means an editor-reported error, warning, or hint. LSP is the language-aware engine that supplies diagnostics, formatting, completion, navigation, and more.

Your current configuration

Key	Action	Context
[h	Previous hunk	Global
]h	Next hunk	Global
ih	Select hunk	Global
ih	Select hunk	Global
Space hB	Toggle line blame	Global
Space hb	Blame line	Global

Markdown workflow

Preview	Rendered, hybrid, or split preview helps read while editing.
Links	Follow the current link or move through nearby links.
Tables & tasks	Format a table or toggle a task checkbox.
Writing hygiene	Project spell words, format-on-save, table mode, and linting are configured per project.

TODO discovery

TODO FIXME HACK	Use clear comment markers so they are searchable.
Quickfix location list	Send discovered TODOs to a navigable list.
Autopairs	Matching delimiters are configurable and intentionally disabled in picker/commit contexts.

Markdown buffers automatically enable US English spell checking, soft wrapping, line breaks, and break indentation in this setup.

Your current configuration

Key	Action	Context
Space ma	Toggle format on save	Global
Space mc	Toggle task	Global
Space mc	Toggle task	Global
Space md	Lint Markdown	Global
Space mF	Unfold section	Global
Space mf	Fold section	Global

Registers, visual mode & block edits

Registers: where copied text lives

<code>"0</code>	Latest yank; <code>"Op</code> pastes the last copied text.
<code>"+</code>	System clipboard in this setup.
<code>"a</code>	Named register: <code>"ayy</code> stores a line; <code>"ap</code> pastes it.
<code>"_</code>	Black-hole register: delete without replacing the clipboard.
<code>:reg</code>	Inspect copied text and registers.

Visual mode

<code>v</code> <code>V</code>	Select characters / whole lines, then use an operator.
<code>Ctrl-v</code>	Select a rectangle; <code>I</code> inserts on every selected line after Esc.
<code>gv</code>	Reselect the previous visual selection.
<code>~</code>	Swap selected text's case.
<code>J</code> <code>gJ</code>	Join lines with / without adding a space.

Your configuration uses `unnamedplus`, so ordinary yank, delete, and paste already share the system clipboard.

Your current configuration

Key	Action	Context
<code>Space ua</code>	Toggle autopairs	Global
<code>Space ui</code>	Toggle indent guides	Global
<code>Space us</code>	Toggle indent scope	Global

Sessions

Find session	Restore a saved workspace.
Save session	Persist the current layout and buffers.
What is saved	Buffers, layout, current directory, terminals, folds, tab pages, and local options.

Dashboard

New file	Start an empty editing buffer.
File recent text projects	Start common Telescope workflows from the dashboard.
Explorer sessions LazyGit	Open a workspace tool before entering an editing buffer.
Plugin manager quit	Maintain plugins or exit Neovim.

Personal display

F2 F3	Toggle absolute / relative line numbers.
Clear highlighting	Remove the visual highlight of the last search.
Indent guides	Toggle indentation and its scope highlight.
Autopairs	Toggle automatic bracket and quote pairing.

Dashboard shortcuts are intentionally context-labeled in the generated appendix: use them from the Alpha start screen, not from an editing buffer.

Your current configuration

Key	Action	Context
e	Start a new empty file	Dashboard buffer
ff	Find files	Dashboard buffer
fk	Find keymaps	Dashboard buffer
fp	Switch projects	Dashboard buffer
fr	Open recent files	Dashboard buffer
fs	Search project text	Dashboard buffer

Testing, debugging & code navigation

Testing loop

Run nearest test	Start with the test closest to the cursor.
Run file suite	Widen scope after the nearest test is useful.
Test output	Open output when a result needs diagnosis.
Toggle summary	Keep test state visible while editing.

Debugging loop

Toggle breakpoint	Mark the next place execution should pause.
Continue	Run to the next breakpoint.
Step over into out	Move through execution without losing the current state.
Inspect UI	Open debugger panels for variables, stack, and console.

Code navigation

Definition references	Jump to where a symbol is defined or used.
Rename	Apply a language-aware rename through the LSP.
Code action	See available fixes and refactors.
Diagnostics	Move through editor-reported problems before changing code.

The complete appendix has the exact current keys. This page teaches the workflow first so it remains useful even when those keys evolve.

Your current configuration

Key	Action	Context
Space tA	Fallback: run test suite	Global
Space ta	Run test suite	Global
Space td	Debug nearest test	Global
Space tf	Run current file	Global
Space tn	Run nearest test	Global
Space to	Show test output	Global

Ctrl+F index

Search this PDF for an exact key string or an ordinary word. The guide repeats literal keys in the teaching sections and keeps a complete generated appendix after them.

Files & project navigation

find files, project text, recent files, buffers, help, keymaps, explorer

Editing

change, delete, copy, paste, repeat, register, text object, visual block

Code help

diagnostic, format, completion, inlay hint, LSP, snippet

Git

hunk, stage, reset, blame, diff, branch, commit, LazyGit

Writing

Markdown, link, preview, table, spell, TODO, lint

Discover anything else: Space f k opens searchable active keymaps. `:help` keyword explains built-ins; `:map`, `:nmap`, and `:imap` inspect mappings directly; `:checkhealth` diagnoses the setup.

Configured Tooling

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
DAP adapter: codelldb	Connects Neovim's debugging controls to this language/runtime.	dap.lua
DAP adapter: debugpy	Connects Neovim's debugging controls to this language/runtime.	dap.lua
DAP adapter: delve	Connects Neovim's debugging controls to this language/runtime.	dap.lua
DAP adapter: netcoredbg	Connects Neovim's debugging controls to this language/runtime.	dap.lua
Executable: codelldb	External command used by a configured editor integration.	dap.lua
Executable: dlv	External command used by a configured editor integration.	dap.lua
Executable: magick	External command used by a configured editor integration.	image.lua
Executable: nvr	External command used by a configured editor integration.	set.lua
Executable: python	External command used by a configured editor integration.	dap.lua
Executable: python3	External command used by a configured editor integration.	dap.lua
Executable: uv	External command used by a configured editor integration.	neotest.lua

Configured Tooling - part 2 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
Formatter: prettier	Rewrites source into the project's configured formatting style.	markdown.lua
Linters: markdownlint-cli2	Checks source for style, correctness, or writing issues.	markdown.lua
LSP server: basedpyright	Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached.	lsp.lua
LSP server: jsonls	Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached.	lsp.lua
LSP server: lua_ls	Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached.	lsp.lua
LSP server: roslyn_ls	Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached.	lsp.lua
LSP server: yamlls	Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached.	lsp.lua
Plugin: 3rd/image.nvim	Display supported images inline in Neovim when the terminal graphics backend is available.	image.lua
Plugin: akinsho/bufferline.nvim	Show open buffers as a navigable tab-like strip.	bufferlines.lua
Plugin: akinsho/neotest-go	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: antoinemadec/FixCursorHold.nvim	Configured integration; use its matching mapping or command in this guide.	neotest.lua

Configured Tooling · part 3 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
Plugin: b0o/SchemaStore.nvim	Configured integration; use its matching mapping or command in this guide.	lsp.lua
Plugin: CollinRobison/neotest-dotnet	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: folke/todo-comments.nvim	Recognize TODO-style annotations and make them searchable through lists and Telescope.	todo-comments.lua
Plugin: folke/tokyonight.nvim	Configured integration; use its matching mapping or command in this guide.	tokyonight.lua
Plugin: folke/which-key.nvim	Display available keybinding continuations after a key prefix.	which-key.lua
Plugin: goolord/alpha-nvim	Show a start dashboard with shortcuts for files, projects, sessions, Git, and plugins.	alpha.lua
Plugin: haydenmeade/neotest-jest	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: jakewvincent/mkdnflow.nvim	Follow links, manage tasks, tables, headings, and Markdown navigation.	markdown.lua
Plugin: jay-babu/mason-nvim-dap.nvim	Pause a program, step through execution, and inspect debugger state.	mason-tools.lua
Plugin: kdheepak/lazygit.nvim	Open a terminal Git interface for status, commits, branches, and logs.	lazygit.lua
Plugin: lewis6991/gitsigns.nvim	Navigate, preview, stage, reset, and blame changed Git hunks.	gitsigns.lua

Configured Tooling - part 4 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
Plugin: <code>lukas-reineke/indent-blankline.nvim</code>	Draw indentation guides and optionally highlight the current scope.	<code>indent-blankline.lua</code>
Plugin: <code>marilari88/neotest-vitest</code>	Run tests, inspect output, and debug a test through DAP.	<code>neotest.lua</code>
Plugin: <code>mason-org/mason-lspconfig.nvim</code>	Install and manage external language servers, formatters, linters, and debug adapters.	<code>mason-tools.lua</code>
Plugin: <code>mason-org/mason-lspconfig.nvim</code>	Install and manage external language servers, formatters, linters, and debug adapters.	<code>lsp.lua</code>
Plugin: <code>mason-org/mason.nvim</code>	Install and manage external language servers, formatters, linters, and debug adapters.	<code>mason-tools.lua</code>
Plugin: <code>mfussenegger/nvim-dap</code>	Pause a program, step through execution, and inspect debugger state.	<code>dap.lua</code>
Plugin: <code>mfussenegger/nvim-lint</code>	Configured integration; use its matching mapping or command in this guide.	<code>markdown.lua</code>
Plugin: <code>neovim/nvim-lspconfig</code>	Configured integration; use its matching mapping or command in this guide.	<code>lsp.lua</code>
Plugin: <code>nvim-lua/plenary.nvim</code>	Configured integration; use its matching mapping or command in this guide.	<code>lazygit.lua</code>
Plugin: <code>nvim-lua/plenary.nvim</code>	Configured integration; use its matching mapping or command in this guide.	<code>telescope.lua</code>
Plugin: <code>nvim-lua/plenary.nvim</code>	Configured integration; use its matching mapping or command in this guide.	<code>todo-comments.lua</code>

Configured Tooling · part 5 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
Plugin: nvim-lualine/lualine.nvim	Show file, Git, diagnostic, mode, and status information in the statusline.	lualine.lua
Plugin: nvim-mini/mini.icons	Provide compact file-type icons to Neovim UI integrations.	mini-icon.lua
Plugin: nvim-neotest/neotest	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: nvim-neotest/neotest-python	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: nvim-neotest/neotest-vim-test	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: nvim-neotest/nvim-nio	Run tests, inspect output, and debug a test through DAP.	dap.lua
Plugin: nvim-neotest/nvim-nio	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: nvim-telescope/telescope-fzf-native.nvim	Search files, text, buffers, help, keymaps, and Git information.	telescope.lua
Plugin: nvim-telescope/telescope-project.nvim	Search files, text, buffers, help, keymaps, and Git information.	telescope.lua
Plugin: nvim-telescope/telescope.nvim	Search files, text, buffers, help, keymaps, and Git information.	telescope.lua
Plugin: nvim-tree/nvim-tree.lua	Browse files and reveal the current file in a tree.	nvimtree.lua

Configured Tooling - part 6 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
Plugin: nvim-tree/nvim-web-devicons	Browse files and reveal the current file in a tree.	nvim-web-devicons.lua
Plugin: nvim-tree/nvim-web-devicons	Browse files and reveal the current file in a tree.	nvimtree.lua
Plugin: nvim-tree/nvim-web-devicons	Browse files and reveal the current file in a tree.	luafile.lua
Plugin: nvim-tree/nvim-web-devicons	Browse files and reveal the current file in a tree.	bufferlines.lua
Plugin: nvim-treesitter/nvim-treesitter	Browse files and reveal the current file in a tree.	image.lua
Plugin: nvim-treesitter/nvim-treesitter	Browse files and reveal the current file in a tree.	nvim-treesitter.lua
Plugin: orjangj/neotest-ctest	Run tests, inspect output, and debug a test through DAP.	neotest.lua
Plugin: OXY2DEV/markview.nvim	Render Markdown while you edit it.	markdown.lua
Plugin: rcarriga/nvim-dap-ui	Pause a program, step through execution, and inspect debugger state.	dap.lua
Plugin: rmagatti/auto-session	Save and restore working layouts and open buffers.	auto-session.lua
Plugin: rouge8/neotest-rust	Run tests, inspect output, and debug a test through DAP.	neotest.lua

Configured Tooling - part 7 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

Tool / plugin	What it enables	Configuration source
Plugin: <code>stevearc/conform.nvim</code>	Configured integration; use its matching mapping or command in this guide.	<code>markdown.lua</code>
Plugin: <code>textDocument/codeLens</code>	Configured integration; use its matching mapping or command in this guide.	<code>lsp.lua</code>
Plugin: <code>textDocument/completion</code>	Configured integration; use its matching mapping or command in this guide.	<code>lsp.lua</code>
Plugin: <code>textDocument/inlayHint</code>	Configured integration; use its matching mapping or command in this guide.	<code>lsp.lua</code>
Plugin: <code>theHamsta/nvim-dap-virtual-text</code>	Pause a program, step through execution, and inspect debugger state.	<code>dap.lua</code>
Plugin: <code>vague-theme/vague.nvim</code>	Configured integration; use its matching mapping or command in this guide.	<code>vague.lua</code>
Plugin: <code>vim-test/vim-test</code>	Configured integration; use its matching mapping or command in this guide.	<code>neotest.lua</code>
Plugin: <code>windwp/nvim-autopairs</code>	Automatically insert and manage matching quotes, brackets, and parentheses while typing.	<code>autopairs.lua</code>
Plugin: <code>windwp/nvim-ts-autotag</code>	Configured integration; use its matching mapping or command in this guide.	<code>nvim-treesitter.lua</code>

Commands & automatic behavior

Type these after `:` in Normal mode. The tooling inventory explains capabilities that happen automatically or do not have a direct keybinding.

Command	What it does	Configuration source
<code>:AutoSession</code>	Save, search, or restore an editor workspace session.	<code>alpha.lua</code>
<code>:bdelete</code>	Close the current buffer without quitting Neovim.	<code>bufferlines.lua</code>
<code>:BufferLineCycleNext</code>	Select the next buffer in the buffer line.	<code>bufferlines.lua</code>
<code>:BufferLineCyclePrev</code>	Select the previous buffer in the buffer line.	<code>bufferlines.lua</code>
<code>:BufferLinePick</code>	Show letter labels so you can jump directly to an open buffer.	<code>bufferlines.lua</code>
<code>:ene</code>	Open a new empty buffer.	<code>alpha.lua</code>
<code>:IBLToggle</code>	Show or hide indentation guides.	<code>indent-blankline.lua</code>
<code>:IBLToggleScope</code>	Show or hide the current indentation scope highlight.	<code>indent-blankline.lua</code>
<code>:Lazy</code>	Open the plugin manager.	<code>alpha.lua</code>
<code>:LazyGit</code>	Open the terminal Git interface for the repository.	<code>alpha.lua</code>

Commands & automatic behavior · part 2 of 3

Type these after `:` in Normal mode. The tooling inventory explains capabilities that happen automatically or do not have a direct keybinding.

Command	What it does	Configuration source
<code>:LazyGitCurrentFile</code>	Open the terminal Git interface for the repository.	<code>lazygit.lua</code>
<code>:LazyGitFilter</code>	Open the terminal Git interface for the repository.	<code>lazygit.lua</code>
<code>:LazyGitFilterCurrentFile</code>	Open the terminal Git interface for the repository.	<code>lazygit.lua</code>
<code>:Markview</code>	Toggle rendered Markdown, hybrid view, or a preview split.	<code>markdown.lua</code>
<code>:MasonInstallDebugAdapters</code>	Install the debugger adapters configured for this Neovim setup.	<code>mason-tools.lua</code>
<code>:MkdnFoldSection</code>	Fold the Markdown section at the cursor.	<code>markdown.lua</code>
<code>:MkdnFollowLink</code>	Open the Markdown link under the cursor.	<code>markdown.lua</code>
<code>:MkdnNextLink</code>	Jump to the next Markdown link.	<code>markdown.lua</code>
<code>:MkdnPrevLink</code>	Jump to the previous Markdown link.	<code>markdown.lua</code>
<code>:MkdnTableFormat</code>	Align and format the Markdown table at the cursor.	<code>markdown.lua</code>

Commands & automatic behavior · part 3 of 3

Type these after `:` in Normal mode. The tooling inventory explains capabilities that happen automatically or do not have a direct keybinding.

Command	What it does	Configuration source
<code>:MkdnToggleToDo</code>	Toggle the Markdown task checkbox at the cursor.	<code>markdown.lua</code>
<code>:MkdnUnfoldSection</code>	Unfold the Markdown section at the cursor.	<code>markdown.lua</code>
<code>:NvimTreeToggle</code>	Open or close the file explorer.	<code>alpha.lua</code>
<code>:qa</code>	Quit all Neovim windows.	<code>alpha.lua</code>
<code>:Telescope</code>	Open a searchable picker; the following argument selects files, text, help, Git, or another source.	<code>alpha.lua</code>
<code>:TestFile</code>	Run the configured test target (nearest test, file, or suite).	<code>neotest.lua</code>
<code>:TestNearest</code>	Run the configured test target (nearest test, file, or suite).	<code>neotest.lua</code>
<code>:TestSuite</code>	Run the configured test target (nearest test, file, or suite).	<code>neotest.lua</code>
<code>:TodoLocList</code>	Collect TODO-style comments in the current window's location list.	<code>todo-comments.lua</code>
<code>:TodoQuickFix</code>	Collect TODO-style comments in the quickfix list.	<code>todo-comments.lua</code>

Buffers & Windows

Extracted from `bufferlines.lua`.

Mode	Key	Action	Context
Normal	Shift-h	Previous buffer	Global
Normal	Shift-l	Next buffer	Global
Normal	Space bd	Close buffer	Global
Normal	Space bp	Pick buffer	Global

Dashboard

Extracted from `alpha.lua`.

Mode	Key	Action	Context
Normal	<code>e</code>	Start a new empty file	Dashboard buffer
Normal	<code>ff</code>	Find files	Dashboard buffer
Normal	<code>fk</code>	Find keymaps	Dashboard buffer
Normal	<code>fp</code>	Switch projects	Dashboard buffer
Normal	<code>fr</code>	Open recent files	Dashboard buffer
Normal	<code>fs</code>	Search project text	Dashboard buffer
Normal	<code>lg</code>	Open LazyGit	Dashboard buffer
Normal	<code>nt</code>	Toggle file explorer	Dashboard buffer
Normal	<code>p</code>	Open plugin manager	Dashboard buffer
Normal	<code>q</code>	Quit Neovim	Dashboard buffer
Normal	<code>ss</code>	Find and restore a session	Dashboard buffer

Debugging

Extracted from dap.lua.

Mode	Key	Action	Context
Normal	Space dB	Conditional breakpoint	Global
Normal	Space db	Toggle breakpoint	Global
Normal	Space dc	Continue	Global
Normal	Space de	Evaluate expression	Global
Normal	Space di	Step into	Global
Normal	Space d0	Step out	Global
Normal	Space do	Step over	Global
Normal	Space dp	Pause debug session	Global
Normal	Space dq	Terminate debug session	Global
Normal	Space dr	Restart debug session	Global
Normal	Space du	Toggle DAP UI	Global
Normal	Space dv	Toggle DAP virtual text	Global

Find & Navigate

Extracted from telescope.lua, todo-comments.lua.

Mode	Key	Action	Context
Normal	[t]	Previous todo comment	Global
Normal	]t	Next todo comment	Global
Normal	Space f/	Find in buffer	Global
Normal	Space fb	Find buffers	Global
Normal	Space fd	Find diagnostics	Global
Normal	Space ff	Find files	Global
Normal	Space fg	Find text	Global
Normal	Space fh	Find help	Global
Normal	Space fk	Find keymaps	Global
Normal	Space fL	Todo comments to location list	Global

Find & Navigate · part 2 of 2

Extracted from telescope.lua, todo-comments.lua.

Mode	Key	Action	Context
Normal	Space fp	Find project	Global
Normal	Space fR	Resume last picker	Global
Normal	Space fr	Find recent files	Global
Normal	Space fT	Todo comments to quickfix	Global
Normal	Space ft	Find todo comments	Global
Normal	Space fw	Find word under cursor	Global
Normal	Space gb	Git branches	Global
Normal	Space gc	Git commits	Global
Normal	Space gs	Git status	Global

Extracted from gitsigns.lua, lazygit.lua.

Mode	Key	Action	Context
Normal	[h	Previous hunk	Global
Normal	]h	Next hunk	Global
Operator-pending	ih	Select hunk	Global
Visual	ih	Select hunk	Global
Normal	Space hB	Toggle line blame	Global
Normal	Space hb	Blame line	Global
Normal	Space hD	Diff against HEAD	Global
Normal	Space hd	Diff against index	Global
Normal	Space hi	Preview hunk inline	Global
Normal	Space hL	Hunks to location list	Global
Normal	Space hp	Preview hunk	Global
Normal	Space hQ	Repository hunks to quickfix	Global
Normal	Space hq	Hunks to quickfix	Global

Git • part 2 of 2

Extracted from `gitsigns.lua`, `lazygit.lua`.

Mode	Key	Action	Context
Normal	Space hR	Reset buffer	Global
Normal	Space hr	Reset hunk	Global
Visual	Space hr	Reset selection	Global
Normal	Space hS	Stage buffer	Global
Normal	Space hs	Stage hunk	Global
Visual	Space hs	Stage selection	Global
Normal	Space hU	Unstage buffer	Global
Normal	Space lG	LazyGit current file	Global
Normal	Space lg	LazyGit dashboard	Global
Normal	Space lL	LazyGit repository log	Global
Normal	Space ll	LazyGit file log	Global
Normal	Space uw	Toggle Git word diff	Global

LSP, Completion & Diagnostics

Extracted from lsp.lua.

Mode	Key	Action	Context
Normal	[d]	Previous diagnostic	Global
Normal	]d	Next diagnostic	Global
Normal	Space ld	Show diagnostic	Global
Insert	Ctrl-Space	Trigger LSP completion	LSP buffer (when attached)
Normal	Space lc	Toggle LSP completion	LSP buffer (when attached)
Normal	Space lf	Format buffer	LSP buffer (when attached)
Normal	Space li	Toggle inlay hints	LSP buffer (when attached)
Normal	Space lr	Refresh C# code lenses	LSP buffer (when attached)
Normal	Space lt	Run C# code lens	LSP buffer (when attached)

Markdown

Extracted from markdown.lua.

Mode	Key	Action	Context
Normal	Space ma	Toggle format on save	Global
Normal	Space mc	Toggle task	Global
Visual	Space mc	Toggle task	Global
Normal	Space md	Lint Markdown	Global
Normal	Space mF	Unfold section	Global
Normal	Space mf	Fold section	Global
Normal	Space mh	Toggle hybrid preview	Global
Normal	Space ml	Follow link	Global
Normal	Space mN	Previous link	Global
Normal	Space mn	Next link	Global

Markdown · part 2 of 2

Extracted from markdown.lua.

Mode	Key	Action	Context
Normal	Space mp	Toggle preview	Global
Normal	Space ms	Toggle preview split	Global
Normal	Space mT	Toggle table mode	Global
Normal	Space mt	Format table	Global
Normal	Space mW	Add all project spelling words	Global
Normal	Space mw	Add project spelling word	Global
Normal	Enter	Mkdnflow smart Enter	Markdown buffer
Insert	Enter	Mkdnflow smart Enter	Markdown buffer
Visual	Enter	Mkdnflow smart Enter	Markdown buffer

NvimTree

Extracted from nvimtree.lua.

Mode	Key	Action	Context
Normal	Space nc	Collapse nvim-tree	Global
Normal	Space ne	Expand nvim-tree	Global
Normal	Space nf	Reveal current file	Global
Normal	Space nn	Focus nvim-tree	Global
Normal	Space nr	Refresh nvim-tree	Global
Normal	Space nt	Toggle nvim-tree	Global

Personal Controls

Extracted from remap.lua, which-key.lua.

Mode	Key	Action	Context
Normal	<F2>	Toggle line numbers	Global
Normal	<F3>	Toggle relative line numbers	Global
Normal	Space ?	Buffer Local Keymaps (which-key)	Global
Normal	Space nh	Clear search highlights	Global

Runtime-discovered keymaps

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	?	Buffer Local Keymaps (which-key)	Global
Normal	fR	Resume last picker	Global
Normal	f/	Find in buffer	Global
Normal	fd	Find diagnostics	Global
Normal	fk	Find keymaps	Global
Normal	fh	Find help	Global
Normal	fr	Find recent files	Global
Normal	fb	Find buffers	Global
Normal	fw	Find word under cursor	Global
Normal	fg	Find text	Global
Normal	ff	Find files	Global
Normal	gs	Git status	Global
Normal	gb	Git branches	Global
Normal	gc	Git commits	Global
Normal	fp	Find project	Global

Runtime-discovered keymaps · part 2 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	wr	Find session	Global
Normal	ws	Save session	Global
Normal	de	Evaluate expression	Global
Normal	dv	Toggle DAP virtual text	Global
Normal	du	Toggle DAP UI	Global
Normal	dq	Terminate debug session	Global
Normal	dr	Restart debug session	Global
Normal	d0	Step out	Global
Normal	do	Step over	Global
Normal	di	Step into	Global
Normal	dp	Pause debug session	Global
Normal	dc	Continue	Global
Normal	dB	Conditional breakpoint	Global
Normal	db	Toggle breakpoint	Global
Normal	ne	Expand nvim-tree	Global

Runtime-discovered keymaps · part 3 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	nc	Collapse nvim-tree	Global
Normal	nr	Refresh nvim-tree	Global
Normal	nf	Reveal current file	Global
Normal	nn	Focus nvim-tree	Global
Normal	nt	Toggle nvim-tree	Global
Normal	ua	Toggle autopairs	Global
Normal	bp	Pick buffer	Global
Normal	bd	Close buffer	Global
Normal	ft	Find todo comments	Global
Normal	fL	Todo comments to location list	Global
Normal	fT	Todo comments to quickfix	Global
Normal	us	Toggle indent scope	Global
Normal	ui	Toggle indent guides	Global
Normal	hQ	Repository hunks to quickfix	Global
Normal	hq	Hunks to quickfix	Global

Runtime-discovered keymaps · part 4 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	hD	Diff against HEAD	Global
Normal	hd	Diff against index	Global
Normal	uw	Toggle Git word diff	Global
Normal	hB	Toggle line blame	Global
Normal	hb	Blame line	Global
Normal	hi	Preview hunk inline	Global
Normal	hp	Preview hunk	Global
Normal	hU	Unstage buffer	Global
Normal	hR	Reset buffer	Global
Normal	hS	Stage buffer	Global
Normal	hr	Reset hunk	Global
Normal	hs	Stage hunk	Global
Normal	hℓ	Hunks to location list	Global
Normal	ℓℓ	LazyGit file log	Global
Normal	ℓL	LazyGit repository log	Global

Runtime-discovered keymaps · part 5 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	lG	LazyGit current file	Global
Normal	lg	LazyGit dashboard	Global
Normal	&	Vim built-in; see :help &-default	Global
Normal	H	Previous buffer	Global
Normal	L	Next buffer	Global
Normal	Y	Vim built-in; see :help Y-default	Global
Normal	[	Add empty line above cursor	Global
Normal	[B	:brewind	Global
Normal	[b	Switch to previous buffer	Global
Normal	[Ctrl-T	:ptprevious	Global
Normal	[T	:trewind	Global
Normal	[A	Jump to the first item in the argument list	Global
Normal	[a	Jump to the previous argument-list item	Global
Normal	[Ctrl-L	:lpfile	Global
Normal	[L	:lrewind	Global

Runtime-discovered keymaps · part 6 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	[l]	:lprevious	Global
Normal	[Ctrl-Q]	:cpfile	Global
Normal	[Q]	:crewind	Global
Normal	[q]	:cprevious	Global
Normal	[D]	Jump to the first diagnostic in the current buffer	Global
Normal	]]	Add empty line below cursor	Global
Normal	]B	Switch to last buffer	Global
Normal	]b	Switch to next buffer	Global
Normal	]Ctrl-T	:ptnext	Global
Normal	]T	:tlast	Global
Normal	]A	:last	Global
Normal	]a	Jump to the next argument-list item	Global
Normal	]Ctrl-L	:lnfile	Global
Normal	]L	:llast	Global
Normal	]l	:lnext	Global

Runtime-discovered keymaps · part 7 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	]Ctrl-Q	:cnfile	Global
Normal	]Q	:clast	Global
Normal	]q	:cnext	Global
Normal	]D	Jump to the last diagnostic in the current buffer	Global
Normal	g0	vim.lsp.buf.document_symbol()	Global
Normal	grt	vim.lsp.buf.type_definition()	Global
Normal	gri	vim.lsp.buf.implementation()	Global
Normal	grr	vim.lsp.buf.references()	Global
Normal	grx	vim.lsp.codelens.run()	Global
Normal	gra	vim.lsp.buf.code_action()	Global
Normal	grn	vim.lsp.buf.rename()	Global
Normal	gcc	Toggle comment line	Global
Normal	gc	Toggle comment	Global
Normal	gx	Opens filepath or URI under cursor with the system handler (file explorer, web browser, ...)	Global
Normal	Ctrl-WCtrl-D	Show diagnostics under the cursor	Global

Runtime-discovered keymaps · part 8 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	Ctrl-Wd	Show diagnostics under the cursor	Global
Normal	Ctrl-L	Vim built-in; see :help CTRL-L-default	Global
Visual	Tab	vim.snippet.jump if active, otherwise <Tab>	Global
Visual	hr	Reset selection	Global
Visual	hs	Stage selection	Global
Visual	#	Vim built-in; see :help v_#-default	Global
Visual	*	Vim built-in; see :help v_star-default	Global
Visual	@	Vim built-in; see :help v_@-default	Global
Visual	Q	Vim built-in; see :help v_Q-default	Global
Visual	[N	Select previous sibling node	Global
Visual	[n	Select previous node	Global
Visual	]N	Select next sibling node	Global
Visual	]n	Select next node	Global
Visual	an	Select parent (outer) node	Global
Visual	gra	vim.lsp.buf.code_action()	Global

Runtime-discovered keymaps · part 9 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Visual	gc	Toggle comment	Global
Visual	gx	Opens filepath or URI under cursor with the system handler (file explorer, web browser, ...)	Global
Visual	in	Select child (inner) node	Global
Visual	Shift-Tab	vim.snippet.jump if active, otherwise <S-Tab>	Global
Visual	Ctrl-S	vim.lsp.buf.signature_help()	Global
Visual	hr	Reset selection	Global
Visual	hs	Stage selection	Global
Visual	#	Vim built-in; see :help v_#-default	Global
Visual	*	Vim built-in; see :help v_star-default	Global
Visual	@	Vim built-in; see :help v_@-default	Global
Visual	Q	Vim built-in; see :help v_Q-default	Global
Visual	[N	Select previous sibling node	Global
Visual	[n	Select previous node	Global
Visual	]N	Select next sibling node	Global
Visual	]n	Select next node	Global

Runtime-discovered keymaps · part 10 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Visual	an	Select parent (outer) node	Global
Visual	gra	vim.lsp.buf.code_action()	Global
Visual	gc	Toggle comment	Global
Visual	gx	Opens filepath or URI under cursor with the system handler (file explorer, web browser, ...)	Global
Visual	in	Select child (inner) node	Global
Operator-pending	an	Select parent (outer) node	Global
Operator-pending	gc	Comment textobject	Global
Operator-pending	in	Select child (inner) node	Global
Insert	Shift-Tab	vim.snippet.jump if active, otherwise <S-Tab>	Global
Insert	Ctrl-S	vim.lsp.buf.signature_help()	Global
Insert	Ctrl-W	Vim built-in; see :help i_CTRL-W-default	Global
Insert	Ctrl-U	Vim built-in; see :help i_CTRL-U-default	Global
Insert	Tab	vim.snippet.jump if active, otherwise <Tab>	Global
Select	Tab	vim.snippet.jump if active, otherwise <Tab>	Global
Select	Shift-Tab	vim.snippet.jump if active, otherwise <S-Tab>	Global

Runtime-discovered keymaps · part 11 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Select	Ctrl-S	vim.lsp.buf.signature_help()	Global
Normal	Tab	Jump to next link	Markdown buffer
Normal	md	Lint Markdown	Markdown buffer
Normal	mT	Toggle table mode	Markdown buffer
Normal	ma	Toggle format on save	Markdown buffer
Normal	mW	Add all project spelling words	Markdown buffer
Normal	mw	Add project spelling word	Markdown buffer
Normal	mF	Unfold section	Markdown buffer
Normal	mf	Fold section	Markdown buffer
Normal	mc	Toggle task	Markdown buffer
Normal	mt	Format table	Markdown buffer
Normal	mN	Previous link	Markdown buffer
Normal	mn	Next link	Markdown buffer
Normal	mL	Follow link	Markdown buffer
Normal	ms	Toggle preview split	Markdown buffer

Runtime-discovered keymaps · part 12 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	mh	Toggle hybrid preview	Markdown buffer
Normal	mp	Toggle preview	Markdown buffer
Normal	o	Create list item above and enter insert mode	Markdown buffer
Normal	[[	Jump to previous heading	Markdown buffer
Normal	]]	Jump to next heading	Markdown buffer
Normal	g0	Show an Outline of the current buffer	Markdown buffer
Normal	gx	Tree-sitter based link opener from `markview.nvim`.	Markdown buffer
Normal	o	Create list item below and enter insert mode	Markdown buffer
Normal	Shift-Tab	Jump to previous link	Markdown buffer
Visual	mc	Toggle task	Markdown buffer
Visual	mc	Toggle task	Markdown buffer
Insert	Shift-CR	Insert new line in table cell	Markdown buffer
Insert	<M-CR>	Jump to previous table row	Markdown buffer
Insert	Shift-Tab	Jump to previous table cell	Markdown buffer
Insert	Ctrl-T	Indent list item and update numbering	Markdown buffer

Runtime-discovered keymaps · part 13 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Insert	Ctrl-D	Dedent list item and update numbering	Markdown buffer
Insert	Tab	Jump to next table cell	Markdown buffer
Select	Enter	Follow link, toggle to-do, or create link from selection	Markdown buffer
Select	mc	Toggle task	Markdown buffer
Normal	Tab	nvim-tree: Open Preview	NvimTree
Normal	Enter	nvim-tree: Open	NvimTree
Normal	-	nvim-tree: Up	NvimTree
Normal	.	nvim-tree: Run Command	NvimTree
Normal	<lt>	nvim-tree: Previous Sibling	NvimTree
Normal	>	nvim-tree: Next Sibling	NvimTree
Normal	B	nvim-tree: Toggle Filter: No Buffer	NvimTree
Normal	C	nvim-tree: Toggle Filter: Git Clean	NvimTree
Normal	D	nvim-tree: Trash	NvimTree
Normal	E	nvim-tree: Expand All	NvimTree
Normal	F	nvim-tree: Live Filter: Clear	NvimTree

Runtime-discovered keymaps · part 14 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	H	nvim-tree: Toggle Filter: Dotfiles	NvimTree
Normal	I	nvim-tree: Toggle Filter: Git Ignored	NvimTree
Normal	J	nvim-tree: Last Sibling	NvimTree
Normal	K	nvim-tree: First Sibling	NvimTree
Normal	L	nvim-tree: Toggle Group Empty	NvimTree
Normal	M	nvim-tree: Toggle Filter: No Bookmark	NvimTree
Normal	O	nvim-tree: Open: No Window Picker	NvimTree
Normal	P	nvim-tree: Parent Directory	NvimTree
Normal	R	nvim-tree: Refresh	NvimTree
Normal	S	nvim-tree: Search	NvimTree
Normal	U	nvim-tree: Toggle Filter: Custom	NvimTree
Normal	W	nvim-tree: Collapse All	NvimTree
Normal	Y	nvim-tree: Copy Relative Path	NvimTree
Normal	[e	nvim-tree: Prev Diagnostic	NvimTree
Normal	[c	nvim-tree: Prev Git	NvimTree

Runtime-discovered keymaps · part 15 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	le	nvim-tree: Next Diagnostic	NvimTree
Normal	lc	nvim-tree: Next Git	NvimTree
Normal	a	nvim-tree: Create File Or Directory	NvimTree
Normal	bm	nvim-tree: Move Bookmarked	NvimTree
Normal	bt	nvim-tree: Trash Bookmarked	NvimTree
Normal	bd	nvim-tree: Delete Bookmarked	NvimTree
Normal	c	nvim-tree: Copy	NvimTree
Normal	d	nvim-tree: Delete	NvimTree
Normal	e	nvim-tree: Rename: Basename	NvimTree
Normal	f	nvim-tree: Live Filter: Start	NvimTree
Normal	gp	nvim-tree: Move	NvimTree
Normal	ge	nvim-tree: Copy Basename	NvimTree
Normal	gy	nvim-tree: Copy Absolute Path	NvimTree
Normal	g?	nvim-tree: Help	NvimTree
Normal	m	nvim-tree: Toggle Bookmark	NvimTree

Runtime-discovered keymaps · part 16 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	o	nvim-tree: Open	NvimTree
Normal	p	nvim-tree: Paste	NvimTree
Normal	q	nvim-tree: Close	NvimTree
Normal	r	nvim-tree: Rename	NvimTree
Normal	s	nvim-tree: Run System	NvimTree
Normal	u	nvim-tree: Rename: Full Path	NvimTree
Normal	x	nvim-tree: Cut	NvimTree
Normal	y	nvim-tree: Copy Name	NvimTree
Normal	<2-RightMouse>	nvim-tree: CD	NvimTree
Normal	<2-LeftMouse>	nvim-tree: Open	NvimTree
Normal		nvim-tree: Delete	NvimTree
Normal	<BS>	nvim-tree: Close Directory	NvimTree
Normal	Ctrl-X	nvim-tree: Open: Horizontal Split	NvimTree
Normal	Ctrl-V	nvim-tree: Open: Vertical Split	NvimTree
Normal	Ctrl-T	nvim-tree: Open: New Tab	NvimTree

Runtime-discovered keymaps · part 17 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Normal	Ctrl-R	nvim-tree: Rename: Omit Filename	NvimTree
Normal	Ctrl-K	nvim-tree: Info	NvimTree
Normal	Ctrl-E	nvim-tree: Open: In Place	NvimTree
Normal	Ctrl-J	nvim-tree: CD	NvimTree
Visual	D	nvim-tree: Trash	NvimTree
Visual	c	nvim-tree: Copy	NvimTree
Visual	d	nvim-tree: Delete	NvimTree
Visual	gy	nvim-tree: Copy Absolute Path	NvimTree
Visual	m	nvim-tree: Toggle Bookmark	NvimTree
Visual	x	nvim-tree: Cut	NvimTree
Visual		nvim-tree: Delete	NvimTree
Visual	D	nvim-tree: Trash	NvimTree
Visual	c	nvim-tree: Copy	NvimTree
Visual	d	nvim-tree: Delete	NvimTree
Visual	gy	nvim-tree: Copy Absolute Path	NvimTree

Runtime-discovered keymaps · part 18 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

Mode	Key	Action	Context
Visual	m	nvim-tree: Toggle Bookmark	NvimTree
Visual	x	nvim-tree: Cut	NvimTree
Visual		nvim-tree: Delete	NvimTree

Testing

Extracted from neotest.lua.

Mode	Key	Action	Context
Normal	Space tA	Fallback: run test suite	Global
Normal	Space ta	Run test suite	Global
Normal	Space td	Debug nearest test	Global
Normal	Space tf	Run current file	Global
Normal	Space tn	Run nearest test	Global
Normal	Space to	Show test output	Global
Normal	Space ts	Toggle test summary	Global
Normal	Space tV	Fallback: run current file	Global
Normal	Space tv	Fallback: run nearest test	Global
Normal	Space tx	Stop test	Global

UI & Editing

Extracted from autopairs.lua, indent-blankline.lua.

Mode	Key	Action	Context
Normal	Space ua	Toggle autopairs	Global
Normal	Space ui	Toggle indent guides	Global
Normal	Space us	Toggle indent scope	Global

Workspaces & Sessions

Extracted from `auto-session.lua`.

Mode	Key	Action	Context
Normal	Space wr	Find session	Global
Normal	Space ws	Save session	Global