

Neovim Dark Complete Atlas

Generated from `/tmp/hermes-dotfiles-main/nvim` on 2026-09-03. Leader key is shown as `Space`. Search this PDF/HTML with Ctrl-F.

Context matters. “LSP buffer” maps exist only after a compatible language server attaches; Markdown/NvimTree maps require those buffers/plugins. Debug keys require configured adapters (debugpy, js-debug-adapter, delve, codelldb, or netcoredbg).

Beginner flow

Move
motions: w, b, f, /

Select
v, V, Ctrl-v or text objects

Act
d, c, y, >, =

Repeat / Undo
. repeats; u undoes; Ctrl-r redoes

Vim / Neovim Essentials

Mode / context	Key	Action	Source
Normal	<code>h j k l</code>	Move left / down / up / right	Built-in
Normal	<code>w b e</code>	Next word / previous word / end of word	Built-in
Normal	<code>0 ^ \$</code>	Line start / first nonblank / line end	Built-in
Normal	<code>gg G</code>	First line / last line	Built-in
Normal	<code>f{char} ; ,</code>	Find character / repeat forward / repeat backward	Built-in
Normal	<code>d c y</code>	Delete / change / yank; combine with a motion or text object	Built-in
Normal	<code>ciw daw yi"</code>	Change inner word / delete a word / yank inside quotes	Built-in
Visual	<code>v V Ctrl-v</code>	Character / line / block selection	Built-in
Normal	<code>u Ctrl-r</code>	Undo / redo	Built-in
Normal	<code>/ ? n N</code>	Search forward/backward; next/previous result	Built-in
Command	<code>:s/old/new/g</code>	Substitute in the current line; add % for file-wide	Built-in
Normal	<code>:w :q :wq</code>	Write / quit / write and quit	Built-in
Normal	<code>:e {file} :b {buf}</code>	Edit file / switch buffer	Built-in
Normal	<code>Ctrl-w h j k l</code>	Move between split windows	Built-in

Mode / context	Key	Action	Source
Normal	za zc zo	Toggle / close / open fold	Built-in
Normal	m{a} '{a}	Set mark / jump to mark line	Built-in
Normal	q{a} q @a @@	Record macro / stop / run / repeat	Built-in
Normal	]s [s z=	Next misspelling / previous / suggestions	Built-in
Insert	Ctrl-n Ctrl-p	Built-in next / previous completion candidate	Built-in
Insert	Ctrl-y Ctrl-e	Accept / cancel built-in completion	Built-in

Debugging, Testing, LSP Completion, and Diagnostics

Mode / context	Key	Action	Source
Normal	Space f f	Find files	Telescope
Normal	Space f g	Find text (live grep)	Telescope
Normal	Space n t	Toggle NvimTree	NvimTree
Normal, Markdown buffer	Space m p	Toggle Markdown preview	Markview
Normal	Space g c	Search Git commits	Telescope
Normal	Space d b	Toggle breakpoint	nvim-dap
Normal	Space d B	Set conditional breakpoint	nvim-dap
Normal	Space d c	Continue / start debugger	nvim-dap
Normal	Space d p	Pause debug session	nvim-dap
Normal	Space d i / d o / d 0	Step into / over / out	nvim-dap
Normal	Space d r / d q	Restart / terminate debug session	nvim-dap
Normal	Space d u / d v	Toggle DAP UI / virtual text	nvim-dap
Normal	Space d e	Evaluate expression	nvim-dap
Normal	Space t n	Run nearest test	Neotest
Normal	Space t f	Run tests in current file	Neotest
Normal	Space t a	Run test suite	Neotest
Normal	Space t d	Debug nearest test through DAP	Neotest
Normal	Space t s / t o / t x	Toggle summary / show output / stop test	Neotest
Normal	Space t v / t V / t A	vim-test fallback: nearest / file / suite	vim-test
Normal, LSP buffer	Space l c	Toggle automatic LSP completion	LSP
Insert, LSP buffer	Ctrl-Space	Trigger LSP completion manually	LSP
Normal, LSP buffer	Space l f	Format buffer	LSP
Normal	[d /] d	Previous / next diagnostic	LSP diagnostics
Normal	Space l d	Show diagnostic in a floating window	LSP diagnostics

Current Custom Mapping Inventory (source extracted)

Mode / context	Key	Action	Source
Normal	<code>rmagatti/auto-session</code>	Find session	auto-session
Normal	<code>Space ws</code>	Save session	auto-session
Normal	<code>windwp/nvim-autopairs</code>	Toggle autopairs	autopairs
Normal	<code>akinsho/bufferline.nvim</code>	Previous buffer	bufferlines
Normal	<code>Shift-l></code>	Next buffer	bufferlines
Normal	<code>Space bp</code>	Pick buffer	bufferlines
Normal	<code>Space bd</code>	Close buffer	bufferlines
Normal	<code>lewis6991/gitsigns.nvim</code>	Next hunk	gitsigns
Normal	<code>[h</code>	Previous hunk	gitsigns
Normal	<code>Space hs</code>	Stage hunk	gitsigns
Normal	<code>Space hr</code>	Reset hunk	gitsigns
Normal	<code>Space hs</code>	Stage selection	gitsigns
Normal	<code>Space hr</code>	Reset selection	gitsigns
Normal	<code>Space hS</code>	Stage buffer	gitsigns
Normal	<code>Space hR</code>	Reset buffer	gitsigns
Normal	<code>Space hU</code>	Unstage buffer	gitsigns
Normal	<code>Space hp</code>	Preview hunk	gitsigns
Normal	<code>Space hi</code>	Preview hunk inline	gitsigns
Normal	<code>Space hb</code>	Blame line	gitsigns
Normal	<code>Space hB</code>	Toggle line blame	gitsigns
Normal	<code>Space uw</code>	Toggle Git word diff	gitsigns
Normal	<code>Space hd</code>	Diff against index	gitsigns
Normal	<code>Space hD</code>	Diff against HEAD	gitsigns
Normal	<code>Space hq</code>	Hunks to quickfix	gitsigns
Normal	<code>Space hQ</code>	Repository hunks to quickfix	gitsigns
Normal	<code>Space hL</code>	Hunks to location list	gitsigns
Normal	<code>ih</code>	Select hunk	gitsigns
Normal	<code>lukas-reineke/indent-blankline.nvim</code>	Toggle indent guides	indent-blankline

Mode / context	Key	Action	Source
Normal	Space us	Toggle indent scope	indent-blankline
Normal	Space lg	LazyGit dashboard	lazygit
Normal	Space lG	LazyGit current file	lazygit
Normal	Space lL	LazyGit repository log	lazygit
Normal	Space ll	LazyGit file log	lazygit
Normal	cs	Refresh C# code lenses	lsp
Normal	Space lf	conform	lsp
Normal	n	Toggle task	markdown
Normal	Space mT	lint	markdown
Normal	nvim-tree/nvim-tree.lua	Toggle nvim-tree	nvimtree
Normal	Space nn	Focus nvim-tree	nvimtree
Normal	Space nf	Reveal current file	nvimtree
Normal	Space nr	Refresh nvim-tree	nvimtree
Normal	Space nc	Collapse nvim-tree	nvimtree
Normal	Space ne	Expand nvim-tree	nvimtree
Normal	nvim-lua/plenary.nvim	Find files	telescope
Normal	Space fg	Find text	telescope
Normal	Space fw	Find word under cursor	telescope
Normal	Space fb	Find buffers	telescope
Normal	Space fr	Find recent files	telescope
Normal	Space fh	Find help	telescope
Normal	Space fk	Find keymaps	telescope
Normal	Space fd	Find diagnostics	telescope
Normal	Space f/	Find in buffer	telescope
Normal	Space fR	Resume last picker	telescope
Normal	Space fp	Find project	telescope
Normal	Space gc	Git commits	telescope
Normal	Space gb	Git branches	telescope
Normal	Space gs	Git status	telescope
Normal	folke/todo-comments.nvim	Next todo comment	todo-comments
Normal	[t	Previous todo comment	todo-comments

Mode / context	Key	Action	Source
Normal	Space ft	Find todo comments	todo-comments
Normal	Space fT	Todo comments to quickfix	todo-comments
Normal	Space fL	Todo comments to location list	todo-comments
Normal	Space ?	Buffer Local Keymaps (which-key)	which-key
Normal	F2	Toggle line numbers	remap
Normal	F3	Toggle relative line numbers	remap
Normal	Space nh	Clear search highlights	remap

Test and Debug Management

Tests: Neotest supplies nearest/file/suite execution, summary, output, stop, and a DAP strategy. It configures Python, Go, Rust, Vitest, Jest, CTest, .NET, and a vim-test fallback. **Debug:** nvim-dap auto-opens DAP UI on initialization and closes it when a session ends; breakpoints, stepping, evaluation, and virtual text are mapped above.

Completion: **Space l c** changes the current LSP buffer's autotrigger setting. **Ctrl-Space** requests completion when it is enabled. Built-in completion controls remain available independently.

Generated by `nvim/scripts/regenerate-keymap-atlas.py`. Regenerate after changing mappings; commit both this script and `nvim/docs/Nvim-Dark-Complete-Atlas.pdf` when publishing.