

# Neovim Complete Field Guide

A practical, searchable map of the Vim language and the mappings declared in this checkout. Every custom row below is rebuilt from the current Lua configuration—new or changed keys replace the old documentation.

## 1 Find

Space f f opens files; Space f g searches project text.

## 2 Move

w / b move by word; / then n searches; gg / G jump in a file.

## 3 Change

Use operator + object: ciw changes a word, daw deletes a word.

## 4 Check

Space l f formats an LSP buffer; :w saves; Space l g opens LazyGit.

**How to read this:** Space f f means press Space, then f, then f. Context labels identify keys that only appear in Markdown, NvimTree, dashboard, or LSP-attached buffers.

Runtime cross-check: global 160, Markdown buffer 37, NvimTree buffer 74; LSP clients attached 0: 271 described runtime mappings observed. The source inventory is the published command truth; runtime data is used as a cross-check.

# Move precisely, then act

## Character, line & screen

|                      |                                             |
|----------------------|---------------------------------------------|
| <b>h j k l</b>       | Left, down, up, right.                      |
| <b>0 ^ \$</b>        | Line start / first nonblank / line end.     |
| <b>H M L</b>         | Top / middle / bottom visible screen line.  |
| <b>Ctrl-u Ctrl-d</b> | Half-page up / down.                        |
| <b>zt zz zb</b>      | Place cursor line at top / center / bottom. |

## Words, paragraphs & file

|                      |                                                   |
|----------------------|---------------------------------------------------|
| <b>w b e</b>         | Next word start / previous word start / word end. |
| <b>W B E</b>         | Same by whitespace-separated WORD.                |
| <b>{ }</b>           | Previous / next paragraph.                        |
| <b>gg G</b>          | First / last line of the file.                    |
| <b>:42 42G</b>       | Go to line 42.                                    |
| <b>%</b>             | Jump between matching delimiters.                 |
| <b>Ctrl-o Ctrl-i</b> | Older / newer jump location.                      |

## Find on one line

|                |                                                          |
|----------------|----------------------------------------------------------|
| <b>f x F x</b> | Find character x forward / backward; land on it.         |
| <b>t x T x</b> | Move until just before x, forward / backward.            |
| <b>; ,</b>     | Repeat the latest find in the same / opposite direction. |
| <b>* #</b>     | Search word under cursor forward / backward.             |

Counts repeat the next command: 3w moves three words; 5dd deletes five lines; d2j deletes the current plus next two lines; 2ci( changes inside the next two parenthesized areas.

## Your current configuration

| Key               | Action                           | Context |
|-------------------|----------------------------------|---------|
| <b>&lt;F2&gt;</b> | Toggle line numbers              | Global  |
| <b>&lt;F3&gt;</b> | Toggle relative line numbers     | Global  |
| <b>Space ?</b>    | Buffer Local Keymaps (which-key) | Global  |
| <b>Space nh</b>   | Clear search highlights          | Global  |

Operators: the verbs

|          |                                               |
|----------|-----------------------------------------------|
| d        | Delete (also copies to a register).           |
| c        | Change: delete, then enter Insert mode.       |
| y        | Yank: copy to a register.                     |
| > <      | Indent right / left; add = to auto-indent.    |
| g~ gu gU | Toggle case / lower / upper.                  |
| =        | Auto-format indentation using filetype rules. |

Text objects: the nouns

|          |                                                |
|----------|------------------------------------------------|
| iw aw    | Inner word / word including surrounding space. |
| i" a"    | Inside quotes / quotes plus contents.          |
| i( i[ i{ | Inside parentheses / brackets / braces.        |
| a( a[ a{ | Object including delimiters.                   |
| ip ap    | Inner paragraph / paragraph plus blank space.  |

Insert, paste & repeat

|          |                                                   |
|----------|---------------------------------------------------|
| i I a A  | Insert at cursor / first text; append / line end. |
| o O      | Open a line below / above and insert.             |
| p P      | Paste after / before cursor or line.              |
| u Ctrl-r | Undo / redo.                                      |
| .        | Repeat the last change.                           |

Read keys as a sentence: dw deletes to the next word; ci" changes inside quotes; ya( copies parentheses and contents. Fast line forms: dd, cc, yy, >>.

Your current configuration

| Key      | Action               | Context |
|----------|----------------------|---------|
| Space ua | Toggle autopairs     | Global  |
| Space ui | Toggle indent guides | Global  |
| Space us | Toggle indent scope  | Global  |

### Search within this file

|                                           |                                                 |
|-------------------------------------------|-------------------------------------------------|
| <code>/text Enter</code>                  | Search forward /                                |
| <code>?text Enter</code>                  | backward.                                       |
| <code>n</code> <code>N</code>             | Next / previous match.                          |
| <code>:noh</code>                         | Clear highlighting, not the search pattern.     |
| <code>/\cword</code> <code>/\Cword</code> | Force case-insensitive / case-sensitive search. |
| <code>/\Vliteral</code>                   | Search punctuation literally.                   |
| <code>q/</code>                           | Open editable search history.                   |

### Substitute

|                                         |                                                         |
|-----------------------------------------|---------------------------------------------------------|
| <code>:s/old/new/</code>                | Replace first match on this line.                       |
| <code>:s/old/new/g</code>               | Replace every match on this line.                       |
| <code>:%s/old/new/gc</code>             | Whole file: replace all and confirm each.               |
| <code>:'&lt;,'&gt;s/old/new/g</code>    | Replace only the current visual selection.              |
| <code>&amp;</code> <code>:%&amp;</code> | Repeat the latest substitute on this line / whole file. |

### Help & recovery

|                                                                   |                                          |
|-------------------------------------------------------------------|------------------------------------------|
| <code>:help {topic}</code>                                        | Open built-in documentation.             |
| <code>:map</code> <code>:nmap</code> <code>:imap</code>           | Inspect mappings by mode.                |
| <code>:checkhealth</code>                                         | Diagnose Neovim, providers, and plugins. |
| <code>:messages</code>                                            | Show recent notifications and errors.    |
| <code>:w</code> <code>:q</code> <code>:wq</code> <code>:q!</code> | Save / quit / save+quit / force quit.    |

Your setup uses ignorecase + smartcase: lowercase searches ignore case; adding any capital makes the search case-sensitive.

Your current configuration

| Key                   | Action                | Context |
|-----------------------|-----------------------|---------|
| <code>[t</code>       | Previous todo comment | Global  |
| <code>]t</code>       | Next todo comment     | Global  |
| <code>Space f/</code> | Find in buffer        | Global  |
| <code>Space fb</code> | Find buffers          | Global  |
| <code>Space fd</code> | Find diagnostics      | Global  |
| <code>Space ff</code> | Find files            | Global  |

Neovim Field Guide • Ctrl-F searchable • source-driven regeneration

# Buffers, windows, tabs & lists

## Buffers

|                       |                       |                                                      |
|-----------------------|-----------------------|------------------------------------------------------|
| <code>:ls</code>      | <code>:buffers</code> | List open buffers.                                   |
| <code>:b name</code>  |                       | Switch by partial buffer name.                       |
| <code>:bnext</code>   | <code>:bprev</code>   | Next / previous buffer.                              |
| <code>:bdelete</code> |                       | Close buffer without necessarily closing its window. |

## Windows

|                             |                      |                                           |
|-----------------------------|----------------------|-------------------------------------------|
| <code>:split</code>         | <code>:vsplit</code> | Horizontal / vertical split.              |
| <code>Ctrl-w h/j/k/l</code> |                      | Move focus between splits.                |
| <code>Ctrl-w c</code>       |                      | Close current / keep only current window. |
| <code>Ctrl-w o</code>       |                      |                                           |
| <code>Ctrl-w =</code>       |                      | Equalize split sizes.                     |

## Tabs, folds & lists

|                      |                     |                 |                                           |
|----------------------|---------------------|-----------------|-------------------------------------------|
| <code>:tabnew</code> | <code>gt</code>     | <code>gT</code> | New tab page / next / previous tab.       |
| <code>za</code>      | <code>zR</code>     | <code>zM</code> | Toggle fold / open all / close all.       |
| <code>:copen</code>  | <code>:cnext</code> |                 | Open quickfix / next project-wide result. |
| <code>:lopen</code>  |                     |                 | Open location list for this window.       |

Use Space f f for file names, Space f g for project text, / for the current file, and Space f / for fuzzy filtering inside the current buffer.

## Your current configuration

| Key                   | Action          | Context |
|-----------------------|-----------------|---------|
| <code>Shift-h</code>  | Previous buffer | Global  |
| <code>Shift-l</code>  | Next buffer     | Global  |
| <code>Space bd</code> | Close buffer    | Global  |
| <code>Space bp</code> | Pick buffer     | Global  |
| <code>Space wr</code> | Find session    | Global  |
| <code>Space ws</code> | Save session    | Global  |

# Git, diagnostics, LSP & completion

## Choose the right Git tool

|                    |                                                              |
|--------------------|--------------------------------------------------------------|
| <b>Space h ...</b> | Act on one changed hunk: stage, reset, preview, blame, diff. |
| <b>Space g ...</b> | Find Git information through Telescope.                      |
| <b>Space l g</b>   | Open the full LazyGit workflow.                              |

## Diagnostics & language features

|                  |                                                           |
|------------------|-----------------------------------------------------------|
| <b>[d ]d</b>     | Previous / next diagnostic; read its message.             |
| <b>Space l d</b> | Show the full diagnostic at the cursor.                   |
| <b>Space l f</b> | Format the current LSP buffer; Markdown can use Prettier. |
| <b>Space l i</b> | Toggle inlay hints when the server supports them.         |

## Completion & snippets

|                      |                                                                          |
|----------------------|--------------------------------------------------------------------------|
| <b>Tab Shift-Tab</b> | Jump forward / backward through an active snippet; otherwise type a tab. |
| <b>Ctrl-n Ctrl-p</b> | Next / previous built-in completion candidate.                           |
| <b>Ctrl-y Ctrl-e</b> | Accept / cancel a built-in completion candidate.                         |
| <b>Ctrl-x Ctrl-o</b> | Request omnifunc completion where supported.                             |

Diagnostic means an editor-reported error, warning, or hint. LSP is the language-aware engine that supplies diagnostics, formatting, completion, navigation, and more.

## Your current configuration

| Key             | Action            | Context |
|-----------------|-------------------|---------|
| <b>[h</b>       | Previous hunk     | Global  |
| <b>]h</b>       | Next hunk         | Global  |
| <b>ih</b>       | Select hunk       | Global  |
| <b>ih</b>       | Select hunk       | Global  |
| <b>Space hB</b> | Toggle line blame | Global  |
| <b>Space hb</b> | Blame line        | Global  |

# Markdown, TODOs & writing tools

## Markdown workflow

|                 |                                                                                          |
|-----------------|------------------------------------------------------------------------------------------|
| Preview         | Rendered, hybrid, or split preview helps read while editing.                             |
| Links           | Follow the current link or move through nearby links.                                    |
| Tables & tasks  | Format a table or toggle a task checkbox.                                                |
| Writing hygiene | Project spell words, format-on-save, table mode, and linting are configured per project. |

## TODO discovery

|                           |                                                                                            |
|---------------------------|--------------------------------------------------------------------------------------------|
| TODO<br>FIXME<br>HACK     | Use clear comment markers so they are searchable.                                          |
| Quickfix<br>location list | Send discovered TODOs to a navigable list.                                                 |
| Autopairs                 | Matching delimiters are configurable and intentionally disabled in picker/commit contexts. |

Markdown buffers automatically enable US English spell checking, soft wrapping, line breaks, and break indentation in this setup.

## Your current configuration

| Key      | Action                | Context |
|----------|-----------------------|---------|
| Space ma | Toggle format on save | Global  |
| Space mc | Toggle task           | Global  |
| Space mc | Toggle task           | Global  |
| Space md | Lint Markdown         | Global  |
| Space mF | Unfold section        | Global  |
| Space mf | Fold section          | Global  |

# Registers, visual mode & block edits

## Registers: where copied text lives

|                   |                                                                              |
|-------------------|------------------------------------------------------------------------------|
| <code>"0</code>   | Latest yank; <code>"Op</code> pastes the last copied text.                   |
| <code>"+</code>   | System clipboard in this setup.                                              |
| <code>"a</code>   | Named register: <code>"ayy</code> stores a line; <code>"ap</code> pastes it. |
| <code>"_</code>   | Black-hole register: delete without replacing the clipboard.                 |
| <code>:reg</code> | Inspect copied text and registers.                                           |

## Visual mode

|                                |                                                                              |
|--------------------------------|------------------------------------------------------------------------------|
| <code>v</code> <code>V</code>  | Select characters / whole lines, then use an operator.                       |
| <code>Ctrl-v</code>            | Select a rectangle; <code>I</code> inserts on every selected line after Esc. |
| <code>gv</code>                | Reselect the previous visual selection.                                      |
| <code>~</code>                 | Swap selected text's case.                                                   |
| <code>J</code> <code>gJ</code> | Join lines with / without adding a space.                                    |

Your configuration uses `unnamedplus`, so ordinary yank, delete, and paste already share the system clipboard.

## Your current configuration

| Key                   | Action               | Context |
|-----------------------|----------------------|---------|
| <code>Space ua</code> | Toggle autopairs     | Global  |
| <code>Space ui</code> | Toggle indent guides | Global  |
| <code>Space us</code> | Toggle indent scope  | Global  |



# Sessions, dashboard & personal display

### Sessions

|                      |                                                                                     |
|----------------------|-------------------------------------------------------------------------------------|
| <b>Find session</b>  | Restore a saved workspace.                                                          |
| <b>Save session</b>  | Persist the current layout and buffers.                                             |
| <b>What is saved</b> | Buffers, layout, current directory, terminals, folds, tab pages, and local options. |

### Dashboard

|                                                          |                                                          |
|----------------------------------------------------------|----------------------------------------------------------|
| <b>New file</b>                                          | Start an empty editing buffer.                           |
| <b>File</b> <b>recent</b><br><b>text</b> <b>projects</b> | Start common Telescope workflows from the dashboard.     |
| <b>Explorer</b><br><b>sessions</b><br><b>LazyGit</b>     | Open a workspace tool before entering an editing buffer. |
| <b>Plugin manager</b><br><b>quit</b>                     | Maintain plugins or exit Neovim.                         |

### Personal display

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>F2</b> <b>F3</b>       | Toggle absolute / relative line numbers.        |
| <b>Clear highlighting</b> | Remove the visual highlight of the last search. |
| <b>Indent guides</b>      | Toggle indentation and its scope highlight.     |
| <b>Autopairs</b>          | Toggle automatic bracket and quote pairing.     |

Dashboard shortcuts are intentionally context-labeled in the generated appendix: use them from the Alpha start screen, not from an editing buffer.

## Your current configuration

| Key       | Action                 | Context          |
|-----------|------------------------|------------------|
| <b>e</b>  | Start a new empty file | Dashboard buffer |
| <b>ff</b> | Find files             | Dashboard buffer |
| <b>fk</b> | Find keymaps           | Dashboard buffer |
| <b>fp</b> | Switch projects        | Dashboard buffer |
| <b>fr</b> | Open recent files      | Dashboard buffer |
| <b>fs</b> | Search project text    | Dashboard buffer |

# Testing, debugging & code navigation

## Testing loop

|                              |                                               |
|------------------------------|-----------------------------------------------|
| <b>Run nearest test</b>      | Start with the test closest to the cursor.    |
| <b>Run file</b> <b>suite</b> | Widen scope after the nearest test is useful. |
| <b>Test output</b>           | Open output when a result needs diagnosis.    |
| <b>Toggle summary</b>        | Keep test state visible while editing.        |

## Debugging loop

|                                         |                                                          |
|-----------------------------------------|----------------------------------------------------------|
| <b>Toggle breakpoint</b>                | Mark the next place execution should pause.              |
| <b>Continue</b>                         | Run to the next breakpoint.                              |
| <b>Step over</b> <b>into</b> <b>out</b> | Move through execution without losing the current state. |
| <b>Inspect UI</b>                       | Open debugger panels for variables, stack, and console.  |

## Code navigation

|                                     |                                                             |
|-------------------------------------|-------------------------------------------------------------|
| <b>Definition</b> <b>references</b> | Jump to where a symbol is defined or used.                  |
| <b>Rename</b>                       | Apply a language-aware rename through the LSP.              |
| <b>Code action</b>                  | See available fixes and refactors.                          |
| <b>Diagnostics</b>                  | Move through editor-reported problems before changing code. |

The complete appendix has the exact current keys. This page teaches the workflow first so it remains useful even when those keys evolve.

## Your current configuration

| Key             | Action                   | Context |
|-----------------|--------------------------|---------|
| <b>Space tA</b> | Fallback: run test suite | Global  |
| <b>Space ta</b> | Run test suite           | Global  |
| <b>Space td</b> | Debug nearest test       | Global  |
| <b>Space tf</b> | Run current file         | Global  |
| <b>Space tn</b> | Run nearest test         | Global  |
| <b>Space to</b> | Show test output         | Global  |

# Ctrl+F index

Search this PDF for an exact key string or an ordinary word. The guide repeats literal keys in the teaching sections and keeps a complete generated appendix after them.

## Files & project navigation

find files, project text, recent files, buffers, help, keymaps, explorer

## Editing

change, delete, copy, paste, repeat, register, text object, visual block

## Code help

diagnostic, format, completion, inlay hint, LSP, snippet

## Git

hunk, stage, reset, blame, diff, branch, commit, LazyGit

## Writing

Markdown, link, preview, table, spell, TODO, lint

**Discover anything else:** Space f k opens searchable active keymaps. `:help` keyword explains built-ins; `:map`, `:nmap`, and `:imap` inspect mappings directly; `:checkhealth` diagnoses the setup.

# Configured Tooling

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin           | What it enables                                                | Configuration source |
|-------------------------|----------------------------------------------------------------|----------------------|
| DAP adapter: codelldb   | Connects Neovim's debugging controls to this language/runtime. | dap.lua              |
| DAP adapter: debugpy    | Connects Neovim's debugging controls to this language/runtime. | dap.lua              |
| DAP adapter: delve      | Connects Neovim's debugging controls to this language/runtime. | dap.lua              |
| DAP adapter: netcoredbg | Connects Neovim's debugging controls to this language/runtime. | dap.lua              |
| Executable: codelldb    | External command used by a configured editor integration.      | dap.lua              |
| Executable: dlvsym      | External command used by a configured editor integration.      | dap.lua              |
| Executable: magick      | External command used by a configured editor integration.      | image.lua            |
| Executable: nvr         | External command used by a configured editor integration.      | set.lua              |
| Executable: python      | External command used by a configured editor integration.      | dap.lua              |
| Executable: python3     | External command used by a configured editor integration.      | dap.lua              |
| Executable: uv          | External command used by a configured editor integration.      | neotest.lua          |

# Configured Tooling - part 2 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin                           | What it enables                                                                                   | Configuration source |
|-----------------------------------------|---------------------------------------------------------------------------------------------------|----------------------|
| Formatter: prettier                     | Rewrites source into the project's configured formatting style.                                   | markdown.lua         |
| Linters: markdownlint-cli2              | Checks source for style, correctness, or writing issues.                                          | markdown.lua         |
| LSP server: basedpyright                | Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached. | lsp.lua              |
| LSP server: jsonls                      | Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached. | lsp.lua              |
| LSP server: lua_ls                      | Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached. | lsp.lua              |
| LSP server: roslyn_ls                   | Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached. | lsp.lua              |
| LSP server: yamlls                      | Adds language-aware diagnostics, navigation, completion, formatting, and refactors when attached. | lsp.lua              |
| Plugin: 3rd/image.nvim                  | Display supported images inline in Neovim when the terminal graphics backend is available.        | image.lua            |
| Plugin: akinsho/bufferline.nvim         | Show open buffers as a navigable tab-like strip.                                                  | bufferlines.lua      |
| Plugin: akinsho/neotest-go              | Run tests, inspect output, and debug a test through DAP.                                          | neotest.lua          |
| Plugin: antoinemadec/FixCursorHold.nvim | Configured integration; use its matching mapping or command in this guide.                        | neotest.lua          |

# Configured Tooling · part 3 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin                                        | What it enables                                                                        | Configuration source              |
|------------------------------------------------------|----------------------------------------------------------------------------------------|-----------------------------------|
| Plugin: <a href="#">b0o/SchemaStore.nvim</a>         | Configured integration; use its matching mapping or command in this guide.             | <a href="#">lsp.lua</a>           |
| Plugin: <a href="#">CollinRobison/neotest-dotnet</a> | Run tests, inspect output, and debug a test through DAP.                               | <a href="#">neotest.lua</a>       |
| Plugin: <a href="#">folke/todo-comments.nvim</a>     | Recognize TODO-style annotations and make them searchable through lists and Telescope. | <a href="#">todo-comments.lua</a> |
| Plugin: <a href="#">folke/tokyonight.nvim</a>        | Configured integration; use its matching mapping or command in this guide.             | <a href="#">tokyonight.lua</a>    |
| Plugin: <a href="#">folke/which-key.nvim</a>         | Display available keybinding continuations after a key prefix.                         | <a href="#">which-key.lua</a>     |
| Plugin: <a href="#">goolord/alpha-nvim</a>           | Show a start dashboard with shortcuts for files, projects, sessions, Git, and plugins. | <a href="#">alpha.lua</a>         |
| Plugin: <a href="#">haydenmeade/neotest-jest</a>     | Run tests, inspect output, and debug a test through DAP.                               | <a href="#">neotest.lua</a>       |
| Plugin: <a href="#">jakewvincent/mkdnflow.nvim</a>   | Follow links, manage tasks, tables, headings, and Markdown navigation.                 | <a href="#">markdown.lua</a>      |
| Plugin: <a href="#">jay-babu/mason-nvim-dap.nvim</a> | Pause a program, step through execution, and inspect debugger state.                   | <a href="#">mason-tools.lua</a>   |
| Plugin: <a href="#">kdheepak/lazygit.nvim</a>        | Open a terminal Git interface for status, commits, branches, and logs.                 | <a href="#">lazygit.lua</a>       |
| Plugin: <a href="#">lewis6991/gitsigns.nvim</a>      | Navigate, preview, stage, reset, and blame changed Git hunks.                          | <a href="#">gitsigns.lua</a>      |

# Configured Tooling - part 4 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin                                            | What it enables                                                                        | Configuration source              |
|----------------------------------------------------------|----------------------------------------------------------------------------------------|-----------------------------------|
| Plugin: <code>lukas-reineke/indent-blankline.nvim</code> | Draw indentation guides and optionally highlight the current scope.                    | <code>indent-blankline.lua</code> |
| Plugin: <code>marilari88/neotest-vitest</code>           | Run tests, inspect output, and debug a test through DAP.                               | <code>neotest.lua</code>          |
| Plugin: <code>mason-org/mason-lspconfig.nvim</code>      | Install and manage external language servers, formatters, linters, and debug adapters. | <code>mason-tools.lua</code>      |
| Plugin: <code>mason-org/mason-lspconfig.nvim</code>      | Install and manage external language servers, formatters, linters, and debug adapters. | <code>lsp.lua</code>              |
| Plugin: <code>mason-org/mason.nvim</code>                | Install and manage external language servers, formatters, linters, and debug adapters. | <code>mason-tools.lua</code>      |
| Plugin: <code>mfussenegger/nvim-dap</code>               | Pause a program, step through execution, and inspect debugger state.                   | <code>dap.lua</code>              |
| Plugin: <code>mfussenegger/nvim-lint</code>              | Configured integration; use its matching mapping or command in this guide.             | <code>markdown.lua</code>         |
| Plugin: <code>neovim/nvim-lspconfig</code>               | Configured integration; use its matching mapping or command in this guide.             | <code>lsp.lua</code>              |
| Plugin: <code>nvim-lua/plenary.nvim</code>               | Configured integration; use its matching mapping or command in this guide.             | <code>lazygit.lua</code>          |
| Plugin: <code>nvim-lua/plenary.nvim</code>               | Configured integration; use its matching mapping or command in this guide.             | <code>todo-comments.lua</code>    |
| Plugin: <code>nvim-lua/plenary.nvim</code>               | Configured integration; use its matching mapping or command in this guide.             | <code>telescope.lua</code>        |

# Configured Tooling - part 5 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin                                    | What it enables                                                             | Configuration source |
|--------------------------------------------------|-----------------------------------------------------------------------------|----------------------|
| Plugin: nvim-lualine/lualine.nvim                | Show file, Git, diagnostic, mode, and status information in the statusline. | lualine.lua          |
| Plugin: nvim-mini/mini.icons                     | Provide compact file-type icons to Neovim UI integrations.                  | mini-icon.lua        |
| Plugin: nvim-neotest/neotest                     | Run tests, inspect output, and debug a test through DAP.                    | neotest.lua          |
| Plugin: nvim-neotest/neotest-python              | Run tests, inspect output, and debug a test through DAP.                    | neotest.lua          |
| Plugin: nvim-neotest/neotest-vim-test            | Run tests, inspect output, and debug a test through DAP.                    | neotest.lua          |
| Plugin: nvim-neotest/nvim-nio                    | Run tests, inspect output, and debug a test through DAP.                    | dap.lua              |
| Plugin: nvim-neotest/nvim-nio                    | Run tests, inspect output, and debug a test through DAP.                    | neotest.lua          |
| Plugin: nvim-telescope/telescope-fzf-native.nvim | Search files, text, buffers, help, keymaps, and Git information.            | telescope.lua        |
| Plugin: nvim-telescope/telescope-project.nvim    | Search files, text, buffers, help, keymaps, and Git information.            | telescope.lua        |
| Plugin: nvim-telescope/telescope.nvim            | Search files, text, buffers, help, keymaps, and Git information.            | telescope.lua        |
| Plugin: nvim-tree/nvim-tree.lua                  | Browse files and reveal the current file in a tree.                         | nvimtree.lua         |



# Configured Tooling - part 6 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin                           | What it enables                                                      | Configuration source  |
|-----------------------------------------|----------------------------------------------------------------------|-----------------------|
| Plugin: nvim-tree/nvim-web-devicons     | Browse files and reveal the current file in a tree.                  | bufferlines.lua       |
| Plugin: nvim-tree/nvim-web-devicons     | Browse files and reveal the current file in a tree.                  | nvim-web-devicons.lua |
| Plugin: nvim-tree/nvim-web-devicons     | Browse files and reveal the current file in a tree.                  | nvimtree.lua          |
| Plugin: nvim-tree/nvim-web-devicons     | Browse files and reveal the current file in a tree.                  | luafile.lua           |
| Plugin: nvim-treesitter/nvim-treesitter | Browse files and reveal the current file in a tree.                  | image.lua             |
| Plugin: nvim-treesitter/nvim-treesitter | Browse files and reveal the current file in a tree.                  | nvim-treesitter.lua   |
| Plugin: orjangj/neotest-ctest           | Run tests, inspect output, and debug a test through DAP.             | neotest.lua           |
| Plugin: OXY2DEV/markview.nvim           | Render Markdown while you edit it.                                   | markdown.lua          |
| Plugin: rcarriga/nvim-dap-ui            | Pause a program, step through execution, and inspect debugger state. | dap.lua               |
| Plugin: rmagatti/auto-session           | Save and restore working layouts and open buffers.                   | auto-session.lua      |
| Plugin: rouge8/neotest-rust             | Run tests, inspect output, and debug a test through DAP.             | neotest.lua           |

# Configured Tooling - part 7 of 7

Declared integrations are listed even when they do not expose a direct user mapping.

| Tool / plugin                                        | What it enables                                                                          | Configuration source             |
|------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------------|
| Plugin: <code>stevearc/conform.nvim</code>           | Configured integration; use its matching mapping or command in this guide.               | <code>markdown.lua</code>        |
| Plugin: <code>textDocument/codeLens</code>           | Configured integration; use its matching mapping or command in this guide.               | <code>lsp.lua</code>             |
| Plugin: <code>textDocument/completion</code>         | Configured integration; use its matching mapping or command in this guide.               | <code>lsp.lua</code>             |
| Plugin: <code>textDocument/inlayHint</code>          | Configured integration; use its matching mapping or command in this guide.               | <code>lsp.lua</code>             |
| Plugin: <code>theHamsta/nvim-dap-virtual-text</code> | Pause a program, step through execution, and inspect debugger state.                     | <code>dap.lua</code>             |
| Plugin: <code>vague-theme/vague.nvim</code>          | Configured integration; use its matching mapping or command in this guide.               | <code>vague.lua</code>           |
| Plugin: <code>vim-test/vim-test</code>               | Configured integration; use its matching mapping or command in this guide.               | <code>neotest.lua</code>         |
| Plugin: <code>windwp/nvim-autopairs</code>           | Automatically insert and manage matching quotes, brackets, and parentheses while typing. | <code>autopairs.lua</code>       |
| Plugin: <code>windwp/nvim-ts-autotag</code>          | Configured integration; use its matching mapping or command in this guide.               | <code>nvim-treesitter.lua</code> |

# Commands & automatic behavior

Type these after `:` in Normal mode. The tooling inventory explains capabilities that happen automatically or do not have a direct keybinding.

| Command                           | What it does                                                   | Configuration source              |
|-----------------------------------|----------------------------------------------------------------|-----------------------------------|
| <code>:AutoSession</code>         | Save, search, or restore an editor workspace session.          | <code>alpha.lua</code>            |
| <code>:bdelete</code>             | Close the current buffer without quitting Neovim.              | <code>bufferlines.lua</code>      |
| <code>:BufferLineCycleNext</code> | Select the next buffer in the buffer line.                     | <code>bufferlines.lua</code>      |
| <code>:BufferLineCyclePrev</code> | Select the previous buffer in the buffer line.                 | <code>bufferlines.lua</code>      |
| <code>:BufferLinePick</code>      | Show letter labels so you can jump directly to an open buffer. | <code>bufferlines.lua</code>      |
| <code>:ene</code>                 | Open a new empty buffer.                                       | <code>alpha.lua</code>            |
| <code>:IBLToggle</code>           | Show or hide indentation guides.                               | <code>indent-blankline.lua</code> |
| <code>:IBLToggleScope</code>      | Show or hide the current indentation scope highlight.          | <code>indent-blankline.lua</code> |
| <code>:Lazy</code>                | Open the plugin manager.                                       | <code>alpha.lua</code>            |
| <code>:LazyGit</code>             | Open the terminal Git interface for the repository.            | <code>alpha.lua</code>            |

# Commands & automatic behavior · part 2 of 3

Type these after `:` in Normal mode. The tooling inventory explains capabilities that happen automatically or do not have a direct keybinding.

| Command                                 | What it does                                                    | Configuration source         |
|-----------------------------------------|-----------------------------------------------------------------|------------------------------|
| <code>:LazyGitCurrentFile</code>        | Open the terminal Git interface for the repository.             | <code>lazygit.lua</code>     |
| <code>:LazyGitFilter</code>             | Open the terminal Git interface for the repository.             | <code>lazygit.lua</code>     |
| <code>:LazyGitFilterCurrentFile</code>  | Open the terminal Git interface for the repository.             | <code>lazygit.lua</code>     |
| <code>:Markview</code>                  | Toggle rendered Markdown, hybrid view, or a preview split.      | <code>markdown.lua</code>    |
| <code>:MasonInstallDebugAdapters</code> | Install the debugger adapters configured for this Neovim setup. | <code>mason-tools.lua</code> |
| <code>:MkdnFoldSection</code>           | Fold the Markdown section at the cursor.                        | <code>markdown.lua</code>    |
| <code>:MkdnFollowLink</code>            | Open the Markdown link under the cursor.                        | <code>markdown.lua</code>    |
| <code>:MkdnNextLink</code>              | Jump to the next Markdown link.                                 | <code>markdown.lua</code>    |
| <code>:MkdnPrevLink</code>              | Jump to the previous Markdown link.                             | <code>markdown.lua</code>    |
| <code>:MkdnTableFormat</code>           | Align and format the Markdown table at the cursor.              | <code>markdown.lua</code>    |

# Commands & automatic behavior · part 3 of 3

Type these after `:` in Normal mode. The tooling inventory explains capabilities that happen automatically or do not have a direct keybinding.

| Command                         | What it does                                                                                        | Configuration source           |
|---------------------------------|-----------------------------------------------------------------------------------------------------|--------------------------------|
| <code>:MkdnToggleToDo</code>    | Toggle the Markdown task checkbox at the cursor.                                                    | <code>markdown.lua</code>      |
| <code>:MkdnUnfoldSection</code> | Unfold the Markdown section at the cursor.                                                          | <code>markdown.lua</code>      |
| <code>:NvimTreeToggle</code>    | Open or close the file explorer.                                                                    | <code>alpha.lua</code>         |
| <code>:qa</code>                | Quit all Neovim windows.                                                                            | <code>alpha.lua</code>         |
| <code>:Telescope</code>         | Open a searchable picker; the following argument selects files, text, help, Git, or another source. | <code>alpha.lua</code>         |
| <code>:TestFile</code>          | Run the configured test target (nearest test, file, or suite).                                      | <code>neotest.lua</code>       |
| <code>:TestNearest</code>       | Run the configured test target (nearest test, file, or suite).                                      | <code>neotest.lua</code>       |
| <code>:TestSuite</code>         | Run the configured test target (nearest test, file, or suite).                                      | <code>neotest.lua</code>       |
| <code>:TodoLocList</code>       | Collect TODO-style comments in the current window's location list.                                  | <code>todo-comments.lua</code> |
| <code>:TodoQuickFix</code>      | Collect TODO-style comments in the quickfix list.                                                   | <code>todo-comments.lua</code> |

# Buffers & Windows

Extracted from `bufferlines.lua`.

| Mode   | Key      | Action          | Context |
|--------|----------|-----------------|---------|
| Normal | Shift-h  | Previous buffer | Global  |
| Normal | Shift-l  | Next buffer     | Global  |
| Normal | Space bd | Close buffer    | Global  |
| Normal | Space bp | Pick buffer     | Global  |

# Dashboard

Extracted from `alpha.lua`.

| Mode   | Key             | Action                     | Context          |
|--------|-----------------|----------------------------|------------------|
| Normal | <code>e</code>  | Start a new empty file     | Dashboard buffer |
| Normal | <code>ff</code> | Find files                 | Dashboard buffer |
| Normal | <code>fk</code> | Find keymaps               | Dashboard buffer |
| Normal | <code>fp</code> | Switch projects            | Dashboard buffer |
| Normal | <code>fr</code> | Open recent files          | Dashboard buffer |
| Normal | <code>fs</code> | Search project text        | Dashboard buffer |
| Normal | <code>lg</code> | Open LazyGit               | Dashboard buffer |
| Normal | <code>nt</code> | Toggle file explorer       | Dashboard buffer |
| Normal | <code>p</code>  | Open plugin manager        | Dashboard buffer |
| Normal | <code>q</code>  | Quit Neovim                | Dashboard buffer |
| Normal | <code>ss</code> | Find and restore a session | Dashboard buffer |

# Debugging

Extracted from dap.lua.

| Mode   | Key                   | Action                  | Context |
|--------|-----------------------|-------------------------|---------|
| Normal | <span>Space dB</span> | Conditional breakpoint  | Global  |
| Normal | <span>Space db</span> | Toggle breakpoint       | Global  |
| Normal | <span>Space dc</span> | Continue                | Global  |
| Normal | <span>Space de</span> | Evaluate expression     | Global  |
| Normal | <span>Space di</span> | Step into               | Global  |
| Normal | <span>Space d0</span> | Step out                | Global  |
| Normal | <span>Space do</span> | Step over               | Global  |
| Normal | <span>Space dp</span> | Pause debug session     | Global  |
| Normal | <span>Space dq</span> | Terminate debug session | Global  |
| Normal | <span>Space dr</span> | Restart debug session   | Global  |
| Normal | <span>Space du</span> | Toggle DAP UI           | Global  |
| Normal | <span>Space dv</span> | Toggle DAP virtual text | Global  |



# Find & Navigate

Extracted from telescope.lua, todo-comments.lua.

| Mode   | Key      | Action                         | Context |
|--------|----------|--------------------------------|---------|
| Normal | [t]      | Previous todo comment          | Global  |
| Normal | ]t       | Next todo comment              | Global  |
| Normal | Space f/ | Find in buffer                 | Global  |
| Normal | Space fb | Find buffers                   | Global  |
| Normal | Space fd | Find diagnostics               | Global  |
| Normal | Space ff | Find files                     | Global  |
| Normal | Space fg | Find text                      | Global  |
| Normal | Space fh | Find help                      | Global  |
| Normal | Space fk | Find keymaps                   | Global  |
| Normal | Space fL | Todo comments to location list | Global  |

# Find & Navigate · part 2 of 2

Extracted from telescope.lua, todo-comments.lua.

| Mode   | Key             | Action                    | Context |
|--------|-----------------|---------------------------|---------|
| Normal | <b>Space fp</b> | Find project              | Global  |
| Normal | <b>Space fR</b> | Resume last picker        | Global  |
| Normal | <b>Space fr</b> | Find recent files         | Global  |
| Normal | <b>Space fT</b> | Todo comments to quickfix | Global  |
| Normal | <b>Space ft</b> | Find todo comments        | Global  |
| Normal | <b>Space fw</b> | Find word under cursor    | Global  |
| Normal | <b>Space gb</b> | Git branches              | Global  |
| Normal | <b>Space gc</b> | Git commits               | Global  |
| Normal | <b>Space gs</b> | Git status                | Global  |

Extracted from gitsigns.lua, lazygit.lua.

| Mode             | Key      | Action                       | Context |
|------------------|----------|------------------------------|---------|
| Normal           | [h       | Previous hunk                | Global  |
| Normal           | ]h       | Next hunk                    | Global  |
| Operator-pending | ih       | Select hunk                  | Global  |
| Visual           | ih       | Select hunk                  | Global  |
| Normal           | Space hB | Toggle line blame            | Global  |
| Normal           | Space hb | Blame line                   | Global  |
| Normal           | Space hD | Diff against HEAD            | Global  |
| Normal           | Space hd | Diff against index           | Global  |
| Normal           | Space hi | Preview hunk inline          | Global  |
| Normal           | Space hL | Hunks to location list       | Global  |
| Normal           | Space hp | Preview hunk                 | Global  |
| Normal           | Space hQ | Repository hunks to quickfix | Global  |
| Normal           | Space hq | Hunks to quickfix            | Global  |

# Git · part 2 of 2

Extracted from gitsigns.lua, lazygit.lua.

| Mode   | Key      | Action                 | Context |
|--------|----------|------------------------|---------|
| Normal | Space hR | Reset buffer           | Global  |
| Normal | Space hr | Reset hunk             | Global  |
| Visual | Space hr | Reset selection        | Global  |
| Normal | Space hS | Stage buffer           | Global  |
| Normal | Space hs | Stage hunk             | Global  |
| Visual | Space hs | Stage selection        | Global  |
| Normal | Space hU | Unstage buffer         | Global  |
| Normal | Space lG | LazyGit current file   | Global  |
| Normal | Space lg | LazyGit dashboard      | Global  |
| Normal | Space lL | LazyGit repository log | Global  |
| Normal | Space ll | LazyGit file log       | Global  |
| Normal | Space uw | Toggle Git word diff   | Global  |

# LSP, Completion & Diagnostics

Extracted from lsp.lua.

| Mode   | Key        | Action                 | Context                    |
|--------|------------|------------------------|----------------------------|
| Normal | [d]        | Previous diagnostic    | Global                     |
| Normal | ]d         | Next diagnostic        | Global                     |
| Normal | Space ld   | Show diagnostic        | Global                     |
| Insert | Ctrl-Space | Trigger LSP completion | LSP buffer (when attached) |
| Normal | Space lc   | Toggle LSP completion  | LSP buffer (when attached) |
| Normal | Space lf   | Format buffer          | LSP buffer (when attached) |
| Normal | Space li   | Toggle inlay hints     | LSP buffer (when attached) |
| Normal | Space lr   | Refresh C# code lenses | LSP buffer (when attached) |
| Normal | Space lt   | Run C# code lens       | LSP buffer (when attached) |

# Markdown

Extracted from markdown.lua.

| Mode   | Key      | Action                | Context |
|--------|----------|-----------------------|---------|
| Normal | Space ma | Toggle format on save | Global  |
| Normal | Space mc | Toggle task           | Global  |
| Visual | Space mc | Toggle task           | Global  |
| Normal | Space md | Lint Markdown         | Global  |
| Normal | Space mF | Unfold section        | Global  |
| Normal | Space mf | Fold section          | Global  |
| Normal | Space mh | Toggle hybrid preview | Global  |
| Normal | Space ml | Follow link           | Global  |
| Normal | Space mN | Previous link         | Global  |
| Normal | Space mn | Next link             | Global  |

# Markdown · part 2 of 2

Extracted from markdown.lua.

| Mode   | Key      | Action                         | Context         |
|--------|----------|--------------------------------|-----------------|
| Normal | Space mp | Toggle preview                 | Global          |
| Normal | Space ms | Toggle preview split           | Global          |
| Normal | Space mT | Toggle table mode              | Global          |
| Normal | Space mt | Format table                   | Global          |
| Normal | Space mW | Add all project spelling words | Global          |
| Normal | Space mw | Add project spelling word      | Global          |
| Normal | Enter    | Mkdnflow smart Enter           | Markdown buffer |
| Insert | Enter    | Mkdnflow smart Enter           | Markdown buffer |
| Visual | Enter    | Mkdnflow smart Enter           | Markdown buffer |

# NvimTree

Extracted from nvimtree.lua.

| Mode   | Key      | Action              | Context |
|--------|----------|---------------------|---------|
| Normal | Space nc | Collapse nvim-tree  | Global  |
| Normal | Space ne | Expand nvim-tree    | Global  |
| Normal | Space nf | Reveal current file | Global  |
| Normal | Space nn | Focus nvim-tree     | Global  |
| Normal | Space nr | Refresh nvim-tree   | Global  |
| Normal | Space nt | Toggle nvim-tree    | Global  |



# Personal Controls

Extracted from remap.lua, which-key.lua.

| Mode   | Key      | Action                           | Context |
|--------|----------|----------------------------------|---------|
| Normal | <F2>     | Toggle line numbers              | Global  |
| Normal | <F3>     | Toggle relative line numbers     | Global  |
| Normal | Space ?  | Buffer Local Keymaps (which-key) | Global  |
| Normal | Space nh | Clear search highlights          | Global  |

# Runtime-discovered keymaps

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key       | Action                           | Context |
|--------|-----------|----------------------------------|---------|
| Normal | <b>?</b>  | Buffer Local Keymaps (which-key) | Global  |
| Normal | <b>nc</b> | Collapse nvim-tree               | Global  |
| Normal | <b>nr</b> | Refresh nvim-tree                | Global  |
| Normal | <b>nf</b> | Reveal current file              | Global  |
| Normal | <b>nn</b> | Focus nvim-tree                  | Global  |
| Normal | <b>nt</b> | Toggle nvim-tree                 | Global  |
| Normal | <b>ne</b> | Expand nvim-tree                 | Global  |
| Normal | <b>de</b> | Evaluate expression              | Global  |
| Normal | <b>dv</b> | Toggle DAP virtual text          | Global  |
| Normal | <b>du</b> | Toggle DAP UI                    | Global  |
| Normal | <b>dq</b> | Terminate debug session          | Global  |
| Normal | <b>dr</b> | Restart debug session            | Global  |
| Normal | <b>d0</b> | Step out                         | Global  |
| Normal | <b>do</b> | Step over                        | Global  |
| Normal | <b>di</b> | Step into                        | Global  |

# Runtime-discovered keymaps · part 2 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key       | Action                 | Context |
|--------|-----------|------------------------|---------|
| Normal | <b>dp</b> | Pause debug session    | Global  |
| Normal | <b>dc</b> | Continue               | Global  |
| Normal | <b>dB</b> | Conditional breakpoint | Global  |
| Normal | <b>db</b> | Toggle breakpoint      | Global  |
| Normal | <b>fk</b> | Find keymaps           | Global  |
| Normal | <b>fh</b> | Find help              | Global  |
| Normal | <b>fr</b> | Find recent files      | Global  |
| Normal | <b>f/</b> | Find in buffer         | Global  |
| Normal | <b>fR</b> | Resume last picker     | Global  |
| Normal | <b>fp</b> | Find project           | Global  |
| Normal | <b>gc</b> | Git commits            | Global  |
| Normal | <b>gs</b> | Git status             | Global  |
| Normal | <b>gb</b> | Git branches           | Global  |
| Normal | <b>fb</b> | Find buffers           | Global  |
| Normal | <b>fw</b> | Find word under cursor | Global  |

# Runtime-discovered keymaps · part 3 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key       | Action                         | Context |
|--------|-----------|--------------------------------|---------|
| Normal | <b>fg</b> | Find text                      | Global  |
| Normal | <b>ff</b> | Find files                     | Global  |
| Normal | <b>fd</b> | Find diagnostics               | Global  |
| Normal | <b>wr</b> | Find session                   | Global  |
| Normal | <b>ws</b> | Save session                   | Global  |
| Normal | <b>bd</b> | Close buffer                   | Global  |
| Normal | <b>bp</b> | Pick buffer                    | Global  |
| Normal | <b>ui</b> | Toggle indent guides           | Global  |
| Normal | <b>us</b> | Toggle indent scope            | Global  |
| Normal | <b>ll</b> | LazyGit file log               | Global  |
| Normal | <b>lL</b> | LazyGit repository log         | Global  |
| Normal | <b>lG</b> | LazyGit current file           | Global  |
| Normal | <b>lg</b> | LazyGit dashboard              | Global  |
| Normal | <b>fT</b> | Todo comments to quickfix      | Global  |
| Normal | <b>fL</b> | Todo comments to location list | Global  |

# Runtime-discovered keymaps · part 4 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key       | Action                       | Context |
|--------|-----------|------------------------------|---------|
| Normal | <b>ft</b> | Find todo comments           | Global  |
| Normal | <b>hl</b> | Hunks to location list       | Global  |
| Normal | <b>hQ</b> | Repository hunks to quickfix | Global  |
| Normal | <b>hq</b> | Hunks to quickfix            | Global  |
| Normal | <b>hD</b> | Diff against HEAD            | Global  |
| Normal | <b>hd</b> | Diff against index           | Global  |
| Normal | <b>uw</b> | Toggle Git word diff         | Global  |
| Normal | <b>hB</b> | Toggle line blame            | Global  |
| Normal | <b>hb</b> | Blame line                   | Global  |
| Normal | <b>hi</b> | Preview hunk inline          | Global  |
| Normal | <b>hp</b> | Preview hunk                 | Global  |
| Normal | <b>hU</b> | Unstage buffer               | Global  |
| Normal | <b>hR</b> | Reset buffer                 | Global  |
| Normal | <b>hS</b> | Stage buffer                 | Global  |
| Normal | <b>hr</b> | Reset hunk                   | Global  |

# Runtime-discovered keymaps · part 5 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key            | Action                                      | Context |
|--------|----------------|---------------------------------------------|---------|
| Normal | <b>hs</b>      | Stage hunk                                  | Global  |
| Normal | <b>ua</b>      | Toggle autopairs                            | Global  |
| Normal | <b>&amp;</b>   | Vim built-in; see :help &-default           | Global  |
| Normal | <b>H</b>       | Previous buffer                             | Global  |
| Normal | <b>L</b>       | Next buffer                                 | Global  |
| Normal | <b>Y</b>       | Vim built-in; see :help Y-default           | Global  |
| Normal | <b>[</b>       | Add empty line above cursor                 | Global  |
| Normal | <b>[B</b>      | :brewind                                    | Global  |
| Normal | <b>[b</b>      | Switch to previous buffer                   | Global  |
| Normal | <b>[Ctrl-T</b> | :ptprevious                                 | Global  |
| Normal | <b>[T</b>      | :trewind                                    | Global  |
| Normal | <b>[A</b>      | Jump to the first item in the argument list | Global  |
| Normal | <b>[a</b>      | Jump to the previous argument-list item     | Global  |
| Normal | <b>[Ctrl-L</b> | :lpfile                                     | Global  |
| Normal | <b>[L</b>      | :lrewind                                    | Global  |

# Runtime-discovered keymaps · part 6 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key      | Action                                             | Context |
|--------|----------|----------------------------------------------------|---------|
| Normal | [l]      | :lprevious                                         | Global  |
| Normal | [Ctrl-Q] | :cpfile                                            | Global  |
| Normal | [Q]      | :crewind                                           | Global  |
| Normal | [q]      | :cprevious                                         | Global  |
| Normal | [D]      | Jump to the first diagnostic in the current buffer | Global  |
| Normal | ] ]      | Add empty line below cursor                        | Global  |
| Normal | ]B       | Switch to last buffer                              | Global  |
| Normal | ]b       | Switch to next buffer                              | Global  |
| Normal | ]Ctrl-T  | :ptnext                                            | Global  |
| Normal | ]T       | :tlast                                             | Global  |
| Normal | ]A       | :last                                              | Global  |
| Normal | ]a       | Jump to the next argument-list item                | Global  |
| Normal | ]Ctrl-L  | :lnfile                                            | Global  |
| Normal | ]L       | :llast                                             | Global  |
| Normal | ]l       | :lnext                                             | Global  |

# Runtime-discovered keymaps · part 7 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key                 | Action                                                                                       | Context |
|--------|---------------------|----------------------------------------------------------------------------------------------|---------|
| Normal | <b>]Ctrl-Q</b>      | :cnfile                                                                                      | Global  |
| Normal | <b>]Q</b>           | :clast                                                                                       | Global  |
| Normal | <b>]q</b>           | :cnext                                                                                       | Global  |
| Normal | <b>]D</b>           | Jump to the last diagnostic in the current buffer                                            | Global  |
| Normal | <b>g0</b>           | vim.lsp.buf.document_symbol()                                                                | Global  |
| Normal | <b>grt</b>          | vim.lsp.buf.type_definition()                                                                | Global  |
| Normal | <b>gri</b>          | vim.lsp.buf.implementation()                                                                 | Global  |
| Normal | <b>grr</b>          | vim.lsp.buf.references()                                                                     | Global  |
| Normal | <b>grx</b>          | vim.lsp.codelens.run()                                                                       | Global  |
| Normal | <b>gra</b>          | vim.lsp.buf.code_action()                                                                    | Global  |
| Normal | <b>grn</b>          | vim.lsp.buf.rename()                                                                         | Global  |
| Normal | <b>gcc</b>          | Toggle comment line                                                                          | Global  |
| Normal | <b>gc</b>           | Toggle comment                                                                               | Global  |
| Normal | <b>gx</b>           | Opens filepath or URI under cursor with the system handler (file explorer, web browser, ...) | Global  |
| Normal | <b>Ctrl-WCtrl-D</b> | Show diagnostics under the cursor                                                            | Global  |



# Runtime-discovered keymaps · part 8 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key            | Action                                      | Context |
|--------|----------------|---------------------------------------------|---------|
| Normal | <b>Ctrl-Wd</b> | Show diagnostics under the cursor           | Global  |
| Normal | <b>Ctrl-L</b>  | Vim built-in; see :help CTRL-L-default      | Global  |
| Visual | <b>Tab</b>     | vim.snippet.jump if active, otherwise <Tab> | Global  |
| Visual | <b>hr</b>      | Reset selection                             | Global  |
| Visual | <b>hs</b>      | Stage selection                             | Global  |
| Visual | <b>#</b>       | Vim built-in; see :help v_#-default         | Global  |
| Visual | <b>*</b>       | Vim built-in; see :help v_star-default      | Global  |
| Visual | <b>@</b>       | Vim built-in; see :help v_@-default         | Global  |
| Visual | <b>Q</b>       | Vim built-in; see :help v_Q-default         | Global  |
| Visual | <b>[N</b>      | Select previous sibling node                | Global  |
| Visual | <b>[n</b>      | Select previous node                        | Global  |
| Visual | <b>]N</b>      | Select next sibling node                    | Global  |
| Visual | <b>]n</b>      | Select next node                            | Global  |
| Visual | <b>an</b>      | Select parent (outer) node                  | Global  |
| Visual | <b>gra</b>     | vim.lsp.buf.code_action()                   | Global  |

# Runtime-discovered keymaps · part 9 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key              | Action                                                                                       | Context |
|--------|------------------|----------------------------------------------------------------------------------------------|---------|
| Visual | <b>gc</b>        | Toggle comment                                                                               | Global  |
| Visual | <b>gx</b>        | Opens filepath or URI under cursor with the system handler (file explorer, web browser, ...) | Global  |
| Visual | <b>in</b>        | Select child (inner) node                                                                    | Global  |
| Visual | <b>Shift-Tab</b> | vim.snippet.jump if active, otherwise <S-Tab>                                                | Global  |
| Visual | <b>Ctrl-S</b>    | vim.lsp.buf.signature_help()                                                                 | Global  |
| Visual | <b>hr</b>        | Reset selection                                                                              | Global  |
| Visual | <b>hs</b>        | Stage selection                                                                              | Global  |
| Visual | <b>#</b>         | Vim built-in; see :help v_#-default                                                          | Global  |
| Visual | <b>*</b>         | Vim built-in; see :help v_star-default                                                       | Global  |
| Visual | <b>@</b>         | Vim built-in; see :help v_@-default                                                          | Global  |
| Visual | <b>Q</b>         | Vim built-in; see :help v_Q-default                                                          | Global  |
| Visual | <b>[N</b>        | Select previous sibling node                                                                 | Global  |
| Visual | <b>[n</b>        | Select previous node                                                                         | Global  |
| Visual | <b>]N</b>        | Select next sibling node                                                                     | Global  |
| Visual | <b>]n</b>        | Select next node                                                                             | Global  |

# Runtime-discovered keymaps · part 10 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode             | Key              | Action                                                                                       | Context |
|------------------|------------------|----------------------------------------------------------------------------------------------|---------|
| Visual           | <b>an</b>        | Select parent (outer) node                                                                   | Global  |
| Visual           | <b>gra</b>       | vim.lsp.buf.code_action()                                                                    | Global  |
| Visual           | <b>gc</b>        | Toggle comment                                                                               | Global  |
| Visual           | <b>gx</b>        | Opens filepath or URI under cursor with the system handler (file explorer, web browser, ...) | Global  |
| Visual           | <b>in</b>        | Select child (inner) node                                                                    | Global  |
| Operator-pending | <b>an</b>        | Select parent (outer) node                                                                   | Global  |
| Operator-pending | <b>gc</b>        | Comment textobject                                                                           | Global  |
| Operator-pending | <b>in</b>        | Select child (inner) node                                                                    | Global  |
| Insert           | <b>Shift-Tab</b> | vim.snippet.jump if active, otherwise <S-Tab>                                                | Global  |
| Insert           | <b>Ctrl-S</b>    | vim.lsp.buf.signature_help()                                                                 | Global  |
| Insert           | <b>Ctrl-W</b>    | Vim built-in; see :help i_CTRL-W-default                                                     | Global  |
| Insert           | <b>Ctrl-U</b>    | Vim built-in; see :help i_CTRL-U-default                                                     | Global  |
| Insert           | <b>Tab</b>       | vim.snippet.jump if active, otherwise <Tab>                                                  | Global  |
| Select           | <b>Tab</b>       | vim.snippet.jump if active, otherwise <Tab>                                                  | Global  |
| Select           | <b>Shift-Tab</b> | vim.snippet.jump if active, otherwise <S-Tab>                                                | Global  |

# Runtime-discovered keymaps · part 11 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key           | Action                         | Context         |
|--------|---------------|--------------------------------|-----------------|
| Select | <b>Ctrl-S</b> | vim.lsp.buf.signature_help()   | Global          |
| Normal | <b>Tab</b>    | Jump to next link              | Markdown buffer |
| Normal | <b>md</b>     | Lint Markdown                  | Markdown buffer |
| Normal | <b>mT</b>     | Toggle table mode              | Markdown buffer |
| Normal | <b>ma</b>     | Toggle format on save          | Markdown buffer |
| Normal | <b>mW</b>     | Add all project spelling words | Markdown buffer |
| Normal | <b>mw</b>     | Add project spelling word      | Markdown buffer |
| Normal | <b>mF</b>     | Unfold section                 | Markdown buffer |
| Normal | <b>mf</b>     | Fold section                   | Markdown buffer |
| Normal | <b>mc</b>     | Toggle task                    | Markdown buffer |
| Normal | <b>mt</b>     | Format table                   | Markdown buffer |
| Normal | <b>mN</b>     | Previous link                  | Markdown buffer |
| Normal | <b>mn</b>     | Next link                      | Markdown buffer |
| Normal | <b>mL</b>     | Follow link                    | Markdown buffer |
| Normal | <b>ms</b>     | Toggle preview split           | Markdown buffer |

# Runtime-discovered keymaps · part 12 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key                 | Action                                              | Context         |
|--------|---------------------|-----------------------------------------------------|-----------------|
| Normal | <b>mh</b>           | Toggle hybrid preview                               | Markdown buffer |
| Normal | <b>mp</b>           | Toggle preview                                      | Markdown buffer |
| Normal | <b>o</b>            | Create list item above and enter insert mode        | Markdown buffer |
| Normal | <b>[ [</b>          | Jump to previous heading                            | Markdown buffer |
| Normal | <b>] ]</b>          | Jump to next heading                                | Markdown buffer |
| Normal | <b>g0</b>           | Show an Outline of the current buffer               | Markdown buffer |
| Normal | <b>gx</b>           | Tree-sitter based link opener from `markview.nvim`. | Markdown buffer |
| Normal | <b>o</b>            | Create list item below and enter insert mode        | Markdown buffer |
| Normal | <b>Shift-Tab</b>    | Jump to previous link                               | Markdown buffer |
| Visual | <b>mc</b>           | Toggle task                                         | Markdown buffer |
| Visual | <b>mc</b>           | Toggle task                                         | Markdown buffer |
| Insert | <b>Shift-Tab</b>    | Jump to previous table cell                         | Markdown buffer |
| Insert | <b>&lt;M-CR&gt;</b> | Jump to previous table row                          | Markdown buffer |
| Insert | <b>Shift-CR</b>     | Insert new line in table cell                       | Markdown buffer |
| Insert | <b>Ctrl-T</b>       | Indent list item and update numbering               | Markdown buffer |

# Runtime-discovered keymaps · part 13 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key               | Action                                                   | Context         |
|--------|-------------------|----------------------------------------------------------|-----------------|
| Insert | <b>Ctrl-D</b>     | Dedent list item and update numbering                    | Markdown buffer |
| Insert | <b>Tab</b>        | Jump to next table cell                                  | Markdown buffer |
| Select | <b>Enter</b>      | Follow link, toggle to-do, or create link from selection | Markdown buffer |
| Select | <b>mc</b>         | Toggle task                                              | Markdown buffer |
| Normal | <b>Tab</b>        | nvim-tree: Open Preview                                  | NvimTree        |
| Normal | <b>Enter</b>      | nvim-tree: Open                                          | NvimTree        |
| Normal | <b>-</b>          | nvim-tree: Up                                            | NvimTree        |
| Normal | <b>.</b>          | nvim-tree: Run Command                                   | NvimTree        |
| Normal | <b>&lt;lt&gt;</b> | nvim-tree: Previous Sibling                              | NvimTree        |
| Normal | <b>&gt;</b>       | nvim-tree: Next Sibling                                  | NvimTree        |
| Normal | <b>B</b>          | nvim-tree: Toggle Filter: No Buffer                      | NvimTree        |
| Normal | <b>C</b>          | nvim-tree: Toggle Filter: Git Clean                      | NvimTree        |
| Normal | <b>D</b>          | nvim-tree: Trash                                         | NvimTree        |
| Normal | <b>E</b>          | nvim-tree: Expand All                                    | NvimTree        |
| Normal | <b>F</b>          | nvim-tree: Live Filter: Clear                            | NvimTree        |

# Runtime-discovered keymaps · part 14 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key       | Action                                | Context  |
|--------|-----------|---------------------------------------|----------|
| Normal | <b>H</b>  | nvim-tree: Toggle Filter: Dotfiles    | NvimTree |
| Normal | <b>I</b>  | nvim-tree: Toggle Filter: Git Ignored | NvimTree |
| Normal | <b>J</b>  | nvim-tree: Last Sibling               | NvimTree |
| Normal | <b>K</b>  | nvim-tree: First Sibling              | NvimTree |
| Normal | <b>L</b>  | nvim-tree: Toggle Group Empty         | NvimTree |
| Normal | <b>M</b>  | nvim-tree: Toggle Filter: No Bookmark | NvimTree |
| Normal | <b>O</b>  | nvim-tree: Open: No Window Picker     | NvimTree |
| Normal | <b>P</b>  | nvim-tree: Parent Directory           | NvimTree |
| Normal | <b>R</b>  | nvim-tree: Refresh                    | NvimTree |
| Normal | <b>S</b>  | nvim-tree: Search                     | NvimTree |
| Normal | <b>U</b>  | nvim-tree: Toggle Filter: Custom      | NvimTree |
| Normal | <b>W</b>  | nvim-tree: Collapse All               | NvimTree |
| Normal | <b>Y</b>  | nvim-tree: Copy Relative Path         | NvimTree |
| Normal | <b>[e</b> | nvim-tree: Prev Diagnostic            | NvimTree |
| Normal | <b>[c</b> | nvim-tree: Prev Git                   | NvimTree |

# Runtime-discovered keymaps · part 15 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key       | Action                              | Context  |
|--------|-----------|-------------------------------------|----------|
| Normal | <b>le</b> | nvim-tree: Next Diagnostic          | NvimTree |
| Normal | <b>lc</b> | nvim-tree: Next Git                 | NvimTree |
| Normal | <b>a</b>  | nvim-tree: Create File Or Directory | NvimTree |
| Normal | <b>bm</b> | nvim-tree: Move Bookmarked          | NvimTree |
| Normal | <b>bt</b> | nvim-tree: Trash Bookmarked         | NvimTree |
| Normal | <b>bd</b> | nvim-tree: Delete Bookmarked        | NvimTree |
| Normal | <b>c</b>  | nvim-tree: Copy                     | NvimTree |
| Normal | <b>d</b>  | nvim-tree: Delete                   | NvimTree |
| Normal | <b>e</b>  | nvim-tree: Rename: Basename         | NvimTree |
| Normal | <b>f</b>  | nvim-tree: Live Filter: Start       | NvimTree |
| Normal | <b>gp</b> | nvim-tree: Move                     | NvimTree |
| Normal | <b>ge</b> | nvim-tree: Copy Basename            | NvimTree |
| Normal | <b>gy</b> | nvim-tree: Copy Absolute Path       | NvimTree |
| Normal | <b>g?</b> | nvim-tree: Help                     | NvimTree |
| Normal | <b>m</b>  | nvim-tree: Toggle Bookmark          | NvimTree |



# Runtime-discovered keymaps · part 16 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key                         | Action                            | Context  |
|--------|-----------------------------|-----------------------------------|----------|
| Normal | <b>o</b>                    | nvim-tree: Open                   | NvimTree |
| Normal | <b>p</b>                    | nvim-tree: Paste                  | NvimTree |
| Normal | <b>q</b>                    | nvim-tree: Close                  | NvimTree |
| Normal | <b>r</b>                    | nvim-tree: Rename                 | NvimTree |
| Normal | <b>s</b>                    | nvim-tree: Run System             | NvimTree |
| Normal | <b>u</b>                    | nvim-tree: Rename: Full Path      | NvimTree |
| Normal | <b>x</b>                    | nvim-tree: Cut                    | NvimTree |
| Normal | <b>y</b>                    | nvim-tree: Copy Name              | NvimTree |
| Normal | <b>&lt;2-RightMouse&gt;</b> | nvim-tree: CD                     | NvimTree |
| Normal | <b>&lt;2-LeftMouse&gt;</b>  | nvim-tree: Open                   | NvimTree |
| Normal | <b>&lt;Del&gt;</b>          | nvim-tree: Delete                 | NvimTree |
| Normal | <b>&lt;BS&gt;</b>           | nvim-tree: Close Directory        | NvimTree |
| Normal | <b>Ctrl-X</b>               | nvim-tree: Open: Horizontal Split | NvimTree |
| Normal | <b>Ctrl-V</b>               | nvim-tree: Open: Vertical Split   | NvimTree |
| Normal | <b>Ctrl-T</b>               | nvim-tree: Open: New Tab          | NvimTree |

# Runtime-discovered keymaps · part 17 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key                | Action                           | Context  |
|--------|--------------------|----------------------------------|----------|
| Normal | <b>Ctrl-R</b>      | nvim-tree: Rename: Omit Filename | NvimTree |
| Normal | <b>Ctrl-K</b>      | nvim-tree: Info                  | NvimTree |
| Normal | <b>Ctrl-E</b>      | nvim-tree: Open: In Place        | NvimTree |
| Normal | <b>Ctrl-J</b>      | nvim-tree: CD                    | NvimTree |
| Visual | <b>D</b>           | nvim-tree: Trash                 | NvimTree |
| Visual | <b>c</b>           | nvim-tree: Copy                  | NvimTree |
| Visual | <b>d</b>           | nvim-tree: Delete                | NvimTree |
| Visual | <b>gy</b>          | nvim-tree: Copy Absolute Path    | NvimTree |
| Visual | <b>m</b>           | nvim-tree: Toggle Bookmark       | NvimTree |
| Visual | <b>x</b>           | nvim-tree: Cut                   | NvimTree |
| Visual | <b>&lt;Del&gt;</b> | nvim-tree: Delete                | NvimTree |
| Visual | <b>D</b>           | nvim-tree: Trash                 | NvimTree |
| Visual | <b>c</b>           | nvim-tree: Copy                  | NvimTree |
| Visual | <b>d</b>           | nvim-tree: Delete                | NvimTree |
| Visual | <b>gy</b>          | nvim-tree: Copy Absolute Path    | NvimTree |

# Runtime-discovered keymaps · part 18 of 18

Extracted from runtime:global, runtime:markdown, runtime:nvimtree.

| Mode   | Key   | Action                     | Context  |
|--------|-------|----------------------------|----------|
| Visual | m     | nvim-tree: Toggle Bookmark | NvimTree |
| Visual | x     | nvim-tree: Cut             | NvimTree |
| Visual | <Del> | nvim-tree: Delete          | NvimTree |

# Testing

Extracted from neotest.lua.

| Mode   | Key                   | Action                     | Context |
|--------|-----------------------|----------------------------|---------|
| Normal | <span>Space tA</span> | Fallback: run test suite   | Global  |
| Normal | <span>Space ta</span> | Run test suite             | Global  |
| Normal | <span>Space td</span> | Debug nearest test         | Global  |
| Normal | <span>Space tf</span> | Run current file           | Global  |
| Normal | <span>Space tn</span> | Run nearest test           | Global  |
| Normal | <span>Space to</span> | Show test output           | Global  |
| Normal | <span>Space ts</span> | Toggle test summary        | Global  |
| Normal | <span>Space tV</span> | Fallback: run current file | Global  |
| Normal | <span>Space tv</span> | Fallback: run nearest test | Global  |
| Normal | <span>Space tx</span> | Stop test                  | Global  |

# UI & Editing

Extracted from autopairs.lua, indent-blankline.lua.

| Mode   | Key      | Action               | Context |
|--------|----------|----------------------|---------|
| Normal | Space ua | Toggle autopairs     | Global  |
| Normal | Space ui | Toggle indent guides | Global  |
| Normal | Space us | Toggle indent scope  | Global  |

# Workspaces & Sessions

Extracted from auto-session.lua.

| Mode   | Key                 | Action       | Context |
|--------|---------------------|--------------|---------|
| Normal | <div>Space wr</div> | Find session | Global  |
| Normal | <div>Space ws</div> | Save session | Global  |

# Mermaid diagrams in Markdown

## What changed

|                                    |                                                                         |
|------------------------------------|-------------------------------------------------------------------------|
| <code>markdown-preview.nvim</code> | Browser-based Markdown preview; renders Mermaid fenced code blocks.     |
| <code>markview.nvim</code>         | Existing inline terminal renderer remains the normal in-editor preview. |

## Use it

|                        |                                                                                 |
|------------------------|---------------------------------------------------------------------------------|
| <code>Space m b</code> | Toggle the Mermaid-capable browser preview for the current Markdown/Rmd buffer. |
| <code>Space m p</code> | Toggle the existing inline Markview preview.                                    |

## Diagram syntax

|                         |                                   |
|-------------------------|-----------------------------------|
| <code>```mermaid</code> | Start a Mermaid fenced block.     |
| <code>graph TD</code>   | Example direction: top to bottom. |

### Example:

```
```mermaid
graph TD
  A[Markdown] --> B[Mermaid]
  B --> C[Browser preview]
```
```

Open a Markdown file and press `Space m b`. The preview is manual (no browser auto-open) and closes automatically when its Markdown buffer closes.

Source: lua/collin/lazy/markdown.lua. Plugin: iamcco/markdown-preview.nvim. The upstream plugin documents Mermaid rendering; the configuration was runtime-checked for the `:MarkdownPreviewToggle` command and mapping.