# Post-quantum-secure public-key encryption from the Learning With Errors problem

Course 01410, Crypto I

#### Christian Majenz

Associate Professor, Cybersecurity Engineering Section, DTU Compute


## Plan for today



Part I




Part III




Post-quantum public-key cryptography and the NIST competition




DH







DH




Luckily, public-key encryption and key exchange can also be constructed based on the hardness of

Lattice problems




DH



- Lattice problems
- Solving systems of multivariate polynomial equations




DH



- Lattice problems
- Solving systems of multivariate polynomial equations
- Decoding "obfuscated" error correction codes



DH



- Lattice problems
- Solving systems of multivariate polynomial equations
- Decoding "obfuscated" error correction codes
- Finding an isogeny between supersingular elliptic curvers

## Post-quantum cryptography

#### ⇒We have

- Lattice-based
- Multivariate-polynomial-based
- Code-based
- Isogeny-based

Public-key encryption/key exchange

Digital signatures are "easier"! Additionally

- Hash-based signatures
- MPC-in-the-head signatures

► Goal: Standardize at least one PQ-secure scheme of each:

- ► Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)

- Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)

- Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)
- Initially: All classes represented

- ► Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)
- Initially: All classes represented
- ► To be standardized:

- ► Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)
- Initially: All classes represented
- ► To be standardized:
  - ▶ 1 Lattice KEM: Crystals-Kyber

- ► Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)
- Initially: All classes represented
- ► To be standardized:
  - 1 Lattice KEM: Crystals-Kyber
  - 3 DSS: 2 based on lattices: Crystals-Dilithium&Falcon, 1 hashbased: SPHICS+

- ► Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)
- Initially: All classes represented
- ► To be standardized:
  - 1 Lattice KEM: Crystals-Kyber
  - 3 DSS: 2 based on lattices: Crystals-Dilithium&Falcon, 1 hashbased: SPHICS+
- 4th round: New call for signature proposals, 3 code-based KEMs under consideration

- Goal: Standardize at least one PQ-secure scheme of each:
  - Key Encapsulation Mechanism (KEM, ~public-key encryption)
  - Digital Signature scheme (DSS)
- Initially: All classes represented
- ► To be standardized:
  - ▶ 1 Lattice KEM: Crystals-Kyber
  - 3 DSS: 2 based on lattices: Crystals-Dilithium&Falcon, 1 hashbased: SPHICS+
- 4th round: New call for signature proposals, 3 code-based KEMs under consideration

### Remainder of today's lecture:

- ► The Learning With Errors (LWE) problem
- ► The Regev encryption scheme
- Short outlook: What's missing to get to Kyber?

## Part II: The Lerning With Errors problem (LWE)

## Warm-up: Gaussian elimination

• Exercise: Solve the following linear system over  $\mathbb{Z}_{23}$  using Gaussian elimination:

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{pmatrix} \begin{pmatrix} 13 \\ 20 \end{pmatrix} = \begin{pmatrix} 7 \\ 4 \\ 1 \end{pmatrix} \mod 23$$

Hint:  $21^{-1} = 11 \mod 23$ 

## A slightly harder problem

• Exercise: Solve the following "noisy" linear system over  $\mathbb{Z}_{23}$  using Gaussian elimination:

$$\begin{pmatrix} 1 & 2 \\ 3 & 4 \\ 5 & 6 \end{pmatrix} \begin{pmatrix} 9 \\ 10 \end{pmatrix} = \begin{pmatrix} 6 \\ 19 \\ 13 \end{pmatrix} + \begin{pmatrix} \epsilon_1 \\ \epsilon_2 \\ \epsilon_3 \end{pmatrix} \mod 23$$

Promise:  $\epsilon_i \in \{-1,0,1\}$  for i = 1,2,3

Hint:  $21^{-1} = 11 \mod 23$ 

## A slightly harder problem

For Example 2. Solve the following "noisy" linear system over  $\mathbb{Z}_{23}$  using "mination:



Promise:  $\epsilon_i \in \{-1,0,1\}$  for i

Hint:  $21^{-1} = 11 \mod 23$ 

Part III: Regev encryption