MICROPHONE FLEX / WIRED SCHEMATIC

Rev C reading copy | Continuous wires | Fit ONE MAX9814 module only

01 HARNESS & FILTER

J1

+5V_IN

AUDIO_OUT

GND

33R / supply filter

R4

0R / 40 dB

R1

0R / A:R 1:500

R2

470R / output

R5

02 THREE ALTERNATIVE SOCKETS — SHARED SIGNALS

M1

UP / vertical

Vdd Gain AR Out GND

J2

LEFT / right angle

VDD GAIN AR MICOUT GND

J3

RIGHT / right angle

VDD GAIN AR MICOUT GND

VDD

GAIN

AR

MICOUT

GND

03 POWER INDICATOR

R6

2K2

D1

GREEN LED

04 DECOUPLING

C7

22uF / 10V X5R

C6

100nF

TP1

MICOUT

TP2

GND

Dots join wires. Crossings without dots are separate. Pins are arranged by signal; numbers match the PCB.

Mounting only:

H1 H2 H3 H4 H5 H6 H7 H8

H1/H2: M5 slots | H3/H4: top M2 | H5–H8: side M2

Electrical reading copy — original PCB and schematic retained

Colloquy of Mobiles

Sheet: /

File: microphone-flex-wired.kicad_sch

Title: Microphone flex — continuous wiring

Size: A3	Date: 2026-10-20	**Rev: C-wired**
KiCad E.D.A. 9.0.7		Id: 1/1