MICROPHONE FLEX / WIRED SCHEMATIC

Rev C reading copy | Continuous wires | Fit ONE MAX9814 module only

JP1 GAIN: 1–2 = 50dB / 2–3 = 40dB / no shunt = 60dB

JP2 A/R: 1–2 = 1:500 / 2–3 = 1:2000 / no shunt = 1:4000

Initial shunts: JP1 2–3; JP2 1–2. Power off before changing.

01 HARNESS & FILTER

J1

+5V_IN

AUDIO_OUT

GND

33R / supply filter

R4

470R / output

R5

02 THREE ALTERNATIVE SOCKETS — SHARED SIGNALS

M1

UP / vertical

Vdd Gain AR Out GND

J2

LEFT / right angle

VDD GAIN AR MICOUT GND

J3

RIGHT / right angle

VDD GAIN AR MICOUT GND

JP1

VDD GAIN GND

JP2

VDD AR GND

VDD

GAIN

AR

MICOUT

GND

03 POWER INDICATOR

R6

2K2

D1

GREEN LED

04 DECOUPLING

C7

22uF / 10V X5R

C6

100nF

TP1

MICOUT

TP2

GND

Dots join wires. Crossings without dots are separate. Pins are arranged by signal; numbers match the PCB.

Mounting only:

H1 H2

H1/H2: M5 frame slots. No module-support mounting holes in this placement.

Electrical reading copy — original PCB and schematic retained

Colloquy of Mobiles

Sheet: /

File: microphone-flex-wired.kicad_sch

Title: Microphone flex — continuous wiring

Size: A3	Date: 2026-10-20	**Rev: C-J wired**
KiCad E.D.A. 9.0.7		Id: 1/1