TECHNICAL REPORT · WAVEFORMJAX

IMRPhenomXPNR and NRSur7dq4 in JAX, checked against LALSimulation

How two precessing waveform models, and LALSimulation's conversions between the time and frequency domains, were written as pure JAX functions that compile, vectorise and differentiate. The report covers how they compare with LALSimulation 6.2.0 and with waveformrs, how their derivatives compare with finite differences, and what they cost.

REPOSITORY
`waveformjax`, branch `main` at `321ebea` (43 commits)

REFERENCE
lalsimulation 6.2.0, lal 7.7.0 (conda-forge, osx-arm64), and waveformrs's Python bindings

PLATFORM
Apple M2 Ultra, 24 cores; JAX 0.11.2 on the CPU; Python 3.12.15

GENERATED
23 October 2026

CONTENTS

1 Summary
2 Models as pure JAX functions
3 IMRPhenomXPNR
4 NRSur7dq4
5 Time and frequency domains
6 How the package is tested
7 Accuracy
8 Derivatives
9 Performance
10 Differences from LALSimulation
11 Limitations and future work
12 Reproducing the results
13 Commit history

1 Summary

waveformjax implements the frequency-domain model IMRPhenomXPNR and the time-domain surrogate NRSur7dq4 in JAX, with the interface of waveformrs's Python bindings and LALSimulation's conventions. Every model is a pure function of a `Binary` pytree, so it can be compiled with `jax.jit`, evaluated for many binaries at once with `jax.vmap`, and differentiated with respect to all twelve parameters of the binary with `jax.grad`, `jax.jvp` and `jax.jacfwd`. LALSimulation's `SimInspiralTD` and `SimInspiralFD` are reproduced as well, with LAL's lengths and start times, and are differentiable too. The models follow LAL's code branch for branch, with each branch written as traced arithmetic. They agree with LALSimulation 6.2.0 to rounding for NRSur7dq4, and for IMRPhenomXPNR to the level at which different builds of LAL agree with each other.

Open items. The tests, the accuracy comparisons, the derivative checks and the timings below are complete. Still open:

- a full test run with `test_nrsur7dq4_float32.py`, added since the last one (the tests section)
- why finite differences of the full IMRPhenomXPNR waveform disagree with its derivatives in the in-plane spins (the derivatives section)
- JAX on one core: setting XLA's thread flags (`--xla_cpu_multi_thread_eigen=false intra_op_parallelism_threads=1`) did not change the ~3 cores it keeps busy, so the per-core comparison with LAL and waveformrs is still to be made
- NRSur7dq4's float32 timings on an idle machine: they were measured while other jobs ran (`report/float32_nrsur7dq4.py --only-timings`; the NRSur7dq4 section)

IMRPHENOMXPNR AGAINST LAL 6.2.0

≤ 6.6×10^{-5}

Largest relative error, $|h - h_{LAL}| / \max |h_{LAL}|$, over 200 random binaries (median 5.0×10^{-7}); largest mismatch 4.9×10^{-9}. With the parity fix, against LAL patched with it: ≤ 2.7×10^{-5}.

NRSUR7DQ4 AGAINST LAL 6.2.0

≤ 2.8×10^{-12}

Over 200 random binaries, with LAL's length and epoch in 200 of them; largest mismatch 3.3×10^{-16}.

NRSUR7DQ4 DERIVATIVES

≤ 2.9×10^{-8}

Largest disagreement of any column of the Jacobian with finite differences, over four binaries, wherever the waveform is differentiable. For IMRPhenomXPNR the finite differences disagree by up to 1.5×10^{-1}, which is still being investigated (section 8).

ONE IMRPHENOMXPNR WAVEFORM

16.18 ms

Compiled, on 8033 frequencies, against 13.54 ms for LALSimulation and 3.10 ms for waveformrs. The first call compiles for 37.6 s.

BATCHES WITH `JAX.VMAP`

102 / s

IMRPhenomXPNR waveforms per second at best over batch sizes, against 4,293 / s for waveformrs on all threads and 72 / s for LALSimulation on one.

TESTS

452 / 452 pass

pytest, including the slow random-draw tests, in 24 minutes. They compare every part of the models with LALSimulation and the reference data of waveformrs.

COMPARISON	DRAWS	MAX REL. ERROR	MEDIAN REL. ERROR	MAX MISMATCH	MEDIAN MISMATCH
IMRPhenomXPNR without the parity fix, against LALSimulation 6.2.0	200/200	6.6×10^{-5}	5.0×10^{-7}	4.9×10^{-9}	5.2×10^{-12}
IMRPhenomXPNR with the parity fix, against 6.2.0 + lalsuite !2593	200/200	2.7×10^{-5}	5.9×10^{-7}	2.8×10^{-9}	6.7×10^{-12}
IMRPhenomXPNR without the fix, against waveformrs	200/200	6.6×10^{-5}	5.0×10^{-7}	4.9×10^{-9}	5.2×10^{-12}
NRSur7dq4, against LALSimulation 6.2.0	200/200	2.8×10^{-12}	2.6×10^{-13}	3.3×10^{-16}	0
NRSur7dq4, against waveformrs	200/200	2.8×10^{-12}	2.6×10^{-13}	3.3×10^{-16}	0

Random binaries drawn as in waveformrs's report (section 7). IMRPhenomXPNR is evaluated on 4,096 uniformly spaced frequencies per draw. "Draws" counts the draws compared. Mismatches use the aLIGO design sensitivity without maximisation.

In short:

- **Implementation.** 67 Python modules (19,869 lines, of which 4,381 are parameter-space fits generated from waveformrs's Rust by a translator) cover the two models, their checks and the conversions (sections 2–5).
- **Accuracy.** NRSur7dq4 agrees with LAL at rounding level. IMRPhenomXPNR's (2,2) mode agrees to ~1e-9. Its higher modes agree to ~1e-5, because LAL takes derivatives by finite differences whose rounding noise JAX's different, but valid, arithmetic changes (section 7).
- **Single precision.** NRSur7dq4 runs in float32 when the binary's parameters are float32, and returns the strain times 10^{21} by default. In float32, an inner product between two different waveforms changes by 2.4×10^{-6} of the product of their norms (median; at most 1.0×10^{-4}). Derivatives agree with float64 to 5.6×10^{-5} (section 4).
- **Derivatives.** IMRPhenomXPNR is differentiated in forward mode, and its reverse-mode gradient is the transpose of that forward-mode Jacobian. NRSur7dq4 is differentiated directly in either mode. NRSur7dq4's derivatives agree with finite differences to ~1e-8. For IMRPhenomXPNR, finite differences of the full waveform disagree with the derivatives by up to 1.5×10^{-1}, most in the in-plane spins; the transform tests, which use the (2,2) mode, agree to ~1e-7. This is still being investigated (section 8).
- **Cost.** A compiled IMRPhenomXPNR waveform costs about as much as LALSimulation's, and a few times as much as waveformrs's. `jax.vmap` over many binaries is how JAX code would use it. Compilation takes tens of seconds for the model and minutes for its gradient (section 9).

Two bugs found while preparing this report, both fixed. First, the conversions and the IMRPhenomXPNR speed-ups had been developed on separate branches. After the merge, `jax.grad` of `simulate_td_function` failed with "Linearization failed to produce known values". The conversions called the model through a reverse-mode wrapper, while the speed-ups had made the model's loops forward-mode only. The conversions now use the model's forward-mode Jacobians, with respect to the binary and to the starting frequency, which itself depends on the binary (`deeffce`). Second, when the first use of NRSur7dq4's data was the pure function under `jax.jit`, the cached data were built inside the trace and leaked tracers into later calls. The tests had always read the data through a plain call first; the gradient measurements of section 8 did not (`0a93b55`, with a test).

2 Models as pure JAX functions

The package has the interface of waveformrs's Python bindings, with the same function names, keyword arguments, options, result classes and exceptions. Underneath, every model is a pure function of a `Binary` : a `NamedTuple` of float64 arrays (or float32 arrays, for NRSur7dq4), and so a JAX pytree.

```
import jax, jax.numpy as jnp, numpy as np
import waveformjax as wf

frequencies = np.arange(20.0, 1024.0, 0.125)
hp, hc = wf.polarizations("IMRPhenomXPNR", frequencies, mass_1=36.0, mass_2=29.0,
                          spin_1=(0.4, 0.2, 0.3), spin_2=(-0.2, 0.3, -0.1), f_ref=20.0)

# the pure function, for jit, vmap and grad
model = wf.polarizations_function("IMRPhenomXPNR")          # f(binary, frequencies)
binary = wf.Binary(mass_1=36.0, mass_2=29.0, spin_1=jnp.array([0.4, 0.2, 0.3]),
                   spin_2=jnp.array([-0.2, 0.3, -0.1]), f_ref=20.0)
loss = lambda b: jnp.sum(jnp.abs(model(b, frequencies)[0]) ** 2)
jax.grad(loss)(binary)                                      # a Binary of derivatives
jax.vmap(model, in_axes=(0, None))(binaries, frequencies)    # many binaries at once

# NRSur7dq4 gives the strain times 1e21 (scaled_strain=False: the strain itself)
h = wf.td_polarizations("NRSur7dq4", 1 / 4096, 20.0, mass_1=40.0, mass_2=20.0)
surrogate = wf.td_polarizations_function("NRSur7dq4")       # f(binary, times)
single = wf.Binary(mass_1=jnp.float32(40.0), mass_2=jnp.float32(20.0), spin_1=jnp.zeros(3, jnp.float32),
                   spin_2=jnp.zeros(3, jnp.float32), f_ref=20.0)
hp, hc = surrogate(single, h.times)                         # in float32
h = wf.simulate_td("IMRPhenomXPNR", 1 / 4096, 20.0, mass_1=36.0, mass_2=29.0)
```

A call goes through four stages:

1. **Checks on the host**
   The public functions convert the arguments and run LALSimulation's checks on concrete values (`MODEL.validate`), outside any JAX transformation. Invalid masses, spins or frequencies, or a precession version LAL would replace while `version_fallback=False` , raise the exceptions of waveformrs: `InvalidParameterError` , `PrecessionVersionUnavailableError` and so on.
2. **A compiled function per configuration**
   The model method is compiled with `jax.jit` with the options fixed. `WaveformOptions` is a frozen dataclass, so it can be a static argument. JAX caches the compiled function per options and array shape, so a sampler that keeps its frequency grid compiles once.
3. **Traced arithmetic**
   Inside, nothing branches in Python on the binary. Each of LAL's `if` s becomes a `jnp.where` between branches that are both evaluated, with safe arguments, so that the branch not taken cannot put NaN into the value or the gradient. Loops of fixed length are `lax.scan` ; loops whose length depends on the binary are `lax.while_loop` . The precession prescriptions are branches of a switch.
4. **Failures as NaN**
   Failures that LAL can only detect while computing, such as a SpinTaylor integration that cannot reach the reference frequency, make the output NaN. The batch functions report those binaries as `ModelError` in `errors` and set their rows to zero.

Importing the package enables 64-bit floats (`jax_enable_x64`), which IMRPhenomXPNR needs; NRSur7dq4 also runs in float32 (section 4). The thousands of fitted coefficients of IMRPhenomX are not copied by hand. `scripts/rust_to_python.py` parses the straight-line Rust of waveformrs (its `let` bindings, arithmetic, `fma` calls and `f64` methods) and emits the same expressions on JAX arrays. `scripts/generate_fits.py` then writes them into `models/xpnr/_generated/` . The control flow is written by hand, file by file after LAL's, and each module's docstring names the LAL function it follows.

Each model package defines a `MODEL` with a fixed contract. A frequency-domain model has `validate` , `polarizations` , `modes` and `choose_fd_modes` . A time-domain model has `validate` , `td_polarizations` , `td_modes` and `polarizations_at` , the last of which evaluates the waveform at any given times. The public functions, the batches and the conversions are written once, against that contract.

3 IMRPhenomXPNR

IMRPhenomXPNR is IMRPhenomXPHM with the phenomenological PNR precession angles, a co-precessing (2,2) mode tuned to numerical relativity, an antisymmetric (2,|2|) contribution and the 122019 release of the higher modes. In LALSimulation it draws on many of the 49 IMRPhenomX source files, together with the SpinTaylor code and GSL. Here it is about 14,800 lines of Python, of which 4,400 are generated fits.

Four prescriptions in one compiled function

LALSimulation chooses the Euler angles by the binary. In-plane spins below 1e-7 give plain IMRPhenomXPHM with the NNLO angles, without the PNR machinery. Below 1e-6, the PNR machinery runs with the NNLO angles (version 102). Otherwise the SpinTaylor angles are used (version 330). Where LAL's SpinTaylor integration fails, it falls back to the MSA angles (223), or to NNLO if the MSA system cannot be set up. Here the decision is a traced index, and the prescriptions are three branches of a switch; versions 102 and 223 of the PNR machinery share one branch, chosen by a traced flag. Under `jax.vmap`, `lax.switch` with a batched index would compute every branch for every binary. The model's own `switch`, `cond` and `while_loop` (`_transforms.py`) instead have batching rules: a branch is computed for the whole batch only if some binary in the batch takes it, and a loop runs to the longest binary in the batch while selecting only its small carry at each iteration.

The SpinTaylor angles

The SpinTaylor angles are the hardest part to make traceable. LAL integrates the orbit-averaged SpinTaylorT4 equations from `f_ref` backwards to below `f_min` and forwards to the end of the inspiral. It uses GSL's adaptive RKF45 at tolerances of 1e-12, samples the solution every $\Delta t = 5 / f_{cut}$, repeats the end with ten times finer sampling, and passes all the samples, millions for light binaries, to natural cubic splines of α and cos β. Where each run ends, and so how many samples there are, depends on the exact sequence of steps. The JAX version therefore splits the work:

- **The forward and fine runs** repeat LAL's adaptive steps one for one in a `while_loop` (`spintaylor/replica.py`): GSL's step control, the retries after a failed derivative, the Hermite-like interpolant and the stopping test. The run then ends where LAL's ends, with the same samples. Its derivatives are those of the recorded steps with the step sizes held fixed.
- **The backward run** is long and only ends at a frequency, so it is solved with Dormand–Prince 8(5,3) and its seventh-order dense output. The steps are equal increments of $u = 1 / (M\omega)$, so each step covers about the same precession angle, and a few hundred steps resolve a whole inspiral to ~1e-12. The step size is a smooth function of the state, so the solution is differentiable. It differs from LAL's samples by LAL's own integration error, ~1e-9.
- **The splines** have as many knots as LAL has samples. Up to 8192 knots they are built as GSL builds them. Beyond that, a natural cubic spline at x depends on knots k intervals away only through factors $\sim(2 - \sqrt{3})^k$. It is then evaluated from the 34 knots around x, which gives the same values to ~1e-15 at a cost per point independent of the number of samples.

Reproducing LAL's discrete choices

Much of LAL's code makes decisions on values that are themselves results of iterations or of NaN arithmetic. Each has to be reproduced exactly, or the waveform changes discontinuously:

- **MSA angles.** GSL's Jacobi elliptic function and elliptic integral are ported with a fixed number of iterations, and the iterations GSL would not do are masked out. Unlike LAL, which stores the roots of the spin cubic in a shared struct and races on them under OpenMP, every value here is local, so the angles agree with single-threaded LAL.
- **Higher modes.** The order of the intermediate amplitude polynomial is lowered when it would cross zero. `CrossZeroP5` takes the roots from GSL's `gsl_poly_complex_solve`, and LAL's indexing of the roots depends on their order, so GSL's balanced companion matrix and Francis QR iteration are ported step for step in `while_loop`s that end where GSL's end.
- **PNR β connection.** LAL picks the connection frequencies of β from the turning and inflection points of a cubic. The computation often produces NaN (complex roots, square roots of negative numbers), which LAL's comparisons then treat as false. It is evaluated twice. The first pass uses LAL's arithmetic, NaN included and under `stop_gradient`, to make the decisions. The second uses finite stand-ins that follow those decisions, to give the values and their gradients. The inflection points are roots from the trigonometric formula, close to an `acos` of 1, so there LAL's fused multiply-adds are reproduced exactly, giving ~1e-12 rather than ~1e-8.
- **Antisymmetric amplitude.** LAL smooths the amplitude ratio with an 81-point moving average computed in place, so each window reads averages it has already written. That is an order-40 linear recurrence. It is evaluated in blocks of 40 values with a triangular solve per block, inside a `lax.scan`.

Derivatives in forward mode

Loops whose number of iterations is traced, such as the SpinTaylor runs and GSL's QR iteration, can be differentiated in forward mode but not in reverse mode. Reverse mode through the model's many scalar set-up computations also compiles slowly. So `_transforms.differentiable` makes the model a `jax.custom_jvp` function. Its rule computes the Jacobian with respect to the parameters that have non-zero tangents, one `jax.jvp` per parameter, and contracts it with the tangents. The contraction is linear, so `jax.grad`, which transposes it, works as well as `jax.jvp` and `jax.jacfwd`. The Jacobian is itself a `custom_vmap` function, so under `jax.vmap` of a gradient the binaries are batched inside the differentiation. Where LAL takes derivatives by finite differences, with steps of 1e-9 and 1e-7 in the intermediate region of the higher modes, the values follow LAL. Their tangents, however, are those of the exact derivatives. The tangents of the finite differences themselves would amplify rounding by up to 1e14.

The parity fix

By default the model includes the fix of lalsuite !2593 from LALSuite's development branch, as waveformrs does. The fix restores the mirror symmetry of the antisymmetric modes: flipping the in-plane spins and taking $\iota \to \pi - \iota$ gives $(h_+, -h_\times)$. `pnr_parity_fix=False`, or `WaveformOptions.lalsimulation_defaults()`, gives the released LALSimulation 6.2.0. Both are compared with LAL in section 7, the fixed model with a LALSimulation 6.2.0 patched with the fix (UNCLEAN: lalsimulation-v6.2.0 + lalsuite!2593 (git diff 64d2004def^1 64d2004def -- lalsimulation/lib)).

Making it compile and run faster

The first complete version took about 32 ms per waveform and 2.3 s for `jax.vmap` over 64 binaries; compiling its reverse-mode gradient took 714 s. A second round of work brought these to about 18 ms, 0.74 s and 132 s (measured during development on this machine). It moved the derivatives to forward mode and added the batch-aware branches and loops. It merged versions 102 and 223 into one branch, computed only the PNR β of the binary's region, chose the intermediate polynomials of all higher modes together, and solved the SpinTaylor equations with the 3-vectors as arrays. The current numbers are in section 9.

4 NRSur7dq4

NRSur7dq4 interpolates numerical-relativity waveforms of precessing binaries. It was trained on mass ratios up to 4 and spin magnitudes up to 0.8, and LAL allows it to extrapolate beyond those. It integrates an ODE for the coprecessing frame, the orbital phase and the spins, with time derivatives given by fits at 233 nodes. It then evaluates the coorbital modes from fits at their empirical-interpolation nodes and rotates them to the inertial frame. The JAX version follows `LALSimIMRPrecessingNRSur.c` and waveformrs's translation of it.

- **Data.** The 17 MB HDF5 file is read once with h5py. Every dynamics fit becomes a dense row over the union of the monomials the fits use, so the nine fits of a node are one matrix–vector product. The fits of the waveform nodes are stored by the order of their mass-ratio monomial, so the mass ratio, which is the same at every node, is folded into the coefficients once per binary.
- **Dynamics.** LAL steps from the reference frequency to the nearest node, takes three RK4 steps (forwards or backwards, depending on that node), and covers the remaining nodes with fourth-order Adams–Bashforth steps in both directions. Since the starting node depends on the binary, the integration is one `lax.scan` of fixed length. It walks backwards from the start and then forwards, evaluating the fits of one node per step as LAL does. The Adams–Bashforth weights depend only on the node and are tabulated once.
- **Splines.** GSL's natural cubic splines solve a tridiagonal system whose matrix depends only on the knots. As in waveformrs, it is factorised once when the data are read, so fitting a spline needs only the two substitution sweeps.
- **Frame rotation.** LAL's Wigner D-matrices use negative powers of the quaternion's components, with special cases where they vanish, as they do for spins along the orbital angular momentum. Here the negative powers are cancelled analytically, which makes each element a polynomial in the quaternion: the same values, no special cases, and finite gradients in the non-precessing limit.
- **Output grid.** The number of samples depends on when the orbital frequency reaches $\pi\, f_{\mathrm{min}}$, so it is found on the host. A compiled pass evaluates the frequency fits, and numpy repeats LAL's search operation by operation. The waveform is then computed on a power-of-two buffer of at least 256 samples, which waveforms of similar length share, and trimmed to the binary's length.

`polarizations_at(binary, times)` evaluates the waveform at any times relative to the peak. It is pure and differentiable with respect to every parameter, including `f_ref`, which moves the reference time and so the frame. It is what `jax.vmap`, `jax.grad` and the conversions use.

Single precision and the scale of the output

NRSur7dq4 is evaluated in the precision of the binary's parameters. A `Binary` of float32 arrays is evaluated in float32 throughout, with a float32 copy of the data cast from the float64 arrays (the spline factorisations included). A test checks that no operation of the traced waveform, or of its gradient, is in float64. The public functions take Python numbers, so they stay in float64. Two changes make float32 usable:

- **The output is the strain times 10^{21}.** This applies to every NRSur7dq4 function, the public functions and the conversions included, unless `scaled_strain=False`. The strain itself fits in float32, but its square (~10^{-42}) and a detector's power spectral density (~10^{-47}) do not. The comparisons with LAL in this report use `scaled_strain=False`.
- **Nothing passes through SI units.** LAL converts the masses to kilograms and back (`m * MSUN_SI / MSUN_SI`) and works with the distance in metres. In float32, XLA folded the square of the solar mass in kilograms (~4×10^{60}, beyond float32's range) into the derivative of the mass ratio, so the compiled gradient was NaN. The derivative with respect to a distance of ~10^{25} m underflowed to zero. The masses now stay in solar masses, and the amplitude is one constant times the total mass over the distance in Mpc. In float64 this changes the waveform by rounding only.

What float32 costs in accuracy was measured on 300 pairs of binaries, drawn as for the accuracy comparison (`report/float32_nrsur7dq4.py`). 150 pairs are two independent binaries, whose overlaps are near zero. The other 150 are a binary and a small perturbation of its masses, spins and angles, with a median overlap of 0.95. Both binaries of a pair are evaluated on one time grid, in float64 and in float32, projected on a detector and tapered at the start. Inner products use the aLIGO design sensitivity from 20 Hz, without maximisation, and are computed in float64 unless stated otherwise.

CHANGE FROM FLOAT64 TO FLOAT32	MEDIAN	90TH PERCENTILE	LARGEST
Inner product of the two waveforms, change over the product of their norms	2.4×10^{-6}	2.0×10^{-5}	1.0×10^{-4}
Normalised overlap, independent binaries	9.9×10^{-7}	8.0×10^{-6}	3.9×10^{-5}
Normalised overlap, nearby binaries	4.1×10^{-6}	3.0×10^{-5}	1.0×10^{-4}
Normalised overlap, with the inner products in float32 too	2.1×10^{-6}	1.9×10^{-5}	1.0×10^{-4}
Normalised overlap, with the dynamics in float64	2.8×10^{-7}	1.7×10^{-6}	4.6×10^{-6}
One waveform, noise-weighted relative error $\|\delta h\| / \|h\|$	3.8×10^{-5}	8.3×10^{-5}	2.5×10^{-4}
One waveform, largest relative error max $\|\delta h\|$ / max $\|h\|$	5.1×10^{-5}	1.3×10^{-4}	7.5×10^{-4}
One waveform, relative error of $\langle h, h\rangle$	6.4×10^{-7}	3.1×10^{-6}	2.9×10^{-5}
Derivatives of a log-likelihood, relative error (40 nearby pairs)	5.6×10^{-5}	6.0×10^{-4}	4.5×10^{-1}
Derivatives of a log-likelihood, error over the typical size of the component	6.5×10^{-7}	3.1×10^{-5}	2.0×10^{-3}

NRSur7dq4 in float32 against float64. The overlaps and inner products are between the two binaries of a pair. "With the inner products in float32 too" also does the whitened Fourier transforms and sums in float32. "With the dynamics in float64" integrates the ODE in float64 and computes the rest in float32. The log-likelihood is $\langle d, h\rangle - \langle h, h\rangle/2$, with noise-free data d from the other binary; its derivatives exclude f_{ref}, which is zero for half the pairs. Data: `report/data/float32_nrsur7dq4.json`.

An inner product between two different waveforms changes by 2.4×10^{-6} of the product of their norms (median), and by at most 1.0×10^{-4}. Doing the inner products themselves in float32 adds at most 1.7×10^{-7} to the overlap. The error of a single waveform, 3.8×10^{-5} (median, noise-weighted), is mostly rounding noise from the final resampling onto the float32 time grid: with everything up to the polarizations on the surrogate's own times in float64, it is still 2.5×10^{-5}. That noise is almost uncorrelated with another waveform, so it barely moves their inner product. The ODE integrated in float32 is what does. With the dynamics in float64 and the rest in float32, the change of the overlap falls from 2.1×10^{-6} to 2.8×10^{-7} (median), and from 1.9×10^{-5} to 1.7×10^{-6} at the 90th percentile.

Between nearby binaries the log-likelihood changes by $4.2\times10^{-6}\ \rho^2$ (median; $2.8\times10^{-5}\ \rho^2$ at the 90th percentile), where ρ is the signal-to-noise ratio. That is 1.7×10^{-3} at ρ = 20 and 4.2×10^{-2} at ρ = 100 (2.8×10^{-1} at the 90th percentile). With noise in the data, a further $\langle n, \delta h\rangle$ of about $\rho\ \|\delta h\| / \|h\|$ is added. The float32 derivatives agree with the float64 ones to 5.6×10^{-5} (median relative error), or 6.0×10^{-4} at the 90th percentile. The largest relative errors are in components whose derivative almost vanishes; measured against the typical size of each component, no error exceeds 2.0×10^{-3}.

On this CPU, float32 is 1.1× as fast for one waveform (2.74 ms against 3.05 ms on 8192 samples). It is 1.7× as fast for a batch of 64 under `jax.vmap` (56.61 ms against 94.01 ms), and 1.4× for a gradient. The dynamics, a sequence of 230 small steps, take 48% of a float64 batch. Keeping them in float64 would make the inner products about ten times more accurate, at the cost of part of the speed-up on the CPU; the package does not do this. float32 matters most on accelerators, where float64 is much slower, and there it has not been measured.

5 Time and frequency domains

`simulate_td` and `simulate_fd` reproduce LALSimulation 6.2.0's `SimInspiralTD` and `SimInspiralFD`. IMRPhenomXPNR can be given in the time domain and NRSur7dq4 in the frequency domain, and each model can also be conditioned in its own domain. They follow waveformrs's `src/conversions/` and `src/conditioning.rs`.

LAL's conditioning starts the model below the requested frequency by an amount set by bounds on the chirp time, merger time and ringdown time. It tapers the extra length, applies a Butterworth high-pass filter, shifts the waveform in time and crops it to a length and epoch derived from the same bounds. The work is split by what needs to be exact:

- **On the host, in Python floats.** The lengths, shifts, taper widths and GPS epochs are computed with LAL's arithmetic. This includes C's `pow`, `cbrt` and `round`, and the fused multiply-adds of clang's arm64 build, reproduced exactly through rational arithmetic. As a result, lengths and epochs are LAL's bit for bit.
- **In JAX, pure and differentiable.** The bounds are computed again where the waveform depends on them continuously: the starting frequency given to the model and the cutoff of the first high-pass filter. So do the filter coefficients, the filter itself (a `lax.scan` of LAL's recursion per second-order section), the tapers and the Fourier transforms. Arrays have fixed, power-of-two lengths, so one compilation serves many binaries.

IMRPhenomXPNR smooths its antisymmetric amplitude with a moving average over the array of frequencies, which LAL takes over its band. To keep one array length per transform length, the model is evaluated on the band, followed by frequencies just above it and then the band's last 82 frequencies again. The first L − 41 values are then averaged as LAL averages them, and the last 41 are taken from the end. `simulate_td_function` and `simulate_fd_function` return the conversion as a pure function. It keeps the lengths, shifts, tapers and epoch of a reference binary, while the starting frequencies and filter cutoffs follow the binary, so the gradient includes their dependence on the masses and spins.

6 How the package is tested

452 pytest tests (452 passed, 0 failed, 0 skipped in the run below) compare every layer of the models with LALSimulation 6.2.0, through its Python API or, for internal functions, through ctypes. They also reuse waveformrs's reference suites, which cover each regime switch and fallback of the models.


TEST FILE	TESTS	RESULT	TIME
`test_api.py` The interface: options, arguments, errors, spherical harmonics	9	9 passed	415 ms
`test_xpnr_xas.py` IMRPhenomXAS (2,2) mode against `SimIMRPhenomXASFrequencySequence`	11	11 passed	663 ms
`test_xpnr_hm.py` Higher modes (release 122019) against `SimIMRPhenomXHMFrequencySequenceOneMode`	25	25 passed	215.8 s
`test_xpnr_msa.py` MSA and NNLO angles and the precession set-up, GSL's elliptic functions	87	87 passed	32.9 s
`test_xpnr_pnr_helpers.py` PNR fits and angle helpers against LAL's internal functions (ctypes)	55	55 passed	24.7 s
`test_xpnr.py` IMRPhenomXPNR polarizations: waveformrs's reference suite, with and without the parity fix	98	98 passed	279.4 s
`test_xpnr_modes.py` IMRPhenomXPNR J-frame modes, `ChooseFDModes`, version fallbacks, checks	12	12 passed	194.1 s
`test_xpnr_random.py` IMRPhenomXPNR, 64 random binaries against LAL (slow)	64	64 passed	67.1 s
`test_transforms_xpnr.py` IMRPhenomXPNR under `jit`, `vmap`, `grad` and `jvp`	5	5 passed	262.2 s
`test_nrsur7dq4.py` NRSur7dq4 polarizations, modes, dynamics, errors, data file, batches	37	37 passed	35.3 s
`test_nrsur7dq4_random.py` NRSur7dq4, 64 random binaries against LAL (slow)	1	1 passed	9.1 s
`test_transforms_nrsur7dq4.py` NRSur7dq4 under `jit`, `vmap` and `grad`, removable singularities	11	11 passed	79.1 s
`test_nrsur7dq4_float32.py` NRSur7dq4 in float32 (no float64 operation, accuracy, `jit`, `vmap`, `grad`) and the scale of its output	–	not in the last run	–
`test_conversions.py` `simulate_td` and `simulate_fd`: lengths, epochs, filters, tapers against LAL	31	31 passed	80.0 s
`test_transforms_conversions.py` The conversions as pure functions under `jit`, `vmap` and `grad`	6	6 passed	181.2 s

The full run with `WAVEFORMJAX_SLOW=1` (the random-draw tests) on the merged `main`, with `OMP_NUM_THREADS=1` for LALSimulation. Data: `report/data/pytest.xml`.

The tests are layered as the model was built: the (2,2) mode, then the higher modes, the angles, the PNR helpers, the polarizations and the modes. Each layer is compared at a tolerance set by what LAL itself can resolve there. The MSA angles, for example, are ill-conditioned for nearly aligned spins, where LAL's own output changes by ~5e-8 for a change of the inputs in the last bit. Every model also has a transform test. It checks that `jax.jit` and `jax.vmap` give the plain call, that gradients agree with central finite differences for every parameter, and that they are finite at removable singularities such as aligned, vanishing or single spins.

7 Accuracy

The random draws are those of waveformrs's report, so the two reports can be compared. For IMRPhenomXPNR: total masses log-uniform in 5–300 $M_\odot$, mass ratios uniform in 1/20–1, isotropic spins of magnitude up to 0.99, $f_{min} \in \{10, 15, 20\}$ Hz, $f_{ref} = f_{min}$ or up to 3 f_{min}, and isotropic lines of sight. For NRSur7dq4: mass ratios 1–6 with either body first, total masses 20–300 $M_\odot$, sampling at 1–8 kHz, and f_{min} above the surrogate's start or zero.



Largest relative error of each draw against total mass. Left: IMRPhenomXPNR on 4,096 uniformly spaced frequencies from f_{min} to min(0.3/M, 2048 Hz), without the parity fix against LALSimulation 6.2.0, and with it against 6.2.0 patched with lalsuite !2593. Right: NRSur7dq4 against `SimInspiralChooseTDWaveform`. Data: `report/data/validation_*.json`.

NRSur7dq4 agrees with LAL to 2.8×10^{-12} at most (median 2.6×10^{-13}), with LAL's length and epoch in every compared draw (200/200). LAL evaluates all 200 draws, and so does waveformjax. The residual comes from summing the fits in a different order and from XLA's own `exp`, `sin` and `cos`. The rotation to the inertial frame and the splines are linear, so the errors stay at rounding level. waveformrs, which agrees with LAL bit for bit, gives the same comparison (2.8×10^{-12}).

IMRPhenomXPNR agrees with LAL 6.2.0 to 6.6×10^{-5} at most, with median 5.0×10^{-7}, a 90th percentile of 3.2×10^{-6} and mismatches below 4.9×10^{-9}. The tests show where the difference comes from. The (2,2) mode alone, with its PNR angles and antisymmetric part, agrees to ~1e-9. The higher modes agree to ~1e-5, as different builds of LAL agree with each other. LAL fixes the intermediate amplitude of each higher mode with a fourth-order finite difference of the inspiral amplitude, with a step of 1e-9, which turns rounding of 1e-16 into ~1e-7 in the derivative. It fixes the intermediate phase of the (3,2) mode with a second derivative of a phase of up to 1e4 rad, by central differences with a step of 1e-7, amplifying rounding by ~1e14. Without fused multiply-adds, which JAX does not expose portably, the JAX arithmetic rounds differently from LAL's arm64 build, and these finite differences turn that into a visible difference. Neither value is more accurate than the other. The errors grow with the total mass, where the merger and ringdown, and so the higher modes, carry more of the band: the median is 2.9×10^{-7} below 20 $M_\odot$ and 1.5×10^{-6} above 150 $M_\odot$. The largest errors, a few 1e-5, are for heavy binaries with in-plane spins near 0.9. 2% of the draws exceed 1e-5.

With the parity fix, the model agrees with LAL 6.2.0 patched with lalsuite !2593 to 2.7×10^{-5} (median 5.9×10^{-7}, mismatch $\leq 2.8\times10^{-9}$, over 200 draws). On the same draws waveformrs agrees with that patched library to 3.4×10^{-15}. LAL evaluates all 200 draws, and so does waveformjax.

Conversions

FUNCTION	MODEL	BINARY	SETTING	MODES	SAMPLES	GRID	VS LAL	VS WAVEFORMRS	LAL MULTIBANDING	WAVEFORMJAX	WAVEFORMRS	LAL
`simulate_td`	IMRPhenomXPNR	36+29	4096 Hz from 20 Hz	all	13,006	`exact`	2.4×10^{-7}	2.4×10^{-7}	8.0×10^{-5}	38.42 ms	4.92 ms	12.52 ms
`simulate_td`	IMRPhenomXPNR	36+29	4096 Hz from 20 Hz	(2,±2)	13,006	`exact`	5.2×10^{-11}	5.2×10^{-11}	7.4×10^{-5}	25.77 ms	2.14 ms	6.04 ms
`simulate_td`	IMRPhenomXPNR	36+29	2048 Hz from 15 Hz	all	11,142	`exact`	2.4×10^{-7}	2.4×10^{-7}	4.2×10^{-5}	40.65 ms	8.05 ms	19.80 ms
`simulate_td`	IMRPhenomXPNR	36+29	2048 Hz from 15 Hz	(2,±2)	11,142	`exact`	8.6×10^{-12}	8.6×10^{-12}	4.0×10^{-5}	26.33 ms	3.37 ms	8.00 ms
`simulate_td`	IMRPhenomXPNR	60+40	2048 Hz from 20 Hz	all	5,398	`exact`	3.6×10^{-6}	3.6×10^{-6}	1.7×10^{-4}	31.22 ms	3.80 ms	9.28 ms
`simulate_td`	IMRPhenomXPNR	20+12	4096 Hz from 20 Hz	all	26,662	`exact`	2.6×10^{-6}	2.6×10^{-6}	3.9×10^{-5}	471 ms	20.64 ms	47.26 ms
`simulate_fd`	IMRPhenomXPNR	36+29	Δf from LAL, 20–2048 Hz	all	8,193	`exact`	2.9×10^{-8}	2.9×10^{-8}	3.8×10^{-5}	27.71 ms	3.82 ms	9.53 ms
`simulate_fd`	IMRPhenomXPNR	36+29	Δf from LAL, 20–2048 Hz	(2,±2)	8,193	`exact`	3.3×10^{-11}	3.3×10^{-11}	3.8×10^{-5}	23.87 ms	1.57 ms	3.67 ms
`simulate_fd`	IMRPhenomXPNR	36+29	Δf = 0.25, 19–1000 Hz	all	4,097	`exact`	2.8×10^{-8}	2.8×10^{-8}	3.6×10^{-5}	34.17 ms	4.01 ms	9.28 ms
`simulate_fd`	IMRPhenomXPNR	60+40	Δf = 0.125, 15–1024 Hz	all	8,193	`exact`	4.1×10^{-7}	4.1×10^{-7}	4.0×10^{-5}	34.13 ms	4.79 ms	11.41 ms
`simulate_td`	NRSur7dq4	40+20	4096 Hz from 20 Hz	all	4,225	`exact`	1.3×10^{-12}	1.3×10^{-12}	–	5.19 ms	1.29 ms	7.26 ms
`simulate_td`	NRSur7dq4	40+20	2048 Hz from 25 Hz	all	1,151	`exact`	3.1×10^{-13}	3.1×10^{-13}	–	4.82 ms	1.28 ms	6.89 ms
`simulate_td`	NRSur7dq4	70+30	2048 Hz from 14 Hz	all	2,619	`exact`	2.6×10^{-14}	2.6×10^{-14}	–	4.31 ms	1.34 ms	6.76 ms
`simulate_fd`	NRSur7dq4	40+20	Δf from LAL, 20–2048 Hz	all	4,097	`exact`	1.1×10^{-13}	1.1×10^{-13}	–	4.64 ms	1.20 ms	7.27 ms
`simulate_fd`	NRSur7dq4	40+20	Δf = 0.25, 19–1000 Hz	all	4,097	`exact`	8.5×10^{-14}	8.5×10^{-14}	–	4.81 ms	1.46 ms	7.32 ms
`simulate_fd`	NRSur7dq4	70+30	Δf = 0.125, 14–1024 Hz	all	8,193	`exact`	3.5×10^{-14}	3.5×10^{-14}	–	4.53 ms	1.20 ms	6.63 ms


End-to-end `simulate_td` and `simulate_fd` against `SimInspiralTD` and `SimInspiralFD` with multibanding off. IMRPhenomXPNR is without the parity fix. "Grid" says whether the length, epoch and sampling are LAL's exactly. Errors are max $|h - h_{LAL}|$ / max $|h_{LAL}|$ over both polarizations. "LAL multibanding" is how far LAL's default output, with multibanding on, is from the output without it. Times are for one call after the first. Data: `report/data/validation_conversions.json`.

All lengths, epochs and samplings are LAL's (16/16). With LAL's own model in place of the JAX one, the conversions agree with LAL to ~1e-12 of the peak in the time domain and to rounding in the frequency domain (`test_conversions.py`). The time-domain high-pass filter, whose poles are close to z = 1, amplifies the rounding differences of the Fourier transforms, which are not FFTW's, by ~1e4. End to end, NRSur7dq4 agrees to 1.3×10^{-12}, IMRPhenomXPNR's (2,2) mode to 5.2×10^{-11}, and all its modes to 3.6×10^{-6}, as the models do. LALSimulation's default multibanding, which waveformjax does not implement, changes LAL's own output by 3.6×10^{-5}–1.7×10^{-4}. This is far more than the differences between the implementations.

8 Derivatives

For each model and four binaries, every column of the Jacobian (`jax.jacfwd`) is compared with central finite differences of the compiled model. The error of a column is max $|J_i - D_i|$ / max $|J_i|$ over the frequencies or times and both polarizations. The finite

difference is the better of a second-order difference with a step of 1e-6 and a fourth-order difference with a step of 1e-4, both relative for the masses, the distance and f_{ref}. The first is limited by rounding, the second by the model's discontinuities.



Disagreement of each column of the Jacobian with finite differences, per parameter and binary. Data: `report/data/gradients.json`.

MODEL	BINARY	MASSES, DISTANCE, ANGLES, F_{REF}	SPINS	WORST PARAMETER	NOT DIFFERENTIABLE	FINITE
IMRPhenomXPNR	36+29, precessing	4.6×10^{-2}	1.5×10^{-1}	`spin_2y`	–	yes
IMRPhenomXPNR	40+20, precessing	4.1×10^{-2}	7.1×10^{-2}	`spin_2y`	–	yes
IMRPhenomXPNR	q = 1/6, strongly precessing	1.3×10^{-3}	1.5×10^{-2}	`spin_2y`	–	yes
IMRPhenomXPNR	nearly aligned spins	8.8×10^{-4}	4.8×10^{-2}	`spin_1y`	–	yes
NRSur7dq4	40+20, precessing	2.9×10^{-8}	4.1×10^{-9}	`f_ref`	–	yes
NRSur7dq4	lighter first, q = 1/3	1.5×10^{-8}	1.4×10^{-9}	`f_ref`	–	yes
NRSur7dq4	aligned spins	1.0×10^{-8}	1.0×10^{-9}	`f_ref`	–	yes
NRSur7dq4	non-spinning	1.3×10^{-8}	–	`f_ref`	`spin_1x`, `spin_1y`, `spin_1z`, `spin_2x`, `spin_2y`, `spin_2z` (zero spin)	yes
simulate_td IMRPhenomXPNR (2,2)	36+29, precessing	9.7×10^{-8}	2.7×10^{-7}	`spin_2x`	–	yes
simulate_fd NRSur7dq4	40+20, precessing	2.0×10^{-8}	3.9×10^{-9}	`f_ref`	–	yes

Largest column error by group of parameters. The conversions are `simulate_td_function` of IMRPhenomXPNR's (2,2) mode at 1024 Hz from 25 Hz and `simulate_fd_function` of NRSur7dq4 up to 1024 Hz from 20 Hz.

The derivatives are those of the function JAX computes, which is smooth almost everywhere but not everywhere. Wherever LAL makes a discrete choice that depends on the binary, the waveform is continuous only up to the size of that choice's effect, and the derivative is that of the branch taken. Such choices include the number of SpinTaylor samples, where LAL's adaptive integration stops, the node where NRSur7dq4's integration starts, the precession prescription, and the order of the intermediate polynomials of the higher modes. In IMRPhenomXPNR the SpinTaylor waveform jumps by about LAL's integration error, ~1e-9 relative, wherever the number of samples changes. A finite difference that straddles such a jump is wrong by the jump divided by the step, which is why small steps are used. The spins are the parameters that move the precession most, and they show the largest disagreements. For nearly aligned in-plane spins the waveform is also far from linear on the scale of the step. None of this affects the derivatives themselves, which are those of the smooth pieces.

One case is not a jump but a point where no derivative exists. After every step of its dynamics, NRSur7dq4 rescales each spin to its initial magnitude (LAL's `PrecessingNRSur_normalize_y`). For a body with no spin, an infinitesimal spin then evolves by a factor that depends on its direction, not only on its size. The waveform therefore has a cone-shaped kink in that body's three spin components: one-sided finite differences tend to different values, and no step size makes them converge. At such a point the JAX derivative is finite, as the transform tests require, but it is a convention rather than a derivative. The table reports these components apart. As soon as a body has any spin, even an aligned one, its derivatives agree with finite differences as for the other binaries.

IMRPhenomXPNR: under investigation. For the full IMRPhenomXPNR waveform, the finite differences disagree with the derivatives by up to 1.5×10^{-1}, by far the most in the in-plane spins. The transform tests, which compare the gradient of a weighted sum of the (2,2) mode with finite differences, agree to ~1e-7. The likely cause is in the higher modes. Their intermediate region is fixed by LAL's finite differences with steps of 1e-9 and 1e-7, which leave rounding noise of ~1e-8 in the waveform. That noise is not smooth in the parameters, so a parameter step of 1e-6 sees a slope of up to ~1e-2 relative from it alone, while the JAX tangents are

those of the exact derivatives. If so, the derivatives are right and the finite differences are not. The check still to run: the (2,2) mode alone, and the full model with larger steps, where that noise matters less.

Cost of derivatives

FUNCTION	COMPILE	VALUE	JVP	COMPILE JACFWD	JACFWD	COMPILE GRAD	GRAD	COMPILE VMAP(GRAD)	VMAP(GRAD) / BINARY	GRAD VS J^TW
IMRPhenomXPNR	31.5 s	15.15 ms	119 ms	107.6 s	114 ms	111.3 s	120 ms	535.3 s	104 ms	2.1×10^{-15}
NRSur7dq4	2.8 s	2.98 ms	6.25 ms	5.6 s	19.08 ms	9.3 s	17.82 ms	12.6 s	12.50 ms	4.2×10^{-15}
simulate_td IMRPhenomXPNR (2,2)	19.0 s	12.24 ms	91.01 ms	69.4 s	113 ms	71.4 s	95.84 ms	104.6 s	99.82 ms	1.7×10^{-13}
simulate_fd NRSur7dq4	1.7 s	2.92 ms	6.13 ms	6.1 s	24.01 ms	9.1 s	18.83 ms	10.1 s	14.67 ms	4.4×10^{-15}

Times of the first call (which compiles) and of later calls, for IMRPhenomXPNR on 2048 frequencies, NRSur7dq4 on 2048 samples and the two conversions. `grad` is of a scalar, a weighted sum of the polarizations. `vmap(grad)` is over 8 binaries (4 for the conversions). The last column is the relative difference between `jax.grad` and the Jacobian contracted with the same weights.

For IMRPhenomXPNR a gradient costs 120 ms, 7.9× the cost of a waveform. It is a forward-mode Jacobian of twelve columns, evaluated together. Its compilation takes 111.3 s. A `jax.jvp` along a direction that moves every parameter costs as much as `jax.jacfwd`, because the rule computes the columns of all the parameters with non-zero tangents and then contracts them. When only some parameters are differentiated, as in `jax.grad` with respect to the masses alone with the rest of the binary held fixed, only their columns are computed. NRSur7dq4 is differentiated directly in reverse mode: a gradient costs 17.82 ms (6.0× a waveform) after 9.3 s of compilation.

9 Performance


All timings are on the CPU (Apple M2 Ultra, 24 cores), with JAX's default settings and LALSimulation single-threaded. The binaries and grids are those of waveformrs's Python benchmark: IMRPhenomXPNR for 36 + 29 $M_\odot$ on 8033 frequencies (20–1024 Hz, $\Delta f = 1/8$ Hz), and NRSur7dq4 for 40 + 20 $M_\odot$ at 4096 Hz from 20 Hz. IMRPhenomXPNR is timed without the parity fix, which costs the same.

WAVEFORM	FIRST CALL	PUBLIC FUNCTION	COMPILED FUNCTION	WAVEFORMRS	LAL	LAL / COMPILED
IMRPhenomXPNR, 8033 frequencies	37.6 s	25.58 ms	16.18 ms	3.10 ms	13.54 ms	0.8×
NRSur7dq4, 4096 Hz from 20 Hz	2.6 s	3.16 ms	2.90 ms	1.07 ms	6.18 ms	2.1×
`simulate_td` of IMRPhenomXPNR, 4096 Hz from 20 Hz	33.2 s	36.48 ms	–	5.52 ms	13.96 ms	0.4×
`simulate_fd` of NRSur7dq4, up to 2048 Hz from 20 Hz	102 ms	3.57 ms	–	1.06 ms	5.76 ms	1.6×

One waveform per call. "First call" includes LAL's checks, tracing and compilation. "Public function" is a later call of `wf.polarizations` (or `td_polarizations`, `simulate_*`), including the checks on the host and the copy of the result. "Compiled function" is the jitted pure function alone. waveformrs is its fastest path from Python. Medians of 7 repeats. Every call is for a different binary of a cycle of 16. Data: `report/data/timings.json`.

A compiled IMRPhenomXPNR waveform takes 16.18 ms, against 13.54 ms for LALSimulation and 6.50 ms (3.10 ms on its grid path) for waveformrs. The public function adds 7.90 ms of checks on the host. To decide, as LAL would, whether a binary must change its precession prescription, they run a compiled pass through the set-up and the SpinTaylor integration; the pure function skips them. The JAX version is 5.2× slower than waveformrs's fastest path. The difference is the cost of being traceable. Every `jnp.where` evaluates both branches. Loops whose length depends on the binary run as `while_loop`s, which XLA cannot fuse across iterations. The SpinTaylor replica must step one GSL step at a time, and XLA's CPU code has no fused multiply-adds. XLA keeps about 3.2 cores busy for one IMRPhenomXPNR waveform, while LAL and waveformrs use one; JAX on a single core is still to be measured. NRSur7dq4 is dominated by vectorisable work (the fits at the nodes and the rotation of every mode sample), and takes 2.90 ms against 6.18 ms for LAL and 1.07 ms for waveformrs. The conversion `simulate_td` of IMRPhenomXPNR takes 36.48 ms, against 13.96 ms for LAL with multibanding off (11.53 ms with its default multibanding) and 5.52 ms for waveformrs.

Batches



Waveforms per second against the number of binaries per call of `jax.jit(jax.vmap(model))`, for binaries around the benchmark binary (masses ±10%, spin components in ±0.5, random angles). The horizontal lines are waveformrs's batch function and a loop over LALSimulation for 64 binaries.

BINARIES PER CALL	1	4	16	64	256
IMRPhenomXPNR, waveforms/s	42	54	72	93	102
IMRPhenomXPNR, compilation	45.3 s	46.2 s	48.2 s	46.7 s	50.6 s
IMRPhenomXPNR, cores busy	3.2	3.8	4.7	5.5	5.5
NRSur7dq4, waveforms/s	353	513	652	736	742
NRSur7dq4, compilation	2.2 s	2.2 s	2.2 s	2.3 s	4.6 s
NRSur7dq4, cores busy	6.0	4.1	4.3	6.9	7.3

Throughput, compilation time and cores kept busy (process CPU time over wall time) for each batch size. NRSur7dq4 is evaluated on LAL's output grid of the benchmark binary.

64 BINARIES	LAL LOOP	WAVEFORMRS, 1 THREAD	WAVEFORMRS, ALL THREADS	WAVEFORMJAX	FIRST CALL
IMRPhenomXPNR	72	311	4,293	53	48.9 s
NRSur7dq4	152	916	11,102	666	2.6 s

Waveforms per second through the public batch functions (`batch_polarizations`, `batch_td_polarizations`), including LAL's checks of every binary on the host.

Under `jax.vmap`, IMRPhenomXPNR reaches 102 waveforms per second. Batching amortises the per-call overhead and XLA spreads the vectorised work over cores, but the loops run to the longest binary in the batch and the branches of all binaries are computed. Each batch size is compiled separately (46.7 s for 64). waveformrs on all threads, with a thread per binary and no padding, remains faster on a CPU. The JAX version is meant for code that is itself written in JAX: a likelihood that is jitted and differentiated end to end, or a sampler that runs on an accelerator.

10 Differences from LALSimulation

- **Rounding, not bit-identity.** waveformrs reproduces LAL bit for bit on macOS arm64, using the fused multiply-adds that clang emits. JAX has no portable fused multiply-add and XLA reorders arithmetic, so waveformjax agrees with LAL to rounding (NRSur7dq4, the (2,2) mode of IMRPhenomXPNR) or to the rounding amplified by LAL's own finite differences (the higher modes, ~1e-5). Only where LAL's decisions hinge on the last bits are its fused multiply-adds reproduced exactly: the PNR inflection points and, on the host, the conversions' lengths and epochs.
- **SpinTaylor backward integration.** The integration from `f_ref` down to `f_min` is a dense Dormand–Prince solution, not LAL's RKF45 steps. It differs from LAL's samples by LAL's integration error (~1e-9).
- **Values where LAL divides by zero.** At isolated points of the parameter space, LAL's MSA formulas divide by an exact zero and produce inf or NaN. Here the values there are finite, and so are the gradients nearby, for example at equal masses or for a single spin.
- **No multibanding.** LAL's `SimInspiralChooseFDWaveform` uses multibanding by default for IMRPhenomXPNR; waveformjax, like waveformrs, evaluates every frequency. `SimInspiralChooseFDWaveformSequence` has multibanding off, and the conversions are compared with it off.
- **No data race.** LAL's MSA and PNR angles race under OpenMP. waveformjax agrees with single-threaded LAL.

- **The scale of NRSur7dq4's output.** NRSur7dq4 returns the strain times 10^{21}, and computes the masses and the amplitude without SI intermediates, which changes its float64 values by rounding. `scaled_strain=False`, which `WaveformOptions.lalsimulation_defaults()` also sets, gives LAL's scale.
- **Two options that are not LAL's defaults.** With `version_fallback=False` the compiled model contains only the SpinTaylor prescription and is NaN where LAL would switch to the MSA or NNLO angles. With `extended_spintaylor=True` it is a different model: the SpinTaylor angles for every binary, with LAL's discrete switches made continuous. A separate report, `report/extended`, maps where the SpinTaylor angles fail and describes and validates the extended model.

11 Limitations and future work

- **Two approximants.** Only IMRPhenomXPNR and NRSur7dq4 are public. IMRPhenomXAS and the 122019 higher modes exist as parts of IMRPhenomXPNR, but IMRPhenomXHM, XP and XPHM with their own flags, TaylorF2 and IMRPhenomD are not exposed.
- **Compilation time.** IMRPhenomXPNR takes tens of seconds to compile, its gradient minutes, and every array shape and batch size compiles separately. JAX's persistent compilation cache (`jax_compilation_cache_dir`) would make the cost one-off per machine; it is not set up by the package.
- **Accelerators untested.** Everything here ran on the CPU. IMRPhenomXPNR uses float64 JAX operations, which are slow on consumer GPUs. NRSur7dq4 also runs in float32, but only through its pure functions, since the public functions and the conversions are float64. Neither model's accuracy or speed has been measured on a GPU.
- **Forward-mode derivatives of IMRPhenomXPNR.** A gradient costs one Jacobian column per parameter with a non-zero tangent, evaluated together. That is affordable for the twelve parameters of a binary (section 8), but it does not scale to derivatives with respect to the frequencies or to many other inputs. A reverse-mode path would need the loops with traced lengths rewritten with fixed bounds.
- **Discontinuities.** The waveform inherits LAL's discrete choices. Gradient-based samplers near a regime boundary, such as in-plane spins near 1e-6, or a SpinTaylor integration that just fails, see the derivative of one side only.
- **Long waveforms.** For light binaries from low frequencies the SpinTaylor splines have millions of knots and the conversions' Fourier transforms millions of samples. These are fixed-shape arrays held in memory, and both cost and compilation grow with them.
- **Multibanding.** LAL's multibanding is not implemented (as in waveformrs).

12 Reproducing the results

```
# environment (conda-forge), with waveformrs checked out next to waveformjax
mamba create -n waveformjax -c conda-forge python=3.12 python-lalsimulation jax numpy h5py scipy matplotlib pytest
conda activate waveformjax
pip install -e .
(cd ../waveformrs/python && maturin develop --release)       # optional: the waveformrs comparisons

# the tests (the data file NRSur7dq4_v1.0.h5 from zenodo.org/records/14999310,
# found through NRSUR7DQ4_DATA, LAL_DATA_PATH or ../waveformrs/lal_data)
WAVEFORMJAX_SLOW=1 python -m pytest

# IMRPhenomXPNR with the parity fix needs LALSimulation 6.2.0 + lalsuite !2593
CC=/path/to/conda-forge/clang-19 bash ../waveformrs/scripts/build_patched_lalsimulation.sh ../lalsuite build/lal-2593
export PATCHED_LALSIMULATION=$PWD/build/lal-2593/liblalsimulation.37.dylib

# every measurement and this report, on an idle machine
bash report/measure_all.sh

# or one at a time
python report/validate_xpnr.py --n-draws 200
python report/validate_nrsur7dq4.py --n-draws 200
python report/float32_nrsur7dq4.py
python report/validate_conversions.py
python report/gradients.py
python report/benchmark.py
python report/build_report.py
```

13 Commit history

The commits on `main`, oldest first. The package was built model by model and milestone by milestone, each checked against LAL before the next. The conversions and the speed-ups of IMRPhenomXPNR were developed in parallel on two branches and merged. Commits that only add or regenerate this report are not listed. The repository has no remote.

COMMIT	TYPE	SUMMARY
229d095	FEAT	the waveformjax package: the waveformrs interface over JAX models
7494344	DOC	per-model transform tests in AGENTS.md
48c6d70	FEAT	NRSur7dq4 data reader, parameter-space fits and GSL interpolation in JAX
839cf04	FEAT	NRSur7dq4 dynamics as fixed-size JAX loops
4da7038	FEAT	NRSur7dq4 coorbital waveform, frame rotation and polarizations

COMMIT	TYPE	SUMMARY
cf2462d	FEAT	NRSur7dq4 MODEL: LAL's checks, output grid, modes and batches
4b1fead	TST	find the NRSur7dq4 data next to a parent directory (git worktrees)
c296de4	TST	NRSur7dq4 against LALSimulation 6.2.0 and under jit, vmap and grad
20502f6	PERF	NRSur7dq4 splines with GSL's factorised systems, cached output grids
a303ecb	DOC	NRSur7dq4 in the README and its original code in NOTICE.md
9d7cb40	DOC	NRSur7dq4 dynamics docstring; share |ra|^2a |rb|^2b in the rotation
f5f9745	PERF	NRSur7dq4 dynamics steps as a few vector operations
d0acb33	MAINT	drop an unused table of the NRSur7dq4 waveform module
0c084c5	FEAT	IMRPhenomXAS (2,2) mode in JAX, with the fits generated from waveformrs
ea84f6e	FEAT	PNR fits and angle helpers, and the SpinTaylor evolution in JAX
91fe045	FEAT	IMRPhenomXHM release 122019 higher modes in JAX
2fcc136	FEAT	MSA (223), NNLO (102) and SpinTaylor (330) precession angles in JAX
8761b4d	FEAT	IMRPhenomXPNR polarizations in JAX
c7f6cba	FIX	one optimization barrier per value
59e311b	FEAT	IMRPhenomXPNR J-frame modes, validation and transform tests
0b05193	TEST	one switch, WAVEFORMJAX_SLOW=1, for the random-draw tests of both models
afe668f	TEST	the NRSur7dq4 random-draw test requires most draws compared, for any NRSUR7DQ4_DRAWS
f57a940	FEAT	LAL's conditioning in JAX: duration bounds, epochs, tapers and the Butterworth filter
787c98e	FEAT	simulate_td and simulate_fd: LAL's SimInspiralTD and SimInspiralFD
a182f49	DOC	the conversions in the README, and their original code in NOTICE.md
4e5a7ae	TEST	the conversions against SimInspiralTD and SimInspiralFD
c9e8eba	DOC	the XPNR adapter's values depend on the whole frequency array
9bdcf41	DOC	the accuracy of the conversions, as measured
568227a	TEST	the conversions as pure functions under jit, vmap and grad
545046e	PERF	SpinTaylor derivatives with the 3-vectors as arrays
eb49f8b	PERF	GSL's quintic solver in loops that end where GSL's do
4fe9828	PERF	IMRPhenomXPNR derivatives in forward mode, batched under jax.vmap
a2d6a68	PERF	the intermediate polynomials of the higher modes chosen together
8e042ff	PERF	one branch for PNR versions 102 and 223; smaller SpinTaylor code
b5c0df1	PERF	only the PNR beta of the binary's region; alpha of the antisymmetric part where used
864c255	PERF	batch-aware branches and loop bodies traced under jax.jit
4476314		Merge the IMRPhenomXPNR compile, batching and forward-mode speed-ups
deeffce	FIX	the conversions of IMRPhenomXPNR differentiate the model in forward mode
0a93b55	FIX	NRSur7dq4 data read inside jax.jit are concrete arrays
027e282	FEAT	IMRPhenomXPNR without fallbacks, and extended, continuous SpinTaylor angles
c31b9c3	FEAT	NRSur7dq4 in float32, with the strain times 1e21 by default
366535e	FEAT	smoother extended XPNR angles where LAL samples a step or a branch
321ebea	DOC	the smoothness study of the extended XPNR model (measurement and draft section)