UK Housing Market API

1.0.0 OAS 3.0

REST API for UK housing sales, affordability, and rental metrics based on ONS and UK House Price Index (HPI) data. Provides housing-sales data, buyer-dwelling breakdowns, affordability metrics, rental metrics, and an affordability index that compares your salary to regional rents and implied borrower income.

Servers

/ - Current host

Authorize

Lookups

Reference data for filters and dropdowns

- GET /api/regions List regions
- POST /api/regions Create a region (admin)
- PUT /api/regions/{id} Update a region (admin)
- DELETE /api/regions/{id} Delete a region (admin)
- GET /api/property-types List property types
- GET /api/buyer-dwelling-categories List buyer/dwelling categories

Housing & rental data

Time-series and filtered datasets

- GET /api/housing-sales Housing sales data (UKHPI)
- GET /api/housing-sales-by-buyer Housing sales by buyer and dwelling type
- GET /api/rental-metrics Rental metrics

Affordability

Affordability metrics and index

- GET /api/affordability Affordability metrics
- GET /api/affordability-index Affordability index (salary vs rent)

AI insights

LLM-generated market analysis (deployer-configured Gemini; no consumer API key)

GET `/api/analysis/market-summary` Market summary by query (LLM)

GET `/api/analysis/{region_id}` Market summary by region ID (LLM)

Health API health check

GET `/api/names` API health check

Schemas

Error {

```
   description:          Standard error response returned for 400, 401, 404, 409, and 500 responses.
   error*                    [...]
   message                   [...]
}
example: { "error": "Bad Request", "message": "salary query parameter is required" }
```

SuccessList {

```
   description:          Paginated list response used by GET endpoints that return arrays. Contains count, optional limit/offset, and a data array.
   count                     [...]
   limit                     [...]
   offset                    [...]
   data                      [...]
}
```

Region {

```
   description:          A geographic region (e.g. United Kingdom, or an ONS area from rental data). Used for filtering housing and rental endpoints.
   id                        [...]
   name                      [...]
   gss_code                  [...]
}
example: { "id": 1, "name": "United Kingdom", "gss_code": "K02000001" }
```

RegionCreate {

```
   description:          Request body for creating a region (POST /api/regions). Admin only; requires x-api-key.
   name*                     [...]
   gss_code                  [...]
}
```

RegionUpdate {

```
   description:          Request body for updating a region (PUT /api/regions/{id}). At least one field required. Admin only; requires x-api-key.
   name                      [...]
   gss_code                  [...]
}
minProperties: 1
```

PropertyType {

description: A property type from the UKHPI taxonomy (e.g. All property types, Detached houses). Used to filter housing-sales.

id [...]

type_name [...]

}

BuyerDwellingCategory {

description: Category combining buyer type and dwelling type (e.g. First time buyers / New dwellings). Used to filter housing-sales-by-buyer and affordability.

id [...]

name [...]

}

AffordabilityIndexSuccess {

description: Response from GET /api/affordability-index. Compares your salary to regional rent and implied income; includes a health score and ratios.

region {...}

inputs {...}

rental_snapshot {...}

ratios {...}

health_score [...]

health_explanation [...]

}

HealthCheckResponse {

description: Response from GET /api/names. Confirms API and database connectivity.

message [...]

timestamp [...]

data [...]

}

MarketSummarySuccess {

description: Response from GET /api/analysis/market-summary or GET /api/analysis/{region_id}. Expert market analysis: LLM-generated 150-word executive summary grounded in HPI, rental, and affordability data.

region {...}

summary [...]

data_snapshot {...}

generated_at [...]

}