

Review

Position ADT

Amortized Analysis & Trees

1

Position ADT

- ◆ The **Position** ADT models the notion of place within a data structure where a single object is stored
- ◆ It gives a unified view of diverse ways of storing data, such as
 - a cell of an array
 - a node of a linked list or tree
- ◆ Just one method:
 - object **element()**: returns the element stored at the position

Stacks, Queues, Vectors, & Lists

2

List Operations

- ◆ The **List** ADT models a sequence of positions storing arbitrary objects
- ◆ It establishes a before/after relation between positions
- ◆ Generic methods:
 - **size()**, **isEmpty()**
- ◆ Query methods:
 - **isFirst(p)**, **isLast(p)**

Accessor methods:

- **first()**, **last()**
- **before(p)**, **after(p)**

Update methods:



- **replaceElement(p, e)**, **swapElements(p, q)**
- **insertBefore(p, e)**, **insertAfter(p, e)**
- **insertFirst(e)**, **insertLast(e)**
- **remove(p)**

Stacks, Queues, Vectors, & Lists

3

Doubly Linked List

- ◆ A doubly linked list provides a natural implementation of the List ADT
- ◆ Nodes implement Position and store:
 - element
 - link to the previous node
 - link to the next node
- ◆ Special header and trailer nodes




Stacks, Queues, Vectors, & Lists

4

Array-based Implementation

- ◆ We use a circular array storing positions
- ◆ A position object stores:
 - Element
 - Rank
- ◆ Indices f and l keep track of first and last positions




Sequences

5

Circular Array-based ADT's

- ◆ Use an array of size N in a circular fashion
- ◆ Two variables keep track of the front and rear
 - f index of the front element
 - r index immediately past the rear element
- ◆ Array location r is kept empty



Stacks, Queues, Vectors, & Lists

6

Lecture 3: Trees and Amortized Analysis

Sequential Unfoldment of Natural Law

Amortized Analysis & Trees

7


Wholeness Statement

Trees are data structures that provide wide ranging capabilities and a highly flexible perspective on a set of element objects.
Science of Consciousness: The whole range of space and time is open to individuals with fully developed awareness. Through the regular twice daily practice of the TM technique, alternated with dynamic activity, we develop more and more of our full potential as demonstrated by 100's of published scientific studies.

Amortized Analysis & Trees

8

Trees



Amortized Analysis & Trees

9

Outline and Reading


- ◆ Tree ADT (§2.3.1)
- ◆ Preorder and postorder traversals (§2.3.2)
- ◆ BinaryTree ADT (§2.3.3)
- ◆ Inorder traversal (§2.3.3)
- ◆ Euler Tour traversal (§2.3.3)
- ◆ Template method pattern
- ◆ Data structures for trees (§2.3.4)

Amortized Analysis & Trees

10

What is a Tree

- ◆ In computer science, a tree is an abstract model of a hierarchical structure
- ◆ A tree consists of nodes with a parent-child relation
- ◆ Applications:
 - Organization charts
 - File systems
 - Programming environments




Amortized Analysis & Trees

11

Tree Terminology

- ◆ **Root**: only node without parent (A)
- ◆ **Internal node**: node with at least one child (A, B, C, F)
- ◆ **External node** (a.k.a. leaf): node without children (E, I, J, K, G, H, D)
- ◆ **Ancestors of a node**: parent, grandparent, grand-grandparent, etc.
- ◆ **Depth of a node**: number of ancestors
- ◆ **Height of a tree**: maximum depth of any node (3 in tree to right)
- ◆ **Descendant of a node**: child, grandchild, grand-grandchild, etc.
- ◆ **Subtree**: tree consisting of a node and its descendants



Amortized Analysis & Trees

12

Tree ADT

- ◆ We use positions to abstract nodes
- ◆ Generic methods:
 - integer `size()`
 - boolean `isEmpty()`
 - objectIterator `elements()`
 - positionIterator `positions()`
- ◆ Accessor methods:
 - position `root()`
 - position `parent(p)`
 - positionIterator `children(p)`
- ◆ Query methods:
 - boolean `isInternal(p)`
 - boolean `isExternal(p)`
 - boolean `isRoot(p)`
- ◆ Update methods:
 - `swapElements(p, q)`
 - object `replaceElement(p, o)`
- ◆ Additional update methods may be defined by data structures implementing the Tree ADT

Amortized Analysis & Trees

13


Preorder Traversal

- ◆ A traversal visits the nodes of a tree in a systematic manner
- ◆ In a preorder traversal, a node is visited before its descendants
- ◆ Application: print a structured document

Algorithm *preOrder*(*T*, *v*)

```

visit(v)
for each w of T.children(v)
    preOrder(T, w)
    
```



Amortized Analysis & Trees

14


Postorder Traversal

- ◆ In a postorder traversal, a node is visited after its descendants
- ◆ Application: compute space used by files in a directory and its subdirectories

Algorithm *postOrder*(*T*, *v*)

```

for each w of T.children(v)
    postOrder(T, w)
visit(v)
    
```




Amortized Analysis & Trees

15

Data Structure for Trees

- ◆ A node is represented by an object storing
 - Element
 - Parent node
 - Sequence of children nodes
- ◆ Node objects implement the Position ADT



Amortized Analysis & Trees

16

Performance of Tree ADT Linked Implementation

- ◆ Generic methods:
 - integer `size()`
 - boolean `isEmpty()`
 - objectIterator `elements()`
 - positionIterator `positions()`
- ◆ Accessor methods:
 - position `root()`
 - position `parent(p)`
 - positionIterator `children(p)`
- ◆ Query methods:
 - boolean `isInternal(p)`
 - boolean `isExternal(p)`
 - boolean `isRoot(p)`
- ◆ Update methods:
 - `swapElements(p, q)`
 - object `replaceElement(p, o)`

Amortized Analysis & Trees

17

Linked Implementation of the Tree ADT

Operation	Time
<code>size</code> , <code>isEmpty</code>	
<code>positions</code> , <code>elements</code>	
<code>swapElements(p, q)</code> , <code>replaceElement(p, o)</code>	
<code>root()</code> , <code>parent(p)</code>	
<code>children(v)</code>	
<code>isInternal(p)</code> , <code>isExternal(p)</code> , <code>isRoot(p)</code>	

Amortized Analysis & Trees

18

Linked Implementation of the Tree ADT

Operation	Time
size, isEmpty	1
positions, elements	n
swapElements(p, q), replaceElement(p, o)	1
root, parent(p)	1
children(v)	c_v
isInternal(p), isExternal(p), isRoot(p)	1

Amortized Analysis & Trees

19

Main Point

1. The Tree ADT models a hierarchical structure between objects simplified to a parent-child relation. Nodes store arbitrary objects/elements and connect to other nodes in the tree. A rooted tree has a root node without a parent; all other nodes have parents.


Science of Consciousness: Pure consciousness is the root of the tree of life. Regular contact with pure consciousness waters that root and re-connects individual consciousness with pure consciousness by removing stress and strain resulting in positive benefit of everyone.

Amortized Analysis & Trees

20

Binary Tree

- ◆ A (proper) binary tree is a tree with the following properties:
 - Each internal node has two children
 - The children of a node are an ordered pair
- ◆ We assume that all binary trees are proper
- ◆ We call the children of an internal node left child and right child
- ◆ A binary tree is either
 - a tree consisting of a single node, or
 - a tree whose root has an ordered pair of children, each of which is a binary tree




Amortized Analysis & Trees

21

Arithmetic Expression Tree

- ◆ Binary tree associated with an arithmetic expression
 - internal nodes: operators
 - external nodes: operands
- ◆ Example: arithmetic expression tree for the expression $(2 \times (a - 1) + (3 \times b))$




Amortized Analysis & Trees

22

Decision Tree

- ◆ Binary tree associated with a decision process
 - internal nodes: questions with yes/no answer
 - external nodes: decisions
- ◆ Example: dining decision



Amortized Analysis & Trees

23


Binary Tree Theorem 2.8 (page 84)

Properties of (Proper) Binary Trees

0. $e = i + 1$
1. $h \leq i \leq 2^h - 1$
2. $h + 1 \leq e \leq 2^h$
3. $2h + 1 \leq n \leq 2^{h+1} - 1$
4. $\log(n + 1) - 1 \leq h \leq (n - 1)/2$

where

- n number of nodes
- h height of the tree
- e number of external nodes
- i number of internal nodes



Amortized Analysis & Trees

24

Proof of Theorem 2.8

Properties 2, 3, and 4 can be proven based on Property 1.

Property 2:

$h \leq i \leq 2^h - 1$ (Property 1)
 $\Leftrightarrow h \leq e - 1 \leq 2^h - 1$ (Property 0, $e = i + 1$)
 $\Leftrightarrow h + 1 \leq e \leq 2^h$ (arithmetic) ■

Property 3:

$h + 1 \leq e \leq 2^h \wedge h \leq i \leq 2^h - 1$ (Properties 1 and 2)
 $\Leftrightarrow 2h + 1 \leq e + i \leq 2^h + 2^h - 1$ (arithmetic)
 $\Leftrightarrow 2h + 1 \leq n \leq 2^{h+1} - 1$ (since $n = i + e$ and $2(2^h) = 2^{h+1}$) ■

Property 4:

$n = 2e - 1$ (since $i = e - 1$ and $n = i + e$)
 $\Leftrightarrow (n + 1)/2 = e$ (algebra)
 $\Leftrightarrow (n + 1)/2 = e \wedge h + 1 \leq (n + 1)/2$ (since $h + 1 \leq e$, from Property 1)
 $\Leftrightarrow (n + 1)/2 = e \wedge h \leq (n - 1)/2$ (algebra)
 $\Leftrightarrow (n + 1)/2 \leq 2^h \wedge h \leq (n - 1)/2$ ($e \leq 2^h$, from Property 1)
 $\Leftrightarrow \log_2(n + 1)/2 \leq \log_2 2^h \wedge h \leq (n - 1)/2$ (logarithms)
 $\Leftrightarrow \log_2(n + 1) - 1 \leq h \wedge h \leq (n - 1)/2$ (logarithms) ■

Amortized Analysis & Trees

25


Properties of Binary Trees

Notation

n number of nodes
 e number of external nodes
 i number of internal nodes
 h height

Properties:

- $e = i + 1$
- $n = 2e - 1$
- $h \leq i$
- $h \leq (n - 1)/2$
- $e \leq 2^h$
- $h \geq \log_2(i + 1)$
- $h \geq \log_2(n + 1) - 1$



Amortized Analysis & Trees

26

BinaryTree ADT

- The BinaryTree ADT extends the Tree ADT, i.e., it inherits all the methods of the Tree ADT
- Update methods may be defined by data structures implementing the BinaryTree ADT

Additional methods:


- position **leftChild**(p)
- position **rightChild**(p)
- position **sibling**(p)

Amortized Analysis & Trees

27

Data Structure for Binary Trees

- A node is represented by an object storing:
 - Element
 - Parent node
 - Left child node
 - Right child node
- Node objects implement the Position ADT



Trees


28

28

Preorder Traversal

- A traversal visits the nodes of a tree in a systematic manner
- In a preorder traversal, a node is visited before its descendants
- Application: print a structured document

Algorithm *preOrder*(T, v)
 if *T.isExternal*(v) then
 visitExternal(v)
 else
 visitInternal(v)
 preOrder(T, *T.leftChild*(v))
 preOrder(T, *T.rightChild*(v))



Trees


29

29

Postorder Traversal

- In an inorder traversal a node is visited after its left subtree and before its right subtree
- Application: evaluate a binary expression or type check an expression and its sub-expressions

Algorithm *postOrder*(T, v)
 if *T.isExternal*(v) then
 visitExternal(v)
 else
 postOrder(T, *T.leftChild*(v))
 postOrder(T, *T.rightChild*(v))
 visitInternal(v)



Trees


30

30

Inorder Traversal

- In an inorder traversal a node is visited after its left subtree and before its right subtree
- Application: draw a binary tree
 - $x(v)$ = inorder rank of v
 - $y(v)$ = depth of v

Algorithm *inOrder*(T, v)
 if $T.isExternal(v)$ then
 visitExternal(v)
 else
 inOrder($T, T.leftChild(v)$)
 visitInternal(v)
 inOrder($T, T.rightChild(v)$)



Trees


31

31

Inorder Traversal (variation)

- In an inorder traversal a node is visited after its left subtree and before its right subtree
- Application: draw a binary tree
 - $x(v)$ = inorder rank of v
 - $y(v)$ = depth of v

Algorithm *inOrder*(T, v)
 if $T.isInternal(v)$ then
 inOrder($T, T.leftChild(v)$)
 visit(v)
 if $T.isInternal(v)$ then
 inOrder($T, T.rightChild(v)$)



Amortized Analysis & Trees


32

32

Evaluate Arithmetic Expressions

- Specialization of a postorder traversal
 - recursive method returning the value of a subtree
 - when visiting an internal node, combine the values of the subtrees

Algorithm *evalExpr*(T, v)
 if $T.isExternal(T.leftChild(v))$ then
 return $v.element()$
 else
 $x \leftarrow evalExpr(T, T.leftChild(v))$
 $y \leftarrow evalExpr(T, T.rightChild(v))$
 $\Diamond \leftarrow$ operator stored at v
 return $x \Diamond y$



Trees


33

33

Print Arithmetic Expressions

- Specialization of an inorder traversal
 - print operand or operator when visiting node
 - print "(" before traversing left subtree
 - print ")" after traversing right subtree

Algorithm *printExpression*(T, v)
 if $T.isInternal(T.leftChild(v))$ then
 print("(")
 printExpression($T, T.leftChild(v)$)
 print($v.element()$)
 if $T.isInternal(T.rightChild(v))$ then
 printExpression($T, T.rightChild(v)$)
 print(")")



Trees

34

34

$((2 \times (a - 1)) + (3 \times b))$

Exercise on Binary Trees

- Generic methods:
 - integer size()
 - boolean isEmpty()
 - objectIterator elements()
 - positionIterator positions()
- Accessor methods:
 - position root()
 - position parent(p)
 - positionIterator children(p)
- Query methods:
 - boolean isInternal(p)
 - boolean isExternal(p)
 - boolean isRoot(p)
- Update methods:
 - swapElements(p, q)
 - object replaceElement(p, o)
- Additional BinaryTree methods:
 - position leftChild(p)
 - position rightChild(p)
 - position sibling(p)

Exercise:
 Write a method to calculate the sum of the integers in a binary tree of integers
 Assume that an integer is stored at each internal node and nothing in external nodes

Algorithm sum(T)

Hint: you also need a helper function with argument Position p

Algorithm sumHelper(T, p)

Amortized Analysis & Trees

35

35

Exercise on Binary Trees

- Generic methods:
 - integer size()
 - boolean isEmpty()
 - objectIterator elements()
 - positionIterator positions()
- Accessor methods:
 - position root()
 - position parent(p)
 - positionIterator children(p)
- Query methods:
 - boolean isInternal(p)
 - boolean isExternal(p)
 - boolean isRoot(p)
- Update methods:
 - swapElements(p, q)
 - object replaceElement(p, o)
- Additional BinaryTree methods:
 - position leftChild(p)
 - position rightChild(p)
 - position sibling(p)

Exercise:
 Write a method to find the largest integer in a binary tree of integers
 Assume that an integer is stored at each internal node and nothing in external nodes (i.e., external nodes are null)

Algorithm findLargest(T)

Hint: you also need a helper function with argument Position p


Amortized Analysis & Trees

36

36

Data Structure for Binary Trees

- ◆ Another alternative: use an array to store the binary tree.
- ◆ Node objects are referenced by index:
 - Index 0 is empty and not used.
 - Root node is at index 1
 - Left child is at $2 \times \text{index}$
 - Right child is at $2 \times \text{index} + 1$



Amortized Analysis & Trees

37

Array-Based Implementation of Binary Tree

Operation	Time
size, isEmpty	
positions, elements	
swapElements(p, q), replaceElement(p, e)	
root, parent(p), children(p)	
isInternal(p), isExternal(p), isRoot(p)	

Amortized Analysis & Trees

38

Array-Based Implementation of Binary Tree


Operation	Time
size, isEmpty	1
positions, elements	n
swapElements(p, q), replaceElement(p, e)	1
root, parent(p), children(p)	1
isInternal(p), isExternal(p), isRoot(p)	1

Amortized Analysis & Trees

39

Euler Tour Traversal

- ◆ Generic traversal of a binary tree
- ◆ Includes as special cases the preorder, postorder, and inorder traversals
- ◆ Walk around the tree and visit each node three times:
 - on the left (preorder)
 - from below (inorder)
 - on the right (postorder)



Amortized Analysis & Trees

40

Template Method Pattern

- ◆ Generic algorithm that can be specialized by redefining certain steps
- ◆ Implemented by means of an abstract Java class
- ◆ Visit methods that can be redefined/overridden by subclasses
- ◆ Template method `eulerTour`
 - Recursively called on the left and right children
 - A `result` array that keeps track of the output of the recursive calls to `eulerTour`
 - `result[0]` keeps track of the final output of the `eulerTour` method
 - `result[1]` keeps track of the output of the recursive call of `eulerTour` on the left child
 - `result[2]` keeps track of the output of the recursive call of `eulerTour` on the right child

Amortized Analysis & Trees

41

Recall Our Earlier Example of the Template Method Pattern in Java

```
public abstract class EulerTour {
    protected void visitExternal(BinaryTree tree, Position p, Object[] r) {}
    protected void visitPreOrder(BinaryTree tree, Position p, Object[] r) {}
    protected void visitInOrder(BinaryTree tree, Position p, Object[] r) {}
    protected void visitPostOrder(BinaryTree tree, Position p, Object[] r) {}
    protected Object eulerTour(BinaryTree tree, Position p) {
        Object[] result = new Object[3];
        if (tree.isExternal(p)) { visitExternal(tree, p, result); }
        else {
            visitPreOrder(tree, p, result);
            result[1] = eulerTour(tree, tree.leftChild(p));
            visitInOrder(tree, p, result);
            result[2] = eulerTour(tree, tree.rightChild(p));
            visitPostOrder(tree, p, result);
        }
        return result[0];
    }
}
```

42

Specializations of EulerTour

```
public class Sum extends EulerTour {
    // Sums the integers in a Binary Tree of Integers
    protected void visitExternal(BinaryTree t, Position p, Object[] res) {
        res[0] = new Integer(0);
    }
    protected void visitPostOrder(BinaryTree t, Position p, Object[] res) {
        res[0] = ((Integer) res[1]) + ((Integer) res[2] + p.element());
    }
    public Integer sum(BinaryTree t) {
        return eulerTour(T, T.root());
    }
}
```

- ◆ We specialize class EulerTour to sum the Integers in a binary tree
- ◆ Assumptions
 - External nodes do not store objects
 - Internal nodes store Integer

Amortized Analysis & Trees

43

Main Point

2. Each internal node of a Binary Tree has two children and each external node has no children. Thus the height, h , of a binary tree ranges as follows: $i \geq h \geq \log_2(i+1)$, that is, $O(\log_2 n) \leq h \leq O(n)$.
Science of Consciousness: Pure consciousness spans the full range of life, from smaller than the smallest to larger than the largest.

Amortized Analysis & Trees

44

Review and Relatives of Big-O

Review of Big Oh notation

Definition:

$f(n)$ is $O(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \leq c \cdot g(n)$ for all $n \geq n_0$

- ◆ $f(n)$ is $O(g(n))$ means that
 - $f(n)$ is asymptotically less than $g(n)$
 - $g(n)$ is an asymptotic upper bound on $f(n)$

Stacks, Queues, Vectors, & Lists

46

Relatives of Big-Oh



- ◆ **big-Omega**
 - $f(n)$ is $\Omega(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \geq c \cdot g(n)$ for all $n \geq n_0$
- ◆ **big-Theta**
 - $f(n)$ is $\Theta(g(n))$ if there are constants $c_1 > 0$ and $c_2 > 0$ and an integer constant $n_0 \geq 1$ such that $c_1 \cdot g(n) \leq f(n) \leq c_2 \cdot g(n)$ for all $n \geq n_0$

47

Intuition for Asymptotic Notation



Big-Oh

- $f(n)$ is $O(g(n))$ if $f(n)$ is asymptotically **less than or equal to** $g(n)$

big-Omega

- $f(n)$ is $\Omega(g(n))$ if $f(n)$ is asymptotically **greater than or equal to** $g(n)$

big-Theta

- $f(n)$ is $\Theta(g(n))$ if $f(n)$ is asymptotically **equal to** $g(n)$

48

Example Uses of the Relatives of Big-Oh



■ $7n^3 + 3n^2$ is $\Omega(n^3)$

$f(n)$ is $\Omega(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \geq c \cdot g(n)$ for $n \geq n_0$

let $c = 7$ and $n_0 = 1$

■ $5n^2$ is $\Omega(n)$

$f(n)$ is $\Omega(g(n))$ if there is a constant $c > 0$ and an integer constant $n_0 \geq 1$ such that $f(n) \geq c \cdot g(n)$ for $n \geq n_0$

let $c = 1$ and $n_0 = 1$

■ $5n^2 + 10n$ is $\Theta(n^2)$

$f(n)$ is $\Theta(g(n))$ if, there are constants $c_1, c_2 > 0$, and there is an integer constant $n_0 > 0$ such that $c_1 \cdot g(n) \leq f(n) \leq c_2 \cdot g(n)$ for all $n \geq n_0$

Let $c_1=4, c_2=6$, then $4 \cdot n^2 \leq 5n^2 + 10n \leq 6 \cdot n^2$ for all $n \geq 6$

49

Big-Oh and Growth Rate


- ◆ The big-Oh notation gives an upper bound on the growth rate of a function
- ◆ The statement " $f(n)$ is $O(g(n))$ " means that the growth rate of $f(n)$ is no more than the growth rate of $g(n)$
- ◆ We can use the big-Oh notation to rank functions according to their growth rate

	$f(n)$ is $O(g(n))$	$f(n)$ is $\Omega(g(n))$
$g(n)$ grows more	Yes	No
$f(n)$ grows more	No	Yes
Same growth (Θ)	Yes	Yes

Introduction and Overview

50

Relationships Between the Complexity Classes



- If $f(n)$ is in both $O(g(n))$ and $\Omega(g(n))$, it is in $\Theta(g(n))$.

Analysis of Algorithms

51

Asymptotic Notation in Practice

- ◆ The fastest algorithm in practice or for practical size input data sets is not always revealed!!!
- ◆ Because
 - Constants are dropped
 - Low-order terms are dropped
 - Algorithm efficiencies on small input sizes are not considered
- ◆ However, asymptotic notation is very effective
 - for comparing the scalability of different algorithms as input sizes become large

Stacks, Queues, Vectors, & Lists

52

Amortization (§1.5)

Analysis of growable array-based stacks and queues

Amortized Analysis & Trees

53

Amortization (§1.5)

- ◆ Comes from the field of accounting
 - Provides a monetary metaphor for algorithm analysis
- ◆ Useful for understanding the running time of algorithms that have steps with widely varying performance
 - i.e., each step performs a widely varying amount of work
 - Rather than focusing on individual operations, we study the interactions of a series of operations

Amortized Analysis & Trees

54

Aggregate Amortized Analysis

- ◆ The average time required to perform an operation within a sequence of operations
 - The worst-case total running time of a series of operations divided by the number of operations
- ◆ Guarantees the average performance of each operation in the worst case

Amortized Analysis & Trees

55

55

Aggregate Analysis

- ◆ Determine an upper bound, $T(n)$,
 - the total cost of a sequence of n operations
- ◆ The average cost per operation is then $T(n)/n$
- ◆ The average cost becomes the amortized cost of each operation
- ◆ Thus all operations have the same amortized cost
 - Even though the cost of each individual operation varies widely

Amortized Analysis & Trees

56

56

Growable Array-based Stack

- ◆ In a push operation, when the array is full, instead of throwing an exception, we can replace the array with a larger one
- ◆ How large should the new array be?
 - incremental strategy: increase the size by a constant c
 - doubling strategy: double the size

```

Algorithm push(o)
if  $t = S.length - 1$  then
     $A \leftarrow$  new array of size ...
    for  $i \leftarrow 0$  to  $t$  do
         $A[i] \leftarrow S[i]$ 
     $S \leftarrow A$ 
     $t \leftarrow t + 1$ 
     $S[t] \leftarrow o$ 
    
```

Amortized Analysis & Trees

57

57

Comparison of the Strategies

- ◆ We compare the incremental strategy and the doubling strategy by analyzing the total time $T(n)$ needed to perform a series of n push operations
- ◆ We start with an empty stack represented by an array of size 1
- ◆ We call amortized time of a push operation the average time taken by a push over the series of operations, i.e., $T(n)/n$

```

Algorithm push(o)
if  $t = S.length - 1$  then
     $A \leftarrow$  new array of size ...
    for  $i \leftarrow 0$  to  $t$  do
         $A[i] \leftarrow S[i]$ 
     $S \leftarrow A$ 
     $t \leftarrow t + 1$ 
     $S[t] \leftarrow o$ 
    
```

Amortized Analysis & Trees

58

58

Incremental Strategy Analysis

- ◆ We replace the array $k = n/c$ times
 - since $n = kc$ in worst case (i.e., we increase array on n th push operation)
- ◆ The total time $T(n)$ of a series of n push operations is proportional to

$$n + c + 2c + 3c + 4c + \dots + kc =$$

$$n + c(1 + 2 + 3 + \dots + k) =$$

$$n + ck(k+1)/2$$
- ◆ Since c is a constant, $T(n)$ is $O(n + k^2)$, i.e., $O(n^2)$
- ◆ Thus the amortized time of a push operation is $O(n) \quad O(n/2c)$ because $k=n/c$

Amortized Analysis & Trees

59

59


Doubling Strategy Analysis

- ◆ We replace the array $k = \log_2 n$ times
 - since $n = 2^k$ in worst case
- ◆ The total time $T(n)$ of a series of n push operations is proportional to

$$n + 1 + 2 + 4 + 8 + \dots + 2^k =$$

$$n + 2^{k+1} - 1 =$$

$$n + 2 * 2^k - 1 = 3n - 1$$
- ◆ $T(n)$ is $O(n)$
- ◆ The amortized time of a push operation is $O(1)$
- ◆ Because $n = 2^k \Rightarrow k = \log n$



Amortized Analysis & Trees

60

60

Array Based Stack

◆ Advantage

- Avoids the usual cost of copying array elements because there is no inserting or deleting of elements in the middle of the array

◆ Disadvantage

- If many more pushes than pops, the array has to be resized often, which is costly

Amortized Analysis & Trees

61

61

Quiz: Growable Array-based Queue

- ◆ In an enqueue operation, when the array is full, instead of throwing an exception, we can replace the array with a larger one
- ◆ What is the amortized running time of the enqueue operation for incremental and doubling strategies?
 - Hint: Similar to what we did for a growable array-based stack

Amortized Analysis & Trees

62

62

Growable Array-based Queue

◆ The enqueue operation has amortized running time

- $O(n)$ with the incremental strategy
- $O(1)$ with the doubling strategy

Amortized Analysis & Trees

63

63

Other Amortization Techniques

Amortized Analysis & Trees

64

64

The Accounting Method

- ◆ Uses a scheme of debits and credits to keep track of the running time of a series of operations
- ◆ Some operations are overcharged, others are undercharged
- ◆ The amount charged is called its *amortized cost*
- ◆ When amortized cost exceeds actual cost, the difference is assigned to specific objects within the data structure as credit
- ◆ Credits are used to pay for other operations that are charged less than they actually cost
- ◆ Amortized costs must be chosen carefully
- ◆ The total amortized cost of a sequence of operations must be an upper bound on the actual cost

Amortized Analysis & Trees

65

65

Accounting Method Example:

push(o) – actual cost 1
pop() – actual cost 1
mutilpop(k) – actual cost $\min(k, n)$

Accounting method:

push(o) – amortized cost 2
pop() – amortized cost 0
mutilpop(k) – amortized cost 0

When we do a push, we charge the actual cost (1 unit) and associate a credit of 1 unit with each element on the stack
When we do a pop or mutilpop, we charge 0 but use the credit associated with each element popped to pay for the operation

Amortized Analysis & Trees

66

66

The Potential Method

- ◆ Determine the amortized cost of each operation
- ◆ Overcharge operations early to compensate for undercharges later
- ◆ Maintains the credit as the “potential energy” of the data structure as a whole instead of associating the credit with individual objects within the data structure

Amortized Analysis & Trees

67

67

Main Point

3. The idea of “borrowing” and later “repaying” a data structure or program can be useful for determining the average case time complexity of algorithms that have operations with widely varying running times. The basic idea of amortized analysis is that, even though a few operations are very costly, they do not occur often enough to dominate the entire algorithm; that is, the number of less costly operations far outnumber the costly ones over a large number of executions. Science of Consciousness: Natural law (physics) says that for every action there is an equal and opposite reaction. To avoid mistakes, it is important to perform action from the silent, orderly level of our own consciousness.

Amortized Analysis & Trees

68

68

Connecting the Parts of Knowledge with the Wholeness of Knowledge

1. The tree ADT is a generalization of the linked-list in which each tree node can have any number of children instead of just one. A proper binary tree is a special case of the generic tree ADT in which each node has either 0 or 2 children (a left and right child).
2. Any ADT will have a variety of implementations of its operations with varying efficiencies, e.g., the binary tree can be implemented as either a set of recursively defined nodes or as an array of elements.

Amortized Analysis & Trees

69

69

3. **Transcendental Consciousness** is pure intelligence, the abstract substance out of which the universe is made.
4. **Impulses within Transcendental Consciousness:** Within this field, the laws of nature continuously organize and govern all activities and processes in creation.
5. **Wholeness moving within itself : In Unity** Consciousness, awareness is awake to its own value, the full value of the intelligence of nature. One's consciousness supports the knowledge that outer is the expression of inner, creation is the play and display of the Self.

Amortized Analysis & Trees

70

70