

ComPDF Conversion SDK for Java 4.1.0

Upgrade Warnings

This document contains a list of considerations that developers should be aware of when upgrading from previous versions to ComPDF Conversion SDK for Java 4.1.0. Changes in the code may be necessary to ensure compatibility with the new version for your project to compile properly.

Upgrading from version 4.0.0 to version 4.1.0

If you are upgrading from version 4.0.0 to version 4.1.0, please note the following additions. None of them break source compatibility — existing 4.0.0 code keeps compiling and behaves the same, because every new option keeps the previous behaviour as its default and every new callback hook on `ConvertCallback` defaults to unset, which makes the SDK fall back to the built-in DocumentAI path.

New conversion option: AI Table Recognition

The option classes used by formats that support Table Recognition, such as `wordOptions`, `ExcelOptions`, `PptOptions`, `HtmlOptions`, `RtfOptions`, `CsvOptions`, `JsonOptions`, and `MarkdownOptions`, now expose a new property:

```
wordOptions opt = new wordOptions();
opt.setEnableAiTableRecognition(true); // enabled by default in 4.1
```

This controls whether the AI Table Recognition stage runs on table regions detected by layout analysis. Set it to `false` to skip the table model entirely and rely on geometric reconstruction from the underlying page objects. The option only takes effect when layout analysis is active, i.e. `enableAiLayout = true`, or implicitly when `enableocr = true`. See the developer guide chapter *Table Recognition* for details.

New AI customization callbacks on `ConvertCallback`

`ConvertCallback` gained six callback hooks that let you plug in your own AI engine for OCR, Layout Analysis, and Table Recognition. All six default to unset, in which case the SDK uses the built-in DocumentAI model loaded via `LibraryManager.setDocumentAIModel`.

Capability	Trigger method	Result getter method
OCR	<code>onOcr</code>	<code>getOcrResult</code>
Layout Analysis	<code>onLayout</code>	<code>getLayoutResult</code>
Table Recognition	<code>onTable</code>	<code>getTableResult</code>

Each capability uses a trigger / getter pair: the trigger receives the path of a page image saved as PNG and runs your inference; the getter returns a `String` containing the JSON result. Both callbacks for a capability must be set together to take effect. See the developer guide chapter *Use Custom AI Models via Callbacks* for the JSON schemas and a complete example.

Extended scope of the `fontName` option

In 4.0.0, `fontName` was honored for PDF to Word, PDF to Excel, and PDF to PowerPoint. In 4.1.0 it additionally applies to:

- PDF to Searchable PDF
- PDF to OFD

For Searchable PDF and OFD, `fontName` controls the font used for the text layer overlaid on the page background.