

ComPDF Conversion SDK for Windows 4.1.0 Upgrade Warnings

This document contains a list of considerations that developers should be aware of when upgrading from previous versions to ComPDF Conversion SDK for Windows 4.1.0. Changes in the code may be necessary to ensure compatibility with the new version for your project to compile properly.

Upgrading from version 4.0 to version 4.1

If you are upgrading from version 4.0 to version 4.1, please note the following additions. None of them break source compatibility — existing 4.0 code keeps compiling and behaves the same, because every new option keeps the previous behaviour as its default and every new callback field defaults to `IntPtr.Zero` (which makes the SDK fall back to the built-in path).

New conversion option: AI Table Recognition

All option classes (`WordOptions`, `ExcelOptions`, `PptOptions`, `HtmlOptions`, `RtfOptions`, `CsvOptions`, `JsonOptions`, `MarkdownOptions`, `TxtOptions`) now expose a new property:

```
public bool EnableAiTableRecognition = true; // default: true
```

This controls whether the AI Table Recognition stage runs on table regions detected by layout analysis. Set it to `false` to skip the table model entirely and rely on geometric reconstruction from the underlying page objects. The option only takes effect when layout analysis is active (i.e. `EnableAiLayout = true`, or implicitly when `EnableOCR = true`). See the developer guide chapter *Table Recognition* for details.

New AI customization callbacks

The `ConvertCallback` struct (declared in `LibraryManager.cs`) gained six new function-pointer fields that let you plug in your own AI engine for OCR, Layout Analysis, and Table Recognition. All six default to `IntPtr.Zero`, in which case the SDK uses the built-in DocumentAI model loaded via `LibraryManager.SetDocumentAIModel`.

Capability	Trigger field	Result getter field	Trigger delegate	Result getter delegate
OCR	<code>ocr</code>	<code>get_ocr_result</code>	<code>OnOCR</code>	<code>OnGetOCRResult</code>
Layout Analysis	<code>layout</code>	<code>get_layout_result</code>	<code>OnLayout</code>	<code>OnGetLayoutResult</code>
Table Recognition	<code>table</code>	<code>get_table_result</code>	<code>OnTable</code>	<code>OnGetTableResult</code>

Each capability uses a trigger / getter pair: the trigger receives the path of a page image (PNG) and runs your inference; the getter returns an `IntPtr` to a UTF-8 JSON C-string with the recognition result. Both must be set together to take effect. See the developer guide chapter *Use Custom AI Models via Callbacks* for the JSON schemas and a complete example.