

closed

Demo ticket

Session
ID: demoPCSAZK-8CN
Time limit: 120 min.

Status: closed
Started on: 2014-01-05 05:44 UTC

Score:

100

of 100



☆☆ 1. MaxCounters

score: 100 of 100



Calculate the values of counters after applying all alternating operations: increase counter by 1; set value of all counters to current maximum.

Task description

You are given N counters, initially set to 0, and you have two possible operations on them:

- *increase(X)* – counter X is increased by 1,
- *max_counter* – all counters are set to the maximum value of any counter.

A non-empty zero-indexed array A of M integers is given. This array represents consecutive operations:

- if $A[K] = X$, such that $1 \leq X \leq N$, then operation K is *increase(X)*,
- if $A[K] = N + 1$ then operation K is *max_counter*.

For example, given integer $N = 5$ and array A such that:

```
A[0] = 3
A[1] = 4
A[2] = 4
A[3] = 6
A[4] = 1
A[5] = 4
A[6] = 4
```

the values of the counters after each consecutive operation will be:

```
(0, 0, 1, 0, 0)
(0, 0, 1, 1, 0)
(0, 0, 1, 2, 0)
(2, 2, 2, 2, 2)
(3, 2, 2, 2, 2)
(3, 2, 2, 3, 2)
(3, 2, 2, 4, 2)
```

The goal is to calculate the value of every counter after all operations.

Write a function:

```
class Solution { public int[] solution(int N,
int[] A); }
```

that, given an integer N and a non-empty zero-indexed array A consisting of M integers, returns a sequence of integers representing the values of the counters.
The sequence should be returned as:

- a structure `Results` (in C), or
- a vector of integers (in C++), or
- a record `Results` (in Pascal), or
- an array of integers (in any other programming language).

For example, given:

```
A[0] = 3
A[1] = 4
A[2] = 4
A[3] = 6
A[4] = 1
A[5] = 4
A[6] = 4
```

Solution

Programming language used: C#

Total time used: 57 minutes

(?)

Effective time used: 1 minutes

(?)

Notes: correct functionality and scalability

Task timeline

What is it? ?



05:44:51

06:41:28

Code: 06:41:27 UTC, cs, final, score: 100.00

```
01. using System;
02. // you can also use other imports, for
   // example:
03. // using System.Collections.Generic;
04. class Solution {
05.     public int[] solution(int N, int[]
       A)
06.     {
07.         var length = A.Length;
08.         if (N < 1 || length < 1 || N >
           100000 || length > 100000)
           throw new
           ArgumentOutOfRangeException();
09.         // write your code in C# with
           .NET 2.0
10.         var result = new int[N];
11.         var maxValue = 0;
12.         var resetValue = 0;
13.         var hasReset = false;
14.         for (var count = 0; count <
           length; count++)
15.         {
16.             if (A[count] <= N)
17.             {
18.                 // Set to maximum value
                   if a reset has been
                   encountered
19.                 if (hasReset &&
                   (resetValue >
                   result[A[count] -
                   1]))
                   result[A[count] - 1]
                   = resetValue;
20.
21.                 result[A[count] - 1] +=
22.                 1;
```

the function should return [3, 2, 2, 4, 2], as explained above.
Assume that:

- N and M are integers within the range [1..100,000];
- each element of array A is an integer within the range [1..N + 1].

Complexity:

- expected worst-case time complexity is O(N+M);
- expected worst-case space complexity is O(N), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2013 by Codility Limited. All Rights Reserved.
Unauthorized copying, publication or disclosure prohibited.

```
23.
24.
25.
26.
27.
28.
29.
30.
31.
32.
33.
34.
35.
36.
37.
38.
39.
40.
41.
42.
43. }
```

```
// Get new maximum value
if (result[A[count] - 1]
    > maxValue)
    maxValue =
        result[A[count] -
            1];
}
else
{
    resetValue = maxValue;
    hasReset = true;
}
}

for (var count = 0; count < N;
    count++)
{
    if (hasReset && resetValue
        > result[count])
        result[count] =
            resetValue;
}

return result;
}
```

Analysis



Detected time complexity:
O(N + M)

test	time	result
example example test	0.080 s.	OK
extreme_small all max_counter operations	0.070 s.	OK
single only one counter	0.080 s.	OK
small_random1 small random test, 6 max_counter operations	0.080 s.	OK
small_random2 small random test, 10 max_counter operations	0.080 s.	OK
medium_random1 medium random test, 50 max_counter operations	0.080 s.	OK
medium_random2 medium random test, 500 max_counter operations	0.080 s.	OK
large_random1 large random test, 2120 max_counter operations	0.090 s.	OK
large_random2 large random test, 10000 max_counter operations	0.110 s.	OK
extreme_large all max_counter operations	0.110 s.	OK

Get account