
Kotlin ∇

A shape-safe DSL for differentiable programming

Breandan Considine
McGill University

Michalis Famelis
Université de Montréal

Liam Paull
Université de Montréal

Abstract

Kotlin is a statically-typed programming language with support for embedded domain-specific languages, asynchronous programming, and multi-platform compilation. In this work, we present an algebraically-based implementation of automatic differentiation (AD) with shape-safe tensor operations, written in pure Kotlin. Our approach differs from existing AD frameworks in that Kotlin ∇ is the first shape-safe AD library fully compatible with the Java type system, requiring no metaprogramming, reflection or compiler intervention to use. A working prototype is available: <https://github.com/breandan/kotlingrad>.

1 Introduction

Many existing AD frameworks are implemented in dynamically-typed languages, like Python. Some frameworks are written in statically-typed languages, but only consider primitive data types, and do not attempt to verify the shape of multidimensional arrays. Those which do, either use dynamic type checking or relatively esoteric languages like Haskell (Piñeyro et al., 2019). In our work, we demonstrate a shape-safe AD framework which supports static type checking and inference on array programs in a widely-used programming language called Kotlin.

Differentiable programming has a rich history among dynamic languages like Python, Lua and JavaScript, with early implementations including projects like Theano (Bergstra et al., 2010), Torch (Collobert et al., 2002), and TensorFlow (Abadi et al., 2016). Similar ideas have arisen in statically-typed, functional languages, such as Haskell’s Stalin ∇ (Pearlmutter & Siskind, 2008b), DiffSharp in F# (Baydin et al., 2015) and recently Swift (Lattner & Wei, 2018). However, the majority of existing AD libraries have a loosely- or dynamically- typed DSL, and few support shape-safe array programming in a widely-adopted programming language. To our knowledge, Kotlin has no prior AD implementation. However, the language has several useful features for implementing a native AD framework. Kotlin ∇ primarily relies on the following language features:

- **Operator overloading and infix functions** allow a concise notation for defining arithmetic operations on algebraic structures, i.e. groups, rings and fields. (Niculescu, 2011)
- **λ -functions** support functional programming, following Pearlmutter & Siskind (2008a,b); Siskind & Pearlmutter (2008); Elliott (2009, 2018), et al.
- **Extension functions** support extending classes with new fields and methods which can be exposed to external callers without requiring sub-classing or inheritance.

Kotlin ∇ is an embedded domain-specific language (eDSL). Embedded programs may appear structurally and behave semantically unlike native code, but are syntactically valid by definition. eDSLs are often used to implement declarative languages, such as SQL/LINQ (Meijer et al., 2006), OptiML (Sujeeth et al., 2011) and other fluent interfaces (Fowler, 2005). With a sufficiently expressive host language, one can implement any other language as a library, without needing to write a lexer, parser, compiler or interpreter. With proper type constraints, users will receive code completion and static analysis from their favorite development tools, with no further effort required.




Figure 1: Adapted from van Merriënboer et al. (2018). Kotlin ∇ models are data structures, constructed by an eDSL. These are compiled into dataflow graphs at runtime, which are eagerly optimized and lazily evaluated.

2 Usage

Kotlin ∇ allows users to implement differentiable programs by composing simple functions to form more complex ones. Operations on functions with an incompatible output shape will fail to compile. Valid expressions are lazily evaluated inside a type-safe numerical context at runtime.

```

with(DoublePrecision) {
    val x = variable("x")
    val y = variable("y")
    val z = sin(10 * (x * x + pow(y, 2))) / 10
    val dz_dx = d(z) / d(x)
    val d2z_dx dy = d(dz_dx) / d(y)
    val d3z_d2xdy = grad(d2z_dx dy)[x]
    plot3D(d3z_d2xdy, -1.0, 1.0)
}
// Use double-precision numerics
// Declare immutable input variables
// (these are just symbolic placeholders)
// Lazy expression
// Leibniz derivative notation
// Mixing higher-order partials
// Gradient indexing operator
// Plot in -1 < x,y,z < 1

```

Figure 2: Above, we define a function with two variables and take a series of partial derivatives with respect to each variable. The function is evaluated on the interval $(-1, 1)$ in each dimension and rendered in 3-space.

$$z = \sin(10(x \times x + y^2))/10, \text{ plot3D}\left(\frac{\partial^3 z}{\partial x^2 \partial y}\right)$$




Figure 3: Output generated by the program shown in Figure 2.

In Kotlin ∇ , all expressions are composed of function(s) in the host language which define a dataflow graph (DFG), and are themselves functions defined by the same DFG. An expression is only evaluated when invoked with numerical values. As shown in Figure 1, Kotlin ∇ straddles the boundary between define-and-run and define-by-run. As an eDSL, it shares properties of both code and data.

3 Type System

Early work in type-safe dimension analysis can be found in Kennedy (1994, 1996) which uses types to encode dimensionality and prevent common bugs related to dimension mismatch from arising, which was later realized in the F# language (Kennedy, 2010). Jay & Sekanina (1997), Rittri (1995), and Zenger (1997) explore the application of dimension types for linear algebra. More recently, Kiselyov (2005); Kiselyov et al. (2009) and Griffioen (2015), show how to manipulate arrays in more complex ways. With the resurgence of interest in tensor algebra and array programming, Chen (2017) and Rink (2018) explore how to encode shape-safety in various type systems.

The problem we attempt to solve can be summarized as follows. Given two values \bar{x} and \bar{y} , and operator $\$$, how do we determine whether the expression $z = \bar{x} \$ \bar{y}$ is valid, and if so, what is the result type of z ? For matrix multiplication, when $\bar{x} \in \mathbb{R}^{m \times n}$ and $\bar{y} \in \mathbb{R}^{n \times p}$, the expression is well-typed and we can infer $\bar{z} \in \mathbb{R}^{m \times p}$. More generally, we would like to infer the type of \bar{z} for some operator $@ : (\mathbb{R}^a, \mathbb{R}^b) \rightarrow \mathbb{R}^c$ where $a \in \mathbb{N}^q, b \in \mathbb{N}^r, c \in \mathbb{N}^s$ and $q, r, s \in \mathbb{N}$. For many linear algebra operations such as matrix multiplication, $\mathcal{T}(\bar{a}, \bar{b}) \stackrel{?}{=} \bar{c}$ is computable in $\mathcal{O}(1)$ – we can simply check the inner dimensions for equivalence ($a_1 \stackrel{?}{=} b_0$).

```
val vecA = Vec(1.0, 2.0)           // Inferred type: Vec<Int, '2'>
val vecB = Vec(1.0, 2.0, 3.0)      // Inferred type: Vec<Int, '3'>
val vecC = vecB + vecB
val vecD = vecA + vecB // Compile error: Expected Vec<2>, found Vec<3>
```

Figure 4: Attempting to sum two vectors whose shapes do not match will fail to compile.

```
val matA = Mat('1', '4', 1.0, 2.0, 3.0, 4.0) // Inferred type: Mat<Double, '1', '4'>
val matB = Mat('4', '1', 1.0, 2.0, 3.0, 4.0) // Inferred type: Mat<Double, '4', '1'>
val matC = matA * matB
val matD = matA * matC // Compile error: Expected Mat<4, *>, found Mat<1, 1>
```

Figure 5: Similarly, multiplying two matrices whose inner dimensions do not match will not compile.

Shape checking operations on multidimensional arrays is not always decidable. For arbitrary type functions $\mathcal{T}(\bar{a}, \bar{b})$, checking $\mathcal{T}(\bar{a}, \bar{b}) \stackrel{?}{=} \bar{c}$ requires a Turing machine. If \mathcal{T} is allowed to use the multiplication operator, as in the case of convolutional arithmetic (Dumoulin & Visin, 2016), shape inference becomes equivalent to Peano arithmetic, which is undecidable (Gödel, 1931). Addition, subtraction, indexing and comparison of integers are all decidable operations (Charlier et al., 2011). Equality checking is trivially decidable, and can be implemented in most static type systems.

Evaluating an arbitrary \mathcal{T} which uses multiplication or division (e.g. convolutional arithmetic) requires a dependently typed language (Xi & Pfenning, 1998; Piñeyro et al., 2019), but checking shape equality (e.g. ordinary arithmetic) is feasible in Java and its cousins.¹ Furthermore, we believe that shape checking ordinary matrix arithmetic is decidable in any type system loosely based on System $F_{<}$ (Cardelli et al., 1994). We propose a type system for enforcing shape-safety which can be implemented in any language with subtyping and generics, such as Java (Naftalin & Wadler, 2007), Kotlin (Tate, 2013), TypeScript (Bierman et al., 2014) or Rust (Crozet et al., 2019).

4 Evaluation

Kotlin ∇ claims to eliminate certain runtime errors, but how do we know the implementation is not incorrect? One method for checking is called property-based testing (PBT) (Fink & Bishop, 1997). PBT uses algebraic properties to verify the result of an operation by constructing semantically

¹Java’s type system is known to be Turing Complete (Grigore, 2017). Thus, emulation of dependent types in Java is theoretically possible, but likely intractable due to the practical limitations noted by Grigore.

Log errors between AD, SD and FD on $f(x) = \frac{\sin(\sin(\sin(x)))}{x} + x \sin(x) + \cos(x) + x$




Figure 6: We compare numerical drift between three types of computational differentiation: (1) finite precision automatic differentiation (AD), (2) finite precision symbolic differentiation (SD) and (3) finite precision finite differences (FD) against infinite precision (IP). AD and SD both exhibit relative errors (i.e. with respect to each other) several orders of magnitude below their absolute errors (i.e. with respect to IP), which roughly agree to within numerical precision. FD exhibits significantly higher drift than AD and SD.

equivalent but syntactically distinct expressions, which should produce the same answer. Kotlin ∇ uses two such equivalences to validate its own AD implementation:

- **Analytical differentiation:** manually differentiate selected functions and compare the numerical result of evaluating random chosen inputs from their domain with the numerical result obtained by evaluating AD on the same inputs.
- **Finite difference approximation:** sample the space of symbolic differentiable functions, comparing the numerical results suggested by the finite difference method and the equivalent AD result, up to a fixed-precision approximation.

We also compare the precision of symbolic differentiation, automatic differentiation and numerical differentiation, as shown in Figure 6. Our results are consistent with the findings of Laue (2019).

5 Conclusion

Unlike most existing AD implementations, Kotlin ∇ does not require any template metaprogramming, compiler augmentation or runtime reflection to ensure type safety. Its implementation leverages several features in the Kotlin language including operator overloading, infix functions and extension functions. It also incorporates various functional programming concepts, like higher order functions, partial application and currying. The practical advantage of this approach is that it can be implemented as a simple library or embedded domain-specific language (eDSL), reusing the host language’s type system to receive code completion and type checking for free. In future work, we hope to extend Kotlin ∇ by compiling to a common intermediate representation (e.g. LLVM IR), and explore the meaning of differentiation in other calculi (cf. Considine (2019), Section 3.20).

References

- Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., Devin, M., Ghemawat, S., Irving, G., Isard, M., Kudlur, M., Levenberg, J., Monga, R., Moore, S., Murray, D. G., Steiner, B., Tucker, P., Vasudevan, V., Warden, P., Wicke, M., Yu, Y., and Zheng, X. TensorFlow: A system for large-scale machine learning. In Proceedings of the 12th USENIX Conference on Operating Systems Design and Implementation, OSDI'16, pp. 265–283, Berkeley, CA, USA, 2016. USENIX Association. ISBN 978-1-931971-33-1. URL <http://dl.acm.org/citation.cfm?id=3026877.3026899>.
- Baydin, A. G., Pearlmutter, B. A., and Siskind, J. M. DiffSharp: Automatic differentiation library. CoRR, abs/1511.07727, 2015. URL <http://arxiv.org/abs/1511.07727>.
- Bergstra, J., Breuleux, O., Bastien, F., Lamblin, P., et al. Theano: a CPU and GPU math expression compiler. In Proceedings of the Python for scientific computing conference (SciPy), volume 4. Austin, TX, 2010. URL <http://deeplearning.net/software/theano/>.
- Bierman, G., Abadi, M., and Torgersen, M. Understanding TypeScript. In European Conference on Object-Oriented Programming, pp. 257–281. Springer, 2014.
- Cardelli, L., Martini, S., Mitchell, J. C., and Scedrov, A. An extension of System F with subtyping. volume 109, pp. 4–56, Duluth, MN, USA, February 1994. Academic Press, Inc. doi: 10.1006/inco.1994.1013. URL <http://dx.doi.org/10.1006/inco.1994.1013>.
- Charlier, É., Rampersad, N., and Shallit, J. Enumeration and decidable properties of automatic sequences. Lecture Notes in Computer Science, pp. 165–179, 2011. ISSN 1611-3349. doi: 10.1007/978-3-642-22321-1_15. URL http://dx.doi.org/10.1007/978-3-642-22321-1_15.
- Chen, T. Typesafe abstractions for tensor operations (short paper). pp. 45–50, 2017. doi: 10.1145/3136000.3136001. URL <http://doi.acm.org/10.1145/3136000.3136001>.
- Collobert, R., Bengio, S., and Mariéthoz, J. Torch: a modular machine learning software library. Idiap-RR Idiap-RR-46-2002, IDIAP, 2002.
- Considine, B. Programming tools for intelligent systems. Master’s thesis, Université de Montréal, 2019. URL <https://github.com/breandan/kotlingrad/blob/master/latex/thesis/thesis.pdf>.
- Crozet, S. et al. nalgebra: a linear algebra library for Rust, 2019. URL <https://nalgebra.org>.
- Dumoulin, V. and Visin, F. A guide to convolution arithmetic for deep learning. arXiv preprint arXiv:1603.07285, 2016.
- Elliott, C. The simple essence of automatic differentiation. Proc. ACM Program. Lang., 2(ICFP): 70:1–70:29, July 2018. ISSN 2475-1421. doi: 10.1145/3236765. URL <http://doi.acm.org/10.1145/3236765>.
- Elliott, C. M. Beautiful differentiation. In Proceedings of the 14th ACM SIGPLAN International Conference on Functional Programming, ICFP '09, pp. 191–202, New York, NY, USA, 2009. ACM. ISBN 978-1-60558-332-7. doi: 10.1145/1596550.1596579. URL <http://doi.acm.org/10.1145/1596550.1596579>.
- Fink, G. and Bishop, M. Property-based testing: A new approach to testing for assurance. SIGSOFT Softw. Eng. Notes, 22(4):74–80, July 1997. ISSN 0163-5948. doi: 10.1145/263244.263267. URL <http://doi.acm.org/10.1145/263244.263267>.
- Fowler, M. Fluent interface, 2005. URL <http://martinfowler.com/bliki/FluentInterface.html>.
- Gödel, K. Über formal unentscheidbare sätze der principia mathematica und verwandter systeme i. Monatshefte für mathematik und physik, 38(1):173–198, 1931.

- Griffioen, P. R. Type inference for array programming with dimensioned vector spaces. In Proceedings of the 27th Symposium on the Implementation and Application of Functional Programming Languages, IFL '15, pp. 4:1–4:12, New York, NY, USA, 2015. ACM. ISBN 978-1-4503-4273-5. doi: 10.1145/2897336.2897341. URL <http://doi.acm.org/10.1145/2897336.2897341>.
- Grigore, R. Java generics are Turing Complete. pp. 73–85, 2017. doi: 10.1145/3009837.3009871. URL <http://doi.acm.org/10.1145/3009837.3009871>.
- Jay, C. B. and Sekanina, M. Shape checking of array programs. Technical report, In Computing: the Australasian Theory Seminar, Proceedings, 1997.
- Kennedy, A. Dimension types. In European Symposium on Programming, pp. 348–362. Springer, 1994.
- Kennedy, A. Types for Units-of-Measure: Theory and Practice, pp. 268–305. Springer Berlin Heidelberg, Berlin, Heidelberg, 2010. ISBN 978-3-642-17685-2. doi: 10.1007/978-3-642-17685-2_8. URL https://doi.org/10.1007/978-3-642-17685-2_8.
- Kennedy, A. J. Programming languages and dimensions. Technical report, University of Cambridge, Computer Laboratory, 1996. URL <https://www.cl.cam.ac.uk/techreports/UCAM-CL-TR-391.pdf>.
- Kiselyov, O. Number-parameterized types. The Monad Reader, 5:73–118, 2005.
- Kiselyov, O., Peyton Jones, S., and Shan, C.-c. Fun with type functions. April 2009. URL <https://www.microsoft.com/en-us/research/publication/fun-type-functions/>.
- Lattner, C. and Wei, R. Swift for TensorFlow. 2018. URL <https://github.com/tensorflow/swift>.
- Laue, S. On the equivalence of forward mode automatic differentiation and symbolic differentiation. CoRR, abs/1904.02990, 2019. URL <http://arxiv.org/abs/1904.02990>.
- Meijer, E., Beckman, B., and Bierman, G. LINQ: reconciling object, relations and XML in the .NET framework. In Proceedings of the 2006 ACM SIGMOD International Conference on Management of Data, SIGMOD '06, pp. 706–706, New York, NY, USA, 2006. ACM. ISBN 1-59593-434-0. doi: 10.1145/1142473.1142552. URL <http://doi.acm.org/10.1145/1142473.1142552>.
- Naftalin, M. and Wadler, P. Java generics and collections. O'Reilly Media, 2007.
- Niculescu, V. On using generics for implementing algebraic structures. Studia Universitatis Babes-Bolyai, Informatica, 56(4), 2011.
- Pearlmutter, B. A. and Siskind, J. M. Reverse-mode AD in a functional framework: Lambda the ultimate backpropagator. ACM Transactions on Programming Languages and Systems (TOPLAS), 30(2):7, 2008a.
- Pearlmutter, B. A. and Siskind, J. M. Using programming language theory to make automatic differentiation sound and efficient. pp. 79–90, 2008b. ISSN 1439-7358. doi: 10.1007/978-3-540-68942-3_8. URL <http://www.bcl.hamilton.ie/~barak/papers/sound-efficient-ad2008.pdf>.
- Piñeyro, L., Pardo, A., and Viera, M. Structure verification of deep neural networks at compilation time using dependent types. In Proceedings of the XXIII Brazilian Symposium on Programming Languages, SBPL 2019, pp. 46–53, New York, NY, USA, 2019. ACM. ISBN 978-1-4503-7638-9. doi: 10.1145/3355378.3355379. URL <http://doi.acm.org/10.1145/3355378.3355379>.
- Rink, N. A. Modeling of languages for tensor manipulation. CoRR, abs/1801.08771, 2018. URL <http://arxiv.org/abs/1801.08771>.

- Rittri, M. Dimension inference under polymorphic recursion. In Proceedings of the Seventh International Conference on Functional Programming Languages and Computer Architecture, FPCA '95, pp. 147–159, New York, NY, USA, 1995. ACM. ISBN 0-89791-719-7. doi: 10.1145/224164.224197. URL <http://doi.acm.org/10.1145/224164.224197>.
- Siskind, J. M. and Pearlmutter, B. A. Nesting forward-mode AD in a functional framework. Higher-Order and Symbolic Computation, 21(4):361–376, Dec 2008. ISSN 1573-0557. doi: 10.1007/s10990-008-9037-1. URL <https://doi.org/10.1007/s10990-008-9037-1>.
- Sujeeth, A., Lee, H., Brown, K., Rompf, T., Chafi, H., Wu, M., Atreya, A., Odersky, M., and Olukotun, K. OptiML: an implicitly parallel domain-specific language for machine learning. In Proceedings of the 28th International Conference on Machine Learning (ICML-11), pp. 609–616, 2011.
- Tate, R. Mixed-site variance. In FOOL '13: Informal Proceedings of the 20th International Workshop on Foundations of Object-Oriented Languages, 2013. URL <http://www.cs.cornell.edu/~ross/publications/mixedsite/>.
- van Merriënboer, B., Moldovan, D., and Wiltchko, A. Tangent: Automatic differentiation using source-code transformation for dynamically typed array programming. In Advances in Neural Information Processing Systems 31, pp. 6256–6265, 2018. URL <https://arxiv.org/abs/1711.02712>.
- Xi, H. and Pfenning, F. Eliminating array bound checking through dependent types. In Proceedings of the ACM SIGPLAN 1998 Conference on Programming Language Design and Implementation, PLDI '98, pp. 249–257, New York, NY, USA, 1998. ACM. ISBN 0-89791-987-4. doi: 10.1145/277650.277732. URL <http://doi.acm.org/10.1145/277650.277732>.
- Zenger, C. Indexed types. Theoretical Computer Science, 187(1-2):147–165, November 1997. ISSN 0304-3975. doi: 10.1016/S0304-3975(97)00062-5. URL [http://dx.doi.org/10.1016/S0304-3975\(97\)00062-5](http://dx.doi.org/10.1016/S0304-3975(97)00062-5).