

# Untitled: A DirectX Game

Sam Drysdale

May 16, 2023

## Contents

<b>1</b>	<b>Summary</b>	<b>1</b>
<b>2</b>	<b>User Controls</b>	<b>1</b>
<b>3</b>	<b>Features</b>	<b>1</b>
3.1	Noise . . . . .	2
3.2	Procedural Terrain . . . . .	2
3.2.1	Case Study: Hexes . . . . .	2
3.2.2	Case Study: Landmarks . . . . .	2
3.3	Procedural Screen Textures . . . . .	2
3.3.1	Case Study: Runes . . . . .	3
3.3.2	Case Study: Blood Vessels . . . . .	3
3.4	Procedural Narrative . . . . .	4
3.4.1	Grammars . . . . .	4
3.4.2	Content Selection Architectures . . . . .	5
<b>4</b>	<b>Code Organisation</b>	<b>5</b>
4.1	Post-Processing . . . . .	5
4.2	GUI . . . . .	5
<b>5</b>	<b>Evaluation</b>	<b>5</b>
5.1	Features . . . . .	5
5.2	Code Organisation . . . . .	5
<b>6</b>	<b>Conclusions</b>	<b>5</b>
	<b>References</b>	<b>6</b>

## 1 Summary

## 2 User Controls

## 3 Features

The following is a technical discussion of the key features of *Untitled*, with a focus on advanced procedural generation. Mathematical models and code snippets are kept to a minimum, edited for clarity rather than accuracy to the original application.

### 3.1 Noise

### 3.2 Procedural Terrain

Given its grounding in nuclear semiotics, this game's terrain is of course intended to evoke a sense of "shunned land" (Trauth et al. 1993). In generating the jutting thorns and blocks so essential to the post-nuclear setting, though, there comes a problem - concavity. Height maps are perfectly adequate for creating rolling hills and valleys, but the fact that each  $(x, z)$ -coordinate can correspond to only one  $y$ -value prevents any features that ominously overhang *Untitled*'s barren earth (see Figure [reference]).

[Hand-drawn figure, demonstrating the shortcomings of thorns].

*Marching cubes* are therefore central to this modelling process. The concept here is best introduced in two dimensions.

In much the same way, [3D generalisation].

[These are just the broad strokes; nuance to, say, weighing vertex normals correctly]. Definitive... Paul Bourke's *Polygonising a Scalar Field* (1994)... [mention marching tetrahedra? While X, marching cubes have been perfectly adequate for the purposes set out below...].

#### 3.2.1 Case Study: Hexes

#### 3.2.2 Case Study: Landmarks

### 3.3 Procedural Screen Textures

The post-processing in *Untitled* is, in one sense, rather simple. The 'stress vignette,' for instance, calls only two renders-to-texture on every frame: the board itself, and an alpha map of blood vessels that sprout from the edges of the screen. As striking as the final effect is, *vignette.ps.hlsl* is surprisingly straightforward in blending the textures into a final, pulsing eye strain overlay; far more deserving of further discussion is how the blood vessels themselves are generated.

In formal languages, a grammar is a tuple  $G = (N, \Sigma, P, \omega_0)$ . This contains two disjoint sets of symbols: nonterminals  $A, B, \dots \in N$ , and terminals  $a, b, \dots \in \Sigma$ . The production rules in  $P$  map nonterminals to strings  $\alpha, \beta, \dots \in (N \cup \Sigma)^*$ ; applied recursively to the axiom  $\omega_0 \in (N \cup \Sigma)^*$ , these rules can produce increasingly complex *sentences* of terminals and/or nonterminals.<sup>1</sup>

The Chomsky hierarchy (Chomsky 1956) classifies grammars by their production rules:

*Type-3. Regular grammars* map  $A \mapsto a$  or  $A \mapsto aB$ .

*Type-2. Context-free grammars* map  $A \mapsto \alpha$ .

*Type-1. Context-sensitive grammars*  $\alpha A \beta \mapsto \alpha \gamma \beta$ .

*Type-0. Unrestricted grammars* map  $\alpha \mapsto \beta$ , where  $\alpha$  is non-empty.

Note that all Type-3 grammars are also Type-2, all Type-2 grammars also Type-1, and so on.

Suppose, for example, that  $N = \{F, G\}$ ,  $\Sigma = \{+, -\}$ ,  $P = \{F \mapsto F + G, G \mapsto F - G\}$ ,  $\omega_0 = F$ .

Letting  $\omega_n$  denote the sentences generated by applying the production rules  $n$  times, it follows that

$$\begin{aligned}\omega_1 &= F + G, \\ \omega_2 &= F + G + F - G, \\ \omega_3 &= F + G + F - G + F + G - F - G, \\ \omega_4 &= F + G + F - G + F + G - F - G + F + G + F - G - F + G - F - G, \dots\end{aligned}$$

---

<sup>1</sup>In mathematical literature,  $\omega_0 \in N$  (Hopcroft, Motwani & Ullman 2000), but *Untitled* takes an informal approach.

While these definitions are rather abstract, Lindenmayer (1968) provides a remarkable application. Treating each symbol as an instruction like ‘go forward’ or ‘turn right’, *L-systems* visualise sentences via ‘turtle graphics’; when those sentences have been generated recursively by a grammar, the line drawings inherit that same self-similar structure. In the above example, interpreting non-terminals  $F$ ,  $G$  as ‘draw a line while moving one unit forwards,’ and terminals  $\pm$  as ‘turn  $\pm \pi/2$  on the spot,’ produces the fractal dragon curves in Figure 1.




Figure 1: Dragon curves, generated by strings  $\omega_2, \omega_4, \dots, \omega_{12}$ .

While *Untitled* only needs them to generate 2D alpha maps, note that L-systems are most common in the modelling of 3D plants and other branching structures (Prusinkiewicz & Lindenmayer 1996). Furthermore, this report will restrict its attention to L-systems paired with context-free grammars.

### 3.3.1 Case Study: Runes

Parametric L-systems (Hanan 1992) exist as a generalisation of the above. [theory].

The modules in *Untitled*, then, track three . More than anything, this offers a certain clarity of code - at least from a

[Example: various geometric runes!].

### 3.3.2 Case Study: Blood Vessels

Zamir (2001), meanwhile, uses parametric L-systems to visualise the bifurcation of blood vessels. Suppose a branch with length  $l$ , width  $w$  bifurcates into two branches  $M$  and  $m$ , such that  $l_M \geq l_m$ . Defining the *asymmetry ratio*  $\alpha = l_m/l_M$ , it follows that

$$l_M = \frac{l}{(1 + \alpha^3)^{1/3}}, \quad l_m = \frac{\alpha \cdot l}{(1 + \alpha^3)^{1/3}}, \quad w_M = \frac{w}{(1 + \alpha^3)^{1/3}}, \quad w_m = \frac{\alpha \cdot w}{(1 + \alpha^3)^{1/3}}.$$

Furthermore, the branches diverge from their parent at angles

$$\theta_M = \arccos \left( \frac{(1 + \alpha^3)^{4/3} + 1 - \alpha^4}{2(1 + \alpha^3)^{2/3}} \right), \quad \theta_m = \arccos \left( \frac{(1 + \alpha^3)^{4/3} + \alpha^4 - 1}{2\alpha^2(1 + \alpha^3)^{2/3}} \right).$$

Figure 2: Zamir’s model of arterial branching, with asymmetry ratios  $\alpha = 1.0, 0.8, \dots, 0.2$ .

*Untitled*’s framework is therefore capable of reproducing Zamir’s results (see Figure 2), using an L-system with the single production rule:

$$\mathbf{C}(l, w, \theta) \mapsto \mathbf{X}(l, w, \theta)[\mathbf{C}(l_M, w_M, \theta + \theta_M)]\mathbf{C}(l_m, w_m, \theta - \theta_m).$$

Liu et al. (2010) expand on this by introducing a stochastic component - that is to say, they allow [a more random structure]. *Untitled* incorporates such randomness into its own rules for blood vessels:

$$\begin{aligned} \mathbf{C}(l, w, \theta) &\xrightarrow{0.4} \mathbf{X}(l, w, \theta)[\mathbf{L}(l_M, w_M, \theta + \theta_M)]\mathbf{R}(l_m, w_m, \theta - \theta_m) \\ \mathbf{C}(l, w, \theta) &\xrightarrow{0.4} \mathbf{X}(l, w, \theta)[\mathbf{L}(l_m, w_m, \theta + \theta_m)]\mathbf{R}(l_M, w_M, \theta - \theta_M) \\ \mathbf{C}(l, w, \theta) &\xrightarrow{0.2} \mathbf{X}(l, w, \theta)\mathbf{C}(l, w, \theta) \\ \mathbf{L}(l, w, \theta) &\xrightarrow{1.0} \mathbf{X}(l, w, \theta)\mathbf{C}(l_M, w_M, \theta - \theta_M) \\ \mathbf{R}(l, w, \theta) &\xrightarrow{1.0} \mathbf{X}(l, w, \theta)\mathbf{C}(l_M, w_M, \theta + \theta_M) \end{aligned}$$

These describe a capillary with a 40% chance of bifurcating with branch  $M$  tacking clockwise, a 40% chance of bifurcating with  $M$  tacking anticlockwise, and a 20% chance of extending forwards without any branching. The deterministic production rules on  $\mathbf{L}$ ,  $\mathbf{R}$  provide course correction, guaranteeing the [...]; further informal tweaks can be found in the `LBloodVessel` class, all intended to get the final look of the L-systems ‘right’ (see Figure [reference]).

[Figure of blood vessels in isolation]

[Discussion of animation (and the shortcomings thereof)...]

[Figure of final render]

### 3.4 Procedural Narrative

*Untitled* was originally conceived as a showcase of procedural text generation, an application of [authored X] towards interactive fiction.

#### 3.4.1 Grammars

Given their origin in linguistics, it is perhaps unsurprising that grammars (see Section 3.3) are of use in the field of procedural narrative - *Tracery* (Compton et al. 2015) being the prime example. From a mathematical perspective, this is a stochastic, context-free grammar, with uniformly-distributed production rules for each non-terminal; it iterates a given axiom until all non-terminals (demarcated by `#HASHTAG#` delimiters) have been replaced. To bemoan the generator as better suited to Twitter bots than immersive storytelling is to misunderstand its design. Compton et al. present a lightweight tool that is left *deliberately* narrow, intended for ease-of-use amongst even the most fledgling authors.

More substantial works, then, adapt *Tracery*’s grammar-based approach to their own specifications. In *The Annals of the Parrigues*, Short sets out the need for a consistent generator, one that “defines any facts about the world that aren’t already defined at the moment of generation” (2015, p. 83).

*Voyageur* (Dias 2018) integrates several weightings into distribution of production rules (Dias 2019). While [this project], this project wears its influences on its sleeve - *Untitled* uses an implementation of *Tracery* with a couple of custom modifications...

**Recency** [Or ‘dryness’].

$p^{n/(N-1)}$ , such that (all other weightings being equal), the most recently used rule (with  $n = N - 1$ ) will be  $p$  times as likely as the least recent ( $n = 0$ ).

Note that [joint recency!].

### 3.4.2 Content Selection Architectures

*Storylets* (Kreminski & Wardrip-Fruin 2018) are [definition].

[Though conceptually no different, ... , our ‘narrative stack’...]

## 4 Code Organisation

### 4.1 Post-Processing

### 4.2 GUI

[Include HDRR/bloom here...]

## 5 Evaluation

### 5.1 Features

### 5.2 Code Organisation

## 6 Conclusions

[Coheres in a way that my CMP502 project absolutely didn’t...]

Of course, there is a distinction to be drawn between *Untitled*’s functionality as an interactive experience and as a game. [Perils of interactive narrative].

[What/how would I go about cannibalising this? Screen shader first/hexes... narrative much more an early experiment in structuring content selection architectures/context-sensitive grammars...]

## References

- Bourke, P. (1994), ‘Polygonising a Scalar Field’, Available at:  
<http://paulbourke.net/geometry/polygonise/>. (Accessed: 9 February 2023).
- Chomsky, N. (1956), ‘Three Models for the Description of Language’, *IRE Transactions on Information Theory* **2**(3), 113–124.
- Compton, K., Kybartas, B. & Mateas, M. (2015), Tracery: An Author-Focused Generative Text Tool, in ‘*8th International Conference on Interactive Digital Storytelling*’, Copenhagen, Denmark: 30 November-4 December, pp. 154–161.
- Dias, B. (2018), *Voyageur*, self-published.
- Dias, B. (2019), ‘Procedural Descriptions in *Voyageur*’, in T. Short & T. Adams, eds, ‘*Procedural Storytelling in Game Design*’, 2<sup>nd</sup> edn, Boca Raton, FL, USA: Taylor & Francis, pp. 193–207.
- Hanan, J. S. (1992), Parametric L-systems and Their Application to the Modelling and Visualization of Plants, PhD thesis, University of Regina, Regina.

- Hopcroft, J., Motwani, R. & Ullman, J. D. (2000), *Introduction to Automata Theory, Languages, and Computation*, 2<sup>nd</sup> edn, Boston, MA, USA: Addison-Wesley.
- Kreminski, M. & Wardrip-Fruin, N. (2018), Sketching a Map of the Storylets Design Space, in ‘*11th International Conference on Interactive Digital Storytelling*’, Dublin, Ireland: 5-8 December, pp. 160–164.
- Lindenmayer, A. (1968), ‘Mathematical Models for Cellular Interactions in Development II. Simple and Branching Filaments With Two-Sided Inputs’, *Journal of Theoretical Biology* **18**(3), 300–315.
- Liu, X., Liu, H., Hao, A. & Zhao, Q. (2010), Simulation of Blood Vessels for Surgery Simulators, in ‘*2010 International Conference on Machine Vision and Human-machine Interface*’, pp. 377–380.
- Prusinkiewicz, P. & Lindenmayer, A. (1996), *The Algorithmic Beauty of Plants*, 2<sup>nd</sup> edn, Berlin, Germany: Springer-Verlag.
- Short, E. (2015), *The Annals of the Parrigues*, self-published.
- Trauth, K., Hora, S. & Guzowski, R. (1993), Expert Judgment on Markers to Deter Inadvertent Human Intrusion Into the Waste Isolation Pilot Plant, Technical report, SANDIA National Laboratories, Albuquerque.
- Zamir, M. (2001), ‘Arterial Branching Within the Confines of Fractal L-System Formalism’, *The Journal of General Physiology* **118**, 267–276.