

Test9

Pierre Ekelmans

General Introduction

This test is designed to achieve contrast invariant response in spatially structured networks with synaptic plasticity.

This is based on the results shown in the Bernaez-Timon et al., manuscript (in preparation)

The features tested are : Distance Connectivity, SpatialGaussianStimulus, PowerLawSynapse and Heatmap recording.

**Warning:** The simulations can take hours to run.

This Live Script runs with Matlab

Figures

```
%% Import Data
base_path = 'C:/Users/ekelmansp/Documents';
project_name1 = 'Test9A';%For the simulation at high input level. project_name is an identifier of the folder(s) containing the simulation data. The date suffix does not need to be included
project_name2 = 'Test9B';%For the simulation at low input level. Idem

%% Import data Simulation1
folderlist=dir([base_path filesep project_name1 '_20*']);
folder_name=folderlist(end).name;
cd([base_path filesep folder_name])
filename = [project_name1 '_HeatmapRate_Pop0.dat'];

delimiter = '\t';
startRow = 14;
formatEl='%f';
formatSpec=formatEl;%the first column is time;
for i=1:51
formatSpec=[formatSpec formatEl;%Each of the 500 recoreded neurons has 3 sources of inputs: recurrent E and I and feedforward
end
formatSpec=[formatSpec '%[\n\r]'];


fileID = fopen(filename,'r');
dataArray = textscan(fileID, formatSpec, 'Delimiter', delimiter, 'EmptyValue' ,NaN,'HeaderLines' ,startRow-1, 'ReturnOnError', false, 'EndOfLine', '\r\n');
fclose(fileID);
Test9A = [dataArray{1:end-1}];

%% Import data Simulation2

folderlist=dir([base_path filesep project_name2 '_20*']);
folder_name=folderlist(end).name;
cd([base_path filesep folder_name])
filename = [project_name2 '_HeatmapRate_Pop0.dat'];

fileID = fopen(filename,'r');
dataArray = textscan(fileID, formatSpec, 'Delimiter', delimiter, 'EmptyValue' ,NaN,'HeaderLines' ,startRow-1, 'ReturnOnError', false, 'EndOfLine', '\r\n');
fclose(fileID);
Test9B = [dataArray{1:end-1}];
clearvars filename delimiter startRow formatSpec fileID dataArray ans folder_name formatEl i;
```


```
%% Analysis
figure
plot(linspace(-0.5,0.5,51),Test9A(end,2:end)./max(Test9A(end,2:end)),'LineWidth',2.5)
hold on
plot(linspace(-0.5,0.5,51),Test9B(end,2:end)./max(Test9B(end,2:end)),'--','LineWidth',2.5)
title('Check Contrast Invariance')
legend('Simulation1','Simulation2')
xlabel('Position')
ylabel('Normalized Firing rate')
set(gca,'FontSize',16)
```



```
figure
plot([0 0.5 1],[0 max(Test9B(end,2:end)) max(Test9A(end,2:end))],'o','LineWidth',2.5)

hold on
I=linspace(0,1,20);
nu_BS=zeros(size(I));
for i=1:length(I)
nu_BS(i)=max(SpaceBalanced([2 -10 5 -12],0.16,0.1,0.05,0.8,I(i),-0.5));
end
plot(I,nu_BS,'k','LineWidth',2.5)

title('Check nonlinearity')
xlabel('Input strength')
ylabel('Peak firing rate')
legend('Simulation','Balanced State Theory')
axis tight
set(gca,'FontSize',16)
```



```
function [nu,X,nu_I]=SpaceBalanced(J,Sstim,SconE,pexE,fracE,mu,k)
Xlim=4*sqrt(Sstim^2-SconE^2);
X=[-1:0.02:1]*Xlim;
X=linspace(-Xlim,Xlim,1e4+1);
J=abs(J);
b=(J(2)-J(4))/(J(1)*J(4)-J(2)*J(3));
c=(J(1)-J(3))/(J(1)*J(4)-J(2)*J(3));

nu=mu*b*Sstim/(pexE*fracE*sqrt(Sstim^2-SconE^2)).*exp(-X.^2/(2*Sstim^2-2*SconE^2));
nu=nu.^(inv(1+k));

SconI=SconE;
pexI=pexE;
nu_I=mu*c*Sstim/(pexI*(1-fracE)*sqrt(Sstim^2-SconI^2)).*exp(-X.^2/(2*Sstim^2-2*SconI^2));

end
```

The first figure illustrates contrast invariance: the firing rate profiles have different amplitudes depending on the input srtngh, but the normalized profiles are identical.

The second figure shows how the peak firing rate (at x=0) changes as a function of the input strength. Due to the power law synaptic plasticity rule, the network response is nonlinear as a function of the input strength. As a comparison, the theoretical solution from the balanced state theory follows the same trend.