

Advanced Topics in Quantum Boltzmann Machines

Quantum Computing Lecture Series

March 28, 2025

Contents

1 Introduction to Quantum Boltzmann Machines (QBMs)

Quantum Boltzmann Machines (QBM) are a quantum generalization of classical Boltzmann machines. They leverage quantum effects such as superposition and entanglement to model complex probability distributions. QBM are well-suited for quantum machine learning tasks, particularly for generative modeling.

1.1 Motivation

Classical Boltzmann Machines suffer from high-dimensional sampling complexity. Quantum mechanics offers exponential state space and quantum tunneling effects that can alleviate these issues.

1.2 Key Concepts

- Quantum States as Probability Distributions
- Quantum Tunneling for Escaping Local Minima
- Exponential State Space in Quantum Systems

2 Mathematical Framework

2.1 Hamiltonian of a Quantum Boltzmann Machine

The quantum analog of the classical energy-based model is expressed by the Hamiltonian H :

$$H = H_Z + H_X, \tag{1}$$

where:

$$H_Z = - \sum_i b_i Z_i - \sum_{i < j} w_{ij} Z_i Z_j, \tag{2}$$

$$H_X = - \sum_i \Gamma_i X_i. \tag{3}$$

- Z_i and X_i are Pauli operators acting on the i -th qubit.
- b_i represents the bias terms.
- w_{ij} represents the interaction between qubits.
- Γ_i is the transverse field strength.

2.2 Density Matrix and Boltzmann Distribution

The quantum Boltzmann distribution is defined by the density matrix:

$$\rho = \frac{e^{-\beta H}}{Z}, \tag{4}$$

where:

- $\beta = 1/k_B T$ is the inverse temperature.

- $Z = \text{Tr}(e^{-\beta H})$ is the partition function.

In the classical case, this reduces to a Gibbs distribution.

3 Training Quantum Boltzmann Machines

3.1 Objective Function

The goal of training a QBM is to minimize the Kullback–Leibler (KL) divergence between the data distribution p_{data} and the model distribution p_{θ} :

$$\mathcal{L}(\theta) = \text{KL}(p_{\text{data}}||p_{\theta}) = \sum_x p_{\text{data}}(x) \log \frac{p_{\text{data}}(x)}{p_{\theta}(x)}. \quad (5)$$

3.2 Gradient-Based Optimization

The gradient of the loss function is computed using:

$$\nabla_{\theta} \mathcal{L}(\theta) = \mathbb{E}_{p_{\text{data}}}[\nabla_{\theta} E(x)] - \mathbb{E}_{p_{\theta}}[\nabla_{\theta} E(x)], \quad (6)$$

where $E(x)$ is the energy function derived from the Hamiltonian.

4 Quantum Sampling Techniques

4.1 Quantum Monte Carlo Methods

Quantum Monte Carlo (QMC) simulates quantum systems by sampling from the quantum density matrix using classical resources. However, it faces limitations due to the ****sign problem****.

4.2 Quantum Annealing

Quantum annealers leverage adiabatic evolution to reach low-energy states efficiently:

$$H(t) = (1 - t/T)H_B + (t/T)H_P, \quad (7)$$

where:

- H_B is the mixing Hamiltonian.
- H_P is the problem Hamiltonian.

5 Advantages and Challenges

5.1 Advantages

- Quantum Parallelism
- Efficient Sampling in Complex Systems
- Potential for Exponential Speedups

5.2 Challenges

- Noisy Quantum Hardware
- High Cost of Quantum Simulation
- Quantum Decoherence

6 Applications

6.1 Generative Modeling

Quantum Boltzmann Machines can generate complex probability distributions with applications in:

- Image and Text Generation
- Quantum Chemistry
- Financial Modeling

6.2 Optimization Problems

QBM's are suitable for solving optimization problems where classical approaches suffer from local minima.

7 Conclusion

Quantum Boltzmann Machines offer a promising path for leveraging quantum resources in machine learning. While hardware limitations currently restrict scalability, ongoing research in quantum algorithms and quantum hardware is likely to overcome these obstacles.

8 References

References

- [1] M. Amin et al., "Quantum Boltzmann Machines", *Physical Review X*, 2018.
- [2] G. Hinton, "Boltzmann Machines: Constraints and Learning", *Cognitive Science*, 1985.
- [3] M. Nielsen and I. Chuang, "Quantum Computation and Quantum Information", Cambridge University Press, 2000.