Supplemental Material for "Resolution refinement followed by the rodeo algorithm: a gate-level benchmark of eigenstate-preparation routes on the pairing Hamiltonian"

Scott Bogner,[1] Cecilie Glittum,[2] Heiko Hergert,[1] Morten Hjorth-Jensen,[2,*] Gunnar Lange,[2] Ryan LaRose,[3] Dean Lee,[1] Francesco Pietro Massel,[4,2] and Jean Paul Sadia[5,6]

[1] *Facility for Rare Isotope Beams and Department of Physics and Astronomy, Michigan State University, East Lansing, MI 48824, USA*
[2] *Department of Physics, University of Oslo, N-0316 Oslo, Norway*
[3] *Department of Computational Mathematics, Science and Engineering and Facility for Rare Isotope Beams, Michigan State University, East Lansing, MI 48824, USA*
[4] *Department of Science and Industry Systems, University of South-Eastern Norway, N-3616 Kongsberg, Norway*
[5] *Department of Computational Mathematics, Science, and Engineering, Michigan State University, East Lansing, MI 48823, USA*
[6] *Center for Quantum Computing, Science, and Engineering, Michigan State University, East Lansing, MI 48823, USA*

(Dated: October 20, 2026)

This Supplemental Material collects the verification material behind the main text: the comparison of coarse solvers at larger basis size (Sec. S1), the refinement energies and the $k = 3 \to 4$ chain (Sec. S2), the shift-scan fits and the response norm along the path (Sec. S3), the evaluation of the sufficient adiabatic-time and Trotter-step conditions (Sec. S4), the rodeo energy scan and its statistics (Sec. S5), the operating points behind the fidelities quoted in the main text (Sec. S6), the other model-space sizes, particle numbers and observables (Sec. S7), and the validation of the pair-basis implementation with the ingredients of the sixteen-qubit study (Sec. S8). Equation, section, figure and table numbers without the prefix S refer to the main text. All numbers are produced by the notebook of the code repository.

S1. COARSE SOLVERS AT LARGER BASIS SIZE

Figure S1 compares all coarse solvers of Sec. IV A of the main text — exact diagonalization, coupled-cluster doubles, statevector and gate-level UCCSD, and a hardware-efficient ansatz — as a function of the number of levels k at $N = 4$, $g = 1$, and Fig. S2 follows the gate-level UCCSD solver to $k = 8$ (sixteen qubits). The hardware-efficient ansatz is exact at $k = 2$, reaches FCI at $k = 3$ only after a multi-start optimization with a particle-number penalty, and fails at $k = 4$; the UCCSD solver stays variational and tight throughout, at a CNOT count that grows steeply (1 312 at $k = 4$).

a. Hardware-efficient ansatz. The HEA [49] used for contrast consists of L layers of R_y rotations on all $2k$ qubits interleaved with a CNOT entangler (nearest-neighbor pairs plus a wrap-around bond), i.e. $2k(L{+}1)$ variational angles and only $O(2kL)$ CNOTs: 12 angles at $k = 2$ ($L = 2$) and 30 at $k = 3$ ($L = 4$). Its depth is far smaller than UCCSD, but the circuit carries no particle-number or seniority structure; a number-penalty term and multi-start optimization are needed at $k = 3$, and at $k = 4$ the optimizer fails to reach the ground state (Fig. S1). Depth is not the only currency: trainability of the symmetry-blind landscape becomes the bottleneck first.

S2. REFINEMENT ENERGIES AND THE $k = 3 \to 4$ CHAIN

Figure S3 shows the overlap and the physical energy $\langle\Phi(T)|H_{\rm high}|\Phi(T)\rangle$ of the refined state versus the adiabatic time T for the $k = 2 \to 3$ and $2 \to 4$ chains at $N = 4$, $g = 1$ (Sec. IV B of the main text), and Fig. S4 compares the $2 \to 4$ chain with the $3 \to 4$ chain that starts from the gate-level UCCSD state at $k = 3$ (Sec. IV C).

S3. SHIFT SCAN: FITS AND RESPONSE NORM

Figure S5 shows the two affine fits to the four shift-scan points of Fig. 4 of the main text, in $1/\Delta E_{\rm min}$ and in $1/\Delta E^2_{\rm min}$, with their sums of squared residuals (28 and 0.2), and the first-order response norm $\chi_u(s)$ along the $k = 2 \to 4$ path for the four shifts; at $s = 0$ it equals g^2/b^2 with $b = \mu - E_{\rm low}$, the $k = 4$, $N = 4$ case of the identity $\chi_u(0) = \|QH_{\rm high}P\psi_{\rm low}\|^2/b^2$, Eq. (13) of the main text, which gives $P(k-P)g^2/(4b^2)$ for the filled pairing seed.

S4. SUFFICIENT CONDITIONS VERSUS PRACTICE

The conditions quoted in Sec. III C of the main text can be evaluated exactly for the path of Eq. (3). Writing $A = P(H_{\rm low} - \mu)P^\dagger$ and $B = H_{\rm high} - \mu$, the schedule

* mhjensen@uio.no




FIG. S1. Ground-state energy at $N = 4$, $g = 1$ obtained with all solvers (left) and their deviation from FCI (right), versus the number of levels k. The structured UCCSD circuits track FCI from above; CCD over-binds; the hardware-efficient ansatz matches FCI for $k \leq 3$ but loses accuracy at $k = 4$.




FIG. S2. Scalability of the Trotterized UCCSD–VQE: ground-state energy (left) and deviation from FCI (right) from $k = 2$ to $k = 8$ ($N = 4$, $g = 1$). The same solver remains variational and tight as the basis — and hence the qubit count — grows.

gives $\dot{H} = \frac{\pi}{2}\sin(\pi s)\,(B-A)$ and $\ddot{H} = \frac{\pi^2}{2}\cos(\pi s)\,(B-A)$, so the integrand of Eq. (6) is fixed by the single number $\|B - A\|$ and by the instantaneous gap $\Delta(s)$, both taken in the $N = 4$ sector in which the evolution takes place. Figure S6 shows the two along the $k = 2 \to 4$ path: the gap rises from the shift-controlled 0.600 at $s = 0$ to the physical gap of H_{high} at $s = 1$, and the integrand peaks near $s \simeq 0.25$, where $\sin(\pi s)$ is already sizable while the gap is still close to its minimum; the term $7\left\|\dot{H}\right\|^2/\Delta^3$ supplies 94% of the integral. Table S1 collects the numbers. Here $\|B - A\| = 7.62$ and $\int_0^1 [\cdots]\, ds = 511$, so Eq. (6) demands $T \geq 5.1 \times 10^3$ for an infidelity of 10^{-2} (and 1.6×10^4 for 10^{-3}), whereas the computed overlap reaches 0.99 at $T^* = 16$: the sufficient condition overshoots the practical time by a factor 3×10^2. The step-count condition is looser still. With $\Lambda_1 = \max_s \left\|\dot{H}\right\| = 12.0$ and, for the term partition of the gate compilation of Sec. V B of the main text (the conditioned coarse term, the diagonal term and the six pair-hopping terms), $\Lambda_2 = \max_s \sum_{i<j} \|[H_i(s), H_j(s)]\| = 13.0$, the first-order bound at $\eta = \sqrt{\epsilon}/2$ requires 3.4×10^4 steps along the $T^* = 16$ path — and 3.4×10^9 along the path of length T_{b} — while 160 first-order or 40 second-order steps already reproduce the exact-slice overlap at T^* to within the adiabatic error of the path itself. The two step counts answer different questions and the ratio between them must be read with that in mind: the bound certifies an operator-norm error of the digitized unitary, whereas re-




FIG. S3. Four-particle refinement up to $k = 4$: overlap (left) and physical energy $\langle\Phi(T)|H_{\rm high}|\Phi(T)\rangle$ (right) versus T for $k_{\rm high} = 3, 4$. The energy approaches the FCI value (dotted) from above while the overlap approaches unity (the time scale is empirical; the scan of Sec. IV D of the main text identifies no exponent).




FIG. S4. Refinement chains to $k = 4$ at $N = 4$, $g = 1$, starting from the gate-free $k = 2$ determinant (circles) and from the 272-CNOT gate-level UCCSD state at $k = 3$ (squares). Left: overlap with the exact ground state versus adiabatic time T; right: the same on a logarithmic scale. The $3 \to 4$ chain starts at overlap 0.964 (versus 0.868) and reaches 0.99 in half the adiabatic time ($T^* = 8$ on a finer grid than the one shown).

producing one scalar overlap does not certify that the two output vectors, let alone the two unitaries, are close.

These ratios — 3×10^2 for the time and 2×10^2 for the step count — are the fermionic counterpart of what Ref. [2] reports for nucleation of a twelve-site Ising chain (6×10^1 and 10^7, respectively), and they carry the same message: the conditions certify convergence but do not predict cost. Part of the reason is visible in the integrand. The bound pays for the full operator norm $\|B - A\| = 7.62$ — the same value in the full $N = 4$ sector and in the six-dimensional seniority-zero block that the dynamics actually explores, so it is not an artifact of inaccessible sectors — and for the global gap, whereas the adiabatic error is governed by the individual matrix elements of dH/ds between the tracked state and the states it couples to, relative to their individual gaps. Those elements are small but not zero for the highest accessible states: at $s = 0.25$ the derivative couplings from the ground state to the five seniority-zero excited states are 0.60, 0.37, 0.00, 0.11 and 0.08. A global norm therefore overestimates the cost by ignoring the state-specific structure of the couplings; the magnitude of the overshoot alone does not single out one cause, nor does it verify the inverse-gap mechanism of Ref. [1].




FIG. S5. Left: the four shift-scan points of Fig. 4 with the two affine fits, in $1/\Delta E_{\min}$ (dashed) and in $1/\Delta E^2_{\min}$ (solid), and their sums of squared residuals. Right: the first-order response norm $\chi_u(s) = \sum_{n>0} |\langle n|\partial_u H|0\rangle|^2/(E_n - E_0)^2$ of the $k = 2 \to 4$ path, $u = \sin^2(\pi s/2)$, for the four shifts; at $s = 0$ it equals g^2/b^2 with $b = \mu - E_{\text{low}}$ and it is largest there, so the quantity that the inverse-gap argument assumes bounded changes by a factor 25 across the scan (χ_u is the response along the affine path of Ref. [1]; the response to the scheduled parameter, $\chi_s = [\frac{\pi}{2}\sin \pi s]^2 \chi_u$, vanishes at both ends and its maximum varies by a factor 3.4).




FIG. S6. The ingredients of the adiabatic-time bound, Eq. (6), along the $k = 2 \to 4$ refinement path at $N = 4$, $g = 1$, $\mu = E_{\text{low}} + 0.6$. Left: instantaneous gap $\Delta(s)$ in the $N = 4$ sector, from the shift-controlled 0.600 at $s = 0$ (dotted line) to the physical gap 1.823 of H_{high} at $s = 1$. Right: the integrand $\left\|\ddot{H}\right\|/\Delta^2 + 7\left\|\dot{H}\right\|^2/\Delta^3$ (logarithmic scale), which peaks near $s \simeq 0.25$ and integrates to $I = 511$ (Table S1).

S5. THE RODEO ENERGY SCAN

Figure S7 shows the energy scans of Sec. IV E of the main text ($M = 4$ cycles, 12 time sets per energy). The coarse scan ($\sigma = 2$, 60 energies on $[-0.5, 4]$) resolves the ground-state peak from the excited band; the fine scan ($\sigma = 8$, 161 energies with spacing 0.0075 on a window of width 1.2 centered on the highest point of the coarse scan, $E = 0.644$, i.e. chosen without knowledge of E_0) locates the peak at $E = 0.6362$ against the exact $E_0 = 0.635548$ by three-point parabolic interpolation at the grid maximum. On a device every acceptance is a shot estimate: adding binomial noise for 10^3 and 10^4 shots per energy and locating the peak by a quadratic fit through the points above 80% of the maximum gives 0.637 ± 0.001 and 0.6373 ± 0.0004, so with this scan the systematic error of the peak estimator ($\sim 2 \times 10^{-3}$, from the non-parabolic shape of the peak over the fitted window) exceeds the shot noise, and the agreement to 10^{-3} is a property of the scan design rather than a demonstrated

TABLE S1. Sufficient conditions of Ref. [2] evaluated for the $k = 2 \to 4$ refinement path ($N = 4$, $g = 1$, $\mu = E_{\rm low} + 0.6$; spectral norms in the $N = 4$ sector) against the empirical cost. $\Delta_{\rm min}$: minimum instantaneous gap; I: the integral in Eq. (6); $T_{\rm b}$: the time bound for infidelity $\epsilon = 10^{-2}$, $T_{\rm b} = I/\sqrt{\epsilon}$; T^*: time for overlap 0.99 (grid of Fig. 4); $\Lambda_1 = \max_s \left\|\dot{H}\right\|$ and $\Lambda_2 = \max_s \sum_{i<j} \|[H_i, H_j]\|$ over the Trotter groups of the gate compilation; $n_{\rm b}(T^*)$: first-order Trotter steps required by the bound along the T^* path at $\eta = \sqrt{\epsilon}/2$; n_1, n_2: first- and second-order steps (from the sequence $5, 10, 20, \ldots$) that reproduce the exact-slice overlap at T^* to within the adiabatic error $1 - p(T^*)$ of the path.

$\Delta_{\rm min}$	$\|B - A\|$	I	$T_{\rm b}$	T^*	$T_{\rm b}/T^*$	Λ_1	Λ_2	$n_{\rm b}(T^*)$	n_1	n_2
0.600	7.62	511	5.1×10^3	16	3.2×10^2	12.0	13.0	3.4×10^4	160	40

four-decimal precision. Starting from the refined state, essentially all spectral weight sits in the single ground-state peak; starting from the prolonged determinant, the small residual weight on excited states is visible as secondary structure above the 2^{-M} background. The fine scan alone evaluates 161 energies with 12 time sets each, about 2×10^3 four-cycle runs, each repeated over enough shots to estimate an acceptance probability.

S6. OPERATING POINTS

Table S2 records the operating points behind the different fidelities quoted in the main text, which belong to different stages of idealization: the ideal filter of Sec. IV E and the digital pipeline of Secs. V B–V C differ in refinement time, slice treatment, filter width and evolution, and the residual errors of the former are not achieved by the counted circuits of the latter.

S7. OTHER MODEL-SPACE SIZES, PARTICLE NUMBERS, AND OBSERVABLES

To see whether the ranking of Table II of the main text is an accident of the smallest nontrivial case, Table S3 repeats the comparison, with exact-slice refinement and exact controlled evolution ($\sigma = 3$, 40 time sets), for $N = 4$ and $N = 6$ particles on $k = 4$ and $k = 6$ levels (eight and twelve qubits), always starting from the filled determinant of the smallest coarse space ($k_{\rm low} = N/2$). The pattern is the same throughout: the prolonged overlap falls to 0.78–0.80 at $k = 6$, refinement for $T = 30$ restores it to 0.997–0.999, and the UCCSD input, whose infidelity grows from 1.8×10^{-4} to 1.0×10^{-3} over the table, still enters the filter with a higher overlap than the refined state and leaves it with a lower infidelity at every cycle number. (At $N = 6$, $k = 4$ the ansatz is exact: three pairs on four levels are the particle–hole conjugate of one pair, for which UCCSD is complete.) The price of the UCCSD input is its circuit — 6 976 CNOTs and 92 parameters at $k = 6$, $N = 4$; 9 024 CNOTs and 117 parameters at $k = 6$, $N = 6$ — and the training of those parameters, which the refinement avoids at the cost of $2n_s(N^{\rm step}_{\rm CNOT} + N^A_{\rm CNOT})$ CNOTs with $N^{\rm step}_{\rm CNOT} = 732$ at $k = 6$. This is a controlled small-system demonstration, not a scaling study; a regime in which refinement wins over the single-layer variational input requires a space for which that input is poor, and Sec. V E of the main text shows that four pairs on eight levels is already such a space (the adaptively grown ansatz remains far cheaper there).

a. Observables. A state-preparation method for nuclear structure is judged by the observables of the state it delivers, not only by its overlap. Table S4 lists the level occupation numbers $n_p = \sum_\sigma \langle n_{p\sigma} \rangle$ and the correlation energy $E - E_{\rm ref}$ of the states of Table II of the main text at $k = 4$, $N = 4$, $g = 1$ (for the filtered states, the acceptance-weighted average over the 40 time sets). The exact ground state depletes the two occupied levels by 0.07 and 0.20 particles. The UCCSD state reproduces the occupations to 3×10^{-3} and the correlation energy to 1.4×10^{-3}; the refined state at $T = 30$, whose infidelity is 2.3×10^{-3}, deviates by up to 0.02 in the occupations and by 10^{-2} in the correlation energy, and two rodeo cycles reduce both deviations by a factor 2–3, six cycles by a factor 4–5. Occupation numbers converge more slowly than the energy, as expected for a quantity that is linear rather than quadratic in the error of the state.

S8. THE PAIR BASIS AND THE SIXTEEN-QUBIT INGREDIENTS

Every stage of the pipeline conserves seniority — the Hamiltonian, the embedding, the path, the exactly exponentiated pair-hopping blocks and the filter — so for an N-paired target the whole computation can be carried out in the pair basis (one bit per level, $\binom{k}{N/2}$ states). The pair-basis implementation used for Sec. V E of the main text was validated against the full-sector code at $k = 4$, $N = 4$: the Hamiltonian and every Trotter term coincide with the seniority-zero blocks of their full-sector counterparts to machine precision, and every anchor of the main text is reproduced — the ground-state energy 0.6355484736, the prolonged overlap $p_0 = 0.8676375677$, the refined overlap $p(25) = 0.9975712826$, the Trotterized $p = 0.9922$ at $T^* = 16$ with 43 second-order steps, the four-pair ansatz $E = 0.6369869810$ with $1 - F = 1.776 \times 10^{-4}$, and the exact-ensemble infidelities 1.216×10^{-3}, 6.08×10^{-4}, 3.80×10^{-5} and 2.38×10^{-6} after 1, 2, 6 and 10 cycles. The gate counts of the sixteen-qubit




FIG. S7. Rodeo energy scan ($M = 4$). Left: coarse scan ($\sigma = 2$); the dotted vertical lines mark exact eigenvalues and the dashed line the 2^{-M} background. Right: fine scan ($\sigma = 8$) on a window centered on the coarse-scan maximum; the peak is located at $E = 0.6362$ (exact $E_0 = 0.6355$).

TABLE S2. Operating points behind the fidelities quoted in this paper ($k = 4$, $N = 4$, $g = 1$).

result	assumptions and operating point	status
coarse state (Sec. III A)	factorized UCCSD, numerically optimized	valid circuit family; ϵ_{low} to be supplied or bounded
prolongation (Sec. IV B)	nested bare Hamiltonians, empty appended levels	gate-free embedding; expectation-value identity exact
adiabatic guarantee, Eq. (6)	exact coarse eigenstate, isolated branch, ideal continuous evolution	conditional bound, not the complete digital budget
refinement (Sec. IV B)	$T = 25$ or 30, exact midpoint slices (160)	ideal; slice error $\sim 10^{-6}$
filter (Sec. IV E)	$T = 25$ refined input, $\sigma = 3$, exact controlled evolution, 40 schedules	ideal; sampling error up to 80% at $M = 10$
circuit comparison (Secs. V B–V C)	product formulas, $T = 16$ or 30, $\sigma = 4$, step ceiling $\delta t = 0.25$	digital; floor 1.1×10^{-4} (converged averaged map), acceptance decaying 0.2% per cycle; sampled 40-schedule values in Table II, exact-channel minima in Table V

study are those of the $2k$-qubit compilation of Sec. V of the main text.

Table S5 lists the ingredients of the sixteen-qubit study for $g = 0.5$ to 2, and Fig. S8 the exact-slice transport along the refinement chains $k_{\text{low}} \to 8$ and along the HF ramp, with its coupling dependence.

[1] S. Bogner, H. Hergert, M. Hjorth-Jensen, R. LaRose, D. Lee, M. Patkowski, *Quantum state preparation with resolution refinement*, Phys. Lett. B **875**, 140363 (2026); arXiv:2511.14732.

[2] J. P. Sadia, M. Hjorth-Jensen, D. Lee, R. LaRose, *Digital quantum state preparation by nucleation*, arXiv:2609.37527 (2026).

TABLE S3. The pipeline and the UCCSD comparator at other sizes ($g = 1$): coarse space the filled determinant at $k_{\rm low} = N/2$, exact-slice refinement for $T = 30$, exact controlled evolution with $\sigma = 3$, 40 time sets. ov_0 and p are the overlaps of the prolonged and refined states with the exact ground state, the UCCSD columns give the infidelity and energy error of the sector-level UCCSD state together with its parameter and CNOT counts, and the last four columns the acceptance-weighted infidelity after M rodeo cycles from the refined and from the UCCSD input. The register has $2k$ qubits (8 and 12) and the uncontrolled first-order Trotter step of Eq. (11) costs 296 CNOTs at $k = 4$ and 732 at $k = 6$.

(k, N)	dim	gap	ov_0	$p\,(T{=}30)$	$1-\mathcal{F}_{\rm UCCSD}$	$\Delta E_{\rm UCCSD}$	params	CNOTs	refined+rodeo		UCCSD+rodeo	
									$M{=}2$	$M{=}6$	$M{=}2$	$M{=}6$
$(4,4)$	70	1.823	0.868	0.9988	1.8×10^{-4}	1.4×10^{-3}	26	1 312	3.4×10^{-4}	2.3×10^{-5}	4.1×10^{-5}	1.4×10^{-6}
$(6,4)$	495	2.017	0.798	0.9976	7.6×10^{-4}	6.1×10^{-3}	92	6 976	6.3×10^{-4}	4.1×10^{-5}	1.7×10^{-4}	7.6×10^{-6}
$(4,6)$	28	1.779	0.894	0.9991	$<10^{-15}$	$<10^{-15}$	15	688	2.5×10^{-4}	1.7×10^{-5}	0	0
$(6,6)$	924	2.052	0.780	0.9972	1.0×10^{-3}	8.3×10^{-3}	117	9 024	7.2×10^{-4}	4.8×10^{-5}	2.4×10^{-4}	1.0×10^{-5}

TABLE S4. Level occupation numbers n_p and energy of the prepared states at $k = 4$, $N = 4$, $g = 1$ ($E_{\rm ref} = 1$); the filtered states use the Trotterized filter of Table II ($\delta t = 0.25$) and are acceptance-weighted averages over 40 time sets; $a\,10^{-b}$ stands for $a \times 10^{-b}$.

state	n_0	n_1	n_2	n_3	$E - E_{\rm ref}$	$1-\mathcal{F}$
exact	1.929	1.803	0.197	0.071	−0.3645	0
reference det.	2	2	0	0	0	$1.3\,10^{-1}$
UCCSD	1.930	1.806	0.194	0.070	−0.3630	$1.8\,10^{-4}$
refined ($T{=}30$)	1.908	1.795	0.205	0.092	−0.3549	$2.3\,10^{-3}$
refined+rodeo $M{=}2$	1.920	1.798	0.202	0.080	−0.3621	$5.3\,10^{-4}$
refined+rodeo $M{=}6$	1.923	1.801	0.199	0.077	−0.3637	$1.5\,10^{-4}$
UCCSD+rodeo $M{=}2$	1.924	1.801	0.199	0.076	−0.3637	$1.3\,10^{-4}$

TABLE S5. Four pairs on eight levels ($N = 8$, $k = 8$): HF and exact energies, seniority-zero gap, HF overlap $p_{\rm HF}$, the 16-parameter pair-double ansatz (768 CNOTs) and the 8-parameter coarse ansatz at $k = 6$ (384 CNOTs) with the overlap of its prolongation, the response norm $\chi_u(0) = P(k-P)g^2/(4b^2)$ at $b = 0.6$, and the exact-slice $1 - p$ at $T = 8$ of the HF ramp, of the $4 \to 8$ chain ($\mu_{\rm buf} = 2$) and of the $6 \to 8$ chain from the exact coarse state ($\mu_{\rm buf} = 2$). The shift scan of the $4 \to 8$ chain is Table IV of the main text.

g	$E_{\rm HF}$	E_0	gap	$p_{\rm HF}$	$1-F_{16}$	$1-F_8^{k=6}$	$p_0(6{\to}8)$	$\chi_u(0)$	$1-p(T{=}8)$: ramp / 4→8 / 6→8
0.5	11	10.790	2.06	0.940	2.2×10^{-5}	7.3×10^{-6}	0.989	2.8	7.6×10^{-6} / 1.4×10^{-4} / 1.1×10^{-4}
1	10	8.889	2.59	0.690	3.1×10^{-3}	6.9×10^{-4}	0.928	11.1	1.1×10^{-4} / 4.6×10^{-4} / 6.1×10^{-4}
1.5	9	6.055	3.97	0.413	2.1×10^{-2}	5.3×10^{-3}	0.817	25.0	1.1×10^{-4} / 9.5×10^{-3} / 1.9×10^{-3}
2	8	2.487	5.95	0.253	4.2×10^{-2}	1.3×10^{-2}	0.709	44.4	4.2×10^{-4} / 7.5×10^{-2} / 4.7×10^{-3}




FIG. S8. Four pairs on eight levels ($N = 8$, $k = 8$, sixteen qubits), exact slices. Left, $g = 1$: $1 - p(T)$ for the refinement chains $k_{\mathrm{low}} \to 8$ with $k_{\mathrm{low}} = 4$–7 at $\mu_{\mathrm{buf}} = 0.6$ (dashed) and 2 (solid), the $4 \to 8$ chain at $\mu_{\mathrm{buf}} = 4$, and the HF adiabatic ramp from the same determinant. Right: coupling dependence of the ramp and of the $4 \to 8$ chain at $\mu_{\mathrm{buf}} = 2$ for $g = 0.5$, 1, 1.5 and 2; the dotted lines are the infidelities of the 16-parameter pair-double ansatz.