



# **Week 4 - Lecture 3**

## **Pointers**

**Edited by: Heshan Du**

**Autumn 2024**




# Overview

- Declaration and initialisation
- Pointer to Constant vs. const Pointer
- Pointers and arrays
  - String literals
- **Array of pointers**
- **Pointer arithmetic (e.g., subtracting, comparing)**




# Arrays of Pointers

- Every element in the array is a pointer to the same data type
- `char *arr[3];` array of 3 pointers to arrays of characters
  - Common use i.e., array of strings



# Arrays of Pointers (2)

- A common use of an array of pointers is to form an array of strings, referred to simply as a string array.
- Consider the definition of string array **suit**, which might be useful in representing a deck of cards.
- `const char *suit[ 4 ] = { "Hearts", "Diamonds", "Clubs", "Spades" };`




# Arrays of Pointers (3)

- The **suits** could have been placed in a two-dimensional array.
  - Such a data structure would have to have a fixed number of columns per row, and that number would have to be as large as the largest string.
  - Therefore, considerable memory could be wasted when storing a large number of strings of which most were shorter than the longest string.
- **Because of this, we use arrays of pointers!**

# Q1: What will be shown here?

- `int *arr[3], i, p[3] = {10, 20, 30};`

```
for(i = 0; i < 3; i++){  
    arr[i] = &p[i];  
    printf("%d", *arr[i]);  
}
```



## Q2: What are first chars?

- ```
char *arr[3];  
int i;  
arr[0] = "This is";  
arr[1] = "a new";  
arr[2] = "message";  
for(i = 0; i < 3; i++)  
    printf("Text: %s\tFirst char: %c\n", arr[i],  
*arr[i]);
```



# Overview

- Declaration and initialisation
- Pointer to Constant vs. const Pointer
- Pointers and arrays
  - String literals
- Array of pointers
- **Pointer arithmetic (e.g., subtracting, comparing)**





# Pointer Arithmetic

$$\text{ptr} = \text{ptr} + n;$$


- **char:** **ptr** is increased by  $n$ ; char size is 1 byte.
- **int or float:** **ptr** is increased by  $n * 4$ , int and float size is 4 bytes.
- **double:** **ptr** is increased by  $n * 8$ ; double size is 8 bytes.



# Remember this?!

- A variable name *directly* references a value, a pointer *indirectly* references a value.

```
int Y = 1;  
int *Yptr;  
Yptr = &Y;
```



Source: <http://www.exforsys.com/tutorials/c-language/c-pointers.html>



# Pointer Arithmetic: Example

- ```
int *ptr, i;  
ptr = &i;  
printf("Address = %p\n", ptr);  
ptr++;  
printf("Address = %p\n", ptr);
```

The second address  
will be 4 bytes higher  
than the first one



# Subtracting Pointers

- Only if both pointers refer to the **same data type**, the result of subtracting pointers indicates **the number of data items between them**
- Suppose ptr1 and ptr2 point to two integer variables stored in addresses 1000 and 1040 respectively
- $(\text{ptr2} - \text{ptr1}) \neq 40$
- $(\text{ptr2} - \text{ptr1}) == (40 / 4) == 10$



# Comparing Pointers

- Only if both point to members of the **same data structure**
- Operators: ==, !=, >, <, >= and <=
- To check if two pointers point to **the same address**
  - `if(ptr1 == ptr2)` or `if(ptr1 != ptr2)`



# Q3: explain how this Pointer works?

```
int *ptr, i;  
ptr = &i;  
printf("Address = %p\n", ptr);  
ptr -= 10;  
printf("Address = %p\n", ptr);
```



## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```

```
ptr = &j;
```

```
*ptr += i;
```

```
ptr = &k;
```

```
*ptr += i + j;
```

```
printf("i = %d j = %d k = %d\n", i, j, k);
```

i

10

1000

ptr



500

j

20

2000

k

30

3000



## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```


```
ptr = &j;
```

```
*ptr += i;
```

```
ptr = &k;
```

```
*ptr += i + j;
```

```
printf("i = %d j = %d k = %d\n", i, j, k);
```





## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```


```
ptr = &j;
```

```
*ptr += i;
```

```
ptr = &k;
```

```
*ptr += i + j;
```

```
printf("i = %d j = %d k = %d\n", i, j, k);
```



## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```


```
ptr = &j;
```

```
*ptr += i;
```

```
ptr = &k;
```

```
*ptr += i + j;
```

```
printf("i = %d j = %d k = %d\n", i, j, k);
```



## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```

```
ptr = &j;
```


```
*ptr += i;
```

**\*ptr = \*ptr + i;  
= 20 + 40**

```
ptr = &k;
```

```
*ptr += i + j;
```

```
printf("i = %d j = %d k = %d\n", i, j, k);
```



## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```


```
ptr = &j;
```

```
*ptr += i;
```

```
ptr = &k;
```

```
*ptr += i + j;
```

```
printf("i = %d j = %d k = %d\n", i, j, k);
```



## Q4: What is the value of i, j and k?

```
int *ptr, i = 10, j = 20, k = 30;
```

```
ptr = &i;
```

```
*ptr = 40;
```

```
ptr = &j;
```


```
*ptr += i;
```

```
ptr = &k;
```

```
*ptr += i + j;
```


```
printf("i = %d j = %d k = %d\n", i, j, k);
```

**\*ptr = \*ptr + i + j;  
= 30 + 40 + 60**




# Q5: What is the value of j?

- ```
int *ptr1, *ptr2, i = 10, j = 20;  
ptr1 = &i;  
*ptr1 = 150;  
ptr2 = &j;  
*ptr2 = 50;  
ptr2 = ptr1;  
*ptr2 = 250;  
ptr2 = &j;  
*ptr2 += *ptr1;  
printf("Val = %d\n", j);
```




# Q5: What is the value of j?

- int \*ptr1, \*ptr2, i = 10, j = 20;  
ptr1 = &i;  
\*ptr1 = 150;  
ptr2 = &j;  
\*ptr2 = 50;  
ptr2 = ptr1;  
\*ptr2 = 250;  
ptr2 = &j;  
\*ptr2 += \*ptr1;  
printf("Val = %d\n", j);



# Q5: What is the value of j?


- int \*ptr1, \*ptr2, i = 10, j = 20;  
ptr1 = &i;  
\*ptr1 = 150;  
ptr2 = &j;  
\*ptr2 = 50;  
ptr2 = ptr1;  
\*ptr2 = 250;  
ptr2 = &j;  
\*ptr2 += \*ptr1;  
printf("Val = %d\n", j);






# Q5: What is the value of j?

- int \*ptr1, \*ptr2, i = 10, j = 20;  
ptr1 = &i;  
\*ptr1 = 150;  
ptr2 = &j;  
\*ptr2 = 50;  
**ptr2 = ptr1;**  
\*ptr2 = 250;  
ptr2 = &j;  
\*ptr2 += \*ptr1;  
printf("Val = %d\n", j);




# Q5: What is the value of j?

- `int *ptr1, *ptr2, i = 10, j = 20;`  
`ptr1 = &i;`  
`*ptr1 = 150;`  
`ptr2 = &j;`  
`*ptr2 = 50;`  
`ptr2 = ptr1;`  
**`*ptr2 = 250;`**  
`ptr2 = &j;`  
`*ptr2 += *ptr1;`  
`printf("Val = %d\n", j);`



# Q5: What is the value of j?


- `int *ptr1, *ptr2, i = 10, j = 20;`  
`ptr1 = &i;`  
`*ptr1 = 150;`  
`ptr2 = &j;`  
`*ptr2 = 50;`  
`ptr2 = ptr1;`  
`*ptr2 = 250;`  
`ptr2 = &j;`  
`*ptr2 += *ptr1;`  
`printf("Val = %d\n", j);`



# Q5: What is the value of j?

- int \*ptr1, \*ptr2, i = 10, j = 20;  
ptr1 = &i;  
\*ptr1 = 150;  
ptr2 = &j;  
\*ptr2 = 50;  
ptr2 = ptr1;  
\*ptr2 = 250;  
ptr2 = &j;  
**\*ptr2 += \*ptr1;**  
printf("Val = %d\n", j);

**\*ptr2 = \*ptr2 + \*ptr1;**  
**\*ptr2 = 50 + 250**



# Summary

- Array of pointers
- Pointer arithmetic (e.g., subtracting, comparing)

