


# Heapsort



# Heaps

- | A *heap* can be seen as a complete binary tree:




- n *What makes a binary tree complete?*
- n *Is the example above complete?*



# Heaps

- | A *heap* can be seen as a complete binary tree:




- n The book calls them “nearly complete” binary trees; can think of unfilled slots as null pointers




# Heaps

- In practice, heaps are usually implemented as arrays:



# Heaps

- | To represent a complete binary tree as an array:
  - n The root node is  $A[1]$
  - n Node  $i$  is  $A[i]$
  - n The parent of node  $i$  is  $A[i/2]$  (note: integer divide)
  - n The left child of node  $i$  is  $A[2i]$
  - n The right child of node  $i$  is  $A[2i + 1]$



# Referencing Heap Elements

| So...

```
Parent(A[i]) { return A[⌊i/2⌋]; }
```

```
Left(A[i]) { return A[2*i]; }
```

```
right(A[i]) { return A[2*i + 1]; }
```



# The Heap Property

- | Heaps also satisfy the *heap property*:

$$A[\textit{Parent}(A[i])] \geq A[i] \quad \text{for all nodes } i > 1$$

- n In other words, the value of a node is at most the value of its parent
- n *Where is the largest element in a heap stored?*



# Heap Height

## | Definitions:

- n The *height* of a node in the tree = the number of edges on the longest downward path to a leaf
- n The height of a tree = the height of its root

## | *What is the height of an $n$ -element heap? Why?*

- | This is nice: basic heap operations take at most time proportional to the height of the heap





# Heap Operations: Heapify()

- | **Heapify()** : maintain the heap property
  - n Given: a node  $i$  in the heap with children  $l$  and  $r$
  - n Given: two subtrees rooted at  $l$  and  $r$ , assumed to be heaps
  - n Problem: The subtree rooted at  $i$  may violate the heap property (*How?*)
  - n Action: let the value of the parent node “float down” so subtree at  $i$  satisfies the heap property
    - u *What do you suppose will be the basic operation between  $i$ ,  $l$ , and  $r$ ?*




# Heap Operations: Heapify()

```
Heapify(A, i)
{
    l = Left(i); r = Right(i);
    if (l <= heap_size(A) && A[l] > A[i])
        largest = l;
    else
        largest = i;
    if (r <= heap_size(A) && A[r] > A[largest])
        largest = r;
    if (largest != i)
        Swap(A, i, largest);
    Heapify(A, largest);
}
```



# Heapify() Example




$A =$ 

16	4	10	14	7	9	3	2	8	1
----	---	----	----	---	---	---	---	---	---



# Heapify() Example





A = 


16	4	10	14	7	9	3	2	8	1
----	---	----	----	---	---	---	---	---	---



# Heapify() Example



# Heapify() Example




$A =$ 

16	14	10	4	7	9	3	2	8	1
----	----	----	---	---	---	---	---	---	---



# Heapify() Example





$A =$ 

16	14	10	4	7	9	3	2	8	1
----	----	----	---	---	---	---	---	---	---




# Heapify() Example





# Heapify() Example




$A =$ 

16	14	10	8	7	9	3	2	4	1
----	----	----	---	---	---	---	---	---	---



# Heapify() Example




$A =$ 

16	14	10	8	7	9	3	2	4	1
----	----	----	---	---	---	---	---	---	---



# Heapify() Example



$A =$ 

16	14	10	8	7	9	3	2	4	1
----	----	----	---	---	---	---	---	---	---



# Analyzing Heapify(): Informal

- | *Aside from the recursive call, what is the running time of **Heapify()**?*
- | *How many times can **Heapify()** recursively call itself?*
- | *What is the worst-case running time of **Heapify()** on a heap of size  $n$ ?*



# Analyzing Heapify(): Formal

- | Fixing up relationships between  $i$ ,  $l$ , and  $r$  takes  $\Theta(1)$  time
- | *If the heap at  $i$  has  $n$  elements, how many elements can the subtrees at  $l$  or  $r$  have?*
  - n Draw it
- | Answer:  $2n/3$  (worst case: bottom row 1/2 full)
- | So time taken by **Heapify()** is given by
$$T(n) \leq T(2n/3) + \Theta(1)$$



# Analyzing Heapify(): Formal

- | So we have

$$T(n) \leq T(2n/3) + \Theta(1)$$

- | By case 2 of the Master Theorem,

$$T(n) = O(\lg n)$$

- | Thus, **Heapify()** takes logarithmic time



# Heap Operations: BuildHeap()

- | We can build a heap in a bottom-up manner by running **Heapify()** on successive subarrays
  - n Fact: for array of length  $n$ , all elements in range  $A[\lfloor n/2 \rfloor + 1 .. n]$  are heaps (*Why?*)
  - n So:
    - u Walk backwards through the array from  $n/2$  to 1, calling **Heapify()** on each node.
    - u Order of processing guarantees that the children of node  $i$  are heaps when  $i$  is processed



# BuildHeap()

```
// given an unsorted array A, make A a heap
BuildHeap(A)
{
    heap_size(A) = length(A);
    for (i = ⌊length[A]/2⌋ downto 1)
        Heapify(A, i);
}
```






# BuildHeap() Example

| Work through example

$A = \{4, 1, 3, 2, 16, 9, 10, 14, 8, 7\}$



# Analyzing BuildHeap()

- | Each call to **Heapify()** takes  $O(\lg n)$  time
- | There are  $O(n)$  such calls (specifically,  $\lfloor n/2 \rfloor$ )
- | Thus the running time is  $O(n \lg n)$ 
  - n *Is this a correct asymptotic upper bound?*
  - n *Is this an asymptotically tight bound?*
- | A tighter bound is  $O(n)$ 
  - n *How can this be? Is there a flaw in the above reasoning?*



# Analyzing BuildHeap(): Tight

- | To **Heapify** ( ) a subtree takes  $O(h)$  time where  $h$  is the height of the subtree
  - n  $h = O(\lg m)$ ,  $m = \#$  nodes in subtree
  - n The height of most subtrees is small
- | Fact: an  $n$ -element heap has at most  $\lceil n/2^{h+1} \rceil$  nodes of height  $h$



# Heapsort

- | Given **BuildHeap()**, an in-place sorting algorithm is easily constructed:
  - n Maximum element is at  $A[1]$
  - n Discard by swapping with element at  $A[n]$ 
    - u Decrement  $\text{heap\_size}[A]$
    - u  $A[n]$  now contains correct value
  - n Restore heap property at  $A[1]$  by calling **Heapify()**
  - n Repeat, always swapping  $A[1]$  for  $A[\text{heap\_size}(A)]$



# Heapsort

Heapsort (A)

```
{  
    BuildHeap(A) ;  
    for (i = length(A) downto 2)  
    {  
        Swap(A[1], A[i]) ;  
        heap_size(A) -= 1 ;  
        Heapify(A, 1) ;  
    }  
}
```



# Analyzing Heapsort

- | The call to **BuildHeap** ( ) takes  $O(n)$  time
- | Each of the  $n - 1$  calls to **Heapify** ( ) takes  $O(\lg n)$  time
- | Thus the total time taken by **HeapSort** ( )  
$$= O(n) + (n - 1) O(\lg n)$$
$$= O(n) + O(n \lg n)$$
$$= O(n \lg n)$$



# Priority Queues

- | Heapsort is a nice algorithm, but in practice Quicksort (coming up) usually wins
- | But the heap data structure is incredibly useful for implementing *priority queues*
  - n A data structure for maintaining a set  $S$  of elements, each with an associated value or *key*
  - n Supports the operations **Insert()**, **Maximum()**, and **ExtractMax()**
  - n *What might a priority queue be useful for?*



# Implementing Priority Queues with Heaps

The heap data structure with the Heapify-down and Heapify-up operations can efficiently implement a priority queue that is constrained to hold at most  $N$  elements at any point in time. Here we summarize the operations we will use.

- **StartHeap( $N$ )** returns an empty heap  $H$  that is set up to store at most  $N$  elements. This operation takes  $O(N)$  time, as it involves initializing the array that will hold the heap.
- **Insert( $H, v$ )** inserts the item  $v$  into heap  $H$ . If the heap currently has  $n$  elements, this takes  $O(\log n)$  time.
- **FindMin( $H$ )** identifies the minimum element in the heap  $H$  but does not remove it. This takes  $O(1)$  time.
- **Delete( $H, i$ )** deletes the element in heap position  $i$ . This is implemented in  $O(\log n)$  time for heaps that have  $n$  elements.
- **ExtractMin( $H$ )** identifies and deletes an element with minimum key value from a heap. This is a combination of the preceding two operations, and so it takes  $O(\log n)$  time.

