

Introduction to Communications and IOT

Praanesh Balakrishnan Nair

February 4, 2025

Contents

| | | |
|----------|---|----------|
| 1 | Introduction | 2 |
| 1.1 | What a Signal is | 2 |
| 1.2 | Types of Communication | 2 |
| 1.2.1 | Wired / Wireless | 2 |
| 1.2.2 | Unidirectional / Bidirectional | 2 |
| 1.2.3 | Analogue / Digital | 2 |
| 1.2.4 | Transmission Technique | 3 |
| 2 | Characteristics of a Signal | 3 |
| 2.1 | Standard Notation of a Standard Sinusoidal Signal | 3 |
| 2.2 | Angular Frequency | 3 |
| 2.3 | Frequency | 3 |
| 2.4 | Phase | 3 |
| 3 | Time Domain vs Frequency Domain | 4 |
| 4 | Odd Signals vs Even Signals | 4 |
| 5 | Energy and Power of a Signal | 4 |
| 5.1 | Prerequisite knowledge | 4 |
| 5.2 | Energy | 5 |
| 5.3 | Power | 5 |
| 6 | Complex Sinusoids | 6 |
| 7 | Sampling | 6 |
| 7.1 | What it is | 6 |
| 7.2 | Sampling Theorem or Nyquist Theorem | 6 |
| 8 | Filters | 7 |
| 8.1 | Analog Filters | 7 |
| 8.2 | Digital Filters | 7 |
| 8.2.1 | Finite Impulse Response (FIR) | 7 |
| 8.2.2 | Infinite Impulse Response (IIR) | 8 |
| 9 | Modulation | 8 |

1 Introduction

1.1 What a Signal is

- It's a Quantitative Representation of Information
- The most basic representation of a signal is in the form of a graph (t on X-axis and $f(t)$ on Y-axis)

1.2 Types of Communication

1.2.1 Wired / Wireless

1. Wired:

- Via Coaxial cables or Fibre-Optic Cables

2. Wireless:

- Via Electromagnetic waves or rays

1.2.2 Unidirectional / Bidirectional

1. Simplex:

- One-way
- Eg. Broadcast, FM

2. Half-Duplex:

- Two-way, but only one direction at a time
- Eg. walkie-talkie

3. Duplex:

- Two-way, and both directions are simultaneously possible

1.2.3 Analogue / Digital

1. Analog:

- Both t and $f(t)$ are continuous

2. Digital:

- Both t and $f(t)$ are discrete

3. Continuous-Time:

- t is continuous, but $f(t)$ is discrete

4. Discrete-Time:

- t is discrete and $f(t)$ is continuous

1.2.4 Transmission Technique

Before knowing this, you must know what bandwidth is:

Bandwidth:

- Range of frequencies a signal operates.
- In other words:

$$\text{Bandwidth} = (\text{Highest Frequency of the Wave/Signal}) - (\text{Lowest Frequency of the Wave/Signal})$$

- Fast, irregular variations in frequency \propto Bandwidth

1. Baseband:

- Digital Signals which are sent via TDM (Time Division Multiplexing)
- One signal uses the entire bandwidth

2. Broadband:

- (I'll add this later)

2 Characteristics of a Signal

2.1 Standard Notation of a Standard Sinusoidal Signal

- For a graph where X-axis = θ and Y-axis = $\sin(\theta)$, the measure of input is θ .
- To actually measure a signal against time, X-axis = t (time) and Y-axis = $\sin(\theta)$
- Here's what we do for that: $\sin(\theta + \phi) = \sin(\omega t + \phi)$

2.2 Angular Frequency

- ω = Angular Frequency/Velocity
- $= \frac{\text{Angle}}{\text{Time}}$
- $= \frac{2\pi}{T}$

2.3 Frequency

- $f = \frac{1}{T}$
- So, $\omega = \frac{2\pi}{T}$ can also be written as $\omega = 2\pi f$

2.4 Phase

- θ or ωt is the X-coordinate.
- Phase ϕ is added to the X-coordinate, so the wave shifts to the left by ϕ
- In a way, it's an offset to a wave. (Check <https://www.geogebra.org/m/rzzqtx6q> for some Visualization)
- For example, if a sine wave is offset by $\frac{1}{6}th$ of a cycle, then the phase would be $\frac{1}{6} * 360^\circ \Rightarrow \text{Phase} = 60^\circ$

3 Time Domain vs Frequency Domain

In both cases, Y-Axis = *Amplitude*. Only X-Axis changes




Figure 1: Time Domain




Figure 2: Frequency Domain

4 Odd Signals vs Even Signals

- **Odd Signals/Functions:** $y(-x) = -y(x)$
- **Even Signals/Functions:** $y(-x) = y(x)$

5 Energy and Power of a Signal

5.1 Prerequisite knowledge

- Let's assume we have a sinusoidal voltage and current
- $P = \frac{V^2}{R} = I^2 R$
- This means that the power of a signal is some **constant** times **voltage squared** or **current squared**
- Let us have a general signal $x(t)$ which can either be sinusoidal voltage or sinusoidal current

$$x(t) = V \text{ or } x(t) = I$$

- So Instantaneous Power = $P = (x(t))^2$




Figure 3: Green Curve showing V or I and the Red Curve showing P

5.2 Energy

- Energy = Power * time
- But the above formula is only applicable for discrete values.
- So the energy of a signal would be the area of the Power-Time Graph




Figure 4: Area under the Red Curve

$$\text{Energy} = \int P dt = \int_{-\frac{T}{2}}^{\frac{T}{2}} (x(t))^2 dt$$

- The limits are actually from 0 to T , but having them from $-\frac{T}{2}$ to $\frac{T}{2}$ simplifies calculations.

5.3 Power

- Power is just $\frac{\text{Energy}}{\text{Time}}$.
- Power = $\frac{\int_{-\frac{T}{2}}^{\frac{T}{2}} (x(t))^2 dt}{T}$

6 Complex Sinusoids

- **In phase:** Two signals are said to be in phase if they have phase difference 0
- **Quadrature:** Two signals are said to be in quadrature if they have a phase difference 0
- A complex sinusoid is given as $\cos(\theta) + j\sin(\theta)$
- $\cos(\theta)$ is the real component plotted on
- Now $\cos(\theta)$ is taken to be on the *Inphase – Time* plane, and $\sin(\theta)$ is taken to be on the *Quadrature – Time* plane
- This results in a helical structure.
- Number of rotations about the *time* axis, per unit time, is the frequency of the complex sinusoid.
- Anti-Clockwise rotation means Positive frequency, so clockwise rotation means negative frequency

7 Sampling

7.1 What it is

- Converting a continuous time signal into a discrete time signal by taking samples of the signals at discrete time intervals
- Say we have a continuous sinusoidal signal:

$$s(t) = A\cos(2\pi Ft + \phi)$$

- In its discrete form, instead of a parameter t , you'd have parameters n and T_s :

$$s[n] = A\cos(2\pi FnT_s + \phi)$$

or

$$s[n] = A\cos(2\pi F \frac{n}{F_s} + \phi)$$

Here, T_s = Sampling Time Period and F_s = Sampling Frequency

7.2 Sampling Theorem or Nyquist Theorem

- F_s is the number of samples taken per second i.e. the **sampling rate**. Likewise, T_s is the time taken to record one sample
- If F_s is too less, you won't be able to capture the wave correctly. You'll end up over-simplifying the wave.
- This is called **aliasing**, and it's where high-frequency components appear as low-frequency components because of insufficient sampling rate.
- Nyquist Theorem states that:

$$F_s \geq 2B$$

where B is the highest bandwidth present in the signal

Another way of saying this would be:

$$B \leq \frac{F_s}{2}$$

8 Filters

8.1 Analog Filters

1. **Low Pass Filters:** Keeps frequencies below a cutoff, and cuts off everything after it
2. **High Pass Filters:** Keeps frequencies after a cutoff, and cuts off everything below it
3. **Band Pass Filters:** Keeps frequencies inside a range (above a lower cutoff, and below a higher cutoff), and cuts off everything outside
4. **Band Reject/Stop Filters:** Keeps frequencies outside a range, and cuts off everything inside

8.2 Digital Filters

- They're mathematical algorithms used on discrete time signals
- Before knowing this, you must know about impulse signals:
 - **Impulse Signal $\delta[n]$:**
 - $\delta[n] = 1$ if $n = 0$, and $\delta[n] = 0$ for any other value of n
 - This function is used for representing frequencies in digital signals
 - **Impulse Response $h[n]$:** Output of a system, if the input is an impulse signal.

8.2.1 Finite Impulse Response (FIR)

1. What it is
 - Output depends only on current and past input
 - Output does NOT depend on past output

$$y[n] = \sum_{i=0}^M b_i x[n-i]$$

where $y[n]$ = output of filter, $x[n]$ = input signal, b_i = filter coefficients, M = filter order = number of taps

- Eg. $y[n] = 0.25x[n] + 0.5x[n-1] + 0.25x[n-2]$
 - This is called a 3-tap FIR Filter
 - The impulse response for this filter would be
 - * $h[n] = [y[0], y[1], y[2], y[3], \dots, y[n]]$
 - * $h[n] = [0.25, 0.5, 0.25, 0, 0, 0, \dots]$

2. Characteristics

- Stable (Phase response is linear, and can be good for image/audio processing)
- Phase Accurate
- Computationally expensive
- Impulse response decays to 0

8.2.2 Infinite Impulse Response (IIR)

1. What is is

- Output depends on past input AND past output i.e. it uses **feedback**.

$$y[n] = \sum_{i=0}^N a_i y[n-i] + \sum_{i=0}^M b_i x[n-i]$$

Here, it's just whatever FIR was, but you're also doing the same thing for the previous **outputs** too.

2. Characteristics

- If order is low, frequency cutoffs will be sharp (Phase response is non-linear) (Can be good for real-time communication)
- Computationally efficient
- Can cause phase distortion
- Impulse response never decays to 0 (hence, it's infinite)

9 Modulation