Bandbreite der Programmiersprachen

Carsten Gips (HSBI)

TL;DR
Am Beispiel des Abzählreims “99 Bottles of Beer” werden (ganz kurz) verschiedene Programmiersprachen betrachtet. Jede der Sprachen hat ihr eigenes Sprachkonzept (Programmierparadigma) und auch ein eigenes Typ-System sowie ihre eigene Strategie zur Speicherverwaltung und Abarbeitung.
Auch wenn die Darstellung längst nicht vollständig ist, macht sie doch deutlich, dass Compiler teilweise sehr unterschiedliche Konzepte “verstehen” müssen.
Videos

- VL Programmiersprachen

---

1 99 Bottles of Beer

> 99 bottles of beer on the wall, 99 bottles of beer. Take one down and pass it around, 98 bottles of beer on the wall.
>
> 98 bottles of beer on the wall, 98 bottles of beer. Take one down and pass it around, 97 bottles of beer on the wall.
>
> [...]
>
> 2 bottles of beer on the wall, 2 bottles of beer. Take one down and pass it around, 1 bottle of beer on the wall.
>
> 1 bottle of beer on the wall, 1 bottle of beer. Take one down and pass it around, no more bottles of beer on the wall.
>
> No more bottles of beer on the wall, no more bottles of beer. Go to the store and buy some more, 99 bottles of beer on the wall.

Quelle: nach “Lyrics of the song 99 Bottles of Beer” on 99-bottles-of-beer.net

2 Imperativ, Hardwarenah: C

```c
#define MAXBEER (99)
void chug(int beers);
main() {
   register beers;
   for(beers = MAXBEER; beers; chug(beers--))  puts("");
   puts("\nTime to buy more beer!\n");
}
void chug(register beers) {
   char howmany[8], *s;
   s = beers != 1 ? "s" : "";
   printf("%d bottle%s of beer on the wall,\n", beers, s);
   printf("%d bottle%s of beeeeer . . . ,\n", beers, s);
```

```
    printf("Take one down, pass it around,\n");
    if(--beers) sprintf(howmany, "%d", beers); else strcpy(howmany, "No more");
    s = beers != 1 ? "s" : "";
    printf("%s bottle%s of beer on the wall.\n", howmany, s);
}
```

Quelle: "Language C" by Bill Wein on 99-bottles-of-beer.net

- Imperativ
- Procedural
- Statisches Typsystem
- Resourcenschonend, aber "unsicher": Programmierer muss wissen, was er tut
- Relativ hardwarenah
- Einsatz: Betriebssysteme, Systemprogrammierung

3 Imperativ, Objektorientiert: Java

```
class bottles {
    public static void main(String args[]) {
        String s = "s";
        for (int beers=99; beers>-1;) {
            System.out.print(beers + " bottle" + s + " of beer on the wall, ");
            System.out.println(beers + " bottle" + s + " of beer, ");
            if (beers==0) {
                System.out.print("Go to the store, buy some more, ");
                System.out.println("99 bottles of beer on the wall.\n");
                System.exit(0);
            } else
                System.out.print("Take one down, pass it around, ");
            s = (--beers == 1)?"":"s";
            System.out.println(beers + " bottle" + s + " of beer on the wall.\n
                ");
        }
    }
}
```

Quelle: "Language Java" by Sean Russell on 99-bottles-of-beer.net

- Imperativ
- Objektorientiert
- Multi-Threading
- Basiert auf C/C++
- Statisches Typsystem
- Automatische Garbage Collection

- “Sichere” Architektur: Laufzeitumgebung fängt viele Probleme ab
- Architekturneutral: Nutzt Bytecode und eine JVM
- Einsatz: High-Level All-Purpose Language

4 Logisch: Prolog

```
bottles :-
    bottles(99).

bottles(1) :-
    write('1 bottle of beer on the wall, 1 bottle of beer,'), nl,
    write('Take one down, and pass it around,'), nl,
    write('Now they are all gone.'), nl,!.
bottles(X) :-
    write(X), write(' bottles of beer on the wall,'), nl,
    write(X), write(' bottles of beer,'), nl,
    write('Take one down and pass it around,'), nl,
    NX is X - 1,
    write(NX), write(' bottles of beer on the wall.'), nl, nl,
    bottles(NX).
```

Quelle: “Language Prolog” by M@ on 99-bottles-of-beer.net

- Deklarativ
- Logisch: Definition von Fakten und Regeln; eingebautes Beweissystem
- Einsatz: Theorem-Beweisen, Natural Language Programming (NLP), Expertensysteme, …

5 Funktional: Haskell

```
bottles 0 = "no more bottles"
bottles 1 = "1 bottle"
bottles n = show n ++ " bottles"

verse 0   = "No more bottles of beer on the wall, no more bottles of beer.\n"
         ++ "Go to the store and buy some more, 99 bottles of beer on the wall.
            "

verse n   = bottles n ++ " of beer on the wall, " ++ bottles n ++ " of beer.\n"
         ++ "Take one down and pass it around, " ++ bottles (n-1)
                                                 ++ " of beer on the wall.\n"

main      = mapM (putStrLn . verse) [99,98..0]
```

Quelle: “Language Haskell” by lavor on 99-bottles-of-beer.net

- Deklarativ

- Funktional
- Lazy, pure
- Statisches Typsystem
- Typinferenz
- Algebraische Datentypen, Patternmatching
- Einsatz: Compiler, DSL, Forschung

6 Brainfuck

Quelle: Screenshot of "Language Brainfuck" by Michal Wojciech Tarnowski on 99-bottles-of-beer.net

- Imperativ
- Feldbasiert (analog zum Band der Turingmaschine)
- 8 Befehle: Zeiger und Zellen inkrementieren/dekrementieren, Aus- und Eingabe, Sprungbefehle

7 Programmiersprache Lox

```
fun fib(x) {
    if (x == 0) {
        return 0;
    } else {
        if (x == 1) {
            return 1;
```

```
        } else {
            fib(x - 1) + fib(x - 2);
        }
    }
}

var wuppie = fib;
wuppie(4);
```

- Die Sprache “Lox” finden Sie hier: craftinginterpreters.com/the-lox-language.html
- C-ähnliche Syntax
- Imperativ, objektorientiert, Funktionen als *First Class Citizens*, Closures
- Dynamisch typisiert
- Garbage Collector
- Statements und Expressions
- (Kleine) Standardbibliothek eingebaut

Die Sprache ähnelt stark anderen modernen Sprachen und ist gut geeignet, um an ihrem Beispiel Themen wie Scanner/Parser/AST, Interpreter, Object Code und VM zu studieren :)

8 Wrap-Up

- Compiler übersetzen formalen Text in ein anderes Format

- Berücksichtigung von unterschiedlichen
  - Sprachkonzepten (Programmierparadigmen)
  - Typ-Systemen
  - Speicherverwaltungsstrategien
  - Abarbeitungsstrategien

9 Zum Nachlesen

- Aho u. a. (2023): Kapitel 1 Introduction
- Grune u. a. (2012): Kapitel 1 Introduction

Lernziele

- k1: Verschiedene Beispiele für verschiedene Programmiersprachen und Paradigmen

---

Quellen

Aho, A. V., M. S. Lam, R. Sethi, J. D. Ullman, und S. Bansal. 2023. *Compilers: Principles, Techniques, and Tools, Updated 2nd Edition by Pearson*. Pearson India. https://learning.oreilly.com/library/view/compilers-principles-techniques/9789357054881/.

Grune, D., K. van Reeuwijk, H. E. Bal, C. J. H. Jacobs, und K. Langendoen. 2012. *Modern Compiler Design*. Springer.

Unless otherwise noted, this work is licensed under CC BY-SA 4.0.

Exceptions:

- “Language Prolog” by M@ on 99-bottles-of-beer.net
- “Language Haskell” by Iavor on 99-bottles-of-beer.net
- nach “Lyrics of the song 99 Bottles of Beer” on 99-bottles-of-beer.net
- “Language Java” by Sean Russell on 99-bottles-of-beer.net
- Screenshot of “Language Brainfuck” by Michal Wojciech Tarnowski on 99-bottles-of-beer.net
- “Language C” by Bill Wein on 99-bottles-of-beer.net

> **Last modified:** a10718a (Remove Hugo: tooling: shift headings (use h1 as top-level headings), 2025-07-25)