

Assignment 6 Design

Lempel-Ziv Compression

Arnav Nepal

February 28, 2023

1 Introduction

In this assignment we will be implementing the 1978 Lempel-Ziv data compression algorithm, otherwise known as LZ78. LZ78 uses a dictionary to map keywords to a “code”, or index. Keywords are first input into the dictionary as single characters. When a repeat character in a text file is encountered, the dictionary stores it as a pair of the index of the repeated character and the new character. It repeats this, performing the same action any time it runs into a repeated character or sequence of characters. In order to make our program we will need to design and implement a host of abstract data types (ADT's), including a trie ADT and word table ADT. The files we will be implementing include:

- encode.c
- decode.c
- trie.c
- word.c
- io.c
- Makefile

2 Design and Psuedocode

This program requires us to implement 3 abstract data types: a trie module, a word table module, and an input/output module.

2.1 trie.c

A trie, a play on “*retrieval*”, is a tree data structure. Also known as a prefix tree, each node in a trie contains a symbol and a pointer to n child nodes, where n is the number of letters in the alphabet being used. As we are using ASCII, $n = 256$. We will be using the trie data structure during compression to store words.

```
//reference for TrieNode struct
struct TrieNode {
    TrieNode *children[ALPHABET];
    uint16_t code;
};

//ALPHABET is defined as 256

TrieNode *trie_node_create(uint16_t index):
    allocate memory for trienode struct *trie
    set trie->code = index
    for i in range (ALPHABET):
        set trie->children[i] to NULL
    return trie

//only a single free() required here since struct
//elements don't need memory here
void trie_node_delete(TrieNode *n);
    free(n)
    set n = NULL

//simple function, just needs to create a node
//and set code to EMPTY_CODE
TrieNode *trie_create(void);
    TrieNode *root = trie_node_create(EMPTY_CODE)
    if root != NULL:
        return root
    else:
        return NULL

void trie_reset(TrieNode *root);

void trie_delete(TrieNode *n);
    if
TrieNode *trie_step(TrieNode *n, uint8_t sym);
```
