

Org-Mode Beamer Example

Derek Feichtinger

2010-03-30 Tue

Outline

- 1 Introduction
- 2 A collection of example pages
- 3 Using Beamer_act for overlays
- 4 Multiple Columns
- 5 Conclusions

Org mode version information

Emacs version: GNU Emacs 24.4.1 (x86_64-unknown-linux-gnu, GTK+ Vers
of 2014-10-31 on dflt1w
org version: 8.2.10

Overview

- This is based on an [the Worg hosted example by Eric S. Fraga](#) and on the [beamer reference card](#) by Fabrice Niessen on GitHub.
- The H:2 setting in the options line is important for setting the Beamer frame level. Headlines will become frames when their level is equal to `org-beamer-frame-level`.
- nice link: [beamer theme matrix](#)
- [nice example on beamer features \(pure Latex\)](#)
- <http://www2.informatik.hu-berlin.de/~mischulz/beamer.html>

A simple slide

This slide consists of some text with a number of bullet points:

- the first, very **important**, point!
- the previous point shows the use of the special markup which translates to the Beamer specific *alert* command for highlighting text.

The above list could be numbered or any other type of list and may include sub-lists.

A more complex slide

This slide illustrates the use of Beamer blocks. The following text, with its own headline, is displayed in a block:

Theorem (Org mode increases productivity)

- *org mode means not having to remember \LaTeX commands.*
- *it is based on ascii text which is inherently portable.*
- *Emacs!*



Some text features

The double @@ can be used to enclose active code. Here we use it to specify beamer code that will highlight text by specifying an overlay.

A useful feature

The following setting acts like `\begin{itemize}[<+>]`. So, it will cause the list items to appear one after the other.

- item 1
- item 2
- item 3

Some text features

The double @@ can be used to enclose active code. Here we use it to specify beamer code that will highlight text by specifying an overlay.

A **useful** feature

The following setting acts like `\begin{itemize}[<+>]`. So, it will cause the list items to appear one after the other.

- item 1
- item 2
- item 3

Some text features

The double @@ can be used to enclose active code. Here we use it to specify beamer code that will highlight text by specifying an overlay.

A **useful** feature

The following setting acts like `\begin{itemize}[<+>]`. So, it will cause the list items to appear one after the other.

- item 1
- item 2
- item 3

block environments

a block

```
\begin{block}{A block}  
...  
\end{block}
```

an alert block

```
\begin{alertblock}{An alert block}  
...  
\end{alertblock}
```

an example block

```
\begin{exampleblock}{An alert block}  
...  
\end{exampleblock}
```

some more blocks

The beamercolorbox does not seem to work

```
\begin{beamercolorbox}[shadow=true, rounded=true]{eecks}  
...  
\end{beamercolorbox}
```

A `fullframe` is a frame with an ignored slide title. `frametitle` is set to the empty string

- A headline with an `ignoreheading` environment will only have its contents displayed in the output. The heading text itself is ignored, and no heading bar is shown.

- Contents are not inserted in any `frame` environment.

- `ignoreheading` is useful as a structural element in order to again place normal text after a previous element (like a block or a column environment).

structureenv environment

- For highlighting text.
- To help the audience see the structure of your presentation.
- **TODO:** Currently I see no effect on the text style when using structureenv
- might need to use ignoreheading (like here) in order to then insert some more normal text after the structureenv.

Definition (definition)

Contents of the definition

proof environment and revealing line by line

proof.

- Suppose p were the largest prime number.
- Let q be the product of the first p numbers.
- Then $q + 1$ is not divisible by any of them.
- But $q + 1$ is greater than 1, thus divisible by some prime number not in the first p numbers. □

proof environment and revealing line by line

proof.

- Suppose p were the largest prime number.
- Let q be the product of the first p numbers.
- Then $q + 1$ is not divisible by any of them.
- But $q + 1$ is greater than 1 , thus divisible by some prime number not in the first p numbers. □

proof environment and revealing line by line

proof.

- Suppose p were the largest prime number.
- Let q be the product of the first p numbers.
- Then $q + 1$ is not divisible by any of them.
- But $q + 1$ is greater than 1, thus divisible by some prime number not in the first p numbers. □

proof environment and revealing line by line

proof.

- Suppose p were the largest prime number.
- Let q be the product of the first p numbers.
- Then $q + 1$ is not divisible by any of them.
- But $q + 1$ is greater than 1 , thus divisible by some prime number not in the first p numbers. □

Tables

The size of the table font can be chosen by giving a #+LATEX: `\small` command (or `\tiny` or `\footnotesize`)

WNs	Processors	Cores/node	HS06/node	total cores	total HS06
20	2*Xeon X5560	8	118	160	2360
11	2*E5-2670 2.60GHz	16	263	176	2893
4	2*AMD 6272 2.40GHz	32	241	128	964
35				464	6217

Two blocks

First Block

- this is visible from the beginning

Second Block

- and this one is revealed afterwards by using the `BEAMER_act` keyword in the `PROPERTIES` section.

Two blocks

First Block

- this is visible from the beginning

Second Block

- and this one is revealed afterwards by using the `BEAMER_act` keyword in the `PROPERTIES` section.

Two blocks with invisible layering

First Block

- this is visible from the beginning

Two blocks with invisible layering

First Block

- this is visible from the beginning

Second Block

- and this one is revealed afterwards by using the `BEAMER_act` keyword in the `PROPERTIES` section.

Three blocks with a different transparency setting

First Block

- this is visible from the beginning

Second Block

- and this one is revealed afterwards by using the `BEAMER_act` keyword in the `PROPERTIES` section.

Third Block

- and this one is revealed afterwards by using the `BEAMER_act` keyword in the `PROPERTIES` section.

Three blocks with a different transparency setting

First Block

- this is visible from the beginning

Second Block

- and this one is revealed afterwards by using the BEAMER_act keyword in the PROPERTIES section.

Third Block

- and this one is revealed afterwards by using the BEAMER_act keyword in the PROPERTIES section.

Three blocks with a different transparency setting

First Block

- this is visible from the beginning

Second Block

- and this one is revealed afterwards by using the BEAMER_act keyword in the PROPERTIES section.

Third Block

- and this one is revealed afterwards by using the BEAMER_act keyword in the PROPERTIES section.

Blocks in two columns

A left block


- this slide consists of two columns
- This is the first column

A right block

- this is the right column


A text section and a figure

- this slide consists of two columns
- the first (left) column has no heading and consists of text
- the second (right) column has an image and is enclosed in an **example** block



A Block and a figure

- a centered text section. I found no good way for using `\vfill` or `\minipage` as referenced [here](#)



Octave code

```
A = [1 2 ; 3 4]
b = [1; 1];
x = A\b
```

The output

```
A =  
  
    1    2  
    3    4  
  
x =  
  
   -1  
    1
```

Summary

- org is an incredible tool for time management
- **but** it is also excellent for writing and for preparing presentations
- Beamer is a very powerful \LaTeX package for presentations
- the combination is unbeatable!

Appendix

SOME BACKUP SLIDES. The Appendix will not be listed in the table of contents.

Backup slide 1

Some backup info

Backup slide 2

These details are not part of the main talk.

- show how to embed SVG pictures