

# Computational Physics

## Topic 03 — Computational Problems involving Marko Chains

---

### Lecture 02 — The Collector Problem

Dr Kieran Murphy

Department of Computing and Mathematics,  
Waterford IT.  
(kmurphy@wit.ie)

Autumn Semester, 2021

#### RESOURCE OUTLINE LABEL

- Problem statement
- Sample run

# Markov chain approach

## Model


- **State:**  $i$ ,  $i = 0, \dots, n$ , where  $i$  is number of collected coupons.

*Have  $i$  of the  $n$  available coupons, so  $(n - i)$  coupons are unseen.*

- Initial state is 0. State  $n$  is terminal.

- **Stage:** Number of coupons purchased.

*How long does it take to travel from 0 to  $n$ ?*



# Markov chain approach

## Model


- **State:**  $i, i = 0, \dots, n$ , where  $i$  is number of collected coupons.  
*Have  $i$  of the  $n$  available coupons, so  $(n - i)$  coupons are unseen.*
- Initial state is  $0$ . State  $n$  is terminal.
- **Stage:** Number of coupons purchased.  
*How long does it take to travel from  $0$  to  $n$ ?*



# Markov chain approach

## Model


- **State:**  $i, i = 0, \dots, n$ , where  $i$  is number of collected coupons.  
Have  $i$  of the  $n$  available coupons, so  $(n - i)$  coupons are unseen.
- Initial state is  $0$ . State  $n$  is terminal.
- **Stage:** Number of coupons purchased.  
How long does it take to travel from  $0$  to  $n$ ?




# Markov chain approach

## Model


- **State:**  $i, i = 0, \dots, n$ , where  $i$  is number of collected coupons.  
Have  $i$  of the  $n$  available coupons, so  $(n - i)$  coupons are unseen.
- Initial state is  $0$ . State  $n$  is terminal.
- **Stage:** Number of coupons purchased.  
How long does it take to travel from  $0$  to  $n$ ?




## Viewing our first simulation run as a Markov chain ...




count: 0 found: collected: set()




## Viewing our first simulation run as a Markov chain ...




count:	0	found:	collected: set()
count:	1	found: {2}	collected: {2}



## Viewing our first simulation run as a Markov chain ...




count:	0	found:		collected:	set()
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}







## Viewing our first simulation run as a Markov chain ...




count:	0	found:		collected:	set()
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}
count:	3	found:	{0}	collected:	{0, 2, 3}




## Viewing our first simulation run as a Markov chain ...




count:	0	found:		collected:	set()
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}
count:	3	found:	{0}	collected:	{0, 2, 3}
count:	4	found:	{2}	collected:	{0, 2, 3}




# Viewing our first simulation run as a Markov chain ...




count:	0	found:		collected:	set()
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}
count:	3	found:	{0}	collected:	{0, 2, 3}
count:	4	found:	{2}	collected:	{0, 2, 3}
count:	5	found:	{2}	collected:	{0, 2, 3}




## Viewing our first simulation run as a Markov chain ...




count:	0	found:		collected:	set()
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}
count:	3	found:	{0}	collected:	{0, 2, 3}
count:	4	found:	{2}	collected:	{0, 2, 3}
count:	5	found:	{2}	collected:	{0, 2, 3}
count:	6	found:	{3}	collected:	{0, 2, 3}




## Viewing our first simulation run as a Markov chain ...




count:	0	found:	collected:	set()	
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}
count:	3	found:	{0}	collected:	{0, 2, 3}
count:	4	found:	{2}	collected:	{0, 2, 3}
count:	5	found:	{2}	collected:	{0, 2, 3}
count:	6	found:	{3}	collected:	{0, 2, 3}
count:	7	found:	{0}	collected:	{0, 2, 3}




## Viewing our first simulation run as a Markov chain ...




count:	0	found:	collected:	set()
count:	1	found:	collected:	{2}
count:	2	found:	collected:	{2, 3}
count:	3	found:	collected:	{0, 2, 3}
count:	4	found:	collected:	{0, 2, 3}
count:	5	found:	collected:	{0, 2, 3}
count:	6	found:	collected:	{0, 2, 3}
count:	7	found:	collected:	{0, 2, 3}
count:	8	found:	collected:	{0, 2, 3}




## Viewing our first simulation run as a Markov chain ...




count:	0	found:	collected:	set()
count:	1	found:	collected:	{2}
count:	2	found:	collected:	{2, 3}
count:	3	found:	collected:	{0, 2, 3}
count:	4	found:	collected:	{0, 2, 3}
count:	5	found:	collected:	{0, 2, 3}
count:	6	found:	collected:	{0, 2, 3}
count:	7	found:	collected:	{0, 2, 3}
count:	8	found:	collected:	{0, 2, 3}
count:	9	found:	collected:	{0, 2, 3}



## Viewing our first simulation run as a Markov chain ...



count:	0	found:		collected:	set()
count:	1	found:	{2}	collected:	{2}
count:	2	found:	{3}	collected:	{2, 3}
count:	3	found:	{0}	collected:	{0, 2, 3}
count:	4	found:	{2}	collected:	{0, 2, 3}
count:	5	found:	{2}	collected:	{0, 2, 3}
count:	6	found:	{3}	collected:	{0, 2, 3}
count:	7	found:	{0}	collected:	{0, 2, 3}
count:	8	found:	{0}	collected:	{0, 2, 3}
count:	9	found:	{2}	collected:	{0, 2, 3}
count:	10	found:	{1}	collected:	{0, 1, 2, 3}



Number of stages needed = 10