



Setting up Julia working environment

VS Code






Setup VS-Code


- Add Julia plugin



- Start Julia REPL (terminal)



Julia REPL (demonstration)



Julia REPL (read-eval-print loop)

Terminal or prompt pasting

- Julia terminal
computation space, execute scripts...

```
[ Info: Precompiling VSCodeServer [9f5989ce-84fe-42d4-91ec-6a7a8d53ed0f]  
julia> |
```

-] package manager
add/update packages

```
[ Info: Precompiling VSCodeServer [9f5989ce-84fe-42d4-91ec-6a7a8d53ed0f]  
(@v1.9) pkg> |
```

- ; shell
Changing directories

```
[ Info: Precompiling VSCodeServer [9f5989ce-84fe-42d4-91ec-6a7a8d53ed0f]  
shell> |
```

- ? help
provide help with functions

```
help?> minimum  
search: minimum minimum! DimensionMismatch  
  
minimum(f, itr; [init])  
  
Return the smallest result of calling function f on each element of itr.
```

- Backspace
back to julia terminal

*Note that on Windows the shell is bugged,
navigate through directory using terminal → `cd("path")`, `pwd()`*

“for” loops

- Open new Julia file and reproduce the following lines of codes

```
1  # example of for loops
2
3  n_iteration = 10
4  total      = 0.0
5
6  for i=1:n_iteration
7      total = total + 1
8  end
9
10 print("total = $total\n")
11
12 # \n -> line break
13 # \t -> tabulation
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
julia> total      = 0.0
0.0
```

```
julia>
```

```
julia> for i=1:n_iteration
        total = total + 1
        end
```

```
julia>
```


```
julia> print("total = $total\n")
total = 10.0
```

```
julia>
```

- Paste it in the terminal

“for” loops

- CTRL + L to clear the terminal
- Save the file as “meaningful_name.jl”
- Execute the scripts using “include”



A screenshot of a Julia REPL terminal window. The window has a dark background and a light-colored text area. At the top, there are tabs for "PROBLEMS", "OUTPUT", "DEBUG CONSOLE", "TERMINAL", and "PORTS". The "TERMINAL" tab is selected and highlighted with a blue underline. Below the tabs, the text "julia> include("w1_for_loops_example.jl")" is displayed in a green monospace font. A cursor is visible at the end of the line.

```
julia> include("w1_for_loops_example.jl")
```

First bug?

```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
julia> include("w1_for_loops_example.jl")
[ Warning: Assignment to `total` in soft scope is ambiguous because a global variable by the same name exists: `total` will be treated as a new local. Disambiguate by using `local total` to suppress this warning or `global total` to assign to the existing global variable.
] @ E:\Nextcloud\RESEARCH\USB_DATA\7_teaching\2023_Mainz\2023_GeoStatistics2_09.065.978\w1_for_loops_example.jl:7
ERROR: UndefVarError: `total` not defined
Stacktrace:
 [1] top-level scope
      @ E:\Nextcloud\RESEARCH\USB_DATA\7_teaching\2023_Mainz\2023_GeoStatistics2_09.065.978\w1_for_loops_example.jl:7
julia> 
```

- Here Julia does not know the “scope” of the variable `total`.
- Scope can be seen as the region of a code where the variable is visible/exists
- The main file here can be thought as an “open space”

→ The right way to solve the issue is to work in a “closed space” i.e. using functions!

```
1  # example of for loops
2
3  n_iteration = 10
4  total      = 0.0
5
6  for i=1:n_iteration
7      total = total + 1
8  end
9
10 print("total = $total\n")
11
12 # \n -> line break
13 # \t -> tabulation
```


Functions

- Take one or multiple entries as arguments
- Return one or multiple variables

```
terminal  Help
Welcome  W1_demonstration.jl  W1_for_loops_example_function.jl X
W1_for_loops_example_function.jl > ...
1  # example of for loops
2
3
4  function sum_iteration(n_iteration)
5      total = 0.0
6
7      for i=1:n_iteration
8          total = total + 1
9      end
10         total = total + 1
11     return total
12 end
13
14 total = sum_iteration(n_iteration)
15
16
17 print("total = $total\n")
18
19 # \n -> line break
20 # \t -> tabulation
```

```
julia> include("W1_for_loops_example_function.jl")
total = 10.0
```

```
julia> |
```



Solve the “scope” problem

Function file

- When developing a code it is useful to put the functions in other files to keep the main file readable
- Create a “functions_file.jl” and copy/paste the For loop example in it
- Add comment before the function definition as


```
1  """
2  |    sum_iteration(n_iteration)
3  |    where n_iteration is an integer
4  |    return sum(n_iteration)
5  |    """
```

```
W1_functions_file.jl > ...
1  """
2  |    test function sum_iteration(n_iteration)
3  |    where n_iteration is an integer
4  |    return sum(n_iteration)
5  |    """
6  function sum_iteration(n_iteration)
7      total = 0.0
8
9      for i=1:n_iteration
10         total = total + 1
11     end
12
13     return total
14 end
15
```

1. The “""" mark the start and ending of the comment
2. The first lines should be the function first lines copied and pasted
3. Subsequent lines describe the input/output and role of the function


Forgot what the function(s) does?

- Open the help in the REPL (terminal) with ?



```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
help?> 
```

- Type `sum_iteration` and enter (or `sum_i` +DOUBLE TAB)



```
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
help?> sum_iteration
search: sum_iteration

    sum_iteration(n_iteration)
      where n_iteration is an integer
      return sum(n_iteration)

julia> 
```



This displays the comment of your function. Very useful:

- When your code becomes big (many files)
- When you did not use your code for a while
- When you share your code!

“while” loops

- Generalization of the for loop: loops until the looping condition is broken
- Reproduce the following code in the functions_file.jl (after sum_iteration function)
- In the REPL include “functions_file.jl” and define M and n_iteration then call the function

```
julia> include("w1_functions_file.jl")
exercise_3


julia> n_iteration = 10
10

julia> M = 50
50

julia> M = while
while      while_loop
julia> M = while_loop(n_iteration,M)
```

Or using default values

```
julia> M = while_loop()
```



```
23 """
24 while_loop(n_iteration,M)
25
26     where n_iteration is an integer, M is an integer
27     return M + sum( (n_iteration-1)*10 )
28 """
29 function while_loop(n_iteration=10,M=50)
30
31     i=1
32     while i < n_iteration
33         M += 10
34         i -= 1
35         print("i = $i, M = $M\n")
36     end
37
38     return M
39 end
```

Note that default values can be defined as such:

Will this program stop or run forever?

“if elseif else” statement

- Check the state of a condition (true or false) and perform different computation depending on the case
- Reproduce code in “functions_file.jl”
- And test it
(re-include “W1_functions_file.jl”)

```
21
22 M = check_M(M)
23
24 print("check_M(M) = $M\n")
25
```



```
37
38 """
39     check_M(M)
40     where...
41 """
42
43 function check_M(M)
44
45     if M < 10
46         M += 25
47     elseif M == 10
48         M = M^2
49     else
50         M = 0
51     end
52
53     return M
54 end
```

Arrays (Vector)

- There is several different ways to declare a Vector in Julia for instance:

```
julia> array = [0,1,2,3,4]
5-element Vector{Int64}:
 0
 1
 2
 3
 4
```



This creates and fill the Vector with given values

```
julia> zeros(5)
5-element Vector{Float64}:
 0.0
 0.0
 0.0
 0.0
 0.0
```



This creates a Vector of length 5 and fill it with zeros

```
julia> zeros{Int64}(5)
5-element Vector{Int64}:
 0
 0
 0
 0
 0
```



The type can be specified

Note: you can also use:
`ones()`

Access/Modify Arrays (Vector)

- Access

```
julia> array = [0,1,2,3,4]
5-element Vector{Int64}:
 0
 1
 2
 3
 4
```

```
julia> array[1]
0
```

By position

```
julia> array[1:4]
4-element Vector{Int64}:
 0
 1
 2
 3
```

Using range

```
julia> array[[1,2,3,4]]
4-element Vector{Int64}:
 0
 1
 2
 3
```

Using vector of positions

- Modify

```
julia> array[1] = 4
4
```

```
julia> array[1:4] .= 4
4-element view(::Vector{Int64}, 1:4) with eltype Int64:
 4
 4
 4
 4
```


Don't forget the dot
(pointwise)

```
julia> array[[1,2,3,4]] .= 4
4-element view(::Vector{Int64}, [1, 2, 3, 4]) with eltype Int64:
 4
 4
 4
 4
```

Arrays (Matrix)


- There is several different ways to declare an array in Julia for instance:

```
julia> array2D = [0 1 2 3 4; 5 6 7 8 9]
2x5 Matrix{Int64}:
 0  1  2  3  4
 5  6  7  8  9
```




This creates and fill the matrix with given values

```
julia> zeros(2,5)
2x5 Matrix{Float64}:
 0.0  0.0  0.0  0.0  0.0
 0.0  0.0  0.0  0.0  0.0
```



This creates a Matrix of 2 lines and 5 columns filled with 0.0

```
julia> zeros(Float64,2,5)
2x5 Matrix{Float64}:
 0.0  0.0  0.0  0.0  0.0
 0.0  0.0  0.0  0.0  0.0
```



As before the type can be specified

Access/Modify Arrays (Matrix)

- Access

```
julia> array2D = [0 1 2 3 4; 5 6 7 8 9]
2x5 Matrix{Int64}:
 0  1  2  3  4
 5  6  7  8  9
```

- Modify

2D arrays are row major

```
julia> array2D[2,4]
8
```

By position

```
julia> array2D[2,4] = 4
4
```

```
julia> array2D[1,2:4]
3-element Vector{Int64}:
 1
 2
 3
```

Using range

```
julia> array2D[1,2:4] .= 4
3-element view(::Matrix{Int64}, 1, 2:4) with eltype Int64:
 4
 4
 4
```

Don't forget the dot
(pointwise)

```
julia> array2D[1,[2,3,4]]
3-element Vector{Int64}:
 1
 2
 3
```

Using vector of positions

```
julia> array2D[1,[2,3,4]] .= 4
3-element view(::Matrix{Int64}, 1, [2, 3, 4]) with eltype Int64:
 4
 4
 4
```

Why does type matters?

- There is three main types in Julia: Int64, Float64 and String
- To find the type of any variable use “typeof”
- Using some of the previous array definition, this gives:

```
julia> array2D = [0 1 2 3 4; 5 6 7 8 9]
2x5 Matrix{Int64}:
 0  1  2  3  4
 5  6  7  8  9

julia> typeof(array2D)
Matrix{Int64} (alias for Array{Int64, 2})
```

```
julia> array = [0 1 2 3 4 5]
1x6 Matrix{Int64}:
 0  1  2  3  4  5

julia> typeof(array)
Matrix{Int64} (alias for Array{Int64, 2})
```

```
julia> array = zeros(Float64,2,5)
2x5 Matrix{Float64}:
 0.0  0.0  0.0  0.0  0.0
 0.0  0.0  0.0  0.0  0.0

julia> typeof(array)
Matrix{Float64} (alias for Array{Float64, 2})
```

```
julia> array = [0, 1, 2, 3, 4, 5]
6-element Vector{Int64}:
 0
 1
 2
 3
 4
 5

julia> typeof(array)
Vector{Int64} (alias for Array{Int64, 1})
```


```
julia> i = 1
1

julia> typeof(i)
Int64
```

Arrays with push!

- Another way to create array is to declare it empty and push elements to it

```
julia> r = []  
Any[]  
  
julia> push!(r,1.0)  
1-element Vector{Any}:  
 1.0  
  
julia> push!(r,2.0)  
2-element Vector{Any}:  
 1.0  
 2.0  
  
julia> push!(r,3.0)  
3-element Vector{Any}:  
 1.0  
 2.0  
 3.0
```



Type Any
(can contain anything)

The type can be enforced too:

```
julia> r = Int64[]  
Int64[]  
  
julia> push!(r,1.0)  
1-element Vector{Int64}:  
 1  
  
julia> push!(r,2.0)  
2-element Vector{Int64}:  
 1  
 2  
  
julia> push!(r,3)  
3-element Vector{Int64}:  
 1  
 2  
 3
```



Note that even if a Float is
pushed, an integer is stored

This can also be done for
Vectors (and Matrix)

```
julia> r = []  
Any[]  
  
julia> push!(r,[1,2,3])  
1-element Vector{Any}:  
 [1, 2, 3]  
  
julia> push!(r,[1,2,3])  
2-element Vector{Any}:  
 [1, 2, 3]  
 [1, 2, 3]
```



And converted to matrix using
mapreduce function

```
julia> tmat = mapreduce(permutedims, vcat, r)  
2x3 Matrix{Int64}:  
 1 2 3  
 1 2 3
```

Working with arrays

- Creates 2 arrays as follow:

```
julia> array1 = [4,3,2,1]
4-element Vector{Int64}:
 4
 3
 2
 1
```



Here no comma is used, the Vector is created using Integers

```
julia> array2 = [4,3,2,1.0]
4-element Vector{Float64}:
 4.0
 3.0
 2.0
 1.0
```



Here a single comma is used, and the Vector is created using Float

- Go through the values of the array using a “for” loop

```
1 for i=1:length(array1)
2     val = array1[i]
3
4     # display value of array at position i, and the value of array at position val
5     print("val: $(val) array1[val]: $(array1[val])\n")
6 end
```

What happens if we use array2 instead?

Working with arrays

- Position in an array has to be accessed with integers

```
julia> for i=1:length(array2)
    val = array2[i]

    # display value of array at position i, and the value of array at position val
    print("val: $(val) array1[val]: $(array1[val])\n")
end
ERROR: ArgumentError: invalid index: 4.0 of type Float64
Stacktrace:
 [1] to_index(i::Float64)
   @ Base .\indices.jl:300
 [2] to_index(A::Vector{Int64}, i::Float64)
   @ Base .\indices.jl:277
 [3] _to_indices1(A::Vector{Int64}, inds::Tuple{Base.OneTo{Int64}}, I1::Float64)
   @ Base .\indices.jl:359
 [4] to_indices
   @ .\indices.jl:354 [inlined]
 [5] to_indices
   @ .\indices.jl:345 [inlined]
 [6] getindex(A::Vector{Int64}, I::Float64)
   @ Base .\abstractarray.jl:1296
 [7] top-level scope
   @ .\REPL[60]:5
```

- Luckily Floats (including `Vector{Float64}`) can be converted to integer as:

```
julia> array2 = Int64.(array2)
4-element Vector{Int64}:
 4
 3
 2
 1
```

First Julia plot

- First add a plotting package “Plots”

] add Plots

“]” opens the package manager

```
(@v1.9) pkg> add Plots  
Resolving package versions...
```


It can take a few minutes as other default packages are updated

- Create a plot_square function (still in functions_file.jl)

```
57  
58      """  
59      plot_square()  
60      |    simply plots the square function between -10 and 10  
61      |  
62      """  
63      function plot_square()  
64      |  
65      |    x = -10:0.1:10  
66      |    y = x.^2  
67      |  
68      |    plot(x,y)  
69      end  
70
```

First Julia plot

- Execute “my_code.jl”
- In the REPL (terminal) type: `plot_square()`




→ The figures are displayed within VS code in a dedicated window

Add title and label

- Modify the function as

```
"""  
plot_square()  
    simply plots the square function between -10 and 10  
""">  
function plot_square()  
  
    x = -10:0.1:10  
    y = x.^2  
  
    plot(x,y)  
    title!("Square function")  
    xlabel!("x")  
    ylabel!("x^2")  
end
```



→ Here the “!” means that the title, x- and y-labels will be added to previously declared plot.

Adding another curve to existing plot

- Modify the function as

```
"""
    plot_square()
    simply plots the square function between -10 and 10
"""

function plot_square()

    x = -10:0.1:10
    y = x.^2
    yp = x.^3

    plot(x,y)
    plot(x,yp)
    title!("Square function")
    xlabel!("x")
    ylabel!("x^2")
end
```




What happens here?

Adding another curve to existing plot

- The “!” is also used to add curves to an existing plot

```
"""  
    plot_square()  
    simply plots the square function between -10 and 10  
""">  
function plot_square()  
  
    x = -10:0.1:10  
    y = x.^2  
    yp = x.^3  
  
    plot(x,y)  
    plot!(x,yp)  
    title!("Square function")  
    xlabel!("x")  
    ylabel!("x^2")  
end
```



Exercise 1a

Assume we have an initial amount of money on the bank ($M=1000$) and each year we save some money ($dM=100$)

1. What will the amount of money be after 25 years? Create Julia function for this.
2. Plot the total amount of money (M) versus time in years.

Example of solution

```
exercice_1(M, dM, n_years)
    Assumes we have an initial amount of money on the bank (M=1000)
    and each year we save some money (dM=100)
    M is starting_money
    dM is yearly_savings
    n_years is the number fo years of savings
```

```
function exercice_1(M, dM, n_years)
```

```
    Mtotal = zeros(n_years)
```

```
    for i=1:n_years
```

```
        M = M + dM;
```

```
        Mtotal[i] = M
```

```
    end
```

```
    plot(Mtotal)
```

```
    title!("Money trend in the bank")
```

```
    xlabel!("time (years)")
```

```
    ylabel!("money \$")
```

```
end
```

```
help?> exercice_1
search: exercice_1
```

```
exercice_1(M, dM, n_years)
```

```
    Assumes we have an initial amount of money on the bank (M=1000)
    and each year we save some money (dM=100)
```


```
    M is starting_money
```

```
    dM is yearly_savings
```

```
    n_years is the number fo years of savings
```

Julia Plots (7/7) X

Money trend in the bank



```
julia> include("w1_functions_file.jl")
exercice_1
```

```
julia> exercice_1(1000, 100,25)
```

Exercise 1b

Most banks give an interest on the money you have and pay that at the end of the year. Let's assume that the interest rate is 10%.

1. Duplicate the previous function and call it `exercice_1b`.
2. Modify the function to account for interest rate



Example of solution

```
"""
exercice_1b(M, dM, n_years, interest_rate)
    Assumes we have an initial amount of money on the bank (M=1000)
    and each year we save some money (dM=100)
    M is starting_money
    dM is yearly_savings
    n_years is the number fo years of savings
    interest_rate is the interest rate of the bank in in %
"""
function exercice_1b(M, dM, n_years, interest_rate)

    Mtotal = zeros(n_years)

    for i=1:n_years
        M = M + M*interest_rate/100
        M = M + dM;
        Mtotal[i] = M
    end

    plot(Mtotal)
    title!("Money trend in the bank \n (interested rate of $interest_rate %)")
    xlabel!("time (years)")
    ylabel!("money \$")
end
```



```
julia> include("w1_functions_file.jl")
exercice_1b

julia> exercice_1b(1000, 100,25, 10)
```

Exercise 1c

1. Explore plotting options (Plots.jl)

use online doc:


<https://docs.juliaplots.org/latest/tutorial/>

1. Improve “exercise_1b()” -> “exercise_1c()”

1. Change colors of the curve
2. Display points on top of the curve function (scatter)

Example of solution

```
129 """
130 exercice_1c(M, dM, n_years, interest_rate)
131     Assumes we have an initial amount of money on the bank (M=1000)
132     and each year we save some money (dM=100)
133     M is starting_money
134     dM is yearly_savings
135     n_years is the number fo years of savings
136     interest_rate is the interest rate of the bank in in %
137 """
138 function exercice_1c(M, dM, n_years, interest_rate)
139
140     Mtotal = zeros(n_years)
141
142     for i=1:n_years
143         M = M + M*interest_rate/100
144         M = M + dM;
145         Mtotal[i] = M
146     end
147
148     plot(Mtotal, lc=:black, lw=2)
149     scatter!(Mtotal, lc=:red, ms=10, ma=0.8)
150     title!("Money trend in the bank \n (interested rate of $interest_rate %)")
151     xlabel!("time (years)")
152     ylabel!("money \$")
153 end
```



Save the plot to a file as:

```
julia> savefig("save_figure_test.png")
```

(The file is saved in the working directory)