

## Lab 13: Shortest Path

Lecture date 6/1/2016  
Due date 7/6/2016 11:59 PM

In this lab, we will implement Dijkstra's algorithm for finding the shortest path. When a graph structure (i.e. a set of nodes and edges) is given, your program prints the shortest path as a result of running Dijkstra's algorithm. You may want to use a priority queue to find the node with the smallest distance from the source node.

### 1. Input


Read a set of vertices from the first line and a set of edges from the second line of the given input file. Each line is described below. You may assume that your node is represented by any integer.

- Vertices are given in the first line. Each vertex is separated by a space.
- Edges are given in the second line. Each edge is represented by a pair of vertices and its weight. For example, "1-3-4" represents an edge from the vertex 1 to 3 with the weight value of 4.

An exemplary input file is given below with the corresponding graph for your reference.

Input.txt


```
1 2 3 4 5 6 7
1-2-2 1-4-1 2-5-10 2-4-3 3-1-4 3-6-5 4-3-2 4-6-8
4-7-4 4-5-2 5-7-6 7-6-1
```



### 2. Data structure

#### (1) Data structure for the graph

You can use an adjacency matrix to store your graph information as we discussed in class. An example is shown below.



#### (2) Data structure for nodes in priority queue

```
struct Node {
    int vertex;
    int priority;
}
```

### 3. Program description

- name : p11.c
- input : an input file name is given as a command line argument. See the example in "1. input" .
- output : the shortest path (for the given graph in input) in the standard output

Submit to the course website (<https://portal.hanyang.ac.kr>) your source code and a written report. Your report should include the description of your own implementation.