

4. The Letter Carrier's Rounds

For an electronic mail application you are to describe the SMTP-based communication that takes place between pairs of MTAs. The sender's User Agent gives a formatted message to the sending Message Transfer Agent (MTA). The sending MTA communicates with the receiving MTA using the Simple Mail Transfer Protocol (SMTP). The receiving MTA delivers mail to the receiver's User Agent. After a communication link is initialized, the sending MTA transmits command lines, one at a time, to the receiving MTA, which returns a three-digit coded response after each command is processed. The sender commands are shown below in the order sent for each message. There is more than one RCPT TO line when the same message is sent to several users at the same MTA. A message to users at different MTAs requires separate SMTP sessions.

HELO <i>myname</i>	Identifies the sender to the receiver (yes, there is only one L).
MAIL FROM:< <i>sender</i> >	Identifies the message sender
RCPT TO:< <i>user</i> >	Identifies one recipient of the message
DATA	Followed by an arbitrary number of lines of text comprising the message body, ending with a line containing a period in column one.
QUIT	Terminates the communication.

The following response codes are sent by the receiving MTA:

- 221 Closing connection (after QUIT)
- 250 Action was okay (after MAIL FROM and RCPT TO specifying an acceptable user, or completion of a message)
- 354 Start sending mail (after DATA)
- 550 Action not taken; no such user here (after RCPT TO with unknown user)

Input

The input contains descriptions of MTAs followed by an arbitrary number of messages. Each MTA description begins with the MTA designation and its name (1 to 15 alphanumeric characters). Following the MTA name is the number of users that receive mail at that MTA and a list of the users (1 to 15 alphanumeric characters each). The MTA description is terminated by an asterisk in column 1. Each message begins with the sending user's name and is followed by a list of recipient identifiers. Each identifier has the form *user@mtaname*. The message (each line containing no more than 72 characters) begins and terminates with an asterisk in column 1. A line with an asterisk in column 1 instead of a sender and recipient list indicates the end of the entire input.

Output

For each message, show the communication between the sending and receiving MTAs. Every MTA mentioned in a message is a valid MTA; however, message recipients may not exist at the destination MTA. The receiving MTA rejects mail for those users by responding to the RCPT TO command with the 550 code. A rejection will not affect delivery to authorized users at the same MTA. If there is not at least one authorized recipient at a particular MTA, the DATA is not sent. Only one SMTP session is used to send a message to users at a particular MTA. For example, a message to 5 users at the same MTA will have only one SMTP session. Also a message is addressed to the same user only once. The order in which receiving MTAs are contacted by the sender is unspecified. As shown in the sample output, prefix the communication with the communicating MTA names, and indent each communication line.

Sample Input

```
MTA London 4 Fiona Paul Heather Nevil
MTA SanFrancisco 3 Mario Luigi Shariff
MTA Paris 3 Jacque Suzanne Maurice
MTA HongKong 3 Chen Jeng Hee
MTA MexicoCity 4 Conrado Estella Eva Raul
MTA Cairo 3 Hamdy Tarik Misa
*
Hamdy@Cairo Conrado@MexicoCity Shariff@SanFrancisco Lisa@MexicoCity
*
Congratulations on your efforts !!
--Hamdy
*
Fiona@London Chen@HongKong Natasha@Paris
*
Thanks for the report!  --Fiona
*
*
```

Sample Output

```
Connection between Cairo and MexicoCity
  HELO Cairo
  250
  MAIL FROM:<Hamdy@Cairo>
  250
  RCPT TO:<Conrado@MexicoCity>
  250
  RCPT TO:<Lisa@MexicoCity>
  550
  DATA
  354
  Congratulations on your efforts !!
  --Hamdy
  .
  250
  QUIT
  221
Connection between Cairo and SanFrancisco
  HELO Cairo
  250
  MAIL FROM:<Hamdy@Cairo>
  250
  RCPT TO:<Shariff@SanFrancisco>
  250
  DATA
  354
  Congratulations on your efforts !!
  --Hamdy
  .
  250
  QUIT
  221
Connection between London and HongKong
  HELO London
  250
  MAIL FROM:<Fiona@London>
  250
  RCPT TO:<Chen@HongKong>
  250
  DATA
  354
  Thanks for the report!  --Fiona
  .
  250
  QUIT
  221
Connection between London and Paris
  HELO London
  250
  MAIL FROM:<Fiona@London>
  250
  RCPT TO:<Natasha@Paris>
  550
  QUIT
  221
```