

SAVETHA SCHOOL OF ENGINEERING

CSA17- ARTIFICIAL INTELLIGENCE - CONCEPT MAP

INDEX

D. INTRODUCTION

1. AI problems
2. Foundation of AI and history of AI
3. Intelligent Agents
4. Agents and Environments
 - a. Agent Function
 - b. Agent Program
 - c. Agent Properties
5. Concept of Rationality
 - a. Nature of environments
 - b. Properties of Task Environment
6. Structure of Agents
 - a. Simple Reflex
 - b. Model Based
 - c. Goal Based
 - d. Utility Based
7. Problem Solving Agents
 - a. Problem formulation
 - b. Toy Problem Vs Real World Problem
 - c. Examples: 8-Puzzle, 8-Queens & Water Jug Problem
8. Searching for solutions
9. Uninformed search strategies
 - a. BFS
 - b. DFS
 - c. Uniform Cost Search
10. Search with partial information
 - a. Sensor less Problems
 - b. Contingency Problems
 - c. Exploration Problems

II) SEARCHING TECHNIQUES

1. Informed Search Strategies
 - a. Best First Search
 - b. Greedy best first search
 - c. A* search
 - d. Heuristic functions- optimization problems
2. Local search algorithms and optimization problems
 - a. Hill Climbing
 - b. Simulated Annealing
 - c. Genetic Algorithms with Optimization
3. Online search agent
 - a. Offline Search Agent
 - b. Online Search Agent
4. Constraint Satisfaction Problem
 - a. Map Coloring
 - b. Cryptarithmic
 - c. Real world CSP
 - d. 4-Queens
5. Game Playing: Adversarial search
 - a. Introduction
 - b. Tic - Tac - Toe
 - c. Minimax- algorithm
 - d. Alpha - Beta pruning
6. Evaluation functions

III) KNOWLEDGE AND REASONING

1. Logical Agents
 - a. Representation and Reasoning
 - b. Two Generic Function
 - c. Knowledge Based Agents
2. Propositional logic
 - a. Atomic Sentence
 - b. Complex Sentence
 - c. Entailment and Derivation
 - d. Soundness and Completeness
3. Reasoning patterns in propositional logic
 - a. Proof by Deduction
4. First order logic
 - a. Basic Elements
 - b. Steps for Knowledge Engineering in FOL
 - c. Examples - Wumpus World
5. Inference in first order logic
 - a. Universal Quantifier
 - b. Existential Quantifier
6. Propositional Vs. first order inference
 - o unification & lifts
 - o forward chaining -
 - o backward chaining -
 - o Resolution.

IV) LEARNING

1. Learning from Observation
 - a. Learning Agents
 - b. Types of Learning
2. Inductive learning
 - a. Definition
 - b. Examples
3. Decision Trees
 - a. Definition & Attributes
 - b. Training Samples and Applications
4. Explanation based learning
 - a. Definition
 - b. Diagram
5. Statistical Learning methods
 - a. Bayes Rule
 - b. Examples - Candy Flavor Problem
6. Learning with complete data
 - a. Likelihood
 - b. Max Likelihood
7. Hidden variables
 - a. Definition
 - b. Examples of Hidden variables
8. Neural Networks
 - a. Neurons
 - b. Typical Neurons with Activation Functions
 - c. Types of NN
9. Kernel machines
10. Reinforcement Learning.

V) SEARCH ENGINE OPTIMIZATION

1. Different Search Engine
2. Evaluating Search Engine
 - o Measures for Search Engine
 - o Measuring user happiness
3. Search techniques
 - o Phrase Searching
 - o Wildcard Searching
 - o Boolean Searching
4. Search Engine Optimization
5. Website Domain
6. Design and Layout
7. Keyword Optimization
8. Meta tag Optimization
9. Title tag Optimization
10. Anchor tag Optimization
11. XHTML Verification for Websites.

WHAT IS AI ?

- * Thinking humanly - cognitive modelling approach
- * Thinking rationally - laws of thought approach
- * Acting humanly - Turing test approach
- * Acting Rationally - Rational agent approach


AI PROBLEMS :

- Psychology → Neuroscience
- Mathematics → Computer Engineering
- Economics → NLP
- Linguistics → Knowledge representation
- Philosophy → Speech processing
- Planning → Control theory & cybernetics
- Robotics

FOUNDATION & HISTORY OF AI :

- 1943-1955 — The gestation of AI
- 1956 — Birth of AI
- 1952-1969 — Early enthusiasm, great expectations
- 1966-1973 — A decade of reality
- 1969-1979 — Knowledge based systems (The key to power)
- 1980-present — AI becomes an industry
- 1986-present — Return of Neural networks
- 1987-present — AI adopts scientific method
- 1995-present — Emergence of intelligent Agents
- 2001-present — Availability of very large Datasets

INTELLIGENT AGENT :



- Agent function
- Agent Program
- Agent Properties

CONCEPT OF RATIONALITY :


- * Nature of Environment -
- Performance Measures
- Nature of Environment
- Actuators
- Sensors

* Properties of Task environment -


Agent type	Performance Measure (P)	Environment (E)	Actuators (A)	Sensors (S)
Path-Picking Robot	% of parts in correct bins	Conveyor belt with parts; bins	Jointed arm & hand	Camera, joint-angle sensors
Interactive English Tutor	Student's score on test	Set of students, Testing agency	Display of exercises, suggestion, corrections	Keyboard, Entry

STRUCTURE OF AGENTS :-


* Simple - Reflex Agents




* Model-Based Reflex Agent



* Goal Based Agents




* Utility Based agents.




APPLICATIONS OF AGENTS


* Vacuum cleaner Agent -




* Path Picking Robot -




BEST-FIRST SEARCH :-



Greedily Best-First Search :-




INFORMED SEARCH STRATEGIES




A* Search :-

- $f(n) = g(n) + h(n)$
- $f(n)$ = estimated total cost from initial node to goal node
- $g(n)$ = cost from initial to current node
- $h(n)$ = estimated cost from current to goal node




Heuristic Function


Heuristic Function




LOCAL SEARCH ALGORITHMS :-




Simulated annealing (SA) :-



Genetic Algorithms



Online search agents



MAP COLOURING:-

Needs to satisfy set of constraints

Input:- 2D array graph $[V, V]$

$\rightarrow V \rightarrow$ no. of vertices

$\rightarrow V \rightarrow$ no. of adjacent matrix

$\rightarrow M \rightarrow$ integer M is maximum no. of colour.

Output:- Array colour "V" should have no. from 1 to m.




Australian Map

graph = $\{0, 1, 1, 1, 1, 1\}$
 $\{1, 1, 0, 1, 1, 0\}$
 $\{1, 1, 1, 0, 1, 1\}$
 $\{1, 1, 0, 1, 1, 0\}$

O/P:- solution exists

following assigned colours
1, 2, 3, 2

By coloring the vertices with colors, adjacent does not have same color.



CONSTRAINT SATISFACTION PROBLEM

CRYPTO ARITHMETIC PROBLEM:-

$\rightarrow$ For A $\rightarrow$ 2 assign
 $0 \rightarrow$ 9 Number

$\rightarrow$ Note: NO 2 Alphabet should have same number

Example:-

$$\begin{array}{r} D \\ + E \\ \hline \end{array} \quad \begin{array}{r} O=7 \\ E=5 \\ \hline 12 \end{array}$$

Value assumed

* BASE + BALL
 Both are same value

* GAMES

Need to get two digit number

B=7 L=5
 A=4 G=1
 E=8 M=9
 E=3

No value should have same number

Ques 2:-

* NOON

MOON

SOON

TUNE

YOUR

+ YOU
 HEART

What is the value of Tune?

What is the value of heart?

WORKING OF CAP:-

* send + More = Money

Initial state

$$\begin{array}{l} M=1, S=8(00)9 \\ O=0(00)1 \\ N=E(00) \quad E+1 \\ N+R>8 \\ E<>9 \end{array}$$

$$\begin{array}{l} N=3 \\ R=8(00)9 \\ 2+0=9 \end{array}$$

$$\begin{array}{l} 2+0=9 \\ N+R=10 \\ R=9 \\ S=8 \end{array}$$

$$\begin{array}{l} 2+0=10+Y \\ D=8+Y \\ D=8(00)9 \\ C1=1 \end{array}$$

$$\begin{array}{l} Y=0 \\ \text{conflict} \end{array}$$

$$\begin{array}{l} Y=1 \\ \text{conflict} \end{array}$$

REAL WORLD CSPs:-

* Assignment problems

-e.g. who teaches what class

* Timetabling problems

-e.g. which class is offered when and where?
 Transportation scheduling
 Factory scheduling.



4- QUEEN PROBLEM

Rule:- Queen can travel



$\rightarrow$ Row wise
 $\rightarrow$ column wise
 $\rightarrow$ diagonal wise

NOTE:- NO queen $\rightarrow$ should

$\rightarrow$ attack $\rightarrow$ each other



Final state:-



Goal:- All Queen should be placed

REAL-TIME APPLICATIONS

$\rightarrow$ Games which satisfies the set of constraints.


Example:- Monopoly Games

$\rightarrow$ Chess

$\rightarrow$ Electronic Banding

$\rightarrow$ Ludo

$\rightarrow$ Snake & Ladder




SEARCH VS GAMES

Search	Games
* NO adversary	* Adversary
* solution-path from start $\rightarrow$ goal	* solution is strategy
* Ex: path planning scheduling activities	* Ex: chess checkers.

TIC TAC TOE PROBLEM

- $\hookrightarrow$ Needs to satisfy set of constraints.
- $\hookrightarrow$ Game consists of Naughts and crosses (or) Xs and Os
- $\hookrightarrow$ 3X3 grid play
- $\hookrightarrow$ If 3 consecutive marks formed then the player who owns the move will win.

Example:-



GAME PLAYING


MINI-MAX ALGORITHM

perfect play for deterministic environments with perfect information

Max-position: largest successor
Min-position: smallest successor

Basic idea: choose move with highest minimax value

Example:-



- 2 player game
- $\rightarrow$ Player 1:- Min-thighest score
- $\rightarrow$ Player 2:- Max-lowest score

Properties:-

- performs a complete depth first exploration of the game tree
- optimal

Time complexity:-

$$O(b^d)$$

space complexity:- $O(bd)$

$\therefore$ b is branching factor
d is depth of tree.

ALPHA BETA PRUNING (α - β)


- $\hookrightarrow$ Needs to satisfy set of constraints
- $\hookrightarrow$ similar like Min Max
- $\hookrightarrow$ Reduce computation time.
- $\hookrightarrow$ cuts of branches in game tree.

Parameters:-

① Alpha :- Max value $-\infty$

② Beta :- Min value $+\infty$

Example:-



$\therefore$ Hence optimal value achieved.

un used nodes are deleted

Pruning

EVALUATION FUNCTIONS

- $\rightarrow$ Order the terminal states
- $\rightarrow$ computation must not take too long.
- $\rightarrow$ For non-terminal states $\rightarrow$ evaluation function should strongly correlated

Ideal function:-

returns the utility of the position.

In practice:- Typically weighted linear sum of features.

$$Eval(s) = w_1 f_1(s) + w_2 f_2(s) + \dots + w_n f_n(s)$$

Example:- chess game

$$f_1(s) = (\text{num white queens} - \text{num black queens}) \text{ etc.}$$

REAL TIME APPLICATIONS

Games

Single agent Games

Multi agent Games


pac-man

subway surfers

pubg

consta

koo



LOGIC AGENTS

Representation Reasoning

How are the things stored? How is the knowledge used?

Two Generic Functions



Knowledge Based Agents

Domain Specific Content

Inference Engine Knowledge Base

Domain Specific Content

KNOWLEDGE AND REASONING

Inference Engine

A Systems that applies logical rules to the knowledge base to deduce new stuff.

Initial state Operators Goal test

MURPUS WORLD

1,1	2,1	3,1	4,1
Struch	SB	Breeze	PIT
1,2	2,2	3,2	4,2
Struch	SB	Breeze	PIT
1,3	2,3	3,3	4,3
Struch	SB	Breeze	PIT
1,4	2,4	3,4	4,4
Struch	SB	Breeze	PIT

1,1	2,1	3,1	4,1
1,2	2,2	3,2	4,2
1,3	2,3	3,3	4,3
1,4	2,4	3,4	4,4

Final Solution

Performance Measures

- Gold + 1000
- Death - 1000

Environment

Squares adjacent to the Mumpus are strictly to the

Squares adjacent to the

PIT go Breeze kill Mumpus

If you are facing it

Bumping picks up the gold if in the same square

Actuators

Left turn, right turn

forward, release, shoot

Sensors

Breeze, Gitter and Small

Sticks

SITUATIONS

* Breeze in (1,2) and (2,1)

- No safe actions

* Small in (1,1)

- Cannot move

S

A

1	2	3	4
1,1	2,1	3,1	4,1
Struch	PIT	PIT	PIT
1,2	2,2	3,2	4,2
Struch	PIT	PIT	PIT
1,3	2,3	3,3	4,3
Struch	PIT	PIT	PIT
1,4	2,4	3,4	4,4
Struch	PIT	PIT	PIT

Constraints

1. Rooms consists of Pits, Mumpus, Struch, Gold

Breeze

2. Adjacent to Room

Mumpus -> Smelly

3. Adjacent to Room

PIT -> Breeze

4. Adjacent to Room

Gitter -> Gold

5. Reward -> +1000

6. Loss -> -1000

7. Each Iteration -> -1

8. Using Arrow -> -10

Real-Time Applications

* Five spaces game

* To locate of predetermined

number of placed

mines in the

shortest possible

time by clicking on safe

1	2	3	4	5	6	7	8	9	10
1,1	2,1	3,1	4,1	5,1	6,1	7,1	8,1	9,1	10,1
1,2	2,2	3,2	4,2	5,2	6,2	7,2	8,2	9,2	10,2
1,3	2,3	3,3	4,3	5,3	6,3	7,3	8,3	9,3	10,3
1,4	2,4	3,4	4,4	5,4	6,4	7,4	8,4	9,4	10,4
1,5	2,5	3,5	4,5	5,5	6,5	7,5	8,5	9,5	10,5
1,6	2,6	3,6	4,6	5,6	6,6	7,6	8,6	9,6	10,6
1,7	2,7	3,7	4,7	5,7	6,7	7,7	8,7	9,7	10,7
1,8	2,8	3,8	4,8	5,8	6,8	7,8	8,8	9,8	10,8
1,9	2,9	3,9	4,9	5,9	6,9	7,9	8,9	9,9	10,9
1,10	2,10	3,10	4,10	5,10	6,10	7,10	8,10	9,10	10,10

Propositional Logic

- Declarative statements with either true or false.

Atomic Sentences

Single Propositional Symbols

True = always true, False = always false

Complex Sentences

- Negation
- If S is a sentence,

[S] is a sentence

Conjunction

- If S₁ and S₂ are sentences,

[S₁ ∧ S₂] is a sentence

Disjunction

- If S₁ and S₂ are sentences,

[S₁ ∨ S₂] is a sentence

Implication

- If S₁ and S₂ are sentences,

[S₁ ⇒ S₂] is a sentence

Biconditional

- If S₁ and S₂ are sentences,

[S₁ ⇔ S₂] is a sentence

Mumps World Sentences

- * Let P_{ij} be true if there is a

Pit in [i, j]

- * Let B_{ij} be true if there is a breeze in [i, j]

Start: 7P_{1,1}
7B_{1,1}
B_{2,1}

- * Pits cause breezes in adjacent squares

B_{1,1} ⇔ (P_{1,2} ∨ B_{2,1})
B_{2,1} ⇔ (P_{1,1} ∨ P_{2,2} ∨ P_{3,1})

Entailment & Derivation

Entailment: KB ⊨ φ

No logically possible world where φ is false

True in every logically possible world

Derivation: KB ⊢ φ

- Valid inference steps

Soundness:

If KB ⊢ φ then KB ⊨ φ

Inference produces only real entailments

Completeness:

If KB ⊨ φ then KB ⊢ φ

Inference produces all entailments

Reasoning Patterns in Propositional Logic

Inference Rules

Reasoning Patterns

Modus Ponens
S₁ ⇒ S₂ and S₁
derive S₂

And-elimination
S₁ ∧ S₂ derive S₁

De Morgan's Law
7 (A ∧ B) = 7A ∨ 7B
7 (A ∨ B) = 7A ∧ 7B

And Elimination
A ∧ B
derive A

Modus Ponens
A ⇒ B, A
derive B

Proof By Deduction

S → strike, P → pit, B → breeze

Knowledge

Rule:
S₁: B_{2,2} ⇔ (P_{2,2} ∨ B_{2,3} ∨ P_{2,1})

Observation
S₂: 7B_{2,2}

Inferences
S₁, B₁ elimination

S₃: (B_{2,2} ⇒ (P_{2,2} ∨ B_{2,3} ∨ P_{2,1}))
(P_{2,2} ∨ B_{2,3} ∨ P_{2,1}) ⇒ B_{2,2}

S₃ and Elimination

S₄: ((P_{2,2} ∨ B_{2,3} ∨ P_{2,1}) ⇒ B_{2,2})

Contradiction
S₅: (7B_{2,2} ⇒ 7(P_{2,2} ∨ B_{2,3} ∨ P_{2,1}))

S₂, S₆, MP
S₆: 7(P_{2,2} ∨ B_{2,3} ∨ P_{2,1})

S₆ De Morgan's Law

S₇: 7P_{2,2} ∧ 7P_{2,3} ∧ 7P_{2,1}

REAL-TIME APPLICATIONS

Our Door Sensors

CRUISE
Four BTL
Radar only
Noilly Dan

Good Climate

Match Condition


Bad

Match Condition


Learning from observation:

- * Learning agents
- * Types of Learning.

Learning agents:
Performance Standard



Types of learning:



Inductive learning:

Information provided by feedback

Instance space X: Set of all possible objects described by attributes.


Target Function: Mapping from attributes to Target feature.

(Often called labels)

Hypothesis space H: Set of all classification rules h_i , we allow

Training data D: set of instances labeled with target feature


Food	Chat	Fast	Price	Bar	BigTip
Great	yes	yes	normal	no	yes
Great	no	yes	normal	no	yes
Mediocre	yes	no	high	no	no
Great	yes	yes	normal	yes	yes



Decision Tree:

Input → Set of attributes
Output → returns a decision.

Example:



- * Each Node Test as attribute
- * Each branch corresponds to an attribute value.
- * Each Assign classification.

Training Example:

Day	Outlook	Temp	Humidity	Wind	Test
D1	Sunny	Hot	high	weak	No
D2	Sunny	Hot	high	strong	No
D3	Overcast	Hot	high	weak	Yes
D4	Rain	mild	high	weak	Yes
D5	Rain	cool	Normal	weak	Yes
D6	Rain	cool	Normal	strong	No
D7	Overcast	cool	Normal	strong	Yes
D8	Sunny	mild	high	weak	No
D9	Sunny	cool	Normal	weak	Yes
D10	Rain	mild	Normal	weak	Yes
D11	Sunny	mild	Normal	strong	Yes
D12	overcast	mild	high	strong	Yes
D13	overcast	Hot	normal	weak	Yes
D14	Rain	mild	high	strong	No

* The Decision tree to represent learned target functions:
* Each internal node tests as attribute
if Outlook = sunny and humidity = normal
if Outlook = overcast
if Outlook = rain and wind = weak.

EBL System Schematic:


- * 2-valued
- * N-valued

- ✱ Examples:

- ### Explanation based learning: EBL

- * A goal concept
- * An operational criterion
- * A domain theory.

Inputs
Specific goal /
problem



Learning with complete data:




- ### Bayes's Rule:

Prior
 $P(A) = \text{True}$


$$P(A|B) = \frac{P(B|A) \cdot P(A)}{P(B)}$$

marginale Zaton
PLB) = true

TWO FLAVORS



Burglar alarm




It's actually easier to work with the log-likelihood:

$$= C \log \theta + C \log (1-\theta)$$


$$\frac{dL(D|\theta)}{d\theta} = \frac{c}{1-\theta} = \frac{c}{1-\theta}$$

Learning with hidden variables

- * Real world problems have hidden variables
- * No training data available on hidden variables
- * Model cannot be built without training data
- * Inference cannot be done without model
- * How to learn model with hidden variables




an equivalent network with heart disease removal.




Neural Networks:

- * Like human brain
- * Neurons Interconnected.



- * Dendrites - Inputs
- * Cell nucleus - Nodus
- * Synapse - weights
- * Axon - outputs

- Advantages:
- * Storing data on entire network.
 - * Having memory distribution
 - * Having fault tolerance
- Disadvantages:
- * Hardware dependence
 - * Unrecognized behaviour of the network




Planning in building a neural network:


- The number of units to use
- The type of units required
- Connection between the units

A computing unit:

- * Now in more detail but for a particular model only.



Activation functions:




Different activation function for unit:

- Step(x) = $\begin{cases} 1, & \text{if } x \geq 0 \\ 0, & \text{if } x < 0 \end{cases}$
- Sign(x) = $\begin{cases} +1, & \text{if } x \geq 0 \\ -1, & \text{if } x < 0 \end{cases}$
- Sigmoid(x) = $\frac{1}{1 + e^{-x}}$

Types of Neural Networks:


- * Feedback ANN $\rightarrow$ o/p returns into the network
- * Feed Forward $\rightarrow$ consists of 2 Input layer and 1 o/p layer.

Example: (Real time application).




Perceptron network:

Single layer Perceptron:




Multi layer Perceptron:



Why Recurrent Neural network?

- * cannot handle sequential data
- * considers only the current input
- * cannot memorize previous inputs.



Recurrent Neural network:

Application: (RNN)

- * Image captioning
- * Time series prediction
- * Natural language processing
- * Machine translation

Types of RNN:

- * One to one
- * One to many
- * Many to one
- * Many to many

Kernel Machine:


- * Single layer network
- + multi layer network

Simple and learning efficient algorithm, limited expressive power

more expressive


Support Vector Machine:

- * It is popular supervised learning algorithm.



Graph of SVM

Real Time Example:



- * SVM used for face detection
- * Image classification
- * Text categorization... etc.

Types:

1. Linear
2. Non-Linear

Used for binary separable data
Ideal for non-linear separable data

Reinforcement learning:

- * The problem is this:

without some feedback about what is good or bad


- * The agent will have no grounds for deciding which move to make

- * The agent needs to know


Something good has happened when it wins

Something bad has happened when it loses

- * This kind of feedback is called a reward or reinforcement.



Applications:




Terms used in Reinforcement learning:

- * Agent ()
- * Environment ()
- * Action ()
- * State ()
- * Reward ()
- * Policy ()
- * Value ()
- * Q value ()

Elements of Reinforcement learning:

- * Policy
- * Reward signal
- * Value function
- * Model of the environment

Example of Reinforcement learning:



In this case,

- * Your cat is an agent that is exposed to the environment.

- * On agent reacts by performing an action transition from "one state to another state."

- * For example, your cat goes sitting to walking.
- * They may get a reward or penalty in return.
- * The reaction of agent is an action.

Types of Reinforcement learning:

Supervised learning

- * Classification
- * Regression

- * Linear SVM
- * Logistic Regression

Unsupervised learning

- * K-Means
- * Neural Networks
- * PCA

Reinforcement learning

- * Supervised
- * Unsupervised

Types of data in ML:

Supervised ML

- * Labeled Data
- * Calculated Outcomes


Unsupervised ML

- * Unlabeled data
- * Discover patterns underlying

- * No-Practical data
- * Learn a sense of a class

INTRODUCTION TO SEARCH ENGINE OPTIMIZATION.

Different Search Engine :-

- 1) A search engine is a web-based tool that enables users to locate information on the world wide web.
 - 2) Popular examples of search engines are Google, Yahoo!, and MSN search.
- 
- 3) Yahoo was founded by -> David Filo, Larry Page, Sergey Brin
 - 4) Google was founded by -> Larry Page, Sergey Brin
- ### USES OF SE :-
- * SE utilize automated software applications that travel along web, follow like Page to Page.
 - * SE search their own databases when a user enters in a search to find related documents.
- ### TYPES OF SE :-
- 1) Crawler based search engines [use "spider" or "crawler"]
 - 2) Search directories or indexes [Depends on] human editors
 - 3) Hybrid Search Engines [Both crawler & search]
 - 4) Meta Search Engines [via the WWW]

Evaluating Search Engine :-

Measures for a search engine:

- * How fast does it index
 - > Number of documents/hour
 - > Average document size
- * How fast does it search
 - > Latency as a function of Index size.
- * Expensiveness of query language
 - > Ability to express complex information needs
 - > Speed on complex queries

Measuring User happiness:

- * Issue: who is the user we are trying to make happy?
 - > Depends on the setting.
- * Web Engine: User finds what they want and return to engine.
 - > can measure rate of return users.

Accuracy:-


- * Given a query an engine classifies each doc as "Relevant" or "Irrelevant".
- * Accuracy of an engine: the fraction of these classifications that is correct.

Search Techniques:-

- * Phrase searching
 - o Instead of -> American English
 - * Try -> American English
- * Truncation
 - * Instead of
 - * Machine
 - * Try - Machine? for machine, machinery.

Wildcard Search:-

- * If you want both
 - Woman
 - Women
- * Try - woman



Boolean Searching:-

- * Boolean Search is query technique that utilize Boolean logic to connect individual keyword within single query.
- 

Real Time Application:-

Yahoo!

Search Yahoo



* Website Design - Layout And Keyword Optimization *

* DESIGN AND LAYOUT *

what type of information goes on a web site?

- * Contact information (phone no, email)
- * Business hours
- * Background information about your business
- * Product / service information

The URL is composed of 3 parts

- The protocol * http://
- The domain name * www.hispanicbusiness.com
- The pathname * /magazine
- A web page is written in a special code called HTML

HTML - Hyper-text markup language
Most sources today offer both domain and web hosting:

Ex: * www.godaddy.com
* www.registrar.com

Free domain with annual purchase	Standard web hosting	Advanced web hosting	Pro web hosting
Disk space (GB)	7	15	30
Monthly data transfer (GB)	150	400	500
FTP Accounts	3	6	15
E-mailboxes	50	100	200
Directory pointers	20	40	50

* Keywords Optimization *

* A keyword is a term that is used to match with the query a person enters into a search engine to find specific information.

* Such phrases may be called

Search phrases, keyword phrases, query phrases or just keywords.

Keyword frequency

* This is calculated as how often does a keyword appear in a website title or description.

* Since on some engines if you repeat a word too many times, you are be penalized for "spamming" or keyword stuffing

Keyword weight

* It refers to the number of keywords appearing on your webpage compared to the total number of words appearing on that same page.

Keyword proximity

* It refers to the placement of keywords on a web page in relation to each other or, in some cases, in relation to other words.

Keyword prominence

* It is a measure of how early or high up on a page, the keywords are found.

Metatags Optimization

There are two important metatags:

- Meta description tags
- Meta keyword tags

* For Google, adding the description meta tag does not result in a boost in the search engine results.

What do the Metatags look like

Ex:

- * <meta name = "keywords">
- * content = "keyword01 keyword02 keyword keyword01 etc. about 30 to 40 unique words"
- * <meta name = "description">
- * content = "An accurate, keyword-rich description about 150 characters"

Real time application

1. zig-zag layout
2. F layout
3. Full-screen photo
4. Grid layout
5. one-column layout



SEARCH ENGINE ARCHITECTURE


⑤

- ## Exemples

- # WEBSITE DOMAIN

- ## CRU Canon Parts

-



Title optimization:-

- * An HTML title tag is put inside the head tag
 - * This is the one place on a webpage where your keywords must be present
 - * Correct use of keywords in the title of every page of your website is extremely important to Google - particularly for the homepage
- ### Designing the title of a webpage:-
- * The title shouldn't consist of more than about 9 words or 60 characters
 - * Use keywords at very beginning of the title
 - * Do not include your company name in titles unless your company name is very well known
- ### Best Practices for creating titles:-
- * Use more specific variations to your primary keyword phrase on your specific product, service, or content page.
 - * Make sure the "<title>" tag is first element in the <head> section of your page - This make it easier for Google to find the page

Anchors optimization:-

- * Use descriptive anchor text for all your text links. Most search engines consider anchor text of incoming links when ranking pages. Here is an example:
- ```
Anchor text
```
- \* `<a href="otherPage.htm" title="Anchor title">Anchor text </a>`
- ⇒ Some of important points to note about anchors:-
- ⇒ The Anchor plays a very important role in the "titles" and is seen by most of search engines
  - ⇒ The anchor title should have an appropriate keywords.
  - ⇒ Anchor title helps the site visitors using a balloon, and displaying written text.
- ### Anchors verification for website:-
- ⇒ Another example of an anchor could be as follows:
- ```
<a href="otherPage.htm" title="Anchor title" </a>
```
- ⇒ In this case, anchor text has been replaced by an image.
- ⇒ So, while using an image in place of an anchor text, it should be checked that you have put alt tag properly.

XML Validation:-

- ⇒ Validation is a method of verifying that we have made no syntax or rules violations on our web pages
- ⇒ This step is important, as it helps ensure that our websites display properly and consistently to our visitors.
- Example:-

```
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Transitional//EN"
"http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd">
```

W3C

Markup validation service
check the markup of your XML documents

validate by URI	validate File upload	validate Direct IP
validate by URI	validate a document online:	
Address:		
More options		
check		


Real Time Application:-

amazon

Electronics mobiles miniv Deals

FUTURE OF AI

* FUTURE OF ARTIFICIAL INTELLIGENCE *



Artificial Intelligence future :-

→ A PwC report estimates that AI will contribute \$15.7 trillion to global economy by 2030.

1. Health Care :

- AI robots would be employed.
- To perform complex surgeries.
- High degree of precision.

2. Autonomous Vehicles :

- Autonomous vehicles are equipped with multiple sensors.
- Like cameras, radars and lidar.
- AI is projected to have a valuation of \$127 billion by 2025.

3. Security and Defence

- AI are often embedded into weapons and Surveillance Systems.
- Securing the borders of the country can be delegated to AI robots, UAVs etc.

4. Manufacturing :

- AI optimizes manufacturing supply chains.
- Helping companies anticipate market changes.
- Future process would be able to inspect, improve, and quality check.
- No need of any human intervention.

5. Education

- The future of classroom is digital.
- It will be redefined from comfort of homes
- Personalized according to every student with AI systems.

6. Entertainment :

- OTT's like Aha, Amazon prime etc are increasing user base.
- In future, AI will be predicting according to your mood and display content.

7. Workplace :

- Businesses are using AI
- To enhance productivity of their employees
- One example is chatbot.

8. Banking and Finance :

- AI is best way for banking
- It brings facility of advanced data analytics to combat fraudulent transactions.
- Improve compliance.

* The ways in which AI can be implemented in different industries are left only to one's imagination

* There is one thing that is for sure which is :

“ The future would be an exciting time to live in.”