

Scan Report

October 30, 2018

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “10.0.0.2”. The scan started at Tue Oct 30 03:47:47 2018 UTC and ended at Tue Oct 30 05:29:40 2018 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	10.0.0.2	2
2.1.1	High 6667/tcp	2
2.1.2	High 80/tcp	3
2.1.3	Medium 6667/tcp	8
2.1.4	Medium 80/tcp	9
2.1.5	Low 80/tcp	19
2.1.6	Low general/tcp	20

Result Overview

Host	High	Medium	Low	Log	False Positive
10.0.0.2 metasploitable.starter_channel	6	11	2	0	0
Total: 1	6	11	2	0	0

Vendor security updates are not trusted.

Overrides are on. When a result has an override, this report uses the threat of the override.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

It only lists hosts that produced issues.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 19 results selected by the filtering described above. Before filtering there were 178 results.

Results per Host

10.0.0.2

Host scan start Tue Oct 30 03:48:12 2018 UTC

Host scan end Tue Oct 30 05:29:40 2018 UTC

Service (Port)	Threat Level
6667/tcp	High
80/tcp	High
6667/tcp	Medium
80/tcp	Medium
80/tcp	Low
general/tcp	Low

High [6667/tcp](#)

High (CVSS: 7.5)

NVT: Check for Backdoor in UnrealIRCd

Summary

Detection of backdoor in UnrealIRCd.

... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Solution Solution type: VendorFix Install latest version of unrealircd and check signatures of software you're installing.
Vulnerability Insight Remote attackers can exploit this issue to execute arbitrary system commands within the context of the affected application. The issue affects Unreal 3.2.8.1 for Linux. Reportedly package Unreal3.2.8.1.tar.gz downloaded in November 2009 and later is affected. The MD5 sum of the affected file is 752e46f2d873c1679fa99de3f52a274d. Files with MD5 sum of 7b741e94e867c0a7370553fd01506c66 are not affected.
Vulnerability Detection Method Details: Check for Backdoor in UnrealIRCd OID:1.3.6.1.4.1.25623.1.0.80111 Version used: \$Revision: 5433 \$
References CVE: CVE-2010-2075 BID:40820 Other: URL:http://www.unrealircd.com/txt/unrealsecadvisory.20100612.txt URL:http://seclists.org/fulldisclosure/2010/Jun/277 URL:http://www.securityfocus.com/bid/40820

[\[return to 10.0.0.2 \]](#)

High 80/tcp

High (CVSS: 10.0) NVT: TWiki XSS and Command Execution Vulnerabilities
Product detection result cpe:/a:twiki:twiki:01.Feb.2003 Detected by TWiki Version Detection (OID: 1.3.6.1.4.1.25623.1.0.800399)
Summary The host is running TWiki and is prone to Cross-Site Scripting (XSS) and Command Execution Vulnerabilities.
Vulnerability Detection Result ... continues on next page ...

...continued from previous page ...
Installed version: 01.Feb.2003 Fixed version: 4.2.4
Impact Successful exploitation could allow execution of arbitrary script code or commands. This could let attackers steal cookie-based authentication credentials or compromise the affected application. Impact Level: Application
Solution Solution type: VendorFix Upgrade to version 4.2.4 or later, http://twiki.org/cgi-bin/view/Codev/TWikiRelease04x02x04
Affected Software/OS TWiki, TWiki version prior to 4.2.4.
Vulnerability Insight The flaws are due to, - %URLPARAM}% variable is not properly sanitized which lets attackers conduct cross-site scripting attack. - %SEARCH}% variable is not properly sanitised before being used in an eval() call which lets the attackers execute perl code through eval injection attack.
Vulnerability Detection Method Details: TWiki XSS and Command Execution Vulnerabilities OID:1.3.6.1.4.1.25623.1.0.800320 Version used: \$Revision: 4227 \$
Product Detection Result Product: cpe:/a:twiki:twiki:01.Feb.2003 Method: TWiki Version Detection OID: 1.3.6.1.4.1.25623.1.0.800399)
References CVE: CVE-2008-5304, CVE-2008-5305 BID:32668, 32669 Other: URL: http://twiki.org/cgi-bin/view/Codev.SecurityAlert-CVE-2008-5304 URL: http://twiki.org/cgi-bin/view/Codev/SecurityAlert-CVE-2008-5305
High (CVSS: 7.5) NVT: phpinfo() output accessible
Summary Many PHP installation tutorials instruct the user to create a file called phpinfo.php or similar containing the phpinfo() statement. Such a file is often times left in webserver directory after completion.
... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result The following files are calling the function phpinfo() which disclose potentially sensitive information to the remote attacker: http://metasploitable.starter_channel/phpinfo.php http://metasploitable.starter_channel/mutillidae/phpinfo.php
Impact Some of the information that can be gathered from this file includes: The username of the user who installed php, if they are a SUDO user, the IP address of the host, the web server version, the system version(unix / linux), and the root directory of the web server.
Solution Solution type: Workaround Delete them or restrict access to the listened files.
Vulnerability Detection Method Details: phpinfo() output accessible OID:1.3.6.1.4.1.25623.1.0.11229 Version used: \$Revision: 10552 \$

High (CVSS: 7.5) NVT: Tiki Wiki CMS Groupware < 4.2 Multiple Unspecified Vulnerabilities
Product detection result cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Detected by Tiki Wiki CMS Groupware Version Detection (OID: 1.3.6.1.4.1.25623.1.0.901001)
Summary Tiki Wiki CMS Groupware is prone to multiple unspecified vulnerabilities, including: - An unspecified SQL-injection vulnerability - An unspecified authentication-bypass vulnerability - An unspecified vulnerability
Vulnerability Detection Result Installed version: 1.9.5 Fixed version: 4.2
Impact Exploiting these issues could allow an attacker to compromise the application, access or modify data, exploit latent vulnerabilities in the underlying database, and gain unauthorized access to the affected application. Other attacks are also possible.
Solution ... continues on next page ...

...continued from previous page ...
Solution type: VendorFix The vendor has released an advisory and fixes. Please see the references for details.
Affected Software/OS Versions prior to Tiki Wiki CMS Groupware 4.2 are vulnerable.
Vulnerability Detection Method Details: Tiki Wiki CMS Groupware < 4.2 Multiple Unspecified Vulnerabilities OID:1.3.6.1.4.1.25623.1.0.100537 Version used: \$Revision: 5144 \$
Product Detection Result Product: cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Method: Tiki Wiki CMS Groupware Version Detection OID: 1.3.6.1.4.1.25623.1.0.901001)
References CVE: CVE-2010-1135, CVE-2010-1134, CVE-2010-1133, CVE-2010-1136 BID:38608 Other: URL:http://www.securityfocus.com/bid/38608 URL:http://tikiwiki.svn.sourceforge.net/viewvc/tikiwiki?view=rev&revision=247 ↪34 URL:http://tikiwiki.svn.sourceforge.net/viewvc/tikiwiki?view=rev&revision=250 ↪46 URL:http://tikiwiki.svn.sourceforge.net/viewvc/tikiwiki?view=rev&revision=254 ↪24 URL:http://tikiwiki.svn.sourceforge.net/viewvc/tikiwiki?view=rev&revision=254 ↪35 URL:http://info.tikiwiki.org/article86-Tiki-Announces-3-5-and-4-2-Releases URL:http://info.tikiwiki.org/tiki-index.php?page=homepage
High (CVSS: 7.5) NVT: PHP-CGI-based setups vulnerability when parsing query string parameters from php files.
Summary PHP is prone to an information-disclosure vulnerability.
Vulnerability Detection Result Vulnerable url: http://metasploitable.starter_channel/cgi-bin/php
Impact Exploiting this issue allows remote attackers to view the source code of files in the context of the server process. This may allow the attacker to obtain sensitive information and to run arbitrary PHP code on the affected computer. Other attacks are also possible.
... continues on next page ...

...continued from previous page ...

Solution**Solution type:** VendorFix

PHP has released version 5.4.3 and 5.3.13 to address this vulnerability. PHP is recommending that users upgrade to the latest version of PHP.

Vulnerability Insight

When PHP is used in a CGI-based setup (such as Apache's mod_cgid), the php-cgi receives a processed query string parameter as command line arguments which allows command-line switches, such as -s, -d or -c to be passed to the php-cgi binary, which can be exploited to disclose source code and obtain arbitrary code execution.

An example of the -s command, allowing an attacker to view the source code of index.php is below:

`http://localhost/index.php?-s`

Vulnerability Detection Method

Details: PHP-CGI-based setups vulnerability when parsing query string parameters from ph.
↪...

OID:1.3.6.1.4.1.25623.1.0.103482

Version used: \$Revision: 10711 \$

References

CVE: CVE-2012-1823, CVE-2012-2311, CVE-2012-2336, CVE-2012-2335

BID:53388

Other:

URL:<http://www.h-online.com/open/news/item/Critical-open-hole-in-PHP-creates-risks-Update-1567532.html>

URL:<http://www.kb.cert.org/vuls/id/520827>

URL:<http://eindbazen.net/2012/05/php-cgi-advisory-cve-2012-1823/>

URL:<https://bugs.php.net/bug.php?id=61910>

URL:<http://www.php.net/manual/en/security.cgi-bin.php>

URL:<http://www.securityfocus.com/bid/53388>

High (CVSS: 7.5)

NVT: Test HTTP dangerous methods

Summary

Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE. This script checks if they are enabled and can be misused to upload or delete files.

Vulnerability Detection Result

We could upload the following files via the PUT method at this web server:

`http://metasploitable.starter_channel/dav/puttest1861071088.html`

We could delete the following files via the DELETE method at this web server:

`http://metasploitable.starter_channel/dav/puttest1861071088.html`

... continues on next page ...

...continued from previous page ...
Impact - Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server. - Enabled DELETE method: This might allow an attacker to delete additional files on this web server.
Solution Solution type: Mitigation Use access restrictions to these dangerous HTTP methods or disable them completely.
Vulnerability Detection Method Details: Test HTTP dangerous methods OID:1.3.6.1.4.1.25623.1.0.10498 Version used: \$Revision: 9335 \$
References BID:12141 Other: OWASP:OWASP-CM-001

[\[return to 10.0.0.2 \]](#)

Medium 6667/tcp

Medium (CVSS: 6.8) NVT: UnrealIRCd Authentication Spoofing Vulnerability
Product detection result cpe:/a:unrealircd:unrealircd:3.2.8.1 Detected by UnrealIRCd Detection (OID: 1.3.6.1.4.1.25623.1.0.809884)
Summary This host is installed with UnrealIRCd and is prone to authentication spoofing vulnerability.
Vulnerability Detection Result Installed version: 3.2.8.1 Fixed version: 3.2.10.7
Impact Successful exploitation of this vulnerability will allows remote attackers to spoof certificate fingerprints and consequently log in as another user. Impact Level: Application.
Solution ... continues on next page ...

...continued from previous page ...
Solution type: VendorFix Upgrade to UnrealIRCd 3.2.10.7, or 4.0.6, or later. For updates refer to https://bugs.unrealircd.org/main_page.php
Affected Software/OS UnrealIRCd before 3.2.10.7 and 4.x before 4.0.6.
Vulnerability Insight The flaw exists due to an error in the 'm_authenticate' function in 'modules/m_sasl.c' script.
Vulnerability Detection Method Get the installed version with the help of detect NVT and check the version is vulnerable or not. Details: UnrealIRCd Authentication Spoofing Vulnerability OID:1.3.6.1.4.1.25623.1.0.809883 Version used: \$Revision: 9341 \$
Product Detection Result Product: cpe:/a:unrealircd:unrealircd:3.2.8.1 Method: UnrealIRCd Detection OID: 1.3.6.1.4.1.25623.1.0.809884)
References CVE: CVE-2016-7144 BID:92763 Other: URL: http://seclists.org/oss-sec/2016/q3/420 URL: http://www.openwall.com/lists/oss-security/2016/09/05/8 URL: https://github.com/unrealircd/unrealircd/commit/f473e355e1dc422c4f019dbf8c6bc50ba1a34a766

[\[return to 10.0.0.2 \]](#)

Medium 80/tcp

Medium (CVSS: 6.8) NVT: TWiki Cross-Site Request Forgery Vulnerability - Sep10
Product detection result cpe:/a:twiki:twiki:01.Feb.2003 Detected by TWiki Version Detection (OID: 1.3.6.1.4.1.25623.1.0.800399)
Summary The host is running TWiki and is prone to Cross-Site Request Forgery vulnerability.
... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.3.2
Impact Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack. Impact Level: Application
Solution Solution type: VendorFix Upgrade to TWiki version 4.3.2 or later, For updates refer to http://twiki.org/cgi-bin/view/Codev/DownloadTWiki
Affected Software/OS TWiki version prior to 4.3.2
Vulnerability Insight Attack can be done by tricking an authenticated TWiki user into visiting a static HTML page on another side, where a Javascript enabled browser will send an HTTP POST request to TWiki, which in turn will process the request as the TWiki user.
Vulnerability Detection Method Details: TWiki Cross-Site Request Forgery Vulnerability - Sep10 OID:1.3.6.1.4.1.25623.1.0.801281 Version used: \$Revision: 4293 \$
Product Detection Result Product: cpe:/a:twiki:twiki:01.Feb.2003 Method: TWiki Version Detection OID: 1.3.6.1.4.1.25623.1.0.800399)
References CVE: CVE-2009-4898 Other: URL: http://www.openwall.com/lists/oss-security/2010/08/03/8 URL: http://www.openwall.com/lists/oss-security/2010/08/02/17 URL: http://twiki.org/cgi-bin/view/Codev/SecurityAuditTokenBasedCsrfFix
Medium (CVSS: 6.0) NVT: TWiki Cross-Site Request Forgery Vulnerability
Product detection result cpe:/a:twiki:twiki:01.Feb.2003 Detected by TWiki Version Detection (OID: 1.3.6.1.4.1.25623.1.0.800399)
... continues on next page ...

...continued from previous page ...
Summary The host is running TWiki and is prone to Cross-Site Request Forgery Vulnerability.
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.3.1
Impact Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack. Impact Level: Application
Solution Solution type: VendorFix Upgrade to version 4.3.1 or later, http://twiki.org/cgi-bin/view/Codev/DownloadTWiki
Affected Software/OS TWiki version prior to 4.3.1
Vulnerability Insight Remote authenticated user can create a specially crafted image tag that, when viewed by the target user, will update pages on the target system with the privileges of the target user via HTTP requests.
Vulnerability Detection Method Details: TWiki Cross-Site Request Forgery Vulnerability OID:1.3.6.1.4.1.25623.1.0.800400 Version used: \$Revision: 4892 \$
Product Detection Result Product: cpe:/a:twiki:twiki:01.Feb.2003 Method: TWiki Version Detection OID: 1.3.6.1.4.1.25623.1.0.800399)
References CVE: CVE-2009-1339 Other: URL: http://secunia.com/advisories/34880 URL: http://bugs.debian.org/cgi-bin/bugreport.cgi?bug=526258 URL: http://twiki.org/p/pub/Codev/SecurityAlert-CVE-2009-1339/TWiki-4.3.0-c-di ↪ff-cve-2009-1339.txt

Medium (CVSS: 5.8) NVT: HTTP Debugging Methods (TRACE/TRACK) Enabled
Summary Debugging functions are enabled on the remote web server. The remote web server supports the TRACE and/or TRACK methods. TRACE and TRACK are HTTP methods which are used to debug web server connections.
Vulnerability Detection Result The web server has the following HTTP methods enabled: TRACE
Impact An attacker may use this flaw to trick your legitimate web users to give him their credentials.
Solution Solution type: Mitigation Disable the TRACE and TRACK methods in your web server configuration. Please see the manual of your web server or the references for more information.
Affected Software/OS Web servers with enabled TRACE and/or TRACK methods.
Vulnerability Insight It has been shown that web servers supporting this methods are subject to cross-site-scripting attacks, dubbed XST for Cross-Site-Tracing, when used in conjunction with various weaknesses in browsers.
Vulnerability Detection Method Details: HTTP Debugging Methods (TRACE/TRACK) Enabled OID:1.3.6.1.4.1.25623.1.0.11213 Version used: \$Revision: 10828 \$
References CVE: CVE-2003-1567, CVE-2004-2320, CVE-2004-2763, CVE-2005-3398, CVE-2006-4683, ↗CVE-2007-3008, CVE-2008-7253, CVE-2009-2823, CVE-2010-0386, CVE-2012-2223, CVE ↗-2014-7883 BID:9506, 9561, 11604, 15222, 19915, 24456, 33374, 36956, 36990, 37995 Other: URL:http://www.kb.cert.org/vuls/id/288308 URL:http://www.kb.cert.org/vuls/id/867593 URL:http://httpd.apache.org/docs/current/de/mod/core.html#traceenable URL:https://www.owasp.org/index.php/Cross_Site_Tracing

Medium (CVSS: 5.0) NVT: /doc directory browsable
Summary ... continues on next page ...

...continued from previous page ...
The /doc directory is browsable. /doc shows the content of the /usr/doc directory and therefore it shows which programs and - important! - the version of the installed programs.
Vulnerability Detection Result Vulnerable url: <code>http://metasploitable.starter_channel/doc/</code>
Solution Solution type: Mitigation Use access restrictions for the /doc directory. If you use Apache you might use this in your access.conf: <Directory /usr/doc> AllowOverride None order deny,allow deny from all allow from localhost </Directory>
Vulnerability Detection Method Details: /doc directory browsable OID:1.3.6.1.4.1.25623.1.0.10056 Version used: \$Revision: 4288 \$
References CVE: CVE-1999-0678 BID:318

Medium (CVSS: 5.0) NVT: Tiki Wiki CMS Groupware Input Sanitation Weakness Vulnerability
Product detection result cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Detected by Tiki Wiki CMS Groupware Version Detection (OID: 1.3.6.1.4.1.25623.1.↔0.901001)
Summary The host is installed with Tiki Wiki CMS Groupware and is prone to input sanitation weakness vulnerability.
Vulnerability Detection Result Installed version: 1.9.5 Fixed version: 2.2
Impact Successful exploitation could allow arbitrary code execution in the context of an affected site. Impact Level: Application
Solution Solution type: VendorFix Upgrade to version 2.2 or latest http://info.tikiwiki.org/tiki-index.php?page=Get+Tiki&bl
... continues on next page ...

...continued from previous page ...
Affected Software/OS Tiki Wiki CMS Groupware version prior to 2.2 on all running platform
Vulnerability Insight The vulnerability is due to input validation error in tiki-error.php which fails to sanitise before being returned to the user.
Vulnerability Detection Method Details: Tiki Wiki CMS Groupware Input Sanitation Weakness Vulnerability OID:1.3.6.1.4.1.25623.1.0.800315 Version used: \$Revision: 5144 \$
Product Detection Result Product: cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Method: Tiki Wiki CMS Groupware Version Detection OID: 1.3.6.1.4.1.25623.1.0.901001)
References CVE: CVE-2008-5318, CVE-2008-5319 Other: URL:http://secunia.com/advisories/32341 URL:http://info.tikiwiki.org/tiki-read_article.php?articleId=41

Medium (CVSS: 5.0) NVT: Tiki Wiki CMS Groupware 'fixedURLData' Local File Inclusion Vulnerability
Product detection result cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Detected by Tiki Wiki CMS Groupware Version Detection (OID: 1.3.6.1.4.1.25623.1.↔0.901001)
Summary The host is installed with Tiki Wiki CMS Groupware and is prone to a local file inclusion vulnerability.
Vulnerability Detection Result Installed version: 1.9.5 Fixed version: 12.11
Impact Successful exploitation will allow an user having access to the admin backend to gain access to arbitrary files and to compromise the application. Impact Level: System/Application
... continues on next page ...

...continued from previous page ...
Solution Solution type: VendorFix Upgrade to Tiki Wiki CMS Groupware version 12.11 LTS, 15.4 or later. For updates refer to https://tiki.org
Affected Software/OS Tiki Wiki CMS Groupware versions: - below 12.11 LTS - 13.x, 14.x and 15.x below 15.4
Vulnerability Insight The Flaw is due to improper sanitization of input passed to the 'fixedURLData' parameter of the 'display_banner.php' script.
Vulnerability Detection Method Get the installed version with the help of the detect NVT and check the version is vulnerable or not. Details: Tiki Wiki CMS Groupware 'fixedURLData' Local File Inclusion Vulnerability OID:1.3.6.1.4.1.25623.1.0.108064 Version used: \$Revision: 5144 \$
Product Detection Result Product: cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Method: Tiki Wiki CMS Groupware Version Detection OID: 1.3.6.1.4.1.25623.1.0.901001)
References CVE: CVE-2016-10143 Other: URL: http://tiki.org/article445-Security-updates-Tiki-16-2-15-4-and-Tiki-12-11-released URL: https://sourceforge.net/p/tikiwiki/code/60308/
Medium (CVSS: 5.0) NVT: awiki Multiple Local File Include Vulnerabilities
Summary awiki is prone to multiple local file-include vulnerabilities because it fails to properly sanitize user-supplied input.
Vulnerability Detection Result Vulnerable url: http://metasploitable.starter_channel/mutillidae/index.php?page=/etc/passwd
Impact ... continues on next page ...

...continued from previous page ...
An attacker can exploit this vulnerability to obtain potentially sensitive information and execute arbitrary local scripts in the context of the webserver process. This may allow the attacker to compromise the application and the host. Other attacks are also possible.
Solution Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS awiki 20100125 is vulnerable. Other versions may also be affected.
Vulnerability Detection Method Details: awiki Multiple Local File Include Vulnerabilities OID:1.3.6.1.4.1.25623.1.0.103210 Version used: \$Revision: 10741 \$
References BID:49187 Other: URL:https://www.exploit-db.com/exploits/36047/ URL:http://www.securityfocus.com/bid/49187 URL:http://www.kobaonline.com/awiki/

Medium (CVSS: 4.8) NVT: Cleartext Transmission of Sensitive Information via HTTP
Summary The host / application transmits sensitive information (username, passwords) in cleartext via HTTP.
Vulnerability Detection Result The following input fields were identified (URL:input name): http://metasploitable.starter_channel/phpMyAdmin/:pma_password http://metasploitable.starter_channel/phpMyAdmin/?D=A:pma_password http://metasploitable.starter_channel/tikiwiki/tiki-install.php:pass http://metasploitable.starter_channel/twiki/bin/view/TWiki/TWikiUserAuthentication:oldpassword
Impact An attacker could use this situation to compromise or eavesdrop on the HTTP communication between the client and the server using a man-in-the-middle attack to get access to sensitive data like usernames or passwords.
Solution ... continues on next page ...

...continued from previous page ...
Solution type: Workaround Enforce the transmission of sensitive data via an encrypted SSL/TLS connection. Additionally make sure the host / application is redirecting all users to the secured SSL/TLS connection before allowing to input sensitive data into the mentioned functions.
Affected Software/OS Hosts / applications which doesn't enforce the transmission of sensitive data via an encrypted SSL/TLS connection.
Vulnerability Detection Method Evaluate previous collected information and check if the host / application is not enforcing the transmission of sensitive data via an encrypted SSL/TLS connection. The script is currently checking the following: - HTTP Basic Authentication (Basic Auth) - HTTP Forms (e.g. Login) with input field of type 'password' Details: Cleartext Transmission of Sensitive Information via HTTP OID:1.3.6.1.4.1.25623.1.0.108440 Version used: \$Revision: 10726 \$
References Other: URL: https://www.owasp.org/index.php/Top_10_2013-A2-Broken_Authentication_and_Session_Management URL: https://www.owasp.org/index.php/Top_10_2013-A6-Sensitive_Data_Exposure URL: https://cwe.mitre.org/data/definitions/319.html

Medium (CVSS: 4.3) NVT: Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability
Summary This host is running Apache HTTP Server and is prone to cookie information disclosure vulnerability.
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successful exploitation will allow attackers to obtain sensitive information that may aid in further attacks. Impact Level: Application
Solution Solution type: VendorFix Upgrade to Apache HTTP Server version 2.2.22 or later, For updates refer to http://httpd.apache.org/
... continues on next page ...

...continued from previous page ...
Affected Software/OS Apache HTTP Server versions 2.2.0 through 2.2.21
Vulnerability Insight The flaw is due to an error within the default error response for status code 400 when no custom ErrorDocument is configured, which can be exploited to expose 'httpOnly' cookies.
Vulnerability Detection Method Details: Apache HTTP Server 'httpOnly' Cookie Information Disclosure Vulnerability OID:1.3.6.1.4.1.25623.1.0.902830 Version used: \$Revision: 11135 \$
References CVE: CVE-2012-0053 BID:51706 Other: URL:http://secunia.com/advisories/47779 URL:http://www.exploit-db.com/exploits/18442 URL:http://rhn.redhat.com/errata/RHSA-2012-0128.html URL:http://httpd.apache.org/security/vulnerabilities_22.html URL:http://svn.apache.org/viewvc?view=revision&revision=1235454 URL:http://lists.opensuse.org/opensuse-security-announce/2012-02/msg00026.htm ↪1

Medium (CVSS: 4.3) NVT: phpMyAdmin 'error.php' Cross Site Scripting Vulnerability
Product detection result cpe:/a:phpmyadmin:phpmyadmin:3.1.1 Detected by phpMyAdmin Detection (OID: 1.3.6.1.4.1.25623.1.0.900129)
Summary The host is running phpMyAdmin and is prone to Cross-Site Scripting Vulnerability.
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successful exploitation will allow attackers to inject arbitrary HTML code within the error page and conduct phishing attacks. Impact Level: Application
Solution Solution type: WillNotFix
... continues on next page ...

...continued from previous page ...
No solution or patch was made available for at least one year since disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS phpMyAdmin version 3.3.8.1 and prior.
Vulnerability Insight The flaw is caused by input validation errors in the 'error.php' script when processing crafted BBcode tags containing '@' characters, which could allow attackers to inject arbitrary HTML code within the error page and conduct phishing attacks.
Vulnerability Detection Method Details: phpMyAdmin 'error.php' Cross Site Scripting Vulnerability OID: 1.3.6.1.4.1.25623.1.0.801660 Version used: \$Revision: 5323 \$
Product Detection Result Product: cpe:/a:phpmyadmin:phpmyadmin:3.1.1 Method: phpMyAdmin Detection OID: 1.3.6.1.4.1.25623.1.0.900129)
References CVE: CVE-2010-4480 Other: URL: http://www.exploit-db.com/exploits/15699/ URL: http://www.vupen.com/english/advisories/2010/3133

[\[return to 10.0.0.2 \]](#)

Low 80/tcp

Low (CVSS: 3.5) NVT: Tiki Wiki CMS Groupware XSS Vulnerability
Product detection result cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Detected by Tiki Wiki CMS Groupware Version Detection (OID: 1.3.6.1.4.1.25623.1.↪0.901001)
Summary An XSS vulnerability (via an SVG image) in Tiki allows an authenticated user to gain administrator privileges if an administrator opens a wiki page with a malicious SVG image, related to lib/filegals/filegallib.php.
... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result Installed version: 1.9.5 Fixed version: 18.0
Solution Solution type: VendorFix Upgrade to version 18.0 or later.
Affected Software/OS Tiki Wiki CMS Groupware prior to version 18.0.
Vulnerability Detection Method Checks the version. Details: Tiki Wiki CMS Groupware XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.140797 Version used: \$Revision: 9171 \$
Product Detection Result Product: cpe:/a:tiki:tikiwiki_cms/groupware:1.9.5 Method: Tiki Wiki CMS Groupware Version Detection OID: 1.3.6.1.4.1.25623.1.0.901001)
References CVE: CVE-2018-7188 Other: URL:http://openwall.com/lists/oss-security/2018/02/16/1

[\[return to 10.0.0.2 \]](#)

Low general/tcp

Low (CVSS: 2.6) NVT: TCP timestamps
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Vulnerability Detection Result It was detected that the host implements RFC1323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 1676419 Packet 2: 1676539
Impact ... continues on next page ...

...continued from previous page ...
A side effect of this feature is that the uptime of the remote host can sometimes be computed.
<p>Solution</p> <p>Solution type: Mitigation</p> <p>To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.</p> <p>To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment.</p> <p>See also: http://www.microsoft.com/en-us/download/details.aspx?id=9152</p>
<p>Affected Software/OS</p> <p>TCP/IPv4 implementations that implement RFC1323.</p>
<p>Vulnerability Insight</p> <p>The remote host implements TCP timestamps, as defined by RFC1323.</p>
<p>Vulnerability Detection Method</p> <p>Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported.</p> <p>Details: TCP timestamps</p> <p>OID:1.3.6.1.4.1.25623.1.0.80091</p> <p>Version used: \$Revision: 10411 \$</p>
<p>References</p> <p>Other:</p> <p>URL:http://www.ietf.org/rfc/rfc1323.txt</p>

[[return to 10.0.0.2](#)]