

GPU Gradient Decent Shape Optimizer Design

November 17, 2021

1 Requirements

Write a GPU accelerated shape optimizer to practice GPU optimizations and investigate speed up for Morpho first version should be able to:

- Optimize surface Area with constant Volume
- Read in morpho meshes (for ease of use)
- Run on the GPU
- Input is Morpho mesh print area and volume. output is optimized morpho mesh print area and volume

2 Conceptual Method

A mesh is a list of vertices \vec{r}_i with rules for how the connect. One dimensional connections are lines, Two dimensional connections are facets. A connection is a list of vertex indices that are part of the higher dimensional element. Let i label verties, k label facets and l label the vertex in a facet. Consider a facet f_k with three vertices labeled $\vec{r}_{f_{k_l}}$ I.E $\vec{r}_{f_{k_1}}, \vec{r}_{f_{k_2}}, \vec{r}_{f_{k_3}}$. The area of this facet is:

$$A_k = (\vec{r}_{f_{k_2}} - \vec{r}_{f_{k_1}}) \times (\vec{r}_{f_{k_3}} - \vec{r}_{f_{k_1}})$$

To minimize area we need to find the gradient of the area with respect to the vertices of the facet.

$$\vec{S}_0 = (\vec{r}_{f_{k_2}} - \vec{r}_{f_{k_1}}) \quad (1)$$

$$\vec{S}_1 = (\vec{r}_{f_{k_3}} - \vec{r}_{f_{k_2}}) \quad (2)$$

$$\vec{S}_{01} = \vec{S}_0 \times \vec{S}_1 \quad (3)$$

$$\vec{S}_{010} = \vec{S}_{01} \times \vec{S}_0 \quad (4)$$

$$\vec{S}_{011} = \vec{S}_{01} \times \vec{S}_1 \quad (5)$$

$$\nabla_{\vec{r}_{f_{k_1}}} A_{f_k} = \frac{\vec{S}_{011}}{2|\vec{S}_{01}|} \quad (6)$$

$$\nabla_{\vec{r}_{f_{k_2}}} A_{f_k} = -\frac{\vec{S}_{011} + \vec{S}_{010}}{2|\vec{S}_{01}|} \quad (7)$$

$$\nabla_{\vec{r}_{f_{k_3}}} A_{f_k} = \frac{\vec{S}_{010}}{2|\vec{S}_{01}|} \quad (8)$$

Now that we have the area per vertex per facet we need to collate them to find the gradient. To do this on the GPU avoiding write collisions we use a map from $F(i) : i \rightarrow (k, l)_{m_i}$ where m_i counts up to the number of facets vertex i is included in. The gradient of the area with respect to a single vertex i is then:

$$\nabla_{\vec{r}_i} A = \sum_{(k, l)_{m_i}} \nabla_{\vec{r}_{f_{k_l}}} A_{f_k}$$

Likewise for volume integrand on a facet we have

$$V_{f_k} = \left| \frac{(\vec{r}_{f_{k_1}} \times \vec{r}_{f_{k_2}}) \cdot \vec{r}_{f_{k_3}}}{6} \right|$$

The gradient of the volume integrand for each vertex on a facet is then

$$s = \text{sign}((\vec{r}_{f_{k_1}} \times \vec{r}_{f_{k_2}}) \cdot \vec{r}_{f_{k_3}}) \quad (9)$$

$$\nabla_{\vec{r}_{f_{k_1}}} V_{f_k} = \frac{s}{6} \vec{r}_{f_{k_2}} \times \vec{r}_{f_{k_3}} \quad (10)$$

$$\nabla_{\vec{r}_{f_{k_2}}} V_{f_k} = \frac{s}{6} \vec{r}_{f_{k_3}} \times \vec{r}_{f_{k_1}} \quad (11)$$

$$\nabla_{\vec{r}_{f_{k_3}}} V_{f_k} = \frac{s}{6} \vec{r}_{f_{k_1}} \times \vec{r}_{f_{k_2}} \quad (12)$$

Then we perform the sum in the same manor

$$\nabla_{\vec{r}_i} V = \sum_{(k, l)_{m_i}} \nabla_{\vec{r}_{f_{k_l}}} V_{f_k}$$

To minimize area with constant volume we project the area gradient vector to the space where the volume change is zero. We call the negative of this

projection the force.

$$\vec{F}_i = - \left(\nabla_{\vec{r}_i} A - \frac{\nabla_{\vec{r}_i} A \cdot \nabla_{\vec{r}_i} V}{\nabla_{\vec{r}_i} V \cdot \nabla_{\vec{r}_i} V} \nabla_{\vec{r}_i} V \right)$$

Gradient decent then consists of calculating this force and moving the vertices on the mesh until the force is below a threshold value.

3 Implementation Method

First pass of this will be done in C++ using CUDA for GPU acceleration Class stucture is below



Figure 1: For this project there will be a optimizer class that manages a gradient and a mesh to perform the optimization. It will load in a mesh from file, create a device mesh from this mesh and tell the gradients to calculate and the mesh to move.