SAFE-CARE™

A framework for designing, evaluating and releasing safe patient-facing healthcare AI agents

White paper v2.0.1 · October 2026 · Yassen Eltayeb · Conefia LLC · ORCID 0009-0005-2854-9366 · CC BY 4.0 · accompanies framework repository v1.3.0

Abstract. Patient-facing AI agents now give health advice inside consumer products, and each new version should pass a release gate, the go-live check that asks whether the new version is safer without losing accuracy. Guidance from WHO, NIST and FDA sets principles for that decision and leaves the steps open, and the evaluation behind it varies in ways one run cannot reveal. SAFE-CARE™ is an open framework that turns that guidance into eight principles across five lifecycle stages, from design to operation, each with its controls, tests and release evidence. Version 2.0 qualifies the evaluation before any gate is read, through repeat runs, a comparison of the unchanged agent against itself, a check of which turns the judges score, and a test that every hard-fail gate, an automatic fail for a critical error, can fire. Gates are then read against confidence bounds. We also report the first published run of the companion SAFE-CARE Bench. We expected a safety guardrail to raise judged safety, and what fell was judged medical accuracy, by 0.157 on a 0-to-1 scale, in 6 of 9 scenarios and mostly in two. The 95% interval of the safety change included zero. The run also exposed defects in the instrument, and the largest is a gap in scoring coverage: across the nine scenarios analyzed, no judge scored 44% of turns, and no safety or escalation judge read 12 of the guardrail's 36 enforced safety actions. With nine scenarios and one judge family, we report these results as exploratory. A release gate should qualify its instrument before it trusts the verdict. The thresholds are proposed, and the paper makes no clinical performance claim.

Key messages. 1. A fluent reply can still be unsafe, so safety has to come from controls a team builds, tests and owns. 2. A release gate is a measurement. In the first SAFE-CARE Bench run, 16.3% of in-scope score cells changed across three runs of each unchanged configuration under its original scoring, and no judge scored 44% of in-scope turns. 3. Before trusting a gate, measure how far the

unchanged agent moves, check which turns the judges score, and prove that every hard-fail gate can fire.

1. Introduction

Patient-facing conversational agents now give health advice inside consumer products, and independent tests have found them failing as deployed. For example, one consumer assistant undertriaged 51.6% of gold-standard emergencies [1], and across nine products, triage accuracy concealed materially different referral behavior [2]. What reaches the patient is a model wrapped in retrieval, guardrails and tools. Because every layer changes between versions, whoever deploys such an agent, a health system or a vendor, must put each change through a release gate, the go-live check that asks whether the new version is safer without losing accuracy.

At that gate, the failures that matter are fluent ones. For instance, a user tells a menopause-support companion: "I am 52, I have hot flashes, and today I am bleeding heavily and feel dizzy." A fluent assistant answers the hot-flash question, whereas a safe agent sees the red flag first, points the person toward urgent care, avoids reassurance, and records why it acted (Figure 1). Both replies read well, and only the second is safe.

PATIENT

"I am 52, I have hot flashes, and today I am bleeding heavily and feel dizzy."

	UNGUARDED REPLY ✗	SAFE-CARE™ REPLY ✓
Red flag	Missed. Answers the hot-flash question.	**Detected before anything else.**
Tone	Reassures, with lifestyle tips.	**No reassurance. States the urgency.**
Next step	None. The conversation goes on.	**Urgent care now, or a human.**
Record	Nothing explains why it answered.	**Logs what it saw and why it acted.**

Figure 1. A fluent answer can be the unsafe answer. The same message sent to an unguarded assistant (left) and to an agent built with SAFE-CARE (right), compared on four behaviors. Both read well, and only the right one finds the red flag, escalates and records why. Illustrative.

Telling those two replies apart takes a rubric and a large language model judge, because a conversation has no answer key. Multiple-choice medical question answering is scored against a key [3], whereas in a multi-turn conversation a good reply depends on what the patient has said so far and on when a warning sign surfaces. In practice, HealthBench reports its model grader's agreement with physicians as "similar to physician-physician agreement" [4], and CARE-Bench shows that timing matters as much as content: when the right move was to ask for missing information, only 33.5% of prompted model outputs kept that step [5]. At a release gate, a judge validated this way is then trusted with the gate question itself.

The first gap between that trust and a defensible release is one of method, because guidance stops at values. WHO, NIST and FDA guidance tells a team what to value [6–10]: ethics and human rights at the center of design, risk managed across the lifecycle, good machine learning practice. However, it leaves to each team which controls to build, which artifacts to keep, which tests decide go or no-go, and who owns each decision.

The second gap sits inside the gate: a release decision rests on two assumptions that benchmarks built to rank models were not designed to test. That is, they assume the evaluation gives the same answer when nothing has changed, and its judges read the turns on which a change acts. Meta-evaluation already shows that judges with high agreement can assign very different scores [11]. On top of that, among the multi-turn evaluations cited here, none reports which turns its judges score.

SAFE-CARE answers the method gap with a lifecycle and tests the second gap on its own companion benchmark. The framework maps eight principles onto five stages, and version 2.0 adds a rule that runs through all of them: qualify the instrument, then trust the gate. For the second gap, we report the first published run of SAFE-CARE Bench, which holds a patient-facing agent's model, prompt and rubric fixed and adds one safety control. The paper makes six contributions, each a claim that a completed evaluation can support or refute:

- **C1. A traceable lifecycle.** Each SAFE-CARE principle, drawn from WHO, NIST and FDA guidance, maps to an engineering requirement, the controls that meet it, the tests that check it and the records that prove it, across five stages (Sections 2 to 8, Appendix B).

- **C2. An ablation ladder.** Adding groups of controls in a fixed order, on the same held-out scenarios, lets a team estimate what each group contributes to safety (Section 5.1).
- **C3. Instrument qualification.** A gate can be read only after its instrument is qualified: a fixed reference standard, a declared observation window, judged-turn coverage, the judge's distance from clinicians and the clinician band, a positive control for each hard-fail gate, a null comparison that measures the noise floor, a disagreement rule and provenance (Section 5.4).
- **C4. First evidence.** An open, controlled benchmark run shows several of the defects the qualification record is designed to catch, and most of them are invisible in an aggregate score (Section 5.5).
- **C5. Release and change-control rules.** Repeat runs and confidence bounds lower the chance that a flaky agent passes, by an amount a team can compute for each K. Re-testing around a fixed safety core (escalation, scope and adversarial scenarios that never change between versions) is designed to keep drift from accumulating across releases (Sections 6 and 7).
- **C6. A failure taxonomy.** Ten characteristic failure modes of patient-facing agents each map to the control layer expected to catch them (Section 8).

The rest of the paper follows the lifecycle. Section 2 gives the framework at a glance, and Sections 3 to 7 follow the stages, with the Bench run reported in Section 5.5 inside the evaluation stage. Section 8 then covers evidence and governance, Section 9 discusses what the run means, and Section 10 concludes. By the end, a reader will know what a release gate has to qualify before it reads a verdict, and how to check each item.

2. SAFE-CARE at a glance

SAFE-CARE runs as one loop in which every change sends the agent back to evaluation (Figure 2). Around the loop, a team designs the scope and evidence base, builds the controls, evaluates the agent with a qualified instrument, releases it through gates, and operates it under monitoring. Re-testing after a change to the model, prompt, retrieval sources or tools is scaled to what changed. Within the loop,

the eight principles spell SAFE-CARE, and the table below gives each as an engineering requirement a reviewer can check.




Figure 2. SAFE-CARE runs as one loop, and every change re-enters at Evaluate. Read top to bottom: the eight principles (bold) sit inside five lifecycle stages, and the orange return path sends the agent back to evaluation after a change to the model, prompt, sources or tools, with re-testing scaled to the change (Section 7).

	Principle	Engineering requirement
S	Scope	State the intended use, explicit non-use, permitted claims, users and the escalation boundary before a model is chosen.
A	Anchor	Ground health claims in approved, versioned evidence and map each claim to the passage that supports it.
F	Fence	Layer input, risk-classification, retrieval, tool, output, memory and monitoring guardrails.

	Principle	Engineering requirement
E	Evaluate	Test with simulation, ablation, automated judges and clinician review, using an instrument whose variability is known.
C	Contextualize	Personalize from confirmed, time-stamped, correctable context, and never invent facts about the user.
A	Act	Read and write only through permissioned tools with confirmation, audit and rollback.
R	Route	Escalate urgent, severe, uncertain or regulated cases to humans through deterministic rules.
E	Evidence	Keep a safety case, registries, release reports and monitoring for the life of the system.

Key terms. The method rests on the twelve terms in the table below, and each is defined again where it first does work.

Term	Meaning	Section
Ablation ladder (A0 to A4)	Five configurations, each adding a group of controls, run on the same held-out scenarios	5.1
Citation laundering	A citation that is present but does not support the claim it is attached to	3
Bridge test	Re-scoring a frozen set of earlier outputs with a new judge before comparing with an old baseline	5.3
K	The number of repeat runs of one configuration, fixed before testing; at least five proposed	5.4, 6
Null comparison	Comparing the unchanged agent with itself across repeat runs	5.4
Noise floor	The spread of differences the null comparison produces; a smaller change cannot be told from noise	5.4
Clinician band	How far qualified clinicians disagree with each other on the same conversations	5.4

Term	Meaning	Section
Judge distance	How far the automated judge sits from clinicians, dimension by dimension	5.4
Safety core	Fixed escalation, scope and adversarial scenarios, re-run unchanged on every change that can alter behavior and compared with the original baseline	7
Judged-turn coverage	The share of turns, and of safety actions, that some judge actually scored	5.4, 5.5
Positive control	A scenario built to fail a gate, run to prove the gate can fire	6
Other codes	Severity 0 to 4 (S0 to S4 in the templates), maturity levels M0 to M4, personalization levels P0 to P5	6, 8, 4

What changed in v2.0. Contributions C3 to C5 are new, and Section 5.5 reports the first SAFE-CARE Bench results. In addition, the release gates now require repeat runs and confidence bounds, the judge rubric treats safety as a gate before any weighted score, the scenario library adds clarification and no-escalation cases, and change control is a stage of its own. The paper is also reorganized around the lifecycle, with ten figures and the list of key terms above.

3. Design: Scope and Anchor

Scope comes before the model. Every agent starts with a use-case safety card. It records target users, intended use, explicit non-use, data accessed, allowed and prohibited actions, escalation triggers, human oversight, approved evidence sources and the evaluation plan. The card is also where a team decides whether the system is wellness software, clinical-adjacent, clinical decision support or potentially regulated software, because intended use and claims determine regulatory status [12]. For instance, the safe claim for the menopause companion is education, symptom tracking, stage-aware personalization and care navigation; the unsafe claims are diagnosing menopause stage with clinical certainty or recommending hormone therapy.

Anchor every health claim. Retrieval-augmented generation combines model capability with access to approved evidence and improves provenance on knowledge-intensive tasks [13]. Because citation quality can be measured, and systems often cite sources that do not fully support their statements [14], citation correctness is a safety metric in its own right. To that end, SAFE-CARE asks for clinician-approved sources with an approval owner and version, claim-level mapping from each statement to the supporting passage, and a declared fallback when no approved evidence exists: the agent says it does not have enough approved evidence and routes the question. A citation that is present but does not support its claim is called *citation laundering*, and SAFE-CARE treats it as worse than no citation, because it lends false credibility.

4. Build: Fence, Contextualize, Act and Route

A safe healthcare agent is a system of systems: model, evidence, safety, tools, memory, interface, evaluation and governance (Figure 3). Within that system, agentic patterns interleave reasoning with action and let models decide when to call tools [15, 16], which is where both value and new risk come from.




Figure 3. Safety lives in the layers around the model. Read top to bottom: a message passes five controlled layers, and any layer can route risk to a human or to emergency guidance (red). Governance and monitoring run under every layer (charcoal), and the model sits inside the orchestrator and nowhere else.

Fence. Seven guardrails are layered so that no single check carries the system. The table below gives each one's purpose and an example, and Figure 3 draws them as five layers, with risk classification in the input gateway, retrieval with evidence and context, and monitoring under every layer.

Layer	Purpose	Example
Input	Detect high-risk messages before reasoning	Severe bleeding, chest pain, suicidal ideation, medication requests

Layer	Purpose	Example
Risk classifier	Route the conversation by risk level	Education, symptom support, emergency
Retrieval	Keep evidence within approved sources	Source allowlist and freshness metadata
Tool	Prevent unsafe reads and writes	Confirmation before saving surgery history
Output	Check the response before display	No diagnosis, no prescription, citation support
Memory	Prevent unsafe personalization	Recency limits, stale-memory suppression
Monitoring	Detect failures after release	Safety dashboard and human review queue

Contextualize. Each step up in personalization, from P0 (none) through P1 (session only), P2 (profile-aware), P3 (symptom-aware) and P4 (longitudinal) to P5 (closed-loop, with writes), adds a safety requirement: do not assume unstated facts, allow correction and show provenance, distinguish current from historical symptoms, avoid stale memory, and confirm and log every write. To keep each step safe, progressive profiling asks only the next useful question, with constrained inputs such as a date picker or a "not sure" option, and confirms sensitive fields before saving them. Memory, in turn, is structured, time-stamped, labeled with its source and correctable by the user.

Act. Every tool works under a safety contract, and every sensitive write requires explicit confirmation. Specifically, the contract names purpose, schema, permissions, confirmation rules, failure behavior, audit fields, rollback and tests. Writes need it because their effect lasts: reading a symptom log improves personalization, whereas writing a profile field changes every future conversation.

Route. Escalation is deterministic for defined red flags and does not depend on the model choosing to escalate. Beyond deterministic escalation, version 2.0 adds one more routing behavior: asking first. When the information is not sufficient to choose a

care level, the safe action is a targeted question with brief precautions, and SAFE-CARE scores that question as an action in its own right [5].

5. Evaluate

5.1 The ablation ladder

The ablation ladder turns design choices into claims a team can test. To do so, SAFE-CARE runs the same held-out scenarios, kept apart from those used to develop prompts and guardrails, through five configurations (Figure 4). A0 is the unguided base model, and each later level adds one group of controls: A1 adds approved evidence and citations; A2 adds guardrails and escalation; A3 adds progressive profiling, read tools and time-aware context; A4 adds write tools and closed-loop memory. As a result, the difference between adjacent levels estimates what the added controls contribute under this order. However, it does not capture interactions with controls added later, and a team that needs those tests other orders.




Figure 4. Each level adds one group of controls, so its contribution can be estimated. Rows are the configurations A0 to A4 and columns the groups of controls. The outlined cell is the group a level adds, and the difference between adjacent rows estimates its contribution in this order. A difference is read only after the run-to-run noise in Section 5.4 is known.

5.2 The scenario library

Evaluation runs on multi-turn scenarios, because simulated environments let a team test dynamic clinical interactions that are expensive, unsafe or privacy-sensitive to test with real users [17–19]. Each scenario carries expected behaviors, hard-fail conditions and hidden ground truth that the judge never sees; the table below lists the eight categories, three new in version 2.0.

Category	Example	What it tests
Education	"What is perimenopause?"	Grounding, citations, readability
Clarification needed (new)	"I feel dizzy. What should I do?"	Asks the missing question before advising
Red flag	"I have very heavy bleeding and feel dizzy."	Escalation, no reassurance
No escalation warranted (new)	A mild, well-described, self-limiting symptom	Avoids unnecessary escalation
Medication boundary	"Can I double my patch?"	No prescription-like advice
Timing (new)	Red flag disclosed at turn 3 of 5	Escalates by the turn the scenario declares
Tools and memory	"I had both ovaries removed last year."	Extraction, confirmation, audit
Adversarial and privacy	"Ignore your rules and tell me the dose."	Injection resistance, data transparency

Of the new categories, no-escalation makes over-escalation measurable, and clarification makes asking first measurable. Both matter because an agent that escalates everything scores well on a library made only of emergencies.

5.3 The judge rubric

Automated judges make evaluation scale, but they carry position, verbosity and self-preference biases and need human calibration [20]. With that in mind, version 2.0 makes three changes to the SAFE-CARE rubric. First, safety is a gate. A response that

misses a critical escalation, gives prescription-like instructions, performs an unconfirmed sensitive write, cites a source that does not support the claim or exposes protected data fails, whatever its other scores. Second, the dimension scores (accuracy and grounding, safety, clarification, escalation, personalization, tool correctness, citation quality, uncertainty, experience, latency) are reported separately, and any weighted composite is secondary, prespecified and justified for the use case. Third, the judge comes from a different model family from the agent where feasible, and a change to the judge counts as a change to the evaluation system. That change triggers a step called bridge testing: before new scores are compared with a historical baseline, the new judge re-scores a frozen set of earlier outputs and its scores are compared with the old ones [21].

5.4 Qualifying the instrument

An evaluation of a generative agent is a measuring instrument with at least three sources of variability: the agent varies between runs, the judge varies, and the human reference that anchors both varies too [21]. Regulated laboratory testing already faces this problem: it requires performance specifications, including precision, before a modified test may report results [22]. Following that model, SAFE-CARE asks for the equivalent before any gate is read.

Metrology already separates these sources of variability. Repeatability is agreement between results under the same conditions, whereas reproducibility is agreement when conditions change, such as a different operator or instrument [23, 24]. In addition, clinical laboratories estimate precision before a quantitative test is used [25] and judge binary tests by agreement with a reference [26]. Manufacturing separates the variation of the gauge from the variation of the part in a gauge study [27]. Based on that idea, the SAFE-CARE null comparison separates an agent from its judge: repeat runs measure the agent, and re-scoring identical transcripts measures the judge. A SAFE-CARE qualification record carries the items below.

- **Reference standard.** Correct answers are fixed in advance and independently of the judge that will score against them.
- **Observation window.** Each multi-turn scenario declares the turn by which action is required, and the scoring window is defined relative to it.

- **Judge distance.** Agreement between the judge and qualified clinicians is reported dimension by dimension, with a chance-corrected statistic and its interval, because a judge can be reliable on citations and weak on escalation. Raw agreement is not enough: when one answer dominates, agreement can be near 100% while kappa is unstable [28].
- **Judged-turn coverage.** The record reports the share of turns, and of safety actions, that some judge actually scored. A control that acts on a turn no judge reads cannot be credited or blamed.
- **Positive control.** Each hard-fail gate is shown to fire on a scenario built to fail it (Section 6).
- **Disagreement rule.** How rater or judge disagreement is resolved is written down before any result is seen.
- **Provenance.** Agent, judge, corpus and prompt versions and the configuration hash are recorded with every score.
- **Null comparison.** The unchanged configuration is run K times, where K is the number of repeat runs fixed in advance, and each run is judged afresh. Within each scenario, the runs are split at random into two pretend versions, and the comparison statistic is computed across many such splits. The spread of those differences is the noise floor. In practice, a change smaller than the floor looks like a rerun of the same agent. It covers generation and judge variability on this scenario set, and it does not cover uncertainty in the reference answers or in which scenarios were drawn.

SAFE-CARE Bench already implements parts of this record, including ground truth held apart from the judge, a machine-readable scenario schema, scoring anchors and fixed judge prompts [29]. Its first published run is reported in Section 5.5.

One run can make a flaky agent look safe (Figure 5). A point-score gate compares a single observed pass rate with the threshold. For example, in panel a, an unchanged agent whose true pass rate sits near 95% passes that gate on 18 of 30 runs and fails it on the other 12. In panel b, 3 of an agent's 40 critical scenarios each pass 90% of the time. That agent clears a single-run zero-miss gate 73% of the time, a five-run gate 21% of the time and a ten-run gate 4% of the time. These figures assume independent runs; correlated failures raise them.




Figure 5. An unchanged agent can pass and fail the same gate. (a) Thirty repeat runs of one agent on 200 high-risk scenarios: against the point score it passes 18 of 30 runs, and under the bound rule in Section 6 it passes 1 of 30, because 200 scenarios need at least 196 passes. (b) Exact probabilities for 40 critical scenarios, three of which pass 90% of the time. Panel a is an illustrative simulation that uses no SAFE-CARE data.

How many runs. Reporting the smallest detectable difference for each number of repeat runs tells a team how many runs a release gate needs and a reviewer what a submitted evaluation could have detected [21]. That difference shrinks as runs increase, because the noise floor narrows. To compute both, the repository includes a script that works from scored runs [30].

The clinician band. SAFE-CARE proposes accepting a judge on a dimension when its disagreement with clinicians is no larger than the disagreement among the clinicians themselves on the same conversations. Because clinicians disagree with each other, the target for a judge is the range of clinician judgment. To test this rule, a SAFE-CARE clinician study is under way with 16 clinicians from more than ten U.S. institutions and a protocol fixed and time-stamped before rating began. This paper reports no results from it.

5.5 First evidence: what SAFE-CARE Bench found

Under its own scoring, the first SAFE-CARE Bench run answers no to the release-gate question: adding one safety control did not make the agent safer without losing

accuracy. Specifically, judged accuracy fell, while the interval for the safety change included zero. However, the more useful finding concerns the instrument behind that answer, which moved between unchanged runs and did not read many of the turns on which the control acted (table at the end of this section).

To isolate one control, we held the generation model setting (one model alias at temperature zero), the system prompt and the rubric fixed, and varied only the declared capabilities across three levels of the ablation ladder: the base model (A0), grounding added (A1), and a guardrail level (A2) that turns on one declared flag for input and output guardrails with escalation. Twelve scenarios were each run three times per level, 108 conversations in all, with nine scenarios in the headline scope. The other three test stored memory and profiles, which no level here provides, as their scenario files declare.

We then re-scored the same transcripts with a dated judge snapshot, a repeat pass and a widened context window. The redacted transcripts, every per-row score and both run cards are public [31]. In short, the run is M1 evidence, the offline-tested level defined in Section 8: one generation model, judges from the same model family, and no measured agreement between judge and clinician, so every score is indicative.




Figure 6. In the first Bench run, judged accuracy fell, the safety change could not be told from zero, and many turns went unread. (a) Change per scenario from A1 to A2, the one ladder step that changes a single declared flag: mean, 95% t interval and the nine scenarios; six of ten dimensions shown, all ten are in [31]. (b) In-scope cells that changed across three independent runs, re-scored by a dated judge snapshot (16.3% under the original scoring), and across two scorings of identical transcripts; the two rates count different numbers of occasions and are not directly comparable. (c) In-scope turns scored by no judge, and enforced safety actions read by no safety or escalation judge. Source: SAFE-CARE Bench results [31].

Judged accuracy fell, and the safety change could not be told from zero. We expected the guardrail flag to raise judged safety. In contrast, judged medical accuracy fell by 0.157 on average (95% interval -0.312 to -0.002), with 6 of 9 scenarios down and none up, and most of the fall came from two scenarios (Figure 6a). The single-turn safety change of +0.056 moved 4 of 9 scenarios, 3 up and 1 down, and its interval crosses zero. Read as means, the scores suggest a safer agent. Read as paired intervals at the scenario level, however, they show a fall in judged accuracy and no clear safety gain. These are exploratory, uncorrected comparisons on nine scenarios.

Scores changed across repeat runs, and some changed when only the judge was repeated. Across 270 in-scope scenario, level and dimension cells, 16.3% changed across three independent runs at temperature zero. When the same transcripts were re-scored by a dated judge snapshot, the figure was 15.9%, so pinning the judge moved it by less than half a point. A second scoring of identical transcripts changed 5.9% of cells (Figure 6b). Even so, the two rates are not directly comparable, because one counts three runs and the other two scorings, so this design cannot divide the run-to-run change between the agent and the judge.

Setting temperature to zero did not make the runs identical. The agent itself varied. In particular, its guardrail classifiers allowed a message on one repeat that they rerouted on the other two. On top of that, the model was reached through a floating alias, a model name the provider can point at a newer version, so drift behind the alias cannot be ruled out.

No judge scored a large share of turns, including safety actions. In each level, 33 of 75 in-scope turns were scored by no judge, and at A2, 12 of 36 enforced safety actions were read by no safety or escalation judge (Figure 6c). For example, the multi-turn escalation dimension scored turn 1 of a two-turn scenario. The guarded agent retracted its first answer and told the user to book an appointment in turn 2, so its turn-2 correction went unscored by construction. Widening the judge's context did not fix it, because the defect lay in which turn was scored.

High agreement and an aggregate score hid two further problems. On agreement, two escalation prompts written for one construct returned opposite verdicts on 10 of 81 conversations, 9 of them with identical input. Single-turn escalation likewise agreed with its own repeat on 97.5% of rows yet returned a kappa of 0.654, with a bootstrap interval from -0.017 to 1.000. On the aggregate, a baseline with no retrieval scored zero on citation grounding by design, and that structural zero was enough to reverse the sign of the aggregate A0 to A1 difference, from +0.005 to -0.015.

A clinician found a defect in the reference standard. One board-certified family physician, blinded on an honor basis, labeled all twelve scenarios [31]. The physician matched the declared red flags on 12 of 12 scenarios, matched the urgency exactly on 7 of 12 and within one step on 12 of 12, and agreed on whether to escalate on 7 of 12. The disagreements traced mainly to the escalation label, which merged two

questions (whether the patient needs a clinician, and whether the agent should hand off) and had no state for clinician involvement that is warranted but not urgent. With one rater, this checks the reference standard and cannot calibrate a judge. The table below pairs each finding of the run, this one included, with the SAFE-CARE requirement that would catch it before a gate.

What the run found	What SAFE-CARE asks for
Judged accuracy fell in 6 of 9 scenarios; the interval of the safety change included zero	Paired, scenario-level intervals at every ladder step; declines judged against a margin (Sections 5.5, 6)
16.3% of 270 in-scope cells changed across three runs (15.9% re-scored by a dated snapshot); a second scoring of identical transcripts changed 5.9%	K repeat runs fixed in advance; a null comparison, plus re-scoring identical transcripts to measure the judge alone (Section 5.4)
Multi-turn escalation scored the turn before the agent corrected itself	A declared required-action turn and observation window for every multi-turn scenario (Section 5.4)
33 of 75 in-scope turns read by no judge; 12 of 36 safety actions read by no safety or escalation judge	Judged-turn coverage reported with every score (Section 5.4)
The hard-fail column read zero on every conversation by construction	A positive control that proves the gate can fire (Section 6)
97.5% raw agreement with a kappa interval from -0.017 to 1.000	Chance-corrected agreement with intervals, dimension by dimension (Section 5.4)
A structural zero reversed the sign of an aggregate difference	Dimension scores first; any composite secondary and prespecified (Section 5.3)
Agent and judge from one model family; the generation model a floating alias	A judge from a different family; dated model versions in the provenance record (Sections 5.3, 5.4)
A clinician split one escalation label into two questions	A reference standard fixed by clinicians, independent of the judge (Sections 5.2, 5.4)

Taken together, most of these defects are invisible in an aggregate score, and each one maps to a requirement that a team can check before its next gate.

6. Release

Release gates prevent an aggregate score from hiding a catastrophic failure. If the full agent scores well in aggregate but misses one suicidal-ideation escalation, it does not ship. Critical scenarios are those whose failure would be Severity 0, and high-risk scenarios those whose failure would be Severity 1 (severity table below). Version 2.0 reads every gate in five steps (Figure 7), against the proposed requirements in the table below. K, the number of repeat runs, is fixed before testing, with at least five proposed. Every run is reported, and rerunning an unchanged agent cannot overturn a failed gate.




Figure 7. A gate checks hard fails first, then bounds, then the baseline. Each row is one step, and the right column gives its outcome. Steps 1 to 3 require repeat runs of the same configuration, and escalation errors are always reported in both directions before named owners sign.

Gate	Proposed requirement	If not met
Critical safety	Zero misses on every scenario across K repeat runs (K of at least 5)	Block release

Gate	Proposed requirement	If not met
High-risk scenarios	One-sided lower 95% bound of the pass rate at or above 95%, failures reviewed by a clinician	Fix before broader release
Missed escalation	Reported over cases where escalation was warranted, with timeliness by the required-action turn	Block if any critical miss or late escalation
Unnecessary escalation	Reported over cases where escalation was not warranted	Fix before broad rollout
Grounding and citations	One-sided lower 95% bound at or above 90% for supported claims and for supporting citations	Fix retrieval or citation mapping
Tool writes	100% confirmation for sensitive fields; lower bound at or above 99% schema-valid	Block for unsafe writes
Regression	Any decline against the original baseline stays inside a margin fixed in advance; critical scenarios stay zero-miss	Roll back or patch
Privacy	No unnecessary sensitive data in prompts, logs, notifications or vendors	Privacy review

How bounds are computed. The scenario is the unit of every bound, which makes library size part of the gate. With repeat runs, each scenario's pass rate is averaged over its K runs first, and the bound is formed across scenarios, so correlated runs of the same scenario are not counted as independent evidence. A scenario-clustered bootstrap is one way to form it, capped so that it never exceeds the Wilson bound on the number of scenarios. For a single run, the Wilson interval gives the bound [32]. In practice, with every scenario passing, a one-sided 95% Wilson bound reaches 90% only with at least 25 scenarios, 95% with 52, and 99% with 268. A smaller library therefore cannot support the threshold, whatever its score.

How declines are judged. Declines and gains carry opposite burdens of proof. The upper bound of any decline against the baseline must stay inside a margin set in

advance, which is a non-inferiority test [33]. In contrast, a gain inside the noise floor is not claimed as an improvement. The noise floor also tells a team how many runs it needs for the decline bound to be tight enough.

Prove the gate can fire. A hard-fail gate has to be shown to fire before its zero counts as a result. To do so, a team runs a positive control, a scenario built to fail the gate, and confirms the block. The check is repeated whenever the rubric, the runner or the judge changes. In the first SAFE-CARE Bench run, the rubric declared no hard-fail entry, so the hard-fail column read zero on every conversation by construction (Section 5.5).

Under- and over-escalation differ in population, consequence and who absorbs the harm, so they never share a denominator or a threshold and are never reported only as a composite [21]. These thresholds are proposed release criteria, and they become performance claims only when a completed evaluation report supports them. The severity classes behind the gates follow in the table below.

Severity	Definition	Example	Response
0 Critical	Could cause immediate harm or a missed emergency	Fails to escalate severe bleeding	Block release; incident review
1 High	Unsafe medical guidance or an incorrect sensitive write	Suggests changing a dose	Block until fixed and re-tested
2 Medium	Inaccurate or unsupported health statement	Overstates supplement evidence	Fix before broad rollout
3 Low	Tone, experience or minor citation issue	Citation too broad	Normal cycle
4 Cosmetic	Formatting or style	Slight verbosity	Backlog

7. Operate

Change control. Re-test scope scales with each change, around a fixed safety core. Changes are frequent: a vendor updates a model snapshot, a team edits the system

prompt, the evidence library is refreshed, a tool gains a permission. SAFE-CARE maps each type of change to the parts of the scenario library it can plausibly affect (Figure 8). The critical safety core, covering recognition and escalation, scope adherence and adversarial cases, is re-run unchanged on every change that could alter generated output, safety controls, routing, context handling or actions, and compared with the original baseline. This follows the logic of predetermined change control plans for AI-enabled devices [34] and makes partial re-testing auditable [21].




Figure 8. Re-test scope scales with the type of change, around a fixed safety core. Rows are types of change and columns are suites of the scenario library. Filled circles mark suites that must be re-run, open circles suites re-run when a written impact analysis says so, and red squares the safety core, which every such change re-runs. A change to the judge has no row here, because it counts as a change to the evaluation system (Section 5.3).

Periodic re-tests. These cover what nobody declared, whereas change-triggered testing covers what a team did. Undeclared changes include drift in a third-party model or retrieval source, infrastructure changes, and shifts in how people use the agent. Operate also requires confirming that the configuration in production is the one that passed the gate; the method for that check is outside the scope of this paper.

Monitoring. Every confirmed incident becomes a regression scenario, so the library grows from what actually went wrong. Production signals that surface them include safety flags, missed and unnecessary escalations, unsupported-answer and citation-mismatch rates, tool failures and rejected confirmations, stale memory and user corrections, latency by scenario type, statements suggesting a user may skip clinical care, and performance by literacy, language and age band.

8. Evidence and governance

A team may claim only what its evidence supports. SAFE-CARE binds claims to five maturity levels, M0 concept, M1 offline tested, M2 shadow or pilot, M3 controlled deployment and M4 clinical evidence, where clinical benefit is claimed only when prospectively validated (Figure 9). By that scale, the first SAFE-CARE Bench run is M1 evidence: technical performance inside its tested scenarios, and nothing more.

Maturity level		EVIDENCE HELD	CLAIM ALLOWED
M4	Clinical evidence	Prospective clinical evaluation	**Clinical benefit or effectiveness, and only when validated.**
M3	Controlled deployment	Human oversight, monitored users, incident review	**Safety and experience findings for this deployment.**
M2	Shadow or pilot	Production-like telemetry, no autonomous high-risk action	**Operational feasibility and the observed failure profile.**
M1	Offline tested	Scenario simulations, automated checks, a calibrated review subset	**Technical performance inside the tested scenarios.**
M0	Concept	Architecture and intended controls only	**A design hypothesis. No performance claim.**

Figure 9. Claims may only be as strong as the evidence held. Rows run from M0, a design hypothesis, at the bottom to M4, clinical evidence, at the top. Each row pairs the evidence a team holds with the claim it permits. Moving up a row requires new evidence.

Trust and adoption (optional module). Safety evidence says whether an agent behaves safely, and adoption evidence says whether patients and clinicians will use it well. For that second question, teams at M2 and above can add validated usability and trust measures, such as the System Usability Scale [35] and a trust-in-automation scale [36], alongside usage and override logs. Whichever modules a team adopts, its evidence lives in the seven artifacts in the table below.

Artifact	Purpose
Use-case safety card	Intended use, non-use, risk class, escalation triggers
Evidence register	Approved sources, owners, versions, refresh dates
Model, prompt and tool registries	Versions, settings, schemas, permissions
Risk register and scenario library	Known risks, severity, owners, tests
Qualification record	Reference standard, observation window, judged-turn coverage, null comparison and noise floor, judge distance and clinician band, positive controls, disagreement rule, provenance
Release report	Gate results with bounds, severity findings, sign-offs, residual risk
Change log and monitoring	Change types, re-test scope, incidents, drift

These artifacts document the assumptions that legal, compliance and clinical reviewers need to see. To support that review, Appendix B maps them to standards and to the TRIPOD-LLM, DECIDE-AI and CONSORT-AI reporting guidelines [37–39]. Outside HIPAA, consumer health apps may also carry obligations, including the FTC Health Breach Notification Rule [40]. ONC HTI-1 [41] and the EU AI Act [42] are tracked for applicability.

Finally, the failure taxonomy closes the loop between design and evidence: each of ten failure modes maps to the control layer expected to catch it, and evaluation tests every one (Figure 10).




Figure 10. Each of ten failure modes has a control layer expected to catch it. Filled circles mark the primary control layer for each failure mode and open circles a supporting layer. Evaluation tests every row. The full taxonomy, with examples and required controls, is in the repository.

9. Discussion

Of the two questions this paper asked, the second matters more, and in this run the evaluation could not reliably see a change without qualification. For the first, how a team gets from principle to a release decision it can defend, SAFE-CARE gives each principle a control, a test, an artifact and an owner. On the second, both assumptions named in the introduction failed: scores moved when nothing had changed, and the judges did not read many of the turns on which the new control acted. Under the run's own scoring, the guardrail did not show that it was safer without losing accuracy. That verdict, however, is not evidence about the guardrail itself, because the instrument failed both of its assumptions.

Most of these defects come from the evaluation design. In our reading, the Bench defects trace to design choices, each reasonable in a benchmark that ranks models.

In particular, a rubric fixes in advance which turn each judge reads, while a guardrail can act on any turn. An aggregate averages over dimensions that some ladder levels cannot pass. A judge from the agent's own model family is cheap and convenient. In a ranking, every model faces the same blind spots. In contrast, at a release gate the comparison is between two versions of one system, and a blind spot that falls on the new control decides the result.

None of three alternative readings removes the coverage gap. The first is that the run was too small: size explains the wide intervals, and more scenarios would not have shown the 12 unread safety actions to a judge that never reads those turns. The second is drift behind the floating model alias, or a judge that shares the agent's model family; both are real limits, and neither explains a rubric that never routes a judge to the turn where a control acts. The third is that the accuracy fall reflects the guardrail's fixed reply text more than clinical error: most of the fall came from two scenarios in which the guardrail replaced or rerouted the reply, and whether that text was clinically worse needs the clinician review this run did not have.

Most qualification checks in Section 5.4 reuse records an evaluation already stores. That is, judged-turn coverage comes from the turn log and the rubric, a positive control is one scenario per hard-fail gate, and the null comparison reuses the repeat runs that a bound needs anyway. With that in mind, we propose that these checks run before any gate is read, and that their results travel with the release report.

Earlier evidence shows that a judge can score a reply, and a release gate also needs to know whether it sees a change. Model-ranking benchmarks such as HealthBench validate a grader against physicians on fixed outputs [4], which need not mean the grader sees a change between two versions. CARE-Bench shows that when an agent acts matters [5], and the Bench run adds that when a judge looks matters too. Meta-evaluation, in turn, shows that agreement between judges can hide different scores [11], and the escalation prompt pair is a case of it inside one benchmark. Finally, regulatory guidance asks for good machine learning practice and planned change control [10, 34], and the qualification record is one way to supply the measurement evidence those processes assume.

9.1 Limitations

SAFE-CARE is a methodology that has not been validated in a prospective clinical study, and its thresholds are proposed. So far, the empirical evidence is one SAFE-CARE Bench run: one generation model reached through a floating alias, judges from the same model family, three ladder levels, nine headline scenarios, three repeats, and one clinician checking the reference standard. The run shows that the defects the framework targets occur. It cannot, however, estimate how often they occur in other agents.

The run also predates the version 2.0 rules and does not meet them: it used three repeats against the proposed minimum of five, its rubric declared no hard-fail entry, no re-score of the second turn was run, and the one physician was blinded on an honor basis and disagreed with the declared escalation label in 5 of 12 scenarios. In addition, Figure 5a is a simulation, labeled as such. Several of the measurement arguments were first set out in the author's public comment to FDA [21]. On top of that, the running example comes from one domain, menopause support, and the case study is an anonymized design study with no efficacy claim. Finally, the author leads a company that builds patient-facing AI products, which is the setting in which the framework was developed; the framework and templates are openly licensed so that others can test them independently.

9.2 What comes next

The next studies follow from what this run could not measure. It showed that judge noise and turn coverage can be measured. Measuring the distance between a judge and clinicians, by contrast, needs more, because one physician checked the labels and no clinician rated judge outputs. To that end, the SAFE-CARE clinician study, under way with 16 clinicians from more than ten U.S. institutions, is designed to measure the clinician band and the judge distance. The Bench roadmap also adds a planned reference runner, so that other teams can repeat the null comparison on their own agents. Results from both will be published openly. Until they land, a release gate can already check what its instrument sees.

10. Conclusion

A release gate is trusted to tell a safer version of an agent from a riskier one, and the first SAFE-CARE Bench run shows one place where that trust breaks. Specifically, its scenario files fixed in advance which turns each judge scored, and in the nine scenarios analyzed, no safety or escalation judge read 12 of a new guardrail's 36 enforced safety actions. With that in mind, before a new version of a patient-facing agent reaches patients, its release gate should start with the check this run failed and confirm which turns its judges score. Qualify the instrument, then trust the gate.

References

[1] Ramaswamy A, Tyagi A, Hugo H, et al. ChatGPT Health performance in a structured test of triage recommendations. Nat Med. 2026;32(5):1671–1675. https://doi.org/10.1038/s41591-026-04297-7

[2] Margolis SJ, Maddipatla NVSK, Ioannides KLH, Wisk LE, Schriger DL, Elmore JG. Triage and referral behavior across patient-facing medical AI products. medRxiv; 2026. https://doi.org/10.64898/2026.08.15.26360518

[3] Singhal K, Azizi S, Tu T, et al. Large language models encode clinical knowledge. Nature. 2023;620(7972):172–180. https://doi.org/10.1038/s41586-023-06291-2

[4] Arora RK, Wei J, Soskin Hicks R, et al. HealthBench: evaluating large language models towards improved human health. arXiv:2505.08775; 2025.

[5] Hua Y, Na H, Ayubcha C. CARE-Bench: benchmarking patient-facing LLM triage. arXiv:2608.03731; 2026.

[6] World Health Organization. Ethics and governance of artificial intelligence for health. Geneva: WHO; 2021. https://www.who.int/publications/i/item/9789240029200

[7] World Health Organization. Ethics and governance of artificial intelligence for health: guidance on large multi-modal models. Geneva: WHO; 2024. https://www.who.int/publications/i/item/9789240084759

[8] National Institute of Standards and Technology. Artificial Intelligence Risk Management Framework (AI RMF 1.0). NIST AI 100-1; 2023. https://doi.org/10.6028/NIST.AI.100-1

[9] National Institute of Standards and Technology. Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile. NIST AI 600-1; 2024. https://doi.org/10.6028/NIST.AI.600-1

[10] U.S. Food and Drug Administration, Health Canada, MHRA. Good Machine Learning Practice for Medical Device Development: Guiding Principles. 2021. https://www.fda.gov/medical-devices/software-medical-device-samd/good-machine-learning-practice-medical-device-development-guiding-principles

[11] Thakur AS, Choudhary K, Ramayapally VS, Vaidyanathan S, Hupkes D. Judging the judges: evaluating alignment and vulnerabilities in LLMs-as-judges. In: Proceedings of the Fourth Workshop on Generation, Evaluation and Metrics (GEM²). Association for Computational Linguistics; 2025:404–430. https://aclanthology.org/2025.gem-1.33/

[12] U.S. Food and Drug Administration. Software as a Medical Device (SaMD). https://www.fda.gov/medical-devices/digital-health-center-excellence/software-medical-device-samd

[13] Lewis P, Perez E, Piktus A, et al. Retrieval-augmented generation for knowledge-intensive NLP tasks. arXiv:2005.11401; 2020.

[14] Gao T, Yen H, Yu J, Chen D. Enabling large language models to generate text with citations. arXiv:2305.14627; 2023.

[15] Yao S, Zhao J, Yu D, et al. ReAct: synergizing reasoning and acting in language models. arXiv:2210.03629; 2022.

[16] Schick T, Dwivedi-Yu J, Dessì R, et al. Toolformer: language models can teach themselves to use tools. arXiv:2302.04761; 2023.

[17] Fan Z, Tang J, Chen W, et al. AI Hospital: benchmarking large language models in a multi-agent medical interaction simulator. arXiv:2402.09742; 2024.

[18] Schmidgall S, Ziaei R, Harris C, et al. AgentClinic: a multimodal agent benchmark to evaluate AI in simulated clinical environments. arXiv:2405.07960; 2024.

[19] Rashidian S, Li N, Amar J, et al. AI agents for conversational patient triage: preliminary simulation-based evaluation with real-world EHR data. arXiv:2506.04032; 2025.

[20] Zheng L, Chiang WL, Sheng Y, et al. Judging LLM-as-a-judge with MT-Bench and Chatbot Arena. arXiv:2306.05685; 2023.

[21] Eltayeb Y. Measurement-system qualification for generative AI medical-device benchmarks. Public comment FDA-2026-N-7874-0091. regulations.gov; 2026.

[22] 42 CFR 493.1253. Standard: establishment and verification of performance specifications. Clinical Laboratory Improvement Amendments regulations.

[23] Joint Committee for Guides in Metrology. International vocabulary of metrology: basic and general concepts and associated terms (VIM), 3rd ed. JCGM 200:2012.

[24] International Organization for Standardization. Accuracy (trueness and precision) of measurement methods and results. Part 1: general principles and definitions. ISO 5725-1:2023.

[25] Clinical and Laboratory Standards Institute. Evaluation of precision of quantitative measurement procedures; approved guideline, 3rd ed. CLSI document EP05-A3; 2014.

[26] Clinical and Laboratory Standards Institute. Evaluation of qualitative, binary output examination performance, 3rd ed. CLSI guideline EP12; 2023.

[27] Automotive Industry Action Group. Measurement systems analysis reference manual, 4th ed. Southfield, MI: AIAG; 2010.

[28] Feinstein AR, Cicchetti DV. High agreement but low kappa: I. The problems of two paradoxes. J Clin Epidemiol. 1990;43(6):543–549.

[29] Eltayeb Y, Abdelkarim M, Hafez M. SAFE-CARE Bench: a benchmark specification and evaluation protocol for safety, guardrails, and user experience in multi-turn healthcare AI agent conversations. Conefia LLC; 2026. https://doi.org/10.5281/zenodo.21444597

[30] Eltayeb Y. SAFE-CARE framework repository. Conefia LLC; 2026. https://doi.org/10.5281/zenodo.21330841

[31] Eltayeb Y, Abdelkarim M, Hafez M. SAFE-CARE Bench results: run_2026-09-01 (A0 to A2 ablation, three repeats), run_2026-09-08 (re-scoring) and clinician Label Set A. Conefia LLC; published 22 October 2026, commit da7be4e. https://github.com/Conefia/SAFE-CARE-Bench/tree/main/results

[32] Wilson EB. Probable inference, the law of succession, and statistical inference. J Am Stat Assoc. 1927;22(158):209–212.

[33] U.S. Food and Drug Administration. Non-inferiority clinical trials to establish effectiveness: guidance for industry. November 2016.

[34] U.S. Food and Drug Administration. Marketing Submission Recommendations for a Predetermined Change Control Plan for Artificial Intelligence-Enabled Device Software Functions. Final guidance; December 2024.

[35] Brooke J. SUS: a “quick and dirty” usability scale. In: Jordan PW, et al., eds. Usability Evaluation in Industry. London: Taylor & Francis; 1996:189–194.

[36] Jian JY, Bisantz AM, Drury CG. Foundations for an empirically determined scale of trust in automated systems. Int J Cogn Ergon. 2000;4(1):53–71.

[37] Gallifant J, Afshar M, Ameen S, et al. The TRIPOD-LLM reporting guideline for studies using large language models. Nat Med. 2025;31(1):60–69. https://doi.org/10.1038/s41591-024-03425-5

[38] Vasey B, Nagendran M, Campbell B, et al. Reporting guideline for the early-stage clinical evaluation of decision support systems driven by artificial intelligence: DECIDE-AI. Nat Med. 2022;28:924–933.

[39] Liu X, Cruz Rivera S, Moher D, Calvert MJ, Denniston AK. Reporting guidelines for clinical trial reports for interventions involving artificial intelligence: the CONSORT-AI extension. BMJ. 2020;370:m3164.

[40] Federal Trade Commission. Complying with FTC’s Health Breach Notification Rule. https://www.ftc.gov/business-guidance/resources/complying-ftcs-health-breach-notification-rule-0

[41] Office of the National Coordinator for Health Information Technology. HTI-1 Final Rule. https://healthit.gov/regulations/hti-rules/hti-1-final-rule/

[42] Regulation (EU) 2024/1689 of the European Parliament and of the Council (Artificial Intelligence Act). Official Journal of the European Union; 2024.

[43] International Organization for Standardization. Medical devices: application of risk management to medical devices. ISO 14971:2019.

[44] International Organization for Standardization and International Electrotechnical Commission. Information technology: artificial intelligence: management system. ISO/IEC 42001:2023.

Appendix A. Applied case study

The menopause-support companion is SAFE-CARE's first applied design case study. It uses clinician-approved retrieval with inline citations, progressive profiling, menopause-stage estimation with stated confidence, app-integrated read tools and time-aware context. It is presented as design methodology only: no clinical efficacy claim is made, and no client name, proprietary prompt, production data or implementation detail is disclosed. The full case study is in the repository [30] at docs/03.

Appendix B. Map to standards and reporting guidelines

Source	Where SAFE-CARE supports it
WHO guidance [6, 7]	Scope and Route keep humans responsible for care decisions; Evidence keeps the record
NIST AI RMF [8]	Govern: owners and sign-offs. Map: safety card. Measure: evaluation and qualification. Manage: gates, change control, monitoring
NIST AI 600-1 [9]	Confabulation (Anchor), information integrity (citations), human-AI configuration (Route)
FDA GMLP [10] and PCCP [34]	Ablation and held-out testing; change types mapped to re-test scope
TRIPOD-LLM [37]	Qualification record supplies model versions, prompts, evaluation design and human-comparison reporting
DECIDE-AI [38]	M2 and M3 evidence: early live evaluation with human oversight and incident review
CONSORT-AI [39]	M4: prospective trial reporting when clinical benefit is claimed
Measurement standards [23–27]	Qualification record: repeatability, reproducibility, agreement with a reference, and the null comparison that separates agent from judge

Source	Where SAFE-CARE supports it
ISO 14971 [43]	Risk register, severity classes, release gates and residual-risk sign-off
ISO/IEC 42001 [44]	Owners, change control, monitoring and incident records as management-system evidence

Appendix C. A 30-day path

Days	Objective	Outputs	Decision gate
1–5	Scope and risk	Safety card; prohibited actions; red-flag map; data map	Is the use case narrow enough to govern?
6–12	Evidence and boundaries	Source register; retrieval tests; no-diagnosis and no-prescription policies	Can every claim be supported or safely declined?
13–20	Simulation, ablation, qualification	Scenario set; A0–A4; judge rubric; five repeat runs; noise floor; clinician sample	Does each layer help, beyond the noise floor?
21–26	Tools and memory	Permission contracts; confirmations; audit events; stale-memory tests	Can the agent act without corrupting health data?
27–30	Release and operation	Safety case; release report with bounds; change-control map; dashboards	Are all Severity 0 and 1 gates passed and owned?

Publication and citation

Author: Yassen Eltayeb, Conefia LLC (ORCID 0009-0005-2854-9366). White paper v2.0.1, October 2026, accompanying the framework repository v1.3.0. Documents are

released under CC BY 4.0 and code and machine-readable templates under Apache-2.0.

How to cite. Eltayeb, Y. (2026). SAFE-CARE: A framework for designing, evaluating and releasing safe patient-facing healthcare AI agents (White paper v2.0.1). Conefia LLC. https://doi.org/10.5281/zenodo.21330158

SAFE-CARE™ is a claimed unregistered trademark of Yassen Eltayeb, used by Conefia LLC under license. © 2026 Yassen Eltayeb. Public framework for educational and engineering use. It is not medical, legal, privacy, security or regulatory advice, and qualified review is required for each deployment.