

2018/19 Semester 1
Object Oriented Programming with Applications
Problem Sheet 3 - Wednesday 17th October 2018¹

Exercise 3.1. You might have noticed that the following code for computing the Fibonacci sequence fails (or takes very long to run) for $n > 100$.

```
static ulong NumberWithoutHashtable(ulong n)
{
    if (n == 0)
        return 0;
    else if (n == 1)
        return 1;
    else
        return NumberWithoutHashtable(n - 1) + NumberWithoutHashtable(n - 2);
}
```

Use either a `Hashtable` or another data structure to store already computed values so that you can calculate the Fibonacci numbers even for large n .

Exercise 3.2. The linear least squares problem consists of finding

$$\hat{\beta} = \arg \min_{\beta \in \mathbb{R}^n} |y - X\beta|^2,$$

where X is a given $m \times n$ matrix such that $X_{i1} = 1$, $i = 1, \dots, m$ and y is a column vector in \mathbb{R}^m . It can be shown (using calculus) that the solution is given by solving the linear system

$$(X^T X)\hat{\beta} = X^T y.$$

Use `MathNet.Numerics` linear algebra methods to complete the class below which is suggested for solving the problem

```
using System;
using MathNet.Numerics.LinearAlgebra;

class LinearLeastSquares
{
    private Matrix<double> X;
    private Vector<double> y;

    public LinearLeastSquares(Matrix<double> dataX, Vector<double> dataY)
    {
        y = dataY;
        int n = dataX.ColumnCount + 1;
        int m = dataX.RowCount;
        X = Matrix<double>.Build.Dense(m, n);
        X.SetColumn(0, Vector<double>.Build.Dense(m, 1.0));
        for (int j = 1; j < n; ++j)
            X.SetColumn(j, dataX.Column(j-1));
    }

    public Vector<double> CalculateCoefficients()
    {
        }
    }
}
```

Here you need to write code to solve $(X^T X)\hat{\beta} = X^T y$ and return $\hat{\beta}$.

¹Last updated 9th October 2018

Now test it by adding the following.

```
class MainClass
{
    public static void Main (string[] args)
    {
        double[,] x = {{ 1.0} , {2.0}, {3.0}, {4.0} };
        Matrix<double> dataX = Matrix<double>.Build.DenseOfArray (x);

        double[] y = {6, 5, 7, 10};
        Vector<double> dataY = Vector<double>.Build.DenseOfArray (y);

        LinearLeastSquares lls = new LinearLeastSquares (dataX, dataY);
        Vector<double> beta = lls.CalculateCoefficients ();
        Console.WriteLine (beta);
    }
}
```

Exercise 3.3. Use the lecture slides on `System.Numerics` and Excel integration with ExcelDNA to create two new Excel functions:

1. `public static double ComplexLogarithmRealPart(double realPart, double imaginaryPart)` **which returns, for $z \in \mathbb{C}$, $\Re(\ln(z))$ i.e. the real part of complex logarithm,**
2. `public static double ComplexLogarithmImaginaryPart(double realPart, double imaginaryPart)` **which returns, for $z \in \mathbb{C}$, $\Im(\ln(z))$ i.e. the imaginary part of complex logarithm.**

For a real number $z = \exp(i\theta)$ use these functions to plot the real and imaginary parts of the complex logarithm for $\theta \in [0, 2\pi]$.