Intelligent Irrigation System for Low-cost Autonomous Water Control in Small-scale Agriculture

Intel-IrriS

Building the Intel-IrriS IoT platform
Part 1: soil sensor device

PRIMA
PARTNERSHIP FOR RESEARCH AND INNOVATION IN THE MEDITERRANEAN AREA

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham
Université de Pau, France

UNIVERSITÉ DE PAU ET DES PAYS DE L'ADOUR

LIUPPA

WAZIup
IoT – from idea to reality
WAZIhub

Review: Technology components

Sensor part

Intel-IrriS



LPWAN

Control part



Embedded Database

Software updates

Embedded User Interface

Review: Low-cost sensors

Sensor part

Intel-IrriS



- Build on low-cost, low-power IoT expertise
- Increase accuracy of low-cost sensors by automatic and remotely controlled procedures for advanced calibration
- Enable deployment of several complementary low-cost sensors
- Include agricultural models / knowledge with corrective & predictive analytics

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Review: Smart embedded control

- Build on low-cost embedded & open IoT gateway expertise
- Implement the “Intelligent Irrigation in-the-box” with "plug-&-sense" approach
- Model complex water-soil-plant interaction
- Embed Decision Support System (DSS) and disruptive Artificial Intelligence (AI)
- Integration of various knowledge streams
- Fully autonomous

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Review: Starter-kits

- "Intelligent Irrigation in-the-box", "plug-&-sense"
- At least 100 starter-kit will be distributed

Soil sensor: electronic parts





RFM95W (868MHz)
RFM96W (433MHz)
NiceRF SX1262 (868MHz)
NiceRF SX1268 (433MHz)
NiceRF SX1280 (2.4GHz)

PCB mount
or pigtail

SMA
female









optional

SMA
male

Soil sensor: casing parts & integration



proof-of-concept



Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Assembling PCB board







Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Get a case for outdoor usage





Here, it is an IP65 box which dimension is 115 x 65 x 40mm.

First, drill a 7mm hole for the SMA female connector.

Installing the PCB board







Connect together switch "off" pin (left) with BAT +
Connect switch "on" pin (middle) to board's VCC
Connect BAT – to board(s GND
Toggling the switch will then power the board

Putting it altogether



- Here we use a 1xAA battery pack
- Fix the battery pack with double-side tape
  e.g. those used to fix mirrors on wall
- Then we use a 3.6V Lithium battery

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Installing your own cable gland





- Drill a hole depending on the gland diameter
- Here PG7, 12mm, so a hole of 13mm

Last step: connect the SEN0308





Insert sensor's wire through cable gland
Connect SEN0308 wires to board:
- **VCC to board's A1**
- **GND to board's GND**
- **Signal to board's A0**

Getting the software: Arduino IDE





Install latest version of Arduino IDE from
https://www.arduino.cc/en/software

Getting the software: Intel-IrriS code



On your computer, create a `sketch` folder

Then download the whole repository as ZIP file

Unzip the file and copy the whole `Arduino` folder into your `sketch` folder

The entire Intel-IrriS GitHub repository is hosted here
https://github.com/CongducPham/PRIMA-Intel-IrriS

GitHub

Setting your Arduino IDE



Run Arduino IDE, open Preferences
Indicate your `sketch` folder in Sketchbook location

Compiling the soil sensor code

Open the Intelirris_Soil_Sensor sketch

Select the ProMini board, 3.3V and 8MHz version

Then click on the "verify" button

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Connecting with an FTDI cable



Some clone version, check the VCC pin





Original Sparkfun version



For the ProMini, you need to have an FTDI breakout cable working at 3.3v

Check the VCC pin position and make it to correspond to the VCC pin of the FTDI breakout.

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Select serial port for uploading



After connecting the cable to your computer/laptop USB port, try to find the serial port

If you don't find it, you may need to install specific drivers

https://learn.sparkfun.com/tutorials/how-to-install-ch340-drivers/all

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Uploading to your board

Click on the "upload" button



And wait until upload is completed



Checking that device is operational



- Open serial monitor
- Set baud rate to 38400
- See output from board
- Check that transmission is OK

Generic & cyclic behavior

2 soil sensors can be attached



Physical sensor management



Arduino Pro Mini @3.3V

Activity duty-cycle, low power

AES encryption

Long-range transmission

Logical sensor management



Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Reducing power consumption



- Remove the power LED by just clipping it off with some wire cutters
- Remove the voltage regulator with a small plier
- Only inject up to 3.6V through the VCC pin
- 5uA in deep sleep mode



https://www.the-diy-life.com/making-an-ultra-low-power-arduino-pro/

Power consumption deep sleep



Measured below 5uA in deep sleep, between 2 active periods with transmissions

Expected autonomy with 1 transmission / hour:

over 2 years with either 2 AA batteries or 1 AA 3.6V Lithium battery

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham