Intel-IrriS

PRIMA
PARTNERSHIP FOR RESEARCH AND INNOVATION
IN THE MEDITERRANEAN AREA

Intelligent Irrigation System for Low-cost Autonomous Water Control in Small-scale Agriculture

Intel-IrriS

Building the Intel-IrriS LoRa IoT platform
Part 3: the INTEL-IRRIS starter-kit

PRIMA
PARTNERSHIP FOR RESEARCH AND INNOVATION IN THE MEDITERRANEAN AREA

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham
Université de Pau, France

UNIVERSITÉ DE PAU ET DES PAYS DE L'ADOUR

LIUPPA

WAZIup
IoT – from idea to reality
WAZIhub

INTEL-IRRIS starter-kit

- "Intelligent Irrigation in-the-box", "plug-&-sense"



Preparing the starter-kits at UPPA

This non-technical video shows the preparation of the kits
https://youtu.be/5nznRcIoe40

Soil sensor device

Fully assembled

Packaging in enclosure

To be assembled

Gateway (WaziGate)

Fully assembled LoRa radio hat



To be assembled





An optional OLED screen can be connected to the radio hat

First round of starter-kits

- 1 fully assembled & configured soil sensor device
- 4 soil sensor devices to be assembled & configured
- 1 fully assembled radio LoRa hat
- 4 radio LoRa hats to be assembled
- INTEL-IRRIS WaziGate image to be downloaded & flashed
- **IMPORTANT**
  - 1 starter-kit= 1 soil sensor + 1 INTEL-IRRIS WaziGate gateway
  - 1 starter-kit / farm to be deployed and tested
  - The WaziGate is only pre-configured for 1 soil sensor / farm
  - If there are several soil sensors in a farm, see advanced configuration

Assembling starter-kit

Algeria (UORAN1), Morocco (ENSA Safi)

- Soil sensor device
  - Tutorial slides on building & assembling the outdoor LoRa IoT soil sensor device
  - Video n°1. YouTube tutorial video showing how to build the IoT microcontroller platform for the LoRa IoT soil sensor device
  - Video n°2. YouTube tutorial video showing how to build the outdoor LoRa IoT soil sensor device
  - Video n°3. YouTube tutorial video showing how to wire the SEN0308 capacitive sensor
- INTEL-IRRIS WaziGate
  - Tutorial slides on preparing the INTEL-IRRIS WaziGate IoT gateway
  - Video n°4. YouTube tutorial video demonstrating the INTEL-IRRIS soil sensor device & WaziGate framework
  - Download SD card image and flashing SD card: Video n°4 at t=124s

Checking WaziGate

- Power the WaziGate, no Internet is required
- Connect to the WaziGate's WiFi with a smartphone
- Open http://wazigate.local or http://10.42.0.1



Look at Video n°4 at t=239s

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Testing transmission to WaziGate

- Test with the fully assembled soil sensor device
  - Toggle switch on the soil sensor device to get data transmission
  - Check reception of data on WaziGate's dashboard



Look at Video n°4 at t=331s

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Transmission to WaziGate

Parameters for
WaziGate (default in red)

SF12BW125
868.1MHz | 433.175MHz
Node id is 26011DAA
1 msg/60mins
1 sensor
XLPP data

This dedicated video will show all these steps, from connecting the SEN0308 to testing transmission to the WaziGate
Video n°4: https://youtu.be/j-1Nk0tv0xM

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Soil sensor: connecting antenna





Be sure to connect the matching antenna
Here, SMA female with SMA male antenna
Need to screw the antenna in <u>all the way</u>

The antenna junction is critical because this is where rain water can come in

Waterproofing the antenna junction



Even when the antenna is screwed in all the way, there might still be a gap

Even with no apparent gap, it is necessary to waterproof the junction

Take an o-ring for that purpose, but do not take it too thick or too large!

Too thick: the antenna will not be screwed in all the way!

There are o-ring for SMA connector but the gap size is an indication

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Do not have or can not use o-ring?

Maybe the gap is too big? Use silicon joint sealant

First, screw in the antenna <u>all the way</u>

Put small amount of silicon around the antenna junction (use a flat screw driver or other flat tool)

Use a <u>wet</u> toothpick to finish and clean the silicon all around the antenna junction



Even with o-ring, if you have a doubt, add silicon!

check especially the back side

Configure soil device for WaziGate

Be sure that

`#define TO_WAZIGATE`

is uncommented

Configuring for EU433 band

If you use the EU433 band

Edit SX127X_RadioSettings.h

comment

```
//#define BAND868
```

and uncommented

```
#define BAND433
```

Uploading to your board



Click on the "upload" button



And wait until upload is completed



Checking that device is operational



- Open serial monitor
- Set baud rate to 38400
- See output from board
- Check that transmission is OK

Deploying the starter-kit

- Calibrate the soil sensor device
  - See dedicated slides/videos
- Install the soil sensor device in the field
  - See dedicated slides/videos
- Install the WaziGate in the farmer's office/home/premise
  - Just power the WaziGate, no Internet is required
  - Test access to WaziGate's dashboard with farmer's smarphone
- Test correct data reception on WaziGate
  - Toggle switch on the soil sensor device to get data transmission
  - Check reception of data on WaziGate's dashboard

Advanced configuration

change soil sensor device address

- Only if you need to have several soil sensors in a single farm:
  change the device address in the soil sensor Arduino code



Default address is

```
{0x26, 0x01, 0x1D, 0xAA};
```

Just increase the last byte

```
{0x26, 0x01, 0x1D, 0xAB};
```

Compile and upload the code to the soil sensor device

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Advanced configuration

create a new sensor device on WaziGate

- Here is the configuration of the default soil sensor device
- Create a new sensor: INTEL-IRRIS Soil Sensor 2





Advanced configuration

configure LoRaWAN parameters

- Select the new sensor and make it as LoRaWAN device



- Set the new address, matching the one of the Arduino code: 26011DAB
- keep same encryption keys
- Select XLPP as codec



Advanced configuration

configure sensor name

- Power on the new soil sensor device to trigger data transmission
- Refresh the WaziGate dashboard, the new data should appear



- Click on the "temperatureSensor 0" and then rename it



Advanced configuration

configure sensor kind

- Change de Sensor kind to "Raw value from SEN0308"



- The dashboard now displays correctly the new sensor