Intel-IrriS

PRIMA
PARTNERSHIP FOR RESEARCH AND INNOVATION
IN THE MEDITERRANEAN AREA

Intelligent Irrigation System for Low-cost Autonomous Water Control in Small-scale Agriculture

Intel-IrriS

Building the Intel-IrriS LoRa IoT platform
Part 1: soil sensor device

PRIMA
PARTNERSHIP FOR RESEARCH AND INNOVATION IN THE MEDITERRANEAN AREA

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham
Université de Pau, France

UNIVERSITÉ DE PAU ET DES PAYS DE L'ADOUR

LIUPPA

WAZIup
IoT – from idea to reality
WAZIhub

Review: Technology components

Sensor part

Intel-IrriS



LPWAN

Control part



Embedded Database

Software updates

Embedded User Interface

Review: Low-cost sensors

Sensor part

Intel-IrriS



- Build on low-cost, low-power IoT expertise
- Increase accuracy of low-cost sensors by automatic and remotely controlled procedures for advanced calibration
- Enable deployment of several complementary low-cost sensors
- Include agricultural models / knowledge with corrective & predictive analytics

Review: Smart embedded control

- Build on low-cost embedded & open IoT gateway expertise
- Implement the “Intelligent Irrigation in-the-box” with "plug-&-sense" approach
- Model complex water-soil-plant interaction
- Embed Decision Support System (DSS) and disruptive Artificial Intelligence (AI)
- Integration of various knowledge streams
- Fully autonomous

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Review: Starter-kits

- "Intelligent Irrigation in-the-box", "plug-&-sense"
- At least 100 starter-kit will be distributed

Soil sensor: electronic parts





RFM95W (868MHz)
RFM96W (433MHz)
NiceRF SX1262 (868MHz)
NiceRF SX1268 (433MHz)
NiceRF SX1280 (2.4GHz)

PCB mount
or pigtail

SMA
female









optional

SMA
male

Soil sensor: enclosure & integration

proof-of-concept



Assembling the PCB board





This dedicated video will show how to solder all the components
https://youtu.be/3jdQ0Uo0phQ



Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Reducing power consumption



- Remove the power LED by just clipping it off with some wire cutters
- Remove the voltage regulator with a small plier
- Only inject up to 3.6V through the VCC pin
- Below 5uA in deep sleep



https://www.the-diy-life.com/making-an-ultra-low-power-arduino-pro/

Power consumption in deep sleep



Measured below 5uA in deep sleep, between 2 active periods with transmissions

Expected autonomy with 1 transmission / hour is over 2 years with either 2 AA batteries or 1 AA 3.6V Lithium battery

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Get an enclosure for outdoor usage

Here, it is an IP65 box which dimension is 115 x 65 x 40mm
https://www.gotronic.fr/art-boitier-abs-etanche-g304m-17977.htm

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Drilling machine and drilling bits

At least a simple cordless drilling machine is necessary
If you have a (small) bench drilling machine it is of course better
Then you need an assortment of drilling bits for metal, not for wood nor concrete! Here, you will mainly need 7mm and 13mm bits
It is also interesting to have step drill bits

Drill a hole for the SMA connector





28mm for the right edge:
- measure from the flat side as the corner is round
9mm from the outside bottom
use a 7mm drill bit for metal, not for wood nor concrete!

Remove unwanted plastic part





we need to remove the plastic reinforcement part for this particular enclosure

use a flat cutter for instance to remove and smooth the inside part (a small plier can be used first to remove most of the part)

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Placing the PCB board



the PCB board can be placed, with the SMA connector going through the hole

both 2-AA (left) and 1-AA (right) battery holder can be used

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Drill a hole for the external switch





20mm for the right edge:
- measure from the flat side as the corner is round
9mm from the outside bottom
use a 7mm drill bit for metal

Drill a hole for the cable gland



a step drill bit can be used
first, drill to 12mm
then use a 13mm drill bit



41mm for the right edge:
- measure from the flat side as the corner is round

9mm from the outside bottom

use a 13mm drill bit for metal

Remove unwanted plastic part



again, we need to remove the plastic reinforcement part for this particular enclosure

use a flat cutter for instance to remove and smooth the inside part (a small plier can be used first to remove most of the part)

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Going for larger production





If you need to prepare many enclosures, it may be faster to first make an assembly jig (here a piece of metal) for marking the holes

But be sure to precisely align the edge of the jig with the edge of the enclosure

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Placing switch and cable gland





- test that everything is OK
- the switch has a water-proof cap

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Connecting switch, battery & board





Connect <u>together</u> switch "off" pin (left) with BAT +
Connect directly switch "on" pin (middle) to board's VCC
Connect directly BAT – to board(s GND
Toggling the switch to right will then power the board

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Putting it altogether



- Here we use a 1-AA battery pack
- Fix the battery pack with double-side tape
  e.g. those used to fix mirrors on wall
- Then we use a 3.6V Lithium battery

- This dedicated video will show
  how to build the outdoor soil device
  https://youtu.be/zcazzDbXvHk

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Last step: wire the SEN0308





Insert sensor's wire through cable gland
Connect SEN0308's wires to board:
- **VCC to board's A1**
- **GND to board's GND (there are 2 GND wires)**
- **Signal to board's A0**

The complete soil sensor device







Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Connecting antenna





Be sure to connect the matching antenna
Here, SMA female with SMA male antenna
Need to screw the antenna in <u>all the way</u>

The antenna junction is critical because this is where rain water can come in

Waterproofing the antenna junction



Even when the antenna is screwed in all the way, there might still be a gap

Even with no apparent gap, it is necessary to waterproof the junction

Take an o-ring for that purpose, but do not take it too thick or too large!

Too thick: the antenna will not be screwed in all the way!

There are o-ring for SMA connector but the gap size is an indication

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Do not have or can not use o-ring?

Maybe the gap is too big? Use silicon joint sealant

First, screw in the antenna <u>all the way</u>

Put small amount of silicon around the antenna junction (use a flat screw driver or other flat tool)

Use a <u>wet</u> toothpick to finish and clean the silicon all around the antenna junction



Even with o-ring, if you have a doubt, add silicon!

check especially the back side

Getting the software: Arduino IDE





Install latest version of Arduino IDE from
https://www.arduino.cc/en/software

Getting the software: Intel-IrriS code



On your computer, create a `sketch` folder

Then download the whole repository as ZIP file

Unzip the file and copy the content of `Arduino` folder into your `sketch` folder

The entire Intel-IrriS GitHub repository is hosted here
https://github.com/CongducPham/PRIMA-Intel-IrriS

GitHub

Setting your Arduino IDE



Run Arduino IDE, open Preferences
Indicate your `sketch` folder in Sketchbook location

Compiling the soil sensor code



Open Intelirris_Soil_Sensor sketch – no change required

Select the ProMini board, 3.3V and 8MHz version

Then click on the "verify" button

Connecting with an FTDI cable



Some clone version, check the VCC pin





Original Sparkfun version



For the ProMini, you need to have an FTDI breakout cable working at 3.3v

Check the VCC pin position and make it to correspond to the VCC pin of the FTDI breakout.

Select serial port for uploading

After connecting the cable to your computer/laptop USB port, try to find the serial port

If you don't find it, you may need to install specific drivers

https://learn.sparkfun.com/tutorials/how-to-install-ch340-drivers/all

Uploading to your board

Click on the "upload" button



And wait until upload is completed



Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Checking that device is operational



- Open serial monitor
- Set baud rate to 38400
- See output from board
- Check that transmission is OK

Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Generic & cyclic behavior

2 sensors can be attached

SEN0308: soil humidity
A0 (signal), A1 (pwr)

DS18B20: soil temperature
3 (signal), 4 (pwr)

Physical sensor management



Arduino Pro Mini @3.3V

Activity duty-cycle, low power

AES encryption

Long-range transmission

Logical sensor management



Prof. Congduc Pham
http://www.univ-pau.fr/~cpham

Transmission to non-LoRaWAN gateway

Default parameters

raw LoRa
SF12BW125
865.2 MHz
node id is 8
1 msg/30mins
1 sensor
ex: `\!SH1/750.50`

This dedicated video will show all these steps, from wiring the SEN0308 to testing transmission to the gateway
https://youtu.be/zcazzDbXvHk



Advanced options

- The `Intelirris_Soil_Sensor` sketch can
  - Drive SX127X, SX126X and SX128X LoRa chips
    - SX128X requires a dedicated PCB for NiceRF SX1280



  - Send AES 128-bit encrypted packet
  - Send uplink LoRaWAN packet (encrypted)
  - Receive downlink LoRaWAN packet
  - Can read additionally from a DS18B20 soil temperature sensor
  - Can read from a Watermark tensiometer sensor
  - Support WaziSense and WaziDev boards

With a Watermark sensor



with a Watermark sensor, the "pseudo-AC Short Pulse" method will be used – see https://www.irrometer.com/200ss.html
D6 and D7 will be used to alternating power the sensor
A0 will be used to read signal from sensor

PRIMA
PARTNERSHIP FOR RESEARCH AND INNOVATION
IN THE MEDITERRANEAN AREA

Intel-IrriS

Starter-kit

Wi Fi

Autonomous

Intelligent Irrigation

Plug-&-Sense

In-the-box