
J. Conor Schehl

<https://www.linkedin.com/in/conor-schehl>
<https://www.conorstech.xyz>

| Pflugerville, TX
| 512-541-5454
| schehljc@gmail.com

EDUCATION

Colorado School of Mines, Golden, CO - Bachelor of Science, Electrical Engineering

—Expected Graduation: May 2028

- GPA: 4.0
- Intent on a MS in Engineering concentrated on Integrated Circuits & Mixed-Signal Design

SKILLS

- **Hardware:** PCB Design (Altium Designer ECAD/EDA), Schematic Capture, STM32, SMD/SMT Soldering
- **Firmware:** Python, C/C++, Linux (Debian), STM32
- **General:** Microsoft Suite, Google Suite, Team Collaboration, Design Reviews, SolidWorks

EXPERIENCE

Formula Society of Automotive Engineers | Electrical Engineer | **September 2025 - Present**

- Collaborate with a multidisciplinary team to make formula-style racecars perform competitively at the collegiate level
- Design and assemble PCBs and Wire Harnesses to acquire telemetry, engine, and car data to maximize performance while adhering to safety regulations

Rosendin | Engineer Intern | **May 2026 - August 2026**

- Conducted thorough short circuit and arc flash analysis for power distribution systems, ensuring strict protocol and safety compliance with NEC and IEEE codes
- Planned system coordination and developed a disciplined approach to power management, fault isolation, and system reliability with ETAP and SKM

PROJECTS

Analog to Digital Converter Data Acquisition and Power Distribution Board, Mines Formula

- Architected a mixed-signal data acquisition board using an STM32 MCU and a dedicated 16-bit ADC communicating over SPI, implementing low-pass input filters for signal integrity
- Routed a power distribution network stepping a 12V input down through a buck converter and using LDO regulators to isolate 5V and 3.3V rails into analog and digital domains
- Engineered high-speed, impedance controlled differential pair traces for a 100Base-T Ethernet PHY for reliable, low latency communication with the Vehicle Control Unit

Custom STM32 Microcontroller Development Board, Mines Formula

- Architected a 4-layer development board with pin exposure for Arduino Shield compatibility and testing via Serial Communications like CAN, SPI, I²C, and UART
- Adhered to >80% power conversion efficiency (12V to 3.3V) using switching and linear regulators isolating the switching converter from sensitive analog traces to minimize EMI
- Routed differential pairs for USB 2.0 and CAN, while optimizing high-speed oscillator placement for minimizing EMI and maximizing clock stability

Power and Safety Circuit Latching Board, Mines Formula

- Designed an analog safety board utilizing relays, optocouplers, diodes, fuses, and MOSFETs to provide reliable voltage switching, galvanic isolation, and safe EV shutdown