

[Edit This Page](#)

# Reference

This section of the Kubernetes documentation contains references.

- [API Reference](#)
- [API Client Libraries](#)
- [CLI Reference](#)
- [Config Reference](#)
- [Design Docs](#)

## API Reference

- [Kubernetes API Overview](#) - Overview of the API for Kubernetes.
- [Kubernetes API Reference v1.17](#)

## API Client Libraries

To call the Kubernetes API from a programming language, you can use [client libraries](#). Officially supported client libraries:

- [Kubernetes Go client library](#)
- [Kubernetes Python client library](#)
- [Kubernetes Java client library](#)
- [Kubernetes JavaScript client library](#)

## CLI Reference

- [kubectl](#) - Main CLI tool for running commands and managing Kubernetes clusters.
  - [JSONPath](#) - Syntax guide for using [JSONPath expressions](#) with kubectl.
- [kubeadm](#) - CLI tool to easily provision a secure Kubernetes cluster.

## Config Reference

- [kubelet](#) - The primary *node agent* that runs on each node. The kubelet takes a set of PodSpecs and ensures that the described containers are running and healthy.
- [kube-apiserver](#) - REST API that validates and configures data for API objects such as pods, services, replication controllers.
- [kube-controller-manager](#) - Daemon that embeds the core control loops shipped with Kubernetes.
- [kube-proxy](#) - Can do simple TCP/UDP stream forwarding or round-robin TCP/UDP forwarding across a set of back-ends.

- [kube-scheduler](#) - Scheduler that manages availability, performance, and capacity.

## Design Docs

An archive of the design docs for Kubernetes functionality. Good starting points are [Kubernetes Architecture](#) and [Kubernetes Design Overview](#).

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 30, 2020 at 8:36 PM PST by [update ref link for v1.16 \(#18837\)](#) ([Page History](#))

# Standardized Glossary

---

[Create an Issue](#)

Page last modified on February 22, 2019 at 1:24 AM PST by [Make k8s.io/docs/home to support i18n \(#12570\)](#) ([Page History](#))

[Edit This Page](#)

# Kubernetes Issue Tracker

To report a security issue, please follow the [Kubernetes security disclosure process](#).

Work on Kubernetes code and public issues are tracked using [GitHub Issues](#).

- [CVE-related issues](#)

Security-related announcements are sent to the [kubernetes-security-announce@googlegroups.com](mailto:kubernetes-security-announce@googlegroups.com) mailing list.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on March 28, 2019 at 2:45 PM PST by [Update issues landing page \(#13503\)](#) ([Page History](#))

[Edit This Page](#)

# Kubernetes Security and Disclosure Information

This page describes Kubernetes security and disclosure information.

- [Security Announcements](#)
- [Report a Vulnerability](#)
- [Security Vulnerability Response](#)
- [Public Disclosure Timing](#)

## Security Announcements

Join the [kubernetes-announce](#) group for emails about security and major API announcements.

You can also subscribe to an RSS feed of the above using [this link](#).

## Report a Vulnerability

We're extremely grateful for security researchers and users that report vulnerabilities to the Kubernetes Open Source Community. All reports are thoroughly investigated by a set of community volunteers.

To make a report, submit your vulnerability to the [Kubernetes bug bounty program](#). This allows triage and handling of the vulnerability with standardized response times.

You can also email the private [security@kubernetes.io](mailto:security@kubernetes.io) list with the security details and the details expected for [all Kubernetes bug reports](#).

You may encrypt your email to this list using the GPG keys of the [Product Security Committee members](#). Encryption using GPG is NOT required to make a disclosure.

## When Should I Report a Vulnerability?

- You think you discovered a potential security vulnerability in Kubernetes
- You are unsure how a vulnerability affects Kubernetes
- You think you discovered a vulnerability in another project that Kubernetes depends on
  - For projects with their own vulnerability reporting and disclosure process, please report it directly there

## When Should I NOT Report a Vulnerability?

- You need help tuning Kubernetes components for security
- You need help applying security related updates
- Your issue is not security related

## Security Vulnerability Response

Each report is acknowledged and analyzed by Product Security Committee members within 3 working days. This will set off the [Security Release Process](#).

Any vulnerability information shared with Product Security Committee stays within Kubernetes project and will not be disseminated to other projects unless it is necessary to get the issue fixed.

As the security issue moves from triage, to identified fix, to release planning we will keep the reporter updated.

## Public Disclosure Timing

A public disclosure date is negotiated by the Kubernetes Product Security Committee and the bug submitter. We prefer to fully disclose the bug as soon as possible once a user mitigation is available. It is reasonable to delay disclosure when the bug or the fix is not yet fully understood, the solution is not well-tested, or for vendor coordination. The timeframe for disclosure is from immediate (especially if it's already publicly known) to a few weeks. For a vulnerability with a straightforward mitigation, we expect report date to disclosure date to be on the order of 7 days. The Kubernetes Product Security Committee holds the final say when setting a disclosure date.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 15, 2020 at 5:09 AM PST by [Add link to K8s bug bounty to K8s website \(#18690\)](#) ([Page History](#))

[Edit This Page](#)

# Kubernetes API Overview

This page provides an overview of the Kubernetes API.

- [API versioning](#)
- [API groups](#)
- [Enabling API groups](#)
- [Enabling resources in the groups](#)



The REST API is the fundamental fabric of Kubernetes. All operations and communications between components, and external user commands are REST API calls that the API Server handles. Consequently, everything in the Kubernetes platform is treated as an API object and has a corresponding entry in the [API](#).

Most operations can be performed through the [kubectl](#) command-line interface or other command-line tools, such as [kubeadm](#), which in turn use the API. However, you can also access the API directly using REST calls.

Consider using one of the [client libraries](#) if you are writing an application using the Kubernetes API.

## API versioning

To eliminate fields or restructure resource representations, Kubernetes supports multiple API versions, each at a different API path. For example: `/api/v1` or `/apis/extensions/v1beta1`.

The version is set at the API level rather than at the resource or field level to:

- Ensure that the API presents a clear and consistent view of system resources and behavior.
- Enable control access to end-of-life and/or experimental APIs.

The JSON and Protobuf serialization schemas follow the same guidelines for schema changes. The following descriptions cover both formats.

**Note:** The API versioning and software versioning are indirectly related. The [API and release versioning proposal](#) describes the relationship between API versioning and software versioning.

Different API versions indicate different levels of stability and support. You can find more information about the criteria for each level in the [API Changes documentation](#).

Here's a summary of each level:

- Alpha:
  - The version names contain alpha (for example, `v1alpha1`).
  - The software may contain bugs. Enabling a feature may expose bugs. A feature may be disabled by default.
  - The support for a feature may be dropped at any time without notice.
  - The API may change in incompatible ways in a later software release without notice.
  - The software is recommended for use only in short-lived testing clusters, due to increased risk of bugs and lack of long-term support.

- Beta:
  - The version names contain `beta` (for example, `v2beta3`).
  - The software is well tested. Enabling a feature is considered safe. Features are enabled by default.
  - The support for a feature will not be dropped, though the details may change.
  - The schema and/or semantics of objects may change in incompatible ways in a subsequent beta or stable release. When this happens, migration instructions are provided. This may require deleting, editing, and re-creating API objects. The editing process may require some thought. This may require downtime for applications that rely on the feature.
  - The software is recommended for only non-business-critical uses because of potential for incompatible changes in subsequent releases. If you have multiple clusters which can be upgraded independently, you may be able to relax this restriction.

**Note:** Try the beta features and provide feedback. After the features exit beta, it may not be practical to make more changes.

- Stable:
  - The version name is `vX` where `X` is an integer.
  - The stable versions of features appear in released software for many subsequent versions.

## API groups

[API groups](#) make it easier to extend the Kubernetes API. The API group is specified in a REST path and in the `apiVersion` field of a serialized object.

Currently, there are several API groups in use:

- The *core* (also called *legacy*) group, which is at REST path `/api/v1` and is not specified as part of the `apiVersion` field, for example, `apiVersion: v1`.
- The named groups are at REST path `/apis/$GROUP_NAME/$VERSION`, and use `apiVersion: $GROUP_NAME/$VERSION` (for example, `apiVersion: batch/v1`). You can find the full list of supported API groups in [Kubernetes API reference](#).

The two paths that support extending the API with [custom resources](#) are:

- [CustomResourceDefinition](#) for basic CRUD needs.
- [aggregator](#) for a full set of Kubernetes API semantics to implement their own apiserver.

## Enabling API groups

Certain resources and API groups are enabled by default. You can enable or disable them by setting `--runtime-config` on the apiserver. `--runtime-`

config accepts comma separated values. For example: - to disable batch/v1, set `--runtime-config=batch/v1=false` - to enable batch/v2alpha1, set `--runtime-config=batch/v2alpha1` The flag accepts comma separated set of key=value pairs describing runtime configuration of the apiserver.

**Note:** When you enable or disable groups or resources, you need to restart the apiserver and controller-manager to pick up the `--runtime-config` changes.

## Enabling resources in the groups

DaemonSets, Deployments, HorizontalPodAutoscalers, Ingress, Jobs and ReplicaSets are enabled by default. You can enable other extensions resources by setting `--runtime-config` on apiserver. `--runtime-config` accepts comma separated values. For example, to disable deployments and jobs, set `--runtime-config=extensions/v1beta1/deployments=false,extensions/v1beta1/jobs=false`

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on August 01, 2019 at 4:44 AM PST by [Fix broken link in API overview \(#15594\)](#) ([Page History](#))

[Edit This Page](#)

# Kubernetes API Concepts

This page describes common concepts in the Kubernetes API.

- [Standard API terminology](#)
- [Efficient detection of changes](#)
- [Retrieving large results sets in chunks](#)
- [Receiving resources as Tables](#)
- [Alternate representations of resources](#)
- [Resource deletion](#)

- [Dry-run](#)
- [Server Side Apply](#)
- [Resource Versions](#)

The Kubernetes API is a resource-based (RESTful) programmatic interface provided via HTTP. It supports retrieving, creating, updating, and deleting primary resources via the standard HTTP verbs (POST, PUT, PATCH, DELETE, GET), includes additional subresources for many objects that allow fine grained authorization (such as binding a pod to a node), and can accept and serve those resources in different representations for convenience or efficiency. It also supports efficient change notifications on resources via "watches" and consistent lists to allow other components to effectively cache and synchronize the state of resources.

## Standard API terminology

Most Kubernetes API resource types are [objects](#): they represent a concrete instance of a concept on the cluster, like a pod or namespace. A smaller number of API resource types are "virtual" - they often represent operations rather than objects, such as a permission check (use a POST with a JSON-encoded body of SubjectAccessReview to the `subjectaccessreviews` resource). All objects will have a unique name to allow idempotent creation and retrieval, but virtual resource types may not have unique names if they are not retrievable or do not rely on idempotency.

Kubernetes generally leverages standard RESTful terminology to describe the API concepts:

- A **resource type** is the name used in the URL (pods, namespaces, services)
- All resource types have a concrete representation in JSON (their object schema) which is called a **kind**
- A list of instances of a resource type is known as a **collection**
- A single instance of the resource type is called a **resource**

All resource types are either scoped by the cluster (`/apis/GROUP/VERSION/*`) or to a namespace (`/apis/GROUP/VERSION/namespaces/NAMESPACE/*`). A namespace-scoped resource type will be deleted when its namespace is deleted and access to that resource type is controlled by authorization checks on the namespace scope. The following paths are used to retrieve collections and resources:

- Cluster-scoped resources:
  - `GET /apis/GROUP/VERSION/RESOURCETYPE` - return the collection of resources of the resource type
  - `GET /apis/GROUP/VERSION/RESOURCETYPE/NAME` - return the resource with NAME under the resource type
- Namespace-scoped resources:
  - `GET /apis/GROUP/VERSION/RESOURCETYPE` - return the collection of all instances of the resource type across all namespaces

- `GET /apis/GROUP/VERSION/namespaces/NAMESPACE/RESOURCE/` - return collection of all instances of the resource type in NAMESPACE
- `GET /apis/GROUP/VERSION/namespaces/NAMESPACE/RESOURCE/NAME` - return the instance of the resource type with NAME in NAMESPACE

Since a namespace is a cluster-scoped resource type, you can retrieve the list of all namespaces with `GET /api/v1/namespaces` and details about a particular namespace with `GET /api/v1/namespaces/NAME`.

Almost all object resource types support the standard HTTP verbs - GET, POST, PUT, PATCH, and DELETE. Kubernetes uses the term **list** to describe returning a collection of resources to distinguish from retrieving a single resource which is usually called a **get**.

Some resource types will have one or more sub-resources, represented as sub paths below the resource:

- Cluster-scoped subresource: `GET /apis/GROUP/VERSION/RESOURCE/NAME/SUBRESOURCE`
- Namespace-scoped subresource: `GET /apis/GROUP/VERSION/namespaces/NAMESPACE/RESOURCE/NAME/SUBRESOURCE`

The verbs supported for each subresource will differ depending on the object - see the API documentation more information. It is not possible to access sub-resources across multiple resources - generally a new virtual resource type would be used if that becomes necessary.

## Efficient detection of changes

To enable clients to build a model of the current state of a cluster, all Kubernetes object resource types are required to support consistent lists and an incremental change notification feed called a **watch**. Every Kubernetes object has a `resourceVersion` field representing the version of that resource as stored in the underlying database. When retrieving a collection of resources (either namespace or cluster scoped), the response from the server will contain a `resourceVersion` value that can be used to initiate a watch against the server. The server will return all changes (creates, deletes, and updates) that occur after the supplied `resourceVersion`. This allows a client to fetch the current state and then watch for changes without missing any updates. If the client watch is disconnected they can restart a new watch from the last returned `resourceVersion`, or perform a new collection request and begin again. See [Resource Version Semantics](#) for more detail.

For example:

1. List all of the pods in a given namespace.

```
GET /api/v1/namespaces/test/pods
---
```

```
200 OK
Content-Type: application/json
{
  "kind": "PodList",
  "apiVersion": "v1",
  "metadata": {"resourceVersion": "10245"},
  "items": [...]
}
```

2. Starting from resource version 10245, receive notifications of any creates, deletes, or updates as individual JSON objects.

```
GET /api/v1/namespaces/test/pods?
watch=1&resourceVersion=10245
---
200 OK
Transfer-Encoding: chunked
Content-Type: application/json
{
  "type": "ADDED",
  "object": {"kind": "Pod", "apiVersion": "v1", "metadata":
{"resourceVersion": "10596", ...}, ...}
}
{
  "type": "MODIFIED",
  "object": {"kind": "Pod", "apiVersion": "v1", "metadata":
{"resourceVersion": "11020", ...}, ...}
}
...
```

A given Kubernetes server will only preserve a historical list of changes for a limited time. Clusters using etcd3 preserve changes in the last 5 minutes by default. When the requested watch operations fail because the historical version of that resource is not available, clients must handle the case by recognizing the status code 410 Gone, clearing their local cache, performing a list operation, and starting the watch from the `resourceVersion` returned by that new list operation. Most client libraries offer some form of standard tool for this logic. (In Go this is called a Reflector and is located in the `k8s.io/client-go/cache` package.)

## Watch bookmarks

To mitigate the impact of short history window, we introduced a concept of bookmark watch event. It is a special kind of event to pass an information that all changes up to a given `resourceVersion` client is requesting has already been send. Object returned in that event is of the type requested by the request, but only `resourceVersion` field is set, e.g.:

```
GET /api/v1/namespaces/test/pods?
watch=1&resourceVersion=10245&allowWatchBookmarks=true
---
200 OK
```

```
Transfer-Encoding: chunked
Content-Type: application/json
{
  "type": "ADDED",
  "object": {"kind": "Pod", "apiVersion": "v1", "metadata":
{"resourceVersion": "10596", ...}, ...}
}
...
{
  "type": "BOOKMARK",
  "object": {"kind": "Pod", "apiVersion": "v1", "metadata":
{"resourceVersion": "12746"} }
}
```

Bookmark events can be requested by `allowWatchBookmarks=true` option in watch requests, but clients shouldn't assume bookmarks are returned at any specific interval, nor may they assume the server will send any bookmark event.

## Retrieving large results sets in chunks

On large clusters, retrieving the collection of some resource types may result in very large responses that can impact the server and client. For instance, a cluster may have tens of thousands of pods, each of which is 1-2kb of encoded JSON. Retrieving all pods across all namespaces may result in a very large response (10-20MB) and consume a large amount of server resources. Starting in Kubernetes 1.9 the server supports the ability to break a single large collection request into many smaller chunks while preserving the consistency of the total request. Each chunk can be returned sequentially which reduces both the total size of the request and allows user-oriented clients to display results incrementally to improve responsiveness.

To retrieve a single list in chunks, two new parameters `limit` and `continue` are supported on collection requests and a new field `continue` is returned from all list operations in the list `metadata` field. A client should specify the maximum results they wish to receive in each chunk with `limit` and the server will return up to `limit` resources in the result and include a `continue` value if there are more resources in the collection. The client can then pass this `continue` value to the server on the next request to instruct the server to return the next chunk of results. By continuing until the server returns an empty `continue` value the client can consume the full set of results.

Like a watch operation, a `continue` token will expire after a short amount of time (by default 5 minutes) and return a `410 Gone` if more results cannot be returned. In this case, the client will need to start from the beginning or omit the `limit` parameter.



For example, if there are 1,253 pods on the cluster and the client wants to receive chunks of 500 pods at a time, they would request those chunks as follows:

1. List all of the pods on a cluster, retrieving up to 500 pods each time.

```
GET /api/v1/pods?limit=500
---
200 OK
Content-Type: application/json
{
  "kind": "PodList",
  "apiVersion": "v1",
  "metadata": {
    "resourceVersion": "10245",
    "continue": "ENCODED_CONTINUE_TOKEN",
    ...
  },
  "items": [...] // returns pods 1-500
}
```

2. Continue the previous call, retrieving the next set of 500 pods.

```
GET /api/v1/pods?limit=500&continue=ENCODED_CONTINUE_TOKEN
---
200 OK
Content-Type: application/json
{
  "kind": "PodList",
  "apiVersion": "v1",
  "metadata": {
    "resourceVersion": "10245",
    "continue": "ENCODED_CONTINUE_TOKEN_2",
    ...
  },
  "items": [...] // returns pods 501-1000
}
```

3. Continue the previous call, retrieving the last 253 pods.

```
GET /api/v1/pods?limit=500&continue=ENCODED_CONTINUE_TOKEN_2
---
200 OK
Content-Type: application/json
{
  "kind": "PodList",
  "apiVersion": "v1",
  "metadata": {
    "resourceVersion": "10245",
    "continue": "", // continue token is empty because we
    have reached the end of the list
    ...
  },
  "items": [...] // returns pods 1001-1253
}
```

```
    "items": [...] // returns pods 1001-1253
}
```

Note that the `resourceVersion` of the list remains constant across each request, indicating the server is showing us a consistent snapshot of the pods. Pods that are created, updated, or deleted after version 10245 would not be shown unless the user makes a list request without the `continue` token. This allows clients to break large requests into smaller chunks and then perform a watch operation on the full set without missing any updates.

## Receiving resources as Tables

`kubectl get` is a simple tabular representation of one or more instances of a particular resource type. In the past, clients were required to reproduce the tabular and describe output implemented in `kubectl` to perform simple lists of objects. A few limitations of that approach include non-trivial logic when dealing with certain objects. Additionally, types provided by API aggregation or third party resources are not known at compile time. This means that generic implementations had to be in place for types unrecognized by a client.

In order to avoid potential limitations as described above, clients may request the Table representation of objects, delegating specific details of printing to the server. The Kubernetes API implements standard HTTP content type negotiation: passing an `Accept` header containing a value of `application/json;as=Table;g=meta.k8s.io;v=v1beta1` with a GET call will request that the server return objects in the Table content type.

For example:

1. List all of the pods on a cluster in the Table format.

```
GET /api/v1/pods
Accept: application/json;as=Table;g=meta.k8s.io;v=v1beta1
---
200 OK
Content-Type: application/json
{
  "kind": "Table",
  "apiVersion": "meta.k8s.io/v1beta1",
  ...
  "columnDefinitions": [
    ...
  ]
}
```

For API resource types that do not have a custom Table definition on the server, a default Table response is returned by the server, consisting of the resource's name and `creationTimestamp` fields.

```
GET /apis/crd.example.com/v1alpha1/namespaces/default/
resources
```

```

---
200 OK
Content-Type: application/json
...
{
  "kind": "Table",
  "apiVersion": "meta.k8s.io/v1beta1",
  ...
  "columnDefinitions": [
    {
      "name": "Name",
      "type": "string",
      ...
    },
    {
      "name": "Created At",
      "type": "date",
      ...
    }
  ]
}

```

Table responses are available beginning in version 1.10 of the kube-apiserver. As such, not all API resource types will support a Table response, specifically when using a client against older clusters. Clients that must work against all resource types, or can potentially deal with older clusters, should specify multiple content types in their Accept header to support fallback to non-Tabular JSON:

```
Accept: application/json;as=Table;g=meta.k8s.io;v=v1beta1,
application/json
```

## Alternate representations of resources

By default Kubernetes returns objects serialized to JSON with content type `application/json`. This is the default serialization format for the API. However, clients may request the more efficient Protobuf representation of these objects for better performance at scale. The Kubernetes API implements standard HTTP content type negotiation: passing an Accept header with a GET call will request that the server return objects in the provided content type, while sending an object in Protobuf to the server for a PUT or POST call takes the Content-Type header. The server will return a Content-Type header if the requested format is supported, or the `406 Not acceptable` error if an invalid content type is provided.

See the API documentation for a list of supported content types for each API.

For example:

1. List all of the pods on a cluster in Protobuf format.

```
GET /api/v1/pods
Accept: application/vnd.kubernetes.protobuf
---
200 OK
Content-Type: application/vnd.kubernetes.protobuf
... binary encoded PodList object
```

2. Create a pod by sending Protobuf encoded data to the server, but request a response in JSON.

```
POST /api/v1/namespaces/test/pods
Content-Type: application/vnd.kubernetes.protobuf
Accept: application/json
... binary encoded Pod object
---
200 OK
Content-Type: application/json
{
  "kind": "Pod",
  "apiVersion": "v1",
  ...
}
```

Not all API resource types will support Protobuf, specifically those defined via Custom Resource Definitions or those that are API extensions. Clients that must work against all resource types should specify multiple content types in their Accept header to support fallback to JSON:

```
Accept: application/vnd.kubernetes.protobuf, application/json
```

## Protobuf encoding

Kubernetes uses an envelope wrapper to encode Protobuf responses. That wrapper starts with a 4 byte magic number to help identify content in disk or in etcd as Protobuf (as opposed to JSON), and then is followed by a Protobuf encoded wrapper message, which describes the encoding and type of the underlying object and then contains the object.

The wrapper format is:

```
A four byte magic number prefix:
Bytes 0-3: "k8s\x00" [0x6b, 0x38, 0x73, 0x00]
```

An encoded Protobuf message with the following IDL:

```
message Unknown {
  // typeMeta should have the string values for "kind" and
  "apiVersion" as set on the JSON object
  optional TypeMeta typeMeta = 1;

  // raw will hold the complete serialized object in protobuf.
  See the protobuf definitions in the client libraries for a given
  kind.
```

```

    optional bytes raw = 2;

    // contentType is encoding used for the raw data.
    // Unspecified means no encoding.
    optional string contentType = 3;

    // contentType is the serialization method used to serialize
    // 'raw'. Unspecified means application/vnd.kubernetes.protobuf and
    // is usually
    // omitted.
    optional string contentType = 4;
}

message TypeMeta {
    // apiVersion is the group/version for this type
    optional string apiVersion = 1;
    // kind is the name of the object schema. A protobuf
    // definition should exist for this object.
    optional string kind = 2;
}

```

Clients that receive a response in `application/vnd.kubernetes.protobuf` that does not match the expected prefix should reject the response, as future versions may need to alter the serialization format in an incompatible way and will do so by changing the prefix.

## Resource deletion

Resources are deleted in two phases: 1) finalization, and 2) removal.

```

{
  "kind": "ConfigMap",
  "apiVersion": "v1",
  "metadata": {
    "finalizers": {"url.io/neat-finalization", "other-url.io/my-finalizer"},
    "deletionTimestamp": nil,
  }
}

```

When a client first deletes a resource, the `.metadata.deletionTimestamp` is set to the current time. Once the `.metadata.deletionTimestamp` is set, external controllers that act on finalizers may start performing their cleanup work at any time, in any order. Order is NOT enforced because it introduces significant risk of stuck `.metadata.finalizers`. `.metadata.finalizers` is a shared field, any actor with permission can reorder it. If the finalizer list is processed in order, then this can lead to a situation in which the component responsible for the first finalizer in the list is waiting for a signal (field value, external system, or other) produced by a component responsible for a finalizer later in the list, resulting in a deadlock. Without enforced ordering

finalizers are free to order amongst themselves and are not vulnerable to ordering changes in the list.

Once the last finalizer is removed, the resource is actually removed from etcd.

## Dry-run

**FEATURE STATE:** Kubernetes v1.13 [beta](#)

This feature is currently in a *beta* state, meaning:

[Edit This Page](#)

# Client Libraries

This page contains an overview of the client libraries for using the Kubernetes API from various programming languages.

- [Officially-supported Kubernetes client libraries](#)
- [Community-maintained client libraries](#)

To write applications using the [Kubernetes REST API](#), you do not need to implement the API calls and request/response types yourself. You can use a client library for the programming language you are using.

Client libraries often handle common tasks such as authentication for you. Most client libraries can discover and use the Kubernetes Service Account to authenticate if the API client is running inside the Kubernetes cluster, or can understand the [kubeconfig file](#) format to read the credentials and the API Server address.

## Officially-supported Kubernetes client libraries

The following client libraries are officially maintained by [Kubernetes SIG API Machinery](#).

Language	Client Library	Sample Programs
Go	<a href="https://github.com/kubernetes/client-go/">github.com/kubernetes/client-go/</a>	<a href="#">browse</a>
Python	<a href="https://github.com/kubernetes-client/python/">github.com/kubernetes-client/python/</a>	<a href="#">browse</a>
Java	<a href="https://github.com/kubernetes-client/java">github.com/kubernetes-client/java</a>	<a href="#">browse</a>
dotnet	<a href="https://github.com/kubernetes-client/csharp">github.com/kubernetes-client/csharp</a>	<a href="#">browse</a>
JavaScript	<a href="https://github.com/kubernetes-client/javascript">github.com/kubernetes-client/javascript</a>	<a href="#">browse</a>
Haskell	<a href="https://github.com/kubernetes-client/haskell">github.com/kubernetes-client/haskell</a>	<a href="#">browse</a>

# Community-maintained client libraries

The following Kubernetes API client libraries are provided and maintained by their authors, not the Kubernetes team.

Language	Client Library
Clojure	<a href="https://github.com/yanatan16/clj-kubernetes-api">github.com/yanatan16/clj-kubernetes-api</a>
Go	<a href="https://github.com/ericchiang/k8s">github.com/ericchiang/k8s</a>
Java (OSGi)	<a href="https://bitbucket.org/amdatulabs/amdatu-kubernetes">bitbucket.org/amdatulabs/amdatu-kubernetes</a>
Java (Fabric8, OSGi)	<a href="https://github.com/fabric8io/kubernetes-client">github.com/fabric8io/kubernetes-client</a>
Lisp	<a href="https://github.com/brendandburns/cl-k8s">github.com/brendandburns/cl-k8s</a>
Lisp	<a href="https://github.com/xh4/cube">github.com/xh4/cube</a>
Node.js (TypeScript)	<a href="https://github.com/Goyoo/node-k8s-client">github.com/Goyoo/node-k8s-client</a>
Node.js	<a href="https://github.com/tenxcloud/node-kubernetes-client">github.com/tenxcloud/node-kubernetes-client</a>
Node.js	<a href="https://github.com/godaddy/kubernetes-client">github.com/godaddy/kubernetes-client</a>
Node.js	<a href="https://github.com/ajpauwels/easy-k8s">github.com/ajpauwels/easy-k8s</a>
Perl	<a href="https://metacpan.org/pod/Net::Kubernetes">metacpan.org/pod/Net::Kubernetes</a>
PHP	<a href="https://github.com/maclof/kubernetes-client">github.com/maclof/kubernetes-client</a>
PHP	<a href="https://github.com/allansun/kubernetes-php-client">github.com/allansun/kubernetes-php-client</a>
PHP	<a href="https://github.com/travisghansen/kubernetes-client-php">github.com/travisghansen/kubernetes-client-php</a>
Python	<a href="https://github.com/eldarion-gondor/pykube">github.com/eldarion-gondor/pykube</a>
Python	<a href="https://github.com/mnubo/kubernetes-py">github.com/mnubo/kubernetes-py</a>
Python	<a href="https://github.com/tomplus/kubernetes_asyncio">github.com/tomplus/kubernetes_asyncio</a>
Ruby	<a href="https://github.com/Ch00k/kuber">github.com/Ch00k/kuber</a>
Ruby	<a href="https://github.com/abonas/kubeclient">github.com/abonas/kubeclient</a>
Ruby	<a href="https://github.com/kontena/k8s-client">github.com/kontena/k8s-client</a>
Rust	<a href="https://github.com/clux/kube-rs">github.com/clux/kube-rs</a>
Rust	<a href="https://github.com/ynqa/kubernetes-rust">github.com/ynqa/kubernetes-rust</a>
Scala	<a href="https://github.com/doriordan/skuber">github.com/doriordan/skuber</a>
dotNet	<a href="https://github.com/tonnyeremin/kubernetes_gen">github.com/tonnyeremin/kubernetes_gen</a>
DotNet (RestSharp)	<a href="https://github.com/masroorhasan/Kubernetes.DotNet">github.com/masroorhasan/Kubernetes.DotNet</a>
Elixir	<a href="https://github.com/obmarg/kazan">github.com/obmarg/kazan</a>
Elixir	<a href="https://github.com/coryodaniel/k8s">github.com/coryodaniel/k8s</a>
Haskell	<a href="https://github.com/kubernetes-client/haskell">github.com/kubernetes-client/haskell</a>

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](https://stackoverflow.com). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on February 10, 2020 at 2:43 PM PST by [adding elixir k8s client \(#19056\)](#) ([Page History](#))

[Edit This Page](#)

# Kubernetes Deprecation Policy

This document details the deprecation policy for various facets of the system.

- [Deprecating parts of the API](#)
- [Deprecating a flag or CLI](#)
- [Deprecating a feature or behavior](#)
- [Exceptions](#)



Kubernetes is a large system with many components and many contributors. As with any such software, the feature set naturally evolves over time, and sometimes a feature may need to be removed. This could include an API, a flag, or even an entire feature. To avoid breaking existing users, Kubernetes follows a deprecation policy for aspects of the system that are slated to be removed.

## Deprecating parts of the API

Since Kubernetes is an API-driven system, the API has evolved over time to reflect the evolving understanding of the problem space. The Kubernetes API is actually a set of APIs, called "API groups", and each API group is independently versioned. [API versions](#) fall into 3 main tracks, each of which has different policies for deprecation:

Example	Track
v1	GA (generally available, stable)
v1beta1	Beta (pre-release)
v1alpha1	Alpha (experimental)

A given release of Kubernetes can support any number of API groups and any number of versions of each.

The following rules govern the deprecation of elements of the API. This includes:

- REST resources (aka API objects)
- Fields of REST resources
- Annotations on REST resources, including "beta" annotations but not including "alpha" annotations.
- Enumerated or constant values
- Component config structures

These rules are enforced between official releases, not between arbitrary commits to master or release branches.

**Rule #1: API elements may only be removed by incrementing the version of the API group.**

Once an API element has been added to an API group at a particular version, it can not be removed from that version or have its behavior significantly changed, regardless of track.

**Note:** For historical reasons, there are 2 "monolithic" API groups - "core" (no group name) and "extensions". Resources will incrementally be moved from these legacy API groups into more domain-specific API groups.

**Rule #2: API objects must be able to round-trip between API versions in a given release without information loss, with the exception of whole REST resources that do not exist in some versions.**

For example, an object can be written as v1 and then read back as v2 and converted to v1, and the resulting v1 resource will be identical to the original. The representation in v2 might be different from v1, but the system knows how to convert between them in both directions. Additionally, any new field added in v2 must be able to round-trip to v1 and back, which means v1 might have to add an equivalent field or represent it as an annotation.

**Rule #3: An API version in a given track may not be deprecated until a new API version at least as stable is released.**

GA API versions can replace GA API versions as well as beta and alpha API versions. Beta API versions *may not* replace GA API versions.

**Rule #4a: Other than the most recent API versions in each track, older API versions must be supported after their announced deprecation for a duration of no less than:**

- **GA: 12 months or 3 releases (whichever is longer)**
- **Beta: 9 months or 3 releases (whichever is longer)**
- **Alpha: 0 releases**

This covers the [maximum supported version skew of 2 releases](#).

**Note:** Until [#52185](#) is resolved, no API versions that have been persisted to storage may be removed. Serving REST endpoints for those versions may be disabled (subject to the deprecation timelines in this document), but the API server must remain capable of decoding/converting previously persisted data from storage.

**Rule #4b: The "preferred" API version and the "storage version" for a given group may not advance until after a release has been made that supports both the new version and the previous version**

Users must be able to upgrade to a new release of Kubernetes and then roll back to a previous release, without converting anything to the new API version or suffering breakages (unless they explicitly used features only available in the newer version). This is particularly evident in the stored representation of objects.

All of this is best illustrated by examples. Imagine a Kubernetes release, version X, which introduces a new API group. A new Kubernetes release is made every approximately 3 months (4 per year). The following table describes which API versions are supported in a series of subsequent releases.

Release	API Versions	Preferred/ Storage Version	Notes
X	v1alpha1	v1alpha1	

<b>Release</b>	<b>API Versions</b>	<b>Preferred/ Storage Version</b>	<b>Notes</b>
X+1	v1alpha2	v1alpha2	<ul style="list-style-type: none"> <li>v1alpha1 is removed, "action required" relnote</li> </ul>
X+2	v1beta1	v1beta1	<ul style="list-style-type: none"> <li>v1alpha2 is removed, "action required" relnote</li> </ul>
X+3	v1beta2, v1beta1 (deprecated)	v1beta1	<ul style="list-style-type: none"> <li>v1beta1 is deprecated, "action required" relnote</li> </ul>
X+4	v1beta2, v1beta1 (deprecated)	v1beta2	
X+5	v1, v1beta1 (deprecated), v1beta2 (deprecated)	v1beta2	<ul style="list-style-type: none"> <li>v1beta2 is deprecated, "action required" relnote</li> </ul>
X+6	v1, v1beta2 (deprecated)	v1	<ul style="list-style-type: none"> <li>v1beta1 is removed, "action required" relnote</li> </ul>
X+7	v1, v1beta2 (deprecated)	v1	
X+8	v2alpha1, v1	v1	<ul style="list-style-type: none"> <li>v1beta2 is removed, "action required" relnote</li> </ul>
X+9	v2alpha2, v1	v1	<ul style="list-style-type: none"> <li>v2alpha1 is removed, "action required" relnote</li> </ul>
X+10	v2beta1, v1	v1	<ul style="list-style-type: none"> <li>v2alpha2 is removed, "action required" relnote</li> </ul>
X+11	v2beta2, v2beta1 (deprecated), v1	v1	<ul style="list-style-type: none"> <li>v2beta1 is deprecated, "action required" relnote</li> </ul>
X+12	v2, v2beta2 (deprecated), v2beta1 (deprecated), v1 (deprecated)	v1	<ul style="list-style-type: none"> <li>v2beta2 is deprecated, "action required" relnote</li> <li>v1 is deprecated, "action required" relnote</li> </ul>

Release	API Versions	Preferred/ Storage Version	Notes
X+13	v2, v2beta1 (deprecated), v2beta2 (deprecated), v1 (deprecated)	v2	
X+14	v2, v2beta2 (deprecated), v1 (deprecated)	v2	<ul style="list-style-type: none"> <li>v2beta1 is removed, "action required" relnote</li> </ul>
X+15	v2, v1 (deprecated)	v2	<ul style="list-style-type: none"> <li>v2beta2 is removed, "action required" relnote</li> </ul>
X+16	v2, v1 (deprecated)	v2	
X+17	v2	v2	<ul style="list-style-type: none"> <li>v1 is removed, "action required" relnote</li> </ul>

## REST resources (aka API objects)

Consider a hypothetical REST resource named Widget, which was present in API v1 in the above timeline, and which needs to be deprecated. We [document](#) and [announce](#) the deprecation in sync with release X+1. The Widget resource still exists in API version v1 (deprecated) but not in v2alpha1. The Widget resource continues to exist and function in releases up to and including X+8. Only in release X+9, when API v1 has aged out, does the Widget resource cease to exist, and the behavior get removed.

## Fields of REST resources

As with whole REST resources, an individual field which was present in API v1 must exist and function until API v1 is removed. Unlike whole resources, the v2 APIs may choose a different representation for the field, as long as it can be round-tripped. For example a v1 field named "magnitude" which was deprecated might be named "deprecatedMagnitude" in API v2. When v1 is eventually removed, the deprecated field can be removed from v2.

## Enumerated or constant values

As with whole REST resources and fields thereof, a constant value which was supported in API v1 must exist and function until API v1 is removed.

## Component config structures

Component configs are versioned and managed just like REST resources.

## Future work

Over time, Kubernetes will introduce more fine-grained API versions, at which point these rules will be adjusted as needed.

## Deprecating a flag or CLI

The Kubernetes system is comprised of several different programs cooperating. Sometimes, a Kubernetes release might remove flags or CLI commands (collectively "CLI elements") in these programs. The individual programs naturally sort into two main groups - user-facing and admin-facing programs, which vary slightly in their deprecation policies. Unless a flag is explicitly prefixed or documented as "alpha" or "beta", it is considered GA.

CLI elements are effectively part of the API to the system, but since they are not versioned in the same way as the REST API, the rules for deprecation are as follows:

**Rule #5a: CLI elements of user-facing components (e.g. kubectl) must function after their announced deprecation for no less than:**

- **GA: 12 months or 2 releases (whichever is longer)**
- **Beta: 3 months or 1 release (whichever is longer)**
- **Alpha: 0 releases**

**Rule #5b: CLI elements of admin-facing components (e.g. kubelet) must function after their announced deprecation for no less than:**

- **GA: 6 months or 1 release (whichever is longer)**
- **Beta: 3 months or 1 release (whichever is longer)**
- **Alpha: 0 releases**

**Rule #6: Deprecated CLI elements must emit warnings (optionally disable) when used.**

## Deprecating a feature or behavior

Occasionally a Kubernetes release needs to deprecate some feature or behavior of the system that is not controlled by the API or CLI. In this case, the rules for deprecation are as follows:

**Rule #7: Deprecated behaviors must function for no less than 1 year after their announced deprecation.**

This does not imply that all changes to the system are governed by this policy. This applies only to significant, user-visible behaviors which impact the correctness of applications running on Kubernetes or that impact the administration of Kubernetes clusters, and which are being removed entirely.

An exception to the above rule is *feature gates*. Feature gates are key=value pairs that allow for users to enable/disable experimental features.

Feature gates are intended to cover the development life cycle of a feature - they are not intended to be long-term APIs. As such, they are expected to be deprecated and removed after a feature becomes GA or is dropped.

As a feature moves through the stages, the associated feature gate evolves. The feature life cycle matched to its corresponding feature gate is:

- Alpha: the feature gate is disabled by default and can be enabled by the user.
- Beta: the feature gate is enabled by default and can be disabled by the user.
- GA: the feature gate is deprecated (see "[Deprecation](#)") and becomes non-operational.
- GA, deprecation window complete: the feature gate is removed and calls to it are no longer accepted.

## Deprecation

Features can be removed at any point in the life cycle prior to GA. When features are removed prior to GA, their associated feature gates are also deprecated.

When an invocation tries to disable a non-operational feature gate, the call fails in order to avoid unsupported scenarios that might otherwise run silently.

In some cases, removing pre-GA features requires considerable time. Feature gates can remain operational until their associated feature is fully removed, at which point the feature gate itself can be deprecated.

When removing a feature gate for a GA feature also requires considerable time, calls to feature gates may remain operational if the feature gate has no effect on the feature, and if the feature gate causes no errors.

Features intended to be disabled by users should include a mechanism for disabling the feature in the associated feature gate.

Versioning for feature gates is different from the previously discussed components, therefore the rules for deprecation are as follows:

**Rule #8: Feature gates must be deprecated when the corresponding feature they control transitions a lifecycle stage as follows. Feature gates must function for no less than:**

- Beta feature to GA: 6 months or 2 releases (whichever is longer)
- Beta feature to EOL: 3 months or 1 release (whichever is longer)
- Alpha feature to EOL: 0 releases

**Rule #9: Deprecated feature gates must respond with a warning when used. When a feature gate is deprecated it must be documented**

**in both in the release notes and the corresponding CLI help. Both warnings and documentation must indicate whether a feature gate is non-operational.**

## Exceptions

No policy can cover every possible situation. This policy is a living document, and will evolve over time. In practice, there will be situations that do not fit neatly into this policy, or for which this policy becomes a serious impediment. Such situations should be discussed with SIGs and project leaders to find the best solutions for those specific cases, always bearing in mind that Kubernetes is committed to being a stable system that, as much as possible, never breaks users. Exceptions will always be announced in all relevant release notes.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on June 12, 2019 at 5:27 PM PST by [Restructure the left navigation pane of setup \(#14826\)](#) ([Page History](#))

[Edit This Page](#)

# Controlling Access to the Kubernetes API


This page provides an overview of controlling access to the Kubernetes API.

- [Transport Security](#)
- [Authentication](#)
- [Authorization](#)
- [Admission Control](#)



- [API Server Ports and IPs](#)

Users [access the API](#) using `kubectl`, client libraries, or by making REST requests. Both human users and [Kubernetes service accounts](#) can be authorized for API access. When a request reaches the API, it goes through several stages, illustrated in the following diagram:



## Transport Security

In a typical Kubernetes cluster, the API serves on port 6443. The API server presents a certificate. This certificate is often self-signed, so `$USER/.kube/config` on the user's machine typically contains the root certificate for the API server's certificate, which when specified is used in place of the system default root certificate. This certificate is typically automatically written into your `$USER/.kube/config` when you create a cluster yourself using `kube-up.sh`. If the cluster has multiple users, then the creator needs to share the certificate with other users.

## Authentication

Once TLS is established, the HTTP request moves to the Authentication step. This is shown as step **1** in the diagram. The cluster creation script or cluster admin configures the API server to run one or more Authenticator Modules. Authenticators are described in more detail [here](#).

The input to the authentication step is the entire HTTP request, however, it typically just examines the headers and/or client certificate.

Authentication modules include Client Certificates, Password, and Plain Tokens, Bootstrap Tokens, and JWT Tokens (used for service accounts).

Multiple authentication modules can be specified, in which case each one is tried in sequence, until one of them succeeds.

On GCE, Client Certificates, Password, Plain Tokens, and JWT Tokens are all enabled.

If the request cannot be authenticated, it is rejected with HTTP status code 401. Otherwise, the user is authenticated as a specific username, and the user name is available to subsequent steps to use in their decisions. Some authenticators also provide the group memberships of the user, while other authenticators do not.

While Kubernetes uses usernames for access control decisions and in request logging, it does not have a user object nor does it store usernames or other information about users in its object store.

## Authorization

After the request is authenticated as coming from a specific user, the request must be authorized. This is shown as step 2 in the diagram.

A request must include the username of the requester, the requested action, and the object affected by the action. The request is authorized if an existing policy declares that the user has permissions to complete the requested action.

For example, if Bob has the policy below, then he can read pods only in the namespace projectCaribou:

```
{
  "apiVersion": "abac.authorization.kubernetes.io/v1beta1",
  "kind": "Policy",
  "spec": {
    "user": "bob",
    "namespace": "projectCaribou",
    "resource": "pods",
    "readonly": true
  }
}
```

If Bob makes the following request, the request is authorized because he is allowed to read objects in the projectCaribou namespace:

```
{
  "apiVersion": "authorization.k8s.io/v1beta1",
  "kind": "SubjectAccessReview",
  "spec": {
    "resourceAttributes": {
      "namespace": "projectCaribou",
      "verb": "get",
      "group": "unicorn.example.org",
      "resource": "pods"
    }
  }
}
```

```
}  
}  
}
```

If Bob makes a request to write (create or update) to the objects in the `projectCaribou` namespace, his authorization is denied. If Bob makes a request to read (get) objects in a different namespace such as `projectFish`, then his authorization is denied.

Kubernetes authorization requires that you use common REST attributes to interact with existing organization-wide or cloud-provider-wide access control systems. It is important to use REST formatting because these control systems might interact with other APIs besides the Kubernetes API.

Kubernetes supports multiple authorization modules, such as ABAC mode, RBAC Mode, and Webhook mode. When an administrator creates a cluster, they configured the authorization modules that should be used in the API server. If more than one authorization modules are configured, Kubernetes checks each module, and if any module authorizes the request, then the request can proceed. If all of the modules deny the request, then the request is denied (HTTP status code 403).

To learn more about Kubernetes authorization, including details about creating policies using the supported authorization modules, see [Authorization Overview](#).

## Admission Control

Admission Control Modules are software modules that can modify or reject requests. In addition to the attributes available to Authorization Modules, Admission Control Modules can access the contents of the object that is being created or updated. They act on objects being created, deleted, updated or connected (proxy), but not reads.

Multiple admission controllers can be configured. Each is called in order.

This is shown as step **3** in the diagram.

Unlike Authentication and Authorization Modules, if any admission controller module rejects, then the request is immediately rejected.

In addition to rejecting objects, admission controllers can also set complex defaults for fields.

The available Admission Control Modules are described [here](#).

Once a request passes all admission controllers, it is validated using the validation routines for the corresponding API object, and then written to the object store (shown as step **4**).

# API Server Ports and IPs

The previous discussion applies to requests sent to the secure port of the API server (the typical case). The API server can actually serve on 2 ports:

By default the Kubernetes API server serves HTTP on 2 ports:

## 1. Localhost Port:

- is intended for testing and bootstrap, and for other components of the master node (scheduler, controller-manager) to talk to the API
- no TLS
- default is port 8080, change with `--insecure-port` flag.
- default IP is localhost, change with `--insecure-bind-address` flag.
- request **bypasses** authentication and authorization modules.
- request handled by admission control module(s).
- protected by need to have host access

## 2. Secure Port:

- use whenever possible
- uses TLS. Set cert with `--tls-cert-file` and key with `--tls-private-key-file` flag.
- default is port 6443, change with `--secure-port` flag.
- default IP is first non-localhost network interface, change with `--bind-address` flag.
- request handled by authentication and authorization modules.
- request handled by admission control module(s).
- authentication and authorization modules run.

When the cluster is created by `kube-up.sh`, on Google Compute Engine (GCE), and on several other cloud providers, the API server serves on port 443. On GCE, a firewall rule is configured on the project to allow external HTTPS access to the API. Other cluster setup methods vary.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on November 06, 2019 at 2:23 PM PST by [fix issue 17420 \(#17439\)](#) ([Page History](#))

[Edit This Page](#)

# Authenticating

This page provides an overview of authenticating.

- [Users in Kubernetes](#)
- [Authentication strategies](#)
- [Anonymous requests](#)
- [User impersonation](#)
- [client-go credential plugins](#)

# Users in Kubernetes

All Kubernetes clusters have two categories of users: service accounts managed by Kubernetes, and normal users.

Normal users are assumed to be managed by an outside, independent service. An admin distributing private keys, a user store like Keystone or Google Accounts, even a file with a list of usernames and passwords. In this regard, *Kubernetes does not have objects which represent normal user accounts*. Normal users cannot be added to a cluster through an API call.

In contrast, service accounts are users managed by the Kubernetes API. They are bound to specific namespaces, and created automatically by the API server or manually through API calls. Service accounts are tied to a set of credentials stored as Secrets, which are mounted into pods allowing in-cluster processes to talk to the Kubernetes API.

API requests are tied to either a normal user or a service account, or are treated as anonymous requests. This means every process inside or outside the cluster, from a human user typing `kubectl` on a workstation, to `kubelet`s on nodes, to members of the control plane, must authenticate when making requests to the API server, or be treated as an anonymous user.

## Authentication strategies

Kubernetes uses client certificates, bearer tokens, an authenticating proxy, or HTTP basic auth to authenticate API requests through authentication plugins. As HTTP requests are made to the API server, plugins attempt to associate the following attributes with the request:

- Username: a string which identifies the end user. Common values might be `kube-admin` or `jane@example.com`.
- UID: a string which identifies the end user and attempts to be more consistent and unique than username.
- Groups: a set of strings which associate users with a set of commonly grouped users.
- Extra fields: a map of strings to list of strings which holds additional information authorizers may find useful.

All values are opaque to the authentication system and only hold significance when interpreted by an [authorizer](#).

You can enable multiple authentication methods at once. You should usually use at least two methods:

- service account tokens for service accounts
- at least one other method for user authentication.

When multiple authenticator modules are enabled, the first module to successfully authenticate the request short-circuits evaluation. The API server does not guarantee the order authenticators run in.

The `system:authenticated` group is included in the list of groups for all authenticated users.

Integrations with other authentication protocols (LDAP, SAML, Kerberos, alternate x509 schemes, etc) can be accomplished using an [authenticating proxy](#) or the [authentication webhook](#).

## X509 Client Certs

Client certificate authentication is enabled by passing the `--client-ca-file=SOMEFILE` option to API server. The referenced file must contain one or more certificate authorities to use to validate client certificates presented to the API server. If a client certificate is presented and verified, the common name of the subject is used as the user name for the request. As of Kubernetes 1.4, client certificates can also indicate a user's group memberships using the certificate's organization fields. To include multiple group memberships for a user, include multiple organization fields in the certificate.

For example, using the `openssl` command line tool to generate a certificate signing request:

```
openssl req -new -key jbeda.pem -out jbeda-csr.pem -subj "/
CN=jbeda/0=app1/0=app2"
```

This would create a CSR for the username "jbeda", belonging to two groups, "app1" and "app2".

See [Managing Certificates](#) for how to generate a client cert.

## Static Token File

The API server reads bearer tokens from a file when given the `--token-auth-file=SOMEFILE` option on the command line. Currently, tokens last indefinitely, and the token list cannot be changed without restarting API server.

The token file is a csv file with a minimum of 3 columns: token, user name, user uid, followed by optional group names.

### Note:

If you have more than one group the column must be double quoted e.g.

```
token,user,uid,"group1,group2,group3"
```

## Putting a Bearer Token in a Request

When using bearer token authentication from an http client, the API server expects an `Authorization` header with a value of `Bearer THETOKEN`. The bearer token must be a character sequence that can be put in

an HTTP header value using no more than the encoding and quoting facilities of HTTP. For example: if the bearer token is 31ada4fd-adec-460c-809a-9e56ceb75269 then it would appear in an HTTP header as shown below.

```
Authorization: Bearer 31ada4fd-adec-460c-809a-9e56ceb75269
```

## Bootstrap Tokens

This feature is currently in **beta**.

To allow for streamlined bootstrapping for new clusters, Kubernetes includes a dynamically-managed Bearer token type called a *Bootstrap Token*. These tokens are stored as Secrets in the kube-system namespace, where they can be dynamically managed and created. Controller Manager contains a TokenCleaner controller that deletes bootstrap tokens as they expire.

The tokens are of the form [a-z0-9]{6}.[a-z0-9]{16}. The first component is a Token ID and the second component is the Token Secret. You specify the token in an HTTP header as follows:

```
Authorization: Bearer 781292.db7bc3a58fc5f07e
```

You must enable the Bootstrap Token Authenticator with the `--enable-bootstrap-token-auth` flag on the API Server. You must enable the TokenCleaner controller via the `--controllers` flag on the Controller Manager. This is done with something like `--controllers=*,tokencleaner`. kubeadm will do this for you if you are using it to bootstrap a cluster.

The authenticator authenticates as `system:bootstrap:<Token ID>`. It is included in the `system:bootstrappers` group. The naming and groups are intentionally limited to discourage users from using these tokens past bootstrapping. The user names and group can be used (and are used by kubeadm) to craft the appropriate authorization policies to support bootstrapping a cluster.

Please see [Bootstrap Tokens](#) for in depth documentation on the Bootstrap Token authenticator and controllers along with how to manage these tokens with kubeadm.

## Static Password File

Basic authentication is enabled by passing the `--basic-auth-file=SOMEFILE` option to API server. Currently, the basic auth credentials last indefinitely, and the password cannot be changed without restarting API server. Note that basic authentication is currently supported for convenience while we finish making the more secure modes described above easier to use.

The basic auth file is a csv file with a minimum of 3 columns: password, user name, user id. In Kubernetes version 1.6 and later, you can specify an optional fourth column containing comma-separated group names. If you



have more than one group, you must enclose the fourth column value in double quotes ("). See the following example:

```
password,user,uid,"group1,group2,group3"
```

When using basic authentication from an http client, the API server expects an Authorization header with a value of Basic `BASE64ENCODED(USER:PASSWORD)`.

## Service Account Tokens

A service account is an automatically enabled authenticator that uses signed bearer tokens to verify requests. The plugin takes two optional flags:

- `--service-account-key-file` A file containing a PEM encoded key for signing bearer tokens. If unspecified, the API server's TLS private key will be used.
- `--service-account-lookup` If enabled, tokens which are deleted from the API will be revoked.

Service accounts are usually created automatically by the API server and associated with pods running in the cluster through the [ServiceAccount Admission Controller](#). Bearer tokens are mounted into pods at well-known locations, and allow in-cluster processes to talk to the API server. Accounts may be explicitly associated with pods using the `serviceAccountName` field of a PodSpec.

**Note:** `serviceAccountName` is usually omitted because this is done automatically.

```
apiVersion: apps/v1 # this apiVersion is relevant as of  
Kubernetes 1.9  
kind: Deployment  
metadata:  
  name: nginx-deployment  
  namespace: default  
spec:  
  replicas: 3  
  template:  
    metadata:  
      # ...  
    spec:  
      serviceAccountName: bob-the-bot  
      containers:  
      - name: nginx  
        image: nginx:1.7.9
```

Service account bearer tokens are perfectly valid to use outside the cluster and can be used to create identities for long standing jobs that wish to talk to the Kubernetes API. To manually create a service account, simply use the `kubectl`

`create serviceaccount (NAME)` command. This creates a service account in the current namespace and an associated secret.

```
kubectl create serviceaccount jenkins
```

```
serviceaccount "jenkins" created
```

Check an associated secret:

```
kubectl get serviceaccounts jenkins -o yaml
```

```
apiVersion: v1
kind: ServiceAccount
metadata:
  # ...
secrets:
- name: jenkins-token-lyvwg
```

The created secret holds the public CA of the API server and a signed JSON Web Token (JWT).

```
kubectl get secret jenkins-token-lyvwg -o yaml
```

```
apiVersion: v1
data:
  ca.crt: (APISERVER'S CA BASE64 ENCODED)
  namespace: ZGVmYXVsdA==
  token: (BEARER TOKEN BASE64 ENCODED)
kind: Secret
metadata:
  # ...
type: kubernetes.io/service-account-token
```

**Note:** Values are base64 encoded because secrets are always base64 encoded.

The signed JWT can be used as a bearer token to authenticate as the given service account. See [above](#) for how the token is included in a request. Normally these secrets are mounted into pods for in-cluster access to the API server, but can be used from outside the cluster as well.


Service accounts authenticate with the username `system:serviceaccount:(NAMESPACE):(SERVICEACCOUNT)`, and are assigned to the groups `system:serviceaccounts` and `system:serviceaccounts:(NAMESPACE)`.

**WARNING:** Because service account tokens are stored in secrets, any user with read access to those secrets can authenticate as the service account. Be cautious when granting permissions to service accounts and read capabilities for secrets.

## OpenID Connect Tokens

[OpenID Connect](#) is a flavor of OAuth2 supported by some OAuth2 providers, notably Azure Active Directory, Salesforce, and Google. The protocol's main extension of OAuth2 is an additional field returned with the access token called an [ID Token](#). This token is a JSON Web Token (JWT) with well known fields, such as a user's email, signed by the server.

To identify the user, the authenticator uses the `id_token` (not the `access_token`) from the OAuth2 [token response](#) as a bearer token. See [above](#) for how the token is included in a request.



1. Login to your identity provider
2. Your identity provider will provide you with an `access_token`, `id_token` and a `refresh_token`
3. When using `kubectl`, use your `id_token` with the `--token` flag or add it directly to your kubeconfig
4. `kubectl` sends your `id_token` in a header called `Authorization` to the API server
5. The API server will make sure the JWT signature is valid by checking against the certificate named in the configuration
6. Check to make sure the `id_token` hasn't expired
7. Make sure the user is authorized
8. Once authorized the API server returns a response to `kubectl`
9. `kubectl` provides feedback to the user

Since all of the data needed to validate who you are is in the `id_token`, Kubernetes doesn't need to "phone home" to the identity provider. In a model where every request is stateless this provides a very scalable solution for authentication. It does offer a few challenges:

1. Kubernetes has no "web interface" to trigger the authentication process. There is no browser or interface to collect credentials which is why you need to authenticate to your identity provider first.

2. The `id_token` can't be revoked, it's like a certificate so it should be short-lived (only a few minutes) so it can be very annoying to have to get a new token every few minutes.
3. There's no easy way to authenticate to the Kubernetes dashboard without using the `kubectl proxy` command or a reverse proxy that injects the `id_token`.

## Configuring the API Server

To enable the plugin, configure the following flags on the API server:

Parameter	Description	Example	Required
<code>--oidc-issuer-url</code>	URL of the provider which allows the API server to discover public signing keys. Only URLs which use the <code>https://</code> scheme are accepted. This is typically the provider's discovery URL without a path, for example " <a href="https://accounts.google.com">https://accounts.google.com</a> " or " <a href="https://login.salesforce.com">https://login.salesforce.com</a> ". This URL should point to the level below <code>.well-known/openid-configuration</code>	If the discovery URL is <code>https://accounts.google.com/.well-known/openid-configuration</code> , the value should be <code>https://accounts.google.com</code>	Yes
<code>--oidc-client-id</code>	A client id that all tokens must be issued for.	kubernetes	Yes
<code>--oidc-username-claim</code>	JWT claim to use as the user name. By default <code>sub</code> , which is expected to be a unique identifier of the end user. Admins can choose other claims, such as <code>email</code> or <code>name</code> , depending on their provider. However, claims other than <code>email</code> will be prefixed with the issuer URL to prevent naming clashes with other plugins.	<code>sub</code>	No

Parameter	Description	Example	Required
<code>--oidc-username-prefix</code>	Prefix prepended to username claims to prevent clashes with existing names (such as <code>system: users</code> ). For example, the value <code>oidc:</code> will create usernames like <code>oidc:jane.doe</code> . If this flag isn't provided and <code>--oidc-user-claim</code> is a value other than email the prefix defaults to <code>( Issuer URL )#</code> where <code>( Issuer URL )</code> is the value of <code>--oidc-issuer-url</code> . The value <code>-</code> can be used to disable all prefixing.	<code>oidc:</code>	No
<code>--oidc-groups-claim</code>	JWT claim to use as the user's group. If the claim is present it must be an array of strings.	<code>groups</code>	No
<code>--oidc-groups-prefix</code>	Prefix prepended to group claims to prevent clashes with existing names (such as <code>system: groups</code> ). For example, the value <code>oidc:</code> will create group names like <code>oidc:engineering</code> and <code>oidc:infra</code> .	<code>oidc:</code>	No
<code>--oidc-required-claim</code>	A key=value pair that describes a required claim in the ID Token. If set, the claim is verified to be present in the ID Token with a matching value. Repeat this flag to specify multiple claims.	<code>claim=value</code>	No

Parameter	Description	Example	Required
<code>--oidc-ca-file</code>	The path to the certificate for the CA that signed your identity provider's web certificate. Defaults to the host's root CAs.	<code>/etc/kubernetes/ssl/kc-ca.pem</code>	No

Importantly, the API server is not an OAuth2 client, rather it can only be configured to trust a single issuer. This allows the use of public providers, such as Google, without trusting credentials issued to third parties. Admins who wish to utilize multiple OAuth clients should explore providers which support the azp (authorized party) claim, a mechanism for allowing one client to issue tokens on behalf of another.

Kubernetes does not provide an OpenID Connect Identity Provider. You can use an existing public OpenID Connect Identity Provider (such as Google, or [others](#)). Or, you can run your own Identity Provider, such as CoreOS [dex](#), [Keycloak](#), CloudFoundry [UAA](#), or Tremolo Security's [OpenUnison](#).

For an identity provider to work with Kubernetes it must:

1. Support [OpenID connect discovery](#); not all do.
2. Run in TLS with non-obsolete ciphers
3. Have a CA signed certificate (even if the CA is not a commercial CA or is self signed)

A note about requirement #3 above, requiring a CA signed certificate. If you deploy your own identity provider (as opposed to one of the cloud providers like Google or Microsoft) you MUST have your identity provider's web server certificate signed by a certificate with the CA flag set to TRUE, even if it is self signed. This is due to GoLang's TLS client implementation being very strict to the standards around certificate validation. If you don't have a CA handy, you can use [this script](#) from the CoreOS team to create a simple CA and a signed certificate and key pair. Or you can use [this similar script](#) that generates SHA256 certs with a longer life and larger key size.

Setup instructions for specific systems:

- [UAA](#)
- [Dex](#)
- [OpenUnison](#)

## Using kubectl

### Option 1 - OIDC Authenticator

The first option is to use the `kubectl oidc` authenticator, which sets the `id_token` as a bearer token for all requests and refreshes the token once it expires. After you've logged into your provider, use `kubectl` to add your `id_token`

oken, refresh\_token, client\_id, and client\_secret to configure the plugin.

Providers that don't return an `id_token` as part of their refresh token response aren't supported by this plugin and should use "Option 2" below.

```
kubectrl config set-credentials USER_NAME \
  --auth-provider=oidc \
  --auth-provider-arg=idp-issuer-url=( issuer url ) \
  --auth-provider-arg=client-id=( your client id ) \
  --auth-provider-arg=client-secret=( your client secret ) \
  --auth-provider-arg=refresh-token=( your refresh token ) \
  --auth-provider-arg=idp-certificate-authority=( path to your
ca certificate ) \
  --auth-provider-arg=id-token=( your id token )
```

As an example, running the below command after authenticating to your identity provider:

```
kubectl config set-credentials mmosley \
--auth-provider=oidc \
--auth-provider-arg=idp-issuer-url=https://
oidcidp.tremolo.lan:8443/auth/idp/OidcIdP \
--auth-provider-arg=client-id=kubernetes \
--auth-provider-arg=client-secret=ldb158f6-177d-4d9c-8a8b
-d36869918ec5 \
--auth-provider-arg=refresh-token=q1bKLF0yUiosTfawzA93TzZ
IDzH2TNa2SMm0zEiPKTUwME6BkEo6Sql5yUWVBSWPkUGphaWpxSVAfekBOZbBhaEW
+VLfUEVRGcluyVF5JT4+haZmPsLuFoFu5XkpXk5BXqHega4GAXlF+ma+vmYpFcHe5
eZR+s1BFpZktQA= \
--auth-provider-arg=idp-certificate-authority=/root/
ca.pem \
--auth-provider-arg=id-token=eyJraWQiOiJDTj1vaWRjaWRwLnRy
ZW1vbG8ubGFuLCBPVT1EZW1vLCBPPVRybWVvbG8gU2VjdXJpdHksIEw9QXJsYW5nd
G9uLCBTVDRlcXJnaW5pYSwgQz1VUy1DTj1rdWJLLWNhLTEyMDIxNDc1MjEwMzYwNz
MyMTUyIiwiaWF0IjoiUlMyNTYifQ.eyJpc3MiOiJodHRwciovLT9pZGNpZHAudHJl
bw9sbys5sYW46ODQ0My9hdXRoL2lkcyC9PaWRJSWRQIiwiaXYxVkIjoia3ViZXJuZXRlc
yIsImV4cCI6MTQ4MzU0OTUxMSwianRpIjoimM96US15TXdfChV4WDlhZUhQdy1hZy
IsImldCI6MTQ4MzU0OTUxMSwibmJmIjoixNDgzNTQ5MzMxLCJzdWIiOiI0YVwiMzdi
YS1iInjQ1LTQ4ZmQtYWIzMC0xYTAxZWU0MWUyMTgifQ.w6p4J_6qQ1HzTG9nrEOru
bxIMb9K5hzcmPxc9IxpX2K4xO9L-
ofIUw93daH3m5pluP6K7eOE6txBuRVfEcpJSwlElS0sw8gb8VJcnzMS9EnZpeAOtW
_p-mnkFc3VcfyXuhe5R3G7aa5d8uhv70yJ9Y3-
UhjiN9EhpMdFPaoEB9fyKKkJRzf7utTTIPGrSaSU6d2pcpfYKaxIwePzEkT4DfcQt
hoZdy9ucNvvLoi1DIC-
UocFD8HLs8LYKEqSXqvOcVnThbObJ9af71Ewmue21f05KzMW20KtAegetlgndOs
Ptz1G5Ewya0401-RPQzPGMVBlD0 zMcAwZttJ4knw
```

Which would produce the below configuration:

```
users:
- name: mmosley
  user:
```





## Webhook Token Authentication

Webhook authentication is a hook for verifying bearer tokens.

- `--authentication-token-webhook-config-file` a configuration file describing how to access the remote webhook service.
- `--authentication-token-webhook-cache-ttl` how long to cache authentication decisions. Defaults to two minutes.

The configuration file uses the [kubeconfig](#) file format. Within the file, `clusters` refers to the remote service and `users` refers to the API server webhook. An example would be:

```
# Kubernetes API version
apiVersion: v1
# kind of the API object
kind: Config
# clusters refers to the remote service.
clusters:
  - name: name-of-remote-authn-service
    cluster:
      certificate-authority: /path/to/ca.pem          # CA for
      server: https://authn.example.com/authenticate # URL of
      verifying the remote service.
      remote service to query. Must use 'https'.

# users refers to the API server's webhook configuration.
users:
  - name: name-of-api-server
    user:
      client-certificate: /path/to/cert.pem # cert for the
      webhook plugin to use
      client-key: /path/to/key.pem         # key matching the
      cert

# kubeconfig files require a context. Provide one for the API
server.
current-context: webhook
contexts:
  - context:
      cluster: name-of-remote-authn-service
      user: name-of-api-sever
      name: webhook
```

When a client attempts to authenticate with the API server using a bearer token as discussed [above](#), the authentication webhook POSTs a JSON-serialized `authentication.k8s.io/v1beta1 TokenReview` object containing the token to the remote service. Kubernetes will not challenge a request that lacks such a header.

Note that webhook API objects are subject to the same [versioning compatibility rules](#) as other Kubernetes API objects. Implementers should be

aware of looser compatibility promises for beta objects and check the "apiVersion" field of the request to ensure correct deserialization. Additionally, the API server must enable the authentication.k8s.io/v1beta1 API extensions group (--runtime-config=authentication.k8s.io/v1beta1=true).

The POST body will be of the following format:

```
{
  "apiVersion": "authentication.k8s.io/v1beta1",
  "kind": "TokenReview",
  "spec": {
    "token": "(BEARERTOKEN)"
  }
}
```

The remote service is expected to fill the status field of the request to indicate the success of the login. The response body's spec field is ignored and may be omitted. A successful validation of the bearer token would return:

```
{
  "apiVersion": "authentication.k8s.io/v1beta1",
  "kind": "TokenReview",
  "status": {
    "authenticated": true,
    "user": {
      "username": "janedoe@example.com",
      "uid": "42",
      "groups": [
        "developers",
        "qa"
      ],
      "extra": {
        "extrafield1": [
          "extravalue1",
          "extravalue2"
        ]
      }
    }
  }
}
```

An unsuccessful request would return:

```
{
  "apiVersion": "authentication.k8s.io/v1beta1",
  "kind": "TokenReview",
  "status": {
    "authenticated": false
  }
}
```

HTTP status codes can be used to supply additional error context.

## Authenticating Proxy

The API server can be configured to identify users from request header values, such as X-Remote-User. It is designed for use in combination with an authenticating proxy, which sets the request header value.

- `--requestheader-username-headers` Required, case-insensitive. Header names to check, in order, for the user identity. The first header containing a value is used as the username.
- `--requestheader-group-headers` 1.6+. Optional, case-insensitive. "X-Remote-Group" is suggested. Header names to check, in order, for the user's groups. All values in all specified headers are used as group names.
- `--requestheader-extra-headers-prefix` 1.6+. Optional, case-insensitive. "X-Remote-Extra-" is suggested. Header prefixes to look for to determine extra information about the user (typically used by the configured authorization plugin). Any headers beginning with any of the specified prefixes have the prefix removed. The remainder of the header name is lowercased and [percent-decoded](#) and becomes the extra key, and the header value is the extra value.

**Note:** Prior to 1.11.3 (and 1.10.7, 1.9.11), the extra key could only contain characters which were [legal in HTTP header labels](#).

For example, with this configuration:

```
--requestheader-username-headers=X-Remote-User
--requestheader-group-headers=X-Remote-Group
--requestheader-extra-headers-prefix=X-Remote-Extra-
```

this request:

```
GET / HTTP/1.1
X-Remote-User: fido
X-Remote-Group: dogs
X-Remote-Group: dachshunds
X-Remote-Extra-Acme.com%2Fproject: some-project
X-Remote-Extra-Scopes: openid
X-Remote-Extra-Scopes: profile
```

would result in this user info:

```
name: fido
groups:
- dogs
- dachshunds
extra:
  acme.com/project:
  - some-project
scopes:
```

```
- openid
- profile
```

In order to prevent header spoofing, the authenticating proxy is required to present a valid client certificate to the API server for validation against the specified CA before the request headers are checked. WARNING: do **not** reuse a CA that is used in a different context unless you understand the risks and the mechanisms to protect the CA's usage.

- `--requestheader-client-ca-file` Required. PEM-encoded certificate bundle. A valid client certificate must be presented and validated against the certificate authorities in the specified file before the request headers are checked for user names.
- `--requestheader-allowed-names` Optional. List of Common Name values (CNs). If set, a valid client certificate with a CN in the specified list must be presented before the request headers are checked for user names. If empty, any CN is allowed.

## Anonymous requests

When enabled, requests that are not rejected by other configured authentication methods are treated as anonymous requests, and given a username of `system:anonymous` and a group of `system:unauthenticated`.

For example, on a server with token authentication configured, and anonymous access enabled, a request providing an invalid bearer token would receive a 401 Unauthorized error. A request providing no bearer token would be treated as an anonymous request.

In 1.5.1-1.5.x, anonymous access is disabled by default, and can be enabled by passing the `--anonymous-auth=true` option to the API server.

In 1.6+, anonymous access is enabled by default if an authorization mode other than `AlwaysAllow` is used, and can be disabled by passing the `--anonymous-auth=false` option to the API server. Starting in 1.6, the ABAC and RBAC authorizers require explicit authorization of the `system:anonymous` user or the `system:unauthenticated` group, so legacy policy rules that grant access to the `* user` or `* group` do not include anonymous users.

## User impersonation

A user can act as another user through impersonation headers. These let requests manually override the user info a request authenticates as. For example, an admin could use this feature to debug an authorization policy by temporarily impersonating another user and seeing if a request was denied.

Impersonation requests first authenticate as the requesting user, then switch to the impersonated user info.

- A user makes an API call with their credentials *and* impersonation headers.

- API server authenticates the user.
- API server ensures the authenticated users have impersonation privileges.
- Request user info is replaced with impersonation values.
- Request is evaluated, authorization acts on impersonated user info.

The following HTTP headers can be used to performing an impersonation request:

- **Impersonate-User:** The username to act as.
- **Impersonate-Group:** A group name to act as. Can be provided multiple times to set multiple groups. Optional. Requires "Impersonate-User"
- **Impersonate-Extra- ( extra name ):** A dynamic header used to associate extra fields with the user. Optional. Requires "Impersonate-User". In order to be preserved consistently, ( extra name ) should be lower-case, and any characters which aren't [legal in HTTP header labels](#) MUST be utf8 and [percent-encoded](#).

**Note:** Prior to 1.11.3 (and 1.10.7, 1.9.11), ( extra name ) could only contain characters which were [legal in HTTP header labels](#).

An example set of headers:

```
Impersonate-User: jane.doe@example.com
Impersonate-Group: developers
Impersonate-Group: admins
Impersonate-Extra-dn: cn=jane,ou=engineers,dc=example,dc=com
Impersonate-Extra-acme.com%2Fproject: some-project
Impersonate-Extra-scopes: view
Impersonate-Extra-scopes: development
```

When using `kubectl` set the `--as` flag to configure the `Impersonate-User` header, set the `--as-group` flag to configure the `Impersonate-Group` header.

```
kubectl drain mynode
```

```
Error from server (Forbidden): User "clark" cannot get nodes at
the cluster scope. (get nodes mynode)
```

Set the `--as` and `--as-group` flag:

```
kubectl drain mynode --as=superman --as-group=system:masters
```

```
node/mynode cordoned
node/mynode drained
```

To impersonate a user, group, or set extra fields, the impersonating user must have the ability to perform the "impersonate" verb on the kind of attribute being impersonated ("user", "group", etc.). For clusters that enable the RBAC authorization plugin, the following `ClusterRole` encompasses the rules needed to set user and group impersonation headers:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
```

```
metadata:
  name: impersonator
rules:
- apiGroups: [""]
  resources: ["users", "groups", "serviceaccounts"]
  verbs: ["impersonate"]
```

Extra fields are evaluated as sub-resources of the resource "userextras". To allow a user to use impersonation headers for the extra field "scopes," a user should be granted the following role:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: scopes-impersonator
rules:
# Can set "Impersonate-Extra-scopes" header.
- apiGroups: ["authentication.k8s.io"]
  resources: ["userextras/scopes"]
  verbs: ["impersonate"]
```

The values of impersonation headers can also be restricted by limiting the set of resourceNames a resource can take.

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: limited-impersonator
rules:
# Can impersonate the user "jane.doe@example.com"
- apiGroups: [""]
  resources: ["users"]
  verbs: ["impersonate"]
  resourceNames: ["jane.doe@example.com"]

# Can impersonate the groups "developers" and "admins"
- apiGroups: [""]
  resources: ["groups"]
  verbs: ["impersonate"]
  resourceNames: ["developers", "admins"]

# Can impersonate the extras field "scopes" with the values
"view" and "development"
- apiGroups: ["authentication.k8s.io"]
  resources: ["userextras/scopes"]
  verbs: ["impersonate"]
  resourceNames: ["view", "development"]
```

## client-go credential plugins

**FEATURE STATE:** Kubernetes v1.11 [beta](#)

This feature is currently in a *beta* state, meaning:

[Edit This Page](#)

# Authenticating with Bootstrap Tokens

Bootstrap tokens are a simple bearer token that is meant to be used when creating new clusters or joining new nodes to an existing cluster. It was built to support [kubeadm](#), but can be used in other contexts for users that wish to start clusters without kubeadm. It is also built to work, via RBAC policy, with the [Kubelet TLS Bootstrapping](#) system.

- [Bootstrap Tokens Overview](#)
- [Token Format](#)
- [Enabling Bootstrap Token Authentication](#)
- [Bootstrap Token Secret Format](#)
- [Token Management with kubeadm](#)
- [ConfigMap Signing](#)

## Bootstrap Tokens Overview

Bootstrap Tokens are defined with a specific type (`bootstrap.kubernetes.io/token`) of secrets that lives in the `kube-system` namespace. These Secrets are then read by the Bootstrap Authenticator in the API Server. Expired tokens are removed with the TokenCleaner controller in the Controller Manager. The tokens are also used to create a signature for a specific ConfigMap used in a "discovery" process through a BootstrapSigner controller.

**FEATURE STATE:** Kubernetes v1.17 [beta](#)

This feature is currently in a *beta* state, meaning:

[Edit This Page](#)

# Using Admission Controllers

This page provides an overview of Admission Controllers.

- [What are they?](#)
- [Why do I need them?](#)
- [How do I turn on an admission controller?](#)
- [How do I turn off an admission controller?](#)
- [Which plugins are enabled by default?](#)
- [What does each admission controller do?](#)
- [Is there a recommended set of admission controllers to use?](#)

## What are they?

An admission controller is a piece of code that intercepts requests to the Kubernetes API server prior to persistence of the object, but after the request is authenticated and authorized. The controllers consist of the [list](#) below, are compiled into the kube-apiserver binary, and may only be configured by the cluster administrator. In that list, there are two special controllers: MutatingAdmissionWebhook and ValidatingAdmissionWebhook. These execute the mutating and validating (respectively) [admission control webhooks](#) which are configured in the API.

Admission controllers may be "validating", "mutating", or both. Mutating controllers may modify the objects they admit; validating controllers may not.

The admission control process proceeds in two phases. In the first phase, mutating admission controllers are run. In the second phase, validating admission controllers are run. Note again that some of the controllers are both.

If any of the controllers in either phase reject the request, the entire request is rejected immediately and an error is returned to the end-user.

Finally, in addition to sometimes mutating the object in question, admission controllers may sometimes have side effects, that is, mutate related resources as part of request processing. Incrementing quota usage is the canonical example of why this is necessary. Any such side-effect needs a corresponding reclamation or reconciliation process, as a given admission controller does not know for sure that a given request will pass all of the other admission controllers.

## Why do I need them?

Many advanced features in Kubernetes require an admission controller to be enabled in order to properly support the feature. As a result, a Kubernetes API server that is not properly configured with the right set of admission controllers is an incomplete server and will not support all the features you expect.

## How do I turn on an admission controller?

The Kubernetes API server flag `enable-admission-plugins` takes a comma-delimited list of admission control plugins to invoke prior to modifying objects in the cluster. For example, the following command line enables the `NamespaceLifecycle` and the `LimitRanger` admission control plugins:

```
kube-apiserver --enable-admission-plugins=NamespaceLifecycle,LimitRanger ...
```

**Note:** Depending on the way your Kubernetes cluster is deployed and how the API server is started, you may need to apply the



settings in different ways. For example, you may have to modify the systemd unit file if the API server is deployed as a systemd service, you may modify the manifest file for the API server if Kubernetes is deployed in a self-hosted way.

## How do I turn off an admission controller?

The Kubernetes API server flag `disable-admission-plugins` takes a comma-delimited list of admission control plugins to be disabled, even if they are in the list of plugins enabled by default.

```
kube-apiserver --disable-admission-plugins=PodNodeSelector,AlwaysDeny ...
```

## Which plugins are enabled by default?

To see which admission plugins are enabled:

```
kube-apiserver -h | grep enable-admission-plugins
```

In 1.16, they are:

```
NamespaceLifecycle, LimitRanger, ServiceAccount,  
TaintNodesByCondition, Priority, DefaultTolerationSeconds,  
DefaultStorageClass, StorageObjectInUseProtection,  
PersistentVolumeClaimResize, MutatingAdmissionWebhook,  
ValidatingAdmissionWebhook, RuntimeClass, ResourceQuota
```

## What does each admission controller do?

### AlwaysAdmit

**FEATURE STATE:** Kubernetes v1.13 [deprecated](#)

This feature is *deprecated*. For more information on this state, see the [Kubernetes Deprecation Policy](#).

This admission controller allows all pods into the cluster. It is deprecated because its behavior is the same as if there were no admission controller at all.

### AlwaysPullImages

This admission controller modifies every new Pod to force the image pull policy to Always. This is useful in a multitenant cluster so that users can be assured that their private images can only be used by those who have the credentials to pull them. Without this admission controller, once an image has been pulled to a node, any pod from any user can use it simply by knowing the image's name (assuming the Pod is scheduled onto the right node), without any authorization check against the image. When this

admission controller is enabled, images are always pulled prior to starting containers, which means valid credentials are required.

## AlwaysDeny

**FEATURE STATE:** Kubernetes v1.13 [deprecated](#)

This feature is *deprecated*. For more information on this state, see the [Kubernetes Deprecation Policy](#).

Rejects all requests. AlwaysDeny is DEPRECATED as no real meaning.

## DefaultStorageClass

This admission controller observes creation of `PersistentVolumeClaim` objects that do not request any specific storage class and automatically adds a default storage class to them. This way, users that do not request any special storage class do not need to care about them at all and they will get the default one.

This admission controller does not do anything when no default storage class is configured. When more than one storage class is marked as default, it rejects any creation of `PersistentVolumeClaim` with an error and an administrator must revisit their `StorageClass` objects and mark only one as default. This admission controller ignores any `PersistentVolumeClaim` updates; it acts only on creation.

See [persistent volume](#) documentation about persistent volume claims and storage classes and how to mark a storage class as default.

## DefaultTolerationSeconds

This admission controller sets the default forgiveness toleration for pods to tolerate the taints `notready:NoExecute` and `unreachable:NoExecute` for 5 minutes, if the pods don't already have toleration for taints `node.kubernetes.io/not-ready:NoExecute` or `node.alpha.kubernetes.io/unreachable:NoExecute`.

## DenyExecOnPrivileged

**FEATURE STATE:** Kubernetes v1.13 [deprecated](#)

This feature is *deprecated*. For more information on this state, see the [Kubernetes Deprecation Policy](#).

This admission controller will intercept all requests to `exec` a command in a pod if that pod has a privileged container.

This functionality has been merged into [DenyEscalatingExec](#). The `DenyExecOnPrivileged` admission plugin is deprecated and will be removed in v1.18.

Use of a policy-based admission plugin (like [PodSecurityPolicy](#) or a custom admission plugin) which can be targeted at specific users or Namespaces

and also protects against creation of overly privileged Pods is recommended instead.

## DenyEscalatingExec

**FEATURE STATE:** Kubernetes v1.13 [deprecated](#)

This feature is *deprecated*. For more information on this state, see the [Kubernetes Deprecation Policy](#).

This admission controller will deny exec and attach commands to pods that run with escalated privileges that allow host access. This includes pods that run as privileged, have access to the host IPC namespace, and have access to the host PID namespace.

The DenyEscalatingExec admission plugin is deprecated and will be removed in v1.18.

Use of a policy-based admission plugin (like [PodSecurityPolicy](#) or a custom admission plugin) which can be targeted at specific users or Namespaces and also protects against creation of overly privileged Pods is recommended instead.

## EventRateLimit

**FEATURE STATE:** Kubernetes v1.13 [alpha](#)

This feature is currently in a *alpha* state, meaning:

[Edit This Page](#)

# Dynamic Admission Control

In addition to [compiled-in admission plugins](#), admission plugins can be developed as extensions and run as webhooks configured at runtime. This page describes how to build, configure, use, and monitor admission webhooks.

- [What are admission webhooks?](#)
- [Experimenting with admission webhooks](#)
- [Webhook request and response](#)
- [Webhook configuration](#)
- [Monitoring admission webhooks](#)
- [Best practices and warnings](#)

## What are admission webhooks?

Admission webhooks are HTTP callbacks that receive admission requests and do something with them. You can define two types of admission webhooks, [validating admission Webhook](#) and [mutating admission webhook](#). Mutating admission Webhooks are invoked first, and can modify objects sent to the API server to enforce custom defaults. After all object modifications

are complete, and after the incoming object is validated by the API server, validating admission webhooks are invoked and can reject requests to enforce custom policies.

**Note:** Admission webhooks that need to guarantee they see the final state of the object in order to enforce policy should use a validating admission webhook, since objects can be modified after being seen by mutating webhooks.

## Experimenting with admission webhooks

Admission webhooks are essentially part of the cluster control-plane. You should write and deploy them with great caution. Please read the [user guides](#) for instructions if you intend to write/deploy production-grade admission webhooks. In the following, we describe how to quickly experiment with admission webhooks.

### Prerequisites

- Ensure that the Kubernetes cluster is at least as new as v1.16 (to use admissionregistration.k8s.io/v1), or v1.9 (to use admissionregistration.k8s.io/v1beta1).
- Ensure that MutatingAdmissionWebhook and ValidatingAdmissionWebhook admission controllers are enabled. [Here](#) is a recommended set of admission controllers to enable in general.
- Ensure that the admissionregistration.k8s.io/v1 or admissionregistration.k8s.io/v1beta1 API is enabled.

### Write an admission webhook server

Please refer to the implementation of the [admission webhook server](#) that is validated in a Kubernetes e2e test. The webhook handles the AdmissionReview request sent by the apiservers, and sends back its decision as an AdmissionReview object in the same version it received.

See the [webhook request](#) section for details on the data sent to webhooks.

See the [webhook response](#) section for the data expected from webhooks.

The example admission webhook server leaves the ClientAuth field [empty](#), which defaults to NoClientCert. This means that the webhook server does not authenticate the identity of the clients, supposedly apiservers. If you need mutual TLS or other ways to authenticate the clients, see how to [authenticate apiservers](#).

## Deploy the admission webhook service

The webhook server in the e2e test is deployed in the Kubernetes cluster, via the [deployment API](#). The test also creates a [service](#) as the front-end of the webhook server. See [code](#).

You may also deploy your webhooks outside of the cluster. You will need to update your webhook configurations accordingly.

## Configure admission webhooks on the fly

You can dynamically configure what resources are subject to what admission webhooks via [ValidatingWebhookConfiguration](#) or [MutatingWebhookConfiguration](#).

The following is an example `ValidatingWebhookConfiguration`, a mutating webhook configuration is similar. See the [webhook configuration](#) section for details about each config field.

- [admissionregistration.k8s.io/v1](#)
- [admissionregistration.k8s.io/v1beta1](#)

```
apiVersion: admissionregistration.k8s.io/v1
kind: ValidatingWebhookConfiguration
metadata:
  name: "pod-policy.example.com"
webhooks:
- name: "pod-policy.example.com"
  rules:
  - apiGroups:  [""]
    apiVersions: ["v1"]
    operations:  ["CREATE"]
    resources:   ["pods"]
    scope:       "Namespaced"
  clientConfig:
    service:
      namespace: "example-namespace"
      name: "example-service"
      caBundle: "Ci0tLS0tQk...<base64-encoded PEM bundle
containing the CA that signed the webhook's serving
certificate>...tLS0K"
    admissionReviewVersions: ["v1", "v1beta1"]
    sideEffects: None
    timeoutSeconds: 5
```

[Edit This Page](#)

# Managing Service Accounts

This is a Cluster Administrator guide to service accounts. It assumes knowledge of the [User Guide to Service Accounts](#).

Support for authorization and user accounts is planned but incomplete. Sometimes incomplete features are referred to in order to better describe service accounts.

- [User accounts versus service accounts](#)
- [Service account automation](#)

## User accounts versus service accounts

Kubernetes distinguishes between the concept of a user account and a service account for a number of reasons:

- User accounts are for humans. Service accounts are for processes, which run in pods.
- User accounts are intended to be global. Names must be unique across all namespaces of a cluster, future user resource will not be namespaced. Service accounts are namespaced.
- Typically, a cluster's User accounts might be synced from a corporate database, where new user account creation requires special privileges and is tied to complex business processes. Service account creation is intended to be more lightweight, allowing cluster users to create service accounts for specific tasks (i.e. principle of least privilege).
- Auditing considerations for humans and service accounts may differ.
- A config bundle for a complex system may include definition of various service accounts for components of that system. Because service accounts can be created ad-hoc and have namespaced names, such config is portable.

## Service account automation

Three separate components cooperate to implement the automation around service accounts:

- A Service account admission controller
- A Token controller
- A Service account controller

### Service Account Admission Controller

The modification of pods is implemented via a plugin called an [Admission Controller](#). It is part of the apiserver. It acts synchronously to modify pods as they are created or updated. When this plugin is active (and it is by default on most distributions), then it does the following when a pod is created or modified:

1. If the pod does not have a ServiceAccount set, it sets the ServiceAccount to default.
2. It ensures that the ServiceAccount referenced by the pod exists, and otherwise rejects it.
3. If the pod does not contain any ImagePullSecrets, then ImagePullSecrets of the ServiceAccount are added to the pod.

4. It adds a volume to the pod which contains a token for API access.
5. It adds a volumeSource to each container of the pod mounted at `/var/run/secrets/kubernetes.io/serviceaccount`.

Starting from v1.13, you can migrate a service account volume to a projected volume when the `BoundServiceAccountTokenVolume` feature gate is enabled. The service account token will expire after 1 hour or the pod is deleted. See more details about [projected volume](#).

## Token Controller

TokenController runs as part of controller-manager. It acts asynchronously. It:

- observes serviceAccount creation and creates a corresponding Secret to allow API access.
- observes serviceAccount deletion and deletes all corresponding ServiceAccountToken Secrets.
- observes secret addition, and ensures the referenced ServiceAccount exists, and adds a token to the secret if needed.
- observes secret deletion and removes a reference from the corresponding ServiceAccount if needed.

You must pass a service account private key file to the token controller in the controller-manager by using the `--service-account-private-key-file` option. The private key will be used to sign generated service account tokens. Similarly, you must pass the corresponding public key to the kube-apiserver using the `--service-account-key-file` option. The public key will be used to verify the tokens during authentication.

### To create additional API tokens

A controller loop ensures a secret with an API token exists for each service account. To create additional API tokens for a service account, create a secret of type `ServiceAccountToken` with an annotation referencing the service account, and the controller will update it with a generated token:

secret.json:

```
{
  "kind": "Secret",
  "apiVersion": "v1",
  "metadata": {
    "name": "mysecretname",
    "annotations": {
      "kubernetes.io/service-account.name": "myserviceaccount"
    }
  },
  "type": "kubernetes.io/service-account-token"
}
```

```
kubectl create -f ./secret.json
kubectl describe secret mysecretname
```

### **To delete/invalidate a service account token**

```
kubectl delete secret mysecretname
```

## **Service Account Controller**

Service Account Controller manages ServiceAccount inside namespaces, and ensures a ServiceAccount named "default" exists in every active namespace.

## **Feedback**

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---



[Create an Issue](#) [Edit This Page](#)

Page last modified on February 18, 2020 at 7:42 PM PST by [latin phrase removed \(#19180\)](#) ([Page History](#))

[Edit This Page](#)

# Authorization Overview

Learn more about Kubernetes authorization, including details about creating policies using the supported authorization modules.

- [Determine Whether a Request is Allowed or Denied](#)
- [Review Your Request Attributes](#)
- [Determine the Request Verb](#)
- [Authorization Modes](#)
- [Using Flags for Your Authorization Module](#)

- [Privilege escalation via pod creation](#)
- [What's next](#)

In Kubernetes, you must be authenticated (logged in) before your request can be authorized (granted permission to access). For information about authentication, see [Accessing Control Overview](#).

Kubernetes expects attributes that are common to REST API requests. This means that Kubernetes authorization works with existing organization-wide or cloud-provider-wide access control systems which may handle other APIs besides the Kubernetes API.

## Determine Whether a Request is Allowed or Denied

Kubernetes authorizes API requests using the API server. It evaluates all of the request attributes against all policies and allows or denies the request. All parts of an API request must be allowed by some policy in order to proceed. This means that permissions are denied by default.

(Although Kubernetes uses the API server, access controls and policies that depend on specific fields of specific kinds of objects are handled by Admission Controllers.)

When multiple authorization modules are configured, each is checked in sequence. If any authorizer approves or denies a request, that decision is immediately returned and no other authorizer is consulted. If all modules have no opinion on the request, then the request is denied. A deny returns an HTTP status code 403.

## Review Your Request Attributes

Kubernetes reviews only the following API request attributes:

- **user** - The user string provided during authentication.
- **group** - The list of group names to which the authenticated user belongs.
- **extra** - A map of arbitrary string keys to string values, provided by the authentication layer.
- **API** - Indicates whether the request is for an API resource.
- **Request path** - Path to miscellaneous non-resource endpoints like `/api` or `/healthz`.
- **API request verb** - API verbs like `get`, `list`, `create`, `update`, `patch`, `watch`, `delete`, and `deletecollection` are used for resource requests. To determine the request verb for a resource API endpoint, see [Determine the request verb](#).
- **HTTP request verb** - Lowercased HTTP methods like `get`, `post`, `put`, and `delete` are used for non-resource requests.

- **Resource** - The ID or name of the resource that is being accessed (for resource requests only) - For resource requests using `get`, `update`, `patch`, and `delete` verbs, you must provide the resource name.
- **Subresource** - The subresource that is being accessed (for resource requests only).
- **Namespace** - The namespace of the object that is being accessed (for namespaced resource requests only).
- **API group** - The [API Group](#) [A set of related paths in the Kubernetes API](#) being accessed (for resource requests only). An empty string designates the [core API group](#).

## Determine the Request Verb

**Non-resource requests** Requests to endpoints other than `/api/v1/...` or `/apis/<group>/<version>/...` are considered "non-resource requests", and use the lower-cased HTTP method of the request as the verb. For example, a GET request to endpoints like `/api` or `/healthz` would use `get` as the verb.

**Resource requests** To determine the request verb for a resource API endpoint, review the HTTP verb used and whether or not the request acts on an individual resource or a collection of resources:

HTTP verb	request verb
POST	create
GET, HEAD	get (for individual resources), list (for collections, including full object content), watch (for watching an individual resource or collection of resources)
PUT	update
PATCH	patch
DELETE	delete (for individual resources), deletecollection (for collections)

Kubernetes sometimes checks authorization for additional permissions using specialized verbs. For example:

- [PodSecurityPolicy](#)
  - use verb on `podsecuritypolicies` resources in the policy API group.
- [RBAC](#)
  - `bind` and `escalate` verbs on `roles` and `clusterroles` resources in the `rbac.authorization.k8s.io` API group.
- [Authentication](#)
  - `impersonate` verb on `users`, `groups`, and `serviceaccounts` in the core API group, and the `userextras` in the `authentication.k8s.io` API group.

# Authorization Modes

The Kubernetes API server may authorize a request using one of several authorization modes:

- **Node** - A special-purpose authorization mode that grants permissions to kubelets based on the pods they are scheduled to run. To learn more about using the Node authorization mode, see [Node Authorization](#).
- **ABAC** - Attribute-based access control (ABAC) defines an access control paradigm whereby access rights are granted to users through the use of policies which combine attributes together. The policies can use any type of attributes (user attributes, resource attributes, object, environment attributes, etc). To learn more about using the ABAC mode, see [ABAC Mode](#).
- **RBAC** - Role-based access control (RBAC) is a method of regulating access to computer or network resources based on the roles of individual users within an enterprise. In this context, access is the ability of an individual user to perform a specific task, such as view, create, or modify a file. To learn more about using the RBAC mode, see [RBAC Mode](#)
  - When specified RBAC (Role-Based Access Control) uses the `rbac.authorization.k8s.io` API group to drive authorization decisions, allowing admins to dynamically configure permission policies through the Kubernetes API.
  - To enable RBAC, start the apiserver with `--authorization-mode=RBAC`.
- **Webhook** - A WebHook is an HTTP callback: an HTTP POST that occurs when something happens; a simple event-notification via HTTP POST. A web application implementing WebHooks will POST a message to a URL when certain things happen. To learn more about using the Webhook mode, see [Webhook Mode](#).

## Checking API Access

`kubectl` provides the `auth can-i` subcommand for quickly querying the API authorization layer. The command uses the `SelfSubjectAccessReview` API to determine if the current user can perform a given action, and works regardless of the authorization mode used.

```
kubectl auth can-i create deployments --namespace dev
```

```
yes
```

```
kubectl auth can-i create deployments --namespace prod
```

```
no
```

Administrators can combine this with [user impersonation](#) to determine what action other users can perform.

```
kubectl auth can-i list secrets --namespace dev --as dave
```

no

SelfSubjectAccessReview is part of the `authorization.k8s.io` API group, which exposes the API server authorization to external services. Other resources in this group include:

- `SubjectAccessReview` - Access review for any user, not just the current one. Useful for delegating authorization decisions to the API server. For example, the kubelet and extension API servers use this to determine user access to their own APIs.
- `LocalSubjectAccessReview` - Like `SubjectAccessReview` but restricted to a specific namespace.
- `SelfSubjectRulesReview` - A review which returns the set of actions a user can perform within a namespace. Useful for users to quickly summarize their own access, or for UIs to hide/show actions.

These APIs can be queried by creating normal Kubernetes resources, where the response "status" field of the returned object is the result of the query.

```
kubectl create -f - -o yaml << EOF
```

```
apiVersion: authorization.k8s.io/v1
kind: SelfSubjectAccessReview
spec:
  resourceAttributes:
    group: apps
    resource: deployments
    verb: create
    namespace: dev
EOF
```

```
apiVersion: authorization.k8s.io/v1
kind: SelfSubjectAccessReview
metadata:
  creationTimestamp: null
spec:
  resourceAttributes:
    group: apps
    resource: deployments
    namespace: dev
    verb: create
status:
  allowed: true
  denied: false
```

## Using Flags for Your Authorization Module

You must include a flag in your policy to indicate which authorization module your policies include:

The following flags can be used:

- `--authorization-mode=ABAC` Attribute-Based Access Control (ABAC) mode allows you to configure policies using local files.
- `--authorization-mode=RBAC` Role-based access control (RBAC) mode allows you to create and store policies using the Kubernetes API.
- `--authorization-mode=Webhook` WebHook is an HTTP callback mode that allows you to manage authorization using a remote REST endpoint.
- `--authorization-mode=Node` Node authorization is a special-purpose authorization mode that specifically authorizes API requests made by kubelets.
- `--authorization-mode=AlwaysDeny` This flag blocks all requests. Use this flag only for testing.
- `--authorization-mode=AlwaysAllow` This flag allows all requests. Use this flag only if you do not require authorization for your API requests.

You can choose more than one authorization module. Modules are checked in order so an earlier module has higher priority to allow or deny a request.

## Privilege escalation via pod creation

Users who have the ability to create pods in a namespace can potentially escalate their privileges within that namespace. They can create pods that access their privileges within that namespace. They can create pods that access secrets the user cannot themselves read, or that run under a service account with different/greater permissions.

**Caution:** System administrators, use care when granting access to pod creation. A user granted permission to create pods (or controllers that create pods) in the namespace can: read all secrets in the namespace; read all config maps in the namespace; and impersonate any service account in the namespace and take any action the account could take. This applies regardless of authorization mode.

## What's next

- To learn more about Authentication, see **Authentication** in [Controlling Access to the Kubernetes API](#).
- To learn more about Admission Control, see [Using Admission Controllers](#).

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 23, 2019 at 11:42 AM PST by [Add "API group" to glossary #15906 \(#16192\)](#) ([Page History](#))

[Edit This Page](#)

# Using RBAC Authorization

Role-based access control (RBAC) is a method of regulating access to computer or network resources based on the roles of individual users within an enterprise.

- [API Overview](#)
- [Default Roles and Role Bindings](#)
- [Privilege Escalation Prevention and Bootstrapping](#)
- [Command-line Utilities](#)
- [Service Account Permissions](#)
- [Upgrading from 1.5](#)
- [Permissive RBAC Permissions](#)

RBAC uses the `rbac.authorization.k8s.io` [API Group](#) [A set of related paths in the Kubernetes API](#), to drive authorization decisions, allowing admins to dynamically configure policies through the Kubernetes API.

As of 1.8, RBAC mode is stable and backed by the `rbac.authorization.k8s.io/v1` API.

To enable RBAC, start the apiserver with `--authorization-mode=RBAC`.

## API Overview

The RBAC API declares four top-level types which will be covered in this section. Users can interact with these resources as they would with any other API resource (via `kubectl`, API calls, etc.). For instance, `kubectl apply -f (resource).yaml` can be used with any of these examples, though readers who wish to follow along should review the section on bootstrapping first.

## Role and ClusterRole

In the RBAC API, a role contains rules that represent a set of permissions. Permissions are purely additive (there are no "deny" rules). A role can be defined within a namespace with a `Role`, or cluster-wide with a `ClusterRole`.

A `Role` can only be used to grant access to resources within a single namespace. Here's an example `Role` in the "default" namespace that can be used to grant read access to pods:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: Role
metadata:
  namespace: default
  name: pod-reader
rules:
- apiGroups: ["" ] # "" indicates the core API group
```



```
resources: ["pods"]
verbs: ["get", "watch", "list"]
```

A ClusterRole can be used to grant the same permissions as a Role, but because they are cluster-scoped, they can also be used to grant access to:

- cluster-scoped resources (like nodes)
- non-resource endpoints (like "/healthz")
- namespaced resources (like pods) across all namespaces (needed to run `kubectl get pods --all-namespaces`, for example)

The following ClusterRole can be used to grant read access to secrets in any particular namespace, or across all namespaces (depending on how it is [bound](#)):

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  # "namespace" omitted since ClusterRoles are not namespaced
  name: secret-reader
rules:
- apiGroups: [""]
  resources: ["secrets"]
  verbs: ["get", "watch", "list"]
```

## RoleBinding and ClusterRoleBinding

A role binding grants the permissions defined in a role to a user or set of users. It holds a list of subjects (users, groups, or service accounts), and a reference to the role being granted. Permissions can be granted within a namespace with a RoleBinding, or cluster-wide with a ClusterRoleBinding.

A RoleBinding may reference a Role in the same namespace. The following RoleBinding grants the "pod-reader" role to the user "jane" within the "default" namespace. This allows "jane" to read pods in the "default" namespace.

roleRef is how you will actually create the binding. The kind will be either Role or ClusterRole, and the name will reference the name of the specific Role or ClusterRole you want. In the example below, this RoleBinding is using roleRef to bind the user "jane" to the Role created above named pod-reader.

```
apiVersion: rbac.authorization.k8s.io/v1
# This role binding allows "jane" to read pods in the "default" namespace.
kind: RoleBinding
metadata:
  name: read-pods
  namespace: default
subjects:
```

```
- kind: User
  name: jane # Name is case sensitive
  apiGroup: rbac.authorization.k8s.io
roleRef:
  kind: Role #this must be Role or ClusterRole
  name: pod-reader # this must match the name of the Role or ClusterRole you wish to bind to
  apiGroup: rbac.authorization.k8s.io
```

A RoleBinding may also reference a ClusterRole to grant the permissions to namespaced resources defined in the ClusterRole within the RoleBinding's namespace. This allows administrators to define a set of common roles for the entire cluster, then reuse them within multiple namespaces.

For instance, even though the following RoleBinding refers to a ClusterRole, "dave" (the subject, case sensitive) will only be able to read secrets in the "development" namespace (the namespace of the RoleBinding).

```
apiVersion: rbac.authorization.k8s.io/v1
# This role binding allows "dave" to read secrets in the "development" namespace.
kind: RoleBinding
metadata:
  name: read-secrets
  namespace: development # This only grants permissions within the "development" namespace.
subjects:
- kind: User
  name: dave # Name is case sensitive
  apiGroup: rbac.authorization.k8s.io
roleRef:
  kind: ClusterRole
  name: secret-reader
  apiGroup: rbac.authorization.k8s.io
```

Finally, a ClusterRoleBinding may be used to grant permission at the cluster level and in all namespaces. The following ClusterRoleBinding allows any user in the group "manager" to read secrets in any namespace.

```
apiVersion: rbac.authorization.k8s.io/v1
# This cluster role binding allows anyone in the "manager" group to read secrets in any namespace.
kind: ClusterRoleBinding
metadata:
  name: read-secrets-global
subjects:
- kind: Group
  name: manager # Name is case sensitive
  apiGroup: rbac.authorization.k8s.io
roleRef:
  kind: ClusterRole
```

```
name: secret-reader
apiGroup: rbac.authorization.k8s.io
```

You cannot modify which Role or ClusterRole a binding object refers to. Attempts to change the `roleRef` field of a binding object will result in a validation error. To change the `roleRef` field on an existing binding object, the binding object must be deleted and recreated. There are two primary reasons for this restriction:

1. A binding to a different role is a fundamentally different binding. Requiring a binding to be deleted/recreated in order to change the `roleRef` ensures the full list of subjects in the binding is intended to be granted the new role (as opposed to enabling accidentally modifying just the `roleRef` without verifying all of the existing subjects should be given the new role's permissions).
2. Making `roleRef` immutable allows giving update permission on an existing binding object to a user, which lets them manage the list of subjects, without being able to change the role that is granted to those subjects.

The `kubectl auth reconcile` command-line utility creates or updates a manifest file containing RBAC objects, and handles deleting and recreating binding objects if required to change the role they refer to. See [command usage and examples](#) for more information.

## Referring to Resources

Most resources are represented by a string representation of their name, such as "pods", just as it appears in the URL for the relevant API endpoint. However, some Kubernetes APIs involve a "subresource", such as the logs for a pod. The URL for the pods logs endpoint is:

```
GET /api/v1/namespaces/{namespace}/pods/{name}/log
```

In this case, "pods" is the namespaced resource, and "log" is a subresource of pods. To represent this in an RBAC role, use a slash to delimit the resource and subresource. To allow a subject to read both pods and pod logs, you would write:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: Role
metadata:
  namespace: default
  name: pod-and-pod-logs-reader
rules:
- apiGroups: [""]
  resources: ["pods", "pods/log"]
  verbs: ["get", "list"]
```

Resources can also be referred to by name for certain requests through the `resourceNames` list. When specified, requests can be restricted to individual

instances of a resource. To restrict a subject to only "get" and "update" a single configmap, you would write:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: Role
metadata:
  namespace: default
  name: configmap-updater
rules:
- apiGroups: [""]
  resources: ["configmaps"]
  resourceNames: ["my-configmap"]
  verbs: ["update", "get"]
```

Note that create requests cannot be restricted by resourceName, as the object name is not known at authorization time. The other exception is deletecollection.

## Aggregated ClusterRoles

As of 1.9, ClusterRoles can be created by combining other ClusterRoles using an aggregationRule. The permissions of aggregated ClusterRoles are controller-managed, and filled in by unioning the rules of any ClusterRole that matches the provided label selector. An example aggregated ClusterRole:

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: monitoring
aggregationRule:
  clusterRoleSelectors:
  - matchLabels:
      rbac.example.com/aggregate-to-monitoring: "true"
rules: [] # Rules are automatically filled in by the controller manager.
```

Creating a ClusterRole that matches the label selector will add rules to the aggregated ClusterRole. In this case rules can be added to the "monitoring" ClusterRole by creating another ClusterRole that has the label `rbac.example.com/aggregate-to-monitoring: true`.

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: monitoring-endpoints
  labels:
    rbac.example.com/aggregate-to-monitoring: "true"
# These rules will be added to the "monitoring" role.
rules:
- apiGroups: [""]
```

```
resources: ["services", "endpoints", "pods"]
verbs: ["get", "list", "watch"]
```

The default user-facing roles (described below) use ClusterRole aggregation. This lets admins include rules for custom resources, such as those served by CustomResourceDefinitions or Aggregated API servers, on the default roles.

For example, the following ClusterRoles let the "admin" and "edit" default roles manage the custom resource "CronTabs" and the "view" role perform read-only actions on the resource.

```
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: aggregate-cron-tabs-edit
  labels:
    # Add these permissions to the "admin" and "edit" default
    # roles.
    rbac.authorization.k8s.io/aggregate-to-admin: "true"
    rbac.authorization.k8s.io/aggregate-to-edit: "true"
rules:
- apiGroups: ["stable.example.com"]
  resources: ["crontabs"]
  verbs: ["get", "list", "watch", "create", "update", "patch", "delete"]
---
kind: ClusterRole
apiVersion: rbac.authorization.k8s.io/v1
metadata:
  name: aggregate-cron-tabs-view
  labels:
    # Add these permissions to the "view" default role.
    rbac.authorization.k8s.io/aggregate-to-view: "true"
rules:
- apiGroups: ["stable.example.com"]
  resources: ["crontabs"]
  verbs: ["get", "list", "watch"]
```

## Role Examples

Only the `rules` section is shown in the following examples.

Allow reading the resource "pods" in the core [API Group](#)[A set of related paths in the Kubernetes API.](#) :

```
rules:
- apiGroups: [""]
  resources: ["pods"]
  verbs: ["get", "list", "watch"]
```

Allow reading/writing "deployments" in both the "extensions" and "apps" API groups:

```
rules:
- apiGroups: ["extensions", "apps"]
  resources: ["deployments"]
  verbs: ["get", "list", "watch", "create", "update", "patch", "delete"]
```

Allow reading "pods" and reading/writing "jobs":

```
rules:
- apiGroups: [""]
  resources: ["pods"]
  verbs: ["get", "list", "watch"]
- apiGroups: ["batch", "extensions"]
  resources: ["jobs"]
  verbs: ["get", "list", "watch", "create", "update", "patch", "delete"]
```

Allow reading a ConfigMap named "my-config" (must be bound with a RoleBinding to limit to a single ConfigMap in a single namespace):

```
rules:
- apiGroups: [""]
  resources: ["configmaps"]
  resourceNames: ["my-config"]
  verbs: ["get"]
```

Allow reading the resource "nodes" in the core group (because a Node is cluster-scoped, this must be in a ClusterRole bound with a ClusterRoleBinding to be effective):

```
rules:
- apiGroups: [""]
  resources: ["nodes"]
  verbs: ["get", "list", "watch"]
```

Allow "GET" and "POST" requests to the non-resource endpoint "/healthz" and all subpaths (must be in a ClusterRole bound with a ClusterRoleBinding to be effective):

```
rules:
- nonResourceURLs: ["/healthz", "/healthz/*"] # '*' in a
  nonResourceURL is a suffix glob match
  verbs: ["get", "post"]
```

## Referring to Subjects

A RoleBinding or ClusterRoleBinding binds a role to *subjects*. Subjects can be groups, users or service accounts.

Users are represented by strings. These can be plain usernames, like "alice", email-style names, like "bob@example.com", or numeric IDs represented as a string. It is up to the Kubernetes admin to configure the [authentication modules](#) to produce usernames in the desired format. The RBAC

authorization system does not require any particular format. However, the prefix `system:` is reserved for Kubernetes system use, and so the admin should ensure usernames do not contain this prefix by accident.

Group information in Kubernetes is currently provided by the Authenticator modules. Groups, like users, are represented as strings, and that string has no format requirements, other than that the prefix `system:` is reserved.

[Service Accounts](#) have usernames with the `system:serviceaccount:` prefix and belong to groups with the `system:serviceaccounts:` prefix.

## Role Binding Examples

Only the `subjects` section of a `RoleBinding` is shown in the following examples.

For a user named "alice@example.com":

```
subjects:
- kind: User
  name: "alice@example.com"
  apiGroup: rbac.authorization.k8s.io
```

For a group named "frontend-admins":

```
subjects:
- kind: Group
  name: "frontend-admins"
  apiGroup: rbac.authorization.k8s.io
```

For the default service account in the kube-system namespace:

```
subjects:
- kind: ServiceAccount
  name: default
  namespace: kube-system
```

For all service accounts in the "qa" namespace:

```
subjects:
- kind: Group
  name: system:serviceaccounts:qa
  apiGroup: rbac.authorization.k8s.io
```

For all service accounts everywhere:

```
subjects:
- kind: Group
  name: system:serviceaccounts
  apiGroup: rbac.authorization.k8s.io
```

For all authenticated users (version 1.5+):

```
subjects:
- kind: Group
  name: system:authenticated
  apiGroup: rbac.authorization.k8s.io
```

For all unauthenticated users (version 1.5+):

```
subjects:
- kind: Group
  name: system:unauthenticated
  apiGroup: rbac.authorization.k8s.io
```

For all users (version 1.5+):

```
subjects:
- kind: Group
  name: system:authenticated
  apiGroup: rbac.authorization.k8s.io
- kind: Group
  name: system:unauthenticated
  apiGroup: rbac.authorization.k8s.io
```

## Default Roles and Role Bindings

API servers create a set of default `ClusterRole` and `ClusterRoleBinding` objects. Many of these are `system:` prefixed, which indicates that the resource is "owned" by the infrastructure. Modifications to these resources can result in non-functional clusters. One example is the `system:node` `ClusterRole`. This role defines permissions for kubelets. If the role is modified, it can prevent kubelets from working.

All of the default cluster roles and rolebindings are labeled with `kubernetes.io/bootstrapping=rbac-defaults`.

### Auto-reconciliation

At each start-up, the API server updates default cluster roles with any missing permissions, and updates default cluster role bindings with any missing subjects. This allows the cluster to repair accidental modifications, and to keep roles and rolebindings up-to-date as permissions and subjects change in new releases.

To opt out of this reconciliation, set the `rbac.authorization.kubernetes.io/autoupdate` annotation on a default cluster role or rolebinding to `false`. Be aware that missing default permissions and subjects can result in non-functional clusters.

Auto-reconciliation is enabled in Kubernetes version 1.6+ when the RBAC authorizer is active.



## Discovery Roles

Default role bindings authorize unauthenticated and authenticated users to read API information that is deemed safe to be publicly accessible (including CustomResourceDefinitions). To disable anonymous unauthenticated access add `--anonymous-auth=false` to the API server configuration.

To view the configuration of these roles via `kubectl` run:

```
kubectl get clusterroles system:discovery -o yaml
```

NOTE: editing the role is not recommended as changes will be overwritten on API server restart via auto-reconciliation (see above).

Default ClusterRole	Default ClusterRoleBinding	Description
<b>system:basic-user</b>	<b>system:authenticated</b> group	Allows a user read-only access to basic information about themselves. Prior to 1.14, this role was also bound to <code>system:unauthenticated</code> by default.
<b>system:discovery</b>	<b>system:authenticated</b> group	Allows read-only access to API discovery endpoints needed to discover and negotiate an API level. Prior to 1.14, this role was also bound to <code>system:unauthenticated</code> by default.
<b>system:public-info-viewer</b>	<b>system:authenticated</b> and <b>system:unauthenticated</b> groups	Allows read-only access to non-sensitive information about the cluster. Introduced in 1.14.

## User-facing Roles

Some of the default roles are not `system:` prefixed. These are intended to be user-facing roles. They include super-user roles (`cluster-admin`), roles intended to be granted cluster-wide using ClusterRoleBindings (`cluster-status`), and roles intended to be granted within particular namespaces using RoleBindings (`admin`, `edit`, `view`).

As of 1.9, user-facing roles use [ClusterRole Aggregation](#) to allow admins to include rules for custom resources on these roles. To add rules to the "admin", "edit", or "view" role, create a ClusterRole with one or more of the following labels:

```
metadata:
  labels:
    rbac.authorization.k8s.io/aggregate-to-admin: "true"
    rbac.authorization.k8s.io/aggregate-to-edit: "true"
    rbac.authorization.k8s.io/aggregate-to-view: "true"
```

Default ClusterRole	Default ClusterRoleBinding	Description
<b>cluster-admin</b>	<b>system:masters</b> group	Allows super-user access to perform any action on any resource. When used in a <b>ClusterRoleBinding</b> , it gives full control over every resource in the cluster and in all namespaces. When used in a <b>RoleBinding</b> , it gives full control over every resource in the rolebinding's namespace, including the namespace itself.
<b>admin</b>	None	Allows admin access, intended to be granted within a namespace using a <b>RoleBinding</b> . If used in a <b>RoleBinding</b> , allows read/write access to most resources in a namespace, including the ability to create roles and rolebindings within the namespace. It does not allow write access to resource quota or to the namespace itself.
<b>edit</b>	None	Allows read/write access to most objects in a namespace. It does not allow viewing or modifying roles or rolebindings.
<b>view</b>	None	Allows read-only access to see most objects in a namespace. It does not allow viewing roles or rolebindings. It does not allow viewing secrets, since those are escalating.

## Core Component Roles

Default ClusterRole	Default ClusterRoleBinding	Description
<b>system:kube-scheduler</b>	<b>system:kube-scheduler</b> user	Allows access to the resources required by the kube-scheduler component.
<b>system:volume-scheduler</b>	<b>system:kube-scheduler</b> user	Allows access to the volume resources required by the kube-scheduler component.

<b>system:kube-controller-manager</b>	<b>system:kube-controller-manager</b> user	Allows access to the resources required by the kube-controller-manager component. The permissions required by individual control loops are contained in the <a href="#">controller roles</a> .
<b>system:node</b>	None in 1.8+	Allows access to resources required by the kubelet component, <b>including read access to all secrets, and write access to all pod status objects</b> . As of 1.7, use of the <a href="#">Node authorizer</a> and <a href="#">NodeRestriction admission plugin</a> is recommended instead of this role, and allow granting API access to kubelets based on the pods scheduled to run on them. Prior to 1.7, this role was automatically bound to the `system:nodes` group. In 1.7, this role was automatically bound to the `system:nodes` group if the `Node` authorization mode is not enabled. In 1.8+, no binding is automatically created.
<b>system:node-proxier</b>	<b>system:kube-proxy</b> user	Allows access to the resources required by the kube-proxy component.

## Other Component Roles

Default ClusterRole	Default ClusterRoleBinding	Description
<b>system:auth-delegator</b>	None	Allows delegated authentication and authorization checks. This is commonly used by add-on API servers for unified authentication and authorization.
<b>system:heapster</b>	None	Role for the <a href="#">Heapster</a> component.
<b>system:kube-aggregator</b>	None	Role for the <a href="#">kube-aggregator</a> component.
<b>system:kube-dns</b>	<b>kube-dns</b> service account in the <b>kube-system</b> namespace	Role for the <a href="#">kube-dns</a> component.
<b>system:kubelet-api-admin</b>	None	Allows full access to the kubelet API.

<b>system:node-bootstrapper</b>	None	Allows access to the resources required to perform <a href="#">Kubelet TLS bootstrapping</a> .
<b>system:node-problem-detector</b>	None	Role for the <a href="#">node-problem-detector</a> component.
<b>system:persistent-volume-provisioner</b>	None	Allows access to the resources required by most <a href="#">dynamic volume provisioners</a> .

## Controller Roles

The [Kubernetes controller manager](#) runs core control loops. When invoked with `--use-service-account-credentials`, each control loop is started using a separate service account. Corresponding roles exist for each control loop, prefixed with `system:controller:`. If the controller manager is not started with `--use-service-account-credentials`, it runs all control loops using its own credential, which must be granted all the relevant roles. These roles include:

- `system:controller:attachdetach-controller`
- `system:controller:certificate-controller`
- `system:controller:clusterrole-aggregation-controller`
- `system:controller:cronjob-controller`
- `system:controller:daemon-set-controller`
- `system:controller:deployment-controller`
- `system:controller:disruption-controller`
- `system:controller:endpoint-controller`
- `system:controller:expand-controller`
- `system:controller:generic-garbage-collector`
- `system:controller:horizontal-pod-autoscaler`
- `system:controller:job-controller`
- `system:controller:namespace-controller`
- `system:controller:node-controller`
- `system:controller:persistent-volume-binder`
- `system:controller:pod-garbage-collector`
- `system:controller:pv-protection-controller`
- `system:controller:pvc-protection-controller`
- `system:controller:replicaset-controller`
- `system:controller:replication-controller`
- `system:controller:resourcequota-controller`
- `system:controller:root-ca-cert-publisher`
- `system:controller:route-controller`
- `system:controller:service-account-controller`
- `system:controller:service-controller`
- `system:controller:statefulset-controller`
- `system:controller:ttl-controller`

# Privilege Escalation Prevention and Bootstrapping

The RBAC API prevents users from escalating privileges by editing roles or role bindings. Because this is enforced at the API level, it applies even when the RBAC authorizer is not in use.

A user can only create/update a role if at least one of the following things is true:

1. They already have all the permissions contained in the role, at the same scope as the object being modified (cluster-wide for a `ClusterRole`, within the same namespace or cluster-wide for a `Role`)
2. They are given explicit permission to perform the `escalate` verb on the `roles` or `clusterroles` resource in the `rbac.authorization.k8s.io` API group (Kubernetes 1.12 and newer)

For example, if "user-1" does not have the ability to list secrets cluster-wide, they cannot create a `ClusterRole` containing that permission. To allow a user to create/update roles:

1. Grant them a role that allows them to create/update `Role` or `ClusterRole` objects, as desired.
2. Grant them permission to include specific permissions in the roles they create/update:
  - implicitly, by giving them those permissions (if they attempt to create or modify a `Role` or `ClusterRole` with permissions they themselves have not been granted, the API request will be forbidden)
  - or explicitly allow specifying any permission in a `Role` or `ClusterRole` by giving them permission to perform the `escalate` verb on `roles` or `clusterroles` resources in the `rbac.authorization.k8s.io` API group (Kubernetes 1.12 and newer)

A user can only create/update a role binding if they already have all the permissions contained in the referenced role (at the same scope as the role binding) *or* if they've been given explicit permission to perform the `bind` verb on the referenced role. For example, if "user-1" does not have the ability to list secrets cluster-wide, they cannot create a `ClusterRoleBinding` to a role that grants that permission. To allow a user to create/update role bindings:

1. Grant them a role that allows them to create/update `RoleBinding` or `ClusterRoleBinding` objects, as desired.
2. Grant them permissions needed to bind a particular role:
  - implicitly, by giving them the permissions contained in the role.
  - explicitly, by giving them permission to perform the `bind` verb on the particular role (or cluster role).

For example, this cluster role and role binding would allow "user-1" to grant other users the `admin`, `edit`, and `view` roles in the "user-1-namespace" namespace:

```

apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: role-grantor
rules:
- apiGroups: ["rbac.authorization.k8s.io"]
  resources: ["rolebindings"]
  verbs: ["create"]
- apiGroups: ["rbac.authorization.k8s.io"]
  resources: ["clusterroles"]
  verbs: ["bind"]
  resourceNames: ["admin", "edit", "view"]
---
apiVersion: rbac.authorization.k8s.io/v1
kind: RoleBinding
metadata:
  name: role-grantor-binding
  namespace: user-1-namespace
roleRef:
  apiGroup: rbac.authorization.k8s.io
  kind: ClusterRole
  name: role-grantor
subjects:
- apiGroup: rbac.authorization.k8s.io
  kind: User
  name: user-1

```

When bootstrapping the first roles and role bindings, it is necessary for the initial user to grant permissions they do not yet have. To bootstrap initial roles and role bindings:

- Use a credential with the `system:masters` group, which is bound to the `cluster-admin` super-user role by the default bindings.
- If your API server runs with the insecure port enabled (`--insecure-port`), you can also make API calls via that port, which does not enforce authentication or authorization.

## Command-line Utilities

### kubectl create role

Creates a Role object defining permissions within a single namespace.  
Examples:

- Create a Role named "pod-reader" that allows user to perform "get", "watch" and "list" on pods:

```
kubectl create role pod-reader --verb=get --verb=list --verb=watch --resource=pods
```

- Create a Role named "pod-reader" with resourceNames specified:

```
kubectl create role pod-reader --verb=get --resource=pods --resource-name=readablepod --resource-name=anotherpod
```

- Create a Role named "foo" with apiGroups specified:

```
kubectl create role foo --verb=get,list,watch --resource=replicasets.apps
```

- Create a Role named "foo" with subresource permissions:

```
kubectl create role foo --verb=get,list,watch --resource=pods,pods/status
```

- Create a Role named "my-component-lease-holder" with permissions to get/update a resource with a specific name:

```
kubectl create role my-component-lease-holder --verb=get,list,watch,update --resource=lease --resource-name=my-component
```

## **kubectl create clusterrole**

Creates a ClusterRole object. Examples:

- Create a ClusterRole named "pod-reader" that allows user to perform "get", "watch" and "list" on pods:

```
kubectl create clusterrole pod-reader --verb=get,list,watch --resource=pods
```

- Create a ClusterRole named "pod-reader" with resourceNames specified:

```
kubectl create clusterrole pod-reader --verb=get --resource=pods --resource-name=readablepod --resource-name=anotherpod
```

- Create a ClusterRole named "foo" with apiGroups specified:

```
kubectl create clusterrole foo --verb=get,list,watch --resource=replicasets.apps
```

- Create a ClusterRole named "foo" with subresource permissions:

```
kubectl create clusterrole foo --verb=get,list,watch --resource=pods,pods/status
```

- Create a ClusterRole name "foo" with nonResourceURL specified:

```
kubectl create clusterrole "foo" --verb=get --non-resource-url=/logs/*
```

- Create a ClusterRole name "monitoring" with aggregationRule specified:

```
kubectl create clusterrole monitoring --aggregation-  
rule="rbac.example.com/aggregate-to-monitoring=true"
```

## kubectl create rolebinding

Grants a Role or ClusterRole within a specific namespace. Examples:

- Within the namespace "acme", grant the permissions in the admin ClusterRole to a user named "bob":

```
kubectl create rolebinding bob-admin-binding --  
clusterrole=admin --user=bob --namespace=acme
```

- Within the namespace "acme", grant the permissions in the view ClusterRole to the service account in the namespace "acme" named "myapp":

```
kubectl create rolebinding myapp-view-binding --  
clusterrole=view --serviceaccount=acme:myapp --namespace=acme
```

- Within the namespace "acme", grant the permissions in the view ClusterRole to a service account in the namespace "myappnamespace" named "myapp":

```
kubectl create rolebinding myappnamespace-myapp-view-binding  
--clusterrole=view --serviceaccount=myappnamespace:myapp --  
namespace=acme
```

## kubectl create clusterrolebinding

Grants a ClusterRole across the entire cluster, including all namespaces. Examples:

- Across the entire cluster, grant the permissions in the cluster-admin ClusterRole to a user named "root":

```
kubectl create clusterrolebinding root-cluster-admin-binding  
--clusterrole=cluster-admin --user=root
```

- Across the entire cluster, grant the permissions in the system:node-proxier ClusterRole to a user named "system:kube-proxy":

```
kubectl create clusterrolebinding kube-proxy-binding --  
clusterrole=system:node-proxier --user=system:kube-proxy
```

- Across the entire cluster, grant the permissions in the view ClusterRole to a service account named "myapp" in the namespace "acme":

```
kubectl create clusterrolebinding myapp-view-binding --  
clusterrole=view --serviceaccount=acme:myapp
```



## kubectl auth reconcile

Creates or updates `rbac.authorization.k8s.io/v1` API objects from a manifest file.

Missing objects are created, and the containing namespace is created for namespaced objects, if required.

Existing roles are updated to include the permissions in the input objects, and remove extra permissions if `--remove-extra-permissions` is specified.

Existing bindings are updated to include the subjects in the input objects, and remove extra subjects if `--remove-extra-subjects` is specified.

Examples:

- Test applying a manifest file of RBAC objects, displaying changes that would be made:

```
kubectl auth reconcile -f my-rbac-rules.yaml --dry-run
```

- Apply a manifest file of RBAC objects, preserving any extra permissions (in roles) and any extra subjects (in bindings):

```
kubectl auth reconcile -f my-rbac-rules.yaml
```

- Apply a manifest file of RBAC objects, removing any extra permissions (in roles) and any extra subjects (in bindings):

```
kubectl auth reconcile -f my-rbac-rules.yaml --remove-extra-subjects --remove-extra-permissions
```

See the CLI help for detailed usage.

## Service Account Permissions

Default RBAC policies grant scoped permissions to control-plane components, nodes, and controllers, but grant *no permissions* to service accounts outside the `kube-system` namespace (beyond discovery permissions given to all authenticated users).

This allows you to grant particular roles to particular service accounts as needed. Fine-grained role bindings provide greater security, but require more effort to administrate. Broader grants can give unnecessary (and potentially escalating) API access to service accounts, but are easier to administrate.

In order from most secure to least secure, the approaches are:

1. Grant a role to an application-specific service account (best practice)

This requires the application to specify a `serviceAccountName` in its pod spec, and for the service account to be created (via the API, application manifest, `kubectl create serviceaccount`, etc.).

For example, grant read-only permission within "my-namespace" to the "my-sa" service account:

```
kubectl create rolebinding my-sa-view \
  --clusterrole=view \
  --serviceaccount=my-namespace:my-sa \
  --namespace=my-namespace
```

## 2. Grant a role to the "default" service account in a namespace

If an application does not specify a `serviceAccountName`, it uses the "default" service account.

**Note:** Permissions given to the "default" service account are available to any pod in the namespace that does not specify a `serviceAccountName`.

For example, grant read-only permission within "my-namespace" to the "default" service account:

```
kubectl create rolebinding default-view \
  --clusterrole=view \
  --serviceaccount=my-namespace:default \
  --namespace=my-namespace
```

Many [add-ons](#) currently run as the "default" service account in the kube-system namespace. To allow those add-ons to run with super-user access, grant cluster-admin permissions to the "default" service account in the kube-system namespace.

**Note:** Enabling this means the kube-system namespace contains secrets that grant super-user access to the API.

```
kubectl create clusterrolebinding add-on-cluster-admin \
  --clusterrole=cluster-admin \
  --serviceaccount=kube-system:default
```

## 3. Grant a role to all service accounts in a namespace

If you want all applications in a namespace to have a role, no matter what service account they use, you can grant a role to the service account group for that namespace.

For example, grant read-only permission within "my-namespace" to all service accounts in that namespace:

```
kubectl create rolebinding serviceaccounts-view \
  --clusterrole=view \
  --group=system:serviceaccounts:my-namespace \
  --namespace=my-namespace
```

#### 4. Grant a limited role to all service accounts cluster-wide (discouraged)

If you don't want to manage permissions per-namespace, you can grant a cluster-wide role to all service accounts.

For example, grant read-only permission across all namespaces to all service accounts in the cluster:

```
kubectl create clusterrolebinding serviceaccounts-view \
  --clusterrole=view \
  --group=system:serviceaccounts
```

#### 5. Grant super-user access to all service accounts cluster-wide (strongly discouraged)

If you don't care about partitioning permissions at all, you can grant super-user access to all service accounts.

**Warning:** This allows any user with read access to secrets or the ability to create a pod to access super-user credentials.

```
kubectl create clusterrolebinding serviceaccounts-cluster-admin \
  --clusterrole=cluster-admin \
  --group=system:serviceaccounts
```

## Upgrading from 1.5

Prior to Kubernetes 1.6, many deployments used very permissive ABAC policies, including granting full API access to all service accounts.

Default RBAC policies grant scoped permissions to control-plane components, nodes, and controllers, but grant *no permissions* to service accounts outside the kube-system namespace (beyond discovery permissions given to all authenticated users).

While far more secure, this can be disruptive to existing workloads expecting to automatically receive API permissions. Here are two approaches for managing this transition:

### Parallel Authorizers

Run both the RBAC and ABAC authorizers, and specify a policy file that contains [the legacy ABAC policy](#):

```
--authorization-mode=RBAC,ABAC --authorization-policy-
file=mypolicy.json
```

The RBAC authorizer will attempt to authorize requests first. If it denies an API request, the ABAC authorizer is then run. This means that any request allowed by *either* the RBAC or ABAC policies is allowed.

When the apiserver is run with a log level of 5 or higher for the RBAC component (--vmodule=rbac\*=5 or --v=5), you can see RBAC denials in the apiserver log (prefixed with RBAC DENY:). You can use that information to determine which roles need to be granted to which users, groups, or service accounts. Once you have [granted roles to service accounts](#) and workloads are running with no RBAC denial messages in the server logs, you can remove the ABAC authorizer.

## Permissive RBAC Permissions

You can replicate a permissive policy using RBAC role bindings.

### Warning:

The following policy allows **ALL** service accounts to act as cluster administrators. Any application running in a container receives service account credentials automatically, and could perform any action against the API, including viewing secrets and modifying permissions. This is not a recommended policy.

```
kubectl create clusterrolebinding permissive-binding \
  --clusterrole=cluster-admin \
  --user=admin \
  --user=kubelet \
  --group=system:serviceaccounts
```

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on February 11, 2020 at 8:42 PM PST by [adding in a docs alias \(#19077\)](#) ([Page History](#))

[Edit This Page](#)

# Using ABAC Authorization

Attribute-based access control (ABAC) defines an access control paradigm whereby access rights are granted to users through the use of policies which combine attributes together.

- [Policy File Format](#)
- [Authorization Algorithm](#)
- [Kubectl](#)
- [Examples](#)

- [A quick note on service accounts](#)

## Policy File Format

To enable ABAC mode, specify `--authorization-policy-file=SOME_FILENAME` and `--authorization-mode=ABAC` on startup.

The file format is [one JSON object per line](#). There should be no enclosing list or map, just one map per line.

Each line is a "policy object", where each such object is a map with the following properties:

- Versioning properties:
  - `apiVersion`, type string; valid values are "abac.authorization.kubernetes.io/v1beta1". Allows versioning and conversion of the policy format.
  - `kind`, type string; valid values are "Policy". Allows versioning and conversion of the policy format.
- `spec` property set to a map with the following properties:
  - Subject-matching properties:
    - `user`, type string; the user-string from `--token-auth-file`. If you specify `user`, it must match the username of the authenticated user.
    - `group`, type string; if you specify `group`, it must match one of the groups of the authenticated user. `system:authenticated` matches all authenticated requests. `system:unauthenticated` matches all unauthenticated requests.
  - Resource-matching properties:
    - `apiGroup`, type string; an API group.
    - Ex: `extensions`
    - Wildcard: `*` matches all API groups.
    - `namespace`, type string; a namespace.
    - Ex: `kube-system`
    - Wildcard: `*` matches all resource requests.
    - `resource`, type string; a resource type
    - Ex: `pods`
    - Wildcard: `*` matches all resource requests.
  - Non-resource-matching properties:
    - `nonResourcePath`, type string; non-resource request paths.
    - Ex: `/version` or `/apis`
    - Wildcard:
      - `*` matches all non-resource requests.
      - `/foo/*` matches all subpaths of `/foo/`.
  - `readOnly`, type boolean, when true, means that the Resource-matching policy only applies to get, list, and watch operations, Non-resource-matching policy only applies to get operation.

**Note:**

An unset property is the same as a property set to the zero value for its type (e.g. empty string, 0, false). However, unset should be preferred for readability.

In the future, policies may be expressed in a JSON format, and managed via a REST interface.

## Authorization Algorithm

A request has attributes which correspond to the properties of a policy object.

When a request is received, the attributes are determined. Unknown attributes are set to the zero value of its type (e.g. empty string, 0, false).

A property set to "\*" will match any value of the corresponding attribute.

The tuple of attributes is checked for a match against every policy in the policy file. If at least one line matches the request attributes, then the request is authorized (but may fail later validation).

To permit any authenticated user to do something, write a policy with the group property set to "system:authenticated".

To permit any unauthenticated user to do something, write a policy with the group property set to "system:unauthenticated".

To permit a user to do anything, write a policy with the apiGroup, namespace, resource, and nonResourcePath properties set to "\*".

## Kubectrl

Kubectrl uses the /api and /apis endpoints of api-server to discover served resource types, and validates objects sent to the API by create/update operations using schema information located at /openapi/v2.

When using ABAC authorization, those special resources have to be explicitly exposed via the nonResourcePath property in a policy (see [examples](#) below):

- /api, /api/\*, /apis, and /apis/\* for API version negotiation.
- /version for retrieving the server version via `kubectrl version`.
- /swaggerapi/\* for create/update operations.

To inspect the HTTP calls involved in a specific kubectrl operation you can turn up the verbosity:

```
kubectrl --v=8 version
```

## Examples

1. Alice can do anything to all resources:

```
{"apiVersion": "abac.authorization.kubernetes.io/v1beta1", "kind": "Policy", "spec": {"user": "alice", "namespace": "*", "resource": "*", "apiGroup": "*"}}
```

- ## 2. The Kubelet can read any pods:

```
{"apiVersion": "abac.authorization.kubernetes.io/v1beta1", "kind": "Policy", "spec": {"user": "kubelet", "namespace": "*", "resource": "pods", "readOnly": true}}
```

- ### 3. The Kubelet can read and write events:

```
{"apiVersion": "abac.authorization.kubernetes.io/v1beta1", "kind": "Policy", "spec": {"user": "kubelet", "namespace": "*", "resource": "events"}}}
```

4. Bob can just read pods in namespace "projectCaribou":

```
{"apiVersion": "abac.authorization.kubernetes.io/v1beta1", "kind": "Policy", "spec": {"user": "bob", "namespace": "project Caribou", "resource": "pods", "readOnly": true}}
```

5. Anyone can make read-only requests to all non-resource paths:

```
{
  "apiVersion": "abac.authorization.kubernetes.io/v1beta1",
  "kind": "Policy",
  "spec": {
    "group": "system:authenticated",
    "readOnly": true,
    "nonResourcePath": "*"
  }
},
{
  "apiVersion": "abac.authorization.kubernetes.io/v1beta1",
  "kind": "Policy",
  "spec": {
    "group": "system:unauthenticated",
    "readOnly": true,
    "nonResourcePath": "*"
  }
}
```

## Complete file example

## A quick note on service accounts

Every service account has a corresponding ABAC username, and that service account's user name is generated according to the naming convention:

system:serviceaccount:<namespace>:<serviceaccountname>

Creating a new namespace leads to the creation of a new service account in the following format:

```
system:serviceaccount:<namespace>:default
```



For example, if you wanted to grant the default service account (in the kube-system namespace) full privilege to the API using ABAC, you would add this line to your policy file:

```
{"apiVersion": "abac.authorization.kubernetes.io/v1beta1", "kind": "Policy", "spec": {"user": "system:serviceaccount:kube-system:default", "namespace": "*", "resource": "*", "apiGroup": "*"}}
```

The apiserver will need to be restarted to pickup the new policy lines.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on September 11, 2019 at 1:56 PM PST by [Revert](#)  
"Update abac.md (#13067)" (#16302) ([Page History](#))

[Edit This Page](#)

# Using Node Authorization

Node authorization is a special-purpose authorization mode that specifically authorizes API requests made by kubelets.

- [Overview](#)
- [Migration considerations](#)

# Overview

The Node authorizer allows a kubelet to perform API operations. This includes:

Read operations:

- services
- endpoints
- nodes
- pods
- secrets, configmaps, persistent volume claims and persistent volumes related to pods bound to the kubelet's node

Write operations:

- nodes and node status (enable the `NodeRestriction` admission plugin to limit a kubelet to modify its own node)
- pods and pod status (enable the `NodeRestriction` admission plugin to limit a kubelet to modify pods bound to itself)
- events

Auth-related operations:

- read/write access to the `certificatesigningrequests` API for TLS bootstrapping
- the ability to create `tokenreviews` and `subjectaccessreviews` for delegated authentication/authorization checks

In future releases, the node authorizer may add or remove permissions to ensure kubelets have the minimal set of permissions required to operate correctly.

In order to be authorized by the Node authorizer, kubelets must use a credential that identifies them as being in the `system:nodes` group, with a username of `system:node:<nodeName>`. This group and user name format match the identity created for each kubelet as part of [kubelet TLS bootstrapping](#).

The value of `<nodeName>` **must** match precisely the name of the node as registered by the kubelet. By default, this is the host name as provided by `hostname`, or overridden via the [kubelet option](#) `--hostname-override`. However, when using the `--cloud-provider` kubelet option, the specific hostname may be determined by the cloud provider, ignoring the local hostname and the `--hostname-override` option. For specifics about how the kubelet determines the hostname, as well as cloud provider overrides, see the [kubelet options reference](#) and the [cloud provider details](#).

To enable the Node authorizer, start the apiserver with `--authorization-mode=Node`.

To limit the API objects kubelets are able to write, enable the [NodeRestriction](#) admission plugin by starting the apiserver with `--enable-admission-plugins=...,NodeRestriction,...`

## Migration considerations

### Kubelets outside the `system:nodes` group

Kubelets outside the `system:nodes` group would not be authorized by the Node authorization mode, and would need to continue to be authorized via whatever mechanism currently authorizes them. The node admission plugin would not restrict requests from these kubelets.

### Kubelets with undifferentiated usernames

In some deployments, kubelets have credentials that place them in the `system:nodes` group, but do not identify the particular node they are associated with, because they do not have a username in the `system:node:...` format. These kubelets would not be authorized by the Node authorization mode, and would need to continue to be authorized via whatever mechanism currently authorizes them.

The `NodeRestriction` admission plugin would ignore requests from these kubelets, since the default node identifier implementation would not consider that a node identity.

### Upgrades from previous versions using RBAC

Upgraded pre-1.7 clusters using [RBAC](#) will continue functioning as-is because the `system:nodes` group binding will already exist.

If a cluster admin wishes to start using the Node authorizer and `NodeRestriction` admission plugin to limit node access to the API, that can be done non-disruptively:

1. Enable the Node authorization mode (`--authorization-mode=Node,RBAC`) and the `NodeRestriction` admission plugin
2. Ensure all kubelets' credentials conform to the group/username requirements
3. Audit apiserver logs to ensure the Node authorizer is not rejecting requests from kubelets (no persistent `NODE DENY` messages logged)
4. Delete the `system:node` cluster role binding

### RBAC Node Permissions

In 1.6, the `system:node` cluster role was automatically bound to the `system:nodes` group when using the [RBAC Authorization mode](#).

In 1.7, the automatic binding of the `system:nodes` group to the `system:node` role is deprecated because the node authorizer accomplishes the same purpose with the benefit of additional restrictions on secret and configmap

access. If the `Node` and RBAC authorization modes are both enabled, the automatic binding of the `system:nodes` group to the `system:node` role is not created in 1.7.

In 1.8, the binding will not be created at all.

When using RBAC, the `system:node` cluster role will continue to be created, for compatibility with deployment methods that bind other users or groups to that role.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 7:39 AM PST by [Fix broken NodeRestriction anchor reference \(#18225\)](#) ([Page History](#))

[Edit This Page](#)

## Webhook Mode

A WebHook is an HTTP callback: an HTTP POST that occurs when something happens; a simple event-notification via HTTP POST. A web application implementing WebHooks will POST a message to a URL when certain things happen.

- [Configuration File Format](#)
- [Request Payloads](#)

When specified, mode Webhook causes Kubernetes to query an outside REST service when determining user privileges.

## Configuration File Format

Mode Webhook requires a file for HTTP configuration, specify by the `--authorization-webhook-config-file=SOME_FILENAME` flag.

The configuration file uses the [kubeconfig](#) file format. Within the file "users" refers to the API Server webhook and "clusters" refers to the remote service.

A configuration example which uses HTTPS client auth:

```
# Kubernetes API version
apiVersion: v1
# kind of the API object
kind: Config
# clusters refers to the remote service.
clusters:
  - name: name-of-remote-authz-service
    cluster:
      # CA for verifying the remote service.
      certificate-authority: /path/to/ca.pem
      # URL of remote service to query. Must use 'https'. May
      # not include parameters.
      server: https://authz.example.com/authorize

# users refers to the API Server's webhook configuration.
users:
  - name: name-of-api-server
    user:
      client-certificate: /path/to/cert.pem # cert for the
      # webhook plugin to use
      client-key: /path/to/key.pem # key matching the
      # cert

# kubeconfig files require a context. Provide one for the API
# Server.
current-context: webhook
contexts:
  - context:
      cluster: name-of-remote-authz-service
      user: name-of-api-server
      name: webhook
```

## Request Payloads

When faced with an authorization decision, the API Server POSTs a JSON-serialized `k8s.io/v1beta1 SubjectAccessReview` object describing the action. This object contains fields describing the user

attempting to make the request, and either details about the resource being accessed or requests attributes.

Note that webhook API objects are subject to the same [versioning compatibility rules](#) as other Kubernetes API objects. Implementers should be aware of looser compatibility promises for beta objects and check the "apiVersion" field of the request to ensure correct deserialization. Additionally, the API Server must enable the authorization.k8s.io/v1beta1 API extensions group (`--runtime-config=authorization.k8s.io/v1beta1=true`).

An example request body:

```
{
  "apiVersion": "authorization.k8s.io/v1beta1",
  "kind": "SubjectAccessReview",
  "spec": {
    "resourceAttributes": {
      "namespace": "kittensandponies",
      "verb": "get",
      "group": "unicorn.example.org",
      "resource": "pods"
    },
    "user": "jane",
    "group": [
      "group1",
      "group2"
    ]
  }
}
```

The remote service is expected to fill the status field of the request and respond to either allow or disallow access. The response body's spec field is ignored and may be omitted. A permissive response would return:

```
{
  "apiVersion": "authorization.k8s.io/v1beta1",
  "kind": "SubjectAccessReview",
  "status": {
    "allowed": true
  }
}
```

For disallowing access there are two methods.

The first method is preferred in most cases, and indicates the authorization webhook does not allow, or has "no opinion" about the request, but if other authorizers are configured, they are given a chance to allow the request. If there are no other authorizers, or none of them allow the request, the request is forbidden. The webhook would return:

```
{
  "apiVersion": "authorization.k8s.io/v1beta1",
```



```

"kind": "SubjectAccessReview",
"status": {
  "allowed": false,
  "reason": "user does not have read access to the namespace"
}
}

```

The second method denies immediately, short-circuiting evaluation by other configured authorizers. This should only be used by webhooks that have detailed knowledge of the full authorizer configuration of the cluster. The webhook would return:

```

{
  "apiVersion": "authorization.k8s.io/v1beta1",
  "kind": "SubjectAccessReview",
  "status": {
    "allowed": false,
    "denied": true,
    "reason": "user does not have read access to the namespace"
  }
}

```

Access to non-resource paths are sent as:

```

{
  "apiVersion": "authorization.k8s.io/v1beta1",
  "kind": "SubjectAccessReview",
  "spec": {
    "nonResourceAttributes": {
      "path": "/debug",
      "verb": "get"
    },
    "user": "jane",
    "group": [
      "group1",
      "group2"
    ]
  }
}

```

Non-resource paths include: /api, /apis, /metrics, /resetMetrics, /logs, /debug, /healthz, /swagger-ui/, /swaggerapi/, /ui, and /version. Clients require access to /api, /api/\*, /apis, /apis/\*, and /version to discover what resources and versions are present on the server. Access to other non-resource paths can be disallowed without restricting access to the REST api.

For further documentation refer to the `authorization.v1beta1` API objects and [webhook.go](https://kubernetes.io/docs/reference/access-authn-authz/webhook/).

# Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on August 21, 2019 at 4:41 AM PST by [Clarify "no opinion" vs. immediate, short-circuiting deny response. \(#15849\)](#) ([Page History](#))

[Edit This Page](#)

# v1.17

[Kubernetes API v1.17](#)

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

[Edit This Page](#)

# Well-Known Labels, Annotations and Taints

Kubernetes reserves all labels and annotations in the `kubernetes.io` namespace.

This document serves both as a reference to the values and as a coordination point for assigning values.

- [kubernetes.io/arch](#)
- [kubernetes.io/os](#)
- [beta.kubernetes.io/arch \(deprecated\)](#)
- [beta.kubernetes.io/os \(deprecated\)](#)
- [kubernetes.io/hostname](#)
- [beta.kubernetes.io/instance-type \(deprecated\)](#)
- [node.kubernetes.io/instance-type](#)
- [failure-domain.beta.kubernetes.io/region \(deprecated\)](#)
- [failure-domain.beta.kubernetes.io/zone \(deprecated\)](#)
- [topology.kubernetes.io/region](#)
- [topology.kubernetes.io/zone](#)

## kubernetes.io/arch

Example: `kubernetes.io/arch=amd64`

Used on: Node

The Kubelet populates this with `runtime.GOARCH` as defined by Go. This can be handy if you are mixing arm and x86 nodes.

## kubernetes.io/os

Example: `kubernetes.io/os=linux`

Used on: Node

The Kubelet populates this with `runtime.GOOS` as defined by Go. This can be handy if you are mixing operating systems in your cluster (for example: mixing Linux and Windows nodes).

## beta.kubernetes.io/arch (deprecated)

This label has been deprecated. Please use `kubernetes.io/arch` instead.

## **beta.kubernetes.io/os (deprecated)**

This label has been deprecated. Please use `kubernetes.io/os` instead.

## **kubernetes.io/hostname**

Example: `kubernetes.io/hostname=ip-172-20-114-199.ec2.internal`

Used on: Node

The Kubelet populates this label with the hostname. Note that the hostname can be changed from the "actual" hostname by passing the `--hostname-override` flag to the kubelet.

## **beta.kubernetes.io/instance-type (deprecated)**

**Note:** Starting in v1.17, this label is deprecated in favor of [node.kubernetes.io/instance-type](https://kubernetes.io/docs/concepts/scheduling/kubernetes-node-labels/#node-kubernetes-io-instance-type).

## **node.kubernetes.io/instance-type**

Example: `node.kubernetes.io/instance-type=m3.medium`

Used on: Node

The Kubelet populates this with the instance type as defined by the cloud provider. This will be set only if you are using a cloudprovider. This setting is handy if you want to target certain workloads to certain instance types, but typically you want to rely on the Kubernetes scheduler to perform resource-based scheduling. You should aim to schedule based on properties rather than on instance types (for example: require a GPU, instead of requiring a g2.2xlarge).

## **failure-domain.beta.kubernetes.io/region (deprecated)**

See [failure-domain.beta.kubernetes.io/zone](https://kubernetes.io/docs/concepts/scheduling/kubernetes-node-labels/#failure-domain-beta-kubernetes-io-zone).

**Note:** Starting in v1.17, this label is deprecated in favor of [topology.kubernetes.io/region](https://kubernetes.io/docs/concepts/scheduling/kubernetes-node-labels/#topology-kubernetes-io-region).

## **failure-domain.beta.kubernetes.io/zone (deprecated)**

Example:

`failure-domain.beta.kubernetes.io/region=us-east-1`

`failure-domain.beta.kubernetes.io/zone=us-east-1c`

Used on: Node, PersistentVolume

On the Node: The kubelet populates this with the zone information as defined by the cloudprovider. This will be set only if you are using a cloudprovider. However, you should consider setting this on the nodes if it makes sense in your topology.

On the PersistentVolume: The PersistentVolumeLabel admission controller will automatically add zone labels to PersistentVolumes, on GCE and AWS.

Kubernetes will automatically spread the Pods in a replication controller or service across nodes in a single-zone cluster (to reduce the impact of failures). With multiple-zone clusters, this spreading behaviour is extended across zones (to reduce the impact of zone failures). This is achieved via *SelectorSpreadPriority*.

*SelectorSpreadPriority* is a best effort placement. If the zones in your cluster are heterogeneous (for example: different numbers of nodes, different types of nodes, or different pod resource requirements), this placement might prevent equal spreading of your Pods across zones. If desired, you can use homogenous zones (same number and types of nodes) to reduce the probability of unequal spreading.

The scheduler (through the *VolumeZonePredicate* predicate) also will ensure that Pods, that claim a given volume, are only placed into the same zone as that volume. Volumes cannot be attached across zones.

The actual values of zone and region don't matter. Nor is the node hierarchy rigidly defined. The expectation is that failures of nodes in different zones should be uncorrelated unless the entire region has failed. For example, zones should typically avoid sharing a single network switch. The exact mapping depends on your particular infrastructure - a three rack installation will choose a very different setup to a multi-datacenter configuration.

If PersistentVolumeLabel does not support automatic labeling of your PersistentVolumes, you should consider adding the labels manually (or adding support for PersistentVolumeLabel). With PersistentVolumeLabel, the scheduler prevents Pods from mounting volumes in a different zone. If your infrastructure doesn't have this constraint, you don't need to add the zone labels to the volumes at all.

**Note:** Starting in v1.17, this label is deprecated in favor of [topology.kubernetes.io/zone](https://kubernetes.io/docs/concepts/scheduling/kubernetes-topology-requirements/#topology.kubernetes.io/zone).

## **topology.kubernetes.io/region**

See [topology.kubernetes.io/zone](https://kubernetes.io/docs/concepts/scheduling/kubernetes-topology-requirements/#topology.kubernetes.io/zone).

# topology.kubernetes.io/zone

Example:

```
topology.kubernetes.io/region=us-east-1
```

```
topology.kubernetes.io/zone=us-east-1c
```

Used on: Node, PersistentVolume

On the Node: The kubelet populates this with the zone information as defined by the cloudprovider. This will be set only if you are using a cloudprovider. However, you should consider setting this on the nodes if it makes sense in your topology.

On the PersistentVolume: The PersistentVolumeLabel admission controller will automatically add zone labels to PersistentVolumes, on GCE and AWS.

Kubernetes will automatically spread the Pods in a replication controller or service across nodes in a single-zone cluster (to reduce the impact of failures). With multiple-zone clusters, this spreading behaviour is extended across zones (to reduce the impact of zone failures). This is achieved via *SelectorSpreadPriority*.

*SelectorSpreadPriority* is a best effort placement. If the zones in your cluster are heterogeneous (for example: different numbers of nodes, different types of nodes, or different pod resource requirements), this placement might prevent equal spreading of your Pods across zones. If desired, you can use homogenous zones (same number and types of nodes) to reduce the probability of unequal spreading.

The scheduler (through the *VolumeZonePredicate* predicate) also will ensure that Pods, that claim a given volume, are only placed into the same zone as that volume. Volumes cannot be attached across zones.

The actual values of zone and region don't matter. Nor is the node hierarchy rigidly defined. The expectation is that failures of nodes in different zones should be uncorrelated unless the entire region has failed. For example, zones should typically avoid sharing a single network switch. The exact mapping depends on your particular infrastructure - a three rack installation will choose a very different setup to a multi-datacenter configuration.

If PersistentVolumeLabel does not support automatic labeling of your PersistentVolumes, you should consider adding the labels manually (or adding support for PersistentVolumeLabel). With PersistentVolumeLabel, the scheduler prevents Pods from mounting volumes in a different zone. If your infrastructure doesn't have this constraint, you don't need to add the zone labels to the volumes at all.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on December 10, 2019 at 5:41 AM PST by [Official 1.17 Release Docs \(#18011\)](#) ([Page History](#))

[Edit This Page](#)

# Overview of kubeadm

- - [How to install](#)



- [What's next](#)



# kubeadm

Kubeadm is a tool built to provide `kubeadm init` and `kubeadm join` as best-practice "fast paths" for creating Kubernetes clusters.

kubeadm performs the actions necessary to get a minimum viable cluster up and running. By design, it cares only about bootstrapping, not about provisioning machines. Likewise, installing various nice-to-have addons, like the Kubernetes Dashboard, monitoring solutions, and cloud-specific addons, is not in scope.

Instead, we expect higher-level and more tailored tooling to be built on top of kubeadm, and ideally, using kubeadm as the basis of all deployments will make it easier to create conformant clusters.

## How to install

To install kubeadm, see the [installation guide](#).

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to bootstrap a Kubernetes worker node and join it to the cluster
- [kubeadm upgrade](#) to upgrade a Kubernetes cluster to a newer version
- [kubeadm config](#) if you initialized your cluster using kubeadm v1.7.x or lower, to configure your cluster for kubeadm upgrade
- [kubeadm token](#) to manage tokens for kubeadm join
- [kubeadm reset](#) to revert any changes made to this host by kubeadm init or kubeadm join
- [kubeadm version](#) to print the kubeadm version
- [kubeadm alpha](#) to preview a set of features made available for gathering feedback from the community

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 09, 2019 at 1:09 PM PST by [remove myself from some reviewers lists \(#16753\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm init

This command initializes a Kubernetes control-plane node.

- [What's next](#)

## Synopsis

Run this command in order to set up the Kubernetes control plane

The "init" command executes the following phases:

preflight	Run pre-flight checks
kubelet-start	Write kubelet settings and
(re)start the kubelet	
certs	Certificate generation
/ca	Generate the self-signed
Kubernetes CA to provision identities for other Kubernetes components	
/apiserver	Generate the certificate for
serving the Kubernetes API	
/apiserver-kubelet-client	Generate the certificate for the
API server to connect to kubelet	
/front-proxy-ca	Generate the self-signed CA to
provision identities for front proxy	
/front-proxy-client	Generate the certificate for the
front proxy client	
/etcd-ca	Generate the self-signed CA to
provision identities for etcd	
/etcd-server	Generate the certificate for
serving etcd	
/etcd-peer	Generate the certificate for etcd
nodes to communicate with each other	
/etcd-healthcheck-client	Generate the certificate for
liveness probes to healthcheck etcd	
/apiserver-etcd-client	Generate the certificate the
apiserver uses to access etcd	
/sa	Generate a private key for
signing service account tokens along with its public key	
kubeconfig	Generate all kubeconfig files
necessary to establish the control plane and the admin kubeconfig file	
/admin	Generate a kubeconfig file for
the admin to use and for kubeadm itself	
/kubelet	Generate a kubeconfig file for
the kubelet to use *only* for cluster bootstrapping purposes	
/controller-manager	Generate a kubeconfig file for
the controller manager to use	
/scheduler	Generate a kubeconfig file for
the scheduler to use	
control-plane	Generate all static Pod manifest
files necessary to establish the control plane	
/apiserver	Generates the kube-apiserver
static Pod manifest	
/controller-manager	Generates the kube-controller-
manager static Pod manifest	
/scheduler	Generates the kube-scheduler
static Pod manifest	
etcd	Generate static Pod manifest file
for local etcd	
/local	Generate the static Pod manifest
file for a local, single-node local etcd instance	

upload-config	Upload the kubeadm and kubelet configuration to a ConfigMap
/kubeadm	Upload the kubeadm ClusterConfiguration to a ConfigMap
/kubelet	Upload the kubelet component config to a ConfigMap
upload-certs	Upload certificates to kubeadm-certs
mark-control-plane	Mark a node as a control-plane
bootstrap-token	Generates bootstrap tokens used to join a node to a cluster
kubelet-finalize	Updates settings relevant to the kubelet after TLS bootstrap
/experimental-cert-rotation	Enable kubelet client certificate rotation
addon	Install required addons for passing Conformance tests
/coredns	Install the CoreDNS addon to a Kubernetes cluster
/kube-proxy	Install the kube-proxy addon to a Kubernetes cluster
kubeadm init [flags]	

## Options

--apiserver-advertise-address string
The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32Â Â Â Â Â Default: 6443
Port for the API Server to bind to.
--apiserver-cert-extra-sans stringSlice
Optional extra Subject Alternative Names (SANs) to use for the API Server serving certificate. Can be both IP addresses and DNS names.
--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.
--certificate-key string
Key used to encrypt the control-plane certificates in the kubeadm-certs Secret.
--config string
Path to a kubeadm configuration file.
--control-plane-endpoint string
Specify a stable IP address or DNS name for the control plane.
--cri-socket string
Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
--dry-run

	Don't apply any changes; just output what would be done.
-k, --experimental-kustomize string	
	The path where kustomize patches for static pod manifests are stored.
--feature-gates string	
	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
-h, --help	
	help for init
--ignore-preflight-errors stringSlice	
	A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.
--image-repository string	Default: "k8s.gcr.io"
	Choose a container registry to pull control plane images from
--kubernetes-version string	Default: "stable-1"
	Choose a specific Kubernetes version for the control plane.
--node-name string	
	Specify the node name.
--pod-network-cidr string	
	Specify range of IP addresses for the pod network. If set, the control plane will automatically allocate CIDRs for every node.
--service-cidr string	Default: "10.96.0.0/12"
	Use alternative range of IP address for service VIPs.
--service-dns-domain string	Default: "cluster.local"
	Use alternative domain for services, e.g. "myorg.internal".
--skip-certificate-key-print	
	Don't print the key used to encrypt the control-plane certificates.
--skip-phases stringSlice	
	List of phases to be skipped
--skip-token-print	
	Skip printing of the default bootstrap token generated by 'kubeadm init'.
--token string	
	The token to use for establishing bidirectional trust between nodes and control-plane nodes. The format is [a-z0-9]{6}\.[a-z0-9]{16} - e.g. abcdef.0123456789abcdef
--token-ttl duration	Default: 24h0m0s
	The duration before the token is automatically deleted (e.g. 1s, 2m, 3h). If set to '0', the token will never expire
--upload-certs	
	Upload control-plane certificates to the kubeadm-certs Secret.

## Options inherited from parent commands

<code>--rootfs string</code>
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Init workflow

`kubeadm init` bootstraps a Kubernetes control-plane node by executing the following steps:

1. Runs a series of pre-flight checks to validate the system state before making changes. Some checks only trigger warnings, others are considered errors and will exit `kubeadm` until the problem is corrected or the user specifies `--ignore-preflight-errors=<list-of-errors>`.
2. Generates a self-signed CA (or using an existing one if provided) to set up identities for each component in the cluster. If the user has provided their own CA cert and/or key by dropping it in the cert directory configured via `--cert-dir` (`/etc/kubernetes/pki` by default). The APIServer certs will have additional SAN entries for any `--apiserver-cert-extra-sans` arguments, lowercased if necessary.
3. Writes kubeconfig files in `/etc/kubernetes/` for the kubelet, the controller-manager and the scheduler to use to connect to the API server, each with its own identity, as well as an additional kubeconfig file for administration named `admin.conf`.
4. Generates static Pod manifests for the API server, controller-manager and scheduler. In case an external etcd is not provided, an additional static Pod manifest is generated for etcd.

Static Pod manifests are written to `/etc/kubernetes/manifests`; the kubelet watches this directory for Pods to create on startup.

Once control plane Pods are up and running, the `kubeadm init` sequence can continue.

1. Apply labels and taints to the control-plane node so that no additional workloads will run there.
2. Generates the token that additional nodes can use to register themselves with a control-plane in the future. Optionally, the user can provide a token via `--token`, as described in the [kubeadm token](#) docs.
3. Makes all the necessary configurations for allowing node joining with the [Bootstrap Tokens](#) and [TLS Bootstrap](#) mechanism:
  - Write a ConfigMap for making available all the information required for joining, and set up related RBAC access rules.
  - Let Bootstrap Tokens access the CSR signing API.
  - Configure auto-approval for new CSR requests.

See [kubeadm join](#) for additional info.

1. Installs a DNS server (CoreDNS) and the kube-proxy add-on components via the API server. In Kubernetes version 1.11 and later CoreDNS is the default DNS server. To install kube-dns instead of CoreDNS, the DNS add-on has to be configured in the kubeadm Cluster Configuration. For more information about the configuration see the section Using kubeadm init with a configuration file below. Please note that although the DNS server is deployed, it will not be scheduled until CNI is installed.

## Using init phases with kubeadm

Kubeadm allows you to create a control-plane node in phases using the `kubeadm init phase` command.

To view the ordered list of phases and sub-phases you can call `kubeadm init --help`. The list will be located at the top of the help screen and each phase will have a description next to it. Note that by calling `kubeadm init` all of the phases and sub-phases will be executed in this exact order.

Some phases have unique flags, so if you want to have a look at the list of available options add `--help`, for example:

```
sudo kubeadm init phase control-plane controller-manager --help
```

You can also use `--help` to see the list of sub-phases for a certain parent phase:

```
sudo kubeadm init phase control-plane --help
```

`kubeadm init` also exposes a flag called `--skip-phases` that can be used to skip certain phases. The flag accepts a list of phase names and the names can be taken from the above ordered list.

An example:

```
sudo kubeadm init phase control-plane all --config=configfile.yaml
l
sudo kubeadm init phase etcd local --config=configfile.yaml
# you can now modify the control plane and etcd manifest files
sudo kubeadm init --skip-phases=control-plane,etcd --config=confi
gfile.yaml
```

What this example would do is write the manifest files for the control plane and etcd in `/etc/kubernetes/manifests` based on the configuration in `configfile.yaml`. This allows you to modify the files and then skip these phases using `--skip-phases`. By calling the last command you will create a control plane node with the custom manifest files.



## Using kubeadm init with a configuration file

**Caution:** The config file is still considered beta and may change in future versions.

It's possible to configure `kubeadm init` with a configuration file instead of command line flags, and some more advanced features may only be available as configuration file options. This file is passed with the `--config` option.

The default configuration can be printed out using the [kubeadm config print](#) command.

It is **recommended** that you migrate your old `v1beta1` configuration to `v1beta2` using the [kubeadm config migrate](#) command.

For more details on each field in the `v1beta2` configuration you can navigate to our [API reference pages](#).

## Adding kube-proxy parameters

For information about kube-proxy parameters in the kubeadm configuration see: - [kube-proxy](#)

For information about enabling IPVS mode with kubeadm see: - [IPVS](#)

## Passing custom flags to control plane components

For information about passing flags to control plane components see: - [control-plane-flags](#)

## Using custom images

By default, kubeadm pulls images from `k8s.gcr.io`. If the requested Kubernetes version is a CI label (such as `ci/latest`) `gcr.io/kubernetes-ci-images` is used.

You can override this behavior by using [kubeadm with a configuration file](#). Allowed customization are:

- To provide an alternative `imageRepository` to be used instead of `k8s.gcr.io`.
- To set `useHyperKubeImage` to `true` to use the HyperKube image.
- To provide a specific `imageRepository` and `imageTag` for `etcd` or `DNS add-on`.

Please note that the configuration field `kubernetesVersion` or the command line flag `--kubernetes-version` affect the version of the images.

## Uploading control-plane certificates to the cluster

By adding the flag `--upload-certs` to `kubeadm init` you can temporarily upload the control-plane certificates to a Secret in the cluster. Please note that this Secret will expire automatically after 2 hours. The certificates are encrypted using a 32byte key that can be specified using `--certificate-key`. The same key can be used to download the certificates when additional control-plane nodes are joining, by passing `--control-plane` and `--certificate-key` to `kubeadm join`.

The following phase command can be used to re-upload the certificates after expiration:

```
kubeadm init phase upload-certs --upload-certs --certificate-key=SOME_VALUE --config=SOME_YAML_FILE
```

If the flag `--certificate-key` is not passed to `kubeadm init` and `kubeadm init phase upload-certs` a new key will be generated automatically.

The following command can be used to generate a new key on demand:

```
kubeadm alpha certs certificate-key
```

## Certificate management with kubeadm

For detailed information on certificate management with kubeadm see [Certificate Management with kubeadm](#). The document includes information about using external CA, custom certificates and certificate renewal.

## Managing the kubeadm drop-in file for the kubelet

The kubeadm package ships with a configuration file for running the kubelet by systemd. Note that the kubeadm CLI never touches this drop-in file. This drop-in file is part of the kubeadm DEB/RPM package.

For further information, see [Managing the kubeadm drop-in file for systemd](#).

## Use kubeadm with CRI runtimes

By default kubeadm attempts to detect your container runtime. For more details on this detection, see the [kubeadm CRI installation guide](#).

## Setting the node name

By default, kubeadm assigns a node name based on a machine's host address. You can override this setting with the `--node-name` flag. The flag passes the appropriate `--hostname-override` value to the kubelet.

Be aware that overriding the hostname can [interfere with cloud providers](#).

## Running kubeadm without an internet connection

For running kubeadm without an internet connection you have to pre-pull the required control-plane images.

You can list and pull the images using the `kubeadm config images` sub-command:

```
kubeadm config images list
kubeadm config images pull
```

All images that kubeadm requires such as `k8s.gcr.io/kube-*`, `k8s.gcr.io/etcd` and `k8s.gcr.io/pause` support multiple architectures.

## Automating kubeadm

Rather than copying the token you obtained from `kubeadm init` to each node, as in the [basic kubeadm tutorial](#), you can parallelize the token distribution for easier automation. To implement this automation, you must know the IP address that the control-plane node will have after it is started, or use a DNS name or an address of a load balancer.

1. Generate a token. This token must have the form `<6 character string>.<16 character string>`. More formally, it must match the regex: `[a-z0-9]{6}\.[a-z0-9]{16}`.

kubeadm can generate a token for you:

```
kubeadm token generate
```

2. Start both the control-plane node and the worker nodes concurrently with this token. As they come up they should find each other and form the cluster. The same `--token` argument can be used on both `kubeadm init` and `kubeadm join`.
3. Similar can be done for `--certificate-key` when joining additional control-plane nodes. The key can be generated using:

```
kubeadm alpha certs certificate-key
```

Once the cluster is up, you can grab the admin credentials from the control-plane node at `/etc/kubernetes/admin.conf` and use that to talk to the cluster.

Note that this style of bootstrap has some relaxed security guarantees because it does not allow the root CA hash to be validated with `--discovery-token-ca-cert-hash` (since it's not generated when the nodes are provisioned). For details, see the [kubeadm join](#).

## What's next

- [kubeadm init phase](#) to understand more about `kubeadm init` phases
- [kubeadm join](#) to bootstrap a Kubernetes worker node and join it to the cluster
- [kubeadm upgrade](#) to upgrade a Kubernetes cluster to a newer version
- [kubeadm reset](#) to revert any changes made to this host by `kubeadm init` or `kubeadm join`

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 7:45 PM PST by [kubeadm: improvements to the cert management documentation \(#18397\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm join

This command initializes a Kubernetes worker node and joins it to the cluster.

- [What's next](#)

## Synopsis

When joining a kubeadm initialized cluster, we need to establish bidirectional trust. This is split into discovery (having the Node trust the Kubernetes Control Plane) and TLS bootstrap (having the Kubernetes Control Plane trust the Node).

There are 2 main schemes for discovery. The first is to use a shared token along with the IP address of the API server. The second is to provide a file - a subset of the standard kubeconfig file. This file can be a local file or downloaded via an HTTPS URL. The forms are `kubeadm join -discovery-token abcdef.1234567890abcdef 1.2.3.4:6443`, `kubeadm join -discovery-file path/to/file.conf`, or `kubeadm join -discovery-file https://url/file.conf`. Only one form can be used. If the discovery information is loaded from a URL, HTTPS must be used. Also, in that case the host installed CA bundle is used to verify the connection.

If you use a shared token for discovery, you should also pass the `-discovery-token-ca-cert-hash` flag to validate the public key of the root certificate authority (CA) presented by the Kubernetes Control Plane. The value of this flag is specified as "`<hash-type>:<hex-encoded-value>`", where the supported hash type is "sha256". The hash is calculated over the bytes of the Subject Public Key Info (SPKI) object (as in RFC7469). This value is available in the output of "kubeadm init" or can be calculated using standard tools. The `-discovery-token-ca-cert-hash` flag may be repeated multiple times to allow more than one public key.

If you cannot know the CA public key hash ahead of time, you can pass the `-discovery-token-unsafe-skip-ca-verification` flag to disable this verification. This weakens the kubeadm security model since other nodes can potentially impersonate the Kubernetes Control Plane.

The TLS bootstrap mechanism is also driven via a shared token. This is used to temporarily authenticate with the Kubernetes Control Plane to submit a certificate signing request (CSR) for a locally created key pair. By default, kubeadm will set up the Kubernetes Control Plane to automatically approve these signing requests. This token is passed in with the `-tls-bootstrap-token abcdef.1234567890abcdef` flag.

Often times the same token is used for both parts. In this case, the `-token` flag can be used instead of specifying each token individually.

The "join [api-server-endpoint]" command executes the following phases:

preflight	Run join pre-flight checks
control-plane-prepare	Prepare the machine for serving a control plane
/download-certs	[EXPERIMENTAL] Download certificates shared among control-plane nodes from the kubeadm-certs Secret
/certs	Generate the certificates for the new control plane components
/kubeconfig	Generate the kubeconfig for the new

```

control plane components
  /control-plane      Generate the manifests for the new
control plane components
kubelet-start         Write kubelet settings, certificates and
(re)start the kubelet
control-plane-join    Join a machine as a control plane instance
  /etcd              Add a new local etcd member
  /update-status      Register the new control-plane node
into the ClusterStatus maintained in the kubeadm-config ConfigMap
  /mark-control-plane Mark a node as a control-plane

```

```
kubeadm join [api-server-endpoint] [flags]
```

## Options

<code>--apiserver-advertise-address</code> string
If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-bind-port</code> int32Â Â Â Â Â Default: 6443
If the node should host a new control plane instance, the port for the API Server to bind to.
<code>--certificate-key</code> string
Use this key to decrypt the certificate secrets uploaded by init.
<code>--config</code> string
Path to kubeadm config file.
<code>--control-plane</code>
Create a new control plane instance on this node
<code>--cri-socket</code> string
Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
<code>--discovery-file</code> string
For file-based discovery, a file or URL from which to load cluster information.
<code>--discovery-token</code> string
For token-based discovery, the token used to validate cluster information fetched from the API server.
<code>--discovery-token-ca-cert-hash</code> stringSlice
For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
<code>--discovery-token-unsafe-skip-ca-verification</code>
For token-based discovery, allow joining without --discovery-token-ca-cert-hash pinning.
<code>-k, --experimental-kustomize</code> string
The path where kustomize patches for static pod manifests are stored.

-h, --help
help for join
--ignore-preflight-errors stringSlice
A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.
--node-name string
Specify the node name.
--skip-phases stringSlice
List of phases to be skipped
--tls-bootstrap-token string
Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
--token string
Use this token for both discovery-token and tls-bootstrap-token when those values are not provided.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## The join workflow

kubeadm join bootstraps a Kubernetes worker node or a control-plane node and adds it to the cluster. This action consists of the following steps for worker nodes:

1. kubeadm downloads necessary cluster information from the API server. By default, it uses the bootstrap token and the CA key hash to verify the authenticity of that data. The root CA can also be discovered directly via a file or URL.
2. Once the cluster information is known, kubelet can start the TLS bootstrapping process.

The TLS bootstrap uses the shared token to temporarily authenticate with the Kubernetes API server to submit a certificate signing request (CSR); by default the control plane signs this CSR request automatically.

1. Finally, kubeadm configures the local kubelet to connect to the API server with the definitive identity assigned to the node.

For control-plane nodes additional steps are performed:

1. Downloading certificates shared among control-plane nodes from the cluster (if explicitly requested by the user).
2. Generating control-plane component manifests, certificates and kubeconfig.



3. Adding new local etcd member.
4. Adding this node to the ClusterStatus of the kubeadm cluster.

## Using join phases with kubeadm

Kubeadm allows you join a node to the cluster in phases using `kubeadm join phase`.

To view the ordered list of phases and sub-phases you can call `kubeadm join --help`. The list will be located at the top of the help screen and each phase will have a description next to it. Note that by calling `kubeadm join` all of the phases and sub-phases will be executed in this exact order.

Some phases have unique flags, so if you want to have a look at the list of available options add `--help`, for example:

```
kubeadm join phase kubelet-start --help
```

Similar to the [kubeadm init phase](#) command, `kubadm join phase` allows you to skip a list of phases using the `--skip-phases` flag.

For example:

```
sudo kubeadm join --skip-phases=preflight --config=config.yaml
```

## Discovering what cluster CA to trust

The kubeadm discovery has several options, each with security tradeoffs. The right method for your environment depends on how you provision nodes and the security expectations you have about your network and node lifecycles.

### Token-based discovery with CA pinning

This is the default mode in kubeadm. In this mode, kubeadm downloads the cluster configuration (including root CA) and validates it using the token as well as validating that the root CA public key matches the provided hash and that the API server certificate is valid under the root CA.

The CA key hash has the format `sha256:<hex_encoded_hash>`. By default, the hash value is returned in the `kubeadm join` command printed at the end of `kubeadm init` or in the output of `kubeadm token create --print-join-command`. It is in a standard format (see [RFC7469](#)) and can also be calculated by 3rd party tools or provisioning systems. For example, using the OpenSSL CLI:

```
openssl x509 -pubkey -in /etc/kubernetes/pki/ca.crt | openssl  
rsa -pubin -outform der 2>/dev/null | openssl dgst -sha256 -hex  
| sed 's/^.* //'
```

### Example kubeadm join commands:

For worker nodes:

```
kubeadm join --discovery-token abcdef.1234567890abcdef --  
discovery-token-ca-cert-hash sha256:1234..cdef 1.2.3.4:6443
```

For control-plane nodes:

```
kubeadm join --discovery-token abcdef.1234567890abcdef --  
discovery-token-ca-cert-hash sha256:1234..cdef --control-plane 1.  
2.3.4:6443
```

You can also call `join` for a control-plane node with `--certificate-key` to copy certificates to this node, if the `kubeadm init` command was called with `--upload-certs`.

### **Advantages:**

- Allows bootstrapping nodes to securely discover a root of trust for the control-plane node even if other worker nodes or the network are compromised.
- Convenient to execute manually since all of the information required fits into a single `kubeadm join` command that is easy to copy and paste.

### **Disadvantages:**

- The CA hash is not normally known until the control-plane node has been provisioned, which can make it more difficult to build automated provisioning tools that use `kubeadm`. By generating your CA in beforehand, you may workaround this limitation.

### **Token-based discovery without CA pinning**

This mode relies only on the symmetric token to sign (HMAC-SHA256) the discovery information that establishes the root of trust for the control-plane. To use the mode the joining nodes must skip the hash validation of the CA public key, using `--discovery-token-unsafe-skip-ca-verification`. You should consider using one of the other modes if possible.

### **Example kubeadm join command:**

```
kubeadm join --token abcdef.1234567890abcdef --discovery-token-  
unsafe-skip-ca-verification 1.2.3.4:6443
```

### **Advantages:**

- Still protects against many network-level attacks.
- The token can be generated ahead of time and shared with the control-plane node and worker nodes, which can then bootstrap in parallel without coordination. This allows it to be used in many provisioning scenarios.

## Disadvantages:

- If an attacker is able to steal a bootstrap token via some vulnerability, they can use that token (along with network-level access) to impersonate the control-plane node to other bootstrapping nodes. This may or may not be an appropriate tradeoff in your environment.

## File or HTTPS-based discovery

This provides an out-of-band way to establish a root of trust between the control-plane node and bootstrapping nodes. Consider using this mode if you are building automated provisioning using kubeadm. The format of the discovery file is a regular Kubernetes [kubeconfig](#) file.

In case the discovery file does not contain credentials, the TLS discovery token will be used.

### Example kubeadm join commands:

- `kubeadm join --discovery-file path/to/file.conf` (local file)
- `kubeadm join --discovery-file https://url/file.conf` (remote HTTPS URL)

## Advantages:

- Allows bootstrapping nodes to securely discover a root of trust for the control-plane node even if the network or other worker nodes are compromised.

## Disadvantages:

- Requires that you have some way to carry the discovery information from the control-plane node to the bootstrapping nodes. If the discovery file contains credentials you must keep it secret and transfer it over a secure channel. This might be possible with your cloud provider or provisioning tool.

## Securing your installation even more

The defaults for kubeadm may not work for everyone. This section documents how to tighten up a kubeadm installation at the cost of some usability.

### Turning off auto-approval of node client certificates

By default, there is a CSR auto-approver enabled that basically approves any client certificate request for a kubelet when a Bootstrap Token was used when authenticating. If you don't want the cluster to automatically approve kubelet client certs, you can turn it off by executing this command:

```
kubectl delete clusterrolebinding kubeadm:node-autoapprove-bootstrap
```

After that, `kubeadm join` will block until the admin has manually approved the CSR in flight:

```
kubectl get csr
```

The output is similar to this:

NAME	AGE
node-csr-c69HXe7aYcqkS1bKmH4faEnHAWxn6i2bHZ2mD04jZyQ	18s
system:bootstrap:878f07	Pending

```
kubectl certificate approve node-csr-c69HXe7aYcqkS1bKmH4faEnHAWxn6i2bHZ2mD04jZyQ
```

The output is similar to this:

```
certificatesigningrequest "node-csr-c69HXe7aYcqkS1bKmH4faEnHAWxn6i2bHZ2mD04jZyQ" approved
```

```
kubectl get csr
```

The output is similar to this:

NAME	AGE
node-csr-c69HXe7aYcqkS1bKmH4faEnHAWxn6i2bHZ2mD04jZyQ	1m
system:bootstrap:878f07	Approved, Issued

This forces the workflow that `kubeadm join` will only succeed if `kubectl certificate approve` has been run.

## Turning off public access to the cluster-info ConfigMap

In order to achieve the joining flow using the token as the only piece of validation information, a ConfigMap with some data needed for validation of the control-plane node's identity is exposed publicly by default. While there is no private data in this ConfigMap, some users might wish to turn it off regardless. Doing so will disable the ability to use the `--discovery-token` flag of the `kubeadm join` flow. Here are the steps to do so:

- Fetch the `cluster-info` file from the API Server:

```
kubectl -n kube-public get cm cluster-info -o yaml | grep "kubeconfig:" -A1 | grep "apiVersion" -A1 | sed "s/ / /" | tee cluster-info.yaml
```

The output is similar to this:

```
apiVersion: v1
kind: Config
```

```
clusters:
- cluster:
  certificate-authority-data: <ca-cert>
  server: https://<ip>:<port>
  name: ""
contexts: []
current-context: ""
preferences: {}
users: []
```

- Use the `cluster-info.yaml` file as an argument to `kubeadm join --discovery-file`.
- Turn off public access to the `cluster-info` ConfigMap:

```
kubectl -n kube-public delete rolebinding kubeadm:bootstrap-signer-clusterinfo
```

These commands should be run after `kubeadm init` but before `kubeadm join`.

## Using kubeadm join with a configuration file

**Caution:** The config file is still considered beta and may change in future versions.

It's possible to configure `kubeadm join` with a configuration file instead of command line flags, and some more advanced features may only be available as configuration file options. This file is passed using the `--config` flag and it must contain a `JoinConfiguration` structure.

To print the default values of `JoinConfiguration` run the following command:

```
kubeadm config print join-defaults
```

For details on individual fields in `JoinConfiguration` see [the godoc](#).

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm token](#) to manage tokens for `kubeadm join`
- [kubeadm reset](#) to revert any changes made to this host by `kubeadm init` or `kubeadm join`

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 10, 2020 at 8:44 PM PST by [kubeadm-join.md: correct alpha->beta wording \(#18366\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm upgrade

`kubeadm upgrade` is a user-friendly command that wraps complex upgrading logic behind one command, with support for both planning an upgrade and actually performing it.

- [kubeadm upgrade guidance](#)
- [kubeadm upgrade plan](#)
- [kubeadm upgrade apply](#)
- [kubeadm upgrade diff](#)
- [kubeadm upgrade node](#)
- [What's next](#)

## kubeadm upgrade guidance

The steps for performing a upgrade using `kubeadm` are outlined in [this document](#). For older versions of `kubeadm`, please refer to older documentation sets of the Kubernetes website.

You can use `kubeadm upgrade diff` to see the changes that would be applied to static pod manifests.

To use kube-dns with upgrades in Kubernetes v1.13.0 and later please follow [this guide](#).

In Kubernetes v1.15.0 and later, `kubeadm upgrade apply` and `kubeadm upgrade node` will also automatically renew the `kubeadm` managed certificates on this node, including those stored in `kubeconfig` files. To opt-out, it is possible to pass the flag `--certificate-renewal=false`. For more details about certificate renewal see the [certificate management documentation](#).

**Note:** The commands `kubeadm upgrade apply` and `kubeadm upgrade plan` have a legacy `--config` flag which makes it possible to reconfigure the cluster, while performing planning or upgrade of that particular control-plane node. Please be aware that the upgrade workflow was not designed for this scenario and there are reports of unexpected results.

## kubeadm upgrade plan

### Synopsis

Check which versions are available to upgrade to and validate whether your current cluster is upgradeable. To skip the internet check, pass in the optional `[version]` parameter

```
kubeadm upgrade plan [version] [flags]
```

## Options

<code>--allow-experimental-upgrades</code>	Show unstable versions of Kubernetes as an upgrade alternative and allow upgrading to an alpha/beta/release candidate versions of Kubernetes.
<code>--allow-release-candidate-upgrades</code>	Show release candidate versions of Kubernetes as an upgrade alternative and allow upgrading to a release candidate versions of Kubernetes.
<code>--config string</code>	Path to a kubeadm configuration file.
<code>--feature-gates string</code>	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
<code>-h, --help</code>	help for plan
<code>--ignore-preflight-errors stringSlice</code>	A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
<code>--print-config</code>	Specifies whether the configuration file that will be used in the upgrade should be printed or not.

## Options inherited from parent commands

<code>--rootfs string</code>	[EXPERIMENTAL] The path to the 'real' host root filesystem.
------------------------------	---

# kubeadm upgrade apply

## Synopsis

Upgrade your Kubernetes cluster to the specified version

```
kubeadm upgrade apply [version]
```

## Options

<code>--allow-experimental-upgrades</code>	Show unstable versions of Kubernetes as an upgrade alternative and allow upgrading to an alpha/beta/release candidate versions of Kubernetes.
<code>--allow-release-candidate-upgrades</code>	



	Show release candidate versions of Kubernetes as an upgrade alternative and allow upgrading to a release candidate versions of Kubernetes.
<code>--certificate-renewal</code> <code>^ ^ ^ ^ ^</code> Default: true	
	Perform the renewal of certificates used by component changed during upgrades.
<code>--config string</code>	
	Path to a kubeadm configuration file.
<code>--dry-run</code>	
	Do not change any state, just output what actions would be performed.
<code>--etcd-upgrade</code> <code>^ ^ ^ ^ ^</code> Default: true	
	Perform the upgrade of etcd.
<code>-k, --experimental-kustomize string</code>	
	The path where kustomize patches for static pod manifests are stored.
<code>--feature-gates string</code>	
	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
<code>-f, --force</code>	
	Force upgrading although some requirements might not be met. This also implies non-interactive mode.
<code>-h, --help</code>	
	help for apply
<code>--ignore-preflight-errors stringSlice</code>	
	A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.
<code>--image-pull-timeout duration</code> <code>^ ^ ^ ^ ^</code> Default: 15m0s	
	The maximum amount of time to wait for the control plane pods to be downloaded.
<code>--kubeconfig string</code> <code>^ ^ ^ ^ ^</code> Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<code>--print-config</code>	
	Specifies whether the configuration file that will be used in the upgrade should be printed or not.
<code>-y, --yes</code>	
	Perform the upgrade and do not prompt for confirmation (non-interactive mode).

## Options inherited from parent commands

<code>--rootfs string</code>	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm upgrade diff

## Synopsis

Show what differences would be applied to existing static pod manifests. See also: `kubeadm upgrade apply -dry-run`

```
kubeadm upgrade diff [version] [flags]
```

## Options

<code>--api-server-manifest string</code>	Default: "/etc/kubernetes/manifests/kube-apiserver.yaml"
path to API server manifest	
<code>--config string</code>	
Path to a kubeadm configuration file.	
<code>-c, --context-lines int</code>	Default: 3
How many lines of context in the diff	
<code>--controller-manager-manifest string</code>	Default: "/etc/kubernetes/manifests/kube-controller-manager.yaml"
path to controller manifest	
<code>-h, --help</code>	
help for diff	
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
<code>--scheduler-manifest string</code>	Default: "/etc/kubernetes/manifests/kube-scheduler.yaml"
path to scheduler manifest	

## Options inherited from parent commands

<code>--rootfs string</code>
[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm upgrade node

## Synopsis

Upgrade commands for a node in the cluster

The "node" command executes the following phases:

```
control-plane  Upgrade the control plane instance deployed on
this node, if any
kubelet-config Upgrade the kubelet configuration for this node
```

```
kubeadm upgrade node [flags]
```

## Options

--certificate-renewal	Default: true
Perform the renewal of certificates used by component changed during upgrades.	
--dry-run	
Do not change any state, just output the actions that would be performed.	
--etcd-upgrade	Default: true
Perform the upgrade of etcd.	
-k, --experimental-kustomize string	
The path where kustomize patches for static pod manifests are stored.	
-h, --help	
help for node	
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
--kubelet-version string	
The *desired* version for the kubelet config after the upgrade. If not specified, the KubernetesVersion from the kubeadm-config ConfigMap will be used	
--skip-phases stringSlice	
List of phases to be skipped	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## What's next

- [kubeadm config](#) if you initialized your cluster using kubeadm v1.7.x or lower, to configure your cluster for kubeadm upgrade

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on November 12, 2019 at 4:28 AM PST by [fix - broken link \(#17529\)](#) ([Page History](#))

[Edit This Page](#)

## kubeadm config

During `kubeadm init`, `kubeadm` uploads the `ClusterConfiguration` object to your cluster in a `ConfigMap` called `kubeadm-config` in the `kube-system` namespace. This configuration is then read during `kubeadm join`, `kubeadm reset` and `kubeadm upgrade`. To view this `ConfigMap` call `kubeadm config view`.

You can use `kubeadm config print` to print the default configuration and `kubeadm config migrate` to convert your old configuration files to a newer

version. `kubeadm config images list` and `kubeadm config images pull` can be used to list and pull the images that kubeadm requires.

In Kubernetes v1.13.0 and later to list/pull kube-dns images instead of the CoreDNS image the `--config` method described [here](#) has to be used.

- [kubeadm config view](#)
- [kubeadm config print init-defaults](#)
- [kubeadm config print join-defaults](#)
- [kubeadm config migrate](#)
- [kubeadm config images list](#)
- [kubeadm config images pull](#)
- [What's next](#)

## kubeadm config view

### Synopsis

Using this command, you can view the ConfigMap in the cluster where the configuration for kubeadm is located.

The configuration is located in the "kube-system" namespace in the "kubeadm-config" ConfigMap.

```
kubeadm config view [flags]
```

### Options

-h, --help
help for view

### Options inherited from parent commands

--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## kubeadm config print init-defaults

### Synopsis

This command prints objects such as the default init configuration that is used for `kubeadm init`.

Note that sensitive values like the Bootstrap Token fields are replaced with placeholder values like `{ "abcdef.0123456789abcdef" "" "nil" <nil> [] [] }` in

order to pass validation but not perform the real computation for creating a token.

```
kubeadm config print init-defaults [flags]
```

## Options

--component-configs stringSlice	
	A comma-separated list for component config API objects to print the default values for. Available values: [KubeProxyConfiguration KubeletConfiguration]. If this flag is not set, no component configs will be printed.
-h, --help	
	help for init-defaults

## Options inherited from parent commands

--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm config print join-defaults

## Synopsis

This command prints objects such as the default join configuration that is used for 'kubeadm join'.

Note that sensitive values like the Bootstrap Token fields are replaced with placeholder values like {"abcdef.0123456789abcdef" "" "nil" <nil> [] []} in order to pass validation but not perform the real computation for creating a token.

```
kubeadm config print join-defaults [flags]
```

## Options

--component-configs stringSlice	
	A comma-separated list for component config API objects to print the default values for. Available values: [KubeProxyConfiguration KubeletConfiguration]. If this flag is not set, no component configs will be printed.
-h, --help	
	help for join-defaults

## Options inherited from parent commands

--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## kubeadm config migrate

### Synopsis

This command lets you convert configuration objects of older versions to the latest supported version, locally in the CLI tool without ever touching anything in the cluster. In this version of kubeadm, the following API versions are supported: - kubeadm.k8s.io/v1beta2

Further, kubeadm can only write out config of version "kubeadm.k8s.io/v1beta2", but read both types. So regardless of what version you pass to the -old-config parameter here, the API object will be read, deserialized, defaulted, converted, validated, and re-serialized when written to stdout or -new-config if specified.

In other words, the output of this command is what kubeadm actually would read internally if you submitted this file to "kubeadm init"

```
kubeadm config migrate [flags]
```

### Options

-h, --help	
help for migrate	
--new-config string	
Path to the resulting equivalent kubeadm config file using the new API version. Optional, if not specified output will be sent to STDOUT.	
--old-config string	
Path to the kubeadm config file that is using an old API version and should be converted. This flag is mandatory.	

## Options inherited from parent commands

--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

# kubeadm config images list

## Synopsis

Print a list of images kubeadm will use. The configuration file is used in case any images or image repositories are customized

```
kubeadm config images list [flags]
```

## Options

--config string	
	Path to a kubeadm configuration file.
--feature-gates string	
	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
-h, --help	
	help for list
--image-repository stringÂ Â Â Â Â Default: "k8s.gcr.io"	
	Choose a container registry to pull control plane images from
--kubernetes-version stringÂ Â Â Â Â Default: "stable-1"	
	Choose a specific Kubernetes version for the control plane.

## Options inherited from parent commands

--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm config images pull

## Synopsis

Pull images used by kubeadm

```
kubeadm config images pull [flags]
```

## Options

--config string	
	Path to a kubeadm configuration file.
--cri-socket string	



	Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
<b>--feature-gates string</b>	
	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
<b>-h, --help</b>	
	help for pull
<b>--image-repository string</b> Default: "k8s.gcr.io"	
	Choose a container registry to pull control plane images from
<b>--kubernetes-version string</b> Default: "stable-1"	
	Choose a specific Kubernetes version for the control plane.

## Options inherited from parent commands

<b>--kubeconfig string</b> Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<b>--rootfs string</b>	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## What's next

- [kubeadm upgrade](#) to upgrade a Kubernetes cluster to a newer version

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 09, 2019 at 1:09 PM PST by [remove myself from some reviewers lists \(#16753\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm reset

Performs a best effort revert of changes made by `kubeadm init` or `kubeadm join`.

- [What's next](#)

## Synopsis

Performs a best effort revert of changes made to this host by `~kubeadm init` or `~kubeadm join`

The "reset" command executes the following phases:

<code>preflight</code>	Run reset pre-flight checks
<code>update-cluster-status</code>	Remove this node from the ClusterStatus object.
<code>remove-etcd-member</code>	Remove a local etcd member.
<code>cleanup-node</code>	Run cleanup node.

```
kubeadm reset [flags]
```

## Options

<code>--cert-dir string</code>	Default: "/etc/kubernetes/pki"
The path to the directory where the certificates are stored. If specified, clean this directory.	
<code>--cri-socket string</code>	
Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.	
<code>-f, --force</code>	
Reset the node without prompting for confirmation.	
<code>-h, --help</code>	
help for reset	
<code>--ignore-preflight-errors stringSlice</code>	
A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.	
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
<code>--skip-phases stringSlice</code>	
List of phases to be skipped	

## Options inherited from parent commands

<code>--rootfs string</code>	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Reset workflow

`kubeadm reset` is responsible for cleaning up a node local file system from files that were created using the `kubeadm init` or `kubeadm join` commands. For control-plane nodes `reset` also removes the local stacked etcd member

of this node from the etcd cluster and also removes this node's information from the kubeadm ClusterStatus object. ClusterStatus is a kubeadm managed Kubernetes API object that holds a list of kube-apiserver endpoints.

`kubeadm reset` phase can be used to execute the separate phases of the above workflow. To skip a list of phases you can use the `--skip-phases` flag, which works in a similar way to the `kubeadm join` and `kubeadm init` phase runners.

## External etcd clean up

`kubeadm reset` will not delete any etcd data if external etcd is used. This means that if you run `kubeadm init` again using the same etcd endpoints, you will see state from previous clusters.

To wipe etcd data it is recommended you use a client like `etcdctl`, such as:

```
etcdctl del "" --prefix
```

See the [etcd documentation](#) for more information.

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to bootstrap a Kubernetes worker node and join it to the cluster

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 09, 2019 at 1:09 PM PST by [remove myself from some reviewers lists \(#16753\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm token

Bootstrap tokens are used for establishing bidirectional trust between a node joining the cluster and a control-plane node, as described in [authenticating with bootstrap tokens](#).

`kubeadm init` creates an initial token with a 24-hour TTL. The following commands allow you to manage such a token and also to create and manage new ones.

- [kubeadm token create](#)
- [kubeadm token delete](#)
- [kubeadm token generate](#)
- [kubeadm token list](#)
- [What's next](#)

## kubeadm token create

### Synopsis

This command will create a bootstrap token for you. You can specify the usages for this token, the "time to live" and an optional human friendly description.

The [token] is the actual token to write. This should be a securely generated random token of the form "[a-z0-9]{6}.[a-z0-9]{16}". If no [token] is given, kubeadm will generate a random token instead.

```
kubeadm token create [token]
```

### Options

--certificate-key string	
	When used together with '--print-join-command', print the full 'kubeadm join' flag needed to join the cluster as a control-plane. To create a new certificate key you must use 'kubeadm init phase upload-certs --upload-certs'.
--config string	
	Path to a kubeadm configuration file.
--description string	
	A human friendly description of how this token is used.
--groups stringSliceÂ Â Â Â Â Default: [system:bootstrappers:kubeadm:default-node-token]	
	Extra groups that this token will authenticate as when used for authentication. Must match "\\Asystem:bootstrappers:[a-z0-9-]{0,255}[a-z0-9]\\z"
-h, --help	
	help for create
--print-join-command	
	Instead of printing only the token, print the full 'kubeadm join' flag needed to join the cluster using the token.
--ttl durationÂ Â Â Â Â Default: 24h0m0s	

	The duration before the token is automatically deleted (e.g. 1s, 2m, 3h). If set to '0', the token will never expire
<code>--usages stringSlice</code> Default: [signing,authentication]	
	Describes the ways in which this token can be used. You can pass <code>--usages</code> multiple times or provide a comma separated list of options. Valid options: [signing,authentication]

## Options inherited from parent commands

<code>--dry-run</code>	
	Whether to enable dry-run mode or not
<code>--kubeconfig string</code> Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<code>--rootfs string</code>	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm token delete

## Synopsis

This command will delete a list of bootstrap tokens for you.

The [token-value] is the full Token of the form "[a-z0-9]{6}.[a-z0-9]{16}" or the Token ID of the form "[a-z0-9]{6}" to delete.

```
kubeadm token delete [token-value] ...
```

## Options

<code>-h, --help</code>	
	help for delete

## Options inherited from parent commands

<code>--dry-run</code>	
	Whether to enable dry-run mode or not
<code>--kubeconfig string</code> Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<code>--rootfs string</code>	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm token generate

## Synopsis

This command will print out a randomly-generated bootstrap token that can be used with the "init" and "join" commands.

You don't have to use this command in order to generate a token. You can do so yourself as long as it is in the format "[a-z0-9]{6}.[a-z0-9]{16}". This command is provided for convenience to generate tokens in the given format.

You can also use "kubeadm init" without specifying a token and it will generate and print one for you.

```
kubeadm token generate [flags]
```

## Options

-h, --help
help for generate

## Options inherited from parent commands

--dry-run
Whether to enable dry-run mode or not
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm token list

## Synopsis

This command will list all bootstrap tokens for you.

```
kubeadm token list [flags]
```

## Options

--allow-missing-template-keysÂ Â Â Â Â Default: true
If true, ignore any errors in templates when a field or map key is missing in the template. Only applies to golang and jsonpath output formats.
-o, --experimental-output stringÂ Â Â Â Â Default: "text"



Output format. One of: text json yaml go-template go-template-file template templatefile jsonpath jsonpath-file.
-h, --help
help for list

## Options inherited from parent commands

--dry-run
Whether to enable dry-run mode or not
--kubeconfig string Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## What's next

- [kubeadm join](#) to bootstrap a Kubernetes worker node and join it to the cluster

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 09, 2019 at 1:09 PM PST by [remove myself from some reviewers lists \(#16753\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm version

This command prints the version of kubeadm.

## Synopsis

Print the version of kubeadm

```
kubeadm version [flags]
```

## Options

-h, --help
help for version
-o, --output string
Output format; available options are 'yaml', 'json' and 'short'

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 09, 2019 at 1:09 PM PST by [remove myself from some reviewers lists \(#16753\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm alpha

- - [kubeadm alpha certs renew](#)
  - [kubeadm alpha certs certificate-key](#)
  - [kubeadm alpha certs check-expiration](#)
  - [kubeadm alpha kubeconfig user](#)
  - [kubeadm alpha kubelet config](#)
  - [kubeadm alpha selfhosting pivot](#)
  - [What's next](#)

**Caution:** kubeadm alpha provides a preview of a set of features made available for gathering feedback from the community. Please try it out and give us feedback!

## kubeadm alpha certs renew

You can renew all Kubernetes certificates using the `all` subcommand or renew them selectively. For more details about certificate expiration and renewal see the [certificate management documentation](#).

- [renew](#)
- [all](#)
- [admin.conf](#)
- [apiserver-etcd-client](#)
- [apiserver-kubelet-client](#)
- [apiserver](#)
- [controller-manager.conf](#)
- [etcd-healthcheck-client](#)
- [etcd-peer](#)
- [etcd-server](#)
- [front-proxy-client](#)
- [scheduler.conf](#)

### Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm alpha certs renew [flags]
```

### Options

-h, --help
help for renew

### Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

### Synopsis

Renew all known certificates necessary to run the control plane. Renewals are run unconditionally, regardless of expiration date. Renewals can also be run individually for more control.

```
kubeadm alpha certs renew all [flags]
```

## Options

<code>--cert-dir string</code>	Default: "/etc/kubernetes/pki"
	The path where to save the certificates
<code>--config string</code>	
	Path to a kubeadm configuration file.
<code>--csr-dir string</code>	
	The path to output the CSRs and private keys to
<code>--csr-only</code>	
	Create CSRs instead of generating certificates
<code>-h, --help</code>	
	help for all
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<code>--use-api</code>	
	Use the Kubernetes certificate API to renew certificates

## Options inherited from parent commands

<code>--rootfs string</code>	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate embedded in the kubeconfig file for the admin to use and for kubeadm itself.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew admin.conf [flags]
```

## Options

<code>--cert-dir string</code>	Default: "/etc/kubernetes/pki"
	The path where to save the certificates
<code>--config string</code>	

	Path to a kubeadm configuration file.
--csr-dir string	
	The path to output the CSRs and private keys to
--csr-only	
	Create CSRs instead of generating certificates
-h, --help	
	help for admin.conf
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"	
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--use-api	
	Use the Kubernetes certificate API to renew certificates

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate the apiserver uses to access etcd.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew apiserver-etcd-client [flags]
```

## Options

--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"	
	The path where to save the certificates
--config string	
	Path to a kubeadm configuration file.
--csr-dir string	
	The path to output the CSRs and private keys to
--csr-only	
	Create CSRs instead of generating certificates
-h, --help	

help for apiserver-etcd-client
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--use-api
Use the Kubernetes certificate API to renew certificates

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate for the API server to connect to kubelet.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew apiserver-kubelet-client [flags]
```

## Options

--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"
The path where to save the certificates
--config string
Path to a kubeadm configuration file.
--csr-dir string
The path to output the CSRs and private keys to
--csr-only
Create CSRs instead of generating certificates
-h, --help
help for apiserver-kubelet-client
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--use-api
Use the Kubernetes certificate API to renew certificates



## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate for serving the Kubernetes API.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew apiserver [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save the certificates	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for apiserver	
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
--use-api	
Use the Kubernetes certificate API to renew certificates	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate embedded in the kubeconfig file for the controller manager to use.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew controller-manager.conf [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
	The path where to save the certificates
--config string	
	Path to a kubeadm configuration file.
--csr-dir string	
	The path to output the CSRs and private keys to
--csr-only	
	Create CSRs instead of generating certificates
-h, --help	
	help for controller-manager.conf
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--use-api	
	Use the Kubernetes certificate API to renew certificates

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate for liveness probes to healthcheck etcd.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew etcd-healthcheck-client [flags]
```

## Options

<code>--cert-dir string</code>	Default: "/etc/kubernetes/pki"
The path where to save the certificates	
<code>--config string</code>	
Path to a kubeadm configuration file.	
<code>--csr-dir string</code>	
The path to output the CSRs and private keys to	
<code>--csr-only</code>	
Create CSRs instead of generating certificates	
<code>-h, --help</code>	
help for etcd-healthcheck-client	
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
<code>--use-api</code>	
Use the Kubernetes certificate API to renew certificates	

## Options inherited from parent commands

<code>--rootfs string</code>	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Renew the certificate for etcd nodes to communicate with each other.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew etcd-peer [flags]
```

## Options

<code>--cert-dir string</code>	Default: "/etc/kubernetes/pki"
The path where to save the certificates	
<code>--config string</code>	
Path to a kubeadm configuration file.	
<code>--csr-dir string</code>	
The path to output the CSRs and private keys to	
<code>--csr-only</code>	
Create CSRs instead of generating certificates	
<code>-h, --help</code>	
help for etcd-peer	
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
<code>--use-api</code>	
Use the Kubernetes certificate API to renew certificates	

## Options inherited from parent commands

<code>--rootfs string</code>	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Renew the certificate for serving etcd.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew etcd-server [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save the certificates	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for etcd-server	
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
--use-api	
Use the Kubernetes certificate API to renew certificates	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Renew the certificate for the front proxy client.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew front-proxy-client [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save the certificates	
--config string	
Path to a kubeadm configuration file.	

<code>--csr-dir string</code>
The path to output the CSRs and private keys to
<code>--csr-only</code>
Create CSRs instead of generating certificates
<code>-h, --help</code>
help for front-proxy-client
<code>--kubeconfig string</code> Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<code>--use-api</code>
Use the Kubernetes certificate API to renew certificates

## Options inherited from parent commands

<code>--rootfs string</code>
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Renew the certificate embedded in the kubeconfig file for the scheduler manager to use.

Renewals run unconditionally, regardless of certificate expiration date; extra attributes such as SANs will be based on the existing file/certificates, there is no need to resupply them.

Renewal by default tries to use the certificate authority in the local PKI managed by kubeadm; as alternative it is possible to use K8s certificate API for certificate renewal, or as a last option, to generate a CSR request.

After renewal, in order to make changes effective, is required to restart control-plane components and eventually re-distribute the renewed certificate in case the file is used elsewhere.

```
kubeadm alpha certs renew scheduler.conf [flags]
```

## Options

<code>--cert-dir string</code> Default: "/etc/kubernetes/pki"
The path where to save the certificates
<code>--config string</code>
Path to a kubeadm configuration file.
<code>--csr-dir string</code>
The path to output the CSRs and private keys to
<code>--csr-only</code>
Create CSRs instead of generating certificates
<code>-h, --help</code>

help for scheduler.conf
--kubeconfig string Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--use-api
Use the Kubernetes certificate API to renew certificates

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm alpha certs certificate-key

This command can be used to generate a new control-plane certificate key. The key can be passed as `--certificate-key` to `kubeadm init` and `kubeadm join` to enable the automatic copy of certificates when joining additional control-plane nodes.

- [certificate-key](#)

## Synopsis

This command will print out a secure randomly-generated certificate key that can be used with the "init" command.

You can also use "kubeadm init -upload-certs" without specifying a certificate key and it will generate and print one for you.

```
kubeadm alpha certs certificate-key [flags]
```

## Options

-h, --help
help for certificate-key

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm alpha certs check-expiration

This command checks expiration for the certificates in the local PKI managed by kubeadm. For more details about certificate expiration and renewal see the [certificate management documentation](#).

- [check-expiration](#)

## Synopsis

Checks expiration for the certificates in the local PKI managed by kubeadm.

```
kubeadm alpha certs check-expiration [flags]
```

## Options

<code>--cert-dir string</code>	Default: "/etc/kubernetes/pki"
The path where to save the certificates	
<code>--config string</code>	
Path to a kubeadm configuration file.	
<code>-h, --help</code>	
help for check-expiration	
<code>--kubeconfig string</code>	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	

## Options inherited from parent commands

<code>--rootfs string</code>	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

# kubeadm alpha kubeconfig user

The user subcommand can be used for the creation of kubeconfig files for additional users.

- [kubeconfig](#)
- [user](#)

## Synopsis

Kubeconfig file utilities.

Alpha Disclaimer: this command is currently alpha.



## Options

-h, --help
help for kubeconfig

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Output a kubeconfig file for an additional user.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm alpha kubeconfig user [flags]
```

## Examples

```
# Output a kubeconfig file for an additional user named foo
kubeadm alpha kubeconfig user --client-name=foo
```

## Options

--apiserver-advertise-address string
The IP address the API server is accessible on
--apiserver-bind-port int32Â Â Â Â Â Default: 6443
The port the API server is accessible on
--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"
The path where certificates are stored
--client-name string
The name of user. It will be used as the CN if client certificates are created
-h, --help
help for user
--org stringSlice
The organizations of the client certificate. It will be used as the O if client certificates are created
--token string
The token that should be used as the authentication mechanism for this kubeconfig, instead of client certificates

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm alpha kubelet config

Use the following commands to either download the kubelet configuration from the cluster or to enable the DynamicKubeletConfiguration feature.

- [kubelet](#)
- [download](#)
- [enable-dynamic](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

## Options

-h, --help
help for kubelet

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Download the kubelet configuration from a ConfigMap of the form "kubelet-config-1.X" in the cluster, where X is the minor version of the kubelet. Either kubeadm autodetects the kubelet version by exec-ing "kubelet -version" or respects the -kubelet-version parameter.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm alpha kubelet config download [flags]
```

## Examples

```
# Download the kubelet configuration from the ConfigMap in the
cluster. Autodetect the kubelet version.
kubeadm alpha phase kubelet config download

# Download the kubelet configuration from the ConfigMap in the
cluster. Use a specific desired kubelet version.
kubeadm alpha phase kubelet config download --kubelet-version
1.17.0
```

## Options

-h, --help
------------

help for download
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--kubelet-version string
The desired version for the kubelet. Defaults to being autodetected from 'kubelet --version'.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Download the kubelet configuration from a ConfigMap of the form "kubelet-config-1.X" in the cluster, where X is the minor version of the kubelet. Either kubeadm autodetects the kubelet version by exec-ing "kubelet -version" or respects the -kubelet-version parameter.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm alpha kubelet config download [flags]
```

## Examples

```
# Download the kubelet configuration from the ConfigMap in the
cluster. Autodetect the kubelet version.
kubeadm alpha phase kubelet config download

# Download the kubelet configuration from the ConfigMap in the
cluster. Use a specific desired kubelet version.
kubeadm alpha phase kubelet config download --kubelet-version
1.17.0
```

## Options

-h, --help
help for download
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--kubelet-version string
The desired version for the kubelet. Defaults to being autodetected from 'kubelet --version'.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm alpha selfhosting pivot

The subcommand `pivot` can be used to convert a static Pod-hosted control plane into a self-hosted one.

[Documentation](#)

- [selfhosting](#)
- [pivot](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

## Options

-h, --help
help for selfhosting

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Convert static Pod files for control plane components into self-hosted DaemonSets configured via the Kubernetes API.

See the documentation for self-hosting limitations.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm alpha selfhosting pivot [flags]
```

## Examples

```
# Convert a static Pod-hosted control plane into a self-hosted one.
```

```
kubeadm alpha phase self-hosting convert-from-staticpods
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where certificates are stored	
--config string	
Path to a kubeadm configuration file.	
-f, --force	
Pivot the cluster without prompting for confirmation	
-h, --help	
help for pivot	
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	
-s, --store-certs-in-secrets	
Enable storing certs in secrets	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to connect a node to the cluster
- [kubeadm reset](#) to revert any changes made to this host by kubeadm init or kubeadm join

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 09, 2019 at 1:09 PM PST by [remove myself from some reviewers lists \(#16753\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm init phase

- - [kubeadm init phase preflight](#)
  - [kubeadm init phase kubelet-start](#)
  - [kubeadm init phase certs](#)
  - [kubeadm init phase kubeconfig](#)
  - [kubeadm init phase control-plane](#)
  - [kubeadm init phase etcd](#)
  - [kubeadm init phase upload-config](#)
  - [kubeadm init phase upload-certs](#)

- [kubeadm init phase mark-control-plane](#)
- [kubeadm init phase bootstrap-token](#)
- [kubeadm init phase addon](#)
- [What's next](#)

`kubeadm init` phase enables you to invoke atomic steps of the bootstrap process. Hence, you can let kubeadm do some of the work and you can fill in the gaps if you wish to apply customization.

`kubeadm init` phase is consistent with the [kubeadm init workflow](#), and behind the scene both use the same code.

## kubeadm init phase preflight

Using this command you can execute preflight checks on a control-plane node.

- [preflight](#)

### Synopsis

Run pre-flight checks for kubeadm init.

```
kubeadm init phase preflight [flags]
```

### Examples

```
# Run pre-flight checks for kubeadm init using a config file.
kubeadm init phase preflight --config kubeadm-config.yml
```

### Options

<code>--config</code>	string
	Path to a kubeadm configuration file.
<code>-h, --help</code>	
	help for preflight
<code>--ignore-preflight-errors</code>	stringSlice
	A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.

### Options inherited from parent commands

<code>--rootfs</code>	string
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm init phase kubelet-start

This phase will write the kubelet configuration file and environment file and then start the kubelet.

- [kubelet-start](#)

## Synopsis

Write a file with KubeletConfiguration and an environment file with node specific kubelet settings, and then (re)start kubelet.

```
kubeadm init phase kubelet-start [flags]
```

## Examples

```
# Writes a dynamic environment file with kubelet flags from a
InitConfiguration file.
kubeadm init phase kubelet-start --config config.yaml
```

## Options

--config string	
	Path to a kubeadm configuration file.
--cri-socket string	
	Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
-h, --help	
	help for kubelet-start
--node-name string	
	Specify the node name.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm init phase certs

Can be used to create all required certificates by kubeadm.

- [certs](#)
- [all](#)
- [ca](#)
- [apiserver](#)
- [apiserver-kubelet-client](#)
- [front-proxy-ca](#)



- [front-proxy-client](#)
- [etcd-ca](#)
- [etcd-server](#)
- [etcd-peer](#)
- [healthcheck-client](#)
- [apiserver-etcd-client](#)
- [sa](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase certs [flags]
```

## Options

-h, --help
help for certs

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate all certificates

```
kubeadm init phase certs all [flags]
```

## Options

--apiserver-advertise-address string
The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-cert-extra-sans stringSlice
Optional extra Subject Alternative Names (SANs) to use for the API Server serving certificate. Can be both IP addresses and DNS names.
--cert-dir string Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.
--config string
Path to a kubeadm configuration file.
--control-plane-endpoint string
Specify a stable IP address or DNS name for the control plane.
-h, --help
help for all

--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	
--service-cidr string	Default: "10.96.0.0/12"
Use alternative range of IP address for service VIPs.	
--service-dns-domain string	Default: "cluster.local"
Use alternative domain for services, e.g. "myorg.internal".	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the self-signed Kubernetes CA to provision identities for other Kubernetes components, and save them into ca.cert and ca.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs ca [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	Path to a kubeadm configuration file.
-h, --help	help for ca
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the certificate for serving the Kubernetes API, and save them into apiserver.cert and apiserver.key files.

Default SANs are kubernetes, kubernetes.default, kubernetes.default.svc, kubernetes.default.svc.cluster.local, 10.96.0.1, 127.0.0.1

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs apiserver [flags]
```

## Options

<code>--apiserver-advertise-address</code> string	
	The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-cert-extra-sans</code> stringSlice	
	Optional extra Subject Alternative Names (SANs) to use for the API Server serving certificate. Can be both IP addresses and DNS names.
<code>--cert-dir</code> string	Default: "/etc/kubernetes/pki"
	The path where to save and store the certificates.
<code>--config</code> string	
	Path to a kubeadm configuration file.
<code>--control-plane-endpoint</code> string	
	Specify a stable IP address or DNS name for the control plane.
<code>--csr-dir</code> string	
	The path to output the CSRs and private keys to
<code>--csr-only</code>	
	Create CSRs instead of generating certificates
<code>-h, --help</code>	
	help for apiserver
<code>--kubernetes-version</code> string	Default: "stable-1"
	Choose a specific Kubernetes version for the control plane.
<code>--service-cidr</code> string	Default: "10.96.0.0/12"
	Use alternative range of IP address for service VIPs.
<code>--service-dns-domain</code> string	Default: "cluster.local"
	Use alternative domain for services, e.g. "myorg.internal".

## Options inherited from parent commands

<code>--rootfs</code> string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the certificate for the API server to connect to kubelet, and save them into apiserver-kubelet-client.cert and apiserver-kubelet-client.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs apiserver-kubelet-client [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for apiserver-kubelet-client	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Generate the self-signed CA to provision identities for front proxy, and save them into front-proxy-ca.cert and front-proxy-ca.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs front-proxy-ca [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
-h, --help	
help for front-proxy-ca	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the certificate for the front proxy client, and save them into front-proxy-client.cert and front-proxy-client.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs front-proxy-client [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for front-proxy-client	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the self-signed CA to provision identities for etcd, and save them into etcd/ca.cert and etcd/ca.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs etcd-ca [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
-h, --help	
help for etcd-ca	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Generate the certificate for serving etcd, and save them into etcd/server.cert and etcd/server.key files.

Default SANs are localhost, 127.0.0.1, 127.0.0.1, ::1

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs etcd-server [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for etcd-server	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the certificate for etcd nodes to communicate with each other, and save them into etcd/peer.cert and etcd/peer.key files.

Default SANs are localhost, 127.0.0.1, 127.0.0.1, ::1

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs etcd-peer [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
	The path where to save and store the certificates.
--config string	
	Path to a kubeadm configuration file.
--csr-dir string	
	The path to output the CSRs and private keys to
--csr-only	
	Create CSRs instead of generating certificates
-h, --help	
	help for etcd-peer
--kubernetes-version string	Default: "stable-1"
	Choose a specific Kubernetes version for the control plane.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the certificate for liveness probes to healthcheck etcd, and save them into etcd/healthcheck-client.cert and etcd/healthcheck-client.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs etcd-healthcheck-client [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for etcd-healthcheck-client	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Generate the certificate the apiserver uses to access etcd, and save them into apiserver-etcd-client.cert and apiserver-etcd-client.key files.

If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs apiserver-etcd-client [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
--csr-dir string	
The path to output the CSRs and private keys to	
--csr-only	
Create CSRs instead of generating certificates	
-h, --help	
help for apiserver-etcd-client	



--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the private key for signing service account tokens along with its public key, and save them into sa.key and sa.pub files. If both files already exist, kubeadm skips the generation step and existing files will be used.

Alpha Disclaimer: this command is currently alpha.

```
kubeadm init phase certs sa [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
-h, --help	
help for sa	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm init phase kubeconfig

You can create all required kubeconfig files by calling the all subcommand or call them individually.

- [kubeconfig](#)
- [all](#)
- [admin](#)
- [kubelet](#)
- [controller-manager](#)
- [scheduler](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase kubeconfig [flags]
```

## Options

--h, --help
help for kubeconfig

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate all kubeconfig files

```
kubeadm init phase kubeconfig all [flags]
```

## Options

--apiserver-advertise-address string
The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32Â Â Â Â Â Default: 6443
Port for the API Server to bind to.
--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.
--config string
Path to a kubeadm configuration file.
--control-plane-endpoint string
Specify a stable IP address or DNS name for the control plane.
-h, --help
help for all
--kubeconfig-dir stringÂ Â Â Â Â Default: "/etc/kubernetes"
The path where to save the kubeconfig file.
--kubernetes-version stringÂ Â Â Â Â Default: "stable-1"
Choose a specific Kubernetes version for the control plane.
--node-name string
Specify the node name.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the kubeconfig file for the admin and for kubeadm itself, and save it to admin.conf file.

```
kubeadm init phase kubeconfig admin [flags]
```

## Options

--apiserver-advertise-address string
The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32Â Â Â Â Â Default: 6443
Port for the API Server to bind to.
--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.
--config string
Path to a kubeadm configuration file.
--control-plane-endpoint string
Specify a stable IP address or DNS name for the control plane.
-h, --help
help for admin
--kubeconfig-dir stringÂ Â Â Â Â Default: "/etc/kubernetes"
The path where to save the kubeconfig file.
--kubernetes-version stringÂ Â Â Â Â Default: "stable-1"
Choose a specific Kubernetes version for the control plane.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the kubeconfig file for the kubelet to use and save it to kubelet.conf file.

Please note that this should *only* be used for cluster bootstrapping purposes. After your control plane is up, you should request all kubelet credentials from the CSR API.

```
kubeadm init phase kubeconfig kubelet [flags]
```

## Options

--apiserver-advertise-address string
--------------------------------------

	The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-bind-port</code> int32Â Â Â Â Â Default: 6443	
	Port for the API Server to bind to.
<code>--cert-dir</code> stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"	
	The path where to save and store the certificates.
<code>--config</code> string	
	Path to a kubeadm configuration file.
<code>--control-plane-endpoint</code> string	
	Specify a stable IP address or DNS name for the control plane.
<code>-h, --help</code>	
	help for kubelet
<code>--kubeconfig-dir</code> stringÂ Â Â Â Â Default: "/etc/kubernetes"	
	The path where to save the kubeconfig file.
<code>--kubernetes-version</code> stringÂ Â Â Â Â Default: "stable-1"	
	Choose a specific Kubernetes version for the control plane.
<code>--node-name</code> string	
	Specify the node name.

## Options inherited from parent commands

<code>--rootfs</code> string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the kubeconfig file for the controller manager to use and save it to controller-manager.conf file

```
kubeadm init phase kubeconfig controller-manager [flags]
```

## Options

<code>--apiserver-advertise-address</code> string	
	The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-bind-port</code> int32Â Â Â Â Â Default: 6443	
	Port for the API Server to bind to.
<code>--cert-dir</code> stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"	
	The path where to save and store the certificates.
<code>--config</code> string	
	Path to a kubeadm configuration file.
<code>--control-plane-endpoint</code> string	
	Specify a stable IP address or DNS name for the control plane.

-h, --help
help for controller-manager
--kubeconfig-dir stringÂ Â Â Â Â Default: "/etc/kubernetes"
The path where to save the kubeconfig file.
--kubernetes-version stringÂ Â Â Â Â Default: "stable-1"
Choose a specific Kubernetes version for the control plane.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the kubeconfig file for the scheduler to use and save it to scheduler.conf file.

```
kubeadm init phase kubeconfig scheduler [flags]
```

## Options

--apiserver-advertise-address string
The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32Â Â Â Â Â Default: 6443
Port for the API Server to bind to.
--cert-dir stringÂ Â Â Â Â Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.
--config string
Path to a kubeadm configuration file.
--control-plane-endpoint string
Specify a stable IP address or DNS name for the control plane.
-h, --help
help for scheduler
--kubeconfig-dir stringÂ Â Â Â Â Default: "/etc/kubernetes"
The path where to save the kubeconfig file.
--kubernetes-version stringÂ Â Â Â Â Default: "stable-1"
Choose a specific Kubernetes version for the control plane.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

# kubeadm init phase control-plane

Using this phase you can create all required static Pod files for the control plane components.

- [control-plane](#)
- [all](#)
- [apiserver](#)
- [controller-manager](#)
- [scheduler](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase control-plane [flags]
```

## Options

-h, --help
help for control-plane

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate all static Pod manifest files

```
kubeadm init phase control-plane all [flags]
```

## Examples

```
# Generates all static Pod manifest files for control plane
components,
# functionally equivalent to what is generated by kubeadm init.
kubeadm init phase control-plane all

# Generates all static Pod manifest files using options read
from a configuration file.
kubeadm init phase control-plane all --config config.yaml
```

## Options

--apiserver-advertise-address string
--------------------------------------

	The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-bind-port</code> int32 Default: 6443	
	Port for the API Server to bind to.
<code>--apiserver-extra-args</code> mapStringString	
	A set of extra flags to pass to the API Server or override default ones in form of <flagname>=<value>
<code>--cert-dir</code> string Default: "/etc/kubernetes/pki"	
	The path where to save and store the certificates.
<code>--config</code> string	
	Path to a kubeadm configuration file.
<code>--control-plane-endpoint</code> string	
	Specify a stable IP address or DNS name for the control plane.
<code>--controller-manager-extra-args</code> mapStringString	
	A set of extra flags to pass to the Controller Manager or override default ones in form of <flagname>=<value>
<code>-k, --experimental-kustomize</code> string	
	The path where kustomize patches for static pod manifests are stored.
<code>--feature-gates</code> string	
	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
<code>-h, --help</code>	
	help for all
<code>--image-repository</code> string Default: "k8s.gcr.io"	
	Choose a container registry to pull control plane images from
<code>--kubernetes-version</code> string Default: "stable-1"	
	Choose a specific Kubernetes version for the control plane.
<code>--pod-network-cidr</code> string	
	Specify range of IP addresses for the pod network. If set, the control plane will automatically allocate CIDRs for every node.
<code>--scheduler-extra-args</code> mapStringString	
	A set of extra flags to pass to the Scheduler or override default ones in form of <flagname>=<value>
<code>--service-cidr</code> string Default: "10.96.0.0/12"	
	Use alternative range of IP address for service VIPs.

## Options inherited from parent commands

<code>--rootfs</code> string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generates the kube-apiserver static Pod manifest

```
kubeadm init phase control-plane apiserver [flags]
```

## Options

--apiserver-advertise-address string	
	The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32 Default: 6443	
	Port for the API Server to bind to.
--apiserver-extra-args mapStringString	
	A set of extra flags to pass to the API Server or override default ones in form of <flagname>=<value>
--cert-dir string Default: "/etc/kubernetes/pki"	
	The path where to save and store the certificates.
--config string	
	Path to a kubeadm configuration file.
--control-plane-endpoint string	
	Specify a stable IP address or DNS name for the control plane.
-k, --experimental-kustomize string	
	The path where kustomize patches for static pod manifests are stored.
--feature-gates string	
	A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
-h, --help	
	help for apiserver
--image-repository string Default: "k8s.gcr.io"	
	Choose a container registry to pull control plane images from
--kubernetes-version string Default: "stable-1"	
	Choose a specific Kubernetes version for the control plane.
--service-cidr string Default: "10.96.0.0/12"	
	Use alternative range of IP address for service VIPs.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generates the kube-controller-manager static Pod manifest



```
kubeadm init phase control-plane controller-manager [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
--controller-manager-extra-args mapStringString	
A set of extra flags to pass to the Controller Manager or override default ones in form of <flagname>=<value>	
-k, --experimental-kustomize string	
The path where kustomize patches for static pod manifests are stored.	
-h, --help	
help for controller-manager	
--image-repository string	Default: "k8s.gcr.io"
Choose a container registry to pull control plane images from	
--kubernetes-version string	Default: "stable-1"
Choose a specific Kubernetes version for the control plane.	
--pod-network-cidr string	
Specify range of IP addresses for the pod network. If set, the control plane will automatically allocate CIDRs for every node.	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## Synopsis

Generates the kube-scheduler static Pod manifest

```
kubeadm init phase control-plane scheduler [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
-k, --experimental-kustomize string	
The path where kustomize patches for static pod manifests are stored.	
-h, --help	
help for scheduler	
--image-repository string	Default: "k8s.gcr.io"

	Choose a container registry to pull control plane images from
--kubernetes-version	string Default: "stable-1"
	Choose a specific Kubernetes version for the control plane.
--scheduler-extra-args	mapStringString
	A set of extra flags to pass to the Scheduler or override default ones in form of <flagname>=<value>

## Options inherited from parent commands

--rootfs	string
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm init phase etcd

Use the following phase to create a local etcd instance based on a static Pod file.

- [etcd](#)
- [local](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase etcd [flags]
```

## Options

-h, --help
help for etcd

## Options inherited from parent commands

--rootfs	string
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the static Pod manifest file for a local, single-node local etcd instance

```
kubeadm init phase etcd local [flags]
```

## Examples

```
# Generates the static Pod manifest file for etcd, functionally
# equivalent to what is generated by kubeadm init.
```

```
kubeadm init phase etcd local
```

```
# Generates the static Pod manifest file for etcd using options  
# read from a configuration file.  
kubeadm init phase etcd local --config config.yaml
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
The path where to save and store the certificates.	
--config string	
Path to a kubeadm configuration file.	
-k, --experimental-kustomize string	
The path where kustomize patches for static pod manifests are stored.	
-h, --help	
help for local	
--image-repository string	Default: "k8s.gcr.io"
Choose a container registry to pull control plane images from	

## Options inherited from parent commands

--rootfs string	
[EXPERIMENTAL] The path to the 'real' host root filesystem.	

## kubeadm init phase upload-config

You can use this command to upload the kubeadm configuration to your cluster. Alternatively, you can use [kubeadm config](#).

- [upload-config](#)
- [all](#)
- [kubeadm](#)
- [kubelet](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase upload-config [flags]
```

## Options

-h, --help	
help for upload-config	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Upload all configuration to a config map

```
kubeadm init phase upload-config all [flags]
```

## Options

--config string
Path to a kubeadm configuration file.
-h, --help
help for all
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Upload the kubeadm ClusterConfiguration to a ConfigMap called kubeadm-config in the kube-system namespace. This enables correct configuration of system components and a seamless user experience when upgrading.

Alternatively, you can use kubeadm config.

```
kubeadm init phase upload-config kubeadm [flags]
```

## Examples

```
# upload the configuration of your cluster
kubeadm init phase upload-config --config=myConfig.yaml
```

## Options

--config string
Path to a kubeadm configuration file.
-h, --help
help for kubeadm

--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Upload kubelet configuration extracted from the kubeadm InitConfiguration object to a ConfigMap of the form kubelet-config-1.X in the cluster, where X is the minor version of the current (API Server) Kubernetes version.

```
kubeadm init phase upload-config kubelet [flags]
```

## Examples

```
# Upload the kubelet configuration from the kubeadm Config
file to a ConfigMap in the cluster.
kubeadm init phase upload-config kubelet --config kubeadm.yaml
```

## Options

--config string	
Path to a kubeadm configuration file.	
-h, --help	
help for kubelet	
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.	

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm init phase upload-certs

Use the following phase to upload control-plane certificates to the cluster. By default the certs and encryption key expire after two hours.

- [upload-certs](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase upload-certs [flags]
```

## Options

--certificate-key string
Key used to encrypt the control-plane certificates in the kubeadm-certs Secret.
--config string
Path to a kubeadm configuration file.
-h, --help
help for upload-certs
--skip-certificate-key-print
Don't print the key used to encrypt the control-plane certificates.
--upload-certs
Upload control-plane certificates to the kubeadm-certs Secret.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm init phase mark-control-plane

Use the following phase to label and taint the node with the `node-role.kubernetes.io/master=""` key-value pair.

- [mark-control-plane](#)

## Synopsis

Mark a node as a control-plane

```
kubeadm init phase mark-control-plane [flags]
```

## Examples

```
# Applies control-plane label and taint to the current node,
functionally equivalent to what executed by kubeadm init.
kubeadm init phase mark-control-plane --config config.yml

# Applies control-plane label and taint to a specific node
kubeadm init phase mark-control-plane --node-name myNode
```

## Options

--config string
Path to a kubeadm configuration file.
-h, --help
help for mark-control-plane
--node-name string
Specify the node name.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm init phase bootstrap-token

Use the following phase to configure bootstrap tokens.

- [bootstrap-token](#)

## Synopsis

Bootstrap tokens are used for establishing bidirectional trust between a node joining the cluster and a control-plane node.

This command makes all the configurations required to make bootstrap tokens works and then creates an initial token.

```
kubeadm init phase bootstrap-token [flags]
```

## Examples

```
# Make all the bootstrap token configurations and create an
initial token, functionally
# equivalent to what generated by kubeadm init.
kubeadm init phase bootstrap-token
```

## Options

--config string
Path to a kubeadm configuration file.
-h, --help
help for bootstrap-token
--kubeconfig string
Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--skip-token-print

Skip printing of the default bootstrap token generated by 'kubeadm init'.
---

## Options inherited from parent commands

--rootfs string
-----------------

[EXPERIMENTAL] The path to the 'real' host root filesystem.
---

## kubeadm init phase addon

You can install all the available addons with the `all` subcommand, or install them selectively.

- [addon](#)
- [all](#)
- [coredns](#)
- [kube-proxy](#)

## Synopsis

This command is not meant to be run on its own. See list of available subcommands.

```
kubeadm init phase addon [flags]
```

## Options

-h, --help
------------

help for addon
----------------

## Options inherited from parent commands

--rootfs string
-----------------

[EXPERIMENTAL] The path to the 'real' host root filesystem.
---

## Synopsis

Install all the addons

```
kubeadm init phase addon all [flags]
```

## Options

--apiserver-advertise-address string
--------------------------------------

The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--

--apiserver-bind-port int32 Default: 6443
---

Port for the API Server to bind to.
-------------------------------------



<code>--config string</code>
Path to a kubeadm configuration file.
<code>--control-plane-endpoint string</code>
Specify a stable IP address or DNS name for the control plane.
<code>--feature-gates string</code>
A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
<code>-h, --help</code>
help for all
<code>--image-repository string</code> Default: "k8s.gcr.io"
Choose a container registry to pull control plane images from
<code>--kubeconfig string</code> Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
<code>--kubernetes-version string</code> Default: "stable-1"
Choose a specific Kubernetes version for the control plane.
<code>--pod-network-cidr string</code>
Specify range of IP addresses for the pod network. If set, the control plane will automatically allocate CIDRs for every node.
<code>--service-cidr string</code> Default: "10.96.0.0/12"
Use alternative range of IP address for service VIPs.
<code>--service-dns-domain string</code> Default: "cluster.local"
Use alternative domain for services, e.g. "myorg.internal".

## Options inherited from parent commands

<code>--rootfs string</code>
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Install the CoreDNS addon components via the API server. Please note that although the DNS server is deployed, it will not be scheduled until CNI is installed.

```
kubeadm init phase addon coredns [flags]
```

## Options

<code>--config string</code>
Path to a kubeadm configuration file.
<code>--feature-gates string</code>

A set of key=value pairs that describe feature gates for various features. Options are: IPv6DualStack=true false (ALPHA - default=false)
-h, --help
help for coredns
--image-repository stringÂ Â Â Â Â Default: "k8s.gcr.io"
Choose a container registry to pull control plane images from
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"
The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--kubernetes-version stringÂ Â Â Â Â Default: "stable-1"
Choose a specific Kubernetes version for the control plane.
--service-cidr stringÂ Â Â Â Â Default: "10.96.0.0/12"
Use alternative range of IP address for service VIPs.
--service-dns-domain stringÂ Â Â Â Â Default: "cluster.local"
Use alternative domain for services, e.g. "myorg.internal".

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Install the kube-proxy addon components via the API server.

```
kubeadm init phase addon kube-proxy [flags]
```

## Options

--apiserver-advertise-address string
The IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32Â Â Â Â Â Default: 6443
Port for the API Server to bind to.
--config string
Path to a kubeadm configuration file.
--control-plane-endpoint string
Specify a stable IP address or DNS name for the control plane.
-h, --help
help for kube-proxy
--image-repository stringÂ Â Â Â Â Default: "k8s.gcr.io"
Choose a container registry to pull control plane images from
--kubeconfig stringÂ Â Â Â Â Default: "/etc/kubernetes/admin.conf"

	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--kubernetes-version string	Default: "stable-1"
	Choose a specific Kubernetes version for the control plane.
--pod-network-cidr string	
	Specify range of IP addresses for the pod network. If set, the control plane will automatically allocate CIDRs for every node.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

To use kube-dns instead of CoreDNS you have to pass a configuration file:

```
# for installing a DNS addon only
kubeadm init phase addon coredns --config=someconfig.yaml
# for creating a complete control plane node
kubeadm init --config=someconfig.yaml
# for listing or pulling images
kubeadm config images list/pull --config=someconfig.yaml
# for upgrades
kubeadm upgrade apply --config=someconfig.yaml
```

The file has to contain a [DNS](#) field in [ClusterConfiguration](#) and also a type for the addon - kube-dns (default value is CoreDNS).

```
apiVersion: kubeadm.k8s.io/v1beta2
kind: ClusterConfiguration
dns:
  type: "kube-dns"
```

For more details on each field in the v1beta2 configuration you can navigate to our [API reference pages](#).

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to connect a node to the cluster
- [kubeadm reset](#) to revert any changes made to this host by kubeadm init or kubeadm join
- [kubeadm alpha](#) to try experimental functionality

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on October 23, 2019 at 8:50 AM PST by [update order of kubeadm init phase command docs \(#16922\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm join phase

- - [kubeadm join phase](#)
  - [kubeadm join phase preflight](#)
  - [kubeadm join phase control-plane-prepare](#)

- [kubeadm join phase kubelet-start](#)
- [kubeadm join phase control-plane-join](#)
- [What's next](#)

`kubeadm join phase` enables you to invoke atomic steps of the join process. Hence, you can let `kubeadm` do some of the work and you can fill in the gaps if you wish to apply customization.

`kubeadm join phase` is consistent with the [kubeadm join workflow](#), and behind the scene both use the same code.

## kubeadm join phase

- [phase](#)

### Synopsis

Use this command to invoke single phase of the join workflow

### Options

-h, --help
help for phase

### Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm join phase preflight

Using this phase you can execute preflight checks on a joining node.

- [preflight](#)

### Synopsis

Run pre-flight checks for `kubeadm join`.

```
kubeadm join phase preflight [api-server-endpoint] [flags]
```

### Examples

```
# Run join pre-flight checks using a config file.
kubeadm join phase preflight --config kubeadm-config.yml
```

### Options

--apiserver-advertise-address string
--------------------------------------

	If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-bind-port int32</code> Default: 6443	
	If the node should host a new control plane instance, the port for the API Server to bind to.
<code>--certificate-key string</code>	
	Use this key to decrypt the certificate secrets uploaded by init.
<code>--config string</code>	
	Path to kubeadm config file.
<code>--control-plane</code>	
	Create a new control plane instance on this node
<code>--cri-socket string</code>	
	Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
<code>--discovery-file string</code>	
	For file-based discovery, a file or URL from which to load cluster information.
<code>--discovery-token string</code>	
	For token-based discovery, the token used to validate cluster information fetched from the API server.
<code>--discovery-token-ca-cert-hash string</code> Slice	
	For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
<code>--discovery-token-unsafe-skip-ca-verification</code>	
	For token-based discovery, allow joining without --discovery-token-ca-cert-hash pinning.
<code>-h, --help</code>	
	help for preflight
<code>--ignore-preflight-errors string</code> Slice	
	A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.
<code>--node-name string</code>	
	Specify the node name.
<code>--tls-bootstrap-token string</code>	
	Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
<code>--token string</code>	
	Use this token for both discovery-token and tls-bootstrap-token when those values are not provided.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm join phase control-plane-prepare

Using this phase you can prepare a node for serving a control-plane.

- [control-plane-prepare](#)
- [all](#)
- [download-certs](#)
- [certs](#)
- [kubeconfig](#)
- [control-plane](#)

## Synopsis

Prepare the machine for serving a control plane

```
kubeadm join phase control-plane-prepare [flags]
```

## Examples

```
# Prepares the machine for serving a control plane
kubeadm join phase control-plane-prepare all
```

## Options

-h, --help
help for control-plane-prepare

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Prepare the machine for serving a control plane

```
kubeadm join phase control-plane-prepare all [api-server-  
endpoint] [flags]
```

## Options

--apiserver-advertise-address string
--------------------------------------

	If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
<code>--apiserver-bind-port</code> int32 Default: 6443	
	If the node should host a new control plane instance, the port for the API Server to bind to.
<code>--certificate-key</code> string	
	Use this key to decrypt the certificate secrets uploaded by init.
<code>--config</code> string	
	Path to kubeadm config file.
<code>--control-plane</code>	
	Create a new control plane instance on this node
<code>--discovery-file</code> string	
	For file-based discovery, a file or URL from which to load cluster information.
<code>--discovery-token</code> string	
	For token-based discovery, the token used to validate cluster information fetched from the API server.
<code>--discovery-token-ca-cert-hash</code> stringSlice	
	For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
<code>--discovery-token-unsafe-skip-ca-verification</code>	
	For token-based discovery, allow joining without <code>--discovery-token-ca-cert-hash</code> pinning.
<code>-k, --experimental-kustomize</code> string	
	The path where kustomize patches for static pod manifests are stored.
<code>-h, --help</code>	
	help for all
<code>--node-name</code> string	
	Specify the node name.
<code>--tls-bootstrap-token</code> string	
	Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
<code>--token</code> string	
	Use this token for both <code>discovery-token</code> and <code>tls-bootstrap-token</code> when those values are not provided.

## Options inherited from parent commands

<code>--rootfs</code> string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.



## Synopsis

[EXPERIMENTAL] Download certificates shared among control-plane nodes from the kubeadm-certs Secret

```
kubeadm join phase control-plane-prepare download-certs [api-server-endpoint] [flags]
```

## Options

--certificate-key string	
	Use this key to decrypt the certificate secrets uploaded by init.
--config string	
	Path to kubeadm config file.
--control-plane	
	Create a new control plane instance on this node
--discovery-file string	
	For file-based discovery, a file or URL from which to load cluster information.
--discovery-token string	
	For token-based discovery, the token used to validate cluster information fetched from the API server.
--discovery-token-ca-cert-hash stringSlice	
	For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
--discovery-token-unsafe-skip-ca-verification	
	For token-based discovery, allow joining without --discovery-token-ca-cert-hash pinning.
-h, --help	
	help for download-certs
--tls-bootstrap-token string	
	Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
--token string	
	Use this token for both discovery-token and tls-bootstrap-token when those values are not provided.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the certificates for the new control plane components

```
kubeadm join phase control-plane-prepare certs [api-server-  
endpoint] [flags]
```

## Options

--apiserver-advertise-address string	
	If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--config string	
	Path to kubeadm config file.
--control-plane	
	Create a new control plane instance on this node
--discovery-file string	
	For file-based discovery, a file or URL from which to load cluster information.
--discovery-token string	
	For token-based discovery, the token used to validate cluster information fetched from the API server.
--discovery-token-ca-cert-hash stringSlice	
	For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
--discovery-token-unsafe-skip-ca-verification	
	For token-based discovery, allow joining without --discovery-token-ca-cert-hash pinning.
-h, --help	
	help for certs
--node-name string	
	Specify the node name.
--tls-bootstrap-token string	
	Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
--token string	
	Use this token for both discovery-token and tls-bootstrap-token when those values are not provided.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the kubeconfig for the new control plane components

```
kubeadm join phase control-plane-prepare kubeconfig [api-server-endpoint] [flags]
```

## Options

--certificate-key string	
	Use this key to decrypt the certificate secrets uploaded by init.
--config string	
	Path to kubeadm config file.
--control-plane	
	Create a new control plane instance on this node
--discovery-file string	
	For file-based discovery, a file or URL from which to load cluster information.
--discovery-token string	
	For token-based discovery, the token used to validate cluster information fetched from the API server.
--discovery-token-ca-cert-hash stringSlice	
	For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
--discovery-token-unsafe-skip-ca-verification	
	For token-based discovery, allow joining without --discovery-token-ca-cert-hash pinning.
-h, --help	
	help for kubeconfig
--tls-bootstrap-token string	
	Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
--token string	
	Use this token for both discovery-token and tls-bootstrap-token when those values are not provided.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Generate the manifests for the new control plane components

```
kubeadm join phase control-plane-prepare control-plane [flags]
```

## Options

--apiserver-advertise-address string
If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--apiserver-bind-port int32 Default: 6443
If the node should host a new control plane instance, the port for the API Server to bind to.
--config string
Path to kubeadm config file.
--control-plane
Create a new control plane instance on this node
-k, --experimental-kustomize string
The path where kustomize patches for static pod manifests are stored.
-h, --help
help for control-plane

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm join phase kubelet-start

Using this phase you can write the kubelet settings, certificates and (re)start the kubelet.

- [kubelet-start](#)

## Synopsis

Write a file with KubeletConfiguration and an environment file with node specific kubelet settings, and then (re)start kubelet.

```
kubeadm join phase kubelet-start [api-server-endpoint] [flags]
```

## Options

--config string
Path to kubeadm config file.
--cri-socket string
Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
--discovery-file string

	For file-based discovery, a file or URL from which to load cluster information.
<code>--discovery-token</code> string	
	For token-based discovery, the token used to validate cluster information fetched from the API server.
<code>--discovery-token-ca-cert-hash</code> stringSlice	
	For token-based discovery, validate that the root CA public key matches this hash (format: "<type>:<value>").
<code>--discovery-token-unsafe-skip-ca-verification</code>	
	For token-based discovery, allow joining without <code>--discovery-token-ca-cert-hash</code> pinning.
<code>-h, --help</code>	
	help for kubelet-start
<code>--node-name</code> string	
	Specify the node name.
<code>--tls-bootstrap-token</code> string	
	Specify the token used to temporarily authenticate with the Kubernetes Control Plane while joining the node.
<code>--token</code> string	
	Use this token for both <code>discovery-token</code> and <code>tls-bootstrap-token</code> when those values are not provided.

## Options inherited from parent commands

<code>--rootfs</code> string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm join phase control-plane-join

Using this phase you can join a node as a control-plane instance.

- [control-plane-join](#)
- [all](#)
- [etcd](#)
- [update-status](#)
- [mark-control-plane](#)

## Synopsis

Join a machine as a control plane instance

```
kubeadm join phase control-plane-join [flags]
```

## Examples

```
# Joins a machine as a control plane instance
kubeadm join phase control-plane-join all
```

## Options

-h, --help
help for control-plane-join

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Join a machine as a control plane instance

```
kubeadm join phase control-plane-join all [flags]
```

## Options

--apiserver-advertise-address string
If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--config string
Path to kubeadm config file.
--control-plane
Create a new control plane instance on this node
-h, --help
help for all
--node-name string
Specify the node name.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Add a new local etcd member

```
kubeadm join phase control-plane-join etcd [flags]
```

## Options

--apiserver-advertise-address string	
	If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--config string	
	Path to kubeadm config file.
--control-plane	
	Create a new control plane instance on this node
-k, --experimental-kustomize string	
	The path where kustomize patches for static pod manifests are stored.
-h, --help	
	help for etcd
--node-name string	
	Specify the node name.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Register the new control-plane node into the ClusterStatus maintained in the kubeadm-config ConfigMap

```
kubeadm join phase control-plane-join update-status [flags]
```

## Options

--apiserver-advertise-address string	
	If the node should host a new control plane instance, the IP address the API Server will advertise it's listening on. If not set the default network interface will be used.
--config string	
	Path to kubeadm config file.
--control-plane	
	Create a new control plane instance on this node
-h, --help	
	help for update-status
--node-name string	
	Specify the node name.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Mark a node as a control-plane

```
kubeadm join phase control-plane-join mark-control-plane [flags]
```

## Options

--config string
Path to kubeadm config file.
--control-plane
Create a new control plane instance on this node
-h, --help
help for mark-control-plane
--node-name string
Specify the node name.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to connect a node to the cluster
- [kubeadm reset](#) to revert any changes made to this host by kubeadm init or kubeadm join
- [kubeadm alpha](#) to try experimental functionality

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---



[Create an Issue](#) [Edit This Page](#)

Page last modified on September 07, 2019 at 1:35 AM PST by [kubeadm: update reference documentation for 1.16 \(#16014\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm reset phase

- - [kubeadm reset phase](#)
  - [kubeadm reset phase preflight](#)
  - [kubeadm reset phase update-cluster-status](#)
  - [kubeadm reset phase remove-etcd-member](#)
  - [kubeadm reset phase cleanup-node](#)
  - [What's next](#)

`kubeadm reset phase` enables you to invoke atomic steps of the node reset process. Hence, you can let `kubeadm` do some of the work and you can fill in the gaps if you wish to apply customization.

`kubeadm reset phase` is consistent with the [kubeadm reset workflow](#), and behind the scene both use the same code.

## kubeadm reset phase

- [phase](#)

### Synopsis

Use this command to invoke single phase of the reset workflow

### Options

-h, --help
help for phase

### Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm reset phase preflight

Using this phase you can execute preflight checks on a node that is being reset.

- [preflight](#)

### Synopsis

Run pre-flight checks for `kubeadm reset`.

```
kubeadm reset phase preflight [flags]
```

### Options

-f, --force
Reset the node without prompting for confirmation.
-h, --help
help for preflight
--ignore-preflight-errors stringSlice
A list of checks whose errors will be shown as warnings. Example: 'IsPrivilegedUser,Swap'. Value 'all' ignores errors from all checks.

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm reset phase update-cluster-status

Using this phase you can remove this control-plane node from the ClusterStatus object.

- [update-cluster-status](#)

### Synopsis

Remove this node from the ClusterStatus object if the node is a control plane node.

```
kubeadm reset phase update-cluster-status [flags]
```

### Options

-h, --help
help for update-cluster-status

## Options inherited from parent commands

--rootfs string
[EXPERIMENTAL] The path to the 'real' host root filesystem.

## kubeadm reset phase remove-etcd-member

Using this phase you can remove this control-plane node's etcd member from the etcd cluster.

- [remove-etcd-member](#)

### Synopsis

Remove a local etcd member for a control plane node.

```
kubeadm reset phase remove-etcd-member [flags]
```

### Options

-h, --help
help for remove-etcd-member
--kubeconfig string Default: "/etc/kubernetes/admin.conf"

The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--

## Options inherited from parent commands

--rootfs string
-----------------

[EXPERIMENTAL] The path to the 'real' host root filesystem.
---

## kubeadm reset phase cleanup-node

Using this phase you can perform cleanup on this node.

- [cleanup-node](#)

## Synopsis

Run cleanup node.

```
kubeadm reset phase cleanup-node [flags]
```

## Options

--cert-dir string	Default: "/etc/kubernetes/pki"
-------------------	--------------------------------

The path to the directory where the certificates are stored. If specified, clean this directory.
--

--cri-socket string
---------------------

Path to the CRI socket to connect. If empty kubeadm will try to auto-detect this value; use this option only if you have more than one CRI installed or if you have non-standard CRI socket.
--

-h, --help
------------

help for cleanup-node
-----------------------

## Options inherited from parent commands

--rootfs string
-----------------

[EXPERIMENTAL] The path to the 'real' host root filesystem.
---

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to connect a node to the cluster
- [kubeadm reset](#) to revert any changes made to this host by kubeadm init or kubeadm join
- [kubeadm alpha](#) to try experimental functionality

# Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on September 07, 2019 at 1:35 AM PST by [kubeadm: update reference documentation for 1.16 \(#16014\)](#) ([Page History](#))

[Edit This Page](#)

# kubeadm upgrade phase

- [kubeadm upgrade node phase](#)
- [What's next](#)

In v1.15.0, kubeadm introduced preliminary support for `kubeadm upgrade node` phases. Phases for other `kubeadm upgrade` sub-commands such as `apply`, could be added in the following releases.

## kubeadm upgrade node phase

Using this phase you can choose to execute the separate steps of the upgrade of secondary control-plane or worker nodes. Please note that `kubeadm upgrade apply` still has to be called on a primary control-plane node.

- [phase](#)
- [control-plane](#)
- [kubelet-config](#)

### Synopsis

Use this command to invoke single phase of the node workflow

### Options

<code>-h, --help</code>
<code>help for phase</code>

### Options inherited from parent commands

<code>--rootfs string</code>
<code>[EXPERIMENTAL]</code> The path to the 'real' host root filesystem.

### Synopsis

Upgrade the control plane instance deployed on this node, if any

```
kubeadm upgrade node phase control-plane [flags]
```

### Options

<code>--certificate-renewal</code> Default: true
Perform the renewal of certificates used by component changed during upgrades.
<code>--dry-run</code>
Do not change any state, just output the actions that would be performed.
<code>--etcd-upgrade</code> Default: true

	Perform the upgrade of etcd.
-k, --experimental-kustomize string	
	The path where kustomize patches for static pod manifests are stored.
-h, --help	
	help for control-plane
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## Synopsis

Download the kubelet configuration from a ConfigMap of the form "kubelet-config-1.X" in the cluster, where X is the minor version of the kubelet. kubeadm uses the KubernetesVersion field in the kubeadm-config ConfigMap to determine what the *desired* kubelet version is, but the user can override this by using the -kubelet-version parameter.

```
kubeadm upgrade node phase kubelet-config [flags]
```

## Options

--dry-run	
	Do not change any state, just output the actions that would be performed.
-h, --help	
	help for kubelet-config
--kubeconfig string	Default: "/etc/kubernetes/admin.conf"
	The kubeconfig file to use when talking to the cluster. If the flag is not set, a set of standard locations can be searched for an existing kubeconfig file.
--kubelet-version string	
	The <i>desired</i> version for the kubelet config after the upgrade. If not specified, the KubernetesVersion from the kubeadm-config ConfigMap will be used

## Options inherited from parent commands

--rootfs string	
	[EXPERIMENTAL] The path to the 'real' host root filesystem.

## What's next

- [kubeadm init](#) to bootstrap a Kubernetes control-plane node
- [kubeadm join](#) to connect a node to the cluster
- [kubeadm reset](#) to revert any changes made to this host by kubeadm init or kubeadm join
- [kubeadm upgrade](#) to upgrade a kubeadm node
- [kubeadm alpha](#) to try experimental functionality

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---



[Create an Issue](#) [Edit This Page](#)

Page last modified on June 11, 2019 at 4:56 AM PST by [kubeadm: update the reference documentation for 1.15 \(#14596\)](#) ([Page History](#))

[Edit This Page](#)

# Implementation details

**FEATURE STATE:** Kubernetes v1.10 [stable](#)

This feature is *stable*, meaning:

[Edit This Page](#)

# Feature Gates

This page contains an overview of the various feature gates an administrator can specify on different Kubernetes components.

See [feature stages](#) for an explanation of the stages for a feature.

- [Overview](#)
- [Using a feature](#)
- [List of feature gates](#)
- [What's next](#)

## Overview

Feature gates are a set of key=value pairs that describe Kubernetes features. You can turn these features on or off using the `--feature-gates` command line flag on each Kubernetes component.

Each Kubernetes component lets you enable or disable a set of feature gates that are relevant to that component. Use `-h` flag to see a full set of feature gates for all components. To set feature gates for a component, such as kubelet, use the `--feature-gates` flag assigned to a list of feature pairs:

```
--feature-gates="...,DynamicKubeletConfig=true"
```

The following tables are a summary of the feature gates that you can set on different Kubernetes components.

- The "Since" column contains the Kubernetes release when a feature is introduced or its release stage is changed.
- The "Until" column, if not empty, contains the last Kubernetes release in which you can still use a feature gate.
- If a feature is in the Alpha or Beta state, you can find the feature listed in the [Alpha/Beta feature gate table](#).
- If a feature is stable you can find all stages for that feature listed in the [Graduated/Deprecated feature gate table](#).
- The [Graduated/Deprecated feature gate table](#) also lists deprecated and withdrawn features.

## Feature gates for Alpha or Beta features

Feature	Default	Stage	Since	Until
APIListChunking	false	Alpha	1.8	1.8
APIListChunking	true	Beta	1.9	
APIPriorityAndFairness	false	Alpha	1.17	
APIResponseCompression	false	Alpha	1.7	
AppArmor	true	Beta	1.4	
BalanceAttachedNodeVolumes	false	Alpha	1.11	
BlockVolume	false	Alpha	1.9	1.12

Feature	Default	Stage	Since	Until
BlockVolume	true	Beta	1.13	-
BoundServiceAccountTokenVolume	false	Alpha	1.13	
CPUManager	false	Alpha	1.8	1.9
CPUManager	true	Beta	1.10	
CRIOContainerLogRotation	false	Alpha	1.10	1.10
CRIOContainerLogRotation	true	Beta	1.11	
CSIBlockVolume	false	Alpha	1.11	1.13
CSIBlockVolume	true	Beta	1.14	
CSIDriverRegistry	false	Alpha	1.12	1.13
CSIDriverRegistry	true	Beta	1.14	
CSIInlineVolume	false	Alpha	1.15	1.15
CSIInlineVolume	true	Beta	1.16	-
CSIMigration	false	Alpha	1.14	1.16
CSIMigration	true	Beta	1.17	
CSIMigrationAWS	false	Alpha	1.14	
CSIMigrationAWS	false	Beta	1.17	
CSIMigrationAWSComplete	false	Alpha	1.17	
CSIMigrationAzureDisk	false	Alpha	1.15	
CSIMigrationAzureDiskComplete	false	Alpha	1.17	
CSIMigrationAzureFile	false	Alpha	1.15	
CSIMigrationAzureFileComplete	false	Alpha	1.17	
CSIMigrationGCE	false	Alpha	1.14	1.16
CSIMigrationGCE	false	Beta	1.17	
CSIMigrationGCEComplete	false	Alpha	1.17	
CSIMigrationOpenStack	false	Alpha	1.14	
CSIMigrationOpenStackComplete	false	Alpha	1.17	
CustomCPUCFSQuotaPeriod	false	Alpha	1.12	
CustomResourceDefaulting	false	Alpha	1.15	1.15
CustomResourceDefaulting	true	Beta	1.16	
DevicePlugins	false	Alpha	1.8	1.9
DevicePlugins	true	Beta	1.10	
DryRun	false	Alpha	1.12	1.12
DryRun	true	Beta	1.13	
DynamicAuditing	false	Alpha	1.13	
DynamicKubeletConfig	false	Alpha	1.4	1.10
DynamicKubeletConfig	true	Beta	1.11	
EndpointSlice	false	Alpha	1.16	1.16
EndpointSlice	false	Beta	1.17	
EphemeralContainers	false	Alpha	1.16	
ExpandCSIVolumes	false	Alpha	1.14	1.15
ExpandCSIVolumes	true	Beta	1.16	
ExpandInUsePersistentVolumes	false	Alpha	1.11	1.14
ExpandInUsePersistentVolumes	true	Beta	1.15	

Feature	Default	Stage	Since	Until
ExpandPersistentVolumes	false	Alpha	1.8	1.10
ExpandPersistentVolumes	true	Beta	1.11	
ExperimentalHostUserNamespaceDefaulting	false	Beta	1.5	
EvenPodsSpread	false	Alpha	1.16	
HPAScaleToZero	false	Alpha	1.16	
HyperVContainer	false	Alpha	1.10	
KubeletPodResources	false	Alpha	1.13	1.14
KubeletPodResources	true	Beta	1.15	
LegacyNodeRoleBehavior	true	Alpha	1.16	
LocalStorageCapacityIsolation	false	Alpha	1.7	1.9
LocalStorageCapacityIsolation	true	Beta	1.10	
LocalStorageCapacityIsolationFSQuotaMonitoring	false	Alpha	1.15	
MountContainers	false	Alpha	1.9	
NodeDisruptionExclusion	false	Alpha	1.16	
NonPreemptingPriority	false	Alpha	1.15	
PodOverhead	false	Alpha	1.16	-
ProcMountType	false	Alpha	1.12	
QOSReserved	false	Alpha	1.11	
RemainingItemCount	false	Alpha	1.15	
ResourceLimitsPriorityFunction	false	Alpha	1.9	
RotateKubeletClientCertificate	true	Beta	1.8	
RotateKubeletServerCertificate	false	Alpha	1.7	1.11
RotateKubeletServerCertificate	true	Beta	1.12	
RunAsGroup	true	Beta	1.14	
RuntimeClass	false	Alpha	1.12	1.13
RuntimeClass	true	Beta	1.14	
SCTPSupport	false	Alpha	1.12	
ServerSideApply	false	Alpha	1.14	1.15
ServerSideApply	true	Beta	1.16	
ServiceNodeExclusion	false	Alpha	1.8	
StartupProbe	false	Alpha	1.16	
StorageVersionHash	false	Alpha	1.14	1.14
StorageVersionHash	true	Beta	1.15	
StreamingProxyRedirects	false	Beta	1.5	1.5
StreamingProxyRedirects	true	Beta	1.6	
SupportNodePidsLimit	false	Alpha	1.14	1.14
SupportNodePidsLimit	true	Beta	1.15	
SupportPodPidsLimit	false	Alpha	1.10	1.13
SupportPodPidsLimit	true	Beta	1.14	
Sysctls	true	Beta	1.11	
TaintBasedEvictions	false	Alpha	1.6	1.12
TaintBasedEvictions	true	Beta	1.13	
TokenRequest	false	Alpha	1.10	1.11

<b>Feature</b>	<b>Default</b>	<b>Stage</b>	<b>Since</b>	<b>Until</b>
TokenRequest	true	Beta	1.12	
TokenRequestProjection	false	Alpha	1.11	1.11
TokenRequestProjection	true	Beta	1.12	
TTLAfterFinished	false	Alpha	1.12	
TopologyManager	false	Alpha	1.16	
ValidateProxyRedirects	false	Alpha	1.12	1.13
ValidateProxyRedirects	true	Beta	1.14	
VolumePVCDDataSource	false	Alpha	1.15	1.15
VolumePVCDDataSource	true	Beta	1.16	
VolumeSnapshotDataSource	false	Alpha	1.12	1.16
VolumeSnapshotDataSource	true	Beta	1.17	-
WindowsGMSA	false	Alpha	1.14	
WindowsGMSA	true	Beta	1.16	
WinDSR	false	Alpha	1.14	
WinOverlay	false	Alpha	1.14	

## Feature gates for graduated or deprecated features

<b>Feature</b>	<b>Default</b>	<b>Stage</b>	<b>Since</b>	<b>Until</b>
Accelerators	false	Alpha	1.6	1.10
Accelerators	-	Deprecated	1.11	-
AdvancedAuditing	false	Alpha	1.7	1.7
AdvancedAuditing	true	Beta	1.8	1.11
AdvancedAuditing	true	GA	1.12	-
AffinityInAnnotations	false	Alpha	1.6	1.7
AffinityInAnnotations	-	Deprecated	1.8	-
AllowExtTrafficLocalEndpoints	false	Beta	1.4	1.6
AllowExtTrafficLocalEndpoints	true	GA	1.7	-
CSINodeInfo	false	Alpha	1.12	1.13
CSINodeInfo	true	Beta	1.14	1.16
CSINodeInfo	true	GA	1.17	
AttachVolumeLimit	false	Alpha	1.11	1.11
AttachVolumeLimit	true	Beta	1.12	1.16
AttachVolumeLimit	true	GA	1.17	-
CSIPersistentVolume	false	Alpha	1.9	1.9
CSIPersistentVolume	true	Beta	1.10	1.12
CSIPersistentVolume	true	GA	1.13	-
CustomPodDNS	false	Alpha	1.9	1.9
CustomPodDNS	true	Beta	1.10	1.13
CustomPodDNS	true	GA	1.14	-
CustomResourcePublishOpenAPI	false	Alpha	1.14	1.14
CustomResourcePublishOpenAPI	true	Beta	1.15	1.15
CustomResourcePublishOpenAPI	true	GA	1.16	-
CustomResourceSubresources	false	Alpha	1.10	1.10

Feature	Default	Stage	Since	Until
CustomResourceSubresources	true	Beta	1.11	1.15
CustomResourceSubresources	true	GA	1.16	-
CustomResourceValidation	false	Alpha	1.8	1.8
CustomResourceValidation	true	Beta	1.9	1.15
CustomResourceValidation	true	GA	1.16	-
CustomResourceWebhookConversion	false	Alpha	1.13	1.14
CustomResourceWebhookConversion	true	Beta	1.15	1.15
CustomResourceWebhookConversion	true	GA	1.16	-
DynamicProvisioningScheduling	false	Alpha	1.11	1.11
DynamicProvisioningScheduling	-	Deprecated	1.12	-
DynamicVolumeProvisioning	true	Alpha	1.3	1.7
DynamicVolumeProvisioning	true	GA	1.8	-
EnableEquivalenceClassCache	false	Alpha	1.8	1.14
EnableEquivalenceClassCache	-	Deprecated	1.15	-
ExperimentalCriticalPodAnnotation	false	Alpha	1.5	1.12
ExperimentalCriticalPodAnnotation	false	Deprecated	1.13	-
GCERegionalPersistentDisk	true	Beta	1.10	1.12
GCERegionalPersistentDisk	true	GA	1.13	-
HugePages	false	Alpha	1.8	1.9
HugePages	true	Beta	1.10	1.13
HugePages	true	GA	1.14	-
Initializers	false	Alpha	1.7	1.13
Initializers	-	Deprecated	1.14	-
KubeletConfigFile	false	Alpha	1.8	1.9
KubeletConfigFile	-	Deprecated	1.10	-
KubeletPluginsWatcher	false	Alpha	1.11	1.11
KubeletPluginsWatcher	true	Beta	1.12	1.12
KubeletPluginsWatcher	true	GA	1.13	-
MountPropagation	false	Alpha	1.8	1.9
MountPropagation	true	Beta	1.10	1.11
MountPropagation	true	GA	1.12	-
NodeLease	false	Alpha	1.12	1.13
NodeLease	true	Beta	1.14	1.16
NodeLease	true	GA	1.17	-
PersistentLocalVolumes	false	Alpha	1.7	1.9
PersistentLocalVolumes	true	Beta	1.10	1.13
PersistentLocalVolumes	true	GA	1.14	-
PodPriority	false	Alpha	1.8	1.10
PodPriority	true	Beta	1.11	1.13
PodPriority	true	GA	1.14	-
PodReadinessGates	false	Alpha	1.11	1.11
PodReadinessGates	true	Beta	1.12	1.13
PodReadinessGates	true	GA	1.14	-

Feature	Default	Stage	Since	Until
PodShareProcessNamespace	false	Alpha	1.10	1.11
PodShareProcessNamespace	true	Beta	1.12	1.16
PodShareProcessNamespace	true	GA	1.17	-
PVCProtection	false	Alpha	1.9	1.9
PVCProtection	-	Deprecated	1.10	-
RequestManagement	false	Alpha	1.15	1.16
ResourceQuotaScopeSelectors	false	Alpha	1.11	1.11
ResourceQuotaScopeSelectors	true	Beta	1.12	1.16
ResourceQuotaScopeSelectors	true	GA	1.17	-
ScheduleDaemonSetPods	false	Alpha	1.11	1.11
ScheduleDaemonSetPods	true	Beta	1.12	1.16
ScheduleDaemonSetPods	true	GA	1.17	-
ServiceLoadBalancerFinalizer	false	Alpha	1.15	1.15
ServiceLoadBalancerFinalizer	true	Beta	1.16	1.16
ServiceLoadBalancerFinalizer	true	GA	1.17	-
StorageObjectInUseProtection	true	Beta	1.10	1.10
StorageObjectInUseProtection	true	GA	1.11	-
SupportIPVSProxyMode	false	Alpha	1.8	1.8
SupportIPVSProxyMode	false	Beta	1.9	1.9
SupportIPVSProxyMode	true	Beta	1.10	1.10
SupportIPVSProxyMode	true	GA	1.11	-
TaintNodesByCondition	false	Alpha	1.8	1.11
TaintNodesByCondition	true	Beta	1.12	1.16
TaintNodesByCondition	true	GA	1.17	-
VolumeScheduling	false	Alpha	1.9	1.9
VolumeScheduling	true	Beta	1.10	1.12
VolumeScheduling	true	GA	1.13	-
VolumeSubpath	true	GA	1.13	-
VolumeSubpathEnvExpansion	false	Alpha	1.14	1.14
VolumeSubpathEnvExpansion	true	Beta	1.15	1.16
VolumeSubpathEnvExpansion	true	GA	1.17	-
WatchBookmark	false	Alpha	1.15	1.15
WatchBookmark	true	Beta	1.16	1.16
WatchBookmark	true	GA	1.17	-

## Using a feature

### Feature stages

A feature can be in *Alpha*, *Beta* or *GA* stage. An *Alpha* feature means:

- Disabled by default.
- Might be buggy. Enabling the feature may expose bugs.
- Support for feature may be dropped at any time without notice.

- The API may change in incompatible ways in a later software release without notice.
- Recommended for use only in short-lived testing clusters, due to increased risk of bugs and lack of long-term support.

A *Beta* feature means:

- Enabled by default.
- The feature is well tested. Enabling the feature is considered safe.
- Support for the overall feature will not be dropped, though details may change.
- The schema and/or semantics of objects may change in incompatible ways in a subsequent beta or stable release. When this happens, we will provide instructions for migrating to the next version. This may require deleting, editing, and re-creating API objects. The editing process may require some thought. This may require downtime for applications that rely on the feature.
- Recommended for only non-business-critical uses because of potential for incompatible changes in subsequent releases. If you have multiple clusters that can be upgraded independently, you may be able to relax this restriction.

**Note:** Please do try *Beta* features and give feedback on them! After they exit beta, it may not be practical for us to make more changes.

A *General Availability* (GA) feature is also referred to as a *stable* feature. It means:

- The feature is always enabled; you cannot disable it.
- The corresponding feature gate is no longer needed.
- Stable versions of features will appear in released software for many subsequent versions.

## List of feature gates

Each feature gate is designed for enabling/disabling a specific feature:

- `Accelerators`: Enable Nvidia GPU support when using Docker
- `AdvancedAuditing`: Enable [advanced auditing](#)
- `AffinityInAnnotations(deprecated)`: Enable setting [Pod affinity or anti-affinity](#).
- `AllowExtTrafficLocalEndpoints`: Enable a service to route external requests to node local endpoints.
- `APIListChunking`: Enable the API clients to retrieve (LIST or GET) resources from API server in chunks.
- `APIPriorityAndFairness`: Enable managing request concurrency with prioritization and fairness at each server. (Renamed from RequestManagement)
- `APIResponseCompression`: Compress the API responses for LIST or GET requests.



- **AppArmor:** Enable AppArmor based mandatory access control on Linux nodes when using Docker. See [AppArmor Tutorial](#) for more details.
- **AttachVolumeLimit:** Enable volume plugins to report limits on number of volumes that can be attached to a node. See [dynamic volume limits](#) for more details.
- **BalanceAttachedNodeVolumes:** Include volume count on node to be considered for balanced resource allocation while scheduling. A node which has closer CPU, memory utilization, and volume count is favored by the scheduler while making decisions.
- **BlockVolume:** Enable the definition and consumption of raw block devices in Pods. See [Raw Block Volume Support](#) for more details.
- **BoundServiceAccountTokenVolume:** Migrate ServiceAccount volumes to use a projected volume consisting of a ServiceAccountTokenVolumeProjection. Check [Service Account Token Volumes](#) for more details.
- **CPUManager:** Enable container level CPU affinity support, see [CPU Management Policies](#).
- **CRIOContainerLogRotation:** Enable container log rotation for cri container runtime.
- **CSIBlockVolume:** Enable external CSI volume drivers to support block storage. See the [csi raw block volume support](#) documentation for more details.
- **CSIDriverRegistry:** Enable all logic related to the CSIDriver API object in csi.storage.k8s.io.
- **CSIInlineVolume:** Enable CSI Inline volumes support for pods.
- **CSIMigration:** Enables shims and translation logic to route volume operations from in-tree plugins to corresponding pre-installed CSI plugins
- **CSIMigrationAWS:** Enables shims and translation logic to route volume operations from the AWS-EBS in-tree plugin to EBS CSI plugin. Supports falling back to in-tree EBS plugin if a node does not have EBS CSI plugin installed and configured. Requires CSIMigration feature flag enabled.
- **CSIMigrationAWSComplete:** Stops registering the EBS in-tree plugin in kubelet and volume controllers and enables shims and translation logic to route volume operations from the AWS-EBS in-tree plugin to EBS CSI plugin. Requires CSIMigration and CSIMigrationAWS feature flags enabled and EBS CSI plugin installed and configured on all nodes in the cluster.
- **CSIMigrationAzureDisk:** Enables shims and translation logic to route volume operations from the Azure-Disk in-tree plugin to AzureDisk CSI plugin. Supports falling back to in-tree AzureDisk plugin if a node does not have AzureDisk CSI plugin installed and configured. Requires CSIMigration feature flag enabled.
- **CSIMigrationAzureDiskComplete:** Stops registering the Azure-Disk in-tree plugin in kubelet and volume controllers and enables shims and translation logic to route volume operations from the Azure-Disk in-tree plugin to AzureDisk CSI plugin. Requires CSIMigration and CSIMigrationAzureDisk feature flags enabled and AzureDisk CSI plugin installed and configured on all nodes in the cluster.
- **CSIMigrationAzureFile:** Enables shims and translation logic to route volume operations from the Azure-File in-tree plugin to AzureFile CSI

plugin. Supports falling back to in-tree AzureFile plugin if a node does not have AzureFile CSI plugin installed and configured. Requires CSIMigration feature flag enabled.

- CSIMigrationAzureFileComplete: Stops registering the Azure-File in-tree plugin in kubelet and volume controllers and enables shims and translation logic to route volume operations from the Azure-File in-tree plugin to AzureFile CSI plugin. Requires CSIMigration and CSIMigrationAzureFile feature flags enabled and AzureFile CSI plugin installed and configured on all nodes in the cluster.
- CSIMigrationGCE: Enables shims and translation logic to route volume operations from the GCE-PD in-tree plugin to PD CSI plugin. Supports falling back to in-tree GCE plugin if a node does not have PD CSI plugin installed and configured. Requires CSIMigration feature flag enabled.
- CSIMigrationGCEComplete: Stops registering the GCE-PD in-tree plugin in kubelet and volume controllers and enables shims and translation logic to route volume operations from the GCE-PD in-tree plugin to PD CSI plugin. Requires CSIMigration and CSIMigrationGCE feature flags enabled and PD CSI plugin installed and configured on all nodes in the cluster.
- CSIMigrationOpenStack: Enables shims and translation logic to route volume operations from the Cinder in-tree plugin to Cinder CSI plugin. Supports falling back to in-tree Cinder plugin if a node does not have Cinder CSI plugin installed and configured. Requires CSIMigration feature flag enabled.
- CSIMigrationOpenStackComplete: Stops registering the Cinder in-tree plugin in kubelet and volume controllers and enables shims and translation logic to route volume operations from the Cinder in-tree plugin to Cinder CSI plugin. Requires CSIMigration and CSIMigrationOpenStack feature flags enabled and Cinder CSI plugin installed and configured on all nodes in the cluster.
- CSINodeInfo: Enable all logic related to the CSINodeInfo API object in `csi.storage.k8s.io`.
- CSIPersistentVolume: Enable discovering and mounting volumes provisioned through a [CSI \(Container Storage Interface\)](#) compatible volume plugin. Check the [csi volume type](#) documentation for more details.
- CustomCPUCFSQuotaPeriod: Enable nodes to change CPUCFSQuotaPeriod.
- CustomPodDNS: Enable customizing the DNS settings for a Pod using its `dnsConfig` property. Check [Pod's DNS Config](#) for more details.
- CustomResourceDefaulting: Enable CRD support for default values in OpenAPI v3 validation schemas.
- CustomResourcePublishOpenAPI: Enables publishing of CRD OpenAPI specs.
- CustomResourceSubresources: Enable `/status` and `/scale` subresources on resources created from [CustomResourceDefinition](#).
- CustomResourceValidation: Enable schema based validation on resources created from [CustomResourceDefinition](#).
- CustomResourceWebhookConversion: Enable webhook-based conversion on resources created from [CustomResourceDefinition](#).  
troubleshoot a running Pod.

- DevicePlugins: Enable the [device-plugins](#) based resource provisioning on nodes.
- DryRun: Enable server-side [dry run](#) requests so that validation, merging, and mutation can be tested without committing.
- DynamicAuditing: Enable [dynamic auditing](#)
- DynamicKubeletConfig: Enable the dynamic configuration of kubelet. See [Reconfigure kubelet](#).
- DynamicProvisioningScheduling: Extend the default scheduler to be aware of volume topology and handle PV provisioning. This feature is superseded by the VolumeScheduling feature completely in v1.12.
- DynamicVolumeProvisioning(*deprecated*): Enable the [dynamic provisioning](#) of persistent volumes to Pods.
- EnableAggregatedDiscoveryTimeout (*deprecated*): Enable the five second timeout on aggregated discovery calls.
- EnableEquivalenceClassCache: Enable the scheduler to cache equivalence of nodes when scheduling Pods.
- EphemeralContainers: Enable the ability to add [ephemeral containersA type of container type that you can temporarily run inside a Pod](#) to running pods.
- EvenPodsSpread: Enable pods to be scheduled evenly across topology domains. See [Pod Topology Spread Constraints](#).
- ExpandInUsePersistentVolumes: Enable expanding in-use PVCs. See [Resizing an in-use PersistentVolumeClaim](#).
- ExpandPersistentVolumes: Enable the expanding of persistent volumes. See [Expanding Persistent Volumes Claims](#).
- ExperimentalCriticalPodAnnotation: Enable annotating specific pods as *critical* so that their [scheduling is guaranteed](#). This feature is deprecated by Pod Priority and Preemption as of v1.13.
- ExperimentalHostUserNamespaceDefaultingGate: Enabling the defaulting user namespace to host. This is for containers that are using other host namespaces, host mounts, or containers that are privileged or using specific non-namespaced capabilities (e.g. MKNODE, SYS\_MODULE etc.). This should only be enabled if user namespace remapping is enabled in the Docker daemon.
- EndpointSlice: Enables Endpoint Slices for more scalable and extensible network endpoints. Requires corresponding API and Controller to be enabled. See [Enabling Endpoint Slices](#).
- GCERegionalPersistentDisk: Enable the regional PD feature on GCE.
- HugePages: Enable the allocation and consumption of pre-allocated [huge pages](#).
- HyperVContainer: Enable [Hyper-V isolation](#) for Windows containers.
- HPAScaleToZero: Enables setting minReplicas to 0 for HorizontalPodAutoscaler resources when using custom or external metrics.
- KubeletConfigFile: Enable loading kubelet configuration from a file specified using a config file. See [setting kubelet parameters via a config file](#) for more details.
- KubeletPluginsWatcher: Enable probe-based plugin watcher utility to enable kubelet to discover plugins such as [CSI volume drivers](#).
- KubeletPodResources: Enable the kubelet's pod resources grpc endpoint. See [Support Device Monitoring](#) for more details.
- LegacyNodeRoleBehavior: When disabled, legacy behavior in service load balancers and node disruption will ignore the node -

role.kubernetes.io/master label in favor of the feature-specific labels.

- LocalStorageCapacityIsolation: Enable the consumption of [local ephemeral storage](#) and also the sizeLimit property of an [emptyDir volume](#).
- LocalStorageCapacityIsolationFSQuotaMonitoring: When LocalStorageCapacityIsolation is enabled for [local ephemeral storage](#) and the backing filesystem for [emptyDir volumes](#) supports project quotas and they are enabled, use project quotas to monitor [emptyDir volume](#) storage consumption rather than filesystem walk for better performance and accuracy.
- MountContainers: Enable using utility containers on host as the volume mounter.
- MountPropagation: Enable sharing volume mounted by one container to other containers or pods. For more details, please see [mount propagation](#).
- NodeDisruptionExclusion: Enable use of the node label node.kubernetes.io/exclude-disruption which prevents nodes from being evacuated during zone failures.
- NodeLease: Enable the new Lease API to report node heartbeats, which could be used as a node health signal.
- NonPreemptingPriority: Enable NonPreempting option for PriorityClass and Pod.
- PersistentLocalVolumes: Enable the usage of local volume type in Pods. Pod affinity has to be specified if requesting a local volume.
- PodOverhead: Enable the [PodOverhead](#) feature to account for pod overheads.
- PodPriority: Enable the descheduling and preemption of Pods based on their [priorities](#).
- PodReadinessGates: Enable the setting of PodReadinessGate field for extending Pod readiness evaluation. See [Pod readiness gate](#) for more details.
- PodShareProcessNamespace: Enable the setting of shareProcessNamespace in a Pod for sharing a single process namespace between containers running in a pod. More details can be found in [Share Process Namespace between Containers in a Pod](#).
- ProcMountType: Enables control over ProcMountType for containers.
- PVCProtection: Enable the prevention of a PersistentVolumeClaim (PVC) from being deleted when it is still used by any Pod.
- QOSReserved: Allows resource reservations at the QoS level preventing pods at lower QoS levels from bursting into resources requested at higher QoS levels (memory only for now).
- ResourceLimitsPriorityFunction: Enable a scheduler priority function that assigns a lowest possible score of 1 to a node that satisfies at least one of the input Pod's cpu and memory limits. The intent is to break ties between nodes with same scores.
- ResourceQuotaScopeSelectors: Enable resource quota scope selectors.
- RotateKubeletClientCertificate: Enable the rotation of the client TLS certificate on the kubelet. See [kubelet configuration](#) for more details.

- **RotateKubeletServerCertificate:** Enable the rotation of the server TLS certificate on the kubelet. See [kubelet configuration](#) for more details.
- **RunAsGroup:** Enable control over the primary group ID set on the init processes of containers.
- **RuntimeClass:** Enable the [RuntimeClass](#) feature for selecting container runtime configurations.
- **ScheduleDaemonSetPods:** Enable DaemonSet Pods to be scheduled by the default scheduler instead of the DaemonSet controller.
- **SCTPSupport:** Enables the usage of SCTP as protocol value in Service, Endpoint, NetworkPolicy and Pod definitions
- **ServerSideApply:** Enables the [Sever Side Apply \(SSA\)](#) path at the API Server.
- **ServiceLoadBalancerFinalizer:** Enable finalizer protection for Service load balancers.
- **ServiceNodeExclusion:** Enable the exclusion of nodes from load balancers created by a cloud provider. A node is eligible for exclusion if labelled with "alpha.service-controller.kubernetes.io/exclude-balancer" key or node.kubernetes.io/exclude-from-external-load-balancers.
- **StartupProbe:** Enable the [startup](#) probe in the kubelet.
- **StorageObjectInUseProtection:** Postpone the deletion of PersistentVolume or PersistentVolumeClaim objects if they are still being used.
- **StorageVersionHash:** Allow apiservers to expose the storage version hash in the discovery.
- **StreamingProxyRedirects:** Instructs the API server to intercept (and follow) redirects from the backend (kubelet) for streaming requests. Examples of streaming requests include the exec, attach and port-forward requests.
- **SupportIPVSProxyMode:** Enable providing in-cluster service load balancing using IPVS. See [service proxies](#) for more details.
- **SupportPodPidsLimit:** Enable the support to limiting PIDs in Pods.
- **Sysctls:** Enable support for namespaced kernel parameters (sysctls) that can be set for each pod. See [sysctls](#) for more details.
- **TaintBasedEvictions:** Enable evicting pods from nodes based on taints on nodes and tolerations on Pods. See [taints and tolerations](#) for more details.
- **TaintNodesByCondition:** Enable automatic tainting nodes based on [node conditions](#).
- **TokenRequest:** Enable the TokenRequest endpoint on service account resources.
- **TokenRequestProjection:** Enable the injection of service account tokens into a Pod through the [projected volume](#).
- **TopologyManager:** Enable a mechanism to coordinate fine-grained hardware resource assignments for different components in Kubernetes. See [Control Topology Management Policies on a node](#).
- **TTLAfterFinished:** Allow a [TTL controller](#) to clean up resources after they finish execution.
- **VolumePVCDataSource:** Enable support for specifying an existing PVC as a DataSource.



- **VolumeScheduling:** Enable volume topology aware scheduling and make the PersistentVolumeClaim (PVC) binding aware of scheduling decisions. It also enables the usage of [local](#) volume type when used together with the PersistentLocalVolumes feature gate.
- **VolumeSnapshotDataSource:** Enable volume snapshot data source support.
- **VolumeSubpathEnvExpansion:** Enable subPathExpr field for expanding environment variables into a subPath.
- **WatchBookmark:** Enable support for watch bookmark events.
- **WindowsGMSA:** Enables passing of GMSA credential specs from pods to container runtimes.
- **WinDSR:** Allows kube-proxy to create DSR loadbalancers for Windows.
- **WinOverlay:** Allows kube-proxy to run in overlay mode for Windows.

## What's next

- The [deprecation policy](#) for Kubernetes explains the project's approach to removing features and components.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on February 19, 2020 at 9:13 PM PST by [Fix initial alpha version of ValidateProxyRedirects \(#19192\)](#) ([Page History](#))

[Edit This Page](#)

# cloud-controller-manager

- [Synopsis](#)
- [Options](#)

## Synopsis

The Cloud controller manager is a daemon that embeds the cloud specific control loops shipped with Kubernetes.

cloud-controller-manager [flags]

## Options

--add-dir-header	
	If true, adds the file directory to the header
--allocate-node-cidrs	
	Should CIDRs for Pods be allocated and set on the cloud provider.
--alsologtostderr	
	log to standard error as well as files
--authentication-kubeconfig string	
	kubeconfig file pointing at the 'core' kubernetes server with enough rights to create tokenaccessreviews.authentication.k8s.io. This is optional. If empty, all token requests are considered to be anonymous and no client CA is looked up in the cluster.
--authentication-skip-lookup	
	If false, the authentication-kubeconfig will be used to lookup missing authentication configuration from the cluster.
--authentication-token-webhook-cache-ttl duration	
	Default: 10s
	The duration to cache responses from the webhook token authenticator.
--authentication-tolerate-lookup-failure	
	If true, failures to look up missing authentication configuration from the cluster are not considered fatal. Note that this can result in authentication that treats all requests as anonymous.
--authorization-always-allow-paths stringSlice	
	Default: [/healthz]
	A list of HTTP paths to skip during authorization, i.e. these are authorized without contacting the 'core' kubernetes server.
--authorization-kubeconfig string	
	kubeconfig file pointing at the 'core' kubernetes server with enough rights to create subjectaccessreviews.authorization.k8s.io. This is optional. If empty, all requests not skipped by authorization are forbidden.
--authorization-webhook-cache-authorized-ttl duration	
	Default: 10s
	The duration to cache 'authorized' responses from the webhook authorizer.
--authorization-webhook-cache-unauthorized-ttl duration	
	Default: 10s
	The duration to cache 'unauthorized' responses from the webhook authorizer.
--azure-container-registry-config string	
	Path to the file containing Azure container registry configuration information.
--bind-address ip	
	Default: 0.0.0.0



	The IP address on which to listen for the --secure-port port. The associated interface(s) must be reachable by the rest of the cluster, and by CLI/web clients. If blank, all interfaces will be used (0.0.0.0 for all IPv4 interfaces and :: for all IPv6 interfaces).
--cert-dir string	
	The directory where the TLS certs are located. If --tls-cert-file and --tls-private-key-file are provided, this flag will be ignored.
--cidr-allocator-type stringÂ Â Â Â Â Default: "RangeAllocator"	
	Type of CIDR allocator to use
--client-ca-file string	
	If set, any request presenting a client certificate signed by one of the authorities in the client-ca-file is authenticated with an identity corresponding to the CommonName of the client certificate.
--cloud-config string	
	The path to the cloud provider configuration file. Empty string for no configuration file.
--cloud-provider string	
	The provider for cloud services. Empty string for no provider.
--cloud-provider-gce-l7lb-src-cidrs cidrsÂ Â Â Â Â Default: 130.211.0.0/22,35.191.0.0/16	
	CIDRs opened in GCE firewall for L7 LB traffic proxy & health checks
--cloud-provider-gce-lb-src-cidrs cidrsÂ Â Â Â Â Default: 130.211.0.0/22,209.85.152.0/22,209.85.204.0/22,35.191.0.0/16	
	CIDRs opened in GCE firewall for L4 LB traffic proxy & health checks
--cluster-cidr string	
	CIDR Range for Pods in cluster. Requires --allocate-node-cidrs to be true
--cluster-name stringÂ Â Â Â Â Default: "kubernetes"	
	The instance prefix for the cluster.
--concurrent-service-syncs int32Â Â Â Â Â Default: 1	
	The number of services that are allowed to sync concurrently. Larger number = more responsive service management, but more CPU (and network) load
--configure-cloud-routesÂ Â Â Â Â Default: true	
	Should CIDRs allocated by allocate-node-cidrs be configured on the cloud provider.
--contention-profiling	
	Enable lock contention profiling, if profiling is enabled
--controller-start-interval duration	
	Interval between starting controller managers.
--controllers stringSliceÂ Â Â Â Â Default: [*]	

	<p>A list of controllers to enable. '*' enables all on-by-default controllers, 'foo' enables the controller named 'foo', '-foo' disables the controller named 'foo'.</p> <p>All controllers: cloud-node, cloud-node-lifecycle, route, service</p> <p>Disabled-by-default controllers:</p>
	<p>--external-cloud-volume-plugin string</p>
	<p>The plugin to use when cloud provider is set to external. Can be empty, should only be set when cloud-provider is external. Currently used to allow node and volume controllers to work for in tree cloud providers.</p>
	<p>--feature-gates mapStringBool</p>

A set of key=value pairs that describe feature gates for alpha/experimental features. Options are:

APIListChunking=true|false (BETA - default=true)  
APIPriorityAndFairness=true|false (ALPHA - default=false)  
APIResponseCompression=true|false (BETA - default=true)  
AllAlpha=true|false (ALPHA - default=false)  
AllBeta=true|false (BETA - default=false)  
AllowInsecureBackendProxy=true|false (BETA - default=true)  
AppArmor=true|false (BETA - default=true)  
BalanceAttachedNodeVolumes=true|false (ALPHA - default=false)  
BlockVolume=true|false (BETA - default=true)  
BoundServiceAccountTokenVolume=true|false (ALPHA - default=false)  
CPUManager=true|false (BETA - default=true)  
CRIContainerLogRotation=true|false (BETA - default=true)  
CSIBlockVolume=true|false (BETA - default=true)  
CSIDriverRegistry=true|false (BETA - default=true)  
CSIInlineVolume=true|false (BETA - default=true)  
CSIMigration=true|false (BETA - default=true)  
CSIMigrationAWS=true|false (BETA - default=false)  
CSIMigrationAWSComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureDisk=true|false (ALPHA - default=false)  
CSIMigrationAzureDiskComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureFile=true|false (ALPHA - default=false)  
CSIMigrationAzureFileComplete=true|false (ALPHA - default=false)  
CSIMigrationGCE=true|false (BETA - default=false)  
CSIMigrationGCEComplete=true|false (ALPHA - default=false)  
CSIMigrationOpenStack=true|false (ALPHA - default=false)  
CSIMigrationOpenStackComplete=true|false (ALPHA - default=false)  
CustomCPUCFSQuotaPeriod=true|false (ALPHA - default=false)  
DevicePlugins=true|false (BETA - default=true)  
DryRun=true|false (BETA - default=true)  
DynamicAuditing=true|false (ALPHA - default=false)  
DynamicKubeletConfig=true|false (BETA - default=true)  
EndpointSlice=true|false (BETA - default=false)  
EphemeralContainers=true|false (ALPHA - default=false)  
EvenPodsSpread=true|false (ALPHA - default=false)  
ExpandCSIVolumes=true|false (BETA - default=true)  
ExpandInUsePersistentVolumes=true|false (BETA - default=true)  
ExpandPersistentVolumes=true|false (BETA - default=true)  
ExperimentalHostUserNamespaceDefaulting=true|false (BETA - default=false)  
HPAScaleToZero=true|false (ALPHA - default=false)  
HyperVContainer=true|false (ALPHA - default=false)  
IPv6DualStack=true|false (ALPHA - default=false)  
KubeletPodResources=true|false (BETA - default=true)  
LegacyNodeRoleBehavior=true|false (ALPHA - default=true)  
LocalStorageCapacityIsolation=true|false (BETA - default=true)  
LocalStorageCapacityIsolationFSQuotaMonitoring=true|false (ALPHA - default=false)  
NodeDisruptionExclusion=true|false (ALPHA - default=false)

-h, --help
help for cloud-controller-manager
--http2-max-streams-per-connection int
The limit that the server gives to clients for the maximum number of streams in an HTTP/2 connection. Zero means to use golang's default.
--kube-api-burst int32 Default: 30
Burst to use while talking with kubernetes apiserver.
--kube-api-content-type string Default: "application/vnd.kubernetes.protobuf"
Content type of requests sent to apiserver.
--kube-api-qps float32 Default: 20
QPS to use while talking with kubernetes apiserver.
--kubeconfig string
Path to kubeconfig file with authorization and master location information.
--leader-elect Default: true
Start a leader election client and gain leadership before executing the main loop. Enable this when running replicated components for high availability.
--leader-elect-lease-duration duration Default: 15s
The duration that non-leader candidates will wait after observing a leadership renewal until attempting to acquire leadership of a led but unrenewed leader slot. This is effectively the maximum duration that a leader can be stopped before it is replaced by another candidate. This is only applicable if leader election is enabled.
--leader-elect-renew-deadline duration Default: 10s
The interval between attempts by the acting master to renew a leadership slot before it stops leading. This must be less than or equal to the lease duration. This is only applicable if leader election is enabled.
--leader-elect-resource-lock endpoints Default: "endpointsleases"
The type of resource object that is used for locking during leader election. Supported options are endpoints (default) and `configmaps`.
--leader-elect-resource-name string Default: "cloud-controller-manager"
The name of resource object that is used for locking during leader election.
--leader-elect-resource-namespace string Default: "kube-system"
The namespace of resource object that is used for locking during leader election.
--leader-elect-retry-period duration Default: 2s
The duration the clients should wait between attempting acquisition and renewal of a leadership. This is only applicable if leader election is enabled.
--log-backtrace-at traceLocation Default: :0
when logging hits line file:N, emit a stack trace

<code>--log-dir</code> string	
	If non-empty, write log files in this directory
<code>--log-file</code> string	
	If non-empty, use this log file
<code>--log-file-max-size</code> uintââââ Default: 1800	
	Defines the maximum size a log file can grow to. Unit is megabytes. If the value is 0, the maximum file size is unlimited.
<code>--log-flush-frequency</code> durationââââ Default: 5s	
	Maximum number of seconds between log flushes
<code>--logtostderr</code> ââââ Default: true	
	log to standard error instead of files
<code>--master</code> string	
	The address of the Kubernetes API server (overrides any value in kubeconfig).
<code>--min-resync-period</code> durationââââ Default: 12h0m0s	
	The resync period in reflectors will be random between MinResyncPeriod and 2*MinResyncPeriod.
<code>--node-monitor-period</code> durationââââ Default: 5s	
	The period for syncing NodeStatus in NodeController.
<code>--node-status-update-frequency</code> durationââââ Default: 5m0s	
	Specifies how often the controller updates nodes' status.
<code>--profiling</code>	
	Enable profiling via web interface host:port/debug/pprof/
<code>--requestheader-allowed-names</code> stringSlice	
	List of client certificate common names to allow to provide usernames in headers specified by --requestheader-username-headers. If empty, any client certificate validated by the authorities in --requestheader-client-ca-file is allowed.
<code>--requestheader-client-ca-file</code> string	
	Root certificate bundle to use to verify client certificates on incoming requests before trusting usernames in headers specified by --requestheader-username-headers. WARNING: generally do not depend on authorization being already done for incoming requests.
<code>--requestheader-extra-headers-prefix</code> stringSliceââââ Default: [x-remote-extra-]	
	List of request header prefixes to inspect. X-Remote-Extra- is suggested.
<code>--requestheader-group-headers</code> stringSliceââââ Default: [x-remote-group]	
	List of request headers to inspect for groups. X-Remote-Group is suggested.
<code>--requestheader-username-headers</code> stringSliceââââ Default: [x-remote-user]	
	List of request headers to inspect for usernames. X-Remote-User is common.

<code>--route-reconciliation-period</code> durationÂ Â Â Â Â Default: 10s	
	The period for reconciling routes created for Nodes by cloud provider.
<code>--secure-port</code> intÂ Â Â Â Â Default: 10258	
	The port on which to serve HTTPS with authentication and authorization.If 0, don't serve HTTPS at all.
<code>--skip-headers</code>	
	If true, avoid header prefixes in the log messages
<code>--skip-log-headers</code>	
	If true, avoid headers when opening log files
<code>--stderrthreshold</code> severityÂ Â Â Â Â Default: 2	
	logs at or above this threshold go to stderr
<code>--tls-cert-file</code> string	
	File containing the default x509 Certificate for HTTPS. (CA cert, if any, concatenated after server cert). If HTTPS serving is enabled, and --tls-cert-file and --tls-private-key-file are not provided, a self-signed certificate and key are generated for the public address and saved to the directory specified by --cert-dir.
<code>--tls-cipher-suites</code> stringSlice	
	Comma-separated list of cipher suites for the server. If omitted, the default Go cipher suites will be use. Possible values: TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_RC4_128_SHA,TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_RC4_128_SHA,TLS_RSA_WITH_3DES_EDE_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA256,TLS_RSA_WITH_AES_128_GCM_SHA256,TLS_RSA_WITH_AES_256_CBC_SHA,TLS_RSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_RC4_128_SHA
<code>--tls-min-version</code> string	
	Minimum TLS version supported. Possible values: VersionTLS10, VersionTLS11, VersionTLS12, VersionTLS13
<code>--tls-private-key-file</code> string	
	File containing the default x509 private key matching --tls-cert-file.
<code>--tls-sni-cert-key</code> namedCertKeyÂ Â Â Â Â Default: []	

	A pair of x509 certificate and private key file paths, optionally suffixed with a list of domain patterns which are fully qualified domain names, possibly with prefixed wildcard segments. If no domain patterns are provided, the names of the certificate are extracted. Non-wildcard matches trump over wildcard matches, explicit domain patterns trump over extracted names. For multiple key/certificate pairs, use the --tls-sni-cert-key multiple times. Examples: "example.crt,example.key" or "foo.crt,foo.key:*.foo.com,foo.com".
--use-service-account-credentials	
	If true, use individual service account credentials for each controller.
-v, --v Level	
	number for the log level verbosity
--version version[=true]	
	Print version information and quit
--vmodule moduleSpec	
	comma-separated list of pattern=N settings for file-filtered logging

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 12:39 PM PST by [regenerate ref docs, 1.17, script chgs \(#18067\)](#) ([Page History](#))

[Edit This Page](#)

# kube-apiserver

- [Synopsis](#)
- [Options](#)

## Synopsis

The Kubernetes API server validates and configures data for the api objects which include pods, services, replicationcontrollers, and others. The API



Server services REST operations and provides the frontend to the cluster's shared state through which all other components interact.

```
kube-apiserver [flags]
```

## Options

<b>--add-dir-header</b>	
	If true, adds the file directory to the header
<b>--admission-control-config-file</b> string	
	File with admission control configuration.
<b>--advertise-address</b> ip	
	The IP address on which to advertise the apiserver to members of the cluster. This address must be reachable by the rest of the cluster. If blank, the --bind-address will be used. If --bind-address is unspecified, the host's default interface will be used.
<b>--allow-privileged</b>	
	If true, allow privileged containers. [default=false]
<b>--alsologtostderr</b>	
	log to standard error as well as files
<b>--anonymous-auth</b> bool Default: true	
	Enables anonymous requests to the secure port of the API server. Requests that are not rejected by another authentication method are treated as anonymous requests. Anonymous requests have a username of system:anonymous, and a group name of system:unauthenticated.
<b>--api-audiences</b> stringSlice	
	Identifiers of the API. The service account token authenticator will validate that tokens used against the API are bound to at least one of these audiences. If the --service-account-issuer flag is configured and this flag is not, this field defaults to a single element list containing the issuer URL .
<b>--apiserver-count</b> int Default: 1	
	The number of apiservers running in the cluster, must be a positive number. (In use when --endpoint-reconciler-type=master-count is enabled.)
<b>--audit-dynamic-configuration</b>	
	Enables dynamic audit configuration. This feature also requires the DynamicAuditing feature flag
<b>--audit-log-batch-buffer-size</b> int Default: 10000	
	The size of the buffer to store events before batching and writing. Only used in batch mode.
<b>--audit-log-batch-max-size</b> int Default: 1	
	The maximum size of a batch. Only used in batch mode.
<b>--audit-log-batch-max-wait</b> duration	
	The amount of time to wait before force writing the batch that hadn't reached the max size. Only used in batch mode.

<code>--audit-log-batch-throttle-burst int</code>	Maximum number of requests sent at the same moment if ThrottleQPS was not utilized before. Only used in batch mode.
<code>--audit-log-batch-throttle-enable</code>	Whether batching throttling is enabled. Only used in batch mode.
<code>--audit-log-batch-throttle-qps float32</code>	Maximum average number of batches per second. Only used in batch mode.
<code>--audit-log-format string</code> Default: "json"	Format of saved audits. "legacy" indicates 1-line text format for each event. "json" indicates structured json format. Known formats are legacy,json.
<code>--audit-log-maxage int</code>	The maximum number of days to retain old audit log files based on the timestamp encoded in their filename.
<code>--audit-log-maxbackup int</code>	The maximum number of old audit log files to retain.
<code>--audit-log-maxsize int</code>	The maximum size in megabytes of the audit log file before it gets rotated.
<code>--audit-log-mode string</code> Default: "blocking"	Strategy for sending audit events. Blocking indicates sending events should block server responses. Batch causes the backend to buffer and write events asynchronously. Known modes are batch,blocking,blocking-strict.
<code>--audit-log-path string</code>	If set, all requests coming to the apiserver will be logged to this file. '-' means standard out.
<code>--audit-log-truncate-enabled</code>	Whether event and batch truncating is enabled.
<code>--audit-log-truncate-max-batch-size int</code> Default: 10485760	Maximum size of the batch sent to the underlying backend. Actual serialized size can be several hundreds of bytes greater. If a batch exceeds this limit, it is split into several batches of smaller size.
<code>--audit-log-truncate-max-event-size int</code> Default: 102400	Maximum size of the audit event sent to the underlying backend. If the size of an event is greater than this number, first request and response are removed, and if this doesn't reduce the size enough, event is discarded.
<code>--audit-log-version string</code> Default: "audit.k8s.io/v1"	API group and version used for serializing audit events written to log.
<code>--audit-policy-file string</code>	Path to the file that defines the audit policy configuration.
<code>--audit-webhook-batch-buffer-size int</code> Default: 10000	

	The size of the buffer to store events before batching and writing. Only used in batch mode.
--audit-webhook-batch-max-size	int32 Default: 400
	The maximum size of a batch. Only used in batch mode.
--audit-webhook-batch-max-wait	duration Default: 30s
	The amount of time to wait before force writing the batch that hadn't reached the max size. Only used in batch mode.
--audit-webhook-batch-throttle-burst	int32 Default: 15
	Maximum number of requests sent at the same moment if ThrottleQPS was not utilized before. Only used in batch mode.
--audit-webhook-batch-throttle-enable	bool Default: true
	Whether batching throttling is enabled. Only used in batch mode.
--audit-webhook-batch-throttle-qps	float32 Default: 10
	Maximum average number of batches per second. Only used in batch mode.
--audit-webhook-config-file	string
	Path to a kubeconfig formatted file that defines the audit webhook configuration.
--audit-webhook-initial-backoff	duration Default: 10s
	The amount of time to wait before retrying the first failed request.
--audit-webhook-mode	string Default: "batch"
	Strategy for sending audit events. Blocking indicates sending events should block server responses. Batch causes the backend to buffer and write events asynchronously. Known modes are batch,blocking,blocking-strict.
--audit-webhook-truncate-enabled	bool
	Whether event and batch truncating is enabled.
--audit-webhook-truncate-max-batch-size	int32 Default: 10485760
	Maximum size of the batch sent to the underlying backend. Actual serialized size can be several hundreds of bytes greater. If a batch exceeds this limit, it is split into several batches of smaller size.
--audit-webhook-truncate-max-event-size	int32 Default: 102400
	Maximum size of the audit event sent to the underlying backend. If the size of an event is greater than this number, first request and response are removed, and if this doesn't reduce the size enough, event is discarded.
--audit-webhook-version	string Default: "audit.k8s.io/v1"
	API group and version used for serializing audit events written to webhook.
--authentication-token-webhook-cache-ttl	duration Default: 2m0s
	The duration to cache responses from the webhook token authenticator.
--authentication-token-webhook-config-file	string
	File with webhook configuration for token authentication in kubeconfig format. The API server will query the remote service to determine authentication for bearer tokens.

<code>--authentication-token-webhook-version</code> string	Default: "v1beta1"
The API version of the authentication.k8s.io TokenReview to send to and expect from the webhook.	
<code>--authorization-mode</code> string	Default: [AlwaysAllow]
Ordered list of plug-ins to do authorization on secure port. Comma-delimited list of: AlwaysAllow,AlwaysDeny,ABAC,Webhook,RBAC,Node.	
<code>--authorization-policy-file</code> string	
File with authorization policy in json line by line format, used with --authorization-mode=ABAC, on the secure port.	
<code>--authorization-webhook-cache-authorized-ttl</code> duration	Default: 5m0s
The duration to cache 'authorized' responses from the webhook authorizer.	
<code>--authorization-webhook-cache-unauthorized-ttl</code> duration	Default: 30s
The duration to cache 'unauthorized' responses from the webhook authorizer.	
<code>--authorization-webhook-config-file</code> string	
File with webhook configuration in kubeconfig format, used with --authorization-mode=Webhook. The API server will query the remote service to determine access on the API server's secure port.	
<code>--authorization-webhook-version</code> string	Default: "v1beta1"
The API version of the authorization.k8s.io SubjectAccessReview to send to and expect from the webhook.	
<code>--azure-container-registry-config</code> string	
Path to the file containing Azure container registry configuration information.	
<code>--bind-address</code> ip	Default: 0.0.0.0
The IP address on which to listen for the --secure-port port. The associated interface(s) must be reachable by the rest of the cluster, and by CLI/web clients. If blank, all interfaces will be used (0.0.0.0 for all IPv4 interfaces and :: for all IPv6 interfaces).	
<code>--cert-dir</code> string	Default: "/var/run/kubernetes"
The directory where the TLS certs are located. If --tls-cert-file and --tls-private-key-file are provided, this flag will be ignored.	
<code>--client-ca-file</code> string	
If set, any request presenting a client certificate signed by one of the authorities in the client-ca-file is authenticated with an identity corresponding to the CommonName of the client certificate.	
<code>--cloud-config</code> string	
The path to the cloud provider configuration file. Empty string for no configuration file.	
<code>--cloud-provider</code> string	
The provider for cloud services. Empty string for no provider.	

--cloud-provider-gce-l7lb-src-cidrs cidrs	Default: 130.211.0.0/22,35.191.0.0/16
CIDRs opened in GCE firewall for L7 LB traffic proxy & health checks	
--contention-profiling	
Enable lock contention profiling, if profiling is enabled	
--cors-allowed-origins	stringSlice
List of allowed origins for CORS, comma separated. An allowed origin can be a regular expression to support subdomain matching. If this list is empty CORS will not be enabled.	
--default-not-ready-toleration-seconds	int Default: 300
Indicates the tolerationSeconds of the toleration for notReady:NoExecute that is added by default to every pod that does not already have such a toleration.	
--default-unreachable-toleration-seconds	int Default: 300
Indicates the tolerationSeconds of the toleration for unreachable:NoExecute that is added by default to every pod that does not already have such a toleration.	
--default-watch-cache-size	int Default: 100
Default watch cache size. If zero, watch cache will be disabled for resources that do not have a default watch size set.	
--delete-collection-workers	int Default: 1
Number of workers spawned for DeleteCollection call. These are used to speed up namespace cleanup.	
--disable-admission-plugins	stringSlice
admission plugins that should be disabled although they are in the default enabled plugins list (NamespaceLifecycle, LimitRanger, ServiceAccount, TaintNodesByCondition, Priority, DefaultTolerationSeconds, DefaultStorageClass, StorageObjectInUseProtection, PersistentVolumeClaimResize, MutatingAdmissionWebhook, ValidatingAdmissionWebhook, RuntimeClass, ResourceQuota). Comma-delimited list of admission plugins: AlwaysAdmit, AlwaysDeny, AlwaysPullImages, DefaultStorageClass, DefaultTolerationSeconds, DenyEscalatingExec, DenyExecOnPrivileged, EventRateLimit, ExtendedResourceToleration, ImagePolicyWebhook, LimitPodHardAntiAffinityTopology, LimitRanger, MutatingAdmissionWebhook, NamespaceAutoProvision, NamespaceExists, NamespaceLifecycle, NodeRestriction, OwnerReferencesPermissionEnforcement, PersistentVolumeClaimResize, PersistentVolumeLabel, PodNodeSelector, PodPreset, PodSecurityPolicy, PodTolerationRestriction, Priority, ResourceQuota, RuntimeClass, SecurityContextDeny, ServiceAccount, StorageObjectInUseProtection, TaintNodesByCondition, ValidatingAdmissionWebhook. The order of plugins in this flag does not matter.	
--egress-selector-config-file	string
File with apiserver egress selector configuration.	

<code>--enable-admission-plugins</code>	<code>stringSlice</code>
admission plugins that should be enabled in addition to default enabled ones (NamespaceLifecycle, LimitRanger, ServiceAccount, TaintNodesByCondition, Priority, DefaultTolerationSeconds, DefaultStorageClass, StorageObjectInUseProtection, PersistentVolumeClaimResize, MutatingAdmissionWebhook, ValidatingAdmissionWebhook, RuntimeClass, ResourceQuota). Comma-delimited list of admission plugins: AlwaysAdmit, AlwaysDeny, AlwaysPullImages, DefaultStorageClass, DefaultTolerationSeconds, DenyEscalatingExec, DenyExecOnPrivileged, EventRateLimit, ExtendedResourceToleration, ImagePolicyWebhook, LimitPodHardAntiAffinityTopology, LimitRanger, MutatingAdmissionWebhook, NamespaceAutoProvision, NamespaceExists, NamespaceLifecycle, NodeRestriction, OwnerReferencesPermissionEnforcement, PersistentVolumeClaimResize, PersistentVolumeLabel, PodNodeSelector, PodPreset, PodSecurityPolicy, PodTolerationRestriction, Priority, ResourceQuota, RuntimeClass, SecurityContextDeny, ServiceAccount, StorageObjectInUseProtection, TaintNodesByCondition, ValidatingAdmissionWebhook. The order of plugins in this flag does not matter.	
<code>--enable-aggregator-routing</code>	
Turns on aggregator routing requests to endpoints IP rather than cluster IP.	
<code>--enable-bootstrap-token-auth</code>	
Enable to allow secrets of type 'bootstrap.kubernetes.io/token' in the 'kube-system' namespace to be used for TLS bootstrapping authentication.	
<code>--enable-garbage-collector</code>	<code>Â Â Â Â Â Default: true</code>
Enables the generic garbage collector. MUST be synced with the corresponding flag of the kube-controller-manager.	
<code>--enable-inflight-quota-handler</code>	
If true, replace the max-in-flight handler with an enhanced one that queues and dispatches with priority and fairness	
<code>--encryption-provider-config</code>	<code>string</code>
The file containing configuration for encryption providers to be used for storing secrets in etcd	
<code>--endpoint-reconciler-type</code>	<code>stringÂ Â Â Â Â Default: "lease"</code>
Use an endpoint reconciler (master-count, lease, none)	
<code>--etcd-cafile</code>	<code>string</code>
SSL Certificate Authority file used to secure etcd communication.	
<code>--etcd-certfile</code>	<code>string</code>
SSL certification file used to secure etcd communication.	
<code>--etcd-compaction-interval</code>	<code>durationÂ Â Â Â Â Default: 5m0s</code>
The interval of compaction requests. If 0, the compaction request from apiserver is disabled.	

--etcd-count-metric-poll-period durationÂ Â Â Â Â Default: 1m0s	
	Frequency of polling etcd for number of resources per type. 0 disables the metric collection.
--etcd-keyfile string	
	SSL key file used to secure etcd communication.
--etcd-prefix stringÂ Â Â Â Â Default: "/registry"	
	The prefix to prepend to all resource paths in etcd.
--etcd-servers stringSlice	
	List of etcd servers to connect with (scheme://ip:port), comma separated.
--etcd-servers-overrides stringSlice	
	Per-resource etcd servers overrides, comma separated. The individual override format: group/resource#servers, where servers are URLs, semicolon separated.
--event-ttl durationÂ Â Â Â Â Default: 1h0m0s	
	Amount of time to retain events.
--external-hostname string	
	The hostname to use when generating externalized URLs for this master (e.g. Swagger API Docs).
--feature-gates mapStringBool	

A set of key=value pairs that describe feature gates for alpha/experimental features. Options are:

APIListChunking=true|false (BETA - default=true)  
APIPriorityAndFairness=true|false (ALPHA - default=false)  
APIResponseCompression=true|false (BETA - default=true)  
AllAlpha=true|false (ALPHA - default=false)  
AllBeta=true|false (BETA - default=false)  
AllowInsecureBackendProxy=true|false (BETA - default=true)  
AppArmor=true|false (BETA - default=true)  
BalanceAttachedNodeVolumes=true|false (ALPHA - default=false)  
BlockVolume=true|false (BETA - default=true)  
BoundServiceAccountTokenVolume=true|false (ALPHA - default=false)  
CPUManager=true|false (BETA - default=true)  
CRIContainerLogRotation=true|false (BETA - default=true)  
CSIBlockVolume=true|false (BETA - default=true)  
CSIDriverRegistry=true|false (BETA - default=true)  
CSIInlineVolume=true|false (BETA - default=true)  
CSIMigration=true|false (BETA - default=true)  
CSIMigrationAWS=true|false (BETA - default=false)  
CSIMigrationAWSComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureDisk=true|false (ALPHA - default=false)  
CSIMigrationAzureDiskComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureFile=true|false (ALPHA - default=false)  
CSIMigrationAzureFileComplete=true|false (ALPHA - default=false)  
CSIMigrationGCE=true|false (BETA - default=false)  
CSIMigrationGCEComplete=true|false (ALPHA - default=false)  
CSIMigrationOpenStack=true|false (ALPHA - default=false)  
CSIMigrationOpenStackComplete=true|false (ALPHA - default=false)  
CustomCPUCFSQuotaPeriod=true|false (ALPHA - default=false)  
DevicePlugins=true|false (BETA - default=true)  
DryRun=true|false (BETA - default=true)  
DynamicAuditing=true|false (ALPHA - default=false)  
DynamicKubeletConfig=true|false (BETA - default=true)  
EndpointSlice=true|false (BETA - default=false)  
EphemeralContainers=true|false (ALPHA - default=false)  
EvenPodsSpread=true|false (ALPHA - default=false)  
ExpandCSIVolumes=true|false (BETA - default=true)  
ExpandInUsePersistentVolumes=true|false (BETA - default=true)  
ExpandPersistentVolumes=true|false (BETA - default=true)  
ExperimentalHostUserNamespaceDefaulting=true|false (BETA - default=false)  
HPAScaleToZero=true|false (ALPHA - default=false)  
HyperVContainer=true|false (ALPHA - default=false)  
IPv6DualStack=true|false (ALPHA - default=false)  
KubeletPodResources=true|false (BETA - default=true)  
LegacyNodeRoleBehavior=true|false (ALPHA - default=true)  
LocalStorageCapacityIsolation=true|false (BETA - default=true)  
LocalStorageCapacityIsolationFSQuotaMonitoring=true|false (ALPHA - default=false)  
NodeDisruptionExclusion=true|false (ALPHA - default=false)



-h, --help
help for kube-apiserver
--http2-max-streams-per-connection int
The limit that the server gives to clients for the maximum number of streams in an HTTP/2 connection. Zero means to use golang's default.
--kubelet-certificate-authority string
Path to a cert file for the certificate authority.
--kubelet-client-certificate string
Path to a client cert file for TLS.
--kubelet-client-key string
Path to a client key file for TLS.
--kubelet-httpsâââââ Default: true
Use https for kubelet connections.
--kubelet-preferred-address-types stringSliceâââââ Default: [Hostname,InternalDNS,InternalIP,ExternalDNS,ExternalIP]
List of the preferred NodeAddressTypes to use for kubelet connections.
--kubelet-timeout durationâââââ Default: 5s
Timeout for kubelet operations.
--kubernetes-service-node-port int
If non-zero, the Kubernetes master service (which apiserver creates/maintains) will be of type NodePort, using this as the value of the port. If zero, the Kubernetes master service will be of type ClusterIP.
--livez-grace-period duration
This option represents the maximum amount of time it should take for apiserver to complete its startup sequence and become live. From apiserver's start time to when this amount of time has elapsed, /livez will assume that unfinished post-start hooks will complete successfully and therefore return true.
--log-backtrace-at traceLocationâââââ Default: :0
when logging hits line file:N, emit a stack trace
--log-dir string
If non-empty, write log files in this directory
--log-file string
If non-empty, use this log file
--log-file-max-size uintâââââ Default: 1800
Defines the maximum size a log file can grow to. Unit is megabytes. If the value is 0, the maximum file size is unlimited.
--log-flush-frequency durationâââââ Default: 5s
Maximum number of seconds between log flushes
--logtostderrâââââ Default: true
log to standard error instead of files
--master-service-namespace stringâââââ Default: "default"

DEPRECATED: the namespace from which the kubernetes master services should be injected into pods.
--max-connection-bytes-per-sec int
If non-zero, throttle each user connection to this number of bytes/sec. Currently only applies to long-running requests.
--max-mutating-requests-inflight int Default: 200
The maximum number of mutating requests in flight at a given time. When the server exceeds this, it rejects requests. Zero for no limit.
--max-requests-inflight int Default: 400
The maximum number of non-mutating requests in flight at a given time. When the server exceeds this, it rejects requests. Zero for no limit.
--min-request-timeout int Default: 1800
An optional field indicating the minimum number of seconds a handler must keep a request open before timing it out. Currently only honored by the watch request handler, which picks a randomized value above this number as the connection timeout, to spread out load.
--oidc-ca-file string
If set, the OpenID server's certificate will be verified by one of the authorities in the oidc-ca-file, otherwise the host's root CA set will be used.
--oidc-client-id string
The client ID for the OpenID Connect client, must be set if oidc-issuer-url is set.
--oidc-groups-claim string
If provided, the name of a custom OpenID Connect claim for specifying user groups. The claim value is expected to be a string or array of strings. This flag is experimental, please see the authentication documentation for further details.
--oidc-groups-prefix string
If provided, all groups will be prefixed with this value to prevent conflicts with other authentication strategies.
--oidc-issuer-url string
The URL of the OpenID issuer, only HTTPS scheme will be accepted. If set, it will be used to verify the OIDC JSON Web Token (JWT).
--oidc-required-claim mapStringString
A key=value pair that describes a required claim in the ID Token. If set, the claim is verified to be present in the ID Token with a matching value. Repeat this flag to specify multiple claims.
--oidc-signing-algs stringSlice Default: [RS256]
Comma-separated list of allowed JOSE asymmetric signing algorithms. JWTs with a 'alg' header value not in this list will be rejected. Values are defined by RFC 7518 <a href="https://tools.ietf.org/html/rfc7518#section-3.1">https://tools.ietf.org/html/rfc7518#section-3.1</a> .
--oidc-username-claim string Default: "sub"

The OpenID claim to use as the user name. Note that claims other than the default ('sub') is not guaranteed to be unique and immutable. This flag is experimental, please see the authentication documentation for further details.
--oidc-username-prefix string
If provided, all usernames will be prefixed with this value. If not provided, username claims other than 'email' are prefixed by the issuer URL to avoid clashes. To skip any prefixing, provide the value '-'.
--profiling Default: true
Enable profiling via web interface host:port/debug/pprof/
--proxy-client-cert-file string
Client certificate used to prove the identity of the aggregator or kube-apiserver when it must call out during a request. This includes proxying requests to a user api-server and calling out to webhook admission plugins. It is expected that this cert includes a signature from the CA in the --requestheader-client-ca-file flag. That CA is published in the 'extension-apiserver-authentication' configmap in the kube-system namespace. Components receiving calls from kube-aggregator should use that CA to perform their half of the mutual TLS verification.
--proxy-client-key-file string
Private key for the client certificate used to prove the identity of the aggregator or kube-apiserver when it must call out during a request. This includes proxying requests to a user api-server and calling out to webhook admission plugins.
--request-timeout duration Default: 1m0s
An optional field indicating the duration a handler must keep a request open before timing it out. This is the default request timeout for requests but may be overridden by flags such as --min-request-timeout for specific types of requests.
--requestheader-allowed-names stringSlice
List of client certificate common names to allow to provide usernames in headers specified by --requestheader-username-headers. If empty, any client certificate validated by the authorities in --requestheader-client-ca-file is allowed.
--requestheader-client-ca-file string
Root certificate bundle to use to verify client certificates on incoming requests before trusting usernames in headers specified by --requestheader-username-headers. WARNING: generally do not depend on authorization being already done for incoming requests.
--requestheader-extra-headers-prefix stringSlice
List of request header prefixes to inspect. X-Remote-Extra- is suggested.
--requestheader-group-headers stringSlice
List of request headers to inspect for groups. X-Remote-Group is suggested.

<code>--requestheader-username-headers stringSlice</code>	
	List of request headers to inspect for usernames. X-Remote-User is common.
<code>--runtime-config mapStringString</code>	
	A set of key=value pairs that enable or disable built-in APIs. Supported options are: v1=true false for the core API group <group>/<version>=true false for a specific API group and version (e.g. apps/v1=true) api/all=true false controls all API versions api/ga=true false controls all API versions of the form v[0-9]+ api/beta=true false controls all API versions of the form v[0-9]+beta[0-9]+ api/alpha=true false controls all API versions of the form v[0-9]+alpha[0-9]+ api/legacy is deprecated, and will be removed in a future version
<code>--secure-port int</code> Default: 6443	
	The port on which to serve HTTPS with authentication and authorization. It cannot be switched off with 0.
<code>--service-account-issuer string</code>	
	Identifier of the service account token issuer. The issuer will assert this identifier in "iss" claim of issued tokens. This value is a string or URI.
<code>--service-account-key-file stringArray</code>	
	File containing PEM-encoded x509 RSA or ECDSA private or public keys, used to verify ServiceAccount tokens. The specified file can contain multiple keys, and the flag can be specified multiple times with different files. If unspecified, --tls-private-key-file is used. Must be specified when --service-account-signing-key is provided
<code>--service-account-lookup</code> Default: true	
	If true, validate ServiceAccount tokens exist in etcd as part of authentication.
<code>--service-account-max-token-expiration duration</code>	
	The maximum validity duration of a token created by the service account token issuer. If an otherwise valid TokenRequest with a validity duration larger than this value is requested, a token will be issued with a validity duration of this value.
<code>--service-account-signing-key-file string</code>	
	Path to the file that contains the current private key of the service account token issuer. The issuer will sign issued ID tokens with this private key. (Requires the 'TokenRequest' feature gate.)
<code>--service-cluster-ip-range string</code>	
	A CIDR notation IP range from which to assign service cluster IPs. This must not overlap with any IP ranges assigned to nodes for pods.
<code>--service-node-port-range portRange</code> Default: 30000-32767	

A port range to reserve for services with NodePort visibility. Example: '30000-32767'. Inclusive at both ends of the range.
--show-hidden-metrics-for-version string
The previous version for which you want to show hidden metrics. Only the previous minor version is meaningful, other values will not be allowed. The format is <major>.<minor>, e.g.: '1.16'. The purpose of this format is make sure you have the opportunity to notice if the next release hides additional metrics, rather than being surprised when they are permanently removed in the release after that.
--shutdown-delay-duration duration
Time to delay the termination. During that time the server keeps serving requests normally and /healthz returns success, but /readyz immediately returns failure. Graceful termination starts after this delay has elapsed. This can be used to allow load balancer to stop sending traffic to this server.
--skip-headers
If true, avoid header prefixes in the log messages
--skip-log-headers
If true, avoid headers when opening log files
--stderrthreshold severityÂ Â Â Â Â Default: 2
logs at or above this threshold go to stderr
--storage-backend string
The storage backend for persistence. Options: 'etcd3' (default).
--storage-media-type stringÂ Â Â Â Â Default: "application/vnd.kubernetes.protobuf"
The media type to use to store objects in storage. Some resources or storage backends may only support a specific media type and will ignore this setting.
--target-ram-mb int
Memory limit for apiserver in MB (used to configure sizes of caches, etc.)
--tls-cert-file string
File containing the default x509 Certificate for HTTPS. (CA cert, if any, concatenated after server cert). If HTTPS serving is enabled, and --tls-cert-file and --tls-private-key-file are not provided, a self-signed certificate and key are generated for the public address and saved to the directory specified by --cert-dir.
--tls-cipher-suites stringSlice

Comma-separated list of cipher suites for the server. If omitted, the default Go cipher suites will be used. Possible values: TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_RC4_128_SHA,TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_RC4_128_SHA,TLS_RSA_WITH_3DES_EDE_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA256,TLS_RSA_WITH_AES_128_GCM_SHA256,TLS_RSA_WITH_AES_256_CBC_SHA,TLS_RSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_RC4_128_SHA
--tls-min-version string
Minimum TLS version supported. Possible values: VersionTLS10, VersionTLS11, VersionTLS12, VersionTLS13
--tls-private-key-file string
File containing the default x509 private key matching --tls-cert-file.
--tls-sni-cert-key namedCertKeyÂ Â Â Â Default: []
A pair of x509 certificate and private key file paths, optionally suffixed with a list of domain patterns which are fully qualified domain names, possibly with prefixed wildcard segments. If no domain patterns are provided, the names of the certificate are extracted. Non-wildcard matches trump over wildcard matches, explicit domain patterns trump over extracted names. For multiple key/certificate pairs, use the --tls-sni-cert-key multiple times. Examples: "example.crt,example.key" or "foo.crt,foo.key:*.foo.com,foo.com".
--token-auth-file string
If set, the file that will be used to secure the secure port of the API server via token authentication.
-v, --v Level
number for the log level verbosity
--version version[=true]
Print version information and quit
--vmodule moduleSpec
comma-separated list of pattern=N settings for file-filtered logging
--watch-cacheÂ Â Â Â Default: true
Enable watch caching in the apiserver
--watch-cache-sizes stringSlice

Watch cache size settings for some resources (pods, nodes, etc.), comma separated. The individual setting format: resource[.group]#size, where resource is lowercase plural (no version), group is omitted for resources of apiVersion v1 (the legacy core API) and included for others, and size is a number. It takes effect when watch-cache is enabled. Some resources (replicationcontrollers, endpoints, nodes, pods, services, apiservices.apiregistration.k8s.io) have system defaults set by heuristics, others default to default-watch-cache-size

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 12:39 PM PST by [regenerate ref docs, 1.17, script chgs \(#18067\)](#) ([Page History](#))

[Edit This Page](#)

# kube-controller-manager

- [Synopsis](#)
- [Options](#)

## Synopsis

The Kubernetes controller manager is a daemon that embeds the core control loops shipped with Kubernetes. In applications of robotics and



automation, a control loop is a non-terminating loop that regulates the state of the system. In Kubernetes, a controller is a control loop that watches the shared state of the cluster through the apiserver and makes changes attempting to move the current state towards the desired state. Examples of controllers that ship with Kubernetes today are the replication controller, endpoints controller, namespace controller, and serviceaccounts controller.

kube-controller-manager [flags]

## Options

--add-dir-header	
	If true, adds the file directory to the header
--allocate-node-cidrs	
	Should CIDRs for Pods be allocated and set on the cloud provider.
--alsologtostderr	
	log to standard error as well as files
--attach-detach-reconcile-sync-period duration	Default: 1m0s
	The reconciler sync wait time between volume attach detach. This duration must be larger than one second, and increasing this value from the default may allow for volumes to be mismatched with pods.
--authentication-kubeconfig string	
	kubeconfig file pointing at the 'core' kubernetes server with enough rights to create tokenaccessreviews.authentication.k8s.io. This is optional. If empty, all token requests are considered to be anonymous and no client CA is looked up in the cluster.
--authentication-skip-lookup	
	If false, the authentication-kubeconfig will be used to lookup missing authentication configuration from the cluster.
--authentication-token-webhook-cache-ttl duration	Default: 10s
	The duration to cache responses from the webhook token authenticator.
--authentication-tolerate-lookup-failure	
	If true, failures to look up missing authentication configuration from the cluster are not considered fatal. Note that this can result in authentication that treats all requests as anonymous.
--authorization-always-allow-paths stringSlice	Default: [/healthz]
	A list of HTTP paths to skip during authorization, i.e. these are authorized without contacting the 'core' kubernetes server.
--authorization-kubeconfig string	
	kubeconfig file pointing at the 'core' kubernetes server with enough rights to create subjectaccessreviews.authorization.k8s.io. This is optional. If empty, all requests not skipped by authorization are forbidden.
--authorization-webhook-cache-authorized-ttl duration	Default: 10s
	The duration to cache 'authorized' responses from the webhook authorizer.

<code>--authorization-webhook-cache-unauthorized-ttl</code> durationÂ Â Â Â Â Default: 10s	
	The duration to cache 'unauthorized' responses from the webhook authorizer.
<code>--azure-container-registry-config</code> string	
	Path to the file containing Azure container registry configuration information.
<code>--bind-address</code> ipÂ Â Â Â Â Default: 0.0.0.0	
	The IP address on which to listen for the <code>--secure-port</code> port. The associated interface(s) must be reachable by the rest of the cluster, and by CLI/web clients. If blank, all interfaces will be used (0.0.0.0 for all IPv4 interfaces and <code>::</code> for all IPv6 interfaces).
<code>--cert-dir</code> string	
	The directory where the TLS certs are located. If <code>--tls-cert-file</code> and <code>--tls-private-key-file</code> are provided, this flag will be ignored.
<code>--cidr-allocator-type</code> stringÂ Â Â Â Â Default: "RangeAllocator"	
	Type of CIDR allocator to use
<code>--client-ca-file</code> string	
	If set, any request presenting a client certificate signed by one of the authorities in the <code>client-ca-file</code> is authenticated with an identity corresponding to the <code>CommonName</code> of the client certificate.
<code>--cloud-config</code> string	
	The path to the cloud provider configuration file. Empty string for no configuration file.
<code>--cloud-provider</code> string	
	The provider for cloud services. Empty string for no provider.
<code>--cluster-cidr</code> string	
	CIDR Range for Pods in cluster. Requires <code>--allocate-node-cidrs</code> to be true
<code>--cluster-name</code> stringÂ Â Â Â Â Default: "kubernetes"	
	The instance prefix for the cluster.
<code>--cluster-signing-cert-file</code> stringÂ Â Â Â Â Default: "/etc/kubernetes/ca/ca.pem"	
	Filename containing a PEM-encoded X509 CA certificate used to issue cluster-scoped certificates
<code>--cluster-signing-key-file</code> stringÂ Â Â Â Â Default: "/etc/kubernetes/ca/ca.key"	
	Filename containing a PEM-encoded RSA or ECDSA private key used to sign cluster-scoped certificates
<code>--concurrent-deployment-syncs</code> int32Â Â Â Â Â Default: 5	
	The number of deployment objects that are allowed to sync concurrently. Larger number = more responsive deployments, but more CPU (and network) load
<code>--concurrent-endpoint-syncs</code> int32Â Â Â Â Â Default: 5	

The number of endpoint syncing operations that will be done concurrently. Larger number = faster endpoint updating, but more CPU (and network) load
--concurrent-gc-syncs int32 Default: 20
The number of garbage collector workers that are allowed to sync concurrently.
--concurrent-namespace-syncs int32 Default: 10
The number of namespace objects that are allowed to sync concurrently. Larger number = more responsive namespace termination, but more CPU (and network) load
--concurrent-replicaset-syncs int32 Default: 5
The number of replica sets that are allowed to sync concurrently. Larger number = more responsive replica management, but more CPU (and network) load
--concurrent-resource-quota-syncs int32 Default: 5
The number of resource quotas that are allowed to sync concurrently. Larger number = more responsive quota management, but more CPU (and network) load
--concurrent-service-endpoint-syncs int32 Default: 5
The number of service endpoint syncing operations that will be done concurrently. Larger number = faster endpoint slice updating, but more CPU (and network) load. Defaults to 5.
--concurrent-service-syncs int32 Default: 1
The number of services that are allowed to sync concurrently. Larger number = more responsive service management, but more CPU (and network) load
--concurrent-serviceaccount-token-syncs int32 Default: 5
The number of service account token objects that are allowed to sync concurrently. Larger number = more responsive token generation, but more CPU (and network) load
--concurrent-statefulset-syncs int32 Default: 5
The number of statefulset objects that are allowed to sync concurrently. Larger number = more responsive statefulsets, but more CPU (and network) load
--concurrent-ttl-after-finished-syncs int32 Default: 5
The number of TTL-after-finished controller workers that are allowed to sync concurrently.
--concurrent_rc_syncs int32 Default: 5
The number of replication controllers that are allowed to sync concurrently. Larger number = more responsive replica management, but more CPU (and network) load
--configure-cloud-routes Default: true
Should CIDRs allocated by allocate-node-cidrs be configured on the cloud provider.

<code>--contention-profiling</code>	
	Enable lock contention profiling, if profiling is enabled
<code>--controller-start-interval duration</code>	
	Interval between starting controller managers.
<code>--controllers stringSlice</code> Default: <code>[*]</code>	
	<p>A list of controllers to enable. '*' enables all on-by-default controllers, 'foo' enables the controller named 'foo', '-foo' disables the controller named 'foo'.</p> <p>All controllers: attachdetach, bootstrapsigner, cloud-node-lifecycle, clusterrole-aggregation, cronjob, csrapproving, csrcleaner, csrsigning, daemonset, deployment, disruption, endpoint, endpointslice, garbagecollector, horizontalpodautoscaling, job, namespace, nodeipam, nodelifecycle, persistentvolume-binder, persistentvolume-expander, podgc, pv-protection, pvc-protection, replicaset, replicationcontroller, resourcequota, root-ca-cert-publisher, route, service, serviceaccount, serviceaccount-token, statefulset, tokencleaner, ttl, ttl-after-finished</p> <p>Disabled-by-default controllers: bootstrapsigner, tokencleaner</p>
<code>--deployment-controller-sync-period duration</code> Default: <code>30s</code>	
	Period for syncing the deployments.
<code>--disable-attach-detach-reconcile-sync</code>	
	Disable volume attach detach reconciler sync. Disabling this may cause volumes to be mismatched with pods. Use wisely.
<code>--enable-dynamic-provisioning</code> Default: <code>true</code>	
	Enable dynamic provisioning for environments that support it.
<code>--enable-garbage-collector</code> Default: <code>true</code>	
	Enables the generic garbage collector. MUST be synced with the corresponding flag of the kube-apiserver.
<code>--enable-hostpath-provisioner</code>	
	Enable HostPath PV provisioning when running without a cloud provider. This allows testing and development of provisioning features. HostPath provisioning is not supported in any way, won't work in a multi-node cluster, and should not be used for anything other than testing or development.
<code>--enable-taint-manager</code> Default: <code>true</code>	
	WARNING: Beta feature. If set to true enables NoExecute Taints and will evict all not-tolerating Pod running on Nodes tainted with this kind of Taints.
<code>--endpoint-updates-batch-period duration</code>	
	<p>The length of endpoint updates batching period. Processing of pod changes will be delayed by this duration to join them with potential upcoming updates and reduce the overall number of endpoints updates. Larger number = higher endpoint programming latency, but lower number of endpoints revision generated</p>

--experimental-cluster-signing-duration durationÂ Â Â Â Â Default: 8760h0m0s	
	The length of duration signed certificates will be given.
--external-cloud-volume-plugin string	
	The plugin to use when cloud provider is set to external. Can be empty, should only be set when cloud-provider is external. Currently used to allow node and volume controllers to work for in tree cloud providers.
--feature-gates mapStringBool	

A set of key=value pairs that describe feature gates for alpha/experimental features. Options are:

APIListChunking=true|false (BETA - default=true)  
APIPriorityAndFairness=true|false (ALPHA - default=false)  
APIResponseCompression=true|false (BETA - default=true)  
AllAlpha=true|false (ALPHA - default=false)  
AllBeta=true|false (BETA - default=false)  
AllowInsecureBackendProxy=true|false (BETA - default=true)  
AppArmor=true|false (BETA - default=true)  
BalanceAttachedNodeVolumes=true|false (ALPHA - default=false)  
BlockVolume=true|false (BETA - default=true)  
BoundServiceAccountTokenVolume=true|false (ALPHA - default=false)  
CPUManager=true|false (BETA - default=true)  
CRIContainerLogRotation=true|false (BETA - default=true)  
CSIBlockVolume=true|false (BETA - default=true)  
CSIDriverRegistry=true|false (BETA - default=true)  
CSIInlineVolume=true|false (BETA - default=true)  
CSIMigration=true|false (BETA - default=true)  
CSIMigrationAWS=true|false (BETA - default=false)  
CSIMigrationAWSComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureDisk=true|false (ALPHA - default=false)  
CSIMigrationAzureDiskComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureFile=true|false (ALPHA - default=false)  
CSIMigrationAzureFileComplete=true|false (ALPHA - default=false)  
CSIMigrationGCE=true|false (BETA - default=false)  
CSIMigrationGCEComplete=true|false (ALPHA - default=false)  
CSIMigrationOpenStack=true|false (ALPHA - default=false)  
CSIMigrationOpenStackComplete=true|false (ALPHA - default=false)  
CustomCPUCFSQuotaPeriod=true|false (ALPHA - default=false)  
DevicePlugins=true|false (BETA - default=true)  
DryRun=true|false (BETA - default=true)  
DynamicAuditing=true|false (ALPHA - default=false)  
DynamicKubeletConfig=true|false (BETA - default=true)  
EndpointSlice=true|false (BETA - default=false)  
EphemeralContainers=true|false (ALPHA - default=false)  
EvenPodsSpread=true|false (ALPHA - default=false)  
ExpandCSIVolumes=true|false (BETA - default=true)  
ExpandInUsePersistentVolumes=true|false (BETA - default=true)  
ExpandPersistentVolumes=true|false (BETA - default=true)  
ExperimentalHostUserNamespaceDefaulting=true|false (BETA - default=false)  
HPAScaleToZero=true|false (ALPHA - default=false)  
HyperVContainer=true|false (ALPHA - default=false)  
IPv6DualStack=true|false (ALPHA - default=false)  
KubeletPodResources=true|false (BETA - default=true)  
LegacyNodeRoleBehavior=true|false (ALPHA - default=true)  
LocalStorageCapacityIsolation=true|false (BETA - default=true)  
LocalStorageCapacityIsolationFSQuotaMonitoring=true|false (ALPHA - default=false)  
NodeDisruptionExclusion=true|false (ALPHA - default=false)

--flex-volume-plugin-dir string	Default: "/usr/libexec/kubernetes/kubelet-plugins/volume/exec/"
	Full path of the directory in which the flex volume plugin should search for additional third party volume plugins.
-h, --help	
	help for kube-controller-manager
--horizontal-pod-autoscaler-cpu-initialization-period duration	Default: 5m0s
	The period after pod start when CPU samples might be skipped.
--horizontal-pod-autoscaler-downscale-stabilization duration	Default: 5m0s
	The period for which autoscaler will look backwards and not scale down below any recommendation it made during that period.
--horizontal-pod-autoscaler-initial-readiness-delay duration	Default: 30s
	The period after pod start during which readiness changes will be treated as initial readiness.
--horizontal-pod-autoscaler-sync-period duration	Default: 15s
	The period for syncing the number of pods in horizontal pod autoscaler.
--horizontal-pod-autoscaler-tolerance float	Default: 0.1
	The minimum change (from 1.0) in the desired-to-actual metrics ratio for the horizontal pod autoscaler to consider scaling.
--http2-max-streams-per-connection int	
	The limit that the server gives to clients for the maximum number of streams in an HTTP/2 connection. Zero means to use golang's default.
--kube-api-burst int32	Default: 30
	Burst to use while talking with kubernetes apiserver.
--kube-api-content-type string	Default: "application/vnd.kubernetes.protobuf"
	Content type of requests sent to apiserver.
--kube-api-qps float32	Default: 20
	QPS to use while talking with kubernetes apiserver.
--kubeconfig string	
	Path to kubeconfig file with authorization and master location information.
--large-cluster-size-threshold int32	Default: 50
	Number of nodes from which NodeController treats the cluster as large for the eviction logic purposes. --secondary-node-eviction-rate is implicitly overridden to 0 for clusters this size or smaller.
--leader-elect	Default: true
	Start a leader election client and gain leadership before executing the main loop. Enable this when running replicated components for high availability.
--leader-elect-lease-duration duration	Default: 15s

	The duration that non-leader candidates will wait after observing a leadership renewal until attempting to acquire leadership of a led but unrenewed leader slot. This is effectively the maximum duration that a leader can be stopped before it is replaced by another candidate. This is only applicable if leader election is enabled.
<code>--leader-elect-renew-deadline duration</code> Â Â Â Â Â Default: 10s	
	The interval between attempts by the acting master to renew a leadership slot before it stops leading. This must be less than or equal to the lease duration. This is only applicable if leader election is enabled.
<code>--leader-elect-resource-lock endpoints</code> Â Â Â Â Â Default: "endpointsleases"	
	The type of resource object that is used for locking during leader election. Supported options are endpoints (default) and `configmaps`.
<code>--leader-elect-resource-name string</code> Â Â Â Â Â Default: "kube-controller-manager"	
	The name of resource object that is used for locking during leader election.
<code>--leader-elect-resource-namespace string</code> Â Â Â Â Â Default: "kube-system"	
	The namespace of resource object that is used for locking during leader election.
<code>--leader-elect-retry-period duration</code> Â Â Â Â Â Default: 2s	
	The duration the clients should wait between attempting acquisition and renewal of a leadership. This is only applicable if leader election is enabled.
<code>--log-backtrace-at traceLocation</code> Â Â Â Â Â Default: :0	
	when logging hits line file:N, emit a stack trace
<code>--log-dir string</code>	
	If non-empty, write log files in this directory
<code>--log-file string</code>	
	If non-empty, use this log file
<code>--log-file-max-size uint</code> Â Â Â Â Â Default: 1800	
	Defines the maximum size a log file can grow to. Unit is megabytes. If the value is 0, the maximum file size is unlimited.
<code>--log-flush-frequency duration</code> Â Â Â Â Â Default: 5s	
	Maximum number of seconds between log flushes
<code>--logtostderr</code> Â Â Â Â Â Default: true	
	log to standard error instead of files
<code>--master string</code>	
	The address of the Kubernetes API server (overrides any value in kubeconfig).
<code>--max-endpoints-per-slice int32</code> Â Â Â Â Â Default: 100	
	The maximum number of endpoints that will be added to an EndpointSlice. More endpoints per slice will result in less endpoint slices, but larger resources. Defaults to 100.
<code>--min-resync-period duration</code> Â Â Â Â Â Default: 12h0m0s	



	The resync period in reflectors will be random between MinResyncPeriod and 2*MinResyncPeriod.
--namespace-sync-period duration	Default: 5m0s
	The period for syncing namespace life-cycle updates
--node-cidr-mask-size	int32
	Mask size for node cidr in cluster. Default is 24 for IPv4 and 64 for IPv6.
--node-cidr-mask-size-ipv4	int32
	Mask size for IPv4 node cidr in dual-stack cluster. Default is 24.
--node-cidr-mask-size-ipv6	int32
	Mask size for IPv6 node cidr in dual-stack cluster. Default is 64.
--node-eviction-rate	float32 Default: 0.1
	Number of nodes per second on which pods are deleted in case of node failure when a zone is healthy (see --unhealthy-zone-threshold for definition of healthy/unhealthy). Zone refers to entire cluster in non-multizone clusters.
--node-monitor-grace-period duration	Default: 40s
	Amount of time which we allow running Node to be unresponsive before marking it unhealthy. Must be N times more than kubelet's nodeStatusUpdateFrequency, where N means number of retries allowed for kubelet to post node status.
--node-monitor-period duration	Default: 5s
	The period for syncing NodeStatus in NodeController.
--node-startup-grace-period duration	Default: 1m0s
	Amount of time which we allow starting Node to be unresponsive before marking it unhealthy.
--pod-eviction-timeout duration	Default: 5m0s
	The grace period for deleting pods on failed nodes.
--profiling	
	Enable profiling via web interface host:port/debug/pprof/
--pv-recycler-increment-timeout-nfs	int32 Default: 30
	the increment of time added per Gi to ActiveDeadlineSeconds for an NFS scrubber pod
--pv-recycler-minimum-timeout-hostpath	int32 Default: 60
	The minimum ActiveDeadlineSeconds to use for a HostPath Recycler pod. This is for development and testing only and will not work in a multi-node cluster.
--pv-recycler-minimum-timeout-nfs	int32 Default: 300
	The minimum ActiveDeadlineSeconds to use for an NFS Recycler pod
--pv-recycler-pod-template-filepath-hostpath	string
	The file path to a pod definition used as a template for HostPath persistent volume recycling. This is for development and testing only and will not work in a multi-node cluster.
--pv-recycler-pod-template-filepath-nfs	string

	The file path to a pod definition used as a template for NFS persistent volume recycling
	<code>--pv-recycler-timeout-increment-hostpath</code> int32 Default: 30
	the increment of time added per Gi to ActiveDeadlineSeconds for a HostPath scrubber pod. This is for development and testing only and will not work in a multi-node cluster.
	<code>--pvclaimbinder-sync-period</code> duration Default: 15s
	The period for syncing persistent volumes and persistent volume claims
	<code>--requestheader-allowed-names</code> stringSlice
	List of client certificate common names to allow to provide usernames in headers specified by <code>--requestheader-username-headers</code> . If empty, any client certificate validated by the authorities in <code>--requestheader-client-ca-file</code> is allowed.
	<code>--requestheader-client-ca-file</code> string
	Root certificate bundle to use to verify client certificates on incoming requests before trusting usernames in headers specified by <code>--requestheader-username-headers</code> . WARNING: generally do not depend on authorization being already done for incoming requests.
	<code>--requestheader-extra-headers-prefix</code> stringSlice Default: [x-remote-extra-]
	List of request header prefixes to inspect. X-Remote-Extra- is suggested.
	<code>--requestheader-group-headers</code> stringSlice Default: [x-remote-group]
	List of request headers to inspect for groups. X-Remote-Group is suggested.
	<code>--requestheader-username-headers</code> stringSlice Default: [x-remote-user]
	List of request headers to inspect for usernames. X-Remote-User is common.
	<code>--resource-quota-sync-period</code> duration Default: 5m0s
	The period for syncing quota usage status in the system
	<code>--root-ca-file</code> string
	If set, this root certificate authority will be included in service account's token secret. This must be a valid PEM-encoded CA bundle.
	<code>--route-reconciliation-period</code> duration Default: 10s
	The period for reconciling routes created for Nodes by cloud provider.
	<code>--secondary-node-eviction-rate</code> float32 Default: 0.01
	Number of nodes per second on which pods are deleted in case of node failure when a zone is unhealthy (see <code>--unhealthy-zone-threshold</code> for definition of healthy/unhealthy). Zone refers to entire cluster in non-multizone clusters. This value is implicitly overridden to 0 if the cluster size is smaller than <code>--large-cluster-size-threshold</code> .
	<code>--secure-port</code> int Default: 10257

	The port on which to serve HTTPS with authentication and authorization. If 0, don't serve HTTPS at all.
<code>--service-account-private-key-file</code> string	
	Filename containing a PEM-encoded private RSA or ECDSA key used to sign service account tokens.
<code>--service-cluster-ip-range</code> string	
	CIDR Range for Services in cluster. Requires <code>--allocate-node-cidrs</code> to be true
<code>--skip-headers</code>	
	If true, avoid header prefixes in the log messages
<code>--skip-log-headers</code>	
	If true, avoid headers when opening log files
<code>--stderrthreshold</code> severity <code>^ ^ ^ ^ ^</code> Default: 2	
	logs at or above this threshold go to stderr
<code>--terminated-pod-gc-threshold</code> int32 <code>^ ^ ^ ^ ^</code> Default: 12500	
	Number of terminated pods that can exist before the terminated pod garbage collector starts deleting terminated pods. If $\leq 0$ , the terminated pod garbage collector is disabled.
<code>--tls-cert-file</code> string	
	File containing the default x509 Certificate for HTTPS. (CA cert, if any, concatenated after server cert). If HTTPS serving is enabled, and <code>--tls-cert-file</code> and <code>--tls-private-key-file</code> are not provided, a self-signed certificate and key are generated for the public address and saved to the directory specified by <code>--cert-dir</code> .
<code>--tls-cipher-suites</code> stringSlice	
	Comma-separated list of cipher suites for the server. If omitted, the default Go cipher suites will be used. Possible values: TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA, TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256, TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256, TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA, TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384, TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305, TLS_ECDHE_ECDSA_WITH_RC4_128_SHA, TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA, TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA, TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256, TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256, TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA, TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384, TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305, TLS_ECDHE_RSA_WITH_RC4_128_SHA, TLS_RSA_WITH_3DES_EDE_CBC_SHA, TLS_RSA_WITH_AES_128_CBC_SHA, TLS_RSA_WITH_AES_128_CBC_SHA256, TLS_RSA_WITH_AES_128_GCM_SHA256, TLS_RSA_WITH_AES_256_CBC_SHA, TLS_RSA_WITH_AES_256_GCM_SHA384, TLS_RSA_WITH_RC4_128_SHA
<code>--tls-min-version</code> string	
	Minimum TLS version supported. Possible values: VersionTLS10, VersionTLS11, VersionTLS12, VersionTLS13

<code>--tls-private-key-file</code>	string
	File containing the default x509 private key matching <code>--tls-cert-file</code> .
<code>--tls-sni-cert-key</code>	namedCertKey[] Default: []
	A pair of x509 certificate and private key file paths, optionally suffixed with a list of domain patterns which are fully qualified domain names, possibly with prefixed wildcard segments. If no domain patterns are provided, the names of the certificate are extracted. Non-wildcard matches trump over wildcard matches, explicit domain patterns trump over extracted names. For multiple key/certificate pairs, use the <code>--tls-sni-cert-key</code> multiple times. Examples: "example.crt,example.key" or "foo.crt,foo.key:*.foo.com,foo.com".
<code>--unhealthy-zone-threshold</code>	float32[] Default: 0.55
	Fraction of Nodes in a zone which needs to be not Ready (minimum 3) for zone to be treated as unhealthy.
<code>--use-service-account-credentials</code>	
	If true, use individual service account credentials for each controller.
<code>-v, --v</code>	Level
	number for the log level verbosity
<code>--version</code>	version[=true]
	Print version information and quit
<code>--vmodule</code>	moduleSpec
	comma-separated list of pattern=N settings for file-filtered logging

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 12:39 PM PST by [regenerate ref docs, 1.17, script chgs \(#18067\)](#) ([Page History](#))

[Edit This Page](#)

# kube-proxy

- [Synopsis](#)
- [Options](#)

## Synopsis

The Kubernetes network proxy runs on each node. This reflects services as defined in the Kubernetes API on each node and can do simple TCP, UDP,

and SCTP stream forwarding or round robin TCP, UDP, and SCTP forwarding across a set of backends. Service cluster IPs and ports are currently found through Docker-links-compatible environment variables specifying ports opened by the service proxy. There is an optional addon that provides cluster DNS for these cluster IPs. The user must create a service with the apiserver API to configure the proxy.

kube-proxy [flags]

## Options

<code>--azure-container-registry-config</code>	string
Path to the file containing Azure container registry configuration information.	
<code>--bind-address</code>	0.0.0.0 Default: 0.0.0.0
The IP address for the proxy server to serve on (set to 0.0.0.0 for all IPv4 interfaces and `::` for all IPv6 interfaces)	
<code>--cleanup</code>	
If true cleanup iptables and ipvs rules and exit.	
<code>--cluster-cidr</code>	string
The CIDR range of pods in the cluster. When configured, traffic sent to a Service cluster IP from outside this range will be masqueraded and traffic sent from pods to an external LoadBalancer IP will be directed to the respective cluster IP instead	
<code>--config</code>	string
The path to the configuration file.	
<code>--config-sync-period</code>	duration Default: 15m0s
How often configuration from the apiserver is refreshed. Must be greater than 0.	
<code>--conntrack-max-per-core</code>	int32 Default: 32768
Maximum number of NAT connections to track per CPU core (0 to leave the limit as-is and ignore conntrack-min).	
<code>--conntrack-min</code>	int32 Default: 131072
Minimum number of conntrack entries to allocate, regardless of conntrack-max-per-core (set conntrack-max-per-core=0 to leave the limit as-is).	
<code>--conntrack-tcp-timeout-close-wait</code>	duration Default: 1h0m0s
NAT timeout for TCP connections in the CLOSE_WAIT state	
<code>--conntrack-tcp-timeout-established</code>	duration Default: 24h0m0s
Idle timeout for established TCP connections (0 to leave as-is)	
<code>--feature-gates</code>	mapStringBool

A set of key=value pairs that describe feature gates for alpha/experimental features. Options are:

APIListChunking=true|false (BETA - default=true)  
APIPriorityAndFairness=true|false (ALPHA - default=false)  
APIResponseCompression=true|false (BETA - default=true)  
AllAlpha=true|false (ALPHA - default=false)  
AllBeta=true|false (BETA - default=false)  
AllowInsecureBackendProxy=true|false (BETA - default=true)  
AppArmor=true|false (BETA - default=true)  
BalanceAttachedNodeVolumes=true|false (ALPHA - default=false)  
BlockVolume=true|false (BETA - default=true)  
BoundServiceAccountTokenVolume=true|false (ALPHA - default=false)  
CPUManager=true|false (BETA - default=true)  
CRIContainerLogRotation=true|false (BETA - default=true)  
CSIBlockVolume=true|false (BETA - default=true)  
CSIDriverRegistry=true|false (BETA - default=true)  
CSIInlineVolume=true|false (BETA - default=true)  
CSIMigration=true|false (BETA - default=true)  
CSIMigrationAWS=true|false (BETA - default=false)  
CSIMigrationAWSComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureDisk=true|false (ALPHA - default=false)  
CSIMigrationAzureDiskComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureFile=true|false (ALPHA - default=false)  
CSIMigrationAzureFileComplete=true|false (ALPHA - default=false)  
CSIMigrationGCE=true|false (BETA - default=false)  
CSIMigrationGCEComplete=true|false (ALPHA - default=false)  
CSIMigrationOpenStack=true|false (ALPHA - default=false)  
CSIMigrationOpenStackComplete=true|false (ALPHA - default=false)  
CustomCPUCFSQuotaPeriod=true|false (ALPHA - default=false)  
DevicePlugins=true|false (BETA - default=true)  
DryRun=true|false (BETA - default=true)  
DynamicAuditing=true|false (ALPHA - default=false)  
DynamicKubeletConfig=true|false (BETA - default=true)  
EndpointSlice=true|false (BETA - default=false)  
EphemeralContainers=true|false (ALPHA - default=false)  
EvenPodsSpread=true|false (ALPHA - default=false)  
ExpandCSIVolumes=true|false (BETA - default=true)  
ExpandInUsePersistentVolumes=true|false (BETA - default=true)  
ExpandPersistentVolumes=true|false (BETA - default=true)  
ExperimentalHostUserNamespaceDefaulting=true|false (BETA - default=false)  
HPAScaleToZero=true|false (ALPHA - default=false)  
HyperVContainer=true|false (ALPHA - default=false)  
IPv6DualStack=true|false (ALPHA - default=false)  
KubeletPodResources=true|false (BETA - default=true)  
LegacyNodeRoleBehavior=true|false (ALPHA - default=true)  
LocalStorageCapacityIsolation=true|false (BETA - default=true)  
LocalStorageCapacityIsolationFSQuotaMonitoring=true|false (ALPHA - default=false)  
NodeDisruptionExclusion=true|false (ALPHA - default=false)

--healthz-bind-address 0.0.0.0	Default: 0.0.0.0:10256
The IP address for the health check server to serve on (set to 0.0.0.0 for all IPv4 interfaces and `::` for all IPv6 interfaces)	
--healthz-port int32	Default: 10256
The port to bind the health check server. Use 0 to disable.	
-h, --help	
help for kube-proxy	
--hostname-override string	
If non-empty, will use this string as identification instead of the actual hostname.	
--iptables-masquerade-bit int32	Default: 14
If using the pure iptables proxy, the bit of the fwmark space to mark packets requiring SNAT with. Must be within the range [0, 31].	
--iptables-min-sync-period duration	
The minimum interval of how often the iptables rules can be refreshed as endpoints and services change (e.g. '5s', '1m', '2h22m').	
--iptables-sync-period duration	Default: 30s
The maximum interval of how often iptables rules are refreshed (e.g. '5s', '1m', '2h22m'). Must be greater than 0.	
--ipvs-exclude-cidrs stringSlice	
A comma-separated list of CIDR's which the ipvs proxier should not touch when cleaning up IPVS rules.	
--ipvs-min-sync-period duration	
The minimum interval of how often the ipvs rules can be refreshed as endpoints and services change (e.g. '5s', '1m', '2h22m').	
--ipvs-scheduler string	
The ipvs scheduler type when proxy mode is ipvs	
--ipvs-strict-arp	
Enable strict ARP by setting arp_ignore to 1 and arp_announce to 2	
--ipvs-sync-period duration	Default: 30s
The maximum interval of how often ipvs rules are refreshed (e.g. '5s', '1m', '2h22m'). Must be greater than 0.	
--kube-api-burst int32	Default: 10
Burst to use while talking with kubernetes apiserver	
--kube-api-content-type string	Default: "application/vnd.kubernetes.protobuf"
Content type of requests sent to apiserver.	
--kube-api-qps float32	Default: 5
QPS to use while talking with kubernetes apiserver	
--kubeconfig string	
Path to kubeconfig file with authorization information (the master location is set by the master flag).	
--log-flush-frequency duration	Default: 5s



	Maximum number of seconds between log flushes
<code>--masquerade-all</code>	
	If using the pure iptables proxy, SNAT all traffic sent via Service cluster IPs (this not commonly needed)
<code>--master string</code>	
	The address of the Kubernetes API server (overrides any value in kubeconfig)
<code>--metrics-bind-address 0.0.0.0</code> Default: 127.0.0.1:10249	
	The IP address for the metrics server to serve on (set to 0.0.0.0 for all IPv4 interfaces and `::` for all IPv6 interfaces)
<code>--metrics-port int32</code> Default: 10249	
	The port to bind the metrics server. Use 0 to disable.
<code>--nodeport-addresses stringSlice</code>	
	A string slice of values which specify the addresses to use for NodePorts. Values may be valid IP blocks (e.g. 1.2.3.0/24, 1.2.3.4/32). The default empty string slice ([]) means to use all local addresses.
<code>--oom-score-adj int32</code> Default: -999	
	The oom-score-adj value for kube-proxy process. Values must be within the range [-1000, 1000]
<code>--profiling</code>	
	If true enables profiling via web interface on /debug/pprof handler.
<code>--proxy-mode ProxyMode</code>	
	Which proxy mode to use: 'userspace' (older) or 'iptables' (faster) or 'ipvs'. If blank, use the best-available proxy (currently iptables). If the iptables proxy is selected, regardless of how, but the system's kernel or iptables versions are insufficient, this always falls back to the userspace proxy.
<code>--proxy-port-range port-range</code>	
	Range of host ports (beginPort-endPort, single port or beginPort+offset, inclusive) that may be consumed in order to proxy service traffic. If (unspecified, 0, or 0-0) then ports will be randomly chosen.
<code>--udp-timeout duration</code> Default: 250ms	
	How long an idle UDP connection will be kept open (e.g. '250ms', '2s'). Must be greater than 0. Only applicable for proxy-mode=userspace
<code>--version version[=true]</code>	
	Print version information and quit
<code>--write-config-to string</code>	
	If set, write the default configuration values to this file and exit.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 12:39 PM PST by [regenerate ref docs, 1.17, script chgs \(#18067\)](#) ([Page History](#))

[Edit This Page](#)

# kube-scheduler

- [Synopsis](#)
- [Options](#)

# Synopsis

The Kubernetes scheduler is a policy-rich, topology-aware, workload-specific function that significantly impacts availability, performance, and capacity. The scheduler needs to take into account individual and collective resource requirements, quality of service requirements, hardware/software/policy constraints, affinity and anti-affinity specifications, data locality, inter-workload interference, deadlines, and so on. Workload-specific requirements will be exposed through the API as necessary.

```
kube-scheduler [flags]
```

## Options

--add-dir-header	
	If true, adds the file directory to the header
--address string	Default: "0.0.0.0"
	DEPRECATED: the IP address on which to listen for the --port port (set to 0.0.0.0 for all IPv4 interfaces and :: for all IPv6 interfaces). See --bind-address instead.
--algorithm-provider string	
	DEPRECATED: the scheduling algorithm provider to use, one of: ClusterAutoscalerProvider   DefaultProvider
--alsologtostderr	
	log to standard error as well as files
--authentication-kubeconfig string	
	kubeconfig file pointing at the 'core' kubernetes server with enough rights to create tokenaccessreviews.authentication.k8s.io. This is optional. If empty, all token requests are considered to be anonymous and no client CA is looked up in the cluster.
--authentication-skip-lookup	
	If false, the authentication-kubeconfig will be used to lookup missing authentication configuration from the cluster.
--authentication-token-webhook-cache-ttl duration	Default: 10s
	The duration to cache responses from the webhook token authenticator.
--authentication-tolerate-lookup-failure	Default: true
	If true, failures to look up missing authentication configuration from the cluster are not considered fatal. Note that this can result in authentication that treats all requests as anonymous.
--authorization-always-allow-paths stringSlice	Default: [/healthz]
	A list of HTTP paths to skip during authorization, i.e. these are authorized without contacting the 'core' kubernetes server.
--authorization-kubeconfig string	

	kubeconfig file pointing at the 'core' kubernetes server with enough rights to create subjectaccessreviews.authorization.k8s.io. This is optional. If empty, all requests not skipped by authorization are forbidden.
--authorization-webhook-cache-authorized-ttl durationÂ Â Â Â Â Default: 10s	
	The duration to cache 'authorized' responses from the webhook authorizer.
--authorization-webhook-cache-unauthorized-ttl durationÂ Â Â Â Â Default: 10s	
	The duration to cache 'unauthorized' responses from the webhook authorizer.
--azure-container-registry-config string	
	Path to the file containing Azure container registry configuration information.
--bind-address ipÂ Â Â Â Â Default: 0.0.0.0	
	The IP address on which to listen for the --secure-port port. The associated interface(s) must be reachable by the rest of the cluster, and by CLI/web clients. If blank, all interfaces will be used (0.0.0.0 for all IPv4 interfaces and :: for all IPv6 interfaces).
--cert-dir string	
	The directory where the TLS certs are located. If --tls-cert-file and --tls-private-key-file are provided, this flag will be ignored.
--client-ca-file string	
	If set, any request presenting a client certificate signed by one of the authorities in the client-ca-file is authenticated with an identity corresponding to the CommonName of the client certificate.
--config string	
	The path to the configuration file. Flags override values in this file.
--contention-profilingÂ Â Â Â Â Default: true	
	DEPRECATED: enable lock contention profiling, if profiling is enabled
--feature-gates mapStringBool	

A set of key=value pairs that describe feature gates for alpha/experimental features. Options are:

APIListChunking=true|false (BETA - default=true)  
APIPriorityAndFairness=true|false (ALPHA - default=false)  
APIResponseCompression=true|false (BETA - default=true)  
AllAlpha=true|false (ALPHA - default=false)  
AllBeta=true|false (BETA - default=false)  
AllowInsecureBackendProxy=true|false (BETA - default=true)  
AppArmor=true|false (BETA - default=true)  
BalanceAttachedNodeVolumes=true|false (ALPHA - default=false)  
BlockVolume=true|false (BETA - default=true)  
BoundServiceAccountTokenVolume=true|false (ALPHA - default=false)  
CPUManager=true|false (BETA - default=true)  
CRIContainerLogRotation=true|false (BETA - default=true)  
CSIBlockVolume=true|false (BETA - default=true)  
CSIDriverRegistry=true|false (BETA - default=true)  
CSIInlineVolume=true|false (BETA - default=true)  
CSIMigration=true|false (BETA - default=true)  
CSIMigrationAWS=true|false (BETA - default=false)  
CSIMigrationAWSComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureDisk=true|false (ALPHA - default=false)  
CSIMigrationAzureDiskComplete=true|false (ALPHA - default=false)  
CSIMigrationAzureFile=true|false (ALPHA - default=false)  
CSIMigrationAzureFileComplete=true|false (ALPHA - default=false)  
CSIMigrationGCE=true|false (BETA - default=false)  
CSIMigrationGCEComplete=true|false (ALPHA - default=false)  
CSIMigrationOpenStack=true|false (ALPHA - default=false)  
CSIMigrationOpenStackComplete=true|false (ALPHA - default=false)  
CustomCPUCFSQuotaPeriod=true|false (ALPHA - default=false)  
DevicePlugins=true|false (BETA - default=true)  
DryRun=true|false (BETA - default=true)  
DynamicAuditing=true|false (ALPHA - default=false)  
DynamicKubeletConfig=true|false (BETA - default=true)  
EndpointSlice=true|false (BETA - default=false)  
EphemeralContainers=true|false (ALPHA - default=false)  
EvenPodsSpread=true|false (ALPHA - default=false)  
ExpandCSIVolumes=true|false (BETA - default=true)  
ExpandInUsePersistentVolumes=true|false (BETA - default=true)  
ExpandPersistentVolumes=true|false (BETA - default=true)  
ExperimentalHostUserNamespaceDefaulting=true|false (BETA - default=false)  
HPAScaleToZero=true|false (ALPHA - default=false)  
HyperVContainer=true|false (ALPHA - default=false)  
IPv6DualStack=true|false (ALPHA - default=false)  
KubeletPodResources=true|false (BETA - default=true)  
LegacyNodeRoleBehavior=true|false (ALPHA - default=true)  
LocalStorageCapacityIsolation=true|false (BETA - default=true)  
LocalStorageCapacityIsolationFSQuotaMonitoring=true|false (ALPHA - default=false)  
NodeDisruptionExclusion=true|false (ALPHA - default=false)

--hard-pod-affinity-symmetric-weight int32	Default: 1
DEPRECATED: RequiredDuringScheduling affinity is not symmetric, but there is an implicit PreferredDuringScheduling affinity rule corresponding to every RequiredDuringScheduling affinity rule. --hard-pod-affinity-symmetric-weight represents the weight of implicit PreferredDuringScheduling affinity rule. Must be in the range 0-100. This option was moved to the policy configuration file	
-h, --help	
help for kube-scheduler	
--http2-max-streams-per-connection int	
The limit that the server gives to clients for the maximum number of streams in an HTTP/2 connection. Zero means to use golang's default.	
--kube-api-burst int32	Default: 100
DEPRECATED: burst to use while talking with kubernetes apiserver	
--kube-api-content-type string	Default: "application/vnd.kubernetes.protobuf"
DEPRECATED: content type of requests sent to apiserver.	
--kube-api-qps float32	Default: 50
DEPRECATED: QPS to use while talking with kubernetes apiserver	
--kubeconfig string	
DEPRECATED: path to kubeconfig file with authorization and master location information.	
--leader-elect	Default: true
Start a leader election client and gain leadership before executing the main loop. Enable this when running replicated components for high availability.	
--leader-elect-lease-duration duration	Default: 15s
The duration that non-leader candidates will wait after observing a leadership renewal until attempting to acquire leadership of a led but unrenewed leader slot. This is effectively the maximum duration that a leader can be stopped before it is replaced by another candidate. This is only applicable if leader election is enabled.	
--leader-elect-renew-deadline duration	Default: 10s
The interval between attempts by the acting master to renew a leadership slot before it stops leading. This must be less than or equal to the lease duration. This is only applicable if leader election is enabled.	
--leader-elect-resource-lock endpoints	Default: "endpointsleases"
The type of resource object that is used for locking during leader election. Supported options are endpoints (default) and `configmaps`.	
--leader-elect-resource-name string	Default: "kube-scheduler"
The name of resource object that is used for locking during leader election.	
--leader-elect-resource-namespace string	Default: "kube-system"

The namespace of resource object that is used for locking during leader election.
--leader-elect-retry-period durationÂ Â Â Â Â Default: 2s
The duration the clients should wait between attempting acquisition and renewal of a leadership. This is only applicable if leader election is enabled.
--lock-object-name stringÂ Â Â Â Â Default: "kube-scheduler"
DEPRECATED: define the name of the lock object. Will be removed in favor of leader-elect-resource-name
--lock-object-namespace stringÂ Â Â Â Â Default: "kube-system"
DEPRECATED: define the namespace of the lock object. Will be removed in favor of leader-elect-resource-namespace.
--log-backtrace-at traceLocationÂ Â Â Â Â Default: :0
when logging hits line file:N, emit a stack trace
--log-dir string
If non-empty, write log files in this directory
--log-file string
If non-empty, use this log file
--log-file-max-size uintÂ Â Â Â Â Default: 1800
Defines the maximum size a log file can grow to. Unit is megabytes. If the value is 0, the maximum file size is unlimited.
--log-flush-frequency durationÂ Â Â Â Â Default: 5s
Maximum number of seconds between log flushes
--logtostderrÂ Â Â Â Â Default: true
log to standard error instead of files
--master string
The address of the Kubernetes API server (overrides any value in kubeconfig)
--policy-config-file string
DEPRECATED: file with scheduler policy configuration. This file is used if policy ConfigMap is not provided or --use-legacy-policy-config=true
--policy-configmap string
DEPRECATED: name of the ConfigMap object that contains scheduler's policy configuration. It must exist in the system namespace before scheduler initialization if --use-legacy-policy-config=false. The config must be provided as the value of an element in 'Data' map with the key='policy.cfg'
--policy-configmap-namespace stringÂ Â Â Â Â Default: "kube-system"
DEPRECATED: the namespace where policy ConfigMap is located. The kube-system namespace will be used if this is not provided or is empty.
--port intÂ Â Â Â Â Default: 10251
DEPRECATED: the port on which to serve HTTP insecurely without authentication and authorization. If 0, don't serve plain HTTP at all. See --secure-port instead.

--profiling	Default: true
DEPRECATED: enable profiling via web interface host:port/debug/pprof/	
--requestheader-allowed-names stringSlice	
List of client certificate common names to allow to provide usernames in headers specified by --requestheader-username-headers. If empty, any client certificate validated by the authorities in --requestheader-client-ca-file is allowed.	
--requestheader-client-ca-file string	
Root certificate bundle to use to verify client certificates on incoming requests before trusting usernames in headers specified by --requestheader-username-headers. WARNING: generally do not depend on authorization being already done for incoming requests.	
--requestheader-extra-headers-prefix stringSlice	
Default: [x-remote-extra-]	
List of request header prefixes to inspect. X-Remote-Extra- is suggested.	
--requestheader-group-headers stringSlice	
Default: [x-remote-group]	
List of request headers to inspect for groups. X-Remote-Group is suggested.	
--requestheader-username-headers stringSlice	
Default: [x-remote-user]	
List of request headers to inspect for usernames. X-Remote-User is common.	
--scheduler-name string	
Default: "default-scheduler"	
DEPRECATED: name of the scheduler, used to select which pods will be processed by this scheduler, based on pod's "spec.schedulerName".	
--secure-port int	
Default: 10259	
The port on which to serve HTTPS with authentication and authorization. If 0, don't serve HTTPS at all.	
--skip-headers	
If true, avoid header prefixes in the log messages	
--skip-log-headers	
If true, avoid headers when opening log files	
--stderrthreshold severity	
Default: 2	
logs at or above this threshold go to stderr	
--tls-cert-file string	
File containing the default x509 Certificate for HTTPS. (CA cert, if any, concatenated after server cert). If HTTPS serving is enabled, and --tls-cert-file and --tls-private-key-file are not provided, a self-signed certificate and key are generated for the public address and saved to the directory specified by --cert-dir.	
--tls-cipher-suites stringSlice	



Comma-separated list of cipher suites for the server. If omitted, the default Go cipher suites will be use. Possible values: TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_RC4_128_SHA,TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_RC4_128_SHA,TLS_RSA_WITH_3DES_EDE_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA256,TLS_RSA_WITH_AES_128_GCM_SHA256,TLS_RSA_WITH_AES_256_CBC_SHA,TLS_RSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_RC4_128_SHA
--tls-min-version string
Minimum TLS version supported. Possible values: VersionTLS10, VersionTLS11, VersionTLS12, VersionTLS13
--tls-private-key-file string
File containing the default x509 private key matching --tls-cert-file.
--tls-sni-cert-key namedCertKeyÂ Â Â Â Â Default: []
A pair of x509 certificate and private key file paths, optionally suffixed with a list of domain patterns which are fully qualified domain names, possibly with prefixed wildcard segments. If no domain patterns are provided, the names of the certificate are extracted. Non-wildcard matches trump over wildcard matches, explicit domain patterns trump over extracted names. For multiple key/certificate pairs, use the --tls-sni-cert-key multiple times. Examples: "example.crt,example.key" or "foo.crt,foo.key:*.foo.com,foo.com".
--use-legacy-policy-config
DEPRECATED: when set to true, scheduler will ignore policy ConfigMap and uses policy config file
-v, --v Level
number for the log level verbosity
--version version[=true]
Print version information and quit
--vmodule moduleSpec
comma-separated list of pattern=N settings for file-filtered logging
--write-config-to string
If set, write the configuration values to this file and exit.

# Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 12:39 PM PST by [regenerate ref docs, 1.17, script chgs \(#18067\)](#) ([Page History](#))

[Edit This Page](#)

# kubelet

- [Synopsis](#)
- [Options](#)

## Synopsis

The kubelet is the primary "node agent" that runs on each node. It can register the node with the apiserver using one of: the hostname; a flag to override the hostname; or specific logic for a cloud provider.

The kubelet works in terms of a PodSpec. A PodSpec is a YAML or JSON object that describes a pod. The kubelet takes a set of PodSpecs that are provided through various mechanisms (primarily through the apiserver) and ensures that the containers described in those PodSpecs are running and healthy. The kubelet doesn't manage containers which were not created by Kubernetes.

Other than from an PodSpec from the apiserver, there are three ways that a container manifest can be provided to the Kubelet.

File: Path passed as a flag on the command line. Files under this path will be monitored periodically for updates. The monitoring period is 20s by default and is configurable via a flag.

HTTP endpoint: HTTP endpoint passed as a parameter on the command line. This endpoint is checked every 20 seconds (also configurable with a flag).

HTTP server: The kubelet can also listen for HTTP and respond to a simple API (underspec'd currently) to submit a new manifest.

```
kubelet [flags]
```

## Options

--add-dir-header	
	If true, adds the file directory to the header
--address 0.0.0.0	
	The IP address for the Kubelet to serve on (set to 0.0.0.0 for all IPv4 interfaces and `::` for all IPv6 interfaces) (default 0.0.0.0) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--allowed-unsafe-sysctls strings	

Comma-separated whitelist of unsafe sysctls or unsafe sysctl patterns (ending in *). Use these at your own risk. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--alsologtostderr
log to standard error as well as files
--anonymous-auth
Enables anonymous requests to the Kubelet server. Requests that are not rejected by another authentication method are treated as anonymous requests. Anonymous requests have a username of system:anonymous, and a group name of system:unauthenticated. (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--application-metrics-count-limit int
Max number of application metrics to store (per container) (default 100) (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--authentication-token-webhook
Use the TokenReview API to determine authentication for bearer tokens. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--authentication-token-webhook-cache-ttl duration
The duration to cache responses from the webhook token authenticator. (default 2m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--authorization-mode string
Authorization mode for Kubelet server. Valid options are AlwaysAllow or Webhook. Webhook mode uses the SubjectAccessReview API to determine authorization. (default "AlwaysAllow") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--authorization-webhook-cache-authorized-ttl duration
The duration to cache 'authorized' responses from the webhook authorizer. (default 5m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--authorization-webhook-cache-unauthorized-ttl duration

	The duration to cache 'unauthorized' responses from the webhook authorizer. (default 30s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--azure-container-registry-config string</b>	
	Path to the file container Azure container registry configuration information.
<b>--boot-id-file string</b>	
	Comma-separated list of files to check for boot-id. Use the first one that exists. (default "/proc/sys/kernel/random/boot_id") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--bootstrap-checkpoint-path string</b>	
	Path to the directory where the checkpoints are stored
<b>--bootstrap-kubeconfig string</b>	
	Path to a kubeconfig file that will be used to get client certificate for kubelet. If the file specified by --kubeconfig does not exist, the bootstrap kubeconfig is used to request a client certificate from the API server. On success, a kubeconfig file referencing the generated client certificate and key is written to the path specified by --kubeconfig. The client certificate and key file will be stored in the directory pointed by --cert-dir.
<b>--cert-dir string</b>	
	The directory where the TLS certs are located. If --tls-cert-file and --tls-private-key-file are provided, this flag will be ignored. (default "/var/lib/kubelet/pki")
<b>--cgroup-driver string</b>	
	Driver that the kubelet uses to manipulate cgroups on the host. Possible values: 'cgroupfs', 'systemd' (default "cgroupfs") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--cgroup-root string</b>	
	Optional root cgroup to use for pods. This is handled by the container runtime on a best effort basis. Default: "", which means use the container runtime default. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--cgroups-per-qos</b>	

Enable creation of QoS cgroup hierarchy, if true top level QoS and pod cgroups are created. (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--chaos-chance float
If > 0.0, introduce random client errors and latency. Intended for testing.
--client-ca-file string
If set, any request presenting a client certificate signed by one of the authorities in the client-ca-file is authenticated with an identity corresponding to the CommonName of the client certificate. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--cloud-config string
The path to the cloud provider configuration file.
--cloud-provider string
The provider for cloud services. Specify empty string for running with no cloud provider. If set, the cloud provider determines the name of the node (consult cloud provider documentation to determine if and how the hostname is used).
--cluster-dns strings
Comma-separated list of DNS server IP address. This value is used for containers DNS server in case of Pods with "dnsPolicy=ClusterFirst". Note: all DNS servers appearing in the list MUST serve the same set of records otherwise name resolution within the cluster may not work correctly. There is no guarantee as to which DNS server may be contacted for name resolution. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--cluster-domain string
Domain for this cluster. If set, kubelet will configure all containers to search this domain in addition to the host's search domains (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--cni-bin-dir string
A comma-separated list of full paths of directories in which to search for CNI plugin binaries. This docker-specific flag only works when container-runtime is set to docker. (default "/opt/cni/bin")
--cni-cache-dir string
The full path of the directory in which CNI should store cache files. This docker-specific flag only works when container-runtime is set to docker. (default "/var/lib/cni/cache")

<b>--cni-conf-dir string</b>	
	The full path of the directory in which to search for CNI config files. This docker-specific flag only works when container-runtime is set to docker. (default "/etc/cni/net.d")
<b>--config string</b>	
	The Kubelet will load its initial configuration from this file. The path may be absolute or relative; relative paths start at the Kubelet's current working directory. Omit this flag to use the built-in default configuration values. Command-line flags override configuration from this file.
<b>--container-hints string</b>	
	location of the container hints file (default "/etc/cadvisor/container_hints.json") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--container-log-max-files int32</b>	
	Set the maximum number of container log files that can be present for a container. The number must be $\geq 2$ . This flag can only be used with --container-runtime=remote. (default 5) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--container-log-max-size string</b>	
	Set the maximum size (e.g. 10Mi) of container log file before it is rotated. This flag can only be used with --container-runtime=remote. (default "10Mi") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--container-runtime string</b>	
	The container runtime to use. Possible values: 'docker', 'remote', 'rkt(deprecated)'. (default "docker")
<b>--container-runtime-endpoint string</b>	
	[Experimental] The endpoint of remote runtime service. Currently unix socket endpoint is supported on Linux, while npipe and tcp endpoints are supported on windows. Examples: 'unix:///var/run/dockershim.sock', 'npipe:///./pipe/dockershim' (default "unix:///var/run/dockershim.sock")
<b>--containerd string</b>	
	containerd endpoint (default "/run/containerd/containerd.sock") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--contention-profiling</b>	
	Enable lock contention profiling, if profiling is enabled (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)

<b>--cpu-cfs-quota</b>	
	Enable CPU CFS quota enforcement for containers that specify CPU limits (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--cpu-cfs-quota-period duration</b>	
	Sets CPU CFS quota period value, <code>cpu.cfs_period_us</code> , defaults to Linux Kernel default (default 100ms) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--cpu-manager-policy string</b>	
	CPU Manager policy to use. Possible values: 'none', 'static'. Default: 'none' (default "none") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--cpu-manager-reconcile-period NodeStatusUpdateFrequency</b>	
	CPU Manager reconciliation period. Examples: '10s', or '1m'. If not supplied, defaults to NodeStatusUpdateFrequency (default 10s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--docker string</b>	
	docker endpoint (default "unix:///var/run/docker.sock") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--docker-endpoint string</b>	
	Use this for the docker endpoint to communicate with. This docker-specific flag only works when container-runtime is set to docker. (default "unix:///var/run/docker.sock")
<b>--docker-env-metadata-whitelist string</b>	
	a comma-separated list of environment variable keys that needs to be collected for docker containers (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--docker-only</b>	
	Only report docker containers in addition to root stats (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--docker-root string</b>	
	DEPRECATED: docker root is read from docker info (this is a fallback, default: /var/lib/docker) (default "/var/lib/docker")



<code>--docker-tls</code>	
	use TLS to connect to docker (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--docker-tls-ca string</code>	
	path to trusted CA (default "ca.pem") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--docker-tls-cert string</code>	
	path to client certificate (default "cert.pem") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--docker-tls-key string</code>	
	path to private key (default "key.pem") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--dynamic-config-dir string</code>	
	The Kubelet will use this directory for checkpointing downloaded configurations and tracking configuration health. The Kubelet will create this directory if it does not already exist. The path may be absolute or relative; relative paths start at the Kubelet's current working directory. Providing this flag enables dynamic Kubelet configuration. The DynamicKubeletConfig feature gate must be enabled to pass this flag; this gate currently defaults to true because the feature is beta.
<code>--enable-cadvisor-json-endpoints</code>	
	Enable cAdvisor json /spec and /stats/* endpoints. (default true)
<code>--enable-controller-attach-detach</code>	
	Enables the Attach/Detach controller to manage attachment/detachment of volumes scheduled to this node, and disables kubelet from executing any attach/detach operations (default true)
<code>--enable-debugging-handlers</code>	
	Enables server endpoints for log collection and local running of containers and commands (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--enable-load-reader</code>	
	Whether to enable cpu load reader (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--enable-server</code>	

Enable the Kubelet's server (default true)
<code>--enforce-node-allocatable</code> stringSlice
A comma separated list of levels of node allocatable enforcement to be enforced by kubelet. Acceptable options are 'none', 'pods', 'system-reserved', and 'kube-reserved'. If the latter two options are specified, '--system-reserved-cgroup' and '--kube-reserved-cgroup' must also be set, respectively. If 'none' is specified, no additional options should be set. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/reserve-compute-resources/">https://kubernetes.io/docs/tasks/administer-cluster/reserve-compute-resources/</a> for more details. (default [pods]) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--event-burst</code> int32
Maximum size of a bursty event records, temporarily allows event records to burst to this number, while still not exceeding event-qps. Only used if --event-qps > 0 (default 10) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--event-qps</code> int32
If > 0, limit event creations per second to this value. If 0, unlimited. (default 5) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--event-storage-age-limit</code> string
Max length of time for which to store events (per type). Value is a comma separated list of key values, where the keys are event types (e.g.: creation, oom) or "default" and the value is a duration. Default is applied to all non-specified event types (default "default=0") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--event-storage-event-limit</code> string
Max number of events to store (per type). Value is a comma separated list of key values, where the keys are event types (e.g.: creation, oom) or "default" and the value is an integer. Default is applied to all non-specified event types (default "default=0") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--eviction-hard</code> mapStringString

<p>A set of eviction thresholds (e.g. <code>memory.available&lt;1Gi</code>) that if met would trigger a pod eviction. (default <code>imagefs.available&lt;15%,memory.available&lt;100Mi,nodefs.available&lt;10%,nodefs.inodesFree&lt;5%</code>) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)</p>
<p><code>--eviction-max-pod-grace-period</code> int32</p>
<p>Maximum allowed grace period (in seconds) to use when terminating pods in response to a soft eviction threshold being met. If negative, defer to pod specified value. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)</p>
<p><code>--eviction-minimum-reclaim</code> mapStringString</p>
<p>A set of minimum reclaims (e.g. <code>imagefs.available=2Gi</code>) that describes the minimum amount of resource the kubelet will reclaim when performing a pod eviction if that resource is under pressure. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)</p>
<p><code>--eviction-pressure-transition-period</code> duration</p>
<p>Duration for which the kubelet has to wait before transitioning out of an eviction pressure condition. (default 5m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)</p>
<p><code>--eviction-soft</code> mapStringString</p>
<p>A set of eviction thresholds (e.g. <code>memory.available&lt;1.5Gi</code>) that if met over a corresponding grace period would trigger a pod eviction. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)</p>
<p><code>--eviction-soft-grace-period</code> mapStringString</p>
<p>A set of eviction grace periods (e.g. <code>memory.available=1m30s</code>) that correspond to how long a soft eviction threshold must hold before triggering a pod eviction. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)</p>
<p><code>--exit-on-lock-contention</code></p>
<p>Whether kubelet should exit upon lock-file contention.</p>
<p><code>--experimental-allocatable-ignore-eviction</code></p>

When set to 'true', Hard Eviction Thresholds will be ignored while calculating Node Allocatable. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/reserve-compute-resources/">https://kubernetes.io/docs/tasks/administer-cluster/reserve-compute-resources/</a> for more details. [default=false]
--experimental-bootstrap-kubeconfig string
(DEPRECATED: Use --bootstrap-kubeconfig)
--experimental-check-node-capabilities-before-mount
[Experimental] if set true, the kubelet will check the underlying node for required components (binaries, etc.) before performing the mount
--experimental-kernel-memcg-notification
If enabled, the kubelet will integrate with the kernel memcg notification to determine if memory eviction thresholds are crossed rather than polling.
--experimental-mounter-path string
[Experimental] Path of mounter binary. Leave empty to use the default mount.
--fail-swap-on
Makes the Kubelet fail to start if swap is enabled on the node. (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--feature-gates mapStringBool

A set of key=value pairs that describe feature gates for alpha/experimental features. Options are:

APIListChunking=true|false (BETA - default=true)  
APIResponseCompression=true|false (BETA - default=true)  
AllAlpha=true|false (ALPHA - default=false)  
AppArmor=true|false (BETA - default=true)  
AttachVolumeLimit=true|false (BETA - default=true)  
BalanceAttachedNodeVolumes=true|false (ALPHA - default=false)  
BlockVolume=true|false (BETA - default=true)  
BoundServiceAccountTokenVolume=true|false (ALPHA - default=false)  
CPUManager=true|false (BETA - default=true)  
CRIContainerLogRotation=true|false (BETA - default=true)  
CSIBlockVolume=true|false (BETA - default=true)  
CSIDriverRegistry=true|false (BETA - default=true)  
CSIInlineVolume=true|false (BETA - default=true)  
CSIMigration=true|false (ALPHA - default=false)  
CSIMigrationAWS=true|false (ALPHA - default=false)  
CSIMigrationAzureDisk=true|false (ALPHA - default=false)  
CSIMigrationAzureFile=true|false (ALPHA - default=false)  
CSIMigrationGCE=true|false (ALPHA - default=false)  
CSIMigrationOpenStack=true|false (ALPHA - default=false)  
CSINodeInfo=true|false (BETA - default=true)  
CustomCPUCFSQuotaPeriod=true|false (ALPHA - default=false)  
CustomResourceDefaulting=true|false (BETA - default=true)  
DevicePlugins=true|false (BETA - default=true)  
DryRun=true|false (BETA - default=true)  
DynamicAuditing=true|false (ALPHA - default=false)  
DynamicKubeletConfig=true|false (BETA - default=true)  
EndpointSlice=true|false (ALPHA - default=false)  
EphemeralContainers=true|false (ALPHA - default=false)  
EvenPodsSpread=true|false (ALPHA - default=false)  
ExpandCSIVolumes=true|false (BETA - default=true)  
ExpandInUsePersistentVolumes=true|false (BETA - default=true)  
ExpandPersistentVolumes=true|false (BETA - default=true)  
ExperimentalHostUserNamespaceDefaulting=true|false (BETA - default=false)  
HPAScaleToZero=true|false (ALPHA - default=false)  
HyperVContainer=true|false (ALPHA - default=false)  
IPv6DualStack=true|false (ALPHA - default=false)  
KubeletPodResources=true|false (BETA - default=true)  
LegacyNodeRoleBehavior=true|false (ALPHA - default=true)  
LocalStorageCapacityIsolation=true|false (BETA - default=true)  
LocalStorageCapacityIsolationFSQuotaMonitoring=true|false (ALPHA - default=false)  
MountContainers=true|false (ALPHA - default=false)  
NodeDisruptionExclusion=true|false (ALPHA - default=false)  
NodeLease=true|false (BETA - default=true)  
NonPreemptingPriority=true|false (ALPHA - default=false)  
PodOverhead=true|false (ALPHA - default=false)  
PodShareProcessNamespace=true|false (BETA - default=true)

<b>--file-check-frequency duration</b>	
	Duration between checking config files for new data (default 20s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--global-housekeeping-interval duration</b>	
	Interval between global housekeepings (default 1m0s) (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<b>--hairpin-mode string</b>	
	How should the kubelet setup hairpin NAT. This allows endpoints of a Service to loadbalance back to themselves if they should try to access their own Service. Valid values are "promiscuous-bridge", "hairpin-veth" and "none". (default "promiscuous-bridge") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--healthz-bind-address 0.0.0.0</b>	
	The IP address for the healthz server to serve on (set to 0.0.0.0 for all IPv4 interfaces and `::` for all IPv6 interfaces) (default 127.0.0.1) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--healthz-port int32</b>	
	The port of the localhost healthz endpoint (set to 0 to disable) (default 10248) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>-h, --help</b>	
	help for kubelet
<b>--hostname-override string</b>	
	If non-empty, will use this string as identification instead of the actual hostname. If --cloud-provider is set, the cloud provider determines the name of the node (consult cloud provider documentation to determine if and how the hostname is used).
<b>--housekeeping-interval duration</b>	
	Interval between container housekeepings (default 10s)
<b>--http-check-frequency duration</b>	
	Duration between checking http for new data (default 20s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--image-gc-high-threshold int32</b>	

	The percent of disk usage after which image garbage collection is always run. Values must be within the range [0, 100], To disable image garbage collection, set to 100. (default 85) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--image-gc-low-threshold int32</code>	
	The percent of disk usage before which image garbage collection is never run. Lowest disk usage to garbage collect to. Values must be within the range [0, 100] and should not be larger than that of --image-gc-high-threshold. (default 80) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--image-pull-progress-deadline duration</code>	
	If no pulling progress is made before this deadline, the image pulling will be cancelled. This docker-specific flag only works when container-runtime is set to docker. (default 1m0s)
<code>--image-service-endpoint string</code>	
	[Experimental] The endpoint of remote image service. If not specified, it will be the same with container-runtime-endpoint by default. Currently unix socket endpoint is supported on Linux, while npipe and tcp endpoints are supported on windows. Examples: 'unix:///var/run/dockershim.sock', 'npipe:///./pipe/dockershim'
<code>--iptables-drop-bit int32</code>	
	The bit of the fwmark space to mark packets for dropping. Must be within the range [0, 31]. (default 15) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--iptables-masquerade-bit int32</code>	
	The bit of the fwmark space to mark packets for SNAT. Must be within the range [0, 31]. Please match this parameter with corresponding parameter in kube-proxy. (default 14) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--keep-terminated-pod-volumes</code>	
	Keep terminated pod volumes mounted to the node after the pod terminates. Can be useful for debugging volume related issues. (DEPRECATED: will be removed in a future version)
<code>--kube-api-burst int32</code>	

Burst to use while talking with kubernetes apiserver (default 10) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--kube-api-content-type string
Content type of requests sent to apiserver. (default "application/vnd.kubernetes.protobuf") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--kube-api-qps int32
QPS to use while talking with kubernetes apiserver (default 5) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--kube-reserved mapStringString
A set of ResourceName=ResourceQuantity (e.g. cpu=200m,memory=500Mi,ephemeral-storage=1Gi) pairs that describe resources reserved for kubernetes system components. Currently cpu, memory and local ephemeral storage for root file system are supported. See <a href="http://kubernetes.io/docs/user-guide/compute-resources">http://kubernetes.io/docs/user-guide/compute-resources</a> for more detail. [default=none] (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--kube-reserved-cgroup string
Absolute name of the top level cgroup that is used to manage kubernetes components for which compute resources were reserved via '--kube-reserved' flag. Ex. '/kube-reserved'. [default=""] (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--kubeconfig string
Path to a kubeconfig file, specifying how to connect to the API server. Providing --kubeconfig enables API server mode, omitting --kubeconfig enables standalone mode.
--kubelet-cgroups string
Optional absolute name of cgroups to create and run the Kubelet in. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--lock-file string
The path to file for kubelet to use as a lock file.
--log-backtrace-at traceLocation
when logging hits line file:N, emit a stack trace (default :0)



<code>--log-cadvisor-usage</code>	
	Whether to log the usage of the cAdvisor container (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--log-dir string</code>	
	If non-empty, write log files in this directory
<code>--log-file string</code>	
	If non-empty, use this log file
<code>--log-file-max-size uint</code>	
	Defines the maximum size a log file can grow to. Unit is megabytes. If the value is 0, the maximum file size is unlimited. (default 1800)
<code>--log-flush-frequency duration</code>	
	Maximum number of seconds between log flushes (default 5s)
<code>--logtostderr</code>	
	log to standard error instead of files (default true)
<code>--machine-id-file string</code>	
	Comma-separated list of files to check for machine-id. Use the first one that exists. (default "/etc/machine-id,/var/lib/dbus/machine-id") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
<code>--make-iptables-util-chains</code>	
	If true, kubelet will ensure iptables utility rules are present on host. (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--manifest-url string</code>	
	URL for accessing additional Pod specifications to run (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--manifest-url-header --manifest-url-header 'a:hello,b:again,c:world' --manifest-url-header 'b:beautiful'</code>	
	Comma-separated list of HTTP headers to use when accessing the url provided to <code>--manifest-url</code> . Multiple headers with the same name will be added in the same order provided. This flag can be repeatedly invoked. For example: <code>--manifest-url-header 'a:hello,b:again,c:world' --manifest-url-header 'b:beautiful'</code> (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's <code>--config</code> flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<code>--master-service-namespace string</code>	

	The namespace from which the kubernetes master services should be injected into pods (default "default") (DEPRECATED: This flag will be removed in a future version.)
<b>--max-open-files int</b>	
	Number of files that can be opened by Kubelet process. (default 1000000) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--max-pods int32</b>	
	Number of Pods that can run on this Kubelet. (default 110) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--maximum-dead-containers int32</b>	
	Maximum number of old instances of containers to retain globally. Each container takes up some disk space. To disable, set to a negative number. (default -1) (DEPRECATED: Use --eviction-hard or --eviction-soft instead. Will be removed in a future version.)
<b>--maximum-dead-containers-per-container int32</b>	
	Maximum number of old instances to retain per container. Each container takes up some disk space. (default 1) (DEPRECATED: Use --eviction-hard or --eviction-soft instead. Will be removed in a future version.)
<b>--minimum-container-ttl-duration duration</b>	
	Minimum age for a finished container before it is garbage collected. Examples: '300ms', '10s' or '2h45m' (DEPRECATED: Use --eviction-hard or --eviction-soft instead. Will be removed in a future version.)
<b>--minimum-image-ttl-duration duration</b>	
	Minimum age for an unused image before it is garbage collected. Examples: '300ms', '10s' or '2h45m'. (default 2m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--network-plugin string</b>	
	The name of the network plugin to be invoked for various events in kubelet/pod lifecycle. This docker-specific flag only works when container-runtime is set to docker.
<b>--network-plugin-mtu int32</b>	
	The MTU to be passed to the network plugin, to override the default. Set to 0 to use the default 1460 MTU. This docker-specific flag only works when container-runtime is set to docker.
<b>--node-ip string</b>	
	IP address of the node. If set, kubelet will use this IP address for the node
<b>--node-labels mapStringString</b>	

Labels to add when registering the node in the cluster. Labels must be key=value pairs separated by ','. Labels in the 'kubernetes.io' namespace must begin with an allowed prefix (kubelet.kubernetes.io, node.kubernetes.io) or be in the specifically allowed set (beta.kubernetes.io/arch, beta.kubernetes.io/instance-type, beta.kubernetes.io/os, failure-domain.beta.kubernetes.io/region, failure-domain.beta.kubernetes.io/zone, failure-domain.kubernetes.io/region, failure-domain.kubernetes.io/zone, kubernetes.io/arch, kubernetes.io/hostname, kubernetes.io/instance-type, kubernetes.io/os)
--node-status-max-images int32
The maximum number of images to report in Node.Status.Images. If -1 is specified, no cap will be applied. (default 50)
--node-status-update-frequency duration
Specifies how often kubelet posts node status to master. Note: be cautious when changing the constant, it must work with nodeMonitorGracePeriod in nodecontroller. (default 10s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--non-masquerade-cidr string
Traffic to IPs outside this range will use IP masquerade. Set to '0.0.0.0/0' to never masquerade. (default "10.0.0.0/8") (DEPRECATED: will be removed in a future version)
--oom-score-adj int32
The oom-score-adj value for kubelet process. Values must be within the range [-1000, 1000] (default -999) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--pod-cidr string
The CIDR to use for pod IP addresses, only used in standalone mode. In cluster mode, this is obtained from the master. For IPv6, the maximum number of IP's allocated is 65536 (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--pod-infra-container-image string
The image whose network/ipc namespaces containers in each pod will use. This docker-specific flag only works when container-runtime is set to docker. (default "k8s.gcr.io/pause:3.1")
--pod-manifest-path string

	Path to the directory containing static pod files to run, or the path to a single static pod file. Files starting with dots will be ignored. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--pod-max-pids int</b>	
	Set the maximum number of processes per pod. If -1, the kubelet defaults to the node allocatable pid capacity. (default -1) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--pods-per-core int32</b>	
	Number of Pods per core that can run on this Kubelet. The total number of Pods on this Kubelet cannot exceed max-pods, so max-pods will be used if this calculation results in a larger number of Pods allowed on the Kubelet. A value of 0 disables this limit. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--port int32</b>	
	The port for the Kubelet to serve on. (default 10250) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--protect-kernel-defaults</b>	
	Default kubelet behaviour for kernel tuning. If set, kubelet errors if any of kernel tunables is different than kubelet defaults. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--provider-id string</b>	
	Unique identifier for identifying the node in a machine database, i.e cloudprovider
<b>--qos-reserved mapStringString</b>	
	A set of ResourceName=Percentage (e.g. memory=50%) pairs that describe how pod resource requests are reserved at the QoS level. Currently only memory is supported. Requires the QOSReserved feature gate to be enabled. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--read-only-port int32</b>	

	The read-only port for the Kubelet to serve on with no authentication/authorization (set to 0 to disable) (default 10255) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--really-crash-for-testing</b>	
	If true, when panics occur crash. Intended for testing.
<b>--redirect-container-streaming</b>	
	Enables container streaming redirect. If false, kubelet will proxy container streaming data between apiserver and container runtime; if true, kubelet will return an http redirect to apiserver, and apiserver will access container runtime directly. The proxy approach is more secure, but introduces some overhead. The redirect approach is more performant, but less secure because the connection between apiserver and container runtime may not be authenticated.
<b>--register-node</b>	
	Register the node with the apiserver. If --kubeconfig is not provided, this flag is irrelevant, as the Kubelet won't have an apiserver to register with. Default=true. (default true)
<b>--register-schedulable</b>	
	Register the node as schedulable. Won't have any effect if register-node is false. (default true) (DEPRECATED: will be removed in a future version)
<b>--register-with-taints []api.Taint</b>	
	Register the node with the given list of taints (comma separated "=:"). No-op if register-node is false.
<b>--registry-burst int32</b>	
	Maximum size of a bursty pulls, temporarily allows pulls to burst to this number, while still not exceeding registry-qps. Only used if --registry-qps > 0 (default 10) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--registry-qps int32</b>	
	If > 0, limit registry pull QPS to this value. If 0, unlimited. (default 5) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--resolv-conf string</b>	
	Resolver configuration file used as the basis for the container DNS resolution configuration. (default "/etc/resolv.conf") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--root-dir string</b>	

Directory path for managing kubelet files (volume mounts,etc). (default "/var/lib/kubelet")
<b>--rotate-certificates</b>
Auto rotate the kubelet client certificates by requesting new certificates from the kube-apiserver when the certificate expiration approaches. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--rotate-server-certificates</b>
Auto-request and rotate the kubelet serving certificates by requesting new certificates from the kube-apiserver when the certificate expiration approaches. Requires the RotateKubeletServerCertificate feature gate to be enabled, and approval of the submitted CertificateSigningRequest objects. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--runonce</b>
If true, exit after spawning pods from local manifests or remote urls. Exclusive with --enable-server
<b>--runtime-cgroups string</b>
Optional absolute name of cgroups to create and run the runtime in.
<b>--runtime-request-timeout duration</b>
Timeout of all runtime requests except long running request - pull, logs, exec and attach. When timeout exceeded, kubelet will cancel the request, throw out an error and retry later. (default 2m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--seccomp-profile-root string</b>
Directory path for seccomp profiles. (default "/var/lib/kubelet/seccomp")
<b>--serialize-image-pulls</b>
Pull images one at a time. We recommend <i>*not*</i> changing the default value on nodes that run docker daemon with version < 1.9 or an Aufs storage backend. Issue #10959 has more details. (default true) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--skip-headers</b>
If true, avoid header prefixes in the log messages
<b>--skip-log-headers</b>
If true, avoid headers when opening log files
<b>--stderrthreshold severity</b>
logs at or above this threshold go to stderr (default 2)
<b>--storage-driver-buffer-duration duration</b>

Writes in the storage driver will be buffered for this duration, and committed to the non memory backends as a single transaction (default 1m0s) (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--storage-driver-db string
database name (default "cadvisor") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--storage-driver-host string
database host:port (default "localhost:8086") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--storage-driver-password string
database password (default "root") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--storage-driver-secure
use secure connection with database (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--storage-driver-table string
table name (default "stats") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--storage-driver-user string
database username (default "root") (DEPRECATED: This is a cadvisor flag that was mistakenly registered with the Kubelet. Due to legacy concerns, it will follow the standard CLI deprecation timeline before being removed.)
--streaming-connection-idle-timeout duration
Maximum time a streaming connection can be idle before the connection is automatically closed. 0 indicates no timeout. Example: '5m' (default 4h0m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--sync-frequency duration
Max period between synchronizing running containers and config (default 1m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--system-cgroups /

Optional absolute name of cgroups in which to place all non-kernel processes that are not already inside a cgroup under /. Empty for no container. Rolling back the flag requires a reboot. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--system-reserved</b> mapStringString
A set of ResourceName=ResourceQuantity (e.g. cpu=200m,memory=500Mi,ephemeral-storage=1Gi) pairs that describe resources reserved for non-kubernetes components. Currently only cpu and memory are supported. See <a href="http://kubernetes.io/docs/user-guide/compute-resources">http://kubernetes.io/docs/user-guide/compute-resources</a> for more detail. [default=none] (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--system-reserved-cgroup</b> string
Absolute name of the top level cgroup that is used to manage non-kubernetes components for which compute resources were reserved via '--system-reserved' flag. Ex. '/system-reserved'. [default=""] (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--tls-cert-file</b> string
File containing x509 Certificate used for serving HTTPS (with intermediate certs, if any, concatenated after server cert). If --tls-cert-file and --tls-private-key-file are not provided, a self-signed certificate and key are generated for the public address and saved to the directory passed to --cert-dir. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
<b>--tls-cipher-suites</b> stringSlice



Comma-separated list of cipher suites for the server. If omitted, the default Go cipher suites will be used. Possible values: TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_ECDSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_ECDSA_WITH_RC4_128_SHA,TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256,TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256,TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA,TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384,TLS_ECDHE_RSA_WITH_CHACHA20_POLY1305,TLS_ECDHE_RSA_WITH_RC4_128_SHA,TLS_RSA_WITH_3DES_EDE_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA,TLS_RSA_WITH_AES_128_CBC_SHA256,TLS_RSA_WITH_AES_128_GCM_SHA256,TLS_RSA_WITH_AES_256_CBC_SHA,TLS_RSA_WITH_AES_256_GCM_SHA384,TLS_RSA_WITH_RC4_128_SHA (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--tls-min-version string
Minimum TLS version supported. Possible values: VersionTLS10, VersionTLS11, VersionTLS12, VersionTLS13 (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--tls-private-key-file string
File containing x509 private key matching --tls-cert-file. (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
--topology-manager-policy string
Topology Manager policy to use. Possible values: 'none', 'best-effort', 'restricted', 'single-numa-node'. (default "none") (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)
-v, --v Level
number for the log level verbosity
--version version[=true]
Print version information and quit
--vmodule moduleSpec
comma-separated list of pattern=N settings for file-filtered logging
--volume-plugin-dir string

	The full path of the directory in which to search for additional third party volume plugins (default "/usr/libexec/kubernetes/kubelet-plugins/volume/exec/")
<b>--volume-stats-aggr-period duration</b>	
	Specifies interval for kubelet to calculate and cache the volume disk usage for all pods and volumes. To disable volume calculations, set to 0. (default 1m0s) (DEPRECATED: This parameter should be set via the config file specified by the Kubelet's --config flag. See <a href="https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/">https://kubernetes.io/docs/tasks/administer-cluster/kubelet-config-file/</a> for more information.)

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on December 10, 2019 at 5:41 AM PST by [Official 1.17 Release Docs \(#18011\)](#) ([Page History](#))

[Edit This Page](#)

# Kubelet authentication/authorization

- - [Overview](#)
  - [Kubelet authentication](#)
  - [Kubelet authorization](#)

# Overview

A kubelet's HTTPS endpoint exposes APIs which give access to data of varying sensitivity, and allow you to perform operations with varying levels of power on the node and within containers.

This document describes how to authenticate and authorize access to the kubelet's HTTPS endpoint.

## Kubelet authentication

By default, requests to the kubelet's HTTPS endpoint that are not rejected by other configured authentication methods are treated as anonymous requests, and given a username of `system:anonymous` and a group of `system:unauthenticated`.

To disable anonymous access and send 401 Unauthorized responses to unauthenticated requests:

- start the kubelet with the `--anonymous-auth=false` flag

To enable X509 client certificate authentication to the kubelet's HTTPS endpoint:

- start the kubelet with the `--client-ca-file` flag, providing a CA bundle to verify client certificates with
- start the apiserver with `--kubelet-client-certificate` and `--kubelet-client-key` flags
- see the [apiserver authentication documentation](#) for more details

To enable API bearer tokens (including service account tokens) to be used to authenticate to the kubelet's HTTPS endpoint:

- ensure the `authentication.k8s.io/v1beta1` API group is enabled in the API server
- start the kubelet with the `--authentication-token-webhook` and `--kubeconfig` flags
- the kubelet calls the TokenReview API on the configured API server to determine user information from bearer tokens

## Kubelet authorization

Any request that is successfully authenticated (including an anonymous request) is then authorized. The default authorization mode is `AlwaysAllow`, which allows all requests.

There are many possible reasons to subdivide access to the kubelet API:

- anonymous auth is enabled, but anonymous users' ability to call the kubelet API should be limited

- bearer token auth is enabled, but arbitrary API users' (like service accounts) ability to call the kubelet API should be limited
- client certificate auth is enabled, but only some of the client certificates signed by the configured CA should be allowed to use the kubelet API

To subdivide access to the kubelet API, delegate authorization to the API server:

- ensure the `authorization.k8s.io/v1beta1` API group is enabled in the API server
- start the kubelet with the `--authorization-mode=Webhook` and the `--kubeconfig` flags
- the kubelet calls the `SubjectAccessReview` API on the configured API server to determine whether each request is authorized

The kubelet authorizes API requests using the same [request attributes](#) approach as the apiserver.

The verb is determined from the incoming request's HTTP verb:

HTTP verb	request verb
POST	create
GET, HEAD	get
PUT	update
PATCH	patch
DELETE	delete

The resource and subresource is determined from the incoming request's path:

Kubelet API	resource	subresource
/stats/*	nodes	stats
/metrics/*	nodes	metrics
/logs/*	nodes	log
/spec/*	nodes	spec
<i>all others</i>	nodes	proxy

The namespace and API group attributes are always an empty string, and the resource name is always the name of the kubelet's `Node` API object.

When running in this mode, ensure the user identified by the `--kubelet-client-certificate` and `--kubelet-client-key` flags passed to the apiserver is authorized for the following attributes:

- `verb=*, resource=nodes, subresource=proxy`
- `verb=*, resource=nodes, subresource=stats`
- `verb=*, resource=nodes, subresource=log`
- `verb=*, resource=nodes, subresource=spec`
- `verb=*, resource=nodes, subresource=metrics`

# Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on July 18, 2018 at 6:07 PM PST by [Update authorization links \(#9465\)](#) ([Page History](#))

[Edit This Page](#)

# TLS bootstrapping

In a Kubernetes cluster, the components on the worker nodes - kubelet and kube-proxy - need to communicate with Kubernetes master components, specifically kube-apiserver. In order to ensure that communication is kept private, not interfered with, and ensure that each component of the cluster is talking to another trusted component, we strongly recommend using client TLS certificates on nodes.

The normal process of bootstrapping these components, especially worker nodes that need certificates so they can communicate safely with kube-apiserver, can be a challenging process as it is often outside of the scope of Kubernetes and requires significant additional work. This in turn, can make it challenging to initialize or scale a cluster.

In order to simplify the process, beginning in version 1.4, Kubernetes introduced a certificate request and signing API to simplify the process. The proposal can be found [here](#).

This document describes the process of node initialization, how to set up TLS client certificate bootstrapping for kubelets, and how it works.

- [Initialization Process](#)
- [Configuration](#)
- [Certificate Authority](#)
- [kube-apiserver configuration](#)
- [kube-controller-manager configuration](#)
- [kubelet configuration](#)
- [Other authenticating components](#)
- [kubectl approval](#)
- [Limits](#)

## Initialization Process

When a worker node starts up, the kubelet does the following:

1. Look for its kubeconfig file
2. Retrieve the URL of the API server and credentials, normally a TLS key and signed certificate from the kubeconfig file
3. Attempt to communicate with the API server using the credentials.

Assuming that the kube-apiserver successfully validates the kubelet's credentials, it will treat the kubelet as a valid node, and begin to assign pods to it.

Note that the above process depends upon:

- Existence of a key and certificate on the local host in the kubeconfig
- The certificate having been signed by a Certificate Authority (CA) trusted by the kube-apiserver

All of the following are responsibilities of whoever sets up and manages the cluster:

1. Creating the CA key and certificate
2. Distributing the CA certificate to the master nodes, where kube-apiserver is running
3. Creating a key and certificate for each kubelet; strongly recommended to have a unique one, with a unique CN, for each kubelet
4. Signing the kubelet certificate using the CA key
5. Distributing the kubelet key and signed certificate to the specific node on which the kubelet is running

The TLS Bootstrapping described in this document is intended to simplify, and partially or even completely automate, steps 3 onwards, as these are the most common when initializing or scaling a cluster.

## Bootstrap Initialization

In the bootstrap initialization process, the following occurs:

1. kubelet begins
2. kubelet sees that it does *not* have a kubeconfig file
3. kubelet searches for and finds a bootstrap-kubeconfig file
4. kubelet reads its bootstrap file, retrieving the URL of the API server and a limited usage "token"
5. kubelet connects to the API server, authenticates using the token
6. kubelet now has limited credentials to create and retrieve a certificate signing request (CSR)
7. kubelet creates a CSR for itself
8. CSR is approved in one of two ways:
  - If configured, kube-controller-manager automatically approves the CSR
  - If configured, an outside process, possibly a person, approves the CSR using the Kubernetes API or via `kubectl`
9. Certificate is created for the kubelet
10. Certificate is issued to the kubelet
11. kubelet retrieves the certificate
12. kubelet creates a proper kubeconfig with the key and signed certificate
13. kubelet begins normal operation
14. Optional: if configured, kubelet automatically requests renewal of the certificate when it is close to expiry
15. The renewed certificate is approved and issued, either automatically or manually, depending on configuration.

The rest of this document describes the necessary steps to configure TLS Bootstrapping, and its limitations.



# Configuration

To configure for TLS bootstrapping and optional automatic approval, you must configure options on the following components:

- kube-apiserver
- kube-controller-manager
- kubelet
- in-cluster resources: ClusterRoleBinding and potentially ClusterRole

In addition, you need your Kubernetes Certificate Authority (CA).

## Certificate Authority

As without bootstrapping, you will need a Certificate Authority (CA) key and certificate. As without bootstrapping, these will be used to sign the kubelet certificate. As before, it is your responsibility to distribute them to master nodes.

For the purposes of this document, we will assume these have been distributed to master nodes at `/var/lib/kubernetes/ca.pem` (certificate) and `/var/lib/kubernetes/ca-key.pem` (key). We will refer to these as "Kubernetes CA certificate and key".

All Kubernetes components that use these certificates - kubelet, kube-apiserver, kube-controller-manager - assume the key and certificate to be PEM-encoded.

## kube-apiserver configuration

The kube-apiserver has several requirements to enable TLS bootstrapping:

- Recognizing CA that signs the client certificate
- Authenticating the bootstrapping kubelet to the `system:bootstrappers` group
- Authorize the bootstrapping kubelet to create a certificate signing request (CSR)

## Recognizing client certificates

This is normal for all client certificate authentication. If not already set, add the `--client-ca-file=FILENAME` flag to the kube-apiserver command to enable client certificate authentication, referencing a certificate authority bundle containing the signing certificate, for example `--client-ca-file=/var/lib/kubernetes/ca.pem`.

## Initial bootstrap authentication

In order for the bootstrapping kubelet to connect to kube-apiserver and request a certificate, it must first authenticate to the server. You can use any [authenticator](#) that can authenticate the kubelet.

While any authentication strategy can be used for the kubelet's initial bootstrap credentials, the following two authenticators are recommended for ease of provisioning.

1. [Bootstrap Tokens](#) - **beta**
2. [Token authentication file](#)

Bootstrap tokens are a simpler and more easily managed method to authenticate kubelets, and do not require any additional flags when starting kube-apiserver. Using bootstrap tokens is currently **beta** as of Kubernetes version 1.12.

Whichever method you choose, the requirement is that the kubelet be able to authenticate as a user with the rights to:

1. create and retrieve CSRs
2. be automatically approved to request node client certificates, if automatic approval is enabled.

A kubelet authenticating using bootstrap tokens is authenticated as a user in the group `system:bootstrappers`, which is the standard method to use.

As this feature matures, you should ensure tokens are bound to a Role Based Access Control (RBAC) policy which limits requests (using the [bootstrap token](#)) strictly to client requests related to certificate provisioning. With RBAC in place, scoping the tokens to a group allows for great flexibility. For example, you could disable a particular bootstrap group's access when you are done provisioning the nodes.

### Bootstrap tokens

Bootstrap tokens are described in detail [here](#). These are tokens that are stored as secrets in the Kubernetes cluster, and then issued to the individual kubelet. You can use a single token for an entire cluster, or issue one per worker node.

The process is two-fold:

1. Create a Kubernetes secret with the token ID, secret and scope(s).
2. Issue the token to the kubelet

From the kubelet's perspective, one token is like another and has no special meaning. From the kube-apiserver's perspective, however, the bootstrap token is special. Due to its Type, namespace and name, kube-apiserver recognizes it as a special token, and grants anyone authenticating with that token special bootstrap rights, notably treating them as a member of the `sys`

tem:bootstrappers group. This fulfills a basic requirement for TLS bootstrapping.

The details for creating the secret are available [here](#).

If you want to use bootstrap tokens, you must enable it on kube-apiserver with the flag:

```
--enable-bootstrap-token-auth=true
```

## Token authentication file

kube-apiserver has an ability to accept tokens as authentication. These tokens are arbitrary but should represent at least 128 bits of entropy derived from a secure random number generator (such as /dev/urandom on most modern Linux systems). There are multiple ways you can generate a token. For example:

```
head -c 16 /dev/urandom | od -An -t x | tr -d ' '
```

will generate tokens that look like 02b50b05283e98dd0fd71db496ef01e8.

The token file should look like the following example, where the first three values can be anything and the quoted group name should be as depicted:

```
02b50b05283e98dd0fd71db496ef01e8,kubelet-bootstrap,  
10001,"system:bootstrappers"
```

Add the --token-auth-file=FILENAME flag to the kube-apiserver command (in your systemd unit file perhaps) to enable the token file. See docs [here](#) for further details.

## Authorize kubelet to create CSR

Now that the bootstrapping node is *authenticated* as part of the system:bootstrappers group, it needs to be *authorized* to create a certificate signing request (CSR) as well as retrieve it when done. Fortunately, Kubernetes ships with a ClusterRole with precisely these (and just these) permissions, system:node-bootstrapper.

To do this, you just need to create a ClusterRoleBinding that binds the system:bootstrappers group to the cluster role system:node-bootstrapper.

```
# enable bootstrapping nodes to create CSR  
apiVersion: rbac.authorization.k8s.io/v1  
kind: ClusterRoleBinding  
metadata:  
  name: create-csrs-for-bootstrapping  
subjects:  
- kind: Group  
  name: system:bootstrappers  
  apiGroup: rbac.authorization.k8s.io  
roleRef:
```

```
kind: ClusterRole
name: system:node-bootstrapper
apiGroup: rbac.authorization.k8s.io
```

## kube-controller-manager configuration

While the apiserver receives the requests for certificates from the kubelet and authenticates those requests, the controller-manager is responsible for issuing actual signed certificates.

The controller-manager performs this function via a certificate-issuing control loop. This takes the form of a [cfssl](#) local signer using assets on disk. Currently, all certificates issued have one year validity and a default set of key usages.

In order for the controller-manager to sign certificates, it needs the following:

- access to the "Kubernetes CA key and certificate" that you created and distributed
- enabling CSR signing

### Access to key and certificate

As described earlier, you need to create a Kubernetes CA key and certificate, and distribute it to the master nodes. These will be used by the controller-manager to sign the kubelet certificates.

Since these signed certificates will, in turn, be used by the kubelet to authenticate as a regular kubelet to kube-apiserver, it is important that the CA provided to the controller-manager at this stage also be trusted by kube-apiserver for authentication. This is provided to kube-apiserver with the flag `--client-ca-file=FILENAME` (for example, `--client-ca-file=/var/lib/kubernetes/ca.pem`), as described in the kube-apiserver configuration section.

To provide the Kubernetes CA key and certificate to kube-controller-manager, use the following flags:

```
--cluster-signing-cert-file="/etc/path/to/kubernetes/ca/ca.crt"
--cluster-signing-key-file="/etc/path/to/kubernetes/ca/ca.key"
```

for example:

```
--cluster-signing-cert-file="/var/lib/kubernetes/ca.pem" --
cluster-signing-key-file="/var/lib/kubernetes/ca-key.pem"
```

The validity duration of signed certificates can be configured with flag:

```
--experimental-cluster-signing-duration
```

## Approval

In order to approve CSRs, you need to tell the controller-manager that it is acceptable to approve them. This is done by granting RBAC permissions to the correct group.

There are two distinct sets of permissions:

- **nodeclient**: If a node is creating a new certificate for a node, then it does not have a certificate yet. It is authenticating using one of the tokens listed above, and thus is part of the group `system:bootstrappers`.
- **selfnodeclient**: If a node is renewing its certificate, then it already has a certificate (by definition), which it uses continuously to authenticate as part of the group `system:nodes`.

To enable the kubelet to request and receive a new certificate, create a `ClusterRoleBinding` that binds the group in which the bootstrapping node is a member `system:bootstrappers` to the `ClusterRole` that grants it permission, `system:certificates.k8s.io:certificatesigningrequests:nodeclient`:

```
# Approve all CSRs for the group "system:bootstrappers"
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRoleBinding
metadata:
  name: auto-approve-csrs-for-group
subjects:
- kind: Group
  name: system:bootstrappers
  apiGroup: rbac.authorization.k8s.io
roleRef:
  kind: ClusterRole
  name: system:certificates.k8s.io:certificatesigningrequests:nodeclient
  apiGroup: rbac.authorization.k8s.io
```

To enable the kubelet to renew its own client certificate, create a `ClusterRoleBinding` that binds the group in which the fully functioning node is a member `system:nodes` to the `ClusterRole` that grants it permission, `system:certificates.k8s.io:certificatesigningrequests:selfnodeclient`:

```
# Approve renewal CSRs for the group "system:nodes"
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRoleBinding
metadata:
  name: auto-approve-renewals-for-nodes
subjects:
- kind: Group
  name: system:nodes
  apiGroup: rbac.authorization.k8s.io
roleRef:
```

```
kind: ClusterRole
name: system:certificates.k8s.io:certificatesigningrequests:sel
fnodeclient
apiGroup: rbac.authorization.k8s.io
```

**Note: Kubernetes Below 1.8:** If you are running an earlier version of Kubernetes, notably a version below 1.8, then the cluster roles referenced above do not ship by default. You will have to create them yourself *in addition to* the ClusterRoleBindings listed.

To create the ClusterRoles:

```
# A ClusterRole which instructs the CSR approver to approve a
user requesting
# node client credentials.
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: system:certificates.k8s.io:certificatesigningrequests:nod
eclient
rules:
- apiGroups: ["certificates.k8s.io"]
  resources: ["certificatesigningrequests/nodeclient"]
  verbs: ["create"]
---
# A ClusterRole which instructs the CSR approver to approve a
node renewing its
# own client credentials.
apiVersion: rbac.authorization.k8s.io/v1
kind: ClusterRole
metadata:
  name: system:certificates.k8s.io:certificatesigningrequests:sel
fnodeclient
rules:
- apiGroups: ["certificates.k8s.io"]
  resources: ["certificatesigningrequests/selfnodeclient"]
  verbs: ["create"]
```

The csrapproving controller that ships as part of [kube-controller-manager](#) and is enabled by default. The controller uses the [SubjectAccessReview API](#) to determine if a given user is authorized to request a CSR, then approves based on the authorization outcome. To prevent conflicts with other approvers, the builtin approver doesn't explicitly deny CSRs. It only ignores unauthorized requests. The controller also prunes expired certificates as part of garbage collection.

## kubelet configuration

Finally, with the master nodes properly set up and all of the necessary authentication and authorization in place, we can configure the kubelet.

The kubelet requires the following configuration to bootstrap:

- A path to store the key and certificate it generates (optional, can use default)
- A path to a kubeconfig file that does not yet exist; it will place the bootstrapped config file here
- A path to a bootstrap kubeconfig file to provide the URL for the server and bootstrap credentials, e.g. a bootstrap token
- Optional: instructions to rotate certificates

The bootstrap kubeconfig should be in a path available to the kubelet, for example `/var/lib/kubelet/bootstrap-kubeconfig`.

Its format is identical to a normal kubeconfig file. A sample file might look as follows:

```
apiVersion: v1
kind: Config
clusters:
- cluster:
    certificate-authority: /var/lib/kubernetes/ca.pem
    server: https://my.server.example.com:6443
  name: bootstrap
contexts:
- context:
    cluster: bootstrap
    user: kubelet-bootstrap
  name: bootstrap
current-context: bootstrap
preferences: {}
users:
- name: kubelet-bootstrap
  user:
    token: 07401b.f395accd246ae52d
```

The important elements to note are:

- `certificate-authority`: path to a CA file, used to validate the server certificate presented by kube-apiserver
- `server`: URL to kube-apiserver
- `token`: the token to use

The format of the token does not matter, as long as it matches what kube-apiserver expects. In the above example, we used a bootstrap token. As stated earlier, *any* valid authentication method can be used, not just tokens.

Because the bootstrap kubeconfig *is* a standard kubeconfig, you can use `kubect` to generate it. To create the above example file:

```
kubect config --kubeconfig=/var/lib/kubelet/bootstrap-
kubeconfig set-cluster bootstrap --server='https://
my.server.example.com:6443' --certificate-authority=/var/lib/
kubernetes/ca.pem
```

```
kubectl config --kubeconfig=/var/lib/kubelet/bootstrap-  
kubeconfig set-credentials kubelet-bootstrap --  
token=07401b.f395accd246ae52d  
kubectl config --kubeconfig=/var/lib/kubelet/bootstrap-  
kubeconfig set-context bootstrap --user=kubelet-bootstrap --  
cluster=bootstrap  
kubectl config --kubeconfig=/var/lib/kubelet/bootstrap-  
kubeconfig use-context bootstrap
```

To indicate to the kubelet to use the bootstrap kubeconfig, use the following kubelet flag:

```
--bootstrap-kubeconfig="/var/lib/kubelet/bootstrap-kubeconfig" --  
kubeconfig="/var/lib/kubelet/kubeconfig"
```

When starting the kubelet, if the file specified via `--kubeconfig` does not exist, the bootstrap kubeconfig specified via `--bootstrap-kubeconfig` is used to request a client certificate from the API server. On approval of the certificate request and receipt back by the kubelet, a kubeconfig file referencing the generated key and obtained certificate is written to the path specified by `--kubeconfig`. The certificate and key file will be placed in the directory specified by `--cert-dir`.

## Client and Serving Certificates

All of the above relate to kubelet *client* certificates, specifically, the certificates a kubelet uses to authenticate to kube-apiserver.

A kubelet also can use *serving* certificates. The kubelet itself exposes an https endpoint for certain features. To secure these, the kubelet can do one of:

- use provided key and certificate, via the `--tls-private-key-file` and `--tls-cert-file` flags
- create self-signed key and certificate, if a key and certificate are not provided
- request serving certificates from the cluster server, via the CSR API

The client certificate provided by TLS bootstrapping is signed, by default, for client auth only, and thus cannot be used as serving certificates, or server auth.

However, you *can* enable its server certificate, at least partially, via certificate rotation.

## Certificate Rotation

Kubernetes v1.8 and higher kubelet implements **beta** features for enabling rotation of its client and/or serving certificates. These can be enabled through the respective `RotateKubeletClientCertificate` and `RotateKubeletServerCertificate` feature flags on the kubelet and are enabled by default.



RotateKubeletClientCertificate causes the kubelet to rotate its client certificates by creating new CSRs as its existing credentials expire. To enable this feature pass the following flag to the kubelet:

```
--rotate-certificates
```

RotateKubeletServerCertificate causes the kubelet **both** to request a serving certificate after bootstrapping its client credentials **and** to rotate that certificate. To enable this feature pass the following flag to the kubelet:

```
--rotate-server-certificates
```

**Note:** The CSR approving controllers implemented in core Kubernetes do not approve node *serving* certificates for [security reasons](#). To use RotateKubeletServerCertificate operators need to run a custom approving controller, or manually approve the serving certificate requests.

## Other authenticating components

All of TLS bootstrapping described in this document relates to the kubelet. However, other components may need to communicate directly with kube-apiserver. Notable is kube-proxy, which is part of the Kubernetes control plane and runs on every node, but may also include other components such as monitoring or networking.

Like the kubelet, these other components also require a method of authenticating to kube-apiserver. You have several options for generating these credentials:

- The old way: Create and distribute certificates the same way you did for kubelet before TLS bootstrapping
- DaemonSet: Since the kubelet itself is loaded on each node, and is sufficient to start base services, you can run kube-proxy and other node-specific services not as a standalone process, but rather as a daemonset in the kube-system namespace. Since it will be in-cluster, you can give it a proper service account with appropriate permissions to perform its activities. This may be the simplest way to configure such services.

## kubectl approval

CSRs can be approved outside of the approval flows builtin to the controller manager.

The signing controller does not immediately sign all certificate requests. Instead, it waits until they have been flagged with an "Approved" status by an appropriately-privileged user. This flow is intended to allow for automated approval handled by an external approval controller or the approval controller implemented in the core controller-manager. However cluster administrators can also manually approve certificate requests using

kubectl. An administrator can list CSRs with `kubectl get csr` and describe one in detail with `kubectl describe csr <name>`. An administrator can approve or deny a CSR with `kubectl certificate approve <name>` and `kubectl certificate deny <name>`.

## Limits

Although Kubernetes supports running control plane master components like kube-apiserver and kube-controller-manager in containers, and even as Pods in a kubelet, as of this writing, you cannot both TLS Bootstrap a kubelet and run master plane components on it.

The reason for this limitation is that the kubelet attempts to bootstrap communication with kube-apiserver *before* starting any pods, even static ones define on disk and referenced via the kubelet option `--pod-manifest-path=<PATH>`. Trying to do both TLS Bootstrapping and master components in kubelet leads to a race condition: kubelet needs to communicate to kube-apiserver to request certificates, yet requires those certificates to be available to start kube-apiserver.

An issue is open referencing this [here](#).

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 09, 2020 at 7:11 AM PST by [Fix typo in TLS bootstrapping document \(#18292\)](#) ([#18293](#)) ([Page History](#))

[Edit This Page](#)

# Overview of kubectl

Kubectl is a command line tool for controlling Kubernetes clusters. `kubectl` looks for a file named `config` in the `$HOME/.kube` directory. You can specify other [kubeconfig](#) files by setting the `KUBECONFIG` environment variable or by setting the [--kubeconfig](#) flag.

This overview covers `kubectl` syntax, describes the command operations, and provides common examples. For details about each command, including

all the supported flags and subcommands, see the [kubectrl](#) reference documentation. For installation instructions see [installing kubectrl](#).

- [Syntax](#)
- [Operations](#)
- [Resource types](#)
- [Output options](#)
- [Examples: Common operations](#)
- [Examples: Creating and using plugins](#)
- [What's next](#)

## Syntax

Use the following syntax to run `kubectrl` commands from your terminal window:

```
kubectrl [command] [TYPE] [NAME] [flags]
```

where `command`, `TYPE`, `NAME`, and `flags` are:

- `command`: Specifies the operation that you want to perform on one or more resources, for example `create`, `get`, `describe`, `delete`.
- `TYPE`: Specifies the [resource type](#). Resource types are case-insensitive and you can specify the singular, plural, or abbreviated forms. For example, the following commands produce the same output:

```
kubectrl get pod pod1
kubectrl get pods pod1
kubectrl get po pod1
```

- `NAME`: Specifies the name of the resource. Names are case-sensitive. If the name is omitted, details for all resources are displayed, for example `kubectrl get pods`.

When performing an operation on multiple resources, you can specify each resource by type and name or specify one or more files:

- To specify resources by type and name:
  - To group resources if they are all the same type: `TYPE1 name1 name2 name<#>`.  
Example: `kubectrl get pod example-pod1 example-pod2`
  - To specify multiple resource types individually: `TYPE1/name1 TYPE1/name2 TYPE2/name3 TYPE<#>/name<#>`.  
Example: `kubectrl get pod/example-pod1 replicationcontroller/example-rc1`

- To specify resources with one or more files: `-f file1 -f file2 -f file<#>`
  - [Use YAML rather than JSON](#) since YAML tends to be more user-friendly, especially for configuration files.  
Example: `kubectl get pod -f ./pod.yaml`
- **flags:** Specifies optional flags. For example, you can use the `-s` or `--server` flags to specify the address and port of the Kubernetes API server.

**Caution:** Flags that you specify from the command line override default values and any corresponding environment variables.

If you need help, just run `kubectl help` from the terminal window.

## Operations

The following table includes short descriptions and the general syntax for all of the `kubectl` operations:

Operation	Syntax	Description
annotate	<code>kubectl annotate (-f FILENAME \   TYPE NAME \   TYPE/NAME) KEY_1=VAL_1 ... KEY_N=VAL_N [--overwrite] [--all] [--resource-version=version] [flags]</code>	Add or update the annotations of one or more resources.
api-versions	<code>kubectl api-versions [flags]</code>	List the API versions that are available.
apply	<code>kubectl apply -f FILENAME [flags]</code>	Apply a configuration change to a resource from a file or stdin.
attach	<code>kubectl attach POD -c CONTAINER [-i] [-t] [flags]</code>	Attach to a running container either to view the output stream or interact with the container (stdin).
autoscale	<code>kubectl autoscale (-f FILENAME \   TYPE NAME \   TYPE/NAME) [--min=MINPODS] --max=MAXPODS [--cpu-percent=CPU] [flags]</code>	Automatically scale the set of pods that are managed by a replication controller.
cluster-info	<code>kubectl cluster-info [flags]</code>	Display endpoint information about the master and services in the cluster.

Operation	Syntax	Description
config	<code>kubectl config SUBCOMMAND [flags]</code>	Modifies kubeconfig files. See the individual subcommands for details.
create	<code>kubectl create -f FILENAME [flags]</code>	Create one or more resources from a file or stdin.
delete	<code>kubectl delete (-f FILENAME \   TYPE [NAME \   /NAME \   -l label \   --all]) [flags]</code>	Delete resources either from a file, stdin, or specifying label selectors, names, resource selectors, or resources.
describe	<code>kubectl describe (-f FILENAME \   TYPE [NAME_PREFIX \   /NAME \   -l label]) [flags]</code>	Display the detailed state of one or more resources.
diff	<code>kubectl diff -f FILENAME [flags]</code>	Diff file or stdin against live configuration ( <b>BETA</b> )
edit	<code>kubectl edit (-f FILENAME \   TYPE NAME \   TYPE/NAME) [flags]</code>	Edit and update the definition of one or more resources on the server by using the default editor.
exec	<code>kubectl exec POD [-c CONTAINER] [-i] [-t] [flags] [-- COMMAND [args...]]</code>	Execute a command against a container in a pod.
explain	<code>kubectl explain [--recursive=false] [flags]</code>	Get documentation of various resources. For instance pods, nodes, services, etc.
expose	<code>kubectl expose (-f FILENAME \   TYPE NAME \   TYPE/NAME) [--port=port] [--protocol=TCP\ UDP] [--target-port=number-or-name] [--name=name] [--external-ip=external-ip-of-service] [--type=type] [flags]</code>	Expose a replication controller, service, or pod as a new Kubernetes service.
get	<code>kubectl get (-f FILENAME \   TYPE [NAME \   /NAME \   -l label]) [--watch] [--sort-by=FIELD] [--o \   --output]=OUTPUT_FORMAT [flags]</code>	List one or more resources.

Operation	Syntax	Description
label	<code>kubectl label (-f FILENAME \   TYPE NAME \   TYPE/NAME) KEY_1=VAL_1 ... KEY_N=VAL_N [--overwrite] [--all] [--resource-version=version] [flags]</code>	Add or update the labels of one or more resources.
logs	<code>kubectl logs POD [-c CONTAINER] [--follow] [flags]</code>	Print the logs for a container in a pod.
patch	<code>kubectl patch (-f FILENAME \   TYPE NAME \   TYPE/NAME) --patch PATCH [flags]</code>	Update one or more fields of a resource by using the strategic merge patch process.
port-forward	<code>kubectl port-forward POD [LOCAL_PORT:]REMOTE_PORT [...] [LOCAL_PORT_N:]REMOTE_PORT_N] [flags]</code>	Forward one or more local ports to a pod.
proxy	<code>kubectl proxy [--port=PORT] [--www=static-dir] [--www-prefix=prefix] [--api-prefix=prefix] [flags]</code>	Run a proxy to the Kubernetes API server.
replace	<code>kubectl replace -f FILENAME</code>	Replace a resource from a file or stdin.
rolling-update	<code>kubectl rolling-update OLD_CONTROLLER_NAME ([NEW_CONTROLLER_NAME] --image=NEW_CONTAINER_IMAGE \   -f NEW_CONTROLLER_SPEC) [flags]</code>	Perform a rolling update by gradually replacing the specified replication controller and its pods.
run	<code>kubectl run NAME --image=image [--env="key=value"] [--port=port] [--replicas=replicas] [--dry-run=bool] [--overrides=inline-json] [flags]</code>	Run a specified image on the cluster.
scale	<code>kubectl scale (-f FILENAME \   TYPE NAME \   TYPE/NAME) --replicas=COUNT [--resource-version=version] [--current-replicas=count] [flags]</code>	Update the size of the specified replication controller.
version	<code>kubectl version [--client] [flags]</code>	Display the Kubernetes version running on the client and server.

Remember: For more about command operations, see the [kubectl](#) reference documentation.

## Resource types

The following table includes a list of all the supported resource types and their abbreviated aliases.

(This output can be retrieved from `kubectl api-resources`, and is accurate as of Kubernetes 1.13.3.)

Resource Name	Short Names	API Group	Namespace
bindings			true
componentstatuses	cs		false
configmaps	cm		true
endpoints	ep		true
limitranges	limits		true
namespaces	ns		false
nodes	no		false
persistentvolumeclaims	pvc		true
persistentvolumes	pv		false
Pods	po		true
podtemplates			true
replicationcontrollers	rc		true
resourcequotas	quota		true
secrets			true
serviceaccounts	sa		true
services	svc		true
mutatingwebhookconfigurations		admissionregistration.k8s.io	false
validatingwebhookconfigurations		admissionregistration.k8s.io	false
customresourcedefinitions	crd, crds	apiextensions.k8s.io	false
apiservices		apiregistration.k8s.io	false
controllerrevisions		apps	true
daemonsets	ds	apps	true
deployments	deploy	apps	true
replicasets	rs	apps	true
statefulsets	sts	apps	true
tokenreviews		authentication.k8s.io	false
localsubjectaccessreviews		authorization.k8s.io	true
selfsubjectaccessreviews		authorization.k8s.io	false
selfsubjectrulesreviews		authorization.k8s.io	false
subjectaccessreviews		authorization.k8s.io	false
horizontalpodautoscalers	hpa	autoscaling	true
cronjobs	cj	batch	true
jobs		batch	true
certificatesigningrequests	csr	certificates.k8s.io	false
leases		coordination.k8s.io	true
events	ev	events.k8s.io	true
ingresses	ing	extensions	true
networkpolicies	netpol	networking.k8s.io	true
poddisruptionbudgets	pdb	policy	true



Resource Name	Short Names	API Group	Namespace
podsecuritypolicies	psp	policy	false
clusterrolebindings		rbac.authorization.k8s.io	false
clusterroles		rbac.authorization.k8s.io	false
rolebindings		rbac.authorization.k8s.io	true
roles		rbac.authorization.k8s.io	true
priorityclasses	pc	scheduling.k8s.io	false
csidrivers		storage.k8s.io	false
csinodes		storage.k8s.io	false
storageclasses	sc	storage.k8s.io	false
volumeattachments		storage.k8s.io	false

## Output options

Use the following sections for information about how you can format or sort the output of certain commands. For details about which commands support the various output options, see the [kubectrl](#) reference documentation.

### Formatting output

The default output format for all `kubectrl` commands is the human readable plain-text format. To output details to your terminal window in a specific format, you can add either the `-o` or `--output` flags to a supported `kubectrl` command.

### Syntax

```
kubectrl [command] [TYPE] [NAME] -o <output_format>
```

Depending on the `kubectrl` operation, the following output formats are supported:

Output format	Description
<code>-o custom-columns=&lt;spec&gt;</code>	Print a table using a comma separated list of <a href="#">custom columns</a> .
<code>-o custom-columns-file=&lt;filename&gt;</code>	Print a table using the <a href="#">custom columns</a> template in the <code>&lt;filename&gt;</code> file.
<code>-o json</code>	Output a JSON formatted API object.
<code>-o jsonpath=&lt;template&gt;</code>	Print the fields defined in a <a href="#">jsonpath</a> expression.
<code>-o jsonpath-file=&lt;filename&gt;</code>	Print the fields defined by the <a href="#">jsonpath</a> expression in the <code>&lt;filename&gt;</code> file.
<code>-o name</code>	Print only the resource name and nothing else.
<code>-o wide</code>	Output in the plain-text format with any additional information. For pods, the node name is included.

Output format	Description
-o yaml	Output a YAML formatted API object.

### Example

In this example, the following command outputs the details for a single pod as a YAML formatted object:

```
kubectl get pod web-pod-13je7 -o yaml
```

Remember: See the [kubectl](#) reference documentation for details about which output format is supported by each command.

### Custom columns

To define custom columns and output only the details that you want into a table, you can use the custom-columns option. You can choose to define the custom columns inline or use a template file: `-o custom-columns=<spec>` or `-o custom-columns-file=<filename>`.

### Examples

Inline:

```
kubectl get pods <pod-name> -o custom-columns=NAME:.metadata.name,RSRC:.metadata.resourceVersion
```

Template file:

```
kubectl get pods <pod-name> -o custom-columns-file=template.txt
```

where the `template.txt` file contains:

```
NAME          RSRC
metadata.name metadata.resourceVersion
```

The result of running either command is:

```
NAME          RSRC
submit-queue  610995
```

### Server-side columns

`kubectl` supports receiving specific column information from the server about objects. This means that for any given resource, the server will return columns and rows relevant to that resource, for the client to print. This allows for consistent human-readable output across clients used against the same cluster, by having the server encapsulate the details of printing.

This feature is enabled by default in `kubectl` 1.11 and higher. To disable it, add the `--server-print=false` flag to the `kubectl get` command.

## Examples

To print information about the status of a pod, use a command like the following:

```
kubectl get pods <pod-name> --server-print=false
```

Output looks like this:

NAME	READY	STATUS	RESTARTS	AGE
pod-name	1/1	Running	0	1m

## Sorting list objects

To output objects to a sorted list in your terminal window, you can add the `--sort-by` flag to a supported `kubectl` command. Sort your objects by specifying any numeric or string field with the `--sort-by` flag. To specify a field, use a [jsonpath](#) expression.

### Syntax

```
kubectl [command] [TYPE] [NAME] --sort-by=<jsonpath_exp>
```

### Example

To print a list of pods sorted by name, you run:

```
kubectl get pods --sort-by=.metadata.name
```

## Examples: Common operations

Use the following set of examples to help you familiarize yourself with running the commonly used `kubectl` operations:

`kubectl apply` - Apply or Update a resource from a file or stdin.

```
# Create a service using the definition in example-service.yaml.  
kubectl apply -f example-service.yaml
```

```
# Create a replication controller using the definition in  
example-controller.yaml.  
kubectl apply -f example-controller.yaml
```

```
# Create the objects that are defined in any .yaml, .yml,  
or .json file within the <directory> directory.  
kubectl apply -f <directory>
```

`kubectl get` - List one or more resources.

```
# List all pods in plain-text output format.  
kubectl get pods
```

*# List all pods in plain-text output format and include additional information (such as node name).*

```
kubectl get pods -o wide
```

*# List the replication controller with the specified name in plain-text output format. Tip: You can shorten and replace the 'replicationcontroller' resource type with the alias 'rc'.*

```
kubectl get replicationcontroller <rc-name>
```

*# List all replication controllers and services together in plain-text output format.*

```
kubectl get rc,services
```

*# List all daemon sets in plain-text output format.*

```
kubectl get ds
```

*# List all pods running on node server01*

```
kubectl get pods --field-selector=spec.nodeName=server01
```

kubectl describe - Display detailed state of one or more resources, including the uninitialized ones by default.

*# Display the details of the node with name <node-name>.*

```
kubectl describe nodes <node-name>
```

*# Display the details of the pod with name <pod-name>.*

```
kubectl describe pods/<pod-name>
```

*# Display the details of all the pods that are managed by the replication controller named <rc-name>.*

*# Remember: Any pods that are created by the replication controller get prefixed with the name of the replication controller.*

```
kubectl describe pods <rc-name>
```

*# Describe all pods*

```
kubectl describe pods
```

**Note:** The `kubectl get` command is usually used for retrieving one or more resources of the same resource type. It features a rich set of flags that allows you to customize the output format using the `-o` or `--output` flag, for example. You can specify the `-w` or `--watch` flag to start watching updates to a particular object. The `kubectl describe` command is more focused on describing the many related aspects of a specified resource. It may invoke several API calls to the API server to build a view for the user. For example, the `kubectl describe node` command retrieves not only the information about the node, but also a summary of the pods running on it, the events generated for the node etc.

`kubectl delete` - Delete resources either from a file, stdin, or specifying label selectors, names, resource selectors, or resources.

*# Delete a pod using the type and name specified in the pod.yaml file.*

```
kubectl delete -f pod.yaml
```

*# Delete all the pods and services that have the label name=<label-name>.*

```
kubectl delete pods,services -l name=<label-name>
```

*# Delete all pods, including uninitialized ones.*

```
kubectl delete pods --all
```

`kubectl exec` - Execute a command against a container in a pod.

*# Get output from running 'date' from pod <pod-name>. By default, output is from the first container.*

```
kubectl exec <pod-name> date
```

*# Get output from running 'date' in container <container-name> of pod <pod-name>.*

```
kubectl exec <pod-name> -c <container-name> date
```

*# Get an interactive TTY and run /bin/bash from pod <pod-name>. By default, output is from the first container.*

```
kubectl exec -ti <pod-name> /bin/bash
```

`kubectl logs` - Print the logs for a container in a pod.

*# Return a snapshot of the logs from pod <pod-name>.*

```
kubectl logs <pod-name>
```

*# Start streaming the logs from pod <pod-name>. This is similar to the 'tail -f' Linux command.*

```
kubectl logs -f <pod-name>
```

## Examples: Creating and using plugins

Use the following set of examples to help you familiarize yourself with writing and using `kubectl` plugins:

*# create a simple plugin in any language and name the resulting executable file*

*# so that it begins with the prefix "kubectl-"*

```
cat ./kubectl-hello
```

```
#!/bin/bash
```

*# this plugin prints the words "hello world"*

```
echo "hello world"
```

```
# with our plugin written, let's make it executable
```

```
sudo chmod +x ./kubectl-hello
```

```
# and move it to a location in our PATH
```

```
sudo mv ./kubectl-hello /usr/local/bin
```

```
# we have now created and "installed" a kubectl plugin.
```

```
# we can begin using our plugin by invoking it from kubectl as  
if it were a regular command
```

```
kubectl hello
```

```
hello world
```

```
# we can "uninstall" a plugin, by simply removing it from our  
PATH
```

```
sudo rm /usr/local/bin/kubectl-hello
```

In order to view all of the plugins that are available to kubectl, we can use the kubectl plugin list subcommand:

```
kubectl plugin list
```

The following kubectl-compatible plugins are available:

```
/usr/local/bin/kubectl-hello
```

```
/usr/local/bin/kubectl-foo
```

```
/usr/local/bin/kubectl-bar
```

```
# this command can also warn us about plugins that are
```

```
# not executable, or that are overshadowed by other
```

```
# plugins, for example
```

```
sudo chmod -x /usr/local/bin/kubectl-foo
```

```
kubectl plugin list
```

The following kubectl-compatible plugins are available:

```
/usr/local/bin/kubectl-hello
```

```
/usr/local/bin/kubectl-foo
```

```
  - warning: /usr/local/bin/kubectl-foo identified as a plugin,  
but it is not executable
```

```
/usr/local/bin/kubectl-bar
```

```
error: one plugin warning was found
```

We can think of plugins as a means to build more complex functionality on top of the existing kubectl commands:

```
cat ./kubectl-whoami
```

```
#!/bin/bash
```

```
# this plugin makes use of the `kubectl config` command in order  
to output
```

```
# information about the current user, based on the currently
```

### *selected context*

```
kubectl config view --template='{{ range .contexts }}{{ if  
eq .name "'$(kubectl config current-context)'" }}Current user:  
{{ .context.user }}{{ end }}{{ end }}'
```

Running the above plugin gives us an output containing the user for the currently selected context in our KUBECONFIG file:

### *# make the file executable*

```
sudo chmod +x ./kubectl-whoami
```

### *# and move it into our PATH*

```
sudo mv ./kubectl-whoami /usr/local/bin
```

```
kubectl whoami
```

```
Current user: plugins-user
```

To find out more about plugins, take a look at the [example cli plugin](#).

## What's next

Start using the [kubectl](#) commands.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 30, 2020 at 1:12 AM PST by [en: Remove kubectl duplicate example \(#18656\)](#) ([Page History](#))

[Edit This Page](#)

## JSONPath Support

Kubectl supports JSONPath template.

JSONPath template is composed of JSONPath expressions enclosed by curly braces `{}`. Kubectl uses JSONPath expressions to filter on specific fields in the JSON object and format the output. In addition to the



original JSONPath template syntax, the following functions and syntax are valid:

1. Use double quotes to quote text inside JSONPath expressions.
2. Use the range, end operators to iterate lists.
3. Use negative slice indices to step backwards through a list.  
Negative indices do not "wrap around" a list and are valid as long as `-index + listLength >= 0`.

**Note:**

- The \$ operator is optional since the expression always starts from the root object by default.
- The result object is printed as its String() function.

Given the JSON input:

```
{
  "kind": "List",
  "items": [
    {
      "kind": "None",
      "metadata": {"name": "127.0.0.1"},
      "status": {
        "capacity": {"cpu": "4"},
        "addresses": [{"type": "LegacyHostIP", "address": "127.0.0.1"}]
      }
    },
    {
      "kind": "None",
      "metadata": {"name": "127.0.0.2"},
      "status": {
        "capacity": {"cpu": "8"},
        "addresses": [
          {"type": "LegacyHostIP", "address": "127.0.0.2"},
          {"type": "another", "address": "127.0.0.3"}
        ]
      }
    }
  ],
  "users": [
    {
      "name": "myself",
      "user": {}
    },
    {
      "name": "e2e",
      "user": {"username": "admin", "password": "secret"}
    }
  ]
}
```

Function	Description	Example	Result
text	the plain text	kind is {.kind}	kind is Lis
@	the current object	{@}	the same as input
. or []	child operator	{.kind}, [{'kind'}] or [{'name\.'type'}]}	List
..	recursive descent	{..name}	127.0.0.1 127.0.0.2 myself e2e
*	wildcard. Get all objects	{.items[*].metadata.name}	[127.0.0.1 127.0.0.2]
[start:end:step]	subscript operator	{.users[0].name}	myself
[,]	union operator	{.items[*]['metadata.name', 'status.capacity']}	127.0.0.1 127.0.0.2 map[cpu:4] map[cpu:8]
?()	filter	{.users[?(@.name=="e2e")].user.password}	secret
range, end	iterate list	{range .items[*]} [{'metadata.name', {.status.capacity}} {end}	[127.0.0.1, map[cpu:4]] [127.0.0.2, map[cpu:8]]
''	quote interpreted string	{range .items[*]} {.metadata.name}{'\t'}{end}	127.0.0.1 127.0.0.2

Examples using kubectl and JSONPath expressions:

```
kubectl get pods -o json
kubectl get pods -o=jsonpath='{@}'
kubectl get pods -o=jsonpath='{.items[0]}'
kubectl get pods -o=jsonpath='{.items[0].metadata.name}'
kubectl get pods -o=jsonpath="{.items[*]['metadata.name', 'status.capacity']}"
kubectl get pods -o=jsonpath='{range .items[*]}
{.metadata.name}{"\t"}{.status.startTime}{"\n"}{end}'
```

### Note:

On Windows, you must *double* quote any JSONPath template that contains spaces (not single quote as shown above for bash). This in turn means that you must use a single quote or escaped double quote around any literals in the template. For example:

```
kubectl get pods -o=jsonpath="{range .items[*]}
{.metadata.name}{'\t'}{.status.startTime}{'\n'}
{end}"
```

```
kubectl get pods -o=jsonpath="{range .items[*]}\n  {.metadata.name}{\\\"\\t\\\"}{.status.startTime}{\\\"\\n\\\"}\n  {end}"
```

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on February 09, 2020 at 3:15 PM PST by [Remove command prompt from Windows example \(#18906\)](#) ([Page History](#))

[Edit This Page](#)

# kubectl

- [Synopsis](#)
- [Options](#)
- [See Also](#)

## Synopsis

kubectl controls the Kubernetes cluster manager.

Find more information at: <https://kubernetes.io/docs/reference/kubectl/overview/>

```
kubectl [flags]
```

## Options

--add-dir-header	
	If true, adds the file directory to the header
--alsologtostderr	
	log to standard error as well as files
--application-metrics-count-limit int	Default: 100
	Max number of application metrics to store (per container)
--as string	
	Username to impersonate for the operation
--as-group stringArray	
	Group to impersonate for the operation, this flag can be repeated to specify multiple groups.
--azure-container-registry-config string	
	Path to the file containing Azure container registry configuration information.
--boot-id-file string	Default: "/proc/sys/kernel/random/boot_id"
	Comma-separated list of files to check for boot-id. Use the first one that exists.
--cache-dir string	Default: "\$HOME/.kube/http-cache"
	Default HTTP cache directory
--certificate-authority string	
	Path to a cert file for the certificate authority
--client-certificate string	
	Path to a client certificate file for TLS
--client-key string	
	Path to a client key file for TLS

--cloud-provider-gce-l7lb-src-cidrs cidrs	Default: 130.211.0.0/22,35.191.0.0/16
CIDRs opened in GCE firewall for L7 LB traffic proxy & health checks	
--cloud-provider-gce-lb-src-cidrs cidrs	Default: 130.211.0.0/22,209.85.152.0/22,209.85.204.0/22,35.191.0.0/16
CIDRs opened in GCE firewall for L4 LB traffic proxy & health checks	
--cluster string	
The name of the kubeconfig cluster to use	
--container-hints string	Default: "/etc/cadvisor/container_hints.json"
location of the container hints file	
--containerd string	Default: "/run/containerd/containerd.sock"
containerd endpoint	
--containerd-namespace string	Default: "k8s.io"
containerd namespace	
--context string	
The name of the kubeconfig context to use	
--default-not-ready-toleration-seconds int	Default: 300
Indicates the tolerationSeconds of the toleration for notReady:NoExecute that is added by default to every pod that does not already have such a toleration.	
--default-unreachable-toleration-seconds int	Default: 300
Indicates the tolerationSeconds of the toleration for unreachable:NoExecute that is added by default to every pod that does not already have such a toleration.	
--disable-root-cgroup-stats	
Disable collecting root Cgroup stats	
--docker string	Default: "unix:///var/run/docker.sock"
docker endpoint	
--docker-env-metadata-whitelist string	
a comma-separated list of environment variable keys that needs to be collected for docker containers	
--docker-only	
Only report docker containers in addition to root stats	
--docker-root string	Default: "/var/lib/docker"
DEPRECATED: docker root is read from docker info (this is a fallback, default: /var/lib/docker)	
--docker-tls	
use TLS to connect to docker	
--docker-tls-ca string	Default: "ca.pem"
path to trusted CA	
--docker-tls-cert string	Default: "cert.pem"
path to client certificate	

--docker-tls-key string	Default: "key.pem"
path to private key	
--enable-load-reader	
Whether to enable cpu load reader	
--event-storage-age-limit string	Default: "default=0"
Max length of time for which to store events (per type). Value is a comma separated list of key values, where the keys are event types (e.g.: creation, oom) or "default" and the value is a duration. Default is applied to all non-specified event types	
--event-storage-event-limit string	Default: "default=0"
Max number of events to store (per type). Value is a comma separated list of key values, where the keys are event types (e.g.: creation, oom) or "default" and the value is an integer. Default is applied to all non-specified event types	
--global-housekeeping-interval duration	Default: 1m0s
Interval between global housekeepings	
-h, --help	
help for kubectl	
--housekeeping-interval duration	Default: 10s
Interval between container housekeepings	
--insecure-skip-tls-verify	
If true, the server's certificate will not be checked for validity. This will make your HTTPS connections insecure	
--kubeconfig string	
Path to the kubeconfig file to use for CLI requests.	
--log-backtrace-at traceLocation	Default: :0
when logging hits line file:N, emit a stack trace	
--log-cadvisor-usage	
Whether to log the usage of the cAdvisor container	
--log-dir string	
If non-empty, write log files in this directory	
--log-file string	
If non-empty, use this log file	
--log-file-max-size uint	Default: 1800
Defines the maximum size a log file can grow to. Unit is megabytes. If the value is 0, the maximum file size is unlimited.	
--log-flush-frequency duration	Default: 5s
Maximum number of seconds between log flushes	
--logtostderr	Default: true
log to standard error instead of files	
--machine-id-file string	Default: "/etc/machine-id,/var/lib/dbus/machine-id"

	Comma-separated list of files to check for machine-id. Use the first one that exists.
<code>--match-server-version</code>	
	Require server version to match client version
<code>-n, --namespace string</code>	
	If present, the namespace scope for this CLI request
<code>--password string</code>	
	Password for basic authentication to the API server
<code>--profile string</code> <code>^ ^ ^ ^ ^</code> Default: "none"	
	Name of profile to capture. One of (none cpu heap goroutine threadcreate block mutex)
<code>--profile-output string</code> <code>^ ^ ^ ^ ^</code> Default: "profile.pprof"	
	Name of the file to write the profile to
<code>--request-timeout string</code> <code>^ ^ ^ ^ ^</code> Default: "0"	
	The length of time to wait before giving up on a single server request. Non-zero values should contain a corresponding time unit (e.g. 1s, 2m, 3h). A value of zero means don't timeout requests.
<code>-s, --server string</code>	
	The address and port of the Kubernetes API server
<code>--skip-headers</code>	
	If true, avoid header prefixes in the log messages
<code>--skip-log-headers</code>	
	If true, avoid headers when opening log files
<code>--stderrthreshold severity</code> <code>^ ^ ^ ^ ^</code> Default: 2	
	logs at or above this threshold go to stderr
<code>--storage-driver-buffer-duration duration</code> <code>^ ^ ^ ^ ^</code> Default: 1m0s	
	Writes in the storage driver will be buffered for this duration, and committed to the non memory backends as a single transaction
<code>--storage-driver-db string</code> <code>^ ^ ^ ^ ^</code> Default: "cadvisor"	
	database name
<code>--storage-driver-host string</code> <code>^ ^ ^ ^ ^</code> Default: "localhost:8086"	
	database host:port
<code>--storage-driver-password string</code> <code>^ ^ ^ ^ ^</code> Default: "root"	
	database password
<code>--storage-driver-secure</code>	
	use secure connection with database
<code>--storage-driver-table string</code> <code>^ ^ ^ ^ ^</code> Default: "stats"	
	table name
<code>--storage-driver-user string</code> <code>^ ^ ^ ^ ^</code> Default: "root"	
	database username
<code>--token string</code>	
	Bearer token for authentication to the API server
<code>--update-machine-info-interval duration</code> <code>^ ^ ^ ^ ^</code> Default: 5m0s	

Interval between machine info updates.
--user string
The name of the kubeconfig user to use
--username string
Username for basic authentication to the API server
-v, --v Level
number for the log level verbosity
--version version[=true]
Print version information and quit
--vmodule moduleSpec
comma-separated list of pattern=N settings for file-filtered logging

## See Also

- [kubectl annotate](#) - Update the annotations on a resource
- [kubectl api-resources](#) - Print the supported API resources on the server
- [kubectl api-versions](#) - Print the supported API versions on the server, in the form of "group/version"
- [kubectl apply](#) - Apply a configuration to a resource by filename or stdin
- [kubectl attach](#) - Attach to a running container
- [kubectl auth](#) - Inspect authorization
- [kubectl autoscale](#) - Auto-scale a Deployment, ReplicaSet, or ReplicationController
- [kubectl certificate](#) - Modify certificate resources.
- [kubectl cluster-info](#) - Display cluster info
- [kubectl completion](#) - Output shell completion code for the specified shell (bash or zsh)
- [kubectl config](#) - Modify kubeconfig files
- [kubectl convert](#) - Convert config files between different API versions
- [kubectl cordon](#) - Mark node as unschedulable
- [kubectl cp](#) - Copy files and directories to and from containers.
- [kubectl create](#) - Create a resource from a file or from stdin.
- [kubectl delete](#) - Delete resources by filenames, stdin, resources and names, or by resources and label selector
- [kubectl describe](#) - Show details of a specific resource or group of resources
- [kubectl diff](#) - Diff live version against would-be applied version
- [kubectl drain](#) - Drain node in preparation for maintenance
- [kubectl edit](#) - Edit a resource on the server
- [kubectl exec](#) - Execute a command in a container
- [kubectl explain](#) - Documentation of resources
- [kubectl expose](#) - Take a replication controller, service, deployment or pod and expose it as a new Kubernetes Service
- [kubectl get](#) - Display one or many resources
- [kubectl kustomize](#) - Build a kustomization target from a directory or a remote url.
- [kubectl label](#) - Update the labels on a resource
- [kubectl logs](#) - Print the logs for a container in a pod
- [kubectl options](#) - Print the list of flags inherited by all commands



- [kubectl patch](#) - Update field(s) of a resource using strategic merge patch
- [kubectl plugin](#) - Provides utilities for interacting with plugins.
- [kubectl port-forward](#) - Forward one or more local ports to a pod
- [kubectl proxy](#) - Run a proxy to the Kubernetes API server
- [kubectl replace](#) - Replace a resource by filename or stdin
- [kubectl rollout](#) - Manage the rollout of a resource
- [kubectl run](#) - Run a particular image on the cluster
- [kubectl scale](#) - Set a new size for a Deployment, ReplicaSet or Replication Controller
- [kubectl set](#) - Set specific features on objects
- [kubectl taint](#) - Update the taints on one or more nodes
- [kubectl top](#) - Display Resource (CPU/Memory/Storage) usage.
- [kubectl uncordon](#) - Mark node as schedulable
- [kubectl version](#) - Print the client and server version information
- [kubectl wait](#) - Experimental: Wait for a specific condition on one or many resources.

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on January 03, 2020 at 12:39 PM PST by [regenerate ref docs, 1.17, script chgs \(#18067\)](#) ([Page History](#))

[Edit This Page](#)

# kubectl Cheat Sheet

See also: [Kubectl Overview](#) and [JsonPath Guide](#).

This page is an overview of the `kubectl` command.

- [Kubectl Autocomplete](#)
- [Kubectl Context and Configuration](#)
- [Apply](#)
- [Creating Objects](#)

- [Viewing, Finding Resources](#)
- [Updating Resources](#)
- [Patching Resources](#)
- [Editing Resources](#)
- [Scaling Resources](#)
- [Deleting Resources](#)
- [Interacting with running Pods](#)
- [Interacting with Nodes and Cluster](#)
- [What's next](#)

# kubectl - Cheat Sheet

## Kubectl Autocomplete

### BASH

```
source <(kubectl completion bash) # setup autocomplete in bash
into the current shell, bash-completion package should be
installed first.
echo "source <(kubectl completion bash)" >> ~/.bashrc # add
autocomplete permanently to your bash shell.
```

You can also use a shorthand alias for kubectl that also works with completion:

```
alias k=kubectl
complete -F __start_kubectl k
```

### ZSH

```
source <(kubectl completion zsh) # setup autocomplete in zsh
into the current shell
echo "if [ \$commands[kubectl] ]; then source <(kubectl
completion zsh); fi" >> ~/.zshrc # add autocomplete permanently
to your zsh shell
```

## Kubectl Context and Configuration

Set which Kubernetes cluster kubectl communicates with and modifies configuration information. See [Authenticating Across Clusters with kubeconfig](#) documentation for detailed config file information.

```
kubectl config view # Show Merged kubeconfig settings.

# use multiple kubeconfig files at the same time and view merged
config
KUBECONFIG=~/.kube/config:~/.kube/kubconfig2

kubectl config view
```

```

# get the password for the e2e user
kubectl config view -o jsonpath='{.users[?(@.name ==
"e2e")].user.password}'

kubectl config view -o jsonpath='{.users[].name}'      # display
the first user
kubectl config view -o jsonpath='{.users[*].name}'     # get a
list of users
kubectl config get-contexts                            # display
list of contexts
kubectl config current-context                        # display
the current-context
kubectl config use-context my-cluster-name            # set the
default context to my-cluster-name

# add a new cluster to your kubeconf that supports basic auth
kubectl config set-credentials kubeuser/foo.kubernetes.com --
username=kubeuser --password=kubepassword

# permanently save the namespace for all subsequent kubectl
commands in that context.
kubectl config set-context --current --namespace=ggckad-s2

# set a context utilizing a specific username and namespace.
kubectl config set-context gce --user=cluster-admin --namespace=f
oo \
    && kubectl config use-context gce

kubectl config unset users.foo                        # delete
user foo

```

## Apply

apply manages applications through files defining Kubernetes resources. It creates and updates resources in a cluster through running `kubectl apply`. This is the recommended way of managing Kubernetes applications on production. See [Kubectl Book](#).

## Creating Objects

Kubernetes manifests can be defined in YAML or JSON. The file extension `.yaml`, `.yml`, and `.json` can be used.

```

kubectl apply -f ./my-manifest.yaml                  # create
resource(s)
kubectl apply -f ./my1.yaml -f ./my2.yaml           # create from
multiple files
kubectl apply -f ./dir                              # create
resource(s) in all manifest files in dir

```

```

kubectl apply -f https://git.io/vPieo # create
resource(s) from url
kubectl create deployment nginx --image=nginx # start a single
instance of nginx
kubectl explain pods,svc # get the
documentation for pod and svc manifests

# Create multiple YAML objects from stdin
cat <<EOF | kubectl apply -f -
apiVersion: v1
kind: Pod
metadata:
  name: busybox-sleep
spec:
  containers:
  - name: busybox
    image: busybox
    args:
    - sleep
    - "1000000"
---
apiVersion: v1
kind: Pod
metadata:
  name: busybox-sleep-less
spec:
  containers:
  - name: busybox
    image: busybox
    args:
    - sleep
    - "1000"
EOF

# Create a secret with several keys
cat <<EOF | kubectl apply -f -
apiVersion: v1
kind: Secret
metadata:
  name: mysecret
type: Opaque
data:
  password: $(echo -n "s33msi4" | base64 -w0)
  username: $(echo -n "jane" | base64 -w0)
EOF

```

## Viewing, Finding Resources

```

# Get commands with basic output
kubectl get services # List all
services in the namespace

```

```

kubectl get pods --all-namespaces # List all pods in all namespaces
kubectl get pods -o wide # List all pods in the current namespace, with more details
kubectl get deployment my-dep # List a particular deployment
kubectl get pods # List all pods in the namespace
kubectl get pod my-pod -o yaml # Get a pod's YAML
kubectl get pod my-pod -o yaml --export # Get a pod's YAML without cluster specific information

# Describe commands with verbose output
kubectl describe nodes my-node
kubectl describe pods my-pod

# List Services Sorted by Name
kubectl get services --sort-by=.metadata.name

# List pods Sorted by Restart Count
kubectl get pods --sort-by='.status.containerStatuses[0].restartCount'

# List PersistentVolumes sorted by capacity
kubectl get pv --sort-by=.spec.capacity.storage

# Get the version label of all pods with label app=cassandra
kubectl get pods --selector=app=cassandra -o \
  jsonpath='{.items[*].metadata.labels.version}'

# Get all worker nodes (use a selector to exclude results that have a label named 'node-role.kubernetes.io/master')
kubectl get node --selector='!node-role.kubernetes.io/master'

# Get all running pods in the namespace
kubectl get pods --field-selector=status.phase=Running

# Get ExternalIPs of all nodes
kubectl get nodes -o jsonpath='{.items[*].status.addresses[?(@.type=="ExternalIP")].address}'

# List Names of Pods that belong to Particular RC
# "jq" command useful for transformations that are too complex for jsonpath, it can be found at https://stedolan.github.io/jq/
sel=${$(kubectl get rc my-rc --output=json | jq -j '.spec.selector | to_entries | .[] | "\(.key)=\(.value),"' )%?}
echo $(kubectl get pods --selector=$sel --output=jsonpath={.items..metadata.name})

# Show labels for all pods (or any other Kubernetes object that

```

*supports labelling)*

```
kubectl get pods --show-labels
```

*# Check which nodes are ready*

```
JSONPATH='{range .items[*]}{@.metadata.name}:{range  
@.status.conditions[*]}{@.type}={@.status};{end}{end}}' \  
&& kubectl get nodes -o jsonpath="$JSONPATH" | grep "Ready=True"
```

*# List all Secrets currently in use by a pod*

```
kubectl get pods -o json | jq '.items[].spec.containers[].env[]?.  
valueFrom.secretKeyRef.name' | grep -v null | sort | uniq
```

*# List Events sorted by timestamp*

```
kubectl get events --sort-by=.metadata.creationTimestamp
```

*# Compares the current state of the cluster against the state  
that the cluster would be in if the manifest was applied.*

```
kubectl diff -f ./my-manifest.yaml
```

## Updating Resources

As of version 1.11 rolling-update have been deprecated (see [CHANGELOG-1.11.md](#)), use rollout instead.

```
kubectl set image deployment/frontend www=image:v2
```

*# Rolling update "www" containers of "frontend" deployment,  
updating the image*

```
kubectl rollout history deployment/frontend
```

*# Check the history of deployments including the revision*

```
kubectl rollout undo deployment/frontend
```

*# Rollback to the previous deployment*

```
kubectl rollout undo deployment/frontend --to-revision=2
```

*# Rollback to a specific revision*

```
kubectl rollout status -w deployment/frontend
```

*# Watch rolling update status of "frontend" deployment until  
completion*

```
kubectl rollout restart deployment/frontend
```

*# Rolling restart of the "frontend" deployment*

*# deprecated starting version 1.11*

```
kubectl rolling-update frontend-v1 -f frontend-v2.json
```

*# (deprecated) Rolling update pods of frontend-v1*

```
kubectl rolling-update frontend-v1 frontend-v2 --image=image:v2
```

*# (deprecated) Change the name of the resource and update the  
image*

```
kubectl rolling-update frontend --image=image:v2
```

*# (deprecated) Update the pods image of frontend*

```
kubectl rolling-update frontend-v1 frontend-v2 --rollback
```

*# (deprecated) Abort existing rollout in progress*

```

cat pod.json | kubectl replace -f -
# Replace a pod based on the JSON passed into std

# Force replace, delete and then re-create the resource. Will
# cause a service outage.
kubectl replace --force -f ./pod.json

# Create a service for a replicated nginx, which serves on port
# 80 and connects to the containers on port 8000
kubectl expose rc nginx --port=80 --target-port=8000

# Update a single-container pod's image version (tag) to v4
kubectl get pod mypod -o yaml | sed 's/\(image: myimage\):.*$/\1:v4/' | kubectl replace -f -

kubectl label pods my-pod new-label=awesome
# Add a Label
kubectl annotate pods my-pod icon-url=http://goo.gl/XXBTWq
# Add an annotation
kubectl autoscale deployment foo --min=2 --max=10
# Auto scale a deployment "foo"

```

## Patching Resources

```

# Partially update a node
kubectl patch node k8s-node-1 -p '{"spec": {"unschedulable": true}}'

# Update a container's image; spec.containers[*].name is
# required because it's a merge key
kubectl patch pod valid-pod -p '{"spec":{"containers":[{"name":"kubernetes-serve-hostname","image":"new image"}]}}'

# Update a container's image using a json patch with positional
# arrays
kubectl patch pod valid-pod --type='json' -p='[{"op": "replace", "path": "/spec/containers/0/image", "value":"new image"}]'

# Disable a deployment livenessProbe using a json patch with
# positional arrays
kubectl patch deployment valid-deployment --type json -p='[{"op": "remove", "path": "/spec/template/spec/containers/0/livenessProbe"}]'

# Add a new element to a positional array
kubectl patch sa default --type='json' -p='[{"op": "add", "path": "/secrets/1", "value": {"name": "whatever" } }]'

```



## Editing Resources

Edit any API resource in your preferred editor.

```
kubectl edit svc/docker-registry # Edit the  
service named docker-registry  
KUBE_EDITOR="nano" kubectl edit svc/docker-registry # Use an  
alternative editor
```

## Scaling Resources

```
kubectl scale --replicas=3 rs/  
foo # Scale a replicaset named  
'foo' to 3  
kubectl scale --replicas=3 -f  
foo.yaml # Scale a resource specified  
in "foo.yaml" to 3  
kubectl scale --current-replicas=2 --replicas=3 deployment/  
mysql # If the deployment named mysql's current size is 2,  
scale mysql to 3  
kubectl scale --replicas=5 rc/foo rc/bar rc/  
baz # Scale multiple replication controllers
```

## Deleting Resources

```
kubectl delete -f ./  
pod.json # Delete a  
pod using the type and name specified in pod.json  
kubectl delete pod,service baz  
foo # Delete pods and  
services with same names "baz" and "foo"  
kubectl delete pods,services -l name=myLabel  
# Delete pods and services with label name=myLabel  
kubectl -n my-ns delete pod,svc --  
all # Delete all pods and  
services in namespace my-ns,  
# Delete all pods matching the awk pattern1 or pattern2  
kubectl get pods -n mynamespace --no-headers=true | awk '/  
pattern1|pattern2/{print $1}' | xargs kubectl delete -n  
mynamespace pod
```

## Interacting with running Pods

```
kubectl logs my-pod # dump pod  
logs (stdout)  
kubectl logs -l name=myLabel # dump pod  
logs, with label name=myLabel (stdout)  
kubectl logs my-pod --previous # dump pod  
logs (stdout) for a previous instantiation of a container
```

```

kubectl logs my-pod -c my-container # dump pod
container logs (stdout, multi-container case)
kubectl logs -l name=myLabel -c my-container # dump pod
logs, with label name=myLabel (stdout)
kubectl logs my-pod -c my-container --previous # dump pod
container logs (stdout, multi-container case) for a previous
instantiation of a container
kubectl logs -f my-pod # stream pod
logs (stdout)
kubectl logs -f my-pod -c my-container # stream pod
container logs (stdout, multi-container case)
kubectl logs -f -l name=myLabel --all-containers # stream all
pods logs with label name=myLabel (stdout)
kubectl run -i --tty busybox --image=busybox -- sh # Run pod as
interactive shell
kubectl run nginx --image=nginx --restart=Never -n
mynamespace # Run pod
nginx in a specific namespace
kubectl run nginx --image=nginx --restart=Never # Run pod
nginx and write its spec into a file called pod.yaml
--dry-run -o yaml > pod.yaml

kubectl attach my-pod -i # Attach to
Running Container
kubectl port-forward my-pod 5000:6000 # Listen on
port 5000 on the local machine and forward to port 6000 on my-pod
kubectl exec my-pod -- ls / # Run
command in existing pod (1 container case)
kubectl exec my-pod -c my-container -- ls / # Run
command in existing pod (multi-container case)
kubectl top pod POD_NAME --containers # Show
metrics for a given pod and its containers

```

## Interacting with Nodes and Cluster

```

kubectl cordon my- # Mark my-
node # Mark my-
node as unschedulable
kubectl drain my- # Drain my-
node # Drain my-
node in preparation for maintenance
kubectl uncordon my- # Mark my-node
node # Mark my-node
as schedulable
kubectl top node my- # Show metrics
node # Show metrics
for a given node
kubectl cluster- # Display
info # Display
addresses of the master and services

```

```
kubectl cluster-info
dump                                     # Dump current
cluster state to stdout
kubectl cluster-info dump --output-directory=/path/to/cluster-
state # Dump current cluster state to /path/to/cluster-state

# If a taint with that key and effect already exists, its value
is replaced as specified.
kubectl taint nodes foo dedicated=special-user:NoSchedule
```

## Resource types

List all supported resource types along with their shortnames, [API group](#), whether they are [namespaced](#), and [Kind](#):

```
kubectl api-resources
```

Other operations for exploring API resources:

```
kubectl api-resources --namespaced=true # All namespaced
resources
kubectl api-resources --namespaced=false # All non-
namespaced resources
kubectl api-resources -o name # All resources
with simple output (just the resource name)
kubectl api-resources -o wide # All resources
with expanded (aka "wide") output
kubectl api-resources --verbs=list,get # All resources
that support the "list" and "get" request verbs
kubectl api-resources --api-group=extensions # All resources in
the "extensions" API group
```

## Formatting output

To output details to your terminal window in a specific format, add the `-o` (or `--output`) flag to a supported `kubectl` command.

Output format	Description
<code>-o=custom-columns=&lt;spec&gt;</code>	Print a table using a comma separated list of custom columns
<code>-o=custom-columns-file=&lt;filename&gt;</code>	Print a table using the custom columns template in the <code>&lt;filename&gt;</code> file
<code>-o=json</code>	Output a JSON formatted API object
<code>-o=jsonpath=&lt;template&gt;</code>	Print the fields defined in a <a href="#">jsonpath</a> expression
<code>-o=jsonpath-file=&lt;filename&gt;</code>	Print the fields defined by the <a href="#">jsonpath</a> expression in the <code>&lt;filename&gt;</code> file
<code>-o=name</code>	Print only the resource name and nothing else

Output format	Description
-o=wide	Output in the plain-text format with any additional information, and for pods, the node name is included
-o=yaml	Output a YAML formatted API object

## Kubectl output verbosity and debugging

Kubectl verbosity is controlled with the `-v` or `--v` flags followed by an integer representing the log level. General Kubernetes logging conventions and the associated log levels are described [here](#).

Verbosity	Description
- -v=0	Generally useful for this to <i>always</i> be visible to a cluster operator.
- -v=1	A reasonable default log level if you don't want verbosity.
- -v=2	Useful steady state information about the service and important log messages that may correlate to significant changes in the system. This is the recommended default log level for most systems.
- -v=3	Extended information about changes.
- -v=4	Debug level verbosity.
- -v=6	Display requested resources.
- -v=7	Display HTTP request headers.
- -v=8	Display HTTP request contents.
- -v=9	Display HTTP request contents without truncation of contents.

## What's next

- Learn more about [Overview of kubectl](#).
- See [kubectl](#) options.
- Also [kubectl Usage Conventions](#) to understand how to use it in reusable scripts.
- See more community [kubectl cheatsheets](#).

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on February 09, 2020 at 2:53 PM PST by [Updated CHANGELOG-11 link \(#19036\)](#) ([Page History](#))

[Edit This Page](#)

# kubectl Commands

[kubectl Command Reference](#)

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on May 11, 2018 at 10:14 AM PST by [Put kubectl commands in left nav. \(#8502\)](#) ([Page History](#))

[Edit This Page](#)

## kubectl for Docker Users

You can use the Kubernetes command line tool `kubectl` to interact with the API Server. Using `kubectl` is straightforward if you are familiar with the Docker command line tool. However, there are a few differences between

the docker commands and the kubectl commands. The following sections show a docker sub-command and describe the equivalent kubectl command.

- [docker run](#)
- [docker ps](#)
- [docker attach](#)
- [docker exec](#)
- [docker logs](#)
- [docker stop and docker rm](#)
- [docker login](#)
- [docker version](#)
- [docker info](#)

## docker run

To run an nginx Deployment and expose the Deployment, see [kubectl run](#).

docker:

```
docker run -d --restart=always -e DOMAIN=cluster --name nginx-app -p 80:80 nginx
```

```
55c103fa129692154a7652490236fee9be47d70a8dd562281ae7d2f9a339a6db
```

docker ps

CONTAINER ID	IMAGE	COMMAND
CREATED	STATUS	PORTS
NAMES		
55c103fa1296	nginx	"nginx -g 'daemon
ofâ€¦" 9 seconds ago	Up 9 seconds	0.0.0.0:80->80/
tcp nginx-app		

kubectl:

```
# start the pod running nginx
```

```
kubectl run --image=nginx nginx-app --port=80 --env="DOMAIN=cluster"
```

```
deployment "nginx-app" created
```

**Note:** kubectl commands print the type and name of the resource created or mutated, which can then be used in subsequent commands. You can expose a new Service after a Deployment is created.

```
# expose a port through with a service
```

```
kubectl expose deployment nginx-app --port=80 --name=nginx-http
```

```
service "nginx-http" exposed
```

By using kubectl, you can create a [Deployment](#) to ensure that N pods are running nginx, where N is the number of replicas stated in the spec and

defaults to 1. You can also create a [service](#) with a selector that matches the pod labels. For more information, see [Use a Service to Access an Application in a Cluster](#).

By default images run in the background, similar to `docker run -d ....` To run things in the foreground, use:

```
kubectl run [-i] [--tty] --attach <name> --image=<image>
```

Unlike `docker run ...`, if you specify `--attach`, then you attach `stdin`, `stdout` and `stderr`. You cannot control which streams are attached (`docker -a ...`). To detach from the container, you can type the escape sequence `Ctrl+P` followed by `Ctrl+Q`.

Because the `kubectl run` command starts a Deployment for the container, the Deployment restarts if you terminate the attached process by using `Ctrl+C`, unlike `docker run -it`. To destroy the Deployment and its pods you need to run `kubectl delete deployment <name>`.

## docker ps

To list what is currently running, see [kubectl get](#).

docker:

```
docker ps -a
```

CONTAINER ID	IMAGE	COMMAND
14636241935f	ubuntu:16.04	"echo test"
5 seconds ago	Exited (0) 5 seconds ago	
55c103fa1296	nginx	"nginx -g 'daemon off€'"
About a minute ago	Up About a minute	
0.0.0.0:80->80/tcp	nginx-app	

kubectl:

```
kubectl get po
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-app-8df569cb7-4gd89	1/1	Running	0	3m
ubuntu	0/1	Completed	0	20s

## docker attach

To attach a process that is already running in a container, see [kubectl attach](#).

docker:



```
docker ps
```

CONTAINER ID	IMAGE	COMMAND
CREATED	STATUS	PORTS
NAMES		
55c103fa1296	nginx	"nginx -g 'daemon
ofâ€¦" 5 minutes ago	Up 5 minutes	0.0.0.0:80->80/
tcp nginx-app		

```
docker attach 55c103fa1296
```

```
...
```

```
kubectrl:
```

```
kubectrl get pods
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-app-5jyvm	1/1	Running	0	10m

```
kubectrl attach -it nginx-app-5jyvm
```

```
...
```

To detach from the container, you can type the escape sequence Ctrl+P followed by Ctrl+Q.

## docker exec

To execute a command in a container, see [kubectrl exec](#).

```
docker:
```

```
docker ps
```

CONTAINER ID	IMAGE	COMMAND
CREATED	STATUS	PORTS
NAMES		
55c103fa1296	nginx	"nginx -g 'daemon
ofâ€¦" 6 minutes ago	Up 6 minutes	0.0.0.0:80->80/
tcp nginx-app		

```
docker exec 55c103fa1296 cat /etc/hostname
```

```
55c103fa1296
```

```
kubectrl:
```

```
kubectrl get po
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-app-5jyvm	1/1	Running	0	10m

```
kubectrl exec nginx-app-5jyvm -- cat /etc/hostname
```

```
nginx-app-5jyvm
```

To use interactive commands.

docker:

```
docker exec -ti 55c103fa1296 /bin/sh
# exit
```

kubectl:

```
kubectl exec -ti nginx-app-5jyvm -- /bin/sh
# exit
```

For more information, see [Get a Shell to a Running Container](#).

## docker logs

To follow stdout/stderr of a process that is running, see [kubectl logs](#).

docker:

```
docker logs -f a9e
```

```
192.168.9.1 - - [14/Jul/2015:01:04:02 +0000] "GET / HTTP/1.1"
200 612 "-" "curl/7.35.0" "-"
192.168.9.1 - - [14/Jul/2015:01:04:03 +0000] "GET / HTTP/1.1"
200 612 "-" "curl/7.35.0" "-"
```

kubectl:

```
kubectl logs -f nginx-app-zibvs
```

```
10.240.63.110 - - [14/Jul/2015:01:09:01 +0000] "GET / HTTP/1.1"
200 612 "-" "curl/7.26.0" "-"
10.240.63.110 - - [14/Jul/2015:01:09:02 +0000] "GET / HTTP/1.1"
200 612 "-" "curl/7.26.0" "-"
```

There is a slight difference between pods and containers; by default pods do not terminate if their processes exit. Instead the pods restart the process. This is similar to the docker run option `--restart=always` with one major difference. In docker, the output for each invocation of the process is concatenated, but for Kubernetes, each invocation is separate. To see the output from a previous run in Kubernetes, do this:

```
kubectl logs --previous nginx-app-zibvs
```

```
10.240.63.110 - - [14/Jul/2015:01:09:01 +0000] "GET / HTTP/1.1"
200 612 "-" "curl/7.26.0" "-"
10.240.63.110 - - [14/Jul/2015:01:09:02 +0000] "GET / HTTP/1.1"
200 612 "-" "curl/7.26.0" "-"
```

For more information, see [Logging Architecture](#).

## docker stop and docker rm

To stop and delete a running process, see [kubectl delete](#).

docker:

```
docker ps
```

CONTAINER ID	IMAGE	COMMAND
CREATED	STATUS	
PORTS	NAMES	
a9ec34d98787	nginx	"nginx -g 'daemon of"
22 hours ago	Up 22 hours	0.0.0.0:80->80/tcp, 443/
tcp	nginx-app	

```
docker stop a9ec34d98787
```

```
a9ec34d98787
```

```
docker rm a9ec34d98787
```

```
a9ec34d98787
```

kubectl:

```
kubectl get deployment nginx-app
```

NAME	READY	UP-TO-DATE	AVAILABLE	AGE
nginx-app	1/1	1	1	2m

```
kubectl get po -l run=nginx-app
```

NAME	READY	STATUS	RESTARTS	AGE
nginx-app-2883164633-aklf7	1/1	Running	0	2m

```
kubectl delete deployment nginx-app
```

```
deployment "nginx-app" deleted
```

```
kubectl get po -l run=nginx-app
```

```
# Return nothing
```

**Note:** When you use kubectl, you don't delete the pod directly. You have to first delete the Deployment that owns the pod. If you delete the pod directly, the Deployment recreates the pod.

## docker login

There is no direct analog of `docker login` in kubectl. If you are interested in using Kubernetes with a private registry, see [Using a Private Registry](#).

## docker version

To get the version of client and server, see [kubectl version](#).

docker:

```
docker version
```

```
Client version: 1.7.0
Client API version: 1.19
Go version (client): go1.4.2
Git commit (client): 0baf609
OS/Arch (client): linux/amd64
Server version: 1.7.0
Server API version: 1.19
Go version (server): go1.4.2
Git commit (server): 0baf609
OS/Arch (server): linux/amd64
```

kubectl:

```
kubectl version
```

```
Client Version: version.Info{Major:"1", Minor:"6",
GitVersion:"v1.6.9+a3d1dfa6f4335",
GitCommit:"9b77fed11a9843ce3780f70dd251e92901c43072",
GitTreeState:"dirty", BuildDate:"2017-08-29T20:32:58Z",
OpenPaasKubernetesVersion:"v1.03.02", GoVersion:"go1.7.5",
Compiler:"gc", Platform:"linux/amd64"}
Server Version: version.Info{Major:"1", Minor:"6",
GitVersion:"v1.6.9+a3d1dfa6f4335",
GitCommit:"9b77fed11a9843ce3780f70dd251e92901c43072",
GitTreeState:"dirty", BuildDate:"2017-08-29T20:32:58Z",
OpenPaasKubernetesVersion:"v1.03.02", GoVersion:"go1.7.5",
Compiler:"gc", Platform:"linux/amd64"}
```

## docker info

To get miscellaneous information about the environment and configuration, see [kubectl cluster-info](#).

docker:

```
docker info
```

```
Containers: 40
Images: 168
Storage Driver: aufs
  Root Dir: /usr/local/google/docker/aufs
  Backing Filesystem: extfs
  Dirs: 248
  Dirperm1 Supported: false
```

```
Execution Driver: native-0.2
Logging Driver: json-file
Kernel Version: 3.13.0-53-generic
Operating System: Ubuntu 14.04.2 LTS
CPUs: 12
Total Memory: 31.32 GiB
Name: k8s-is-fun.mtv.corp.google.com
ID: ADUV:GCYR:B3VJ:HMP0:LNPQ:KD5S:YKFQ:76VN:IANZ:7TFV:ZBF4:BYJO
WARNING: No swap limit support
```

kubectl:

```
kubectl cluster-info
```

```
Kubernetes master is running at https://203.0.113.141
KubeDNS is running at https://203.0.113.141/api/v1/namespaces/
kube-system/services/kube-dns/proxy
kubernetes-dashboard is running at https://203.0.113.141/api/v1/
namespaces/kube-system/services/kubernetes-dashboard/proxy
Grafana is running at https://203.0.113.141/api/v1/namespaces/
kube-system/services/monitoring-grafana/proxy
Heapster is running at https://203.0.113.141/api/v1/namespaces/
kube-system/services/monitoring-heapster/proxy
InfluxDB is running at https://203.0.113.141/api/v1/namespaces/
kube-system/services/monitoring-influxdb/proxy
```

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on February 19, 2020 at 8:38 PM PST by [Add missing space in documentation line \(#19013\)](#) ([Page History](#))

[Edit This Page](#)

# kubectl Usage Conventions

Recommended usage conventions for `kubectl`.

- [Using kubectl in Reusable Scripts](#)
- [Best Practices](#)

# Using `kubectl` in Reusable Scripts

For a stable output in a script:

- Request one of the machine-oriented output forms, such as `-o name`, `-o json`, `-o yaml`, `-o go-template`, or `-o jsonpath`.
- Fully-qualify the version. For example, `jobs.v1.batch/myjob`. This will ensure that `kubectl` does not use its default version that can change over time.
- Specify the `--generator` flag to pin to a specific behavior when you use generator-based commands such as `kubectl run` or `kubectl expose`.
- Don't rely on context, preferences, or other implicit states.

## Best Practices

### `kubectl run`

For `kubectl run` to satisfy infrastructure as code:

- Tag the image with a version-specific tag and don't move that tag to a new version. For example, use `:v1234`, `v1.2.3`, `r03062016-1-4`, rather than `:latest` (For more information, see [Best Practices for Configuration](#)).
- Capture the parameters in a checked-in script, or at least use `--record` to annotate the created objects with the command line for an image that is lightly parameterized.
- Pin to a specific [generator](#) version, such as `kubectl run --generator=run-pod/v1`.
- Check in the script for an image that is heavily parameterized.
- Switch to configuration files checked into source control for features that are needed, but not expressible via `kubectl run` flags.

## Generators

You can create the following resources using `kubectl run` with the `--generator` flag:

Resource	API group	<code>kubectl</code> command
Pod	v1	<code>kubectl run --generator=run-pod/v1</code>
ReplicationController ( <i>deprecated</i> )	v1	<code>kubectl run --generator=run/v1</code>
Deployment ( <i>deprecated</i> )	extensions/ v1beta1	<code>kubectl run --generator=deployment/ v1beta1</code>
Deployment ( <i>deprecated</i> )	apps/ v1beta1	<code>kubectl run --generator=deployment/ apps.v1beta1</code>

Resource	API group	kubectl command
Job <i>(deprecated)</i>	batch/v1	<code>kubectl run --generator=job/v1</code>
CronJob <i>(deprecated)</i>	batch/v2alpha1	<code>kubectl run --generator=cronjob/v2alpha1</code>
CronJob <i>(deprecated)</i>	batch/v1beta1	<code>kubectl run --generator=cronjob/v1beta1</code>

**Note:** Generators other than `run-pod/v1` are deprecated.

If you explicitly set `--generator`, kubectl uses the generator you specified. If you invoke `kubectl run` and don't specify a generator, kubectl automatically selects which generator to use based on the other flags you set. The following table lists flags and the generators that are activated if you didn't specify one yourself:

Flag	Generated Resource
<code>--schedule=&lt;schedule&gt;</code>	CronJob
<code>--restart=Always</code>	Deployment
<code>--restart=OnFailure</code>	Job
<code>--restart=Never</code>	Pod

If you don't specify a generator, kubectl pays attention to other flags in the following order:

1. `--schedule`
2. `--restart`

You can use the `--dry-run` flag to preview the object that would be sent to your cluster, without really submitting it.

## kubectl apply

- You can use `kubectl apply` to create or update resources. For more information about using `kubectl apply` to update resources, see [Kubectl Book](#).

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---



[Create an Issue](#) [Edit This Page](#)

Page last modified on December 10, 2019 at 5:41 AM PST by [Official 1.17 Release Docs \(#18011\)](#) ([Page History](#))

[Edit This Page](#)

# Tools

Kubernetes contains several built-in tools to help you work with the Kubernetes system.

- [Kubectl](#)
- [Kubeadm](#)
- [Kubefed](#)
- [Minikube](#)
- [Dashboard](#)

- [Helm](#)
- [Kompose](#)

## Kubectl

[kubectl](#) is the command line tool for Kubernetes. It controls the Kubernetes cluster manager.

## Kubeadm

[kubeadm](#) is the command line tool for easily provisioning a secure Kubernetes cluster on top of physical or cloud servers or virtual machines (currently in alpha).

## Kubefed

[kubefed](#) is the command line tool to help you administrate your federated clusters.

## Minikube

[minikube](#) is a tool that makes it easy to run a single-node Kubernetes cluster locally on your workstation for development and testing purposes.

## Dashboard

[Dashboard](#), the web-based user interface of Kubernetes, allows you to deploy containerized applications to a Kubernetes cluster, troubleshoot them, and manage the cluster and its resources itself.

## Helm

[Kubernetes Helm](#) is a tool for managing packages of pre-configured Kubernetes resources, aka Kubernetes charts.

Use Helm to:

- Find and use popular software packaged as Kubernetes charts
- Share your own applications as Kubernetes charts
- Create reproducible builds of your Kubernetes applications
- Intelligently manage your Kubernetes manifest files
- Manage releases of Helm packages

## Kompose

[Kompose](#) is a tool to help Docker Compose users move to Kubernetes.

Use Kompose to:

- Translate a Docker Compose file into Kubernetes objects
- Go from local Docker development to managing your application via Kubernetes
- Convert v1 or v2 Docker Compose yaml files or [Distributed Application Bundles](#)

## Feedback

Was this page helpful?

Yes No

Thanks for the feedback. If you have a specific, answerable question about how to use Kubernetes, ask it on [Stack Overflow](#). Open an issue in the GitHub repo if you want to [report a problem](#) or [suggest an improvement](#).

---

[Create an Issue](#) [Edit This Page](#)

Page last modified on June 12, 2019 at 5:27 PM PST by [Restructure the left navigation pane of setup \(#14826\)](#) ([Page History](#))