

Description	Parameters			
	TSK2116 / TSK2216	TSK2120 / TSK2220	TSK2136 / TSK2236	TSK2150 / TSK2250
Boring Diameter Range (mm)	Ø30mm - Ø80mm			40mm - Ø120mm
Boring diameter range (mm)		100mm - Ø200mm	40mm - Ø360mm	120mm - Ø500mm
Working/Boring Range (mm)	1000 - 6000mm	1000 - 1200mm		1000 - 15000mm
Workpiece OD range (mm)	50mm - Ø200mm	60mm - Ø300mm	100mm - Ø450mm	100mm - Ø6500mm
Center height (mm)	400mm	500mm	500mm	625mm
Spindle bore hole (mm)	Ø75mm			Ø130mm
Spindle front taper hole (mm)	Ø85 1:20			
Speed range (r/min)	61 - 1250	61 - 1000	40 - 500	3.15 - 315
Speed range stepless (mm/min)	50 - 1000			5 - 500
Rapid speed stepless (mm/min)	1500			1500
Main motor power (KW)	15	30	30	45
Hydraulic system motor power (Kw)	1.5	1.5	1.5	15
Pressure motor (Kw)	4.3	4.3	4.3	5.5
Infeed motor (Kw)	4.3	4.3	4.3	5.5
Plant pump motor (Kw)	5.5*3	5.5*4	5.5*4	7.5*3

Max. pressure (Mpa)	2.5	2.5	2.5	2.5
Max. flow (L/min)	300	400	600	900